

CIT SOLE CO.,LTD

Houayhong Village, Chanthabouli District, Vientiane Capital.

Mobile: 02058189995, 58189996, 55556905

Web: www.citgroup.la or www.citsole.comEmail: citgroupplao@gmail.com or dahualaos@gmail.com**QOUTATION**

CIT0032

17/03/2021




To: **Sokxay GROUP**






Tel:


Address:



Currency:

USD

No	Name/Images	Specification	Wty	Qty	Price	Amount	Remark
		Speed Dome		104			
1	SD49225T-HN 	2MP 25x Starlight IR PTZ Network Camera > 1/2.8" 2Megapixel STARVIS™ CMOS > Powerful 25x optical zoom > Starlight technology > 1080P/720P/D1(1 ~ 25/30fps) > IVS, Support PoE+, IR distance up to 100m, IP66	2Y	2	400	800	Full HD Starlighth
2	DH-SD6C3220-HN-UE 	Powerful 20x/30x optical zoom Starlight Technology • H.264 & MJPEG dual-stream encoding • Max. 15fps@3Mp, 25/30fps@1080p resolution(320) • Max 25/30fps@1080p, 50/60fps@720P(220/230) • Defog(220/230), EIS(220/230), WDR, Day/Night(ICR), DNR(2D&3D), Auto iris, Auto focus, AWB, AGC,BLC • Multiple network monitoring: Web viewer, CMS(DSS/PSS) & DMSS • Max 240°/s pan speed, 360° endless pan rotation • Up to 255 presets, 5 auto scan, 8 tour, 5 pattern • Built-in 7/2 alarm in/out • Support intelligent 3D positioning with DH-SD protocol • Micro SD memory, IP66 • IR Distance up to 150m	2Y	4	450	1.800	Full HD Starlighth
		Thermal Fire Detection, Perimeter Protection and Office			-		
3	TPC-BF1241 	AI WizSense Thermal Network Bullet Camera > Uncooled VOx thermal sensor technology > Athermalized lens (thermal camera), focus-free > 1/2.7" 4Megapixel progressive scan CMOS > Wi-Fi Optional > Support ROI, motion detection, color palettes > Smoking and call behaviour detection > Support fire detection & alarm > Built-in 1/1 alarm in/out > Micro SD memory, IP67, PoE > Smart linkage with strobe light & audio > Dual image fusion (visible and thermal images) > General Intelligence: Tripwire, Intrusion, Fire Detection & Alarm, Cold & Hot Spot Trace. > Advanced Intelligence: Human & Vehicle Classification, Smoking Detection, Call Detection	2 Y	12	650	7.800	ກ້ອງ AI ຈັບຄວາມຮ້ອນ, ຈັບອຸນຫະພູມ, ຈັບແປວໄຟ, ຈັບຄົນ ແລະ ຈັບລົດ
4	TPC-DF1241 	AI WizSense Thermal Network Bullet Camera > Uncooled VOx thermal sensor technology > Athermalized lens (thermal camera), focus-free > 1/2.7" 4Megapixel progressive scan CMOS > Wi-Fi Optional > Support ROI, motion detection, color palettes > Smoking and call behaviour detection > Support fire detection & alarm > Built-in 1/1 alarm in/out > Micro SD memory, IP67, PoE > Smart linkage with strobe light & audio > Dual image fusion (visible and thermal images) > General Intelligence: Tripwire, Intrusion, Fire Detection & Alarm, Cold & Hot Spot Trace. > Advanced Intelligence: Human & Vehicle Classification, Smoking Detection, Call Detection	2 Y	12	650	7.800	ກ້ອງ AI ຈັບຄວາມຮ້ອນ, ຈັບອຸນຫະພູມ, ຈັບແປວໄຟ, ຈັບຄົນ ແລະ ຈັບລົດ

No	Name/Images	Specification	Wty	Qty	Price	Amount	Remark
5	IPC-HFW3441T-ZS  	4MP IR Vari-focal Bullet WizSense Network Camera > 4MP, 1/3" CMOS image sensor, low illuminance, high image definition > Outputs max. 4MP (2688 × 1520) @30 fps > H.265 codec, high compression rate, low bit rate > Built-in IR LED, max. IR distance: 60 m > ROI, SMART H.264+/H.265+, flexible coding, applicable to various bandwidth and storage environments > Rotation mode, WDR, 3D DNR, HLC, BLC, digital watermarking, applicable to various monitoring scenes > Intelligent detection: Intrusion, tripwire (support the classification and accurate detection of vehicle and human) > Abnormality detection: Motion detection, video tampering, scene changing, no SD card, SD card full, SD card error, network disconnection, IP conflict, illegal access, voltage detection > Supports max. 256 G Micro SD card > 12V DC/POE power supply > IP67, IK10(optional) protection > SMD Plus	2 Y	14	150	2.100	ກ້ອງ AI ສຳລັບຈັບ ການບຸກລຸກ ຝ່າງກຳແພງ
6	DH-IPC-HDW2439T-AS-LED-S2 	4MP Lite Full-color Fixed-focal Eyeball Network Camera > 4MP, 1/3" CMOS image sensor, low illuminance, high image definition > Outputs 4MP (2560 × 1440) @ 25/30 fps, Max. supports 4MP > H.265 codec, high compression rate, ultra-low bit rate > Built-in warm lights, max. illumination distance: 30 m > ROI, SMART H.264+/H.265+, flexible coding, applicable to various > Rotation mode, WDR, 3D NR, HLC, BLC, digital watermarking, > Intelligent detection: Intrusion, tripwire > Abnormality detection: Motion detection, video tampering, scene > Supports max. 256 GB Micro SD card and built-in Mic > 12V DC/PoE power supply > IP67 protection	2 Y	22	50	1.100	ບັນທຶກສຽງ ກາງຄືນເປັນ ພາບສີ
7	IPC-HFW2439S-SA-LED-S2 	4MP Lite Full-color Fixed-focal Bullet Network Camera > 4MP, 1/3" CMOS image sensor, low illuminance, high image definition > Outputs 4MP (2560 × 1440) @ 25/30 fps, Max. supports 4MP > H.265 codec, high compression rate, ultra-low bit rate > Built-in warm lights, max. illumination distance: 30 m > ROI, SMART H.264+/H.265+, flexible coding, applicable to various > Rotation mode, WDR, 3D NR, HLC, BLC, digital watermarking, > Intelligent detection: Intrusion, tripwire > Abnormality detection: Motion detection, video tampering, scene > Supports max. 256 GB Micro SD card and built-in Mic > 12V DC/PoE power supply > IP67 protection	2 Y	38	50	1.900	ບັນທຶກສຽງ ກາງຄືນເປັນ ພາບສີ
Access Control					-		
8	ASI1212D 	Water-proof Fingerprint Standalone > Touch keyboard and LCD display > Support 30,000 valid cards & 150,000 records > Support multiple cards(default IC card) ("-D" means ID EM card) > Support card, password, fingerprint and combination > TCP/IP to PC, support WAN communication > Support P2P add device > Wiegand or RS-485 interface to reader > Door time out alarm, intrusion alarm, duress alarm and tamper alarm > Anti-passback, multi-card open > Software attendance > Support 128 efficient time and holiday schedules	1Y	3	210	630	

No	Name/Images	Specification	Wty	Qty	Price	Amount	Remark
9	IC-S50 	>Mifare card, 13.56MHz; >8K bit EEPROM memory; >86*54*1mm;	1Y	100	1	100	
10	DHI-ASF280A 	> Power on-NC; > Single Door; > Relay Input&output; > Anti-pull 280kg; > Working Temperature: -30°C~60°C; > DC12V/24V; > 250*47*26mm;	1Y	3	62	186	
11	ASF900 	>ABS plastic; >86*86*25mm; >-30°C~60°C;	1Y	3	3	9	
AI NVR					-		
12	IVSS7016-4I 	3U 16HDD WizMind Intelligent Video Surveillance Server > Industry embedded micro-controller > Max 512Mbps incoming bandwidth > 256-channel IP video access > Up to 64-channel perimeter protection > Up to 32-channel face recognition with normal IPC > Up to 80-channel face recognition with face detection IPC > Up to 16-channel video metadata > Up to 50 face databases with 300,000 face pictures in total > Supports RAID 0/1/5/6/10 > 3 HDMI/1 VGA video output	1 Y	1	17.485	17.485	ຫົວບັນທຶກ AI ຮອງຮັບ 256 ກ້ອງ IP, ບັນທຶກ ໄດ້ຫຼາຍກວ່າ > 90 days
13	ST14000NM001G	14TB/7200RPM/256M/ SATA 6Gb/s	1 Y	16	850	13.600	
14	ARA16 	Outdoor Siren	1 Y	25	10	250	
Transmission					-		
15	PFS3005-4P-58 	4-Port PoE Switch (Unmanaged) > Two-layer PoE Ethernet switch > MAC auto study and aging, MAC address list capacity is 1K > Conform IEEE802.3, IEEE802.3u and IEEE802.3X standards > Default Mode: The device works as a general switch and all ports support 10/100Mbps auto-negotiation. > Extend Mode: VLAN isolation is enabled. Ports 1-4 will be isolated respectively (10Mbps auto-negotiation), but they can communicate with the Uplink port. Besides, the transmission distance of power and network data is up to 250m.	1 Y	12	40	480	
16	PFS3010-8ET-96 	8-Port PoE Switch (Unmanaged) > Layer two commercial switch > Supports PoE power management > Supports wall-mount installation > Supports anti-theft lock hole > MAC auto learning and aging, MAC address capacity is 16K > Supports IEEE802.3, IEEE802.3u and IEEE802.3X standards > RJ45 port supports 10/100 Mbps self-adaptation > Supports 250 meters long distance PoE transmission > Conforms to IEEE802.3af and IEEE802.3at power supply standard. Port 1 supports Hi-PoE 60W power supply	1 Y	8	90	720	

No	Name/Images	Specification	Wty	Qty	Price	Amount	Remark
17	PFS4226-24ET-240 	24-Port PoE Switch 27 Port LAN > Layer 2 management PoE switch > PoE budget: 240W > Support PoE, PoE+, Hi-PoE > 'Orange port' support Hi-PoE, can be used with the PoE extender (PFT1300) > 250 meters long distance PoE transmission > PoE management, PoE Setting/Event Statistics/Green PoE > Search and upgrade via ConfigTool > Support Web management > High lightning protection design > Non-blocking video transmission	1 Y	8	400	3.200	
18	PFS5428-24GT 	L2+ Managed Switch > Hardened L2+ managed aggregation Switch > 24GE+4 x GE/10GE SFP+ > Switching Capacity: 128Gbps > High lightning protection: Common/Differential mode 4KV/2KV > Wide working temperature: -20~55°C > SFP+ fiber uplink > Fanless thermal design > Rack mounting	1 Y	1	840	840	Aggregation Switch
Total:				284	22.391	60.800	-
VAT:				10%		6.080	
Grand Total:						66.880	

Some products no have in stock so need to order about 60 days arrive Lao PDR.

This bill of quantity is not a contract or a bill. It is our best guess at the total price for the service and goods described above and can use <= 30 days.



Director

ທ ຈັນທະວີໄລ ບຸນທະລາ

Mr Chanthavilay BOUNTHALA