CIT SOLE CO.,LTD

QUOTATION

Houayhong Village, Chanthabouli District, Vientaine Capital.
Mobile: 02058189995, 58189996, 55556905
Web: www.citgroup.la or www.citsole.com
Email: citgrouplao@gmail.com or dahualaos@gmail.com

CIT0038
29/03/2021

To: .... Tel: ....

Address: ....

					Currency:		USD	
No	Name/Images	Specification	Wty	Qty	Price	Amount	Remark	

No	Name/Images	Specification	Wty	Qty	Price	Amount	Remark
1	SD40212T-HN(-S2)	2MP 12x Starlight PTZ Network Camera > 1/2.8" 2Megapixel STARVIS™ CMOS > Powerful 12x optical zoom > Support Triple-streams encoding > Max. 25/30fps@1080P > IVS > Support PoE+ > IP66, IK10	2Y	1	226	226	Full HD Starligth
2	SD49225T-HN	2MP 25x Starlight IR PTZ Network Camera > 1/2.8" 2Megapixel STARVIS™ CMOS > Powerful 25x optical zoom > Starlight technology > 1080P/720P/D1(1 ~ 25/30fps) > IVS, Support PoE+, IR distance up to 100m, IP67	2Y	1	310	310	Full HD Starligth
3	IPC-HDBW2231R-ZAS-S2	2MP Lite IR Vari-focal Dome Network Camera > 2MP, 1/2.8" CMOS image sensor, low illuminance, high image definition > Outputs 2MP (1920 × 1080)@25/30 fps > H.265 codec, high compression rate, ultra-low bit rate > Built-in IR LED, max IR distance: 40 m > ROI, SMART H.264+/H.265+, flexible coding, applicable to various bandwidth and storage environments > Rotation mode, WDR, 3D NR, HLC, BLC, digital watermarking, applicable to various monitoring scenes > Intelligent detection: Intrusion, tripwire > Abnormality detection: Motion detection, video tampering, no SD card, SD card full, SD card error, network disconnected, IP conflict, illegal ac- cess, voltage detection > Alarm: 1 in, 1 out; audio: 1 in, 1 out; supports max. 256 GB Micro SD card > 12V DC/PoE power supply > IP67, IK10 protection grade	2 Y	1	126	126	Motorized vari-focal
4	IPC-HFW2231T-ZAS-S2	2MP Lite IR Vari-focal Bullet Network Camera > 2MP, 1/2.8" CMOS image sensor, low illuminance, high image definition > Outputs 2MP (1920 × 1080)@25/30 fps > H.265 codec, high compression rate, ultra-low bit rate > Built-in IR LED, max IR distance: 60 m > ROI, SMART H.264+/H.265+, flexible coding, applicable to various bandwidth and storage environments > Rotation mode, WDR, 3D NR, HLC, BLC, digital watermarking, applicable to various monitoring scenes > Intelligent detection: Intrusion, tripwire > Abnormality detection: Motion detection, video tampering, no SD card, SD card full, SD card error, network disconnected, IP conflict, illegal ac- cess, local alarm, voltage detection,audio abnormal > Alarm: 1 in, 1 out; audio: 1 in, 1 out; supports max. 256 GB Micro SD card > 12V DC/PoE power supply > IP67 protection ,IK10 protection (optional)	2 Y	1	126	126	Motorized vari-focal

No	Name/Images	Specification	Wty	Qty	Price	Amount	Remark
5	NVR616-128-4KS2	**128 Channel 3U 16HDDs Ultra series Network Video Recorder** > New 4.0 user interface > 16-channel decoding @1080p (30 fps); self-adaptive decoding capability > Access, storage or forwarding at 384 Mbps > Simultaneous video output for VGA and HDMI1; 4K heterogeneous output for the 2 HDMI ports > Multiple data mode such as Raid0, Raid1, Raid5, Raid6, and Raid10 > Remote configuration and management of IPCs, such as setting pa rameters, acquiring information and upgrading IPCs of the same model in batches > AI-by-camera functions such as perimeter protection, face detection and recognition, SMD Plus, video metadata, ANPR and 3D behavior analysis > N+M cluster. When the host fails, the standbydevice will continue to record; once the host recovers,video recorded on the standby device will be transmitted back	**1 Y**	**2**	**4.250**	**8.500**	**> 50 Days**
6	ST8000NM0055	8TB/7200RPM/256M/ SATA 6Gb/s	1 Y	28	281	7.868	
7	Server	Dell Server R240 & Win10 IoT Ent	1Y	1	4.800	4.800	
8	DSS PRO	DHI-DSSPro-Base-License	N Y	1	3.000	3.000	
9		DHI-DSSPro-Video-License	N Y	21	70	1.470	
10	ARA16	Outdoor Siren	1 Y	1	10	10	
11	PFS3005-4P-58	4-Port PoE Switch (Unmanaged) 5 Port LAN > Two-layer PoE Ethernet switch > MAC auto study and aging, MAC address list capacity is 1K > Conform IEEE802.3, IEEE802.3u and IEEE802.3X standards > Default Mode: The device works as a general switch and all ports support 10/100Mbps auto-negotiation. > Extend Mode: VLAN isolation is enabled. Ports 1-4 will be isolated respectively (10Mbps auto-negotiation), but they can communicate with the Uplink port. Besides, the transmission distance of power and network data is up to 250m.	1 Y	1	33	33	
12	PFS3110-8P-96	PFS3110-8P-96 9 Port LAN 8-Port PoE Switch (Unmanaged) > Two-layer industrial PoE switch > MAC auto study and aging, MAC address list capacity is 8K > Support IEEE802.3af, IEEE802.3at standard > Conform IEEE802.3, IEEE802.3u, IEEE802.3ab/z and IEEE802.3X standards > Industrial wide temperature design	1 Y	1	70	70	

No	Name/Images	Specification	Wty	Qty	Price	Amount	Remark
13	**PFS4218-16ET-190**	16-Port PoE Switch 19 Port LAN > Layer 2 management PoE switch > PoE budget: 190W > Support PoE, PoE+, Hi-PoE > 'Orange port' support Hi-PoE, can be used with the PoE extender (PFT1300) > 250 meters long distance PoE transmission > PoE management, PoE Setting/Event Statistics/Green PoE > Search and upgrade via ConfigTool > Support Web management > High lightning protection design > Non-blocking video transmission	1 Y	1	180	180	
14	**PFS4226-24ET-240**	24-Port PoE Switch 27 Port LAN > Layer 2 management PoE switch > PoE budget: 240W > Support PoE, PoE+, Hi-PoE > 'Orange port' support Hi-PoE, can be used with the PoE extender (PFT1300) > 250 meters long distance PoE transmission > PoE management, PoE Setting/Event Statistics/Green PoE > Search and upgrade via ConfigTool > Support Web management > High lightning protection design > Non-blocking video transmission	1 Y	1	400	400	
15	**PFS3005-5GT**	5-Port Gigabit Switch (Unmanaged) > Layer 2 unmanaged access switch > All gigabit Ethernet ports > Lightning protection > Plug and play > Adopts metal enclosure > Good heat dissipation	1 Y	1	14	14	
16	**PFS3008-8GT+POE**	8-Port Gigabit Switch (Unmanaged) > Layer 2 unmanaged access switch > All gigabit ethernet ports > Lightning protection > Plug and play > Adopts metal enclosure > Good heat dissipation	1 Y	1	60	60	
17	**PFS3016-16GT**	16-Port Gigabit Switch (Unmanaged) > Layer 2 unmanaged access switch > All gigabit Ethernet ports > Lightning protection > Plug and play > Adopts metal enclosure > Good heat dissipation	1 Y	1	80	80	
18	**PFS5428-24GT**	**L2+ Managed Switch** **> Hardened L2+ managed aggregation Switch** **> 24GE+4 x GE/10GE SFP+** **> Switching Capacity: 128Gbps** **> High lightning protection: Common/Differential mode 4KV/2KV** **> Wide working temperature: -20~55°C** **> SFP+ fiber uplink** **> Fanless thermal design** **> Rack mounting**	**0 Y**	**1**	**840**	**840**	**Aggregation Switch**

No	Name/Images	Specification	Wty	Qty	Price	Amount	Remark
19	PFB220C	Ceiling Mount Bracket of Mini Dome & Eyeball Camera >Neat & Integrated design. >Ceiling mount bracket. >Material: Aluminum.	1 Y	1	17	17	
20	PFA154	Pole Mount Bracket > Pole mount bracket > Material: SECC & SUS304 > Aesthetic design > Pole mount bracket *1 > M4 screw *3 > Wrench *1 > 80~150mm metal hoop: 3	1 Y	1	14	14	
21	PFB710W	Wall Mount Bracket > Aesthetic design > Wall mount bracket > Material: stainless steel	1 Y	1	120	120	
21	PFB211W	Wall Mount Bracket > Aluminum alloy material > Matched with particular cameras, beautiful and elegant designed	1 Y	1	15	15	
21	PFA13G	Junction Box > Aluminum alloy material, cost-effective > Dedicated for particular cameras, beautiful and elegant designed > Cabling inside the junction box > Cable threading through bottom or side	1 Y	1	5	5	
21	PFB120C	Ceiling Mount Bracket > Aluminum alloy material, cost-effective > Dedicated for particular cameras, beautiful and elegant designed	1 Y	1	60	60	
21	**DHI-NKB1000**	Keyboard to Control > Dahua High Speed Dome (all models) > Dahua Standalone DVR (KBD1000 &NKB1000 only) > Dahua Network High Speed Dome NKB1000 only) > Network Video Server NKB1000 only) Connection >NKB1000: RS485, RS422, USB, RS232 & Network Functions > Three Dimensional Joystick Control of PTZ Functions > Preset Position, Auto Scan, Auto Pan, Auto Tour & Pattern Auxiliary Functions Auxiliary Functions > On-Screen Menu & User Operation Procedure Tips > Connect to SmartPSS via USB NKB1000 only)	1 Y	1	162	162	Keyboard
		Total:		73	15.269	28.506	-
		VAT:		10%		2.851	
		Grand Total:				31.357	

If confirm do contract and pay 50% and some products no have in stock so need to order about 60 days arrive to Lao PDR.

This bill of quantity is not a contract or a bill. It is our best guess at the total price for the service and goods described above and can use <= 30 days.

Director

ທ ຈັນທະວິໄລ ບຸນທະລາ

Mr Chanthavilay BOUNTHALA