

Relatório 06

Vinícius de Oliveira Peixoto Rodrigues (245294)

Setembro de 2022

Questão 1

Item 1

```
meu-webspace/:
total 12
drwxr-xrwx 2 nuke nuke 4096 Sep 28 15:10 dir1
drw-r-xr-- 2 nuke nuke 4096 Sep 28 14:49 dir2
-r--r----- 1 nuke nuke 116 Sep 28 15:12 index.html

meu-webspace/dir1:
total 8
drwxr-xr-x 2 nuke nuke 4096 Sep 28 15:47 dir11
-r--r--r-- 1 nuke nuke 118 Sep 28 15:09 texto1.html
-r--r--r-- 1 nuke nuke 118 Sep 28 15:10 texto2.html

meu-webspace/dir2:
total 0
```

Item 2

```
> for f in $(find meu-webspace | grep html); do echo "*** $f ***";
cat -A $f; echo ""; done
*** meu-webspace/index.html ***
<!DOCTYPE html>^M$
<html>^M$
^M$
<head>^M$
    <title>index</title>^M$
</head>^M$
^M$
<body>^M$
    INDEX.HTML^M$
</body>^M$
^M$
```

```

</html>^M$

*** meu-webspace/dir1/texto2.html ***
<!DOCTYPE html>^M$
<html>^M$
^M$
<head>^M$
    <title>texto2</title>^M$
</head>^M$
^M$
<body>^M$
    TEXTO2.HTML^M$
</body>^M$
^M$
</html>^M$

*** meu-webspace/dir1/texto1.html ***
<!DOCTYPE html>^M$
<html>^M$
^M$
<head>^M$
    <title>texto1</title>^M$
</head>^M$
^M$
<body>^M$
    TEXTO1.HTML^M$
</body>^M$
^M$
</html>^M$

```

Questão 2

Item 1

```

> for f in $(ls requests/); do cat -A requests/$f; done
GET /dir1 HTTP/1.1^M$
Host: localhost:5555^M$
User-Agent: Mozilla/5.0 (X11; Linux x86_64; rv:103.0) Gecko/20100101 Firefox/103.0^M$
Accept: text/html,application/xhtml+xml,application/xml;q=0.9,image/avif,image/webp,*/*;q=0.8^M$
Accept-Language: en-US,en;q=0.5^M$
Accept-Encoding: gzip, deflate, br^M$
Connection: keep-alive^M$
Upgrade-Insecure-Requests: 1^M$
Sec-Fetch-Dest: document^M$
Sec-Fetch-Mode: navigate^M$

```

```

Sec-Fetch-Site: none^M$
Sec-Fetch-User: ?1^M$
^M$
GET /dir2 HTTP/1.1^M$
Host: localhost:5555^M$
User-Agent: Mozilla/5.0 (X11; Linux x86_64; rv:103.0) Gecko/20100101 Firefox/103.0^M$
Accept: text/html,application/xhtml+xml,application/xml;q=0.9,image/avif,image/webp,*/*;q=0.8^M$
Accept-Language: en-US,en;q=0.5^M$
Accept-Encoding: gzip, deflate, br^M$
Connection: keep-alive^M$
Upgrade-Insecure-Requests: 1^M$
Sec-Fetch-Dest: document^M$
Sec-Fetch-Mode: navigate^M$
Sec-Fetch-Site: none^M$
Sec-Fetch-User: ?1^M$
^M$
GET /dir1/texto1.html HTTP/1.1^M$
Host: localhost:5555^M$
User-Agent: Mozilla/5.0 (X11; Linux x86_64; rv:103.0) Gecko/20100101 Firefox/103.0^M$
Accept: text/html,application/xhtml+xml,application/xml;q=0.9,image/avif,image/webp,*/*;q=0.8^M$
Accept-Language: en-US,en;q=0.5^M$
Accept-Encoding: gzip, deflate, br^M$
Connection: keep-alive^M$
Upgrade-Insecure-Requests: 1^M$
Sec-Fetch-Dest: document^M$
Sec-Fetch-Mode: navigate^M$
Sec-Fetch-Site: none^M$
Sec-Fetch-User: ?1^M$
^M$
GET /dir1/texto2.html HTTP/1.1^M$
Host: localhost:5555^M$
User-Agent: Mozilla/5.0 (X11; Linux x86_64; rv:103.0) Gecko/20100101 Firefox/103.0^M$
Accept: text/html,application/xhtml+xml,application/xml;q=0.9,image/avif,image/webp,*/*;q=0.8^M$
Accept-Language: en-US,en;q=0.5^M$
Accept-Encoding: gzip, deflate, br^M$
Connection: keep-alive^M$
Upgrade-Insecure-Requests: 1^M$
Sec-Fetch-Dest: document^M$
Sec-Fetch-Mode: navigate^M$
Sec-Fetch-Site: none^M$
Sec-Fetch-User: ?1^M$
^M$

```

Item 2

Todas as requisições têm todas as linhas terminadas em ^M\$.

Questão 3

```
> cat -A requests/head.txt requests/options.txt requests/trace.txt
HEAD /index.html HTTP/1.1^M$
Host: localhost:5555^M$
^M$
OPTIONS / HTTP/1.1^M$
Host: localhost:5555^M$
^M$
GET / HTTP/1.1^M$
Host: localhost:5555^M$
^M$
```

Os outros são exatamente iguais, só mudando o nome do resource.