

AS40419 Peering Policy

NullCloud operates Autonomous System AS40419 and maintains an open peering policy designed to improve routing efficiency, reduce latency, and enhance resilience between networks.

Network	NullCloud
ASN	40419
Peering Policy	OPEN
Settlements	Settlement free
IP Protocols	IPv4 and IPv6
Locations	IXPs and mutually suitable private interconnects

General Policy

- We operate an open peering policy, requests are normally accepted where the requesting network satisfies this policy and a technically suitable interconnection is available.
- All peering is settlement-free. Neither party is charged for the exchange of traffic itself
- Peering may be established through an IXP route server, bilateral IX session, or a private interconnect where agreed mutually.
- We may decline, defer, suspend, or terminate a peering session for network stability, security, capacity, integrity or operational reasons.

Technical Requirements

- The peer must provide a valid, publicly routable ASN.
- The peer should support both IPv4 and IPv6 where possible. IPv6 peering may be considered where appropriate.
- BGP sessions must use publicly routable addressing or otherwise, mutually agreed peering addresses. RFC1918 addressing is not used for public IXP peering.
- The peer must announce only prefixes it is authorised to originate or transit: and must maintain accurate routing information.
- BGP sessions must not be used as a default route, or a last resort route. A peer should not send traffic to us that is not destined for routes legitimately announced by us.
- Peers should maintain sufficient interface and routing capacities congestion or instability.

Security of Routing

- We strongly prefer our peers to maintain accurate IRR objects and RPKI ROAs for all announced prefixes.
- Prefixes that are not valid under RPKI, unauthorised, bogon, martian - or are just inconsistent with the agreed routing policy will be filtered by us.
- We apply maximum prefix limits and inbound route filters to protect our network.
- Peers must not advertise our routes back to AS40419, create routing loops, or manipulate attributes in a matter that could cause instability.
- Peers must implement sensible BGP/GRE security practices, including prefix filtering, RPKI validation and route link prevention.

Operational Requirements

- Peers should maintain an accurate PeeringDB record containing their ASN, peering locations, session information, and operational contact details.
- The peer must provide a working operational contact capable of responding to BGP or routing incidents.
- Planned maintenance that is likely to affect a peering session should be communicated in advance wherever reasonably possible.
- Network incidents involving route leaks, route hijacks, or other routing issues should be addressed promptly and communicated to the relevant parties.

Traffic Policy

- NullCloud generally prefers public Internet Exchange (IX) peering for standard traffic exchange.
- Private peering may be considered where traffic levels, network topology, capacity requirements, or operational considerations make a private interconnection appropriate.
- Traffic ratios are not ordinarily enforced for public peering. Private interconnections may be subject to mutually agreed traffic, engineering, or capacity requirements where necessary.

IX Peering

- Where NullCloud and the requesting network are present at the same Internet Exchange Point, peering through the exchange route server is generally preferred where available.
- Bilateral sessions may also be established when operationally useful or when mutually agreed.
- The requesting network is responsible for ensuring its exchange port, VLAN and BGP configuration are correctly provisioned.

BGP Sessions

- BGP sessions should be configured with appropriate inbound and outbound prefix filters.
- Peers should announce a consistent set of routes across sessions at the same peering location unless a different traffic-engineering arrangement has been agreed.
- BGP communities and traffic-engineering attributes may be supported on a per-session basis.
- Their exact behaviour should be confirmed with us before use.
- Us may enforce route limits and filtering without prior notice where necessary to protect network stability