

Probability Matching-based Adaptive Strategy Selection Compared with Uniform Strategy Selection within Differential Evolution on the Noiseless Testbed

Draft version *

Álvaro Fialho
Microsoft Research – INRIA
Joint Centre
Parc Orsay Université
91893 Orsay, France
alvaro.fialho@inria.fr

Wenyin Gong
School of Computer Science
China University of
Geosciences
Wuhan, 430074 P.R. China
cug11100304@yahoo.com.cn

Zhihua Cai
School of Computer Science
China University of
Geosciences
Wuhan, 430074 P.R. China
zhcai@cug.edu.cn

ABSTRACT

The decision of which of the several existent strategies should be applied for the offspring generation is critical for the performance of the Differential Evolution algorithm, besides being problem-dependent. In this paper, we use the BBOB noiseless benchmarking suite to better empirically validate the Probability Matching-based Adaptive Strategy Selection, a technique used to automatically select between the available strategies while solving the problem, recently proposed in [2], referred to as *PM-AdapSS-DE*. It is compared with what would be a possible choice for a naïve user, the uniform strategy selection within the same sub-set of strategies.

Categories and Subject Descriptors

G.1.6 [Numerical Analysis]: Optimization—*global optimization, unconstrained optimization*; F.2.1 [Analysis of Algorithms and Problem Complexity]: Numerical Algorithms and Problems

General Terms

Algorithms

Keywords

Benchmarking, Black-box optimization

1. INTRODUCTION

The decision of which of the several available strategies should be applied for the offspring generation in Differential Evolution is critical for its performance, besides being

*Submission deadline: March 25th.

Permission to make digital or hard copies of all or part of this work for personal or classroom use is granted without fee provided that copies are not made or distributed for profit or commercial advantage and that copies bear this notice and the full citation on the first page. To copy otherwise, to republish, to post on servers or to redistribute to lists, requires prior specific permission and/or a fee.

GECCO'10, July 7–11, 2010, Portland, Oregon, USA.
Copyright 2010 ACM 978-1-4503-0073-5/10/07 ...\$10.00.

problem-dependent. Although the best strategy for a given problem might be found by means of statistics over an expensive set of experiments, a subsequent use of different strategies during the optimization process should achieve better performance, following its intuitive migration from a global (early) exploration of the landscape to a more focused, exploitation-like behavior.

2. ALGORITHM PRESENTATION

3. RESULTS

Results from experiments according to [3] on the benchmark functions given in [1, 4] are presented in Figures 1, 2 and 3 and in Table 1. The **expected running time (ERT)**, used in the figures and table, depends on a given target function value, $f_t = f_{\text{opt}} + \Delta f$, and is computed over all relevant trials as the number of function evaluations executed during each trial while the best function value did not reach f_t , summed over all trials and divided by the number of trials that actually reached f_t [3, 5]. **Statistical significance** is tested with the rank-sum test for a given target Δf_t (10^{-8} in Figure 1) using, for each trial, either the number of needed function evaluations to reach Δf_t (inverted and multiplied by -1), or, if the target was not reached, the best Δf -value achieved, measured only up to the smallest number of overall function evaluations for any unsuccessful trial under consideration.

4. REFERENCES

- [1] S. Finck, N. Hansen, R. Ros, and A. Auger. Real-parameter black-box optimization benchmarking 2009: Presentation of the noiseless functions. Technical Report 2009/20, Research Center PPE, 2009. Updated February 2010.
- [2] W. Gong, A. Fialho, and Z. Cai. Adaptive strategy selection in differential evolution. In J. B. et al., editor, *GECCO'10: Proceedings of the 12th Annual Conference on Genetic and Evolutionary Computation*. ACM Press, July 2010. to appear.
- [3] N. Hansen, A. Auger, S. Finck, and R. Ros. Real-parameter black-box optimization benchmarking 2010: Experimental setup. Technical Report RR-7215, INRIA, 2010.




Figure 1: ERT ratio of ALG1-acronym divided by ALG0-acronym versus $\log_{10}(\Delta f)$ for f_1 – f_{24} in 2, 3, 5, 10, 20, 40-D. Ratios $< 10^0$ indicate an advantage of ALG1-acronym, smaller values are always better. The line gets dashed when for any algorithm the ERT exceeds thrice the median of the trial-wise overall number of f -evaluations for the same algorithm on this function. Symbols indicate the best achieved Δf -value of one algorithm (ERT gets undefined to the right). The dashed line continues as the fraction of successful trials of the other algorithm, where 0 means 0% and the y-axis limits mean 100%, values below zero for ALG1-acronym. The line ends when no algorithm reaches Δf anymore. The number of successful trials is given, only if it was in $\{1 \dots 9\}$ for ALG1-acronym (1st number) and non-zero for ALG0-acronym (2nd number). Results are significant with $p = 0.05$ for one star and $p = 10^{-\#*}$ otherwise, with Bonferroni correction within each figure.




Figure 2: Expected running time (ERT in log10 of number of function evaluations) of ALG1-acronym versus ALG0-acronym for 46 target values $\Delta f \in [10^{-8}, 10]$ in each dimension for functions f_1 – f_{24} . Markers on the upper or right egde indicate that the target value was never reached by ALG1-acronym or ALG0-acronym respectively. Markers represent dimension: 2:+, 3:∇, 5:*, 10:○, 20:□, 40:◇.

5-D

20-D




Figure 3: Empirical cumulative distributions (ECDF) of run lengths and speed-up ratios in 5-D (left) and 20-D (right). Left sub-columns: ECDF of the number of function evaluations divided by dimension D (FEvals/D) to reach a target value $f_{\text{opt}} + \Delta f$ with $\Delta f = 10^k$, where $k \in \{1, -1, -4, -8\}$ is given by the first value in the legend, for ALG1-acronym (solid) and ALG0-acronym (dashed). Light beige lines show the ECDF of FEvals for target value $\Delta f = 10^{-8}$ of algorithms benchmarked during BBOB-2009. Right sub-columns: ECDF of FEval ratios of ALG1-acronym divided by ALG0-acronym, all trial pairs for each function. Pairs where both trials failed are disregarded, pairs where one trial failed are visible in the limits being > 0 or < 1 . The legends indicate the number of functions that were solved in at least one trial (ALG1-acronym first).

5-D

Δf	1e+11e+0	1e-1	1e-3	1e-5	1e-7	#succ
f₁	11	12	12	12	12	15/15
0: stG	8.6	42	80	160	240	310
1: wen	7.4	41	80	150	220	300
f₂	83	87	88	90	92	94
0: stG	20	24	30	40	50	58
1: wen	20	25	29	38	47	55*
f₃	720	1600	1600	1600	1700	1700
0: stG	3.5	12	130	130	130	130
1: wen	3.9	11	220	210	210	210
f₄	810	1600	1700	1800	1900	1900
0: stG	5.1	630	1.9e3	1.8e3	1.7e3	1.7e3
1: wen	4.8	620	∞	∞	∞	∞
f₅	10	10	10	10	10	10
0: stG	20	34	35	35	35	35
1: wen	19	32	34	34	34	34
f₆	110	210	280	580	1000	1300
0: stG	9	9.2	10	7.8	6.1	6.1
1: wen	8.2	8.2	9.4	7.3	5.8	5.8
f₇	24	320	1200	1600	1600	1600
0: stG	14	2.7	1.2	1.4	1.4	1.6
1: wen	11	2.5	1.1	1.4	1.4	1.5
f₈	73	270	340	390	410	420
0: stG	15	10	14	17	18	20
1: wen	14	12	16	20	21	22
f₉	35	130	210	300	340	370
0: stG	30	23	21	21	22	22
1: wen	28	20	20	20	20	20
f₁₀	350	500	570	630	830	880
0: stG	4.5	4.2	4.6	5.5	5.4	6.2
1: wen	4.8	4.3	4.5	5.6	5.2	6
f₁₁	140	200	760	1200	1500	1700
0: stG	6.2	6.6	2.4	2.4	2.6	2.8
1: wen	6	6.4	2.4	2.3	2.5	2.7
f₁₂	110	270	370	460	1300	1500
0: stG	28	21	21	22	10	11
1: wen	27	14	14	18	9.3	10
f₁₃	130	190	250	1300	1800	2300
0: stG	11	12	13	3.7	3.8	3.7
1: wen	10*	11*	12*	3.4*	3.5*	3.4*
f₁₄	9.8	41	58	140	250	480
0: stG	2.3	10	16	15	13	9.3
1: wen	1.8	10	18	15	12*	9
f₁₅	510	9300	1.9e4	2.0e4	2.1e4	2.1e4
0: stG	4.8	2.2	3	3	2.9	2.9
1: wen	5.3	1.9	14	13	13	13
f₁₆	120	610	2700	1.0e4	1.2e4	1.2e4
0: stG	4.3	44	20	17	16	15
1: wen	5.6	43	41	27	41	39
f₁₇	5.2	210	900	3700	6400	7900
0: stG	3.8	4.3	2.7	1.6	1.5	1.6
1: wen	3	4.3	2.5	1.5	1.4*	1.5*
f₁₈	100	380	4000	9300	1.1e4	1.2e4
0: stG	4	4.3	0.81	0.73	0.95	1.1
1: wen	3.5	4.2	0.78	0.72	0.92	1
f₁₉	1	1	240	1.2e5	1.2e5	1.2e5
0: stG	35	3.4e3	1.6e3	13	13	13
1: wen	41	3.2e3	1.6e3	60	60	59
f₂₀	16	850	3.8e4	5.4e4	5.5e4	5.5e4
0: stG	11	10	9.2	6.4	6.4	6.4
1: wen	8.5	8.9	20	14	14	14
f₂₁	41	1200	1700	1700	1700	1800
0: stG	4.5	33	76	75	74	74
1: wen	5.4	110	150	150	150	140
f₂₂	71	390	940	1000	1000	1100
0: stG	6.6	200	470	440	420	410
1: wen	5	96	200	180	180	170
f₂₃	3	520	1.4e4	3.2e4	3.3e4	3.4e4
0: stG	2	11	2.5	3.6	5.5	7.2
1: wen	2.1	9.7	2.1	3.1*	4.8*	5.9*
f₂₄	1600	2.2e5	6.4e6	9.6e6	1.3e7	1.3e7
0: stG	4.3	3.7	0.17	0.15	0.11	0.11
1: wen	3.7	15	0.52	0.34	0.26	0.26

20-D

Δf	1e+1	1e+0	1e-1	1e-3	1e-5	1e-7	#succ
f₁	43	43	43	43	43	43	15/15
0: stG	150	300	440	730	1.0e3	1.3e3	15/15
1: wen	110*	210*	310*	510*	710*	910*	15/15
f₂	380	390	390	390	390	390	15/15
0: stG	77	92	110	140	170	200	15/15
1: wen	57*	68*	80*	100*	120*	140*	15/15
f₃	5100	7600	7600	7600	7600	7700	15/15
0: stG	∞	∞	∞	∞	∞	∞	0/15
1: wen	730*	∞	∞	∞	∞	∞	0/15
f₄	4700	7600	7700	7700	7800	1.4e5	9/15
0: stG	∞	∞	∞	∞	∞	∞	0/15
1: wen	∞	∞	∞	∞	∞	∞	0/15
f₅	41	41	41	41	41	41	15/15
0: stG	69	83	85	86	86	86	15/15
1: wen	72	87	88	88	88	88	15/15
f₆	1300	2300	3400	5200	6700	8400	15/15
0: stG	29	23	20	20	20	20	15/15
1: wen	23*	18*	16*	16*	16*	16*	15/15
f₇	1400	4300	9500	1.7e4	1.7e4	1.7e4	15/15
0: stG	8.4	5.2	3.3	2.7	2.7	2.7	15/15
1: wen	6.3*	3.7*	2.3*	1.8*	1.8*	1.9*	15/15
f₈	2000	3900	4000	4200	4400	4500	15/15
0: stG	34	31	33	35	37	39	15/15
1: wen	35	33	35	37	38	39	15/15
f₉	1700	3100	3300	3500	3600	3700	15/15
0: stG	41	39	41	43	45	46	15/15
1: wen	38	40	43	45	46	47	15/15
f₁₀	7400	8700	1.1e4	1.5e4	1.7e4	1.7e4	15/15
0: stG	3.9	4.1	3.9	3.6	3.9	4.6	15/15
1: wen	2.9*	3*	2.8*	2.6*	2.8*	3.2*	15/15
f₁₁	1000	2200	6300	9800	1.2e4	1.5e4	15/15
0: stG	11	8.1	3.8	3.8	4	4.2	15/15
1: wen	9.6*	6.2*	2.9*	2.8*	2.9*	3*	15/15
f₁₂	1000	1900	2700	4100	1.2e4	1.4e4	15/15
0: stG	44	27	25	26	12	13	15/15
1: wen	31*	19*	17*	22*	12	13	15/15
f₁₃	650	2000	2800	1.9e4	2.4e4	3.0e4	15/15
0: stG	43	20	19	4.1	4.2	4.2	15/15
1: wen	30*	14*	13*	2.8*	2.9*	2.9*	15/15
f₁₄	75	240	300	930	1600	1.6e4	15/15
0: stG	53	50	64	38	31	4.2	15/15
1: wen	46	37*	47*	27*	22*	3*	15/15
f₁₅	3.0e4	1.5e5	3.1e5	3.2e5	4.5e5	4.6e5	15/15
0: stG	980	∞	∞	∞	∞	∞	0/15
1: wen	230	∞	∞	∞	∞	∞	0/15
f₁₆	1400	2.7e4	7.7e4	1.9e5	2.0e5	2.2e5	15/15
0: stG	2.1e4	∞	∞	∞	∞	∞	0/15
1: wen	2.1e4	∞	∞	∞	∞	∞	0/15
f₁₇	63	1000	4000	3.1e4	5.6e4	8.0e4	15/15
0: stG	38	19	10	3	3.2	2.8	15/15
1: wen	23	14*	7.5*	2.1*	2.1*	3.6	14/15
f₁₈	620	4000	2.0e4	6.8e4	1.3e5	1.5e5	15/15
0: stG	18	7.8	2.8	1.7	1.5	1.6	15/15
1: wen	14*	5.5*	2*	1.2*	2.1	2.1	14/15
f₁₉	1	1	3.4e5	6.2e6	6.7e6	6.7e6	15/15
0: stG	2.8e3	9.5e6	∞	∞	∞	∞	0/15
1: wen	1.9e3*	1.4e7	∞	∞	∞	∞	0/15
f₂₀	82	4.6e4	3.1e6	5.5e6	5.6e6	5.6e6	14/15
0: stG	76	∞	∞	∞	∞	∞	0/15
1: wen	51*	300	∞	∞	∞	∞	0/15
f₂₁	560	6500	1.4e4	1.5e4	1.6e4	1.8e4	15/15
0: stG	21	460	570	550	520	460	3/15
1: wen	13*	210	210	210	190	170	6/15
f₂₂	470	5600	2.3e4	2.5e4	2.7e4	1.3e5	12/15
0: stG	1.6e3	990	∞	∞	∞	∞	0/15
1: wen	1.6e3	990	∞	∞	∞	∞	0/15
f₂₃	3.2	1600	6.7e4	4.9e5	8.1e5	8.4e5	15/15
0: stG	3	6.0e3	∞	∞	∞	∞	0/15
1: wen	2.4	940*	430*	∞	∞	∞	0/15
f₂₄	1.3e6	7.5e6	5.2e7	5.2e7	5.2e7	5.2e7	3/15
0: stG	∞	∞	∞	∞	∞	∞	0/15
1: wen	∞	∞	∞	∞	∞	∞	0/15

Table 1: Expected running time (ERT in number of function evaluations) divided by the best ERT measured during BBOB-2009 (given in the respective first row) for different Δf values for functions f_1 – f_{24} . The median number of conducted function evaluations is additionally given in *italics*, if $\text{ERT}(10^{-7}) = \infty$. #succ is the number of trials that reached the final target $f_{\text{opt}} + 10^{-8}$. 0: stG is ALG0-acronym and 1: wen is ALG1-acronym. Bold entries are statistically significantly better compared to the other algorithm, with $p = 0.05$ or $p = 10^{-k}$ where $k > 1$ is the number following the $*$ symbol, with Bonferroni correction of 48.

Algorithm 1 Probability matching-based DE with adaptive strategy selection: PM-AdapSS-DE

```
1: Set  $CR = 0.9$ ,  $F = 0.5$  and  $NP = 10 \times D$ 
2: Generate the initial population
3: Evaluate the fitness for each individual
4: Set the generation counter  $t = 1$ 
5: Set  $K = 4$ ,  $p_{min} = 0.05$ , and  $\alpha = 0.3$ 
6: For each strategy  $a$ , set  $q_a(t) = 0$  and  $p_a(t) = 1/K$ 
7: while The halting criterion is not satisfied do
8:   for  $i = 1$  to  $NP$  do
9:     Select the strategy  $SI_i$  based on its probability
10:    Select uniform randomly  $r_1 \neq r_2 \neq r_3 \neq r_4 \neq r_5 \neq i$ 
11:     $j_{rand} = \text{rndint}(1, D)$ 
12:    for  $j = 1$  to  $D$  do
13:      if  $\text{rndreal}_j[0, 1) < CR$  or  $j == j_{rand}$  then
14:        if  $SI_i == 1$  then
15:           $u_{i,j}$  is generated by “DE/rand/1” strategy
16:        else if  $SI_i == 2$  then
17:           $u_{i,j}$  is generated by “DE/rand/2” strategy
18:        else if  $SI_i == 3$  then
19:           $u_{i,j}$  is generated by “DE/rand-to-best/2” strategy
20:        else if  $SI_i == 4$  then
21:           $u_{i,j}$  is generated by “DE/current-to-rand/1”
22:        end if
23:      else
24:         $u_{i,j} = x_{i,j}$ 
25:      end if
26:    end for
27:  end for
28:  for  $i = 1$  to  $NP$  do
29:    Evaluate the offspring  $\mathbf{u}_i$ 
30:    if  $f(\mathbf{u}_i)$  is better than or equal to  $f(\mathbf{x}_i)$  then
31:      Calculate  $\eta_i$  using Eqn. (??)
32:      Replace  $\mathbf{x}_i$  with  $\mathbf{u}_i$ 
33:    else
34:      Set  $\eta_i = 0$ 
35:    end if
36:     $S_{SI_i} \leftarrow \eta_i$ 
37:  end for
38:  Calculate the reward  $r_a(t)$  for each strategy
39:  Update the quality  $q_a(t)$  for each strategy
40:  Update the probability  $p_a(t)$  for each strategy
41:   $t = t + 1$ 
42: end while
```

- [4] N. Hansen, S. Finck, R. Ros, and A. Auger. Real-parameter black-box optimization benchmarking 2009: Noiseless functions definitions. Technical Report RR-6829, INRIA, 2009. Updated February 2010.
- [5] K. Price. Differential evolution vs. the functions of the second ICEO. In *Proceedings of the IEEE International Congress on Evolutionary Computation*, pages 153–157, 1997.