Appendix A

UNF

CARNIVAL(<u>cdate</u>, director,location, events, {sponsorname, isNaming, sponsoramount, sponsorcontact, sponsorphone})

1NF

CARNIVAL(<u>cdate</u>, director, location, events, <u>sponsorname</u>, isNaming, sponsoramount, sponsorcontact) sponsorname -> isNaming TRANSITIVE sponsorname -> amount TRANSITIVE

sponsorname -> sponsorcontact TRANSITIVE

sponsorname -> sponsorphone TRANSITIVE

2NF

CARNIVAL(cdate, director, location, events)

SPONSOR(<u>sponsorname</u>, isNaming, sponsoramount, sponsorcontact)

3NF

CARNIVAL(cdate, director, location, events)

SPONSOR(<u>sponsorname</u>, isNaming, sponsoramount, sponsorcontact, sponsorphone)

Appendix B

UNF

COMPETITOR(<u>cnumber</u>, cfirstname, clastname, cname, cgender, cbirthday, cemail, clsStu, cMobile, clsAnyCondition, cArea, ecfirstname, eclastname, ename, ecphone, ecrelation, gfirstname, glastname, gname, gphone)

1NF

COMPETITOR(<u>cnumber</u>, cfirstname, clastname, cgender, cbirthday, cemail, clsStu, cMobile, clsAnyCondition, cArea, ecfirstname, eclastname, ecphone, ecrelation, gfirstname, glastname, gname, gphone)

2NF

COMPETITOR(<u>cnumber</u>, cfirstname, clastname, cgender, cbirthday, cemail, clsStu, cMobile, clsAnyCondition, cArea, ecfirstname, eclastname, ecphone, ecrelation, gfirstname, glastname, gname, gphone)

3NF

COMPETITOR(<u>cnumber</u>, cfirstname, clastname, cgender, cbirthday, cemail, clsStu, cMobile, clsAnyCondition, cArea, ecfirstname, eclastname, ecphone, ecrelation, gfirstname, glastname, gname, gphone)

Appendix C

UNF

ENTRY(enumber, cnumber, cfirstname, clastname, cname, event, teamname)

1NF

ENTRY(enumber, cnumber, cfirstname, clastname, cname, event, teamname)

cnumber ->cfirstname TRANSITIVE

cnumber -> clastname TRANSITIVE

cnumber -> cname TRANSITIVE

2NF

ENTRY(<u>enumber</u>, cnumber, cfirstname, clastname, cname, event, teamname)

3NF

ENTRY(enumber, cnumber, event, teamname)

Appendix D

UNF

ORDER(cdate, location, <u>ordernumber</u>, orderdate, cnumber, cname, {Iltemcode, ItemDescription, cost, qtn, linecost}, delivery, totalCost)

1NF

ORDER(cdate, location, ordernumber, orderdate, cnumber, cname, delivery, totalCost)

MERCHANDISE(ordernumber, itemcode, ItemDescription, cost, qtn, linecost)

cdate -> location TRANSITIVE

cnumber -> cname TRANSITIVE

ordernumber, itemcode -> itemDescription PARTIAL

ordernumber, itemcode -> cost PARTIAL

2NF

ORDER(cdate, location, <u>ordernumber</u>, orderdate, cnumber, cname, delivery, totalCost)

MERCHANDISE(<u>ordernumber</u>, <u>itemcode</u>, qtn, linecost)

ITEM(itemcode, itemdescription, itemcost)

3NF

ORDER(cdate, ordernumber, orderdate, cnumber, delivery, totalCost)

MERCHANDISE(ordernumber, itemcode, qtn, linecost)

ITEM(itemcode, itemdescription, itemcost)

Appendix E

UNF

ORDER(cdate, location, <u>ordernumber</u>, orderdate, vnumber, vname, {Iltemcode, ItemDescription, cost, qtn, linecost}, delivery, totalCost)

1NF

ORDER(cdate, location, ordernumber, orderdate, vnumber, vname, delivery, totalCost)

```
MERCHANDISE(<u>ordernumber</u>, <u>itemcode</u>, ItemDescription, cost, qtn, linecost)
cdate -> location TRANSITIVE
vnumber -> vname TRANSITIVE
ordernumber, itemcode -> itemDescription PARTIAL
```

2NF

ORDER(cdate, location, <u>ordernumber</u>, orderdate, vnumber, vname, delivery, totalCost)

MERCHANDISE(<u>ordernumber</u>, <u>itemcode</u>, qtn, linecost)

ITEM(itemcode, itemdescription, itemcost)

3NF

ORDER(cdate, <u>ordernumber</u>, orderdate, vnumber, delivery, totalCost)
MERCHANDISE(<u>ordernumber</u>, <u>itemcode</u>, qtn, linecost)
ITEM(<u>itemcode</u>, itemdescription, itemcost)
VOLUNTEER(<u>vnumber</u>, vname)

Final

CARNIVAL(cdate, director, location, events)

ordernumber, itemcode -> cost PARTIAL

SPONSOR(sponsorname, isNaming, sponsoramount, sponsorcontact, sponsorphone)

COMPETITOR(<u>cnumber</u>, cfirstname, clastname, cname, cgender, cbirthday, cemail, clsStu, cMobile, clsAnyCondition, cArea, ecfirstname, eclastname, ecphone, ecrelation, gfirstname, glastname, gname, gphone)

ENTRY(<u>enumber</u>, cnumber, event, teamname)

ORDER(cdate, ordernumber, orderdate, cvnumber, delivery, totalCost)

MERCHANDISE(ordernumber, itemcode, qtn, linecost)

ITEM(itemcode, itemdescription, itemcost)

VOLUNTEER(vnumber, vname)