
Determine

Dumb glasses. Your phone does the thinking. A warning you can hear or feel.




Cars beep when we can't see behind us. People who are blind deserve a head-level warning too.

Proposed design · HackTX 26
Not built or tested yet
UT Austin, 24–25 Oct 2026
For judges, Meta and Annapurna Labs
Full architecture contract on request

A A cane finds the ground. The branch is at head height.

About 1 in 8 blind travellers hit their head at least once a month.

In a survey of 307 blind travellers, 13% had a head-level accident at least monthly. 86% of those happened outdoors, mostly on tree branches, and 23% had medical consequences.[2] A long cane sweeps the ground ahead of you. Its own makers' field calls it a primary aid, and it is excellent at curbs and steps. It cannot feel a branch at eye level, an open cabinet door or a truck mirror.



The long cane “does not protect users from obstacles at the upper body and head levels.”

Pittet et al., *Scientific Reports*, 2026[1]

Maya

ILLUSTRATIVE TRAVELLER

Walks to class with a long cane. Her left ear is weaker than her right.

Keeps her cane

Determine adds a head-level layer. It never replaces the cane or a guide dog, and it never says the path is clear.


Wants a warning, not a narrator

In a 2026 trial, every participant preferred short, precise output (“person to your left at 11 o'clock, 3 metres”) to generative descriptions.[1]

Learns it in minutes

4 of 13 trial users struggled with a rival's spatialised sounds.[1] Determine uses a small cue set, taught at setup, with direction carried twice.

B Dumb glasses. Your phone does the thinking.



Sense · two boards on the frame

A candidate ESP32-CAM sends JPEG frames; the C3 sends a grid of 64 distances. Two independent Wi-Fi streams to the phone, each packet timestamped. No decisions are made on the face.

Decide · on the phone

The phone aligns the two streams by timestamp and receive age, then an on-device object detector plus the distance grid feed fixed hazard rules and pick *one* cue: which sound, how loud on each side, which temple buzzes.

Play · on the glasses

The C3 plays a stored sound straight to the bone over I2S, so urgent beeps skip Bluetooth audio delay. Every command expires: a late one is dropped, never played late.

Range plus context. The 8×8 ToF grid measures distance even when a branch or open door has no detector label; the camera adds object context.

Same app, other glasses. Meta's Wearables DAT 1.0 can stream supported glasses' camera to a phone; its Mock Device Kit simulates it.[9] Determine's frame input could accept Meta frames. Claim only if built at HackTX.


Two boards, one hotspot. The C3 has no camera or Espressif parallel-camera driver support,[10] so a separate ESP32-CAM candidate would supply JPEG. Both join the phone hotspot; the phone drops stale frames and grids after clock-offset and receive-age checks. No inter-board wire.

Power and one bus. Two power-bank outputs and two leads; verify draw and fit. C3 has one hardware I2C bus,[6] so two identical-address haptic drivers need a mux or PWM drive.

C A parking sensor that knows what it's beeping at.


How close → tempo

The car-sensor model everyone already knows. Never above 6 notes a second.[3]




Where → which ear

Left staff plays the left ear, right staff the right. The matching temple buzzes too.



What → timbre

Timbre and rhythm are the strongest cues for telling sounds apart.[3]



Words → optional

Sped-up spoken words (spearcons) after the beep, never instead of it.[4]

"left" "door" "person" "right"


"11 o'clock, 2 metres"



There is no all-clear sound. Silence is a rest, not the end of the piece.

Silence would mean “nothing to report from a working system”, never “path clear”. If the camera, distance grid or either board's link fails, the design targets a descending **system off** motif within one second, repeated until recovery. If both boards lose power, the dead glasses cannot beep: the phone must speak or vibrate the failure instead. Timing and audibility are untested. Tempo, motif and haptics carry urgency too.

D Equally loud in both ears, even when one is weaker.



Weaker left ear → higher left level → equal loudness.

Uses the audiology convention (**X** left, **O** right) but it is not a hearing test and never shows results as one. Values are illustrative.

Two to three minutes at setup, a 20-second check each time you put them on.

1 Fit
Seat the frame. The app notes which output is in use and which side feels weaker.

2 Find each side's quietest audible level
An adaptive staircase, tap “heard” or “not heard”, in the three bands the cues use.

3 Set the level
10–20 dB above that threshold, your choice, clamped to the ceiling.[3]

4 Balance
The real obstacle cue alternates left and right. Nudge until both feel the same.

5 Verify
Name the side of five random cues. Four right keeps stereo; otherwise switch mode.

Stereo

Each ear gets its own calibrated level. Side is heard, and the matching temple confirms it.

One deaf ear

Bone-conducted sound crosses the skull losing only about 0–10 dB,[5] so left/right audio can't carry direction. Audio goes the same to both sides; the temple buzz and words carry direction.


Haptic only

For anyone who prefers it. No calibration step, slider or urgency boost ever passes the ceiling; if the weak side would need more, it's marked unusable.

E Two loops. One can't wait. One can think.

Warnings never touch the network. Scene description is a question Maya chooses to ask; the design target is AWS's Annapurna silicon: a Graviton API and a small vision-language model on Inferentia2. Trainium2 is the documented alternative if the Inf2 path fails.[11,13–15]

Reflex PHONE · OFFLINE · ALWAYS ON



Target ≤ 250 ms from capture to cue at the 95th percentile, shown live on the judges' screen. It's a goal until we measure it, and nothing is measured yet — the shared hotspot carrying two streams is the least certain part. At walking pace (1.4 m/s), 250 ms is about 35 cm, so warning distances budget for it.

Three tiers of silicon, each placed by its latency, power and failure budget: two small ESP32-class boards on the glasses — a C3 for the distance grid, cues and haptics[6], and a classic-ESP32 camera module for JPEG frames[10] — then the phone's processor for every decision, and Annapurna silicon for the one job that can wait seconds. No board on the face decides anything.

Describe ON REQUEST · ANNAPURNA SILICON

ASK	Long-press: **"what's ahead?"** Never automatic.
REDACT	The phone would blur faces and sensitive details before upload; imperfect redaction is a privacy risk, so upload requires the user's choice.
GRAVITON	A small arm64 Lambda API (Graviton2) would hold the prompt: two sentences, surroundings first, no guesses about people.[17]
INFERENTIA2	SmolVLM on one inf2.xlarge ($0.76/h) using Hugging Face Optimum Neuron. The model family is listed for Inf2; this deployment is still untested by us.[14,15]
SPEAK	The phone would say **"may be wrong"**, then read the result. Any mid- or near-range hazard interrupts it.

Kept short on purpose: trial participants preferred concise, precise output to generative description.[1] End-to-end time is unmeasured; we plan for seconds, not milliseconds.

Maya asks

"What's ahead?" The user, not the model, chooses when description is useful. A fast hazard beep would interrupt this answer.

"May be wrong. A doorway is open on your right; a person is farther ahead near the wall."

ILLUSTRATIVE COPY · NOT MODEL OUTPUT OR A NAVIGATION INSTRUCTION

Describe adds context after the urgent Reflex loop. It never reassures the user that an area is safe, and cloud failure never silences the local cue. Time to response is not measured.

Inferentia2 · target

SmolVLM via Hugging Face Optimum Neuron on inf2.xlarge. Supported model family, not a validated deployment.[14,15]

Trainium2 · alternative

AWS Neuron documents Qwen2-VL-7B on one chip; fit on a smaller trn2.3xlarge is untested.[12,13,16]


Bedrock · fallback

Nova Lite can handle images, but Bedrock does not guarantee the silicon. New accounts start with Inf/Trn quota 0.[18,19]

Determine · Reflex and Describe

Request accelerator access now; approval is not guaranteed. Compile and integrate the model at HackTX under its all-work-at-the-event rule.[20]

F Three minutes, one course, one pulled plug.



0:00 — Hook 20 s
The parking-sensor line, moved from the bumper to the brow.

0:20 — Live course 75 s
A spotter walks the wearer past a head-height foam bar, a person, then a left and a right obstacle. The judges' screen shows both streams' age, the 8×8 grid, the chosen cue and measured latency.

1:35 — One-ear mode 30 s
Switch to a single-sided profile: audio goes mono, the temples carry direction.

2:05 — Pull the plug 20 s
Unplug the camera board. "System off" plays; reconnect and wait for ready. Never silence.

2:25 — Ask 20 s
After recovery, "What's ahead?" If cloud is ready, send a redacted frame for a two-sentence description.

2:45 — Close 15 s
What we measured, what it can't see, what's next.

3:00

The parts, priced only where provable

C3 · 3-PACK	One on the glasses, two spare. Wi-Fi client, one hardware I2C bus, 400 KB SRAM.[6] Micro Center price and local stock unverified.
ESP32-CAM	Candidate, not yet bought: classic-ESP32 camera module, its own hotspot client, JPEG frames. OV2640 sensor and PSRAM are checked on the actual item before we rely on them.[10]
TOF GRID	VL53L5CX 8×8 time-of-flight imager — $25.95 and listed in stock at SparkFun when rechecked 18 Oct.[7]
CUES + HAPTICS	Bone transducers, I2S amps and haptic motors. Adafruit's bone transducer was out of stock when checked 18 Oct; find a suitable substitute.[8]
POWER + FRAME	Power bank with two outputs, two cables, the frame — picked at build, checked on the items.

No total on purpose: Micro Center's pages for both boards returned HTTP 403 from research on 18 Oct, so price and local availability are unverified — a parts total, and any comparison, waits until confirmed in store. The C3 3-pack is the chosen buy; the ESP32-CAM is a candidate. The old single-board total is withdrawn with the board.

Built at HackTX, by four people

The official rule: "All work must be done at the event."[20] Parts are bought ahead; firmware, app and frame are built on site.

Glasses firmware
Two boards: C3 runs grid, cues, haptics; candidate ESP32-CAM streams JPEG

Phone perception
Stream alignment, detector, hazard rules, judge screen

Sound and calibration
Cue bank, balance flow, one-ear mode

Describe and demo
Graviton API, Neuron model, the pitch

Demo branches: if accelerator access fails, skip the scene answer and show the offline warning loop. If the camera module cannot stream, use the phone camera on a headband as a labelled software fallback — not the proposed glasses. No prerecorded result or fabricated latency; sponsor integration is a goal, not a claim.

G What it can't see, said out loud.

Glass doors and windows	LIGHT PASSES THROUGH
Thin wires and ropes	TOO SMALL FOR 8×8
Drop-offs, curbs, stairs going down	THE CANE'S JOB
Anything outside the forward view	63° FIELD
Fast-moving vehicles	NOT A TRAFFIC AID
Glare, darkness, rain and fog	DEGRADES, ANNOUNCED
Anything beyond about 3 m	BY DESIGN

Spoken to every new user during setup. Demos run on a staged indoor course with a sighted spotter.

Fail loud.
Design target: announce “system off” within one second through a working output, including the phone if the frame loses power. Never call silence a clear path. Not yet tested.

Unknown is not clear.
No detections never produces a reassuring sound.

The cane stays.
Determine is a secondary aid, on top of a cane or guide dog.

Claim only what we measured.
Every threshold and latency here is a target until tested with blind and low-vision people, with an orientation and mobility specialist.

Sources (24 Oct 2026; hardware 6–8, 10 checked 18 Oct)

1. Pittet et al., secondary travel-aid trial, 2026
2. Manduchi & Kurniawan, mobility accidents, 2011
3. Brewster et al., earcon guidelines, 1995
4. Walker et al., spearcons, 2013
5. Stenfelt, sound crossing the skull, 2012
6. Seeed, XIAO ESP32-C3 wiki: 400 KB SRAM, one I2C; Espressif, I2S
7. SparkFun, VL53L5CX ToF, $25.95
8. Adafruit: bone, amp, haptic driver, motor
9. Meta, Wearables DAT and Mock Device Kit
10. Espressif, esp32-camera driver: ESP32/S2/S3; PSRAM above-CIF JPEG
11. About Amazon, Annapurna Labs
12. AWS Neuron, NxD release notes, Trn2+
13. AWS Neuron, Qwen2-VL tutorial
14. Hugging Face, Optimum Neuron models
15. AWS, EC2 Inf2 instances
16. AWS, EC2 Trn2 instances
17. AWS, Lambda arm64 / Graviton2
18. AWS, Bedrock Nova Lite model card
19. AWS, EC2 accelerator quotas
20. Freetail Hackers, HackTX 26 FAQ