]0;admlocal@devOps: ~/leantime_ansibleadmlocal@devOps:~/leantime_ansible$ molecule converge INFO default scenario test matrix: dependency, create, prepare, converge INFO Performing prerun... INFO Using .cache/roles/nunomourinho.leantime_ansible symlink to current repository in order to enable Ansible to find the role using its expected full name. INFO Added ANSIBLE_ROLES_PATH=~/.ansible/roles:/usr/share/ansible/roles:/etc/ansible/roles:./.cache/roles INFO Running default > dependency WARNING Skipping, missing the requirements file. WARNING Skipping, missing the requirements file. INFO Running default > create WARNING Skipping, instances already created. INFO Running default > prepare WARNING Skipping, instances already prepared. INFO Running default > converge PLAY [Converge]
****
TASK [Gathering Facts]
*** ok: [ubuntu-20.04] TASK [Include leantime_ansible]
** TASK [leantime_ansible : Atualiza a cache (equivalente a apt update)]
*** changed: [ubuntu-20.04] TASK [leantime_ansible : Atualiza o sistema operativo] ** ok: [ubuntu-20.04] TASK [leantime_ansible : Instalar as dependencias necessária ao programa leantime]
*** ok: [ubuntu-20.04] TASK [leantime_ansible : Instala o serviço apache2 no arranque do sistema] ** ok: [ubuntu-20.04] TASK [leantime_ansible : Rotina Auxiliar: Procura o caminho do ficheiro php.ini do servidor apache2]
***************************** ok: [ubuntu-20.04] TASK [leantime_ansible : Ativa várias opÃ§Ãµes no ficheiro php.ini, utilizando o mÃ³dulo lineinfile.] ***************************** ok: [ubuntu-20.04] => (item={'regexp': '^file_uploads', 'line': 'file_uploads = 1'}) ok: [ubuntu-20.04] => (item={'regexp': '^upload_max_filesize', 'line': 'upload_max_filesize = 1G'}) ok: [ubuntu-20.04] => (item={'regexp': '^max_file_uploads', 'line': 'max_file_uploads = 20'}) ok: [ubuntu-20.04] => (item={'regexp': '^post_max_size', 'line': 'post_max_size = 2G'}) ok: [ubuntu-20.04] => (item= {'regexp': '^memory_limit', 'line': 'memory_limit = 2G'}) ok: [ubuntu-20.04] => (item={'regexp': '^max_input_time', 'line': 'max_input_time = 3600'}) TASK [leantime_ansible : Cria a directoria temporária leantime e a directoria de apache leantime] ****************************** ok: [ubuntu-20.04] => (item={'path': '/tmp/leantime'}) ok: [ubuntu-20.04] => (item={'path': '/var/www/leantime'}) TASK [leantime_ansible : Cria a base de dados de mysql para o leantime] ** ok: [ubuntu-20.04] TASK [leantime_ansible : Cria o utilizador para a base de dados leantime] ** **[WARNING]: Module did not set no_log for update_password** ok: [ubuntu-20.04] TASK [leantime_ansible : Faz o download do software leantime a partir do repositÃ³rio git] *** ok: [ubuntu-20.04] TASK [leantime_ansible : Descomprime o software leantime]
** ok: [ubuntu-20.04] TASK [leantime_ansible : Copia o ficheiro de configuraçÃ£o configuration.sample.php] *** changed: [ubuntu-20.04] TASK [leantime_ansible : Altera as variÃ¡veis dbuser, dbpassword e dbdatabase no ficheiro configuration.php utilizando o mÃ³dulo replace.] *** changed: [ubuntu-20.04] => (item={'regexp': 'dbUser=""', 'line': 'dbUser="leantimeDBadmin"'}) changed: [ubuntu-20.04] => (item={'regexp': 'dbDatabase=""', 'line': 'dbDatabase="leantime_database"'}) changed: [ubuntu-20.04] => (item={'regexp': 'dbPassword=""', 'line': 'dbPassword="#S3gr3d0S3cr3t0#"'}) PLAY RECAP
****
ubuntu-20.04 : ok=14 changed=3 unreachable=0 failed=0 skipped=0 rescued=0 ignored=0]0;admlocal@devOps: ~/leantime_ansibleadmlocal@devOps:~/leantime_ansible$ molecule idempotence INFO default scenario test matrix: idempotence INFO Performing prerun... INFO Using .cache/roles/nunomourinho.leantime_ansible symlink to current repository in order to enable Ansible to find the role using its expected full name. INFO Added ANSIBLE_ROLES_PATH=~/.ansible/roles:/usr/share/ansible/roles:/etc/ansible/roles:./.cache/roles INFO Running default > idempotence PLAY [Converge]
****
TASK [Gathering Facts]
*** ok: [ubuntu-20.04] TASK [Include leantime_ansible]
** TASK [leantime_ansible : Atualiza a cache (equivalente a apt update)]
*** ok: [ubuntu-20.04] TASK [leantime_ansible : Atualiza o sistema operativo] ** ok: [ubuntu-20.04] TASK [leantime_ansible : Instalar as dependencias necessária ao programa leantime]
*** ok: [ubuntu-20.04] TASK [leantime_ansible : Instala o serviço apache2 no arranque do sistema] ** ok: [ubuntu-20.04] TASK [leantime_ansible : Rotina Auxiliar: Procura o caminho do ficheiro php.ini do servidor apache2]
***************************** ok: [ubuntu-20.04] TASK [leantime_ansible : Ativa várias opÃ§Ãµes no ficheiro php.ini, utilizando o mÃ³dulo lineinfile.] ***************************** ok: [ubuntu-20.04] => (item={'regexp': '^file_uploads', 'line': 'file_uploads = 1'}) ok: [ubuntu-20.04] => (item={'regexp': '^upload_max_filesize', 'line': 'upload_max_filesize = 1G'}) ok: [ubuntu-20.04] => (item={'regexp': '^max_file_uploads', 'line': 'max_file_uploads = 20'}) ok: [ubuntu-20.04] => (item={'regexp': '^post_max_size', 'line': 'post_max_size = 2G'}) ok: [ubuntu-20.04] => (item= {'regexp': '^memory_limit', 'line': 'memory_limit = 2G'}) ok: [ubuntu-20.04] => (item={'regexp': '^max_input_time', 'line': 'max_input_time = 3600'}) TASK [leantime_ansible : Cria a directoria temporária leantime e a directoria de apache leantime] ****************************** ok: [ubuntu-20.04] => (item={'path': '/tmp/leantime'}) ok: [ubuntu-20.04] => (item={'path': '/var/www/leantime'}) TASK [leantime_ansible : Cria a base de dados de mysql para o leantime] ** ok: [ubuntu-20.04] TASK [leantime_ansible : Cria o utilizador para a base de dados leantime] ** **[WARNING]: Module did not set no_log for update_password** ok: [ubuntu-20.04] TASK [leantime_ansible : Faz o download do software leantime a partir do repositÃ³rio git] *** ok: [ubuntu-20.04] TASK [leantime_ansible : Descomprime o software leantime]
** ok: [ubuntu-20.04] TASK [leantime_ansible : Copia o ficheiro de configuraçÃ£o configuration.sample.php] ***

changed: [ubuntu-20.04] TASK [leantime_ansible : Altera as variáveis dbuser, dbpassword e dbdatabase no ficheiro configuration.php utilizando o módulo replace.] *** changed: [ubuntu-20.04] => (item={'regexp': 'dbUser=""', 'line': 'dbUser="leantimeDBadmin"'}) changed: [ubuntu-20.04] => (item={'regexp': 'dbDatabase=""', 'line': 'dbDatabase="leantime_database"'}) changed: [ubuntu-20.04] => (item={'regexp': 'dbPassword=""', 'line': 'dbPassword="#S3gr3d0S3cr3t0#"'}) PLAY RECAP

****
ubuntu-20.04 : ok=14 changed=2 unreachable=0 failed=0 skipped=0 rescued=0 ignored=0 **CRITICAL** Idempotence test failed because of the following tasks: * => leantime_ansible : Copia o ficheiro de configuração configuration.sample.php * => leantime_ansible : Altera as variáveis dbuser, dbpassword e dbdatabase no ficheiro configuration.php utilizando o módulo replace. * => leantime_ansible : Altera as variáveis dbuser, dbpassword e dbdatabase no ficheiro configuration.php utilizando o módulo replace. * => leantime_ansible : Altera as variáveis dbuser, dbpassword e dbdatabase no ficheiro configuration.php utilizando o módulo replace.]0;admlocal@devOps: ~/leantime_ansibleadmlocal@devOps:~/leantime_ansible$ nano tasks/tasks.yml [?2004h[?1049h[?7h[?1h=[?1h=[?25l[A ler...][147 linhas lidas] GNU nano 4.8 tasks/tasks.yml ^G Ajuda^O Gravar^W Procurar^K Cortar txt ^J Justificar ^C Pos cursor M-U Desfazer M-A Marcar txt ^X Sair^R Carregar^\ Substituir ^U Colar txt ^T Ortografia ^_ Ir p/ linha M-E RefazerM-6 Copiar txt ---- name: Atualiza a cache (equivalente a apt update)apt:update_cache: truecache_valid_time: 3600- name: "Atualiza o sistema operativo"apt:upgrade: safe- name: "Instalar as dependencias necessária ao programa leantime"apt:pkg:- mc- screen- git- apache2- mysql-server- php- php-mysql- php-ldap- php-cli- php-soap- php-json- graphviz- php-xml- php-gd- php-zip- libapache2-mod-php- php-dev- libmcrypt-dev- gcc- make- autoconf- libc-dev [?12l[?25h[?25l - autoconf - libc-dev - pkg-config- pwgen- curl- unzip - zip - php-mbstring- expect- net-tools - python3-mysqldb - python3-apt- python3-pycurl # Fonte de inspiração: https://docs.ansible.com/ansible/latest/collections/ansible/builtin/service_module.html- name: "Instala o serviço apache2 no arranque do sistema"service:name: apache2state: startedenabled: true # Fonte: https://www.mydailytutorials.com/using-ansible-find-module-search-filesfolder- name: "Rotina Auxiliar: Procura o caminho do ficheiro php.ini do servidor apache2"find:paths: /etcpatterns: "php.ini"recurse: trueregister: caminho_php_ini # Fonte: https://docs.ansible.com/ansible/latest/collections/ansible/builtin/lineinfile_module.html- name: "Ativa várias opções no ficheiro php.ini, utilizando o módulo lineinfile."ansible.builtin.lineinfile:path: "{{ caminho_php_ini.files[0].path }}"regexp: "{{ item.regexp }}"line: "{{ item.line }}" [?12l[?25h[?25lregexp: "{{ item.regexp }}"line: "{{ item.line }}"with_items:regexp: "^file_uploads" line: "file_uploads = 1"regexp: "^upload_max_filesize" line: "upload_max_filesize = 1G"regexp: "^max_file_uploads" line: "max_file_uploads = 20"regexp: "^post_max_size" line: "post_max_size = 2G"regexp: "^memory_limit" line: "memory_limit = 2G"- regexp: "^max_input_time" line: "max_input_time = 3600" # Fonte: https://docs.ansible.com/ansible/2.7/modules/file_module.html- name: Cria a directoria temporária leantime e a directoria de apache leantimefile:path: "{{ item.path }}"state: directory mode: 0755 owner: www-data group: www-datawith_items:- path: "/tmp/leantime"- path: "/var/www/leantime" # Fonte: Ansible for DevOps - Server and configuration management for humans de Jeff Geerling, página 98 - name: "Cria a base de dados de mysql para o leantime" mysql_db: "db=leantime_database state=present" - name: "Cria o utilizador para a base de dados leantime"mysql_user:namlogin_leantime }}" [?12l[?25h[?25lmysql_user:namlogin_leantime }}" password: "{{ password_leantime }}"priv: "leantime_database.*:ALL"host: localhoststate: present - name: "Faz o download do software leantime a partir do repositório git"get_url:url: https://github.com/Leantime/leantime/releases/download/{{ versao_leantime }}/Leantime-{{ versao_leantime }}.zipdest: /tmp/leantimemode: 0755 # O ficheiro Leantime-versao.zip necessita de ser descomprimido- name: Descomprime o software leantimeunarchive: src: "/tmp/leantime/Leantime-{{ versao_leantime }}.zip" dest: "/var/www/leantime" owner: www-datagroup: www-datamode: 0755remote_src: true # Após a descompressão, se o ficheiro configuration.php não existir, este necessita de ser # criado a partir do ficheiro configuration.sample.php # Fonte: https://docs.ansible.com/ansible/latest/collections/ansible/builtin/copy_module.html- name: Copia o ficheiro de configuração configuration.sample.phpansible.builtin.copy: src: /var/www/leantime/config/configuration.sample.php dest: /var/www/leantime/config/configuration.php owner: www-datagroup: www-data mode: '0755' remote_src: true [?12l[?25h[?25l remote_src: true # Fonte: https://docs.ansible.com/ansible/latest/collections/ansible/builtin/replace_module.html- name: Altera as variáveis dbuser, dbpassword e dbdatabase no ficheiro configuration.php utilizando o módulo replace.ansible.builtin.replace:path: /var/www/leantime/config/configuration.phpregexp: "{{ item.regexp }}" replace: "{{ item.line }}"with_items:- regexp: 'dbUser=""' line: 'dbUser="{{ login_leantime }}"'- regexp: 'dbDatabase=""'line: 'dbDatabase="leantime_database"' - regexp: 'dbPassword=""' line: 'dbPassword="{{ password_leantime }}"' [?12l[?25h[?25l[?12l[?25h[?25l[?12l[?25h[?25l[?12l[?25h[?25l[?12l[?25h[?25lmysql_user:name: "{{ login_leantime }}" password: "{{ password_leantime }}" priv: "leantime_database.*:ALL" host: localhoststate: present - name: "Faz o download do software leantime a partir do repositório git"get_url:url: https://github.com/Leantime/leantime/releases/download/{{ versao_leantime }}/Leantime-{{ versao_leantime }}.zipdest: /tmp/leantimemode: 0755 # O ficheiro Leantime-versao.zip necessita de ser descomprimido- name: Descomprime o software leantimeunarchive:src: "/tmp/leantime/Leantime-{{ versao_leantime }}.zip"dest: "/var/www/leantime"owner: www-datagroup: www-datamode: 0755remote_src: true # Após a descompressão, se o ficheiro configuration.php não existir, este necessita de ser # criado a partir do ficheiro configuration.sample.php # Fonte: https://docs.ansible.com/ansible/latest/collections/ansible/builtin/copy_module.html- name: Copia o ficheiro de configuração configuration.sample.phpansible.builtin.copy:src: /var/www/leantime/config/configuration.sample.phpdest: /var/www/leantime/config/configuration.phpowner: www-datagroup: www-datamode: '0755'remote_src: true [?12l[?25h[?25l178 # Fonte: https://docs.ansible.com/ansible/latest/collections/ansible/builtin/replace_module.html [?12l[?25h[?25l178 - name: Altera as variáveis dbuser, dbpassword e dbdatabase no ficheiro configuration.php utilizando o módulo replace. [?12l[?25h[?25l178 ansible.builtin.replace: [?12l[?25h[?25l178 path: /var/www/leantime/config/configuration.php [?12l[?25h[?25l178 regexp: "{{ item.regexp }}" [?12l[?25h[?25l178 replace: "{{ item.line }}" [?12l[?25h[?25l178 with_items: [?12l[?25h[?25l178 [?12l[?25h[?25l[?12l[?25h[?25lModificadoM[?12l[?25h[?25l [?12l[?25h[?25l [?12l[?25h[?25l [?12l[?25h[?25l [?12l[?25h[?25l [?12l[?25h[?25l [?12l[?25h[?25l [?12l[?25h[?25lf[?12l[?25h[?25lo[?12l[?25h[?25lr[?12l[?25h[?25lc[?12l[?25h[?25le[?12l[?25h[?25l:[?12l[?25h[?25l [?12l[?25h[?25lf[?12l[?25h[?25la[?12l[?25h[?25ll[?12l[?25h[?25ls[?12l[?25h[?25le[?12l[?25h[?25l M-D Formato DOSM-A AnexarB SegurançaC Cancelar M-M Formato MacM-P Prepor^T P/ ficheiros Nome do ficheiro onde escrever: tasks/tasks.yml [?12l[?25h[?25l [A escrever...] [148 linhas escritas]^O Gravar^W Procurar ^K Cortar txt ^J Justificar ^C Pos cursorU Desfazer M-A Marcar txtX Sair ^R Carregar^\ Substituir ^U Colar txt ^T Ortografia ^_ Ir p/ linha M-E Refazer M-6 Copiar txt [?12l[?25h[?25l [?12l[?25h[?25l[?12l[?25h[1049l [?1l>[?2004l]0;admlocal@devOps: ~/leantime_ansibleadmlocal@devOps:~/leantime_ansible$ molecule converge INFO default

scenario test matrix: dependency, create, prepare, converge INFO Performing prerun... INFO Using
.cache/roles/nunomourinho.leantime_ansible symlink to current repository in order to enable Ansible to find the role using
its expected full name. INFO Added
ANSIBLE_ROLES_PATH=~/.ansible/roles:/usr/share/ansible/roles:/etc/ansible/roles:./.cache/roles INFO Running default >
dependency WARNING Skipping, missing the requirements file. WARNING Skipping, missing the requirements file. INFO
Running default > create WARNING Skipping, instances already created. INFO Running default > prepare WARNING
Skipping, instances already prepared. INFO Running default > converge PLAY [Converge]
****
TASK [Gathering Facts]
*** ok:
[ubuntu-20.04] TASK [Include leantime_ansible]
*** TASK
[leantime_ansible : Atualiza a cache (equivalente a apt update)]
*** ok: [ubuntu-20.04] TASK [leantime_ansible : Atualiza o
sistema operativo] *** ok: [ubuntu-20.04]
TASK [leantime_ansible : Instalar as dependencias necessÃ¡ria ao programa leantime]
*** ok: [ubuntu-20.04] TASK [leantime_ansible : Instala o serviÃ§o
apache2 no arranque do sistema] *** ok: [ubuntu-20.04] TASK
[leantime_ansible : Rotina Auxiliar: Procura o caminho do ficheiro php.ini do servidor apache2]
********************************** ok: [ubuntu-20.04] TASK [leantime_ansible : Ativa vÃ¡rias opÃ§Ãµes no ficheiro
php.ini, utilizando o mÃ³dulo lineinfile.] *** ok: [ubuntu-20.04] => (item={'regexp':
'^file_uploads', 'line': 'file_uploads = 1'}) ok: [ubuntu-20.04] => (item={'regexp': '^upload_max_filesize', 'line':
'upload_max_filesize = 1G'}) ok: [ubuntu-20.04] => (item={'regexp': '^max_file_uploads', 'line': 'max_file_uploads = 20'})
ok: [ubuntu-20.04] => (item={'regexp': '^post_max_size', 'line': 'post_max_size = 2G'}) ok: [ubuntu-20.04] => (item=
{'regexp': '^memory_limit', 'line': 'memory_limit = 2G'}) ok: [ubuntu-20.04] => (item={'regexp': '^max_input_time', 'line':
'max_input_time = 3600'}) TASK [leantime_ansible : Cria a directoria temporÃ¡ria leantime e a directoria de apache
leantime] *** ok: [ubuntu-20.04] => (item={'path': '/tmp/leantime'}) ok: [ubuntu-
20.04] => (item={'path': '/var/www/leantime'}) TASK [leantime_ansible : Cria a base de dados de mysql para o leantime]
** ok: [ubuntu-20.04] TASK [leantime_ansible : Cria o
utilizador para a base de dados leantime] ** **[WARNING]:
Module did not set no_log for update_password** ok: [ubuntu-20.04] TASK [leantime_ansible : Faz o download do
software leantime a partir do repositÃ³rio git] *** ok: [ubuntu-20.04] TASK
[leantime_ansible : Descomprime o software leantime]
*** ok: [ubuntu-20.04] TASK [leantime_ansible :
Copia o ficheiro de configuraÃ§Ã£o configuration.sample.php] ** ok:
[ubuntu-20.04] TASK [leantime_ansible : Altera as variÃ¡veis dbuser, dbpassword e dbdatabase no ficheiro
configuration.php utilizando o mÃ³dulo replace.] *** ok: [ubuntu-20.04] => (item={'regexp': 'dbUser=""', 'line':
'dbUser="leantimeDBadmin"'}) ok: [ubuntu-20.04] => (item={'regexp': 'dbDatabase=""', 'line':
'dbDatabase="leantime_database"'}) ok: [ubuntu-20.04] => (item={'regexp': 'dbPassword=""', 'line':
'dbPassword="#S3gr3d0S3cr3t0#"'}) PLAY RECAP
****
ubuntu-20.04 : ok=14 changed=0 unreachable=0 failed=0 skipped=0 rescued=0 ignored=0]0;admlocal@devOps:
~/leantime_ansibleadmlocal@devOps:~/leantime_ansible$ molecule idempotence INFO default scenario test matrix:
idempotence INFO Performing prerun... INFO Using .cache/roles/nunomourinho.leantime_ansible symlink to current
repository in order to enable Ansible to find the role using its expected full name. INFO Added
ANSIBLE_ROLES_PATH=~/.ansible/roles:/usr/share/ansible/roles:/etc/ansible/roles:./.cache/roles INFO Running default >
idempotence PLAY [Converge]
****
TASK [Gathering Facts]
*** ok:
[ubuntu-20.04] TASK [Include leantime_ansible]
*** TASK
[leantime_ansible : Atualiza a cache (equivalente a apt update)]
*** ok: [ubuntu-20.04] TASK [leantime_ansible : Atualiza o
sistema operativo] *** ok: [ubuntu-20.04]
TASK [leantime_ansible : Instalar as dependencias necessÃ¡ria ao programa leantime]
*** ok: [ubuntu-20.04] TASK [leantime_ansible : Instala o serviÃ§o
apache2 no arranque do sistema] *** ok: [ubuntu-20.04] TASK
[leantime_ansible : Rotina Auxiliar: Procura o caminho do ficheiro php.ini do servidor apache2]
********************************** ok: [ubuntu-20.04] TASK [leantime_ansible : Ativa vÃ¡rias opÃ§Ãµes no ficheiro
php.ini, utilizando o mÃ³dulo lineinfile.] *** ok: [ubuntu-20.04] => (item={'regexp':
'^file_uploads', 'line': 'file_uploads = 1'}) ok: [ubuntu-20.04] => (item={'regexp': '^upload_max_filesize', 'line':
'upload_max_filesize = 1G'}) ok: [ubuntu-20.04] => (item={'regexp': '^max_file_uploads', 'line': 'max_file_uploads = 20'})
ok: [ubuntu-20.04] => (item={'regexp': '^post_max_size', 'line': 'post_max_size = 2G'}) ok: [ubuntu-20.04] => (item=
{'regexp': '^memory_limit', 'line': 'memory_limit = 2G'}) ok: [ubuntu-20.04] => (item={'regexp': '^max_input_time', 'line':
'max_input_time = 3600'}) TASK [leantime_ansible : Cria a directoria temporÃ¡ria leantime e a directoria de apache
leantime] *** ok: [ubuntu-20.04] => (item={'path': '/tmp/leantime'}) ok: [ubuntu-
20.04] => (item={'path': '/var/www/leantime'}) TASK [leantime_ansible : Cria a base de dados de mysql para o leantime]
** ok: [ubuntu-20.04] TASK [leantime_ansible : Cria o
utilizador para a base de dados leantime] ** **[WARNING]:
Module did not set no_log for update_password** ok: [ubuntu-20.04] TASK [leantime_ansible : Faz o download do
software leantime a partir do repositÃ³rio git] *** ok: [ubuntu-20.04] TASK
[leantime_ansible : Descomprime o software leantime]
*** ok: [ubuntu-20.04] TASK [leantime_ansible :
Copia o ficheiro de configuraÃ§Ã£o configuration.sample.php] ** ok:
[ubuntu-20.04] TASK [leantime_ansible : Altera as variÃ¡veis dbuser, dbpassword e dbdatabase no ficheiro

configuration.php utilizando o mÃ³dulo replace.] *** ok: [ubuntu-20.04] => (item={'regexp': 'dbUser=""', 'line': 'dbUser="leantimeDBadmin"'}) ok: [ubuntu-20.04] => (item={'regexp': 'dbDatabase=""', 'line': 'dbDatabase="leantime_database"'}) ok: [ubuntu-20.04] => (item={'regexp': 'dbPassword=""', 'line': 'dbPassword="#S3gr3d0S3cr3t0#"'}) PLAY RECAP
****
ubuntu-20.04 : ok=14 changed=0 unreachable=0 failed=0 skipped=0 rescued=0 ignored=0 INFO Idempotence completed successfully.]0;admlocal@devOps: ~/leantime_ansibleadmlocal@devOps:~/leantime_ansible$ exit exit