[?2004h[?1049h[?7h[?1h=[?1h=[?25l[A ler...][173 linhas lidas] GNU nano 4.8 tasks/tasks.yml

^G Ajuda ^O Gravar ^W Procurar ^K Cortar txt ^J Justificar ^C Pos cursor M-U Desfazer M-A Marcar txt
^X Sair ^R Carregar ^\ Substituir ^U Colar txt ^T Ortografia ^_ Ir p/ linha M-E RefazerM-6 Copiar txt

---- name: Atualiza a cache (equivalente a apt update)apt:update_cache: truecache_valid_time: 3600- name: "Atualiza o sistema operativo"apt:upgrade: safe- name: "Instalar as dependencias necessÃ¡ria ao programa leantime"apt:pkg:- mc- screen- git- apache2- mysql-server- php- php-mysql- php-ldap- php-cli- php-soap- php-json- graphviz- php-xml- php-gd- php-zip- libapache2-mod-php- php-dev- libmcrypt-dev- gcc- make- autoconf- libc-dev

[?12l[?25h[?25l - autoconf - libc-dev - pkg-config- pwgen- curl- unzip - zip - php-mbstring- expect- net-tools - python3-mysqldb - python3-apt- python3-pycurl

Fonte de inspiraçÃ£o: https://docs.ansible.com/ansible/latest/collections/ansible/builtin/service_module.html- name: "Instala o serviço apache2 no arranque do sistema"service:name: apache2state: startedenabled: true

Fonte: https://www.mydailytutorials.com/using-ansible-find-module-search-filesfolder- name: "Rotina Auxiliar: Procura o caminho do ficheiro php.ini do servidor apache2"find:paths: /etcpatterns: "php.ini"recurse: trueregister: caminho_php_ini

Fonte: https://docs.ansible.com/ansible/latest/collections/ansible/builtin/lineinfile_module.html- name: "Ativa vÃ¡rias opçÃµes no ficheiro php.ini, utilizando o mÃ³dulo lineinfile."ansible.builtin.lineinfile:path: "{{ caminho_php_ini.files[0].path }}"regexp: "{{ item.regexp }}"line: "{{ item.line }}"

[?12l[?25h[?25lregexp: "{{ item.regexp }}"line: "{{ item.line }}"with_items:regexp: "^file_uploads" line: "file_uploads = 1"regexp: "^upload_max_filesize" line: "upload_max_filesize = 1G"regexp: "^max_file_uploads" line: "max_file_uploads = 20"regexp: "^post_max_size" line: "post_max_size = 2G"regexp: "^memory_limit" line: "memory_limit = 2G"- regexp: "^max_input_time" line: "max_input_time = 3600"

Fonte: https://docs.ansible.com/ansible/2.7/modules/file_module.html- name: Cria a directoria temporÃ¡ria leantime e a directoria de apache leantimefile:path: "{{ item.path }}"state: directory mode: 0755 owner: www-data group: www-datawith_items:- path: "/tmp/leantime"- path: "/var/www/leantime"

Fonte: Ansible for DevOps - Server and configuration management for humans de Jeff Geerling, pÃ¡gina 98
- name: "Cria a base de dados de mysql para o leantime" mysql_db: "db=leantime_database state=present"
- name: "Cria o utilizador para a base de dados leantime"mysql_user:namlogin_leantime }}"

[?12l[?25h[?25lmysql_user:namlogin_leantime }}" password: "{{ password_leantime }}"priv: "leantime_database.*:ALL"host: localhoststate: present
- name: "Faz o download do software leantime a partir do repositÃ³rio git"get_url:url: https://github.com/Leantime/leantime/releases/download/{{ versao_leantime }}/Leantime-{{ versao_leantime }}.zipdest: /tmp/leantimemode: 0755

O ficheiro Leantime-versao.zip necessita de ser descomprimido- name: Descomprime o software leantimeunarchive: src: "/tmp/leantime/Leantime-{{ versao_leantime }}.zip" dest: "/var/www/leantime" owner: www-datagroup: www-datamode: 0755remote_src: true

ApÃ³s a descompressÃ£o, se o ficheiro configuration.php nÃ£o existir, este necessita de ser
criado a partir do ficheiro configuration.sample.php
Fonte: https://docs.ansible.com/ansible/latest/collections/ansible/builtin/copy_module.html- name: Copia o ficheiro de configuraçÃ£o configuration.sample.phpansible.builtin.copy: src: /var/www/leantime/config/configuration.sample.php dest: /var/www/leantime/config/configuration.php owner: www-datagroup: www-data mode: '0755' remote_src: trueforce: false

[?12l[?25h[?25l remote_src: trueforce: false

Fonte: https://docs.ansible.com/ansible/latest/collections/ansible/builtin/replace_module.html- name: Altera as variÃ¡veis dbuser, dbpassword e dbdatabase no ficheiro configuration.php utilizando o mÃ³dulo replace.ansible.builtin.replace:path: /var/www/leantime/config/configuration.php regexp: "{{ item.regexp }}" replace: "{{ item.line }}"with_items:- regexp: 'dbUser=""' line: 'dbUser="{{ login_leantime }}"'- regexp: 'dbDatabase=""' line: 'dbDatabase="leantime_database"' - regexp: 'dbPassword=""' line: 'dbPassword="{{ password_leantime }}"'

Fonte: https://docs.ansible.com/ansible/latest/collections/ansible/builtin/template_module.html- name: Copia o template do site para a pÃ¡sta /etc/apache2/sites-availableansible.builtin.template:src: leantime.template.j2dest: /etc/apache2/sites-available/leantime.confowner: root group: www-data mode: 0644 force: false

Fonte: https://docs.ansible.com/ansible/latest/collections/ansible/builtin/file_module.html- name: "Cria um link simbÃ³lico para o ficheiro leantime.conf na pasta /etc/apache/sites-enabled"ansible.builtin.file:src: /etc/apache2/sites-available/leantime.confdest: /etc/apache2/sites-enabled/leantime.confstate: link

Fonte: https://docs.ansible.com/ansible/latest/collections/ansible/builtin/file_module.html

[?12l[?25h[?25l # Fonte: https://docs.ansible.com/ansible/latest/collections/ansible/builtin/file_module.html- name: "Cria um link simbÃ³lico para o ficheiro leantime.conf na pasta /etc/apache/sites-enabled" ansible.builtin.file: path: /etc/apache2/sites-available/leantime.conf owner: rootgroup: www-datamode: '0777'

[?12l[?25h[?25l[?12l[?25h[?25l[?12l[?25h[?25l[?12l[?25h[?25l[?12l[?25h[?25l[?12l[?25h[?25l[?12l[?25h[?25l[?12l[?25h[?25l[?12l[?25h[?25l[?12l[?25h[?25l[?12l[?25h[?25l[?12l[?25h[?25l[?12l[?25h[?25l[?12l[?25h[?25l[?12l[?25h[?25l[?12l[?25h[?25lModificado

[?12l[?25h[?25l [?12l[?25h[?25l [?12l[?25h[?25l-[?12l[?25h[?25l

[?12l[?25h[?25ln[?12l[?25h[?25la[?12l[?25h[?25lm[?12l[?25h[?25le[?12l[?25h[?25l:[?12l[?25h[?25l [?12l[?25h[?25l"[?12l[?25h[?25lA[?12l[?25h[?25lp[?12l[?25h[?25la[?12l[?25h[?25lg[?12l[?25h[?25la[?12l[?25h[?25l [?12l[?25h[?25lo[?12l[?25h[?25l [?12l[?25h[?25ll[?12l[?25h[?25li[?12l[?25h[?25ln[?12l[?25h[?25lk[?12l[?25h[?25l [?12l[?25h[?25l0[?12l[?25h[?25l0[?12l[?25h[?25l0[?12l[?25h[?25l-[?12l[?25h[?25ld[?12l[?25h[?25le[?12l[?25h[?25lf[?12l[?25h[?25la[?12l[?25h[?25lu[?12l[?25h[?25ll[?12l[?25h[?25lt[?12l[?25h[?25l.[?12l[?25h[?25lc[?12l[?25h[?25lo[?12l[?25h[?25ln[?12l[?25h[?25lf[?12l[?25h[?25l[?12l[?25h[?25ln[?12l[?25h[?25la[?12l[?25h[?25l [?12l[?25h[?25lp[?12l[?25h[?25la[?12l[?25h[?25ls[?12l[?25h[?25lt[?12l[?25h[?25la[?12l[?25h[?25l [?12l[?25h[?25ls[?12l[?25h[?25li[?12l[?25h[?25lt[?12l[?25h[?25le[?12l[?25h[?25ls[?12l[?25h[?25l-[?12l[?25h[?25le[?12l[?25h[?25ln[?12l[?25h[?25la[?12l[?25h[?25lb[?12l[?25h[?25ll[?12l[?25h[?25le[?12l[?25h[?25ld[?12l[?25h[?25l [?12l[?25h[?25ld[?12l[?25h[?25lo[?12l[?25h[?25l [?12l[?25h[?25la[?12l[?25h[?25lp[?12l[?25h[?25la[?12l[?25h[?25lc[?12l[?25h[?25lh[?12l[?25h[?25le[?12l[?25h[?25l2[?12l[?25h[?25l"[?12l[?25h[?25l

[?12l[?25h[?25l [?12l[?25h[?25l [?12l[?25h[?25l [?12l[?25h[?25l [?12l[?25h[?25la[?12l[?25h[?25ln[?12l[?25h[?25ls[?12l[?25h[?25li[?12l[?25h[?25lb[?12l[?25h[?25ll[?12l[?25h[?25le[?12l[?25h[?25l.[?12l[?25h[?25lb[?12l[?25h[?25lu[?12l[?25h[?25li[?12l[?25h[?25ll[?12l[?25h[?25lt[?12l[?25h[?25li[?12l[?25h[?25ln[?12l[?25h[?25l.[?12l[?25h[?25lf[?12l[?25h[?25li[?12l[?25h[?25ll[?12l[?25h[?25le[?12l[?25h[?25l:[?12l[?25h[?25l

[?12l[?25h[?25l [?12l[?25h[?25l [?12l[?25h[?25l [?12l[?25h[?25l [?12l[?25h[?25l [?12l[?25h[?25l [?12l[?25h[?25lp[?12l[?
25h[?25la[?12l[?25h[?25lt[?12l[?25h[?25lh[?12l[?25h[?25l:[?12l[?25h[?25l [?12l[?25h[?25l/[?12l[?25h[?25le[?12l[?25h[?
25lt[?12l[?25h[?25lc[?12l[?25h[?25l/[?12l[?25h[?25la[?12l[?25h[?25lp[?12l[?25h[?25la[?12l[?25h[?25lc[?12l[?25h[?25lh[?
12l[?25h[?25le[?12l[?25h[?25l2[?12l[?25h[?25l/[?12l[?25h[?25ls[?12l[?25h[?25li[?12l[?25h[?25lt[?12l[?25h[?25le[?12l[?
25h[?25ls[?12l[?25h[?25l-[?12l[?25h[?25le[?12l[?25h[?25ln[?12l[?25h[?25la[?12l[?25h[?25lb[?12l[?25h[?25ll[?12l[?25h[?
25le[?12l[?25h[?25ld[?12l[?25h[?25l/[?12l[?25h[?25l0[?12l[?25h[?25l0[?12l[?25h[?25l0[?12l[?25h[?25l-[?12l[?25h[?25ld[?
12l[?25h[?25le[?12l[?25h[?25lf[?12l[?25h[?25la[?12l[?25h[?25lu[?12l[?25h[?25ll[?12l[?25h[?25lt[?12l[?25h[?25l.[?12l[?
25h[?25lc[?12l[?25h[?25lo[?12l[?25h[?25ln[?12l[?25h[?25lf[?12l[?25h[?25l

[?12l[?25h[?25l [?12l[?25h[?25l [?12l[?25h[?25l [?12l[?25h[?25l [?12l[?25h[?25l [?12l[?25h[?25l [?12l[?25h[?25ls[?12l[?
25h[?25lt[?12l[?25h[?25la[?12l[?25h[?25lt[?12l[?25h[?25le[?12l[?25h[?25l:[?12l[?25h[?25l [?12l[?25h[?25lab[?12l[?25h[?
25ls[?12l[?25h[?25le[?12l[?25h[?25ln[?12l[?25h[?25lt[?12l[?25h[?25l

[?12l[?25h[?25l M-D Formato DOSM-A AnexarB SegurançaC Cancelar M-M Formato MacM-P Prepor^T P/ ficheiros
Nome do ficheiro onde escrever: tasks/tasks.yml [?12l[?25h[?25l [A escrever...] [178 linhas escritas]^O Gravar^W
Procurar ^K Cortar txt ^J Justificar ^C Pos cursorU Desfazer M-A Marcar txtX Sair ^R Carregar^\ Substituir ^U Colar txt
^T Ortografia ^_ Ir p/ linha M-E Refazer M-6 Copiar txt
[?12l[?25h[?25l[?12l[?25h[?1049l
[?1l>[?2004l]0;admlocal@devOps: ~/leantime_ansibleadmlocal@devOps:~/leantime_ansible$ molecule lint
INFO default scenario test matrix: dependency, lint
INFO Performing prerun...
INFO Using .cache/roles/nunomourinho.leantime_ansible symlink to current repository in order to enable Ansible to find
the role using its expected full name.
INFO Added ANSIBLE_ROLES_PATH=~/.ansible/roles:/usr/share/ansible/roles:/etc/ansible/roles:./.cache/roles
INFO Running default > dependency
WARNING Skipping, missing the requirements file.
WARNING Skipping, missing the requirements file.
INFO Running default > lint
COMMAND: set -e
yamllint .
ansible-lint

./tasks/tasks.yml
175:3 error syntax error: expected '<document start>', but found '<block sequence start>' (syntax)

CRITICAL Lint failed with error code 1
]0;admlocal@devOps: ~/leantime_ansibleadmlocal@devOps:~/leantime_ansible$ molecule lintnano tasks/tasks.yml
[?2004h[?1049h[?7h[?1h=[?1h=[?25l[A ler...][178 linhas lidas] GNU nano 4.8 tasks/tasks.yml
^G Ajuda^O Gravar^W Procurar^K Cortar txt ^J Justificar ^C Pos cursor M-U Desfazer M-A Marcar txt
^X Sair^R Carregar^\ Substituir ^U Colar txt ^T Ortografia ^_ Ir p/ linha M-E RefazerM-6 Copiar txt
---- name: Atualiza a cache (equivalente a apt update)apt:update_cache: truecache_valid_time: 3600- name: "Atualiza o
sistema operativo"apt:upgrade: safe- name: "Instalar as dependencias necessária ao programa leantime"apt:pkg:- mc-
screen- git- apache2- mysql-server- php- php-mysql- php-ldap- php-cli- php-soap- php-json- graphviz- php-xml- php-gd- php-
zip- libapache2-mod-php- php-dev- libmcrypt-dev- gcc- make- autoconf- libc-dev
[?12l[?25h[?25l - autoconf - libc-dev - pkg-config- pwgen- curl- unzip - zip - php-mbstring- expect- net-tools - python3-
mysqldb - python3-apt- python3-pycurl
Fonte de inspiração: https://docs.ansible.com/ansible/latest/collections/ansible/builtin/service_module.html- name:
"Instala o serviço apache2 no arranque do sistema"service:name: apache2state: startedenabled: true
Fonte: https://www.mydailytutorials.com/using-ansible-find-module-search-filesfolder- name: "Rotina Auxiliar: Procura o
caminho do ficheiro php.ini do servidor apache2"find:paths: /etcpatterns: "php.ini"recurse: trueregister: caminho_php_ini
# Fonte: https://docs.ansible.com/ansible/latest/collections/ansible/builtin/lineinfile_module.html- name: "Ativa várias
opções no ficheiro php.ini, utilizando o módulo lineinfile."ansible.builtin.lineinfile:path: "{{
caminho_php_ini.files[0].path }}"regexp: "{{ item.regexp }}"line: "{{ item.line }}"
[?12l[?25h[?25lregexp: "{{ item.regexp }}"line: "{{ item.line }}"with_items:regexp: "^file_uploads" line: "file_uploads =
1"regexp: "^upload_max_filesize" line: "upload_max_filesize = 1G"regexp: "^max_file_uploads" line: "max_file_uploads =
20"regexp: "^post_max_size" line: "post_max_size = 2G"regexp: "^memory_limit" line: "memory_limit = 2G"- regexp:
"^max_input_time" line: "max_input_time = 3600"
Fonte: https://docs.ansible.com/ansible/2.7/modules/file_module.html- name: Cria a directoria temporária leantime e a
directoria de apache leantimefile:path: "{{ item.path }}"state: directory mode: 0755 owner: www-data group: www-
datawith_items:- path: "/tmp/leantime"- path: "/var/www/leantime"
Fonte: Ansible for DevOps - Server and configuration management for humans de Jeff Geerling, página 98
- name: "Cria a base de dados de mysql para o leantime" mysql_db: "db=leantime_database state=present"
- name: "Cria o utilizador para a base de dados leantime"mysql_user:namlogin_leantime }}"
[?12l[?25h[?25lmysql_user:namlogin_leantime }}" password: "{{ password_leantime }}"priv:
"leantime_database.*:ALL"host: localhoststate: present
- name: "Faz o download do software leantime a partir do repositório git"get_url:url:
https://github.com/Leantime/leantime/releases/download/{{ versao_leantime }}/Leantime-{{ versao_leantime }}.zipdest:
/tmp/leantimemode: 0755
O ficheiro Leantime-versao.zip necessita de ser descomprimido- name: Descomprime o software leantimeunarchive: src:
"/tmp/leantime/Leantime-{{ versao_leantime }}.zip" dest: "/var/www/leantime" owner: www-datagroup: www-datamode:
0755remote_src: true
Após a descompressão, se o ficheiro configuration.php não existir, este necessita de ser
criado a partir do ficheiro configuration.sample.php
Fonte: https://docs.ansible.com/ansible/latest/collections/ansible/builtin/copy_module.html- name: Copia o ficheiro de
configuração configuration.sample.phpansible.builtin.copy: src: /var/www/leantime/config/configuration.sample.php
dest: /var/www/leantime/config/configuration.php owner: www-datagroup: www-data mode: '0755' remote_src: trueforce:
false
[?12l[?25h[?25l remote_src: trueforce: false
Fonte: https://docs.ansible.com/ansible/latest/collections/ansible/builtin/replace_module.html- name: Altera as variáveis

dbuser, dbpassword e dbdatabase no ficheiro configuration.php utilizando o módulo replace.ansible.builtin.replace:path: /var/www/leantime/config/configuration.php regexp: "{{ item.regexp }}" replace: "{{ item.line }}"with_items:- regexp: 'dbUser=""' line: 'dbUser="{{ login_leantime }}"'- regexp: 'dbDatabase=""' line: 'dbDatabase="leantime_database"' - regexp: 'dbPassword=""' line: 'dbPassword="{{ password_leantime }}"'
Fonte: https://docs.ansible.com/ansible/latest/collections/ansible/builtin/template_module.html- name: Copia o template do site para a pásta /etc/apache2/sites-availableansible.builtin.template:src: leantime.template.j2dest: /etc/apache2/sites-available/leantime.confowner: root group: www-data mode: 0644 force: false
Fonte: https://docs.ansible.com/ansible/latest/collections/ansible/builtin/file_module.html- name: "Cria um link simbólico para o ficheiro leantime.conf na pasta /etc/apache/sites-enabled"ansible.builtin.file:src: /etc/apache2/sites-available/leantime.confdest: /etc/apache2/sites-enabled/leantime.confstate: link
Fonte: https://docs.ansible.com/ansible/latest/collections/ansible/builtin/file_module.html
[?12l[?25h[?25l # Fonte: https://docs.ansible.com/ansible/latest/collections/ansible/builtin/file_module.html- name: "Cria um link simbólico para o ficheiro leantime.conf na pasta /etc/apache/sites-enabled" ansible.builtin.file: path: /etc/apache2/sites-available/leantime.conf owner: rootgroup: www-datamode: '0777'
- name: "Apaga o link 000-default.conf na pasta sites-enabled do apache2"ansible.builtin.file:path: /etc/apache2/sites-enabled/000-default.confstate: absent
[?12l[?25h[?25lModificado
- name: "Apaga o link 000-default.conf na pasta sites-enabled do apache2"
[?12l[?25h[?25l[?12l[?25h[?25l ansible.builtin.file:
[?12l[?25h[?25l[?12l[?25h[?25l
path: /etc/apache2/sites-enabled/000-default.conf
[?12l[?25h[?25l[?12l[?25h[?25l
state: absent
[?12l[?25h[?25l
[?12l[?25h[?25l78
M[?12l[?25h[?25l
path: /etc/apache2/sites-enabled/000-default.conf[?12l[?25h[?25l
[?12l[?25h[?25l
path: /etc/apache2/sites-enabled/000-default.conf[?12l[?25h[?25l
[?12l[?25h[?25l[?12l[?25h[?25l M-D Formato DOSM-A AnexarB SegurançaC Cancelar M-M Formato MacM-P Prepor^T P/ ficheiros
Nome do ficheiro onde escrever: tasks/tasks.yml [?12l[?25h[?25l [A escrever...] [178 linhas escritas]^O Gravar^W Procurar ^K Cortar txt ^J Justificar ^C Pos cursorU Desfazer M-A Marcar txtX Sair ^R Carregar^\ Substituir ^U Colar txt ^T Ortografia ^_ Ir p/ linha M-E Refazer M-6 Copiar txt
[?12l[?25h[?25l[?12l[?25h[?1049l
[?1l>[?2004l]0;admlocal@devOps: ~/leantime_ansibleadmlocal@devOps:~/leantime_ansible$ nano tasks/tasks.yml
molecule lint
INFO default scenario test matrix: dependency, lint
INFO Performing prerun...
INFO Using .cache/roles/nunomourinho.leantime_ansible symlink to current repository in order to enable Ansible to find the role using its expected full name.
INFO Added ANSIBLE_ROLES_PATH=~/.ansible/roles:/usr/share/ansible/roles:/etc/ansible/roles:./.cache/roles
INFO Running default > dependency
WARNING Skipping, missing the requirements file.
WARNING Skipping, missing the requirements file.
INFO Running default > lint
COMMAND: set -e
yamllint .
ansible-lint

Loading custom .yamllint config file, this extends our internal yamllint config.
]0;admlocal@devOps: ~/leantime_ansibleadmlocal@devOps:~/leantime_ansible$ molecule deploy
Usage: molecule [OPTIONS] COMMAND [ARGS]...
Try "molecule --help" for help.

Error: No such command "deploy".
]0;admlocal@devOps: ~/leantime_ansibleadmlocal@devOps:~/leantime_ansible$ molecule deployconverge
INFO default scenario test matrix: dependency, create, prepare, converge
INFO Performing prerun...
INFO Using .cache/roles/nunomourinho.leantime_ansible symlink to current repository in order to enable Ansible to find the role using its expected full name.
INFO Added ANSIBLE_ROLES_PATH=~/.ansible/roles:/usr/share/ansible/roles:/etc/ansible/roles:./.cache/roles
INFO Running default > dependency
WARNING Skipping, missing the requirements file.
WARNING Skipping, missing the requirements file.
INFO Running default > create
WARNING Skipping, instances already created.
INFO Running default > prepare
WARNING Skipping, instances already prepared.
INFO Running default > converge

PLAY [Converge]
****

TASK [Gathering Facts]
****
ok: [ubuntu-20.04]

```
TASK [Include leantime_ansible]
********************************************************************************

TASK [leantime_ansible : Atualiza a cache (equivalente a apt update)]
********************************************************
ok: [ubuntu-20.04]

TASK [leantime_ansible : Atualiza o sistema operativo]
**********************************************************************
ok: [ubuntu-20.04]

TASK [leantime_ansible : Instalar as dependencias necessÃ¡ria ao programa leantime]
***************************************************
ok: [ubuntu-20.04]

TASK [leantime_ansible : Instala o serviÃ§o apache2 no arranque do sistema]
*********************************************************
ok: [ubuntu-20.04]

TASK [leantime_ansible : Rotina Auxiliar: Procura o caminho do ficheiro php.ini do servidor apache2]
***********************************
ok: [ubuntu-20.04]

TASK [leantime_ansible : Ativa vÃ¡rias opÃ§Ãµes no ficheiro php.ini, utilizando o mÃ³dulo lineinfile.]
**************************************
ok: [ubuntu-20.04] => (item={'regexp': '^file_uploads', 'line': 'file_uploads = 1'})
ok: [ubuntu-20.04] => (item={'regexp': '^upload_max_filesize', 'line': 'upload_max_filesize = 1G'})
ok: [ubuntu-20.04] => (item={'regexp': '^max_file_uploads', 'line': 'max_file_uploads = 20'})
ok: [ubuntu-20.04] => (item={'regexp': '^post_max_size', 'line': 'post_max_size = 2G'})
ok: [ubuntu-20.04] => (item={'regexp': '^memory_limit', 'line': 'memory_limit = 2G'})
ok: [ubuntu-20.04] => (item={'regexp': '^max_input_time', 'line': 'max_input_time = 3600'})

TASK [leantime_ansible : Cria a directoria temporÃ¡ria leantime e a directoria de apache leantime]
**************************************
ok: [ubuntu-20.04] => (item={'path': '/tmp/leantime'})
ok: [ubuntu-20.04] => (item={'path': '/var/www/leantime'})

TASK [leantime_ansible : Cria a base de dados de mysql para o leantime]
*********************************************************
ok: [ubuntu-20.04]

TASK [leantime_ansible : Cria o utilizador para a base de dados leantime]
*********************************************************
[WARNING]: Module did not set no_log for update_password
ok: [ubuntu-20.04]

TASK [leantime_ansible : Faz o download do software leantime a partir do repositÃ³rio git]
********************************************
ok: [ubuntu-20.04]

TASK [leantime_ansible : Descomprime o software leantime]
*****************************************************************
ok: [ubuntu-20.04]

TASK [leantime_ansible : Copia o ficheiro de configuraÃ§Ã£o configuration.sample.php]
*****************************************************
ok: [ubuntu-20.04]

TASK [leantime_ansible : Altera as variÃ¡veis dbuser, dbpassword e dbdatabase no ficheiro configuration.php utilizando o
mÃ³dulo replace.] ***
ok: [ubuntu-20.04] => (item={'regexp': 'dbUser=""', 'line': 'dbUser="leantimeDBadmin"'})
ok: [ubuntu-20.04] => (item={'regexp': 'dbDatabase=""', 'line': 'dbDatabase="leantime_database"'})
ok: [ubuntu-20.04] => (item={'regexp': 'dbPassword=""', 'line': 'dbPassword="#S3gr3d0S3cr3t0#"'})

TASK [leantime_ansible : Copia o template do site para a pÃ¡sta /etc/apache2/sites-available]
***********************************************
ok: [ubuntu-20.04]

TASK [leantime_ansible : Cria um link simbÃ³lico para o ficheiro leantime.conf na pasta /etc/apache/sites-enabled]
**********************
ok: [ubuntu-20.04]

TASK [leantime_ansible : Cria um link simbÃ³lico para o ficheiro leantime.conf na pasta /etc/apache/sites-enabled]
**********************
ok: [ubuntu-20.04]
```

TASK [leantime_ansible : Apaga o link 000-default.conf na pasta sites-enabled do apache2]
****
changed: [ubuntu-20.04]

PLAY RECAP
****
ubuntu-20.04 : ok=18 changed=1 unreachable=0 failed=0 skipped=0 rescued=0 ignored=0

]0;admlocal@devOps: ~/leantime_ansibleadmlocal@devOps:~/leantime_ansible$ molecule idempotence
INFO default scenario test matrix: idempotence
INFO Performing prerun...
INFO Using .cache/roles/nunomourinho.leantime_ansible symlink to current repository in order to enable Ansible to find the role using its expected full name.
INFO Added ANSIBLE_ROLES_PATH=~/.ansible/roles:/usr/share/ansible/roles:/etc/ansible/roles:./.cache/roles
INFO Running default > idempotence

PLAY [Converge]
****

TASK [Gathering Facts]
****
ok: [ubuntu-20.04]

TASK [Include leantime_ansible]
****
ok: [ubuntu-20.04]

TASK [leantime_ansible : Atualiza a cache (equivalente a apt update)]
****
ok: [ubuntu-20.04]

TASK [leantime_ansible : Atualiza o sistema operativo]
****
ok: [ubuntu-20.04]

TASK [leantime_ansible : Instalar as dependencias necessária ao programa leantime]
****
ok: [ubuntu-20.04]

TASK [leantime_ansible : Instala o serviço apache2 no arranque do sistema]
****
ok: [ubuntu-20.04]

TASK [leantime_ansible : Rotina Auxiliar: Procura o caminho do ficheiro php.ini do servidor apache2]
****
ok: [ubuntu-20.04]

TASK [leantime_ansible : Ativa várias opções no ficheiro php.ini, utilizando o módulo lineinfile.]
****
ok: [ubuntu-20.04] => (item={'regexp': '^file_uploads', 'line': 'file_uploads = 1'})
ok: [ubuntu-20.04] => (item={'regexp': '^upload_max_filesize', 'line': 'upload_max_filesize = 1G'})
ok: [ubuntu-20.04] => (item={'regexp': '^max_file_uploads', 'line': 'max_file_uploads = 20'})
ok: [ubuntu-20.04] => (item={'regexp': '^post_max_size', 'line': 'post_max_size = 2G'})
ok: [ubuntu-20.04] => (item={'regexp': '^memory_limit', 'line': 'memory_limit = 2G'})
ok: [ubuntu-20.04] => (item={'regexp': '^max_input_time', 'line': 'max_input_time = 3600'})

TASK [leantime_ansible : Cria a directoria temporária leantime e a directoria de apache leantime]
****
ok: [ubuntu-20.04] => (item={'path': '/tmp/leantime'})
ok: [ubuntu-20.04] => (item={'path': '/var/www/leantime'})

TASK [leantime_ansible : Cria a base de dados de mysql para o leantime]
****
ok: [ubuntu-20.04]

TASK [leantime_ansible : Cria o utilizador para a base de dados leantime]
****
[WARNING]: Module did not set no_log for update_password
ok: [ubuntu-20.04]

TASK [leantime_ansible : Faz o download do software leantime a partir do repositório git]
****
ok: [ubuntu-20.04]

TASK [leantime_ansible : Descomprime o software leantime]
****
ok: [ubuntu-20.04]

TASK [leantime_ansible : Copia o ficheiro de configuração configuration.sample.php]
****
ok: [ubuntu-20.04]

TASK [leantime_ansible : Altera as variáveis dbuser, dbpassword e dbdatabase no ficheiro configuration.php utilizando o módulo replace.] ***
ok: [ubuntu-20.04] => (item={'regexp': 'dbUser=""', 'line': 'dbUser="leantimeDBadmin"'})
ok: [ubuntu-20.04] => (item={'regexp': 'dbDatabase=""', 'line': 'dbDatabase="leantime_database"'})
ok: [ubuntu-20.04] => (item={'regexp': 'dbPassword=""', 'line': 'dbPassword="#S3gr3d0S3cr3t0#"'})

TASK [leantime_ansible : Copia o template do site para a pásta /etc/apache2/sites-available]
****
ok: [ubuntu-20.04]

TASK [leantime_ansible : Cria um link simbólico para o ficheiro leantime.conf na pasta /etc/apache/sites-enabled]
****
ok: [ubuntu-20.04]

TASK [leantime_ansible : Cria um link simbólico para o ficheiro leantime.conf na pasta /etc/apache/sites-enabled]
****
ok: [ubuntu-20.04]

TASK [leantime_ansible : Apaga o link 000-default.conf na pasta sites-enabled do apache2]
****
ok: [ubuntu-20.04]

PLAY RECAP
****
ubuntu-20.04 : ok=18 changed=0 unreachable=0 failed=0 skipped=0 rescued=0 ignored=0

INFO Idempotence completed successfully.
]0;admlocal@devOps: ~/leantime_ansibleadmlocal@devOps:~/leantime_ansible$ molecule verify
INFO default scenario test matrix: verify
INFO Performing prerun...
INFO Using .cache/roles/nunomourinho.leantime_ansible symlink to current repository in order to enable Ansible to find the role using its expected full name.
INFO Added ANSIBLE_ROLES_PATH=~/.ansible/roles:/usr/share/ansible/roles:/etc/ansible/roles:./.cache/roles
INFO Running default > verify
INFO Running Ansible Verifier

PLAY [Infraestrutura conduzida por testes]
****
TASK [Variáveis]
****
ok: [ubuntu-20.04]

TASK [Simulação: Atualizar a cache do sistema]
****
ok: [ubuntu-20.04]

TASK [teste: a cache encontra-se actualizada?]
****
ok: [ubuntu-20.04] => {
"changed": false,
"msg": "SUCESSO: A cache está atualizada"
}

TASK [Atualizar o sistema operativo (equivalente a apt upgrade)]
****
ok: [ubuntu-20.04]

TASK [teste: o sistema operativo encontra-se atualizado?]
****
ok: [ubuntu-20.04] => {
"changed": false,
"msg": "SUCESSO: O sistema operativo está atualizado"
}

TASK [Teste: a cache encontra-se atualizada?]
****
ok: [ubuntu-20.04] => {
"changed": false,
"msg": "SUCESSO: A cache está atualizada"
}

TASK [Simulação: testa se as aplicações dependencia do software leantime se encontram instaladas]
****
ok: [ubuntu-20.04]

TASK [Teste: as dependencias encontra-se instaladas?]
****
ok: [ubuntu-20.04] => {
"changed": false,
"msg": "SUCESSO: As dependencias estavam instaladas"
}

TASK [Simulação: Testar se o serviço apache2 se encontra instalado, iniciado e ativo no arranque]
****
ok: [ubuntu-20.04]

TASK [Teste: O serviço apache2 encontra-se ativo no arranque no sistema, e está iniciado?]
****
ok: [ubuntu-20.04] => {
"changed": false,
"msg": "SUCESSO: O serviço apache2 está correctamente instalado e inicia com o arranque do sistema"
}

TASK [Rotina Auxiliar> Procura o caminho do ficheiro php.ini do servidor apache2]
****
ok: [ubuntu-20.04]

TASK [Simulação: Ativa a opção file_uploads no ficheiro php.ini, utilizando o módulo lineinfile.]
****
ok: [ubuntu-20.04] => (item={'regexp': '^file_uploads', 'line': 'file_uploads = 1'})
ok: [ubuntu-20.04] => (item={'regexp': '^upload_max_filesize', 'line': 'upload_max_filesize = 1G'})
ok: [ubuntu-20.04] => (item={'regexp': '^max_file_uploads', 'line': 'max_file_uploads = 20'})
ok: [ubuntu-20.04] => (item={'regexp': '^post_max_size', 'line': 'post_max_size = 2G'})
ok: [ubuntu-20.04] => (item={'regexp': '^memory_limit', 'line': 'memory_limit = 2G'})
ok: [ubuntu-20.04] => (item={'regexp': '^max_input_time', 'line': 'max_input_time = 3600'})

TASK [Teste: As linhas do php.ini encontram-se alteradas ?]
****
ok: [ubuntu-20.04] => {
"changed": false,
"msg": "SUCESSO: O ficheiro php.ini foi alterado com sucesso"
}

TASK [Simulação: Obtem informação sobre a pastas /var/www/leantime]
****
ok: [ubuntu-20.04]

TASK [Teste: A pasta /var/www/leantime existe e tem as permissões certas?]
****
ok: [ubuntu-20.04] => {
"changed": false,
"msg": "SUCESSO: Permissões correctas no site leantime"
}

TASK [Simulação: Verifica se é necessário criar a base de dados leantime_database]
****
ok: [ubuntu-20.04]

TASK [Teste: A base de dados leantime_database existe ?]
****
ok: [ubuntu-20.04] => {
"changed": false,
"msg": "SUCESSO: A base de dados leantime_database já se encontra criada"
}

TASK [Simulação e Teste: Verifica se o endereço git para a versão de leantime existe]
****
ok: [ubuntu-20.04]

TASK [Simulação: Obtem informação sobre o ficheiro /var/www/leantime/config/configuration.php]
****
ok: [ubuntu-20.04]

TASK [Teste: O ficheiro /var/www/leantime/config/configuration.php existe e tem as permissões certas?]
****
ok: [ubuntu-20.04] => {
"changed": false,

```
"msg": "SUCESSO: Permissões correctas e ficheiro configuration.php existente"
}

TASK [Simulação: Testa se o dbuser foi alterado no ficheiro configuration.php utilizando o módulo replace.]
*************************
ok: [ubuntu-20.04]

TASK [Teste: O dbUser foi alterado?]
****************************************************************************************
ok: [ubuntu-20.04] => {
"changed": false,
"msg": "SUCESSO: O dbUser foi alterado no ficheiro configuration.php"
}

TASK [Simulação: Testa se o dbDatabase foi alterado no ficheiro configuration.php utilizando o módulo replace.]
*************************
ok: [ubuntu-20.04]

TASK [Teste: a variável dbDatabase foi alterada?]
*********************************************************************************
ok: [ubuntu-20.04] => {
"changed": false,
"msg": "SUCESSO: O dbDatabase foi alterado no ficheiro configuration.php"
}

TASK [Simulação: Testa se o dbPassword foi alterado no ficheiro configuration.php utilizando o módulo replace.]
*************************
ok: [ubuntu-20.04]

TASK [Teste: O dbPassword foi alterado?]
***********************************************************************************
ok: [ubuntu-20.04] => {
"changed": false,
"msg": "SUCESSO: O dbPassword foi alterado no ficheiro configuration.php"
}

TASK [Simulação: Obtem informação sobre o ficheiro /etc/apache2/sites-available/leantime.conf]
*******************************************
ok: [ubuntu-20.04]

TASK [Teste: O ficheiro /etc/apache2/sites-available/leantime.conf existe e tem as permissões certas?]
*********************************
ok: [ubuntu-20.04] => {
"changed": false,
"msg": "SUCESSO: Permissões correctas"
}

TASK [Simulação: Obtem informação sobre o ficheiro /etc/apache2/sites-enabled/leantime.conf]
*********************************************
ok: [ubuntu-20.04]

TASK [Teste: O ficheiro /etc/apache2/sites-enabled/leantime.conf existe e tem as permissões certas?]
**************************************
ok: [ubuntu-20.04] => {
"changed": false,
"msg": "SUCESSO: Permissões correctas"
}

TASK [Simulação: Obtem informação sobre o ficheiro /etc/apache2/sites-enabled/000-default.conf]
*********************************************
ok: [ubuntu-20.04]

TASK [Teste: O ficheiro /etc/apache2/sites-enabled/000-default.conf NÃO existe?]
******************************************************
ok: [ubuntu-20.04] => {
"changed": false,
"msg": "All assertions passed"
}

PLAY RECAP
*********************************************************************************************************************
ubuntu-20.04 : ok=32 changed=0 unreachable=0 failed=0 skipped=0 rescued=0 ignored=0

INFO Verifier completed successfully.
]0;admlocal@devOps: ~/leantime_ansibleadmlocal@devOps:~/leantime_ansible$ exit
exit
```