

Configuration and Management of Networks


Pedro Amaral

Configuration and Management of Networks

Access Control Lists

Sales 172.16.40.0/24

Sales cannot have access to finance



```
nv set acl BLOCK-SALES type ipv4
```

```
nv set acl BLOCK-SALES rule 10 match ip source-ip 172.16.40.0/24
```

```
nv set acl BLOCK-SALES rule 10 action deny
```

```
nv set acl BLOCK-SALES rule 20 action permit
```

```
nv set interface swp1 acl BLOCK-SALES outbound
```

```
Lab_A(config)#int e1
```

```
Lab_A(config-if)#ip access-group 10 out
```


```
Lab_A#config t
```

```
Lab_A(config)#access-list 10 deny 172.16.40.0 0.0.0.255
```

```
Lab_A(config)#access-list 10 permit any
```

Configuration and Management of Networks

Access Control Lists



Blocks accounting in access to HR server

```
Lab_B#config t
Lab_B(config)#access-list 10 deny 192.168.10.128 0.0.0.31
Lab_B(config)#access-list 10 permit any
Lab_B(config)#interface Ethernet 0
Lab_B(config-if)#ip access-group 10 out
```

```
nv set acl BLOCK-ACCOUNTING type ipv4
nv set acl BLOCK-ACCOUNTING rule 10 match ip source-ip 192.168.10.128/27
nv set acl BLOCK-ACCOUNTING rule 10 action deny
nv set acl BLOCK-ACCOUNTING rule 20 action permit

nv set interface swp1 acl BLOCK-ACCOUNTING outbound
```

Configuration and Management of Networks

Access Control Lists

Only host 172.16.10.3 can ssh to router

```
# Create the ACL
```

```
nv set acl SSH-ACCESS type ipv4
```

```
# Permit SSH (TCP port 22) from specific host only (rule 10)
```

```
nv set acl SSH-ACCESS rule 10 match ip protocol tcp
```

```
nv set acl SSH-ACCESS rule 10 match ip source-ip 172.16.10.3/32
```

```
nv set acl SSH-ACCESS rule 10 match ip tcp dest-port 22
```

```
nv set acl SSH-ACCESS rule 10 action permit
```

```
# Deny all other SSH attempts (rule 20)
```

```
nv set acl SSH-ACCESS rule 20 match ip protocol tcp
```

```
nv set acl SSH-ACCESS rule 20 match ip tcp dest-port 22
```

```
nv set acl SSH-ACCESS rule 20 action deny
```

```
# Apply to control plane
```

```
nv set system control-plane acl SSH-ACCESS inbound
```

```
nv config apply
```

Configuration and Management of Networks

IP Prefix Lists

Why Use Prefix Lists Instead of ACLs?

Prefix lists are specifically designed **for filtering routing updates** and offer significant advantages over traditional ACLs :

- Better performance - Optimized for route filtering
- User-friendly syntax - More intuitive than ACL wildcards
- Flexible matching - Match networks with prefix lengths in a specified range

```
# Create a prefix list
```

```
nv set router policy prefix-list <NAME> rule <ID> match <PREFIX>
```

```
# Optional: Match prefix length range
```

```
nv set router policy prefix-list <NAME> rule <ID> match <PREFIX> min-prefix-len <VALUE>
```

```
nv set router policy prefix-list <NAME> rule <ID> match <PREFIX> ny>max-prefix-len <VALUE>
```

```
# Set action (permit or deny)
```

```
nv set router policy prefix-list <NAME> rule <ID> action <permit|de
```

Configuration and Management of Networks




Prefix Lists examples

Example 1: Exact Match (No min/max-prefix-len)

Match only the exact prefix 192.168.0.0/16 - nothing else

```
nv set router policy prefix-list EXACT-MATCH rule 10 match 192.168.0.0/16
nv set router policy prefix-list EXACT-MATCH rule 10 action permit
```

What matches:

-  192.168.0.0/16 - Match
-  192.168.0.0/20 - No Match (different prefix length)
-  192.168.2.0/24 - No Match (different prefix length)

Configuration and Management of Networks






Prefix Lists examples

Example 2: Range Matching with min/max-prefix-len

Match any subnet between /26 and /32 within 10.1.1.0/24

```
nv set router policy prefix-list RANGE-MATCH rule 10 match 10.1.1.0/24
nv set router policy prefix-list RANGE-MATCH rule 10 match 10.1.1.0/24 min-prefix-len 26
nv set router policy prefix-list RANGE-MATCH rule 10 match 10.1.1.0/24 max-prefix-len 32
nv set router policy prefix-list RANGE-MATCH rule 10 action permit
```

What matches:

-  10.1.1.0/25 - No Match (prefix length < 26)
-  10.1.1.0/27 - Match ($26 \leq 27 \leq 32$)
-  10.1.1.64/26 - Match (within 10.1.1.0/24 range, length = 26)
-  10.1.1.128/30 - Match (within range)
-  10.10.10.0/24 - No Match (different prefix)

TWO conditions **simultaneously**:

- Bits must match for the first 24 bits.
- Prefix length between min (26) and max (32)

Configuration and Management of Networks

Filtering – Route Maps

Route maps are advanced routing policies that combine match criteria with set actions - similar to “if-then”.

Think of route maps as:

- More sophisticated than ACLs or prefix lists
- A scripting language for routing policies
- Combining filtering with route manipulation

```
# Create route map with rule number
nv set router policy route-map <NAME> rule <ID> action <permit|deny>

# Match criteria (the "IF" part)
nv set router policy route-map <NAME> rule <ID> match <criteria>

# Set actions (the "THEN" part)
nv set router policy route-map <NAME> rule <ID> set <action>

# Apply the configuration
nv config apply
```


Configuration and Management of Networks

Filtering – Route Maps Cisco Syntax

```
route-map MyRouteMap permit 10
    { match statements }
    { match statements }
    { set statements }
    { set statements }
route-map MyRouteMap deny 20
    ::      ::      ::
    ::      ::      ::
route-map MyRouteMap permit 30
    ::      ::      ::
    ::      ::      ::
```

Configuration and Management of Networks

Route Maps

Understanding AND vs. OR Logic

Route maps use conditional logic to determine which routes match and what actions to perform.

Multiple Match Criteria on Separate Lines = AND: All match conditions must be true for the route to match

```
nv set router policy route-map MULTI-AND rule 10 action permit
nv set router policy route-map MULTI-AND rule 10 match interface swp1
nv set router policy route-map MULTI-AND rule 10 match ip-prefix-list MY-PREFIXES
```

Logic: Route **matches IF:**

- Coming from interface swp1 AND
- Matches prefix list MY-PREFIXES

Configuration and Management of Networks

Route Maps

Understanding AND vs. OR Logic

Route maps use conditional logic to determine which routes match and what actions to perform.

Multiple Values in Same Match Type = OR: At least one value must match.

```
# Multiple prefix lists in one match criterion
nv set router policy route-map MULTI-OR rule 10 action permit
nv set router policy route-map MULTI-OR rule 10 match ip-prefix-list LIST1
nv set router policy route-map MULTI-OR rule 10 match ip-prefix-list LIST2
nv set router policy route-map MULTI-OR rule 10 match ip-prefix-list LIST3
```

Logic: Route **matches IF:**

- Matches prefix list LIST1 OR LIST 2 OR LIST 3

Configuration and Management of Networks

Route Maps

Understanding AND vs. OR Logic

Different Rule Sequences = OR: Sequential processing - if a route matches one rule, subsequent rules are not evaluated.

```
nv set router policy route-map BGP-FILTER rule 10 action permit
nv set router policy route-map BGP-FILTER rule 10 match interface swp1

nv set router policy route-map BGP-FILTER rule 20 action permit
nv set router policy route-map BGP-FILTER rule 20 match ip-prefix-list LIST3
```

Logic: Route **matches IF:**

- Coming from interface swp1 OR
- Matches prefix list LIST3

Configuration and Management of Networks

Route Maps

Understanding AND vs. OR Logic

Combined AND+OR

```
nv set router policy route-map COMPLEX rule 10 action permit
nv set router policy route-map COMPLEX rule 10 match as-path-list AS-100
nv set router policy route-map COMPLEX rule 10 match ip-prefix-list LIST-A
nv set router policy route-map COMPLEX rule 10 match ip-prefix-list LIST-B
```

Logic: Route **matches IF:**

- Matches AS-PATH-LIST AS-100 AND
- Matches LIST-A OR LIST-B)

The AS-path must match, plus at least one prefix list

Configuration and Management of Networks

Route Maps

Example: Basic Route Map Structure

Scenario: Create a route map that matches a prefix list and sets an outbound interface

```
# Step 1: Create the prefix list
nv set router policy prefix-list MyList rule 10 match 10.0.0.0/8
nv set router policy prefix-list MyList rule 10 action permit

# Step 2: Create the route map
nv set router policy route-map MyRouteMap rule 10 action permit

# Step 3: Match the prefix list
nv set router policy route-map MyRouteMap rule 10 match ip-prefix-list MyList

# Step 4: Set the outbound interface (for policy-based routing)
nv set router policy route-map MyRouteMap rule 10 set interface swp1

# Apply configuration
nv config apply
```

Configuration and Management of Networks

Route Maps – BGP example

Scenario: Set different MED values for specific networks vs. all other networks when advertising to BGP neighbor.

```
# Step 1: Create prefix list for specific networks
```

```
nv set router policy prefix-list PRIORITY-NETS rule 10 match 192.168.25.0/24
```

```
nv set router policy prefix-list PRIORITY-NETS rule 10 action permit
```

```
nv set router policy prefix-list PRIORITY-NETS rule 20 match 192.168.26.0/24
```

```
nv set router policy prefix-list PRIORITY-NETS rule 20 action permit
```

```
# Step 2: Create route map with multiple rules
```

```
nv set router policy route-map MED-65020 rule 10 action permit
```

```
nv set router policy route-map MED-65020 rule 10 match ip-prefix-list PRIORITY-NETS
```

```
nv set router policy route-map MED-65020 rule 10 set metric 100
```

```
# Step 3: Set default MED for all other routes
```

```
nv set router policy route-map MED-65020 rule 100 action permit
```

```
nv set router policy route-map MED-65020 rule 100 set metric 200
```

```
# Step 4: Apply route map to BGP neighbor (outbound)
```

```
nv set vrf default router bgp neighbor 192.168.28.1 address-family ipv4-unicast policy outbound route-map MED-65020
```

```
# Step 5: Apply configuration
```

```
nv config apply
```