

Product	SINOPEC JUSTAR J700 SP/GF-6A 0W-20 Engine Oil
Summary	Product description Моторное масло China Petrochemic J700 SP / GF - 6A 0W - 20 изготовлено из полностью синтетического базового масла и высококачественных многофункциональных добавок. Он обладает отличной устойчивостью к окислению, контролем осадков, износостойкостью и экономичностью топлива..



Applications

- Подходит для высокопроизводительных бензиновых автомобилей, E10, E85, LPG и CNG / LNG легковых автомобилей или внедорожников, MPV и других легких транспортных средств (особенно американских и азиатских брендов), особенно двигателей с различными новыми технологиями выбросов выхлопных газов, включая GPF / TWC и турбонаддув (TGDI / GDI / TFSI), с переменным временем подачи воздуха (VVT), двойным впрыском, автоматическим запуском и остановкой, гибридным двигателем и т. Д..

Technical Features:

- Улучшение свойств трения, снижение расхода топлива;
- Мощность очистки и низкий риск LSPI;
- Медленное старение масла при высоких температурах, увеличение интервала замены масла.

Typical data

SINOPEC JUSTAR J700 SP/GF-6A 0W-20 Engine Oil		
Properties	Method	Results
Kinematic viscosity@40°C, mm ² /s	ASTM D445	46.50
Kinematic viscosity@100°C, mm ² /s	ASTM D445	8.82
Viscosity Index	ASTM D2270	173
Low Temperature Pumpability(MRV) @-40°C, mPa.s	ASTM D4684	26400
Pour point, °C	ASTM D97	-42
Flash point (COC), °C	ASTM D92	224
Density @ 15°C, kg/l	ASTM D4052	0.843

These data are given as an indication of typical values, not exact specifications.

Product Data Sheet

Industry and OEM specifications

SINOPEC JUSTAR J700 SP/GF-6A 0W-20 Engine Oil meets the performance requirements of the following industry and OEM specifications:	
API Service Classification	SP; SN PLUS(RC)
ILSAC	GF-6A
OEM Specifications	GM Dexos1 Gen3; Chrysler MS6395; Ford WSS-M2C962-A1; Ford WSS-M2C947-B1

Accuracy of information

Data provided in this PDS is typical and subject to change as a result of continuing product research and development. The information given was correct at the time of printing. The typical values given are subject to variations in the testing procedures and the manufacturing process may also result in slight variations. Sinopec guarantees that its lubricants meet any industry and OEM specifications referred to on this data sheet.

Sinopec cannot be held responsible for any deterioration in the product due to incorrect storage or handling. Information on best practice is available from your local distributor.

Health, Safety & Environment

- This product is unlikely to cause any significant health problems when used in the applications suggested and when the guidance provided in the Safety Data Sheet (SDS) is followed. Please consult the SDS for more detailed advice on handling; SDSs are available from your local distributor. Do not use the product in applications other than those suggested.
- Avoid contact with skin. Use impervious gloves with used oil. After skin contact, wash immediately with soap and water.
- As with all products, please take care to avoid environmental contamination when disposing of this product. Used oil should be sent for reclamation/recycling or, if not possible, must be disposed of according to relevant government/authority regulations.

The SINOPEC trademark is registered and protected.

Issued: March 2023

© Sinopec 2023

SINOPEC JUSTAR J700 SP/GF-6A 0W-20 Engine Oil