

Product	SINOPEC JUSTAR JP1 C5/SP 0W-20 Engine Oil
Summary	Product description Моторное масло SINOPEC JUSTAR JP1 C5 / SP 0W - 20 представляет собой сверхсинтетическое моторное масло, изготовленное из высококачественных сверхсинтетических базовых масел и многофункциональных систем добавок для высокопроизводительных бензиновых и легких дизельных транспортных средств. Они обладают сверхстойкостью к окислению, контролем осадков и защитой от износа, перекачкой при сверхнизких температурах и высокотемпературной смазкой..



Applications

- Высокопроизводительные бензиновые, дизельные, дизельные, E10, легковые автомобили LPG и CNG / LNG европейских, американских и азиатских брендов, внедорожники, MPV и другие легкие транспортные средства, особенно двигатели с различными новыми технологиями, включая GPF / DPF / TWC и турбонаддув (TGDI / GDI / TFSI), переменное время работы клапанов (VVT), двойное впрыскивание, автоматическое включение и остановка, гибрид и т. Д..

Technical Features:

- сверхвысокая криогенная производительность позволяет ему справляться с экстремальными условиями частых остановок и запусков, обеспечивая стабильный и мощный выход энергии и удобный опыт вождения;
- Улучшение антифрикционных и фрикционных свойств, снижение расхода топлива;
- замедлить старение масла и увеличить интервал замены масла;
- Долгосрочная чистка и низкий риск LSPI.

Typical data

SINOPEC JUSTAR JP1 C5/SP 0W-20 Engine Oil		
Properties	Method	Results
Kinematic viscosity@40°C, mm ² /s	ASTM D445	44.30
Kinematic viscosity@100°C, mm ² /s	ASTM D445	8.72
Viscosity Index	ASTM D2270	180
Low Temperature Pumpability(MRV) @-40°C, mPa.s	ASTM D4684	22300
Pour point, °C	ASTM D97	-45
Flash point (COC), °C	ASTM D92	222
Density @ 15°C, kg/l	ASTM D4052	0.842

These data are given as an indication of typical values, not exact specifications.

Product Data Sheet

Industry and OEM specifications

SINOPEC JUSTAR JP1 C5/SP 0W-20 Engine Oil meets the performance requirements of the following industry and OEM specifications:	
API Service Classification	Petrol/Gasoline: SP and earlier specifications
ACEA Classification	C5
OEM Specifications	MB-Approval 229.71; BMW LL-17 FE+; STJLR.03.5006; Renault RN17 FE; Opel OV040 1547; VOLVO VCCRBS0-2AE; GM Dexos D

Accuracy of information

Data provided in this PDS is typical and subject to change as a result of continuing product research and development. The information given was correct at the time of printing. The typical values given are subject to variations in the testing procedures and the manufacturing process may also result in slight variations. Sinopec guarantees that its lubricants meet any industry and OEM specifications referred to on this data sheet.

Sinopec cannot be held responsible for any deterioration in the product due to incorrect storage or handling. Information on best practice is available from your local distributor.

Health, Safety & Environment

- This product is unlikely to cause any significant health problems when used in the applications suggested and when the guidance provided in the Safety Data Sheet (SDS) is followed. Please consult the SDS for more detailed advice on handling; SDSs are available from your local distributor. Do not use the product in applications other than those suggested.
- Avoid contact with skin. Use impervious gloves with used oil. After skin contact, wash immediately with soap and water.
- As with all products, please take care to avoid environmental contamination when disposing of this product. Used oil should be sent for reclamation/recycling or, if not possible, must be disposed of according to relevant government/authority regulations.

The SINOPEC trademark is registered and protected.

Issued: March 2023

© Sinopec 2023

SINOPEC JUSTAR JP1 C5/SP 0W-20 Engine Oil