

Contents

Supabase Backend — Setup	1
1. Apply the schema	1
2. Get the anon key and set env vars	1
3. Create the admin users (for later)	1
4. Verify	1
What's wired now vs next	2

Supabase Backend — Setup

This covers applying the database schema and connecting the site to it. Project ref: axbsghyqhhdaiylcksbv · API URL: <https://axbsghyqhhdaiylcksbv.supabase.co>.

1. Apply the schema

1. Open the dashboard → **SQL Editor** → **New query**: <https://supabase.com/dashboard/project/axbsghyqhhdaiylcksbv/sql/new>
2. Paste the entire contents of `supabase/migrations/0001_initial_schema.sql` and click **Run**.
3. It's safe to re-run. If the **storage** statements at the bottom error (some projects restrict SQL on the storage schema), create two **public** buckets named `product-images` and `blog-images` under **Storage** → **Buckets** instead, and add the same read/write policies in the Storage UI.

This creates the profiles, products, blog_posts, and orders tables with Row Level Security, the API-role grants, indexes, and the storage buckets.

2. Get the anon key and set env vars

1. Dashboard → **Project Settings** → **API** → copy the **anon / public** key.
2. **Local**: create `.env.local` (copy from `.env.example`) and set:

```
NEXT_PUBLIC_SUPABASE_URL=https://axbsghyqhhdaiylcksbv.supabase.co
NEXT_PUBLIC_SUPABASE_ANON_KEY=<the anon key>
```
3. **Production (Vercel)**: Project → Settings → Environment Variables → add the same two, then redeploy. (The anon key is public-safe — RLS protects the data. Never add the `service_role` key to client/NEXT_PUBLIC_vars.)

3. Create the admin users (for later)

The order form needs no login. Admin **reads** (and the future dashboard) require an admin account. Under **Authentication** → **Users**, add the three admins (`nurvexthink@gmail.com`, `fatima.abdulraheemdev.17@gmail.com`, `muhammadalidev3@gmail.com`). A profiles row with role = 'admin' is created automatically by a trigger; promote one to owner if you like:

```
update public.profiles set role = 'owner' where email = 'fatima.abdulraheemdev.17@gmail.com';
```

4. Verify

1. With the env vars set, run `npm run dev` and open **/order**.
2. Submit the form. You should land on the "Request received" confirmation.
3. In the dashboard → **Table Editor** → **orders**, the new lead row appears.

If submissions say "not connected yet," the anon key isn't set in that environment.

What's wired now vs next

- **Now:** schema + RLS + storage; the **Order form saves real leads** to orders (validated server-side, with a honeypot). Products/blog still render from `src/lib/content.ts`.
- **Next milestone:** admin login + dashboard to manage products/blog/orders, and moving the products/blog content into the database.