JEBAT × KIRO IDE

Automatic JEBAT-MCP pairing for Kiro IDE

Install JEBAT, detect your IDE, merge the MCP configuration safely, and use JEBAT directly in Kiro Chat.

> Two commands. No manual JSON required.
> JEBAT detects installed IDEs, preserves existing settings, backs up existing MCP JSON, and registers its local stdio server.

```
npx --yes @nusabyte/jebat --version
npx --yes @nusabyte/jebat mcp pair
```

After pairing

Restart or reconnect Kiro → open MCP servers → confirm jebat is connected → open Kiro Chat → type # → select plan-act-verify-remember.

Requirements: Node.js 18+, Python 3.11+, Git, and bash for the initial bootstrap. No public URL or manually running server is required.

01 · Install and pair automatically

1. Bootstrap once. Run this in a terminal and confirm it prints the JEBAT version.

```
npx --yes @nusabyte/jebat --version
```

2. Detect installed IDEs. This inspection does not modify files.

```
npx --yes @nusabyte/jebat mcp pair --list
```

3. Pair every detected IDE, or Kiro only.

```
npx --yes @nusabyte/jebat mcp pair
# Kiro only
npx --yes @nusabyte/jebat mcp pair --ide kiro
```

Detection covers Kiro, Cursor, VS Code, and Windsurf from their user configuration directories. It does not launch or probe the applications.

What the installer changes

- Writes the user-level `mcpServers.jebat` entry for local stdio.
- Preserves unrelated settings and existing MCP servers.
- Backs up existing JSON before changing it.
- Refuses to overwrite malformed JSON; fix it and retry.

> Explicit opt-in. Ordinary installation does not change IDE settings. Pairing runs only when you call `mcp pair` or install with `--ide`.

Bootstrap installer alternative

```
curl -fsSL https://raw.githubusercontent.com/nusabyte-my/jebat-core/main/install.sh | bash -s --
--ide=kiro
# Auto-detect supported IDEs: use --ide
# Skip IDE configuration: use --no-ide
```

02 · Use JEBAT in Kiro Chat

Restart Kiro or right-click jebat in the MCP servers panel → Reconnect. If necessary, enable MCP support in Kiro Settings.

Load the governed workflow

In Kiro Chat, type # to open the context picker. Find the JEBAT prompt plan-act-verify-remember and select it.

```
#[jebat] plan-act-verify-remember
```

`/load-jebat` belongs to the JEBAT CLI. It is not a native Kiro command or MCP tool.

Run a safe first test

```
Use JEBAT MCP tools to inspect the current workspace
and list its root files. Do not modify anything.
```

Review the proposed tool and arguments, then approve the read-only call.

Examples

```
Use JEBAT to inspect the current git diff and summarize risk.
Use JEBAT to recall project conventions before making changes.
Use JEBAT to review CLI startup behavior. Do not edit files.
```

> Keep approvals on. Start without `autoApprove`. Manually approve file writes, terminal commands, deployments, and destructive actions.

Optional provider setup

```
npx --yes @nusabyte/jebat provider add
```

Provider inference is separate from MCP connection and tool discovery.

03 · Manual fallback and troubleshooting

If automatic pairing is unsuitable, open Command Palette → Kiro: Open user MCP config (JSON) and merge this entry:

```
{
"mcpServers": {
"jebat": {
"command": "npx",
"args": ["--yes", "@nusabyte/jebat", "mcp", "serve", "--transport", "stdio"],
"disabled": false
}
}
}
```

On Windows, if Kiro cannot start npx, use `"command": "cmd.exe"` and insert `"/c", "npx"` at the start of `args`.

Common fixes

Issue	Action
No IDE detected	Create/open the IDE's normal user settings once, or pair manually.
Existing JSON invalid	Fix the JSON; JEBAT leaves it untouched and creates no backup.
Server not connected	Save config, reconnect, inspect Output → Kiro – MCP Logs.
npx not found	Install Node.js 18+ and restart Kiro to refresh PATH.
Provider error	MCP may be connected; run the provider setup separately.

Success checklist

- The version command succeeds.
- JEBAT is connected in Kiro → MCP servers.
- The # picker lists JEBAT prompts/tools.
- A read-only workspace call succeeds.
- Write and terminal tools remain manually approved.

Kiro MCP documentation · JEBAT `MCP.md`