

---

ASSIGNMENT - LOOP

---

Name : Nusrat Jahan Chaiti

ID : 2023-1-60-255

COURSE CODE : CSE 103

Course Title: Structured Programming Language

SECTION :11



**Q1.** Write a program (WAP) that will print following series upto Nth terms.

1, 2, 3, 4, 5, 6, 7, 8, 9, 10, 11, 12, 13, 14,.....

**Answer:**

```
#include <stdio.h>
int main() {
int n, i;
printf("Enter the number of terms: ");
scanf("%d", &n);

for (i = 1; i <= n; i++) {
printf("%d ", i);
}
return 0;
}
```

***Output:***

```
Enter the number of terms: 20
1 2 3 4 5 6 7 8 9 10 11 12 13 14 15 16 17 18 19 20
Process returned 0 (0x0)   execution time : 4.533 s
Press any key to continue.
```

**Q2.** Write a program (WAP) that will print following series upto Nth terms.  
1,3,5,7,9, 11, 13, 15, 17, 19, 21, 23, 25, 27, 29, 31

**Answer:**

```
#include <stdio.h>
int main() {
int n, i;
printf("Enter the number of terms: ");
scanf("%d", &n);

for (i = 1; i <= n; i++) {
printf("%d ", 2*i-1);
}

return 0;
}
```

**Output:**

```
Enter the number of terms: 30
1 3 5 7 9 11 13 15 17 19 21 23 25 27 29 31 33 35 37 39 41 43 45 47 49 51 53 55 57 59
Process returned 0 (0x0)   execution time : 3.910 s
Press any key to continue.
```

**Q3.** Write a program (WAP) that will print following series upto Nth terms.

1, 0, 1, 0, 1, 0, 1, 0, 1, 0, 1, 0, 1, 0, 1,

**Answer:**

```
#include <stdio.h>

int main() {
    int n, i;
    printf("Enter the number of terms: ");
    scanf("%d", &n);

    for (i = 1; i <= n; i++) {
        if (i % 2 == 1) {
            printf("1 ");
        } else {
            printf("0 ");
        }
    }

    return 0;
}
```

**Output:**

```
Enter the number of terms: 10
1 0 1 0 1 0 1 0 1 0
Process returned 0 (0x0)   execution time : 7.387 s
Press any key to continue.
```

**Q4.** Write a program (WAP) that will take N numbers as inputs and compute their average.  
(Restriction: Without using any array)

**Answer:**

```
#include <stdio.h>
int main() {
    int n, i, num;
    float sum = 0, avg;
    printf("Enter the number of elements: ");
    scanf("%d", &n);

    for (i = 1; i <= n; i++) {
        printf("Enter element %d: ", i);
        scanf("%d", &num);
        sum += num;
    }
    avg = sum / n;
    printf("The average is %.2f\n", avg);

    return 0;
}
```

**Output:**

```
Enter the number of elements: 3
Enter element 1: 10
Enter element 2: 20
Enter element 3: 30.5
The average is 20.00
```

**Q5.** Write a program (WAP) that will take two numbers X and Y as inputs. Then it will print the square of X and increment (if  $X < Y$ ) or decrement (if  $X > Y$ ) X by 1, until X reaches Y. If and when X is equal to Y, the program prints "Reached!"

**Answer:**

```
#include <stdio.h>
int main() {
    int x, y, i;
    printf("Enter two numbers: ");
    scanf("%d %d", &x, &y);

    while (x != y) {
        printf("The square of %d is %d\n", x, x*x);
        if (x < y) {
            x++;
        } else {
            x--;
        }
    }
    printf("Reached!\n");
    return 0;
}
```

**Output:**

```
Enter two numbers: 10
5
The square of 10 is 100
The square of 9 is 81
The square of 8 is 64
The square of 7 is 49
The square of 6 is 36
Reached!
```

---

**Q6.** Write a program (WAP) for the described scenario: Player-1 picks a number X and Player-2 has to guess that number within N tries. For each wrong guess by Player-2, the program prints "Wrong, N-1 Choice(s) Left!" if Player-2 at any time successfully guesses the number, the program prints "Right, Player-2 wins!" and terminates right away. Otherwise after the completion of N wrong tries, the program prints "Player-1 wins!" and halts

---

**Answer:**

```
#include <stdio.h>
int main() {
    int x, guess, n, i;
    printf("Player-1, enter a number: ");
    scanf("%d", &x);
    printf("Player-2, you have to guess the number in how many tries? ");
    scanf("%d", &n);

    for (i = 1; i <= n; i++) {
        printf("Guess the number (try %d): ", i);
        scanf("%d", &guess);

        if (guess == x) {
            printf("Right, Player-2 wins!\n");
            break;
        } else {
            printf("Wrong, %d Choice(s) Left!\n", n - i);
            if (i == n) {
                printf("Player-1 wins!\n");
            }
        }
    }
    return 0;
}
```

***Output:***

```
Player-1, enter a number: 5
Player-2, you have to guess the number in how many tries? 4
Guess the number (try 1): 12
Wrong, 3 Choice(s) Left!
Guess the number (try 2): 8
Wrong, 2 Choice(s) Left!
Guess the number (try 3): 5
Right, Player-2 wins!
```

**Q7.** Write a program (WAP) that will run and show keyboard inputs until the user types an "A" at the keyboard.

**Answer:**

```
#include <stdio.h>

int main() {
    char ch;
    int i = 1;
    printf("Enter keyboard inputs (type 'A' to exit):\n");
    do {
        ch = getchar();
        printf("Input %d: %c\n", i++, ch);
    } while (ch != 'A');
    printf("Exiting...\n");
    return 0;
}
```

**Output:**

```
Enter keyboard inputs (type 'A' to exit):
X
Input 1: X
Input 2:
A
Input 3: A
Exiting...
```



**Q8.** Write a program (WAP) that will reverse the digits of an input integer.

**Answer:**

```
#include <stdio.h>
int main() {
int num, rev_num = 0;

printf("Enter an integer: ");
scanf("%d", &num);

while (num != 0) {
int digit = num % 10;
rev_num = rev_num * 10 + digit;
num /= 10;
}
printf("Reversed number: %d\n", rev_num);

return 0;
}
```

**Output:**

```
Enter an integer: 4321
Reversed number: 1234
```

**Q9.** Write a program (WAP) that will find the grade of N students. For each student, it will take the marks of his/her the attendance (on 5 marks), assignment (on 10 marks), class test (on 15 marks), midterm (on 50 marks), term final (on 100 marks).

**Answer:**

```
#include <stdio.h>
int main() {
    int n, i;
    float attendance, assignment, class_test, midterm, term_final, total_marks, percentage;
    char grade;
    printf("Enter the number of students: ");
    scanf("%d", &n);

    for (i = 1; i <= n; i++) {
        printf("Enter the marks of student %d:\n", i);

        printf("Attendance (out of 5): ");
        scanf("%f", &attendance);

        printf("Assignment (out of 10): ");
        scanf("%f", &assignment);

        printf("Class Test (out of 15): ");
        scanf("%f", &class_test);

        printf("Midterm (out of 50): ");
        scanf("%f", &midterm);
        printf("Term Final (out of 100): ");
        scanf("%f", &term_final);
        total_marks = attendance + assignment + class_test + midterm + term_final;
        percentage = (total_marks / 180) * 100;

        if (percentage >= 90) {
            grade = 'A';
        } else if (percentage >= 80) {
            grade = 'B';
        } else if (percentage >= 70) {
            grade = 'C';
        } else if (percentage >= 60) {
            grade = 'D';
        } else {
            grade = 'F';
        }
        printf("Total marks: %.2f\n", total_marks);
        printf("Percentage: %.2f%%\n", percentage);
        printf("Grade: %c\n", grade);
    }
    return 0;
}
```

**Output:**

```
Enter the number of students: 25
Enter the marks of student 1:
Attendance (out of 5): 5
Assignment (out of 10): 10
Class Test (out of 15): 15
Midterm (out of 50): 48
Term Final (out of 100): 98
Total marks: 176.00
Percentage: 97.78%
Grade: A
```

**Q10.** Write a program (WAP) that will give the sum of first Nth terms for the following series.

1,-2,3,-4,5,-6,7,-8,9,-10, 11,-12, 13, -14,.....

**Answer:**

```
#include <stdio.h>
int main() {
    int n, i, num = 1, sign = 1, sum = 0;

    printf("Enter the number of terms: ");
    scanf("%d", &n);

    for (i = 1; i <= n; i++) {
        sum += num * sign;
        num++;

        if (num % 2 == 0) {
            sign = -1 * sign;
        }
    }
    printf("The sum of the first %d terms is %d\n", n, sum);
    return 0;
}
```

**Output:**

```
Enter the number of terms: 2
The sum of the first 2 terms is -1
```

**Q11.** Write a program (WAP) that will calculate the result for the first Nth terms of the following series. [In that series sum, dot sign (.) means multiplication]

$$1*2.2+2*2.3+3*2.4+4*2.5+.....$$

**Answer:**

```
#include <stdio.h>
int main() {
    int n, i;
    float sum = 0;

    printf("Enter the number of terms: ");
    scanf("%d", &n);

    for (i = 1; i <= n; i++) {
        sum += i * (i + 1) * 2;
    }
    printf("The sum of the first %d terms is %.2f\n", n, sum);

    return 0;
}
```

**Output:**

```
Enter the number of terms: 3
The sum of the first 3 terms is 40.00
```

**Q12.** Write a program (WAP) that will print Fibonacci series upto Nth terms.  
1,1,2,3,5, 8, 13, 21, 34, 55, 89,.....

**Answer:**


```
#include <stdio.h>

int main() {
    int n, i;
    long long int a = 0, b = 1, c;

    printf("Enter the number of terms: ");
    scanf("%d", &n);

    for (i = 1; i <= n; i++) {
        printf("%lld ", b);
        c = a + b;
        a = b;
        b = c;
    }
    return 0;
}
```

**Output:**

A screenshot of a terminal window showing the output of the program. The first line is "Enter the number of terms: 7" and the second line is "1 1 2 3 5 8 13". The text is displayed in a monospaced font with a light blue/cyan color on a black background.

```
Enter the number of terms: 7
1 1 2 3 5 8 13
```

**Q13.** Write a program (WAP) that will print the factorial (N!) of a given number N

**Answer:**

```
#include <stdio.h>
int main() {
    int n, i;
    unsigned long long fact = 1;

    printf("Enter an integer: ");
    scanf("%d", &n);

    for (i = 1; i <= n; ++i) {
        fact *= i;
    }
    printf("Factorial of %d = %llu", n, fact);
    return 0;
}
```

**Output:**

```
Enter an integer: 4
Factorial of 4 = 24
```

**Q14.** Write a program (WAP) that will find  $nCr$  where  $n \geq r$ ;  $n$  and  $r$  are integers

**Answer:**

```
#include <stdio.h>
int factorial(int n);
int nCr(int n, int r);

int main() {
    int n, r;

    printf("Enter n and r (n >= r): ");
    scanf("%d %d", &n, &r);

    printf("%dC%d = %d", n, r, nCr(n, r));
    return 0;
}

int factorial(int n) {
    int i, fact = 1;
    for (i = 1; i <= n; ++i) {
        fact *= i;
    }
    return fact;
}

int nCr(int n, int r) {
    int num, den;
    num = factorial(n);
    den = factorial(r) * factorial(n - r);
    return num / den;
}
```

**Qutput:**

```
Enter n and r (n >= r): 10
3
10C3 = 120
```

**Q15.** Write a program (WAP) that will find (x to the power y) where x, y are positive integers.

**Answer:**

```
#include <stdio.h>
int power(int x, int y);

int main() {
    int x, y;

    printf("Enter x and y (both positive integers): ");
    scanf("%d %d", &x, &y);

    printf("%d to the power %d = %d", x, y, power(x, y));
    return 0;
}

int power(int x, int y) {
    int result = 1, i;
    for (i = 1; i <= y; ++i) {
        result *= x;
    }
    return result;
}
```

**Output:**

```
Enter x and y (both positive integers): 5
2
5 to the power 2 = 25
```



**Q16.** WAP that will find the GCD (greatest common divisor) and LCM (least common multiple) of two positive integers

**Answer:**

```
#include <stdio.h>
int gcd(int x, int y);
int lcm(int x, int y);

int main() {
    int x, y;

    printf("Enter two positive integers (x, y): ");
    scanf("%d %d", &x, &y);

    printf("GCD of %d and %d = %d\n", x, y, gcd(x, y));
    printf("LCM of %d and %d = %d", x, y, lcm(x, y));
    return 0;
}

int gcd(int x, int y) {
    int temp;
    while (y != 0) {
        temp = x % y;
        x = y;
        y = temp;
    }
    return x;
}

int lcm(int x, int y) {
    return (x * y) / gcd(x, y);
}
```

**Output:**

```
Enter two positive integers (x, y): 12
32
GCD of 12 and 32 = 4
LCM of 12 and 32 = 96
```

**Q17.** WAP that will determine whether a number is prime or not

**Answer:**

```
#include <stdio.h>
int is_prime(int n);

int main() {
    int n;
    printf("Enter a positive integer: ");
    scanf("%d", &n);

    if (is_prime(n)) {
        printf("%d is a prime number", n);
    } else {
        printf("%d is not a prime number", n);
    }
    return 0;
}

int is_prime(int n) {
    if (n <= 1) {
        return 0;
    }
    for (int i = 2; i * i <= n; i++) {
        if (n % i == 0) {
            return 0;
        }
    }
    return 1;
}
```

**Output:**

```
Enter a positive integer: 39
39 is not a prime number
```

**Q18.** WAP that will determine whether an integer is palindrome number or not.

**Answer:**

```
#include <stdio.h>
int is_palindrome(int n);

int main() {
    int n;

    printf("Enter an integer: ");
    scanf("%d", &n);

    if (is_palindrome(n)) {
        printf("%d is a palindrome number", n);
    } else {
        printf("%d is not a palindrome number", n);
    }
    return 0;
}

int is_palindrome(int n) {
    int reverse = 0, temp = n;

    while (temp != 0) {
        reverse = (reverse * 10) + (temp % 10);
        temp /= 10;
    }
    return (n == reverse);
}
```

**Output:**

```
Enter an integer: 222
222 is a palindrome number
```

**Q19.**WAP that will calculate following mathematical function for the input of x.  
 $\text{Sinx} = (x - x^3/3!) + (x^5/5!) - (x^7/7!) + \dots$

**Answer:**

```
#include <stdio.h>
#include <math.h>

double sinx(double x);

int main() {
    double x;
    printf("Enter a value for x (in radians): ");
    scanf("%lf", &x);

    printf("sin(%lf) = %lf", x, sinx(x));

    return 0;
}

double sinx(double x) {
    double term, sum = 0.0;
    int sign = 1, denominator = 1;

    for (int i = 1; i <= 5; i++) {
        term = (pow(x, i) / denominator) * sign;
        sum += term;
        sign = -sign;
        denominator *= (2 * i) * (2 * i + 1);
    }
    return sum;
}
```

**Output:**

```
Enter a value for x (in radians): 1
sin(1.000000) = 0.841471
```

**Q20.** Write a program that takes an integer number n as input and find out the sum of the following series up to n terms.

1+12+123 + 1234+.....

**Answer:**

```
#include <stdio.h>
int main() {
    int n, sum = 0, term = 0;

    printf("Enter the value of n: ");
    scanf("%d", &n);

    for (int i = 1; i <= n; i++) {
        term = (term * 10) + i;
        sum += term;
    }
    printf("The sum of the series up to %d terms is: %d", n, sum);

    return 0;
}
```

**Output:**

```
Enter the value of n: 3
The sum of the series up to 3 terms is: 136
```