### **Essentials Blade Directives**

```
@foreach, @for, @while, forelse → Loops.
@if, @elseif, @else → Conditional statements.
@switch, @case, @default, @break → Switch-case logic.
@php → Run raw PHP inside Blade.
@isset, @empty → Check if variables are set or empty.
@csrf → Include CSRF protection.
@method('PUT'), @method('DELETE') → Method Spoofing (PUT, DELETE)
@error → Display validation errors.
@session → Display session data.
@auth, @guest → Authentication checks.
```

#### **Blade Comments**

```
Use {{-- --}} for Blade comments (not visible in HTML).
```

@push , @stack → Manage stacked sections

```
{{-- This is a Blade comment --}}
```

### **Blade Conditional Statements**

## **If-Else**

```
@if($user)
     Welcome, {{$user->name}}
@else
     Please log in
@endif
```

### **If-Elself-Else**

## **Isset & Empty**

### **Blade Switch-Case**

## **Blade Loops**

## **Foreach Loop**

## **Forelse**

```
@forelse($posts as $post)
      <h1>{{ $post }}</h1>
@empty
      <h1>No posts</h1>
@endforelse
```

## **For Loop**

```
@endfor
```

## While Loop

## **Blade PHP Execution**

If you need to write raw PHP inside Blade:

# **Blade Forms & Security**

### **CSRF Protection**

```
<form method="POST" action="/submit">
    @csrf
    <button type="submit">Submit</button>
</form>
```

## **Method Spoofing (PUT, DELETE)**

```
<form method="POST" action="/update">
    @csrf
    @method('PUT')
    <button type="submit">Update</button>
</form>
```

#### **Validation Errors**

#### **Session Data**

```
@session('message')
     <h1>{{ session('message') }}</h1>
@endsession
```

## **Blade Authentication Directives**

#### **Check Authenticated User**

```
@auth
     Welcome, {{auth()->user()->name}}
@endauth
```

## **Check Guest (Not Logged In)**

```
@guest
     Please log in
@endguest
```

# Blade Stacks (@push & @stack)

Useful for adding dynamic content (e.g., JavaScript).

#### 🖈 In Layout:

#### ★ In Child View:

# **Blade Layouting**

#### main.blade.php file inside layouts folder

```
<!DOCTYPE html>
<html lang="en">
<head>
   <meta charset="UTF-8">
   <meta name="viewport" content="width=device-width, initial-scale=1.0">
   <meta http-equiv="X-UA-Compatible" content="ie=edge">
   <title>My APP | @yield('title', 'Default Page')</title>
   <link rel="stylesheet" href="style.css">
   // Page Specific CSS will load here
   @yield('styles')
   // Page Specific JS will load here
   @stack('scripts')
</head>
<body>
   ul>
       home
       about
   @yield('content')
   <script src="script.js"></script>
</body>
</html>
```

#### home.blade.php inside views folder

```
@extends('layouts.main')

@section('title', 'Home')

@section('content')

<h1>Home Page</h1>
```

## about.blade.php inside views folder