

Week-5: Code-along

Jing Ying

2023-09-10

```
knitr::opts_chunk$set(echo = TRUE)
```

II. Code to edit and execute using the Code-along.Rmd file

A. Writing a function

1. Write a function to print a “Hello” message (Slide #14)

```
# Enter code here
# name <- "Kashif"
# print(paste0("Hello ", name, "!"))

say_hello_to <- function(name) {
  print(paste0("Hello ", name, "!"))
}

say_hello_to('Kashif')
```

```
## [1] "Hello Kashif!"
```

2. Function call with different input names (Slide #15)

```
# Enter code here

say_hello_to('Kashif')
```

```
## [1] "Hello Kashif!"
```

```
say_hello_to('Zach')
```

```
## [1] "Hello Zach!"
```

```
say_hello_to('Deniz')
```

```
## [1] "Hello Deniz!"
```

3. typeof primitive functions (Slide #16)

```
# Enter code here
```

```
typeof(`+`)
```

```
## [1] "builtin"
```

```
typeof(sum)
```

```
## [1] "builtin"
```

4. typeof user-defined functions (Slide #17)

```
# Enter code here
```

```
typeof(say_hello_to)
```

```
## [1] "closure"
```

```
typeof(mean)
```

```
## [1] "closure"
```

5. Function to calculate mean of a sample (Slide #19)

```
# Enter code here
```

```
calc_sample_mean <- function(sample_size) {  
  mean(rnorm(sample_size))  
}
```

6. Test your function (Slide #22)

```
# With one input
```

```
calc_sample_mean(1000)
```

```
## [1] 0.006358833
```

```
# With vector input
```

```
calc_sample_mean(c(100, 300, 3000))
```

```
## [1] -0.2396945
```

7. Customizing the function to suit input (Slide #23)

Enter code here

```
library(tidyverse)
```

```
## -- Attaching core tidyverse packages ----- tidyverse 2.0.0 --
## v dplyr      1.1.2      v readr      2.1.4
## v forcats    1.0.0      v stringr   1.5.0
## v ggplot2    3.4.3      v tibble    3.2.1
## v lubridate  1.9.2      v tidyr     1.3.0
## v purrr      1.0.2
## -- Conflicts ----- tidyverse_conflicts() --
## x dplyr::filter() masks stats::filter()
## x dplyr::lag()     masks stats::lag()
## i Use the conflicted package (<http://conflicted.r-lib.org/>) to force all conflicts to become errors
```

```
sample_tibble <- tibble(sample_sizes =
  c(100, 300, 3000))
```

```
sample_tibble %>%
  group_by(sample_sizes) %>%
  mutate(sample_means =
    calc_sample_mean(sample_sizes))
```

```
## # A tibble: 3 x 2
## # Groups:   sample_sizes [3]
##   sample_sizes sample_means
##         <dbl>         <dbl>
## 1         100         -0.0789
## 2          300         -0.0368
## 3         3000          0.0144
```

8. Setting defaults (Slide #25)

First define the function

```
calc_sample_mean <- function(sample_size,
  our_mean, our_sd)
{
  sample <- rnorm(sample_size,
    mean = our_mean,
    mean(sample),
    sd = our_sd)
}
```

Call the function

```
calc_sample_mean <- function(sample_size,
  our_mean=0,
```

```

    our_sd=1) {
  sample <- rnorm(sample_size,
    mean = our_mean,
    sd = our_sd)
  mean(sample)
}

calc_sample_mean(sample_size = 10)

```

```
## [1] -0.3236144
```

9. Different input combinations (Slide #26)

```

# Enter code here

calc_sample_mean(10, our_sd = 2)

```

```
## [1] 0.3165914
```

```
calc_sample_mean(10, our_mean = 6)
```

```
## [1] 6.264243
```

```
calc_sample_mean(10, 6, 2)
```

```
## [1] 4.914621
```

10. Different input combinations (Slide #27)

```

# set error=TRUE to see the error message in the output
# Enter code here

calc_sample_mean(our_mean = 5)

```

```
## Error in calc_sample_mean(our_mean = 5): argument "sample_size" is missing, with no default
```

11. Some more examples (Slide #28)

```

# Enter code here

add_two <- function(x) {
  x+2
}

add_two(4)

```

```
## [1] 6
```

```
add_two(-34)
```

```
## [1] -32
```

```
add_two(5.784)
```

```
## [1] 7.784
```

B. Scoping

12. Multiple assignment of z (Slide #36)

```
# Enter code here
```

```
z <- 1  
sprintf("The value assigned to z outside the function is %d",z)
```

```
## [1] "The value assigned to z outside the function is 1"
```

```
foo <- function(z = 2) {  
  # reassigning z  
  z <- 3  
  return(z+3)  
}  
foo()
```

```
## [1] 6
```

13. Multiple assignment of z (Slide #37)

```
# Enter code here
```

```
z <- 1  
foo <- function(z = 2) {  
  z <- 3  
  return(z+3)}  
foo(z = 4)
```

```
## [1] 6
```

```
sprintf("The final value of z after reassigning it to a different value inside the function is %d",z)
```

```
## [1] "The final value of z after reassigning it to a different value inside the function is 1"
```