Vanloka Laravel API & Web Routes — with Node (Express) comparison

Reference for the **PHP Laravel** app (`routes/*.php`). Paths use Laravel's default **`/api` prefix** for `routes/api.php`. Central API routes are constrained to each **central domain** from `config('tenancy.central_domains')`. Tenant API routes use **tenant hostnames** (subdomain) per `routes/api_tenant.php`.

Node (Express) routes in this repo live under `application-backend/src/` (same tree as the Docker/TS API). They use a **single host** with prefix **`/api`**; tenant APIs are under **`/api/tenant/...`** and need header **`x-tenant-id`** (or `tenantId` on the tenant JWT), not a separate subdomain.

For an exact Laravel list:

```
php artisan route:list
```

Node column legend

Symbol	Meaning
✅	Implemented in Node — cells list **`METHOD /full/path`** (`{id}` in PHP ≈ `:id` in Node). **`(JWT)`** = send `Authorization: Bearer …`.
⚠️	Implemented with a **different** path or auth/behavior (see note)
🔶	Implemented but **stub** or intentionally simplified
❌	**Not** in Node (typical: Inertia / Fortify web only)

Summary — PHP vs Node

Area	PHP	Node
Laravel `/up`	✅	❌ (Node: `GET /api/health`, `GET /api/ready`)
Web `/`, `/health`, dashboard, settings pages	✅	❌ (Node: `PATCH/DELETE /api/settings/profile`, `PUT /api/settings/password`, `GET /api/settings/two-factor` stub)
Fortify (login/register/reset/2FA web)	✅	❌
Central `/api/*` (REST)	✅	✅ (mostly); masters pickup/state often **JWT** on Node
Mobile Firebase login	✅	⚠️ `POST /api/mobile/auth/cognito-login`
User notifications	✅	🔶 `GET /api/user/notifications/:userId` (empty list until modeled)
User-app trips path	`/api/user-app/trips/trip-purposes/...`	⚠️ `/api/user-app/trip-purposes/...` (no `trips` segment)
Tenant API host	Tenant subdomain + `/api/...`	⚠️ Same host + `/api/tenant/...`
Swagger	—	✅ `GET /api/docs`, `GET /api/docs.json`

Framework

Method	Path (PHP)	Node
GET	`/up`	❌
GET	—	✅ `GET /api/health`
GET	—	✅ `GET /api/ready`
GET	—	✅ `GET /api`
GET	—	✅ `GET /api/docs`, `GET /api/docs.json`

Web — central domain (`routes/web.php`, `routes/settings.php`)

Method	Path	Node
GET	`/`	❌
GET	`/health`	⚠️ `GET /api/health`

Method	Path	Node
GET	`/dashboard`	❌
GET	`/settings/profile`	❌
PATCH	`/settings/profile`	⚠️ `PATCH /api/settings/profile` (JWT)
DELETE	`/settings/profile`	⚠️ `DELETE /api/settings/profile` (JWT)
GET	`/settings/password`	❌
PUT	`/settings/password`	⚠️ `PUT /api/settings/password` (JWT)
GET	`/settings/appearance`	❌
GET	`/settings/two-factor`	🔶 `GET /api/settings/two-factor` (stub)
GET	`/settings`	❌

Fortify (web auth — central)

`config/fortify.php`: `'prefix' => ''` (central domain root, not `/api`). **Not** mirrored in Node; use `/api/login` (JWT) and Cognito mobile flow.

Method	Path	Node
Various	`/login`, `/register`, `/forgot-password`, `/reset-password/*`, `/email/verify*`, `/two-factor-challenge`, `/user/*` (Fortify)	❌

API — central domain (`routes/api.php`)

Base prefix: **`/api`**.

Auth / misc

Method	Path	Node
GET	`/api/user`	✅ `GET /api/user` (JWT)
GET	`/api/me`	✅ `GET /api/me` (JWT)
POST	`/api/login`	✅ `POST /api/login`
GET	`/api/hello`	❌

Permissions & roles

Method	Path	Node
GET	`/api/permissions`	✅ `GET /api/permissions` (JWT)
GET	`/api/roles`	✅ `GET /api/roles` (JWT)
POST	`/api/roles`	✅ `POST /api/roles` (JWT)
GET	`/api/roles/{role}`	✅ `GET /api/roles/:id` (JWT)
PUT	`/api/roles/{role}`	✅ `PUT /api/roles/:id` (JWT)
DELETE	`/api/roles/{role}`	✅ `DELETE /api/roles/:id` (JWT)

Employees (`apiResource`)

Method	Path	Node
GET	`/api/employees`	✅ `GET /api/employees` (JWT)
POST	`/api/employees`	✅ `POST /api/employees` (JWT)
GET	`/api/employees/{employee}`	✅ `GET /api/employees/:id` (JWT)
PUT/PATCH	`/api/employees/{employee}`	✅ `PUT /api/employees/:id` (JWT)
DELETE	`/api/employees/{employee}`	✅ `DELETE /api/employees/:id` (JWT)

Masters — pickup locations

Method	Path	Node
GET	/api/masters/pickup-locations	✅ GET /api/masters/pickup-locations (JWT)
POST	/api/masters/pickup-locations/import	✅ POST /api/masters/pickup-locations/import (JWT)
DELETE	/api/masters/pickup-locations/{id}	✅ DELETE /api/masters/pickup-locations/:id (JWT)
GET	/api/masters/pickup-locations/stats	✅ GET /api/masters/pickup-locations/stats (JWT)

Masters — state districts

Method	Path	Node
GET	/api/masters/state-districts	✅ GET /api/masters/state-districts (JWT)
POST	/api/masters/state-districts/import	✅ POST /api/masters/state-districts/import (JWT)
DELETE	/api/masters/state-districts/{id}	✅ DELETE /api/masters/state-districts/:id (JWT)

Masters — form fields

Method	Path	Node
GET	/api/masters/form-fields	✅ GET /api/masters/form-fields (JWT)
POST	/api/masters/form-fields/import	✅ POST /api/masters/form-fields/import (JWT)
DELETE	/api/masters/form-fields/{id}	✅ DELETE /api/masters/form-fields/:id (JWT)

Form dropdowns

Method	Path	Node
GET	/api/masters/forms/dropdowns/fields	✅ GET /api/masters/forms/dropdowns/fields
GET	/api/masters/forms/dropdowns/states	✅ GET /api/masters/forms/dropdowns/states
GET	/api/masters/forms/dropdowns/districts/{state}	✅ GET /api/masters/forms/dropdowns/districts/:state

Onboarding & organisations

Method	Path	Node
POST	/api/onboarding	✅ POST /api/onboarding
GET	/api/organisations	✅ GET /api/organisations
GET	/api/organisations/filter-options	✅ GET /api/organisations/filter-options
GET	/api/organisations/stats	✅ GET /api/organisations/stats
GET	/api/organisations/show/{id}	✅ GET /api/organisations/show/:id
PUT	/api/organisations/update/{id}	✅ PUT /api/organisations/update/:id
DELETE	/api/organisations/{id}	✅ DELETE /api/organisations/:id

Pickup locations (assign)

Method	Path	Node
GET	/api/pickup-locations/all	✅ GET /api/pickup-locations/all (JWT)
GET	/api/pickup-locations/filter-options	✅ GET /api/pickup-locations/filter-options (JWT)
GET	/api/organisations/{id}/pickup-locations	✅ GET /api/organisations/:id/pickup-locations (JWT)
POST	/api/organisations/{id}/pickup-locations/assign	✅ POST /api/organisations/:id/pickup-locations/assign (JWT)

Beacon devices

Method	Path	Node
GET	/api/all/beacon/devices	✅ GET /api/all/beacon/devices (JWT)
GET	/api/organisations/{id}/assined/beacon/devices	✅ GET /api/organisations/:id/assined/beacon/devices (JWT)

Method	Path	Node
GET	/api/organisations/assined/beacon/devices/statistics	✅ GET /api/organisations/assined/beacon/devices/statistics (JWT)
POST	/api/organisations/{id}/assign/beacon/devices	✅ POST /api/organisations/:id/assign/beacon/devices (JWT)
POST	/api/beacon-devices/import	✅ POST /api/beacon-devices/import (JWT)
GET	/api/beacon-devices/export	✅ GET /api/beacon-devices/export (JWT)
GET	/api/beacon-devices	✅ GET /api/beacon-devices (JWT)
POST	/api/beacon-devices	✅ POST /api/beacon-devices (JWT)
GET	/api/beacon-devices/{beacon_device}	✅ GET /api/beacon-devices/:id (JWT)
PUT/PATCH	/api/beacon-devices/{beacon_device}	✅ PUT /api/beacon-devices/:id (JWT)
DELETE	/api/beacon-devices/{beacon_device}	✅ DELETE /api/beacon-devices/:id (JWT)

GPS devices

Method	Path	Node
GET	/api/all/gps/devices	✅ GET /api/all/gps/devices (JWT)
GET	/api/organisations/{id}/assined/gps/devices	✅ GET /api/organisations/:id/assined/gps/devices (JWT)
GET	/api/organisations/assined/gps/devices/statistics	✅ GET /api/organisations/assined/gps/devices/statistics (JWT)
POST	/api/organisations/{id}/assign/gps/devices	✅ POST /api/organisations/:id/assign/gps/devices (JWT)
POST	/api/gps-devices/import	✅ POST /api/gps-devices/import (JWT)
GET	/api/gps-devices/export	✅ GET /api/gps-devices/export (JWT)
GET	/api/gps-devices	✅ GET /api/gps-devices (JWT)
POST	/api/gps-devices	✅ POST /api/gps-devices (JWT)
GET	/api/gps-devices/{gps_device}	✅ GET /api/gps-devices/:id (JWT)
PUT/PATCH	/api/gps-devices/{gps_device}	✅ PUT /api/gps-devices/:id (JWT)
DELETE	/api/gps-devices/{gps_device}	✅ DELETE /api/gps-devices/:id (JWT)

Plans

Method	Path	Node
GET	/api/plans-by-type	✅ GET /api/plans-by-type (JWT)
GET	/api/plans	✅ GET /api/plans (JWT)
POST	/api/plans	✅ POST /api/plans (JWT)
GET	/api/plans/{plan}	✅ GET /api/plans/:id (JWT)
PUT/PATCH	/api/plans/{plan}	✅ PUT /api/plans/:id (JWT)
DELETE	/api/plans/{plan}	✅ DELETE /api/plans/:id (JWT)

Central admin — app users

Method	Path	Node
GET	/api/app-users	✅ GET /api/app-users (JWT)
GET	/api/app-users/{id}	✅ GET /api/app-users/:id (JWT)
POST	/api/app-users/update/{id}	⚠️ POST /api/app-users/update/:id (JWT, multipart); also PUT /api/app-users/update/:id (JWT)
DELETE	/api/app-users/delete/{id}	✅ DELETE /api/app-users/delete/:id (JWT)
GET	/api/app-users/filters/options	✅ GET /api/app-users/filters/options (JWT)
GET	/api/app-users/stats/overview	✅ GET /api/app-users/stats/overview (JWT)

Central admin — travellers

Method	Path	Node
GET	`/api/travellers`	✅ `GET /api/travellers` (JWT)
GET	`/api/travellers/{id}`	✅ `GET /api/travellers/:id` (JWT)
POST	`/api/travellers/update/{id}`	⚠️ `POST /api/travellers/update/:id` (JWT, multipart); also `PUT /api/travellers/update/:id` (JWT)
DELETE	`/api/travellers/delete/{id}`	✅ `DELETE /api/travellers/delete/:id` (JWT)
GET	`/api/travellers/filters/options`	✅ `GET /api/travellers/filters/options` (JWT)
GET	`/api/travellers/stats/overview`	✅ `GET /api/travellers/stats/overview` (JWT)
GET	`/api/traveller/all/bookings/{id}`	✅ `GET /api/traveller/all/bookings/:id` (JWT)
GET	`/api/traveller/app/user/details/{traveller_uid}`	✅ `GET /api/traveller/app/user/details/:traveller_uid` (JWT)

Feedback (central)

Method	Path	Node
GET	`/api/feedbacks`	✅ `GET /api/feedbacks` (JWT)
GET	`/api/feedbacks/{id}`	✅ `GET /api/feedbacks/:id` (JWT)
PATCH	`/api/feedbacks/{id}/status`	✅ `PATCH /api/feedbacks/:id/status` (JWT)

Mobile

Method	Path	Node
POST	`/api/mobile/auth/firebase-login`	⚠️ `POST /api/mobile/auth/cognito-login`
GET	`/api/user/notifications/{userId}`	🔶 `GET /api/user/notifications/:userId` (JWT); stub `[]`

User-app prefix `/api/user-app`

Users

Method	Path	Node
GET	`/api/user-app/users`	✅ `GET /api/user-app/users`
POST	`/api/user-app/users`	✅ `POST /api/user-app/users`
GET	`/api/user-app/users/phone/{mobile_number}`	✅ `GET /api/user-app/users/phone/:mobile_number`
POST	`/api/user-app/users/phone/{mobile_number}/update`	✅ `POST /api/user-app/users/phone/:mobile_number/update`
GET	`/api/user-app/users/{id}`	✅ `GET /api/user-app/users/:id`
PUT	`/api/user-app/users/{id}`	✅ `PUT /api/user-app/users/:id`
POST	`/api/user-app/users/{id}`	✅ `POST /api/user-app/users/:id` (multipart)
DELETE	`/api/user-app/users/{id}`	✅ `DELETE /api/user-app/users/:id`
POST	`/api/user-app/users/delete/account`	✅ `POST /api/user-app/users/delete/account`

Travellers

Method	Path	Node
GET	`/api/user-app/travellers`	✅ `GET /api/user-app/travellers`
POST	`/api/user-app/travellers`	✅ `POST /api/user-app/travellers`
GET	`/api/user-app/travellers/{id}`	✅ `GET /api/user-app/travellers/:id`
PUT	`/api/user-app/travellers/{id}`	✅ `PUT /api/user-app/travellers/:id`
POST	`/api/user-app/travellers/{id}`	✅ `POST /api/user-app/travellers/:id` (multipart)
DELETE	`/api/user-app/travellers/{id}`	✅ `DELETE /api/user-app/travellers/:id`
GET	`/api/user-app/travellers/app-user/{userId}`	✅ `GET /api/user-app/travellers/app-user/:userId`

Trips — PHP uses `/api/user-app/trips/...`; **Node** omits `trips`:

Method	Path (PHP)	Node
GET	`/api/user-app/trips/trip-purposes`	⚠️ `GET /api/user-app/trip-purposes`
GET	`/api/user-app/trips/trip-purposes/{purpose}/pincodes`	⚠️ `GET /api/user-app/trip-purposes/:purpose/pincodes`
GET	`/api/user-app/trips/trip-purposes/{purpose}/organisations`	⚠️ `GET /api/user-app/trip-purposes/:purpose/organisations`
GET	`/api/user-app/trips/trip-purposes/{purpose}/{organisationId}/pickup-pincodes`	⚠️ `GET /api/user-app/trip-purposes/:purpose/:organisationId/pickup-pincodes`
GET	`/api/user-app/trips/trip-purposes/{purpose}/{organisationId}/pickup-locations`	⚠️ `GET /api/user-app/trip-purposes/:purpose/:organisationId/pickup-locations`

Bookings & tracking

Method	Path	Node
POST	`/api/user-app/bookings`	✅ `POST /api/user-app/bookings`
GET	`/api/user-app/travellers/pending/bookings/{traveller_uid}`	✅ `GET /api/user-app/travellers/pending/bookings/:traveller_uid`
GET	`/api/user-app/travellers/approved/bookings/{traveller_uid}`	✅ `GET /api/user-app/travellers/approved/bookings/:traveller_uid`
GET	`/api/user-app/travellers/{traveller_uid}/active-booking/check`	✅ `GET /api/user-app/travellers/:traveller_uid/active-booking/check`
GET	`/api/user-app/{userId}/travellers/active-bookings`	✅ `GET /api/user-app/:userId/travellers/active-bookings`
GET	`/api/user-app/vehicles/track/{vehicleNumber}/live/location/{tenantId}`	✅ `GET /api/user-app/vehicles/track/:vehicleNumber/live/location/:tenantId`
POST	`/api/user-app/send/feedback`	✅ `POST /api/user-app/send/feedback`

Web — tenant subdomain (`routes/tenant.php`)

Method	Path	Node
GET	`/`	❌
GET	`/dashboard`	❌

API — tenant (`routes/api_tenant.php` vs Node `/api/tenant`)

PHP: tenant host + path `/api/...`
Node: any host + path **`/api/tenant/...`** (+ `x-tenant-id` or tenant JWT)

Method	Path (PHP on tenant host)	Node
GET	`/api/`	✅ `GET /api/tenant/` (JWT)
POST	`/api/tenant-login`	⚠️ `POST /api/tenant/tenant-login`
GET	`/api/user`	⚠️ `GET /api/user` (JWT, central); or use tenant JWT payload
GET	`/api/refreshMe`	✅ `GET /api/tenant/refreshMe` (JWT)
GET	`/api/permissions`	✅ `GET /api/tenant/permissions` (JWT)
GET	`/api/roles`	✅ `GET /api/tenant/roles` (JWT)
POST	`/api/roles`	✅ `POST /api/tenant/roles` (JWT)
GET	`/api/roles/{role}`	✅ `GET /api/tenant/roles/:id` (JWT)
PUT	`/api/roles/{role}`	✅ `PUT /api/tenant/roles/:id` (JWT)
DELETE	`/api/roles/{role}`	✅ `DELETE /api/tenant/roles/:id` (JWT)

Employees

Method	Path (PHP)	Node
GET	`/api/employees`	✅ `GET /api/tenant/employees` (JWT)
POST	`/api/employees`	✅ `POST /api/tenant/employees` (JWT)
GET	`/api/employees/{employee}`	✅ `GET /api/tenant/employees/:id` (JWT)
PUT/PATCH	`/api/employees/{employee}`	✅ `PUT /api/tenant/employees/:id` (JWT)
DELETE	`/api/employees/{employee}`	✅ `DELETE /api/tenant/employees/:id` (JWT)

Vehicles

Method	Path (PHP)	Node
GET	`/api/vehicles`	✅ `GET /api/tenant/vehicles` (JWT)
POST	`/api/vehicles`	✅ `POST /api/tenant/vehicles` (JWT)
GET	`/api/vehicles/{vehicle}`	✅ `GET /api/tenant/vehicles/:id` (JWT)
PUT/PATCH	`/api/vehicles/{vehicle}`	✅ `PUT /api/tenant/vehicles/:id` (JWT)
DELETE	`/api/vehicles/{vehicle}`	✅ `DELETE /api/tenant/vehicles/:id` (JWT)

Drivers

Method	Path (PHP)	Node
GET	`/api/drivers`	✅ `GET /api/tenant/drivers` (JWT)
POST	`/api/drivers`	✅ `POST /api/tenant/drivers` (JWT)
GET	`/api/drivers/{driver}`	✅ `GET /api/tenant/drivers/:id` (JWT)
PUT/PATCH	`/api/drivers/{driver}`	✅ `PUT /api/tenant/drivers/:id` (JWT)
DELETE	`/api/drivers/{driver}`	✅ `DELETE /api/tenant/drivers/:id` (JWT)

Instructors

Method	Path (PHP)	Node
GET	`/api/instructors`	✅ `GET /api/tenant/instructors` (JWT)
POST	`/api/instructors`	✅ `POST /api/tenant/instructors` (JWT)
GET	`/api/instructors/{instructor}`	✅ `GET /api/tenant/instructors/:id` (JWT)
PUT/PATCH	`/api/instructors/{instructor}`	✅ `PUT /api/tenant/instructors/:id` (JWT)
DELETE	`/api/instructors/{instructor}`	✅ `DELETE /api/tenant/instructors/:id` (JWT)

Travellers

Method	Path (PHP)	Node
GET	`/api/travellers`	✅ `GET /api/tenant/travellers` (JWT)
POST	`/api/travellers`	❌ (no `POST /api/tenant/travellers` on Node)
GET	`/api/travellers/{traveller}`	✅ `GET /api/tenant/travellers/:id` (JWT)
PUT/PATCH	`/api/travellers/{traveller}`	✅ `PUT /api/tenant/travellers/:id` (JWT)
DELETE	`/api/travellers/{traveller}`	❌ (no `DELETE /api/tenant/travellers/:id` on Node)
POST	`/api/travellers/update/{id}`	⚠️ `PUT /api/tenant/travellers/:id` (JWT)

Bookings

Method	Path (PHP)	Node
GET	`/api/bookings`	✅ `GET /api/tenant/bookings` (JWT)
POST	`/api/bookings`	✅ `POST /api/tenant/bookings` (JWT)

Method	Path (PHP)	Node
GET	`/api/bookings/{booking}`	✅ `GET /api/tenant/bookings/:id` (JWT)
PUT/PATCH	`/api/bookings/{booking}`	✅ `PUT /api/tenant/bookings/:id` (JWT)
DELETE	`/api/bookings/{booking}`	✅ `DELETE /api/tenant/bookings/:id` (JWT)

Vehicle tracking & dropdowns

Method	Path (PHP)	Node
GET	`/api/vehicles/live/location/{tenantId}`	✅ `GET /api/tenant/vehicles/live/location/:tenantId` (JWT)
GET	`/api/vehicles/track/{vehicleNumber}/live/location/{tenantId}`	✅ `GET /api/tenant/vehicles/track/:vehicleNumber/live/location/:tenantId` (JWT)
GET	`/api/active-vehicles/for/dropdown`	✅ `GET /api/tenant/active-vehicles/for/dropdown` (JWT)
GET	`/api/beacon-device/for/dropdown`	✅ `GET /api/tenant/beacon-device/for/dropdown` (JWT)
GET	`/api/gps-device/for/dropdown`	✅ `GET /api/tenant/gps-device/for/dropdown` (JWT)

Console

`routes/console.php` defines Artisan commands only (e.g. `inspire`), not HTTP routes — **N/A** for Node comparison.