



*Erk IRC Client, Version 0.860*

# Erk Plugin Guide

A guide for using and writing plugins for the Erk IRC Client

**<https://github.com/nutjob-laboratories/erk>**

<b>Ərk Plugin Guide.....</b>	<b>1</b>
<b>Summary.....</b>	<b>3</b>
<b>Using Ərk Plugins.....</b>	<b>4</b>
<b>Writing Ərk Plugins.....</b>	<b>5</b>
<b>Plugin Requirements.....</b>	<b>5</b>
<b>Event Methods.....</b>	<b>6</b>
line_in.....	6
line_out.....	6
public.....	6
private.....	6
action.....	6
mode.....	7
tick.....	7
input.....	7
notice.....	7
motd.....	8
registered.....	8
join.....	8
part.....	8
joined.....	8
parted.....	8
kick.....	9
kicked.....	9
<b>Plugin Built-In Tools.....</b>	<b>10</b>
irc Object.....	10
Built-In Methods.....	10
console.....	10
exec.....	11
print.....	11
script.....	11
write.....	11
<b>Miscellany.....</b>	<b>12</b>

## Summary

Ərk plugins are Python 3 classes that inherit from a base class, named “Plugin”, that is imported from the Ərk application. They are loaded from a subdirectory in the main directory where Ərk stores settings and scripts, **.erk/plugins**, located in the user’s home directory.

A basic plugin looks something like this:

```
from erk import *

class DumpPlugin(Plugin):
    name = "Dump Plugin"
    version = "1.0"
    description = "Displays all IRC network traffic"

    def input(self,data):
        print("<- "+data)

    def output(self,data):
        print("-> "+data)
```

If this was saved to a file and placed in **.erk/plugins**, the next time Ərk is started, it would load the plugin and appear in Ərk’s “Plugins” menu like so:



Once loaded, the plugin would print all network traffic, both input and output, from all servers that Ərk is connected to, to the console.

## Using Ərk Plugins

To install an Ərk plugin, simply place it in the **.erk/plugins** directory in your home directory. The next time Ərk starts up, the plugin will be loaded automatically. If there are major errors in the plugin (for example, improper Python code), Ərk will not start, and any errors will be printed to the console. If there are minor errors (for example, if plugins are missing needed attributes), Ərk will start normally, and any errors will be displayed to the user in a dialog window. Plugins with minor errors will *not* be loaded into the client, and, thus, will be ignored by Ərk.

Uninstalling Ərk plugins is as easy as deleting the plugin from **.erk/plugins**. No other steps are required.

# Writing Ærk Plugins

## Plugin Requirements

Ærk plugins are Python 3 classes that must meet four basic requirements:

- The class must inherit from the base class **Plugin**
- The class must have a **name** attribute string
- The class must have a **version** attribute string
- The class must have at least one event method

To get access to the first requirement, simply import **Plugin** from **erk**. You can either explicitly import **Plugin**:

```
from erk import Plugin
```

or use a “splat” and import it implicitly:

```
from erk import *
```

The end result is the same either way; the only thing exported by **erk** is **Plugin**.

The second two requirements, the **name** and **version** attributes, are used by Ærk to display the plugin in the client (see page 3). These should be class attributes, rather than instance attributes<sup>1</sup>. **name** should be set to the name of the plugin, a short descriptive string; it must contain at least one character that is not whitespace. **version** should be the version number of the plugin; if no version number is required, this attribute can be set to a blank string, but it *must* exist. A third attribute, **description**, is optional; this should be a short string that describes what the plugin does.

The last requirement is for the plugin to have at least one event method. An event method is a plugin method that Ærk will execute when a specific event occurs (see *Event Methods* on page 6).

---

<sup>1</sup> <https://www.geeksforgeeks.org/class-instance-attributes-python/>

## Event Methods

Θrk executes the event method of every plugin that contains that event method when a specific event occurs (like the reception of a public message, a private message, or a notice message). In short, Θrk plugins are event-driven<sup>2</sup>.

### line\_in

Arguments	<b>data</b> (string)
Description	Triggered every time Θrk receives data from an IRC server. <b>data</b> contains the data sent to the client.

### line\_out

Arguments	<b>data</b> (string)
Description	Triggered every time Θrk sends data to an IRC server. <b>data</b> contains the data sent to the server.

### public

Arguments	<b>channel</b> (string), <b>user</b> (string), <b>message</b> (string)
Description	Triggered every time Θrk receives a public message. <b>channel</b> contains the name of the channel the message was sent to, <b>user</b> contains the nickname, username, and hostname of the user that sent it (in the format <b>nickname!username@hostname</b> ), and <b>message</b> contains the contents of the message.

### private

Arguments	<b>user</b> (string), <b>message</b> (string)
Description	Triggered every time Θrk receives a private message. <b>user</b> contains the nickname, username, and hostname of the user that sent it (in the format <b>nickname!username@hostname</b> ), and <b>message</b> contains the contents of the message.

### action

Arguments	<b>target</b> (string), <b>user</b> (string), <b>message</b> (string)
Description	Triggered every time Θrk receives a CTCP action message. <b>target</b> contains the target of the message (if it's a public message, <b>target</b> will contain the name of the channel the message was sent to, and if it's a private message, <b>target</b> will contain the nickname the Θrk client is using), <b>user</b> contains the nickname, username, and hostname of the user that sent it (in the format <b>nickname!username@hostname</b> ), and <b>message</b> contains the contents of the message.

---

<sup>2</sup> [https://en.wikipedia.org/wiki/Event-driven\\_programming](https://en.wikipedia.org/wiki/Event-driven_programming)

## mode

Arguments	<b>channel</b> (string), <b>user</b> (string), <b>mset</b> (bool), <b>modes</b> (string), <b>args</b> (list)
Description	Triggered every time Ɖrk receives a mode message. <b>channel</b> contains the name of the channel the message was sent to, <b>user</b> contains the nickname, username, and hostname of the user that sent it (in the format <b>nickname!username@hostname</b> ), <b>mset</b> is True if a mode is being set and False if a mode is being removed/unset, <b>modes</b> contains the mode(s) being set, and <b>args</b> contains a list of the arguments to the mode being set/unset.

## tick

Arguments	<b>uptime</b> (integer)
Description	Triggered once every second that Ɖrk is connected to a server. <b>uptime</b> is the length of the connection to the server in seconds. Timers are specific to each connection; each server connection's tick event is independent of all the other server connections.

## input

Arguments	<b>name</b> (string), <b>text</b> (string)
Description	Triggered every time a user types something into Ɖrk's text input widget. <b>name</b> is the name of the window where the text was entered (a channel name for a public chat window, or a nickname for a private chat window), and <b>text</b> is the text that was entered. If the text was entered into a server console window, name will be set to <b>None</b> . If the user has implemented any macros, they will be interpolated into the text <i>before</i> being handed to this method. To stop Ɖrk from processing the user input, return <b>True</b> from this method; to allow Ɖrk to continue to work with the input text, return <b>False</b> or nothing. As it would be very easy to write a malicious plugin that would disable <i>any</i> input, Ɖrk will try to detect malicious <b>input()</b> methods and prevent the plugin that contains them from being loaded.

## notice

Arguments	<b>target</b> (string), <b>user</b> (string), <b>message</b> (string)
Description	Triggered every time Ɖrk receives a notice message. <b>target</b> contains the name of the target the message was sent to (either a channel or your nickname), <b>user</b> contains the nickname, username, and hostname of the user that sent it (in the format <b>nickname!username@hostname</b> ), and <b>message</b> contains the contents of the message.

## motd

Arguments **message** (list)

Description Triggered when  rk receives the message of the day (MOTD) from an IRC server. **message** contains the MOTD, with each entry consisting of one line.

## registered

Arguments None

Description Triggered when  rk completes connecting to an IRC server.

## join

Arguments **channel** (string), **user** (string)

Description Triggered every time another user joins a channel that the  rk client is "present" in. **channel** contains the channel the user joined, and **user** contains the nickname, username, and hostname of the user that joined (in the format **nickname!username@hostname**).

## part

Arguments **channel** (string), **user** (string)

Description Triggered every time another user leaves a channel that the  rk client is "present" in. **channel** contains the channel the user left, and **user** contains the nickname, username, and hostname of the user that left (in the format **nickname!username@hostname**).

## joined

Arguments **channel** (string)

Description Triggered whenever  rk joins a channel. **channel** contains the channel that the client joined.

## parted

Arguments **channel** (string)

Description Triggered whenever  rk leaves a channel. **channel** contains the channel that the client left.



## **kick**

Arguments	<b>channel</b> (string), <b>kickee</b> (string), <b>kicker</b> (string), <b>message</b> (string)
Description	Triggered whenever a user is kicked from a channel $\Theta$ rk is "present" in. <b>channel</b> contains the channel the user was kicked from, <b>kickee</b> contains the nickname of the user that was kicked out of the channel, <b>kicker</b> contains the nick of the user that kicked the user out, and <b>message</b> contains the message attached to the kick notification.

## **kicked**

Arguments	<b>channel</b> (string), <b>kicker</b> (string), <b>message</b> (string)
Description	Triggered whenever $\Theta$ rk is kicked from a channel. <b>channel</b> contains the channel the client was kicked from, <b>kicker</b> contains the nick of the user that kicked the client out, and <b>message</b> contains the message attached to the kick notification.

## Plugin Built-In Tools

The **Plugin** class contains some built-in methods and the **irc** object to make interacting with the Ærk client and any connected IRC servers easy.

### irc Object

The **irc** object is part of the **Plugin** class, and is the way plugins interact with IRC servers. It is integrated as an instance attribute of the class. This object is the instance of the Twisted IRC client<sup>3</sup> that Ærk is using for communication with the IRC server. Anything you can normally do with the Twisted IRC client, you can use **irc** for. Whenever an event method is triggered, the **irc** object is set to the Twisted instance that is connected to the server event that triggered the method. So, for example, if you wanted to write a private event method that forwards all private messages to another user with the nickname "OtherNick", you could write:

```
def private(user,message):  
    self.irc.msg("OtherNick",user+": "+message)
```

If the **irc** object is unavailable (due to a disconnection, error, or other reason), the object's value is set to **None**.

For help on how to use the **irc** object, take a look at the documentation for the Twisted IRC Client<sup>4</sup>.

### Built-In Methods

The Plugin class also comes with several methods built into it. These methods are used to interact with the Ærk graphical user interface (GUI).

#### console

Arguments	<b>text</b> (string)
Returns	Nothing
Description	Prints <b>text</b> to the window associated with the current server connection, called the "console".

---

<sup>3</sup> `twisted.words.protocols.irc.IRCClient`

<sup>4</sup> <https://twistedmatrix.com/documents/current/api/twisted.words.protocols.irc.IRCClient.html>

## **exec**

Arguments	<b>text</b> (string)
Returns	Nothing
Description	Executes the contents of <b>text</b> as if it were entered into the text input widget in the Ærk client. This allows plugins to execute miscellaneous scripting commands (see <i>Erk Scripting and Commands</i> for more information). If <b>text</b> does not contain a command, it will be sent to the currently open window as chat.

## **print**

Arguments	<b>text</b> (string), ...
Returns	Nothing
Description	Prints <b>text</b> to the currently open window; if the currently open window can't be found, then the text will print to the console. To print multiple items in the same command, separate the strings to print with commas (much like Python's <b>print</b> function).

## **script**

Arguments	<b>filename</b> (string), <b>arguments</b> (list)
Returns	Nothing
Description	Executes the contents of <b>filename</b> as an Ærk script. This functions exactly like the Ærk command <b>/script</b> (see <i>Erk Scripting and Commands</i> ).

## **write**

Arguments	<b>target</b> (string), <b>text</b> (string)
Returns	Bool
Description	Prints <b>text</b> to the window with <b>target</b> as its name. Windows are named after the chat they display; so, for example, the window displaying channel chat for #erk would be named "#erk". The window displaying private chat with a user named "Bob" would be named "Bob". If the window was found and the text was written to it, <b>write</b> will return <b>True</b> ; if the window was <i>not</i> found, <b>write</b> will return <b>False</b> .

## Miscellany

Users that have been ignored with the **/ignore** command or through the GUI (see *Erk Scripting and Commands* for more information) will not trigger the **private** (page 6), **public** (page 6) , **notice** (page 7), and **action** (page 6) events. Any messages sent from ignored users to the client are completely ignored.