

Erkle IRC Library

Erkle is an event-driven IRC library for Python 3. Functions can be "hooked" to a specific event by using a function decorator named **hook**.

Requirements

Erkle uses, for the most part, only modules that are included by default with Python. To use SSL to connect to IRC servers, however, the *pyOpenSSL*¹ library must be installed. To install this library via pip, execute this command:

```
pip install pyOpenSSL
```

Example usage

```
from erkle import *

@hook.event("welcome")
def welcome(connection):
    connection.join("#erklelib")

@hook.event("join")
def cjoin(connection, nickname, host, channel):
    connection.msg(channel, "Hello world!")
    connection.quit()

bot = ErkleClient("mybot", "mybot", "Erkle Bot", "irc.efnet.org", 6667)
bot.connect()
```

ErkleClient

ErkleClient is an object that creates and manages an IRC connection. *ErkleClient* can take seven arguments:

Argument	Type	Description
nickname	<i>string</i>	Sets the nickname the IRC client connection will use.
username	<i>string</i>	Sets the username the IRC client connection will use.
realname	<i>string</i>	Sets the realname the IRC client connection will use.
server	<i>string</i>	Sets the IP/hostname of the IRC server to connect to.
port	<i>integer</i>	Sets the port on the IRC server to connect to. <i>Default: 6667</i>
password	<i>string</i>	Sets the password the IRC client connection will send to the server if required. <i>Default: empty string</i>
SSL	<i>boolean</i>	Sets whether to use SSL to connect to the IRC server; set to True to use SSL. <i>Default: False</i>

¹ <https://www.pyopenssl.org>

Once the *ErkleClient* object is created, use the **connect()** function to cause the object to connect to the IRC server. Once connected, *ErkleClient* has 6 other methods that can be used to send messages or perform actions on the IRC server. Optional arguments are in italics:

Method	Arguments	Description
connect	<i>None.</i>	Connects to the IRC server.
send	<ul style="list-style-type: none">• data (string)	Sends a "raw" message to the IRC server; the message will not be processed in any way before being sent.
msg	<ul style="list-style-type: none">• target (string)• message (string)	Sends a chat message to a channel or user.
action	<ul style="list-style-type: none">• target (string)• message (string)	Sends a CTCP action message to a channel or user.
join	<ul style="list-style-type: none">• channel (string)• key (string)	Joins a channel.
part	<ul style="list-style-type: none">• channel (string)• reason (string)	Leaves a channel.
quit	<ul style="list-style-type: none">• reason (string)	Disconnects from the IRC server.

hook Decorator

Included with the *ErkleClient* object is the *hook* object. The *hook* object is used to decorate² functions that should be executed when specific events occur; this is called "hooking" an event. *hook* exposes one method: **event**. To hook an event, pass the name of the event (as a string) as the only argument to **event** method. For example, to hook an event named "connect", the decorator required would look like:

```
@hook.event("connect")
```

Events can be hooked to an unlimited number of functions. Function hooks will be executed in the order in which they were hooked.

There are 16 IRC events that can be hooked. The hooked function can take a number of different arguments, depending on the event. The first (and sometimes only) argument passed to every hooked function is **connection**, which is the *ErkleClient* object running the IRC connection.

Event	Arguments	Description
connect	<ul style="list-style-type: none">• ErkleClient object	Triggered when the <i>ErkleClient</i> object connects to IRC.
motd	<ul style="list-style-type: none">• ErkleClient object• message (string)	Triggered when the server's message of the day (MOTD) is received.

² <https://www.python.org/dev/peps/pep-0318/>

welcome	<ul style="list-style-type: none"> • ErkleClient object 	Triggered when registration with the IRC server is complete.
nick-taken	<ul style="list-style-type: none"> • ErkleClient object • nickname (string) 	Triggered when the client's nickname is already taken during registration; nickname contains the new nickname.
ping	<ul style="list-style-type: none"> • ErkleClient object 	Triggered when the IRC server sends <i>ErkleClient</i> a PING command.
join	<ul style="list-style-type: none"> • ErkleClient object • nickname (string) • host (string) • channel (string) 	Triggered whenever a user joins a channel the client is in. nickname contains the user's nickname, host contains the user's host, and channel contains the name of the channel joined. This event will trigger when the <i>ErkleClient</i> object joins a channel as well.
part	<ul style="list-style-type: none"> • ErkleClient object • nickname (string) • host (string) • channel (string) • reason (string) 	Triggered whenever a user leaves a channel the client is in. nickname contains the nickname of the user, host contains the user's host, channel contains the name of the channel, and reason contains the reason why the user quit. If no reason has been provided, reason will be set to None .
quit	<ul style="list-style-type: none"> • ErkleClient object • nickname (string) • host (string) • reason (string) 	Triggered when a user quits the IRC server. nickname contains the user's nickname, host contains the user's host, and reason contains the reason why the user quit. If no reason has been provided, reason will be set to None .
nick	<ul style="list-style-type: none"> • ErkleClient object • nickname (string) • host (string) • new_nickname (string) 	Triggered when a user changes their nickname. nickname contains the user's original nickname, host contains the user's host, and new_nickname contains the user's new nickname.
names	<ul style="list-style-type: none"> • ErkleClient object • channel (string) • users (list) 	Triggered when <i>ErkleClient</i> generates a list of users in a specific channel. This list will be regenerated every time a user changes their nick, quits IRC, or leaves a channel. channel contains the name of the channel, and users contains a list of users in that channel.
public	<ul style="list-style-type: none"> • ErkleClient object • nickname (string) • host (string) • channel (string) • message (string) 	Triggered when <i>ErkleClient</i> receives a public message. nickname contains the sender's nickname, host contains the sender's host, channel contains the name of the channel the message was sent to, and message contains the message contents.
private	<ul style="list-style-type: none"> • ErkleClient object • nickname (string) • host (string) • message (string) 	Triggered when <i>ErkleClient</i> receives a private message. nickname contains the sender's nickname, host contains the sender's host, and message contains the message contents.
notice	<ul style="list-style-type: none"> • ErkleClient object • sender (string) • message (string) 	Triggered when <i>ErkleClient</i> receives a notice message. sender contains the nickname of the sender, and message contains the message contents.

action	<ul style="list-style-type: none"> • ErkleClient object • nickname (string) • host (string) • target (string) • message (string) 	Triggered when <i>ErkleClient</i> receives a CTCP action message. nickname contains the sender's nickname, host contains the sender's host, target contains the name of the channel or username the message was sent to, and message contains the message contents.
away	<ul style="list-style-type: none"> • ErkleClient object • nickname (string) • reason (string) 	Triggered when <i>ErkleClient</i> receives an "away" notification.
back	<ul style="list-style-type: none"> • ErkleClient object 	Triggered when <i>ErkleClient</i> unsets itself as "away".

ErkleClient's `connect()` is a blocking function, so hooked functions should be declared before `connect()` is called.

Examples

Greeter Bot

Here's an example bot that connect to an IRC server, join a channel, and greet everyone who joins that channel by name:

```
from erkle import *

SERVER = "irc.efnet.org"
PORT = 6667
CHANNEL = "#erklebot"

@hook.event("welcome")
def welcomed(connection):
    connection.join(CHANNEL)

@hook.event("join")
def joined(connection, nickname, host, channel):
    connection.msg("Welcome to "+CHANNEL+", "+nickname+"!")

bot = ErkleClient("greetbot", "greetbot", "Erkle Bot", SERVER, PORT)
bot.connect()
```

...