# PACE: Priced Adaptive Control for Evolving Harnesses

Navid Mehrdad

October 2026

**Abstract**

Agent harnesses contain per-request decisions that nobody prices: which model tier answers, whether a step is verified, whether an answer is refined, which specialist is delegated to. Recent work evolves the harness at design time or trains the orchestrator with an outcome-only reward; we study the complementary runtime problem. The harness is frozen within a generation, and a small, cost-priced controller is learned at its decision points from logged traffic. Three pieces make this deployable: a policy trained offline under a budget whose price is a learned Lagrange multiplier; an off-policy promotion gate that admits a candidate only when doubly-robust estimates with bootstrap intervals clear a quality floor and a cost cap on logged traffic; and priced backward- and forward-transfer metrics for the harness changing underneath the controller. On CRMArena-Pro (300 B2B and 150 B2C tasks, every task on three tiers) the learned policy has a higher priced value than every fixed tier held-out, with higher quality than the frontier tier at 40% lower cost on B2B; the gate's decision depends on the logged draw, with an interval that narrows as $1/\sqrt{n}$ in the number of logged tasks, and two further suites, $\tau$-bench and EvoHarnessBench's hosted service, reproduce the tier-level picture. A continually trained orchestrator over a growing harness has the lowest regret of every learned arm and bounded, mostly positive transfer. Negative results on multi-agent decomposition, process verification, self-refinement and a language-model controller trained by group-relative policy optimisation (GRPO) are reported as results, each with its cause.

## 1 Introduction

An agent harness is the scaffold around a model: the loop that decides which tool runs next, which model answers, whether a step is checked, when the episode ends. Inside that loop sit decisions made per request by a rule somebody wrote: "always use the large model", "verify every sub-result", "refine if confidence is low". Each decision has a price in dollars and latency, and each is made without reference to that price. Figure 1 shows where these decisions sit and what this paper puts around them.

Two lines of recent work optimise the harness rather than the request. The design-time line evolves the harness itself: the Darwin Gödel Machine [46], GEPA [2], DarwinX [47], Meta-Harness [21], EnvHarness [12] and HarnessX [6] search over designs, and EvoHarnessBench [16] grows a harness $H_t = \{\text{tools}, \text{skills}, \text{specialist agents}\}$ by stages and measures what a fixed agent policy forgets or gains, reporting $-34.7\%$ backward transfer from agent-pool expansion alone. The orchestrator-training line trains the policy that assembles the system. MAS-Orchestra [15] generates a complete multi-agent system in one step and optimises the generator with an outcome-only reward; it reports that this holistic formulation outperforms stepwise orchestration, in which an orchestrator chooses one tool or model call at a time [34], and attributes the gap to long-horizon credit assignment under a single terminal reward. Orchestration reward modelling [39] then takes the sub-agents out of the training loop by scoring the plan before it is executed, and MAS-ProVe [40] works at the other end, verifying each agent call or iteration as it happens, and reports that such process verification helps inconsistently and at high variance.

This paper takes the opposite route to the same difficulty. The decisions are per-step and priced, as in the stepwise setting, and control, logging and evaluation are per decision: every served decision logs its propensity (the probability with which it was chosen), the objective is quality minus a learned price of cost, the trainer anchors each of its groups at a logged decision point, and a candidate policy is valued on logged traffic, which it did not generate, by doubly-robust estimators with bootstrap intervals before it is promoted. This does not by itself attribute an outcome to one decision: within a sampled continuation every decision receives the same advantage, and attribution comes from averaging over many groups anchored at different points (Section 3.2). Holistic generation avoids the credit-assignment problem by removing the steps; the controller here keeps the steps, pays for them with replay and off-policy estimators, and treats per-step verification as one more priced action whose value is estimated rather than assumed. ToolOrchestra's efficiency term is, to our knowledge, the closest prior use of a priced orchestration reward; it is an episode-level reward without





**Figure 1: PACE.** A frozen harness exposes one decision point per step (which operation, on which model tier). A trace logger records every decision with its propensity and realised cost. A small controller is trained offline from that log under a learned price $\lambda$; an off-policy gate scores each candidate on the logged traffic and promotes or reverts it; drift events (a repricing, a new version, a grown harness) are measured by priced transfer. Within a generation nothing in the model weights or the harness structure moves.

a per-decision estimator or a promotion gate, and the stepwise result reported for it by Ke et al. [15] is a transplanted baseline, so the comparison of the two formulations under a common price remains open.

**Contributions.**

- **A priced controller** (Section 3): a policy over (op, tier) pairs whose objective is quality minus a learned price of cost, trained offline by a constrained group-relative policy gradient on replay (the group-baseline variant of GRPO, without ratio clipping or a reference term), the Lagrange multiplier found by damped dual ascent against a per-task budget and the served policy an iterate average whose budget is measured rather than inherited.
- **An off-policy promotion gate**: per-decision inverse-propensity (IPS), self-normalised (SNIPS) and doubly-robust (DR) estimators with cross-fitted direct models and percentile-bootstrap intervals, and a two-bar decision rule on the interval edges. We measure its promotion rate, interval width and empirical coverage against sample size on real agent logs rather than assuming them.
- **Priced transfer metrics**: backward and forward transfer in the sense of Lopez-Paz and Ranzato [23], applied to the controller's priced objective as the harness is repriced, re-versioned or grown.
- **Measurements on four suites** (Section 4): 450 CRMArena-Pro tasks on three tiers each, $\tau$-bench retail and airline, three stages of EvoHarnessBench's hosted service, and a 40-day continual-orchestrator study over a frozen, growing harness, together with negative results on decomposition, verification, refinement and LLM controllers, each with its cause stated.

**What the measurements say.** On CRMArena-Pro the learned per-category policy has a higher priced value at $\lambda = 2$ per dollar than every fixed tier (a cheap, mid or frontier model used for every task) held-out, and on B2B it has higher quality than the frontier tier at 40% lower cost (0.644 at \$0.079 against 0.614 at \$0.131); on the B2C organisation it matches the frontier tier's quality within 0.002 at 43% lower cost. The gate's decision on a realised one-arm log depends on the draw, promoting in 30% of redraws at 300 tasks, and its interval narrows as $1/\sqrt{n}$ in the number of logged tasks, as measured from 150 to 300; resolving a half-cent budget margin is a matter of one to two thousand tasks. On $\tau$-bench and EvoHarnessBench the mid tier matches or beats the frontier tier at about half its cost and the per-task oracle (the best tier for each task in hindsight) beats every tier, while a first-step controller has nothing to condition on in $\tau$-bench. The continual orchestrator has the lowest regret of every learned arm, recovers after every harness stage, and has bounded, mostly positive transfer; a fixed mode beats it over the whole stream because of a twelve-day cold start, the days before the gate's first promotion during which the exploration policy is served. The negative results share one cause: in every experiment the limiting factor was the signal available at the decision point, not the learner. Every

number in this paper is taken from the committed result files of the public repository.[1]

## 2 Related work

**Cost-aware routing.** FrugalGPT [5] cascades models by a learned score; RouteLLM [26] learns a router between a strong and a weak model from preference data, and xRouter [29] trains a cost-aware orchestration system with reinforcement learning. These choose a model per query at the first turn and are evaluated by accuracy at a cost. The controller here is a per-step policy with a learned price, served through a gate and evaluated under drift. SkillOrchestra [41] routes to a typed agent in a pool by a learned competence profile with an explicit cost penalty, learned once from traces; it is a design-time baseline in the continual study (Section 4.3).

**Harness evolution and orchestrator training.** The design-time line [2, 6, 12, 21, 46, 47] and EvoHarnessBench [16] evolve or grow the harness. This paper freezes the harness within a generation, learns inside it, and measures what the controller keeps across generations with the transfer definitions of Lopez-Paz and Ranzato [23]. MAS-Orchestra [15], orchestration reward modelling [39], MAS-ProVe [40] and ToolOrchestra [34] are positioned in Section 1; the multi-agent experiment of Appendix D measures MAS-Orchestra's compute-matched single-agent bar and MAS-ProVe's process-verification finding on one priced log.

**Off-policy evaluation and bandits in production.** The Decision Service [1] and Horizon [10] established the logging discipline used here: propensities with exploration, and counterfactual evaluation before deployment. The estimators are the per-decision importance sampling of Precup et al. [28], self-normalised importance sampling [35], and the doubly-robust estimators of Dudík et al. [8] and Jiang and Li [14], with the cross-fitting of Chernozhukov et al. [7]. The contribution here is the gate as a deployment rule and the measurement of its power on real agent logs.

**Self-evolving agents, test-time compute, and constrained and offline RL.** A position paper from the AReaL group [42] names an evolution control plane that chooses among memory, skill, harness and weight updates behind replay-first evaluation; Agent Lightning [24] exposes the proxy seam that makes per-call logging possible; recursive agent optimisation [9] prices delegation effort. Socratic self-refinement [32] and test-time scaling are purchases of compute whose value we measure under a budget (Appendix E). The trainers draw on constrained RL [33, 37], GRPO [31] and DAPO [45], and on offline RL [18, 19, 27]. Appendix K discusses each of these lines at length.

## 3 Method

### 3.1 The harness as a frozen, priced decision process

A harness exposes, at each step $t$ of an episode on task $x$, an observable state $s_t$ and a legal set $\mathcal{A}(s_t)$ of actions $a = (\text{op}, \text{tier})$: an operation the harness can run (for example continue, answer, retrieve, verify, refine, escalate, delegate, re-plan, call a tool or engage a skill; each host exposes its own set of two to six, listed in Appendix N) on a model tier (cheap, mid, frontier; in every experiment here `claude-haiku-4-5`, `claude-sonnet-5-5` and `claude-opus-5-5` at their list prices, Table 26). The harness's own transition $s_{t+1} \sim P_H(\cdot \mid s_t, a_t)$ is fixed; the controller $\pi(a \mid s)$ only chooses among what is legal. Each step has a realised cost $c_t$ (tokens times the provider's published per-token price, the list price) and latency $\ell_t$, and the episode ends with a quality $q \in [0, 1]$ that is the harness's own score. We write $C = \sum_t c_t$ and $L = \sum_t \ell_t$. The harness is therefore a frozen Markov decision process over the controller's decision points, and the controller is the only thing trained. Figure 2 places this inside the two outer layers that do not move: the model weights, frozen throughout, and the harness structure, frozen within a generation (one version of its tools, prompts, agent pool and prices) and changed only between generations.

**Priced objective.** A product specification is a budget, so the objective, which we call the priced value, is

$$J(\pi) = \mathbb{E}_\pi[q] - \lambda\, \mathbb{E}_\pi[C] - \mu\, \mathbb{E}_\pi[L], \tag{1}$$

with $\mu = 0$ in every experiment reported here (latency is logged but not priced), and the constrained form

$$\max_\pi \ \mathbb{E}_\pi[q] \quad \text{s.t.} \quad \mathbb{E}_\pi[C] \le B, \qquad \mathcal{L}(\pi, \lambda) = \mathbb{E}_\pi[q] - \lambda\big(\mathbb{E}_\pi[C] - B\big),\ \lambda \ge 0. \tag{2}$$

The price $\lambda$ is learned by projected dual ascent on an exponential moving average $\hat{c}$ of realised episode cost, with a proportional damping term (the PID-Lagrangian of Stooke et al. [33] without its derivative term; cf. RCPO [37]):

$$\hat{c}_k = \rho\, \hat{c}_{k-1} + (1-\rho)\, \bar{C}_k, \qquad \lambda^{\text{int}}_k = \big[\lambda^{\text{int}}_{k-1} + \eta\,(\hat{c}_k - B)\big]_+, \qquad \lambda_k = \big[\lambda^{\text{int}}_k + k_p\,(\hat{c}_k - B)\big]_+. \tag{3}$$

[1] https://github.com/nvdm59/PACE-Harness





**Figure 2: Three layers, two loops.** Model weights are frozen. The harness structure $H_t$ (tools, skills, agent pool, prices) is frozen within a generation and changes between generations at design time. The controller is the only layer that learns, in two loops: a serve-time loop (log, train, gate, serve) inside a generation, and a design-time loop across generations, in which priced backward and forward transfer measure what the controller keeps when $H_t$ becomes $H_{t+1}$.

Primal–dual iterates orbit the budget rather than converging to it, so the served policy is the statewise iterate average $\bar{\pi}(a \mid s) = \frac{1}{|\mathcal{S}|} \sum_{W \in \mathcal{S}} \pi_W(a \mid s)$ over weight snapshots $\mathcal{S}$ from the second half of training [25], and $\bar{\lambda}$ is the mean price over the same half. The averaging is of action probabilities at each state, not a choice of one snapshot per episode. For a one-decision bandit the two coincide and the mixture's expected quality and cost are the averages of the snapshots'. In a multi-step harness they are not in general: a statewise average can visit state sequences that no snapshot follows, so a budget met by every snapshot is not inherited by their average (Appendix M.1 gives a two-step counterexample). The budget of the served mixture is therefore measured on the served log, not inferred from training, and the greedy decoding of a mixture is reported as a separate policy with its own measured cost.

### 3.2 Controller and trainer

**Policy class and logged propensities.** The linear controller is a softmax over soft-clipped logits, mixed with $\epsilon$-exploration:

$$z = L \tanh\big(Wx/L\big), \qquad \pi_\epsilon(a \mid x) = (1-\epsilon)\,\mathrm{softmax}_{\mathcal{A}}(z)_a + \frac{\epsilon}{|\mathcal{A}|}, \tag{4}$$

where $x = \phi(s)$ is a feature vector and the softmax runs over the legal set. The logit clip keeps the softmax steerable by $\lambda$ and keeps importance ratios bounded. The propensity written to the log is $\mu_t = \pi_\epsilon(a_t \mid x_t)$, exploration included, so every served log is usable for off-policy evaluation, the logging discipline of Bottou et al. [4] and Li et al. [22]. A small language model can take the place of the linear policy (Appendix C); the logging contract is the same.

**Constrained GRPO on replay.** When the harness can be re-rolled from a logged state (a simulator, or a counterfactual lookup table in which every arm of every task is logged), training samples a logged state $s$, draws a group of $G$ continuations from the policy *as served* ($\pi_\epsilon$, so that the cost the dual variable tracks is the served cost), scores each by $R_i = q_i - \lambda C_i$, and uses the group-relative advantage with the group mean as baseline [31]:

$$A_i = R_i - \frac{1}{G}\sum_{j=1}^{G} R_j, \qquad \nabla_W \mathcal{L} = \sum_i A_i \sum_t \nabla_W \log \pi_\epsilon(a_t^i \mid x_t^i), \tag{5}$$

$$\nabla \log \pi_\epsilon(a \mid x) = \frac{(1-\epsilon)\,\pi(a \mid x)}{\pi_\epsilon(a \mid x)}\,\nabla \log \pi(a \mid x). \tag{6}$$

The last factor is the score correction for the $\epsilon$-mixture: the gradient of the mixed policy is the bare softmax's score, scaled by the share of the served probability that the softmax contributes. Two properties of this update are worth making explicit. It is the on-policy group-baseline variant of GRPO [31]: no ratio clipping and no reference-policy term, which the language-model backends of Appendix C do use. And the advantage is continuation-level: every decision in a sampled continuation receives the same $A_i$, so a single group does not say which of its decisions earned the outcome; per-decision attribution emerges only across many groups anchored at different decision points, and the

method's per-decision character lies in where groups are anchored and in what is logged and evaluated, not in a per-step reward. The cost of anchoring at decision points is counted in groups: an episode with $T_d$ controller decisions contributes $T_d$ anchors where per-task GRPO would contribute one, with continuations of half an episode on average, and $T_d$ is one to four in every harness here; the continuations run on the simulator or the lookup table and never call a model, which is what makes the trade affordable, and where no re-roll exists the trainer is AWR on the log. Half of the anchors are episode starts and half are interior logged states, so the primal gradient optimises value under that restart distribution rather than under the task-start distribution alone, while the dual step tracks full-episode cost from start-state rollouts; Appendix M.2 compares start-only and mixed anchoring under a matched transition budget. When no replay exists, the trainer is advantage-weighted regression (AWR) with inverse-propensity weights at a fixed price (Appendix I); offline RL can only reweight what the log contains.

### 3.3 The off-policy promotion gate

**Estimators.** The gate must value a candidate from episodes that another policy generated, which is the off-policy evaluation problem. Three estimators are used: inverse propensity scoring (IPS), which reweights each logged outcome by the ratio of the candidate's probability of the logged action to the logging policy's; its self-normalised form (SNIPS), which divides by the realised sum of the weights instead of by $n$, trading a small bias for much lower variance; and the doubly-robust estimator (DR), which starts from a direct model of the outcome fitted on the log and applies the importance weights only to that model's residuals, so that it is correct if either the model or the propensities are. For an episode $i$ with per-step rewards $r_t^i$ (the terminal quality, or the per-step cost) and cumulative ratio $\rho_{0:t}^i = \prod_{k\le t} \pi(a_k^i \mid s_k^i)/\mu_k^i$ clipped at $\rho_{\max} = 50$,

$$\hat{V}_{\mathrm{IPS}} = \frac{1}{n}\sum_i \sum_t \rho_{0:t}^i\, r_t^i, \qquad \hat{V}_{\mathrm{SNIPS}} = \sum_t \frac{\sum_i \rho_{0:t}^i\, r_t^i}{\sum_i \rho_{0:t}^i}, \tag{7}$$

$$\hat{V}_{\mathrm{DR}} = \frac{1}{n}\sum_i \Big[\hat{V}(s_0^i) + \sum_t \rho_{0:t}^i \big(r_t^i + \hat{V}(s_{t+1}^i) - \hat{Q}(s_t^i, a_t^i)\big)\Big], \qquad \hat{V}(s) = \sum_a \pi(a \mid s)\, \hat{Q}(s,a), \tag{8}$$

the per-decision importance-sampling estimator of Precup et al. [28], the self-normalised estimator of Swaminathan and Joachims [35], and the sequential doubly-robust (DR) estimator of Jiang and Li [14] (see also 38); we call Eq. (8), which carries the cumulative ratio across the steps of an episode, *sequential DR*. The direct model $\hat{Q}$ is a per-feature-bucket mean fitted from the log and iterated under the candidate, which is bucketed fitted-Q evaluation [20]; the clip biases DR only through the direct-model residual. On a first-step contextual bandit (one decision per task, fixed continuation) the bandit form of Dudík et al. [8], *bandit DR* below, applies with a *cross-fitted* direct model:

$$\hat{V}_{\mathrm{DR}} = \frac{1}{n}\sum_i \Big[\sum_a \pi(a \mid x_i)\, \hat{Q}^{(-i)}(x_i, a) + w_i\big(r_i - \hat{Q}^{(-i)}(x_i, a_i)\big)\Big], \qquad w_i = \frac{\pi(a_i \mid x_i)}{\mu_i}, \tag{9}$$

where $\hat{Q}^{(-i)}$ is fitted leaving out task $i$. The cross-fitting matters at small $n$ [7]: an in-sample direct model shares the logged reward it corrects and shrinks the correction toward zero. For multi-step orchestration logs with two to four decisions over twelve actions, a per-decision variant treats each logged decision as a bandit sample with single-step ratio $w_t = \pi(a_t \mid x_t)/\mu_t$ and reward the episode's quality or cost-to-go; it values changing one decision while the rest of the episode stays as logged, trading bias for ratios bounded by $|\mathcal{A}|/\epsilon$. Every estimate is reported with its effective sample size $\mathrm{ESS} = (\sum_i w_i)^2 / \sum_i w_i^2$ [17]. Appendix Q gives the derivations.

**Decision rule.** Confidence intervals are percentile bootstraps over episodes (over tasks, with all logged arms of a task resampled together, in the bandit case), with 200 resamples and the direct model refitted on every resample so that the DR interval includes direct-model variance. The decision is

$$\textsc{promote} \iff \hat{q}_{\mathrm{DR}}^{\mathrm{lo}} \;\ge\; q_{\mathrm{prev}} - \epsilon_q \quad \text{and} \quad \hat{c}_{\mathrm{DR}}^{\mathrm{hi}} \;\le\; B + \mathrm{tol}, \tag{10}$$

with $q_{\mathrm{prev}}$ the incumbent's quality: its on-policy log mean if it is the behaviour policy, its own DR estimate on the log otherwise, or the DR quality recorded at the incumbent's own promotion after a repricing, since an over-budget incumbent would otherwise set a bar that no budget-respecting candidate can pass. Defaults are $\epsilon_q = 0.03$ and $\mathrm{tol} = \$0.005$ (0.02 in simulator units). The gate uses the interval edges, not the point estimates. The rule is local: it guards non-inferiority against the current incumbent and a cost cap, not an absolute quality floor, so a sequence of $k$ individually acceptable promotions can drift by up to $k\epsilon_q$ against the first incumbent; and it compares the candidate's lower bound with the incumbent's point estimate rather than bounding their difference. Appendix F reports a variant that bounds the paired difference and adds an overlap guard.

### 3.4 Priced transfer under harness drift

Let $R_{i,j}$ be the held-out priced value $J_j$ of the policy in service at the end of stage $i$, evaluated on stage $j$, with $J_j$ priced at the stage's own $\bar{\lambda}_j$. Following Lopez-Paz and Ranzato [23], backward transfer (BWT) measures what the final policy keeps of its value on an earlier stage and forward transfer (FWT) what the policy in service brings to a stage it has not yet trained on:

$$\mathrm{BWT}_j = R_{T,j} - R_{j,j} \ (j < T), \qquad \mathrm{FWT}_j = R_{j-1,j} - b_j, \tag{11}$$

with $b_j$ the value of a uniform policy on stage $j$. For the two-version case we report a different quantity and name it differently: the *drift impact* on a frozen policy, $J(\text{frozen on } v_2) - J(\text{frozen on } v_1)$, which measures the environment's change with the policy held fixed, and the recovery, $J(\text{served on } v_2 \text{ after retrain and gate}) - J(\text{frozen on } v_2)$. BWT in Eq. (11) compares two policies on one fixed stage and measures what learning kept or lost; the drift impact compares one policy on two stages and would be zero for no policy, so the two must not be read as the same number. The distinction from EvoHarnessBench's metrics is the object measured: there, a fixed agent policy under a changing harness; here, the priced value of a controller that keeps learning while the structure around it changes.

### 3.5 Platform

A host harness implements `reset`, `legal_actions`, `step` and `quality`; a simulable one also implements `snapshot` and `restore`, which is what constrained GRPO on replay needs. Its operations are the ops, its model pool the tiers, its version string a feature. The trace schema has one record per controller decision (features, action, propensity with exploration included, the legal set the behaviour chose from, realised cost and latency, and a state snapshot when the harness is simulable) and one record per episode (terminal quality, the agent's answer, the queries, the evaluator's calls). Every model call is logged with its model, token counts, priced cost, task and purpose, and a hard budget check on the call's worst-case cost runs before the call is sent, so every paid collection is fail-closed and resumable per (task, arm). Four hosts are used: a hand-written simulator with twelve actions over a latent task difficulty (Appendix A); CRMArena-Pro [13], whose ReAct agent [43] is re-expressed as a steppable loop over the benchmark's own tasks, prompts, live customer-relationship-management (CRM) connector and evaluator, with actions `CONTINUE@tier` (one more agent turn on that tier) and `ANSWER@tier` (force the final answer on that tier) over three tiers and 43 features (Appendix B); $\tau$-bench [44]; and the hosted service of EvoHarnessBench [16]. Every setting of every run is in Appendix N.

## 4 Experiments

Seven experiments exercise the method in increasing realism. The body reports the four that carry the paper's claims and summarises the rest; every experiment is reported in full, with setup, results and limitations, in the appendices. All real-harness collections follow one *counterfactual protocol*: every task is run on every tier with propensity $1/3$ at the first step and a fixed continuation on the chosen tier, so that the held-out quality and cost of any first-step policy is an exact lookup and the off-policy estimators can be checked against the truth. Costs are token counts times list prices, with one exception stated where it occurs. Two reference quantities recur. The *per-task oracle* picks, for each task, the tier with the best logged quality, cheapest among ties. It is a realised-outcome oracle: it sees the one realised outcome of each arm, so its gap to the best learned policy mixes predictable heterogeneity, which better observables could recover, with hindsight over stochastic outcomes, which nothing could. Three identical arms succeeding independently with probability one half give such an oracle 0.875 against 0.5 for any policy, with no routing signal at all. Appendix M.3 bounds the hindsight component from the one repeated run available; the gap is an upper bound on headroom, not a measurement of it. In the continual study the *per-stage oracle* is a controller trained on fresh exploration episodes of that stage with no gate, a reference rather than a proven optimum, and *regret* is the sum over days of the oracle's held-out priced value minus the serving policy's on the day's stage.

### 4.1 CRMArena-Pro at 300 B2B and 150 B2C tasks

CRMArena-Pro [13] poses CRM tasks over a live Salesforce organisation with a program-checked answer, in two sandbox organisations, B2B and B2C, with different schemas and task mixes; the harness is its own ReAct agent, re-expressed as a steppable loop, and the learned decision is the first-step tier from 43 step-0 features, chiefly the task category. The first collection, 50 tasks, is where the controller memorised: no learned policy clearly beat the best fixed tier held-out, and the gate said so (Appendix B). The collection was then resumed on the same seeded, category-stratified sample to 150 and 300 B2B tasks (900 episodes), and a second collection of 150 tasks was run on the B2C organisation with the same protocol. Everything was re-run with the same code and folds. Policies are trained and evaluated by 5-fold cross-validation over task ids, stratified by category: a held-out number is the mean over the five

| held-out, 5-fold; $J$ at $\lambda = 2$ | B2B, 300 tasks | | | | B2C, 150 tasks | | | |
|---|---|---|---|---|---|---|---|---|
| | quality | cost | $J$ [fold SD] | $\leq B$/tol | quality | cost | $J$ [fold SD] | $\leq B$/tol |
| fixed cheap | 0.434 | \$0.057 | 0.320 [0.063] | y/y | 0.469 | \$0.056 | 0.358 [0.078] | y/y |
| fixed mid | 0.482 | \$0.126 | 0.230 [0.026] | n/n | 0.508 | \$0.126 | 0.255 [0.109] | n/n |
| fixed frontier | 0.614 | \$0.131 | 0.353 [0.046] | n/n | 0.638 | \$0.143 | 0.352 [0.116] | n/n |
| uniform behaviour | 0.510 | \$0.104 | 0.301 [0.028] | n/y | 0.538 | \$0.108 | 0.322 [0.090] | n/n |
| AWR+IPS linear, greedy | 0.596 | \$0.080 | 0.437 [0.028] | y/y | 0.598 | \$0.081 | 0.435 [0.057] | y/y |
| **per-category rule (train-fold argmax)** | **0.644** | **\$0.079** | **0.486 [0.035]** | y/y | **0.636** | **\$0.081** | **0.474 [0.067]** | y/y |
| budgeted per-category LP, $B = \$0.10$ | 0.644 | \$0.094 | 0.455 [0.052] | y/y | 0.634 | \$0.094 | 0.446 [0.102] | y/y |
| constrained, $B = \$0.10$, served (iterate mix)† | 0.596 | \$0.102 | 0.393 [0.049] | n/y | 0.617 | \$0.103 | 0.411 [0.097] | n/y |
| constrained, greedy decoding of the mix† | 0.644 | \$0.103 | 0.438 [0.082] | n/y | 0.677 | \$0.105 | 0.466 [0.123] | n/n |
| per-task oracle (realised outcomes) | 0.708 | \$0.058 | 0.592 [0.032] | y/y | 0.727 | \$0.061 | 0.606 [0.068] | y/y |

**Table 1: CRMArena-Pro, held-out tier policies** (5-fold cross-validation over task ids, exact lookups; every row's $J$ at the same evaluation price $\lambda = 2$ per dollar; "$\leq B$/tol" is whether the mean held-out cost is within the budget \$0.10 and within the tolerance \$0.105). The per-category rule has the highest priced value of any policy in both organisations. †The constrained rows are trained under the budget with a learned multiplier, mean $\bar{\lambda}$ over folds 1.22 per dollar on B2B and 1.21 on B2C, which is why they do not maximise $J$ at $\lambda = 2$; the served policy is the statewise iterate mixture and the greedy row is a different policy with its own measured cost, over the tolerance on B2C. The fold SD is a descriptive spread, not a confidence interval.

test folds, and the bracketed fold SD is the standard deviation of $J$ across them. Five learned policies are compared with the fixed tiers and the oracle, every one at the same evaluation price: the *per-category rule*, which assigns to each category the tier with the best training-fold $J$; a *budgeted per-category linear programme* over category-by-tier probabilities on training-fold means, the matched baseline for a category policy under a budget; the *AWR+IPS linear* controller of Appendix I, served greedily; and the *constrained* controller of Section 3.2, trained under the budget $B$ on the lookup table with a learned multiplier, shown both as served (the statewise iterate mixture) and as its greedy decoding, which is a different policy with its own cost.

**The held-out ordering is stable across scale and organisation** (Table 1). At 50 tasks no learned controller clearly beat the best fixed arm; at 150 the per-category rule led by a little over one fold SD; at 300 its $J$ of 0.486 is 0.13 above the best fixed arm (frontier, 0.353), and the same rule leads on B2C, a different data schema and task mix, by 0.12 over its best fixed arm. The bracketed fold SD is a descriptive spread across five overlapping training sets, not a confidence interval, so "0.13 against a fold SD of 0.035" is a stable ordering and not a significance test. The claim is about priced value: on B2B the rule also has higher quality than the mid and frontier tiers at lower cost, but it is not cheaper than the cheap tier; on B2C its quality is within 0.002 of the frontier tier's, which is a tie at this sample size, at 43% lower cost. The constrained controller, trained under $B = \$0.10$ with a learned multiplier of about 1.2 per dollar, serves at \$0.102–0.103, inside the tolerance but above $B$, with four of five folds feasible; its greedy decoding reaches the frontier tier's quality at 22% less cost on B2B but costs \$0.105 on B2C, over the tolerance, and at the common price both sit below the per-category rule, as a policy optimised for a different price should. A budgeted per-category linear programme on training-fold means, the natural matched baseline for a category policy, is within budget on both organisations (0.644 at \$0.094 and 0.634 at \$0.094) and is the strongest constrained policy at $\lambda = 2$; on this fully observed table an exact-gradient trainer matches the sampled one within 0.012 in $J$ at a fraction of the table reads, so the sampled trainer is used here to exercise the interface that the replay experiments need, not because sampling helps (Appendix M.5). **The tier means keep moving as tasks are added** (B2B mid $0.533 \to 0.482$ from 150 to 300 tasks; frontier $0.616 \to 0.614$), which is why the held-out comparison, not the tier table, is the result. **Repricing drift replicates on both organisations.** Held-out, a frontier price rise of $1.5\times$ costs the frozen policy $-0.050$ in priced value on B2B and $-0.049$ on B2C, of which a retrain recovers $+0.035$ and $+0.027$; halving the mid price is neutral ($+0.002$ on both) and the retrain gains $+0.031$ and $+0.030$ by moving traffic to mid; tripling the cheap price costs $-0.038$ and $-0.047$, and the retrained policy on B2B recovers $+0.044$ but leaves the budget. Every retrained candidate is REVERTed by the gate on the repriced realised log, on the quality bar recorded at the incumbent's promotion, the cost bound, or both: at this sample size the gate is the conservative element of the loop, by design.

### 4.2 The gate's sample-size result

The gate is run on the *realised log*, one uniformly drawn tier per task, which is what a deployment log looks like, and then over 200 independent redraws of that log (a fresh uniform draw of one tier per task each time), so that the decision's dependence on the draw is measured rather than assumed. **The gate's answer depends on the draw, and more data moves the rate, not the decision.** On the seed-0 realised log at 300 tasks the DR estimate for the all-task constrained





**Figure 3: Gate power.** Left: the DR cost interval width measured at $n = 50$ with its $1/\sqrt{n}$ extrapolation against twice the budget tolerance, and the widths later measured at $n = 150$ and 300 (diamonds). The two measurements sit about 30% above the curve anchored at 50 and on the curve anchored at 150; the vertical marker is the 50-anchored estimate of the tasks needed, and the 300-anchored one is about 1,700. Right: estimator RMSE, interval width and coverage over 200 redraws of the realised log at $n = 50$.

policy is 0.607 [0.525, 0.668] in quality and \$0.095 [0.087, 0.113] in cost, and the gate REVERTS on the cost bound; the policy's exact cost is \$0.098 against a \$0.100 budget, so the candidate sits inside the budget by less than the tolerance and the interval cannot certify it. Over 200 redraws the promotion rate is 30% at 300 tasks (10% at 150, 6% at 50) and 8% on B2C; the DR cost interval has mean width 0.024 (0.030 on B2C) with 96% coverage of the exact value, and the DR quality estimate has RMSE 0.029 (Figure 3). From 150 to 300 tasks the width fell from 0.036 to 0.024, which is what the $1/\sqrt{n}$ law predicts from the 150-task point (0.025); the projection made from the 50-task width had been optimistic (0.019 at 300), and the promotion rate exceeded the ten to fifteen percent projected from it. Certifying a half-cent margin needs an interval near \$0.01, which from the 300-task width is about 1,700 tasks. That number is a result rather than a limitation: it says what a production gate on this kind of log costs in traffic, and it is why Section 5 recommends bounding cost and treating quality as a floor. Two qualifications apply to this experiment. The candidate was trained on the full outcome table and then evaluated on one-arm masks of that same table, so it is a controlled test of the estimators on a fixed table, not an end-to-end test of learning from a sparse log; Appendix M.4 adds the end-to-end protocol, with the candidate trained on training folds and gated on the held-out fold's realised log: there DR is unbiased (bias $+0.001$ in quality) and its intervals cover the exact value 98% of the time, but at 30–60 held-out tasks the quality interval is 0.29–0.40 wide against true gains of 0.06–0.12, so the gate promotes in only 7% (B2B) and 2% (B2C) of redraws and the one decision it gets reliably right is reverting the fold whose candidate is over budget. And the redraws are repeated masks of one table, so their coverage is conditional on that table.

### 4.3 The continual orchestrator

The centrepiece asks EvoHarnessBench's question turned around: when the harness $H_t = \{\text{tools}, \text{skills}, \text{agents}\}$ grows under an orchestrator that keeps learning, what happens to the policy's priced backward and forward transfer, and does the gate keep it safe without making it too slow to matter? The multi-agent structure of Appendix D is expressed as a typed harness (18 actions over an agent pool, tools and skills; 88 features) on a simulator calibrated to the real logs (Appendix R) and run for 40 days of 96 tasks under four pre-registered stages: a repricing, new specialists including a better verifier, new tools, and skills with a second planner. The continual arm serves its incumbent with $\epsilon = 0.1$, trains daily by constrained GRPO on the last five days of replay, and is gated daily against the incumbent by sequential DR, the multi-step form of Eq. (8), since each episode here holds two to four decisions. Comparators on the same traffic: the frozen day-5 policy, a SkillOrchestra-style router learned once and one re-learned per stage, the fixed modes `always_verify` and `never_verify`, and the per-stage oracle defined above. Appendix F gives the stages, the day loop, every table, a mild-schedule sensitivity run and the verifier ablation.

**The online learner has the lowest regret of every learned arm and recovers after every stage** (Figure 4): cumulative regret 1.26, against 2.60 for the frozen policy and 3.03–3.46 for the static routers, ending each stage within 0.014 of the oracle. **A fixed mode beats it over the whole stream, and that headline is a cold-start artefact.** `never_verify`





**Figure 4: The continual orchestrator over 40 days** (default schedule). Left: held-out $J_g$ of the policy in service each day; the grey upper line is the per-stage oracle. Right: cumulative regret to the oracle from day 6. The continual arm is the only learned arm that recovers after every stage; the fixed mode `never_verify` has the lowest regret of all.





**Figure 5: The crossover.** Left: served $J$ of the continual arm minus `never_verify`, per day (bars) and averaged per stage window (black lines), with the harness events (dotted) and the first promotion (dashed, day 13). Right: cumulative held-out regret to the oracle over the full stream (days 6–40) and restricted to after the agent-pool event (17–40) and after the tools event (25–40).

has regret 0.56 ($0.74 \pm 0.08$ against the learner's $1.06 \pm 0.21$ over 5 seeds): the learner spends twelve days on the uniform exploration policy before its first promotion, crosses the fixed mode around day 22–25 (Figure 5), and from day 25 leads it (0.22 against 0.50; $+0.031 \pm 0.007$ at the last stage over 5 seeds), while the fixed mode falls further below the oracle at each capability stage because it cannot use what arrives. **The gate is the conservative element.** 32 of 40 candidates were reverted, 9 rightly (all budget violations) and 23 as false alarms; at $n \approx 500$ episodes the DR quality interval is $\pm 0.04$ or wider, while the cost interval is \$0.008 wide and its criterion is the one that binds. A paired-difference gate with an overlap guard (Appendix M.6) halves the learner's regret to $0.70 \pm 0.11$ over 5 seeds, below the fixed mode, at the price of marginal budget overshoots of at most 0.6 cents per task in 3 of 5 seeds; holding out a gate slice removes the overshoots and most of the power. The served policy is a statewise mixture whose budget





**Figure 6: Quality against cost per task on every suite.** Fixed tiers (circles), the per-task oracle (star) and, on CRMArena-Pro, the learned per-category policy (diamond) and the budgeted controller (square). On every suite the oracle sits above and to the left of every tier; on $\tau$-bench airline and all three EvoHarnessBench stages the mid tier beats the frontier tier outright at about half its cost. EvoHarnessBench costs are at cached prices.

is measured, not inherited: its realised cost per task stays within $B + \text{tol}$ in every stage of the committed run, with four of forty days over. **Orchestrator-level BWT is bounded and mostly positive**, because the structure is frozen and only the policy moves; FWT is a property of the policy in service, not of anticipation. **Verification helps only when the verifier is informative and the retry does not come out of the plan's call budget** (Appendix F.2): under the committed configuration `always_verify` is below `never_verify` by $0.033 \pm 0.001$ in quality; with an informative verifier (one whose flags carry information about correctness, which the measured verifier's do not) and the per-episode cap on role calls raised from 8 to 12, it is above by $0.029 \pm 0.001$, for $+18\%$ cost. Three follow-ups (Appendix H) add that RAO-style delegation credit buys over-delegation ($-0.02$ to $-0.04$ in stationary $J$ at every stage), that a meta-learned initialisation halves the learner's regret ($1.06 \pm 0.21 \rightarrow 0.47 \pm 0.08$) without changing its first promotion day, and that a skill handbook for the cheap tier does nothing measurable once a no-notes control is run.

### 4.4 Two further suites: $\tau$-bench and EvoHarnessBench

To see whether the tier-level findings depend on the shape of CRMArena-Pro, the same protocol was run on $\tau$-bench [44], a multi-turn conversation with a simulated customer under a policy document (retail, 60 tasks; airline, 49), and on EvoHarnessBench's hosted service [16], which grades the final state of a live enterprise environment with hidden verifiers and grows the tool set by stages (50 tasks at each of stages 1, 2 and 4, under each stage's own allowlist, with prompt caching on the fixed prefix, so its cost column is at cached prices). Figure 6 places every suite on one quality–cost plane; the full tables are in Appendix G.

**The per-task headroom is largest where episodes are longest.** On $\tau$-bench retail the oracle reaches 0.867 at \$0.171 against the frontier tier's 0.717 at \$0.487, because the tiers fail on different tasks (52 of 60 solved by at least one tier, 26 by all three); on airline the mid tier beats the frontier tier outright (0.551 against 0.531 at half the cost). On EvoHarnessBench the mid tier beats the frontier tier on verifier score at every stage (0.702 vs 0.619, 0.699 vs 0.610, 0.643 vs 0.631) and the oracle beats every tier at mid-tier cost, choosing the frontier tier for only 4 tasks in 50; the

ordering is the same at the three harness sizes. **None of the $\tau$-bench headroom is reachable by a first-step controller, and the log says why.** The task is revealed by the simulated user over the conversation, so at step 0 the feature vector is the domain one-hot and every learned first-step policy collapses to a fixed arm; the realised-log gate reverts and 5% of redraws promote. The decision that would capture the headroom is a mid-episode tier switch conditioned on the conversation so far, which this protocol does not log. No controller was trained on the EvoHarnessBench logs, and every task ran under its own stage's harness, so that collection feeds the benchmark's forward-transfer group only (tasks scored under the stage that introduced them).

### 4.5 Negative results

Three further experiments returned negative results. Each is reported in full in the appendices with its cause; the causes are what make them results.

**A GRPO-trained LLM controller did not find the budgeted optimum** (Appendix C). A 1.7B-parameter model with a low-rank (LoRA) adapter, trained by GRPO on the simulator under the same dual-ascent price, produced near-identical rollout groups (83–97% of groups degenerate, meaning every completion in the group was the same, which makes the group-relative advantage zero for every value of $\lambda$), so the policy update came only from the few non-degenerate groups and the regularisation terms, while the moving price kept changing which arm those groups favoured; the policy jumped between arms instead of conditioning on the state. An SFT warm start on oracle labels did the conditioning (100% held-out agreement), and GRPO's contribution was the price, $\lambda \approx 0.44$. Platform controls settled the cause: with the price held fixed, TRL, verl on Ray and NeMo-RL all learn the split and agree within 0.001 in priced value, and DAPO's dynamic sampling sharpens it; the moving price, not the sampler or the stack, broke the run.

**A planner/worker/verifier decomposition scores below a single agent** (Appendix D): 0.480 against 0.608 on the same 50 tasks, dominated on the priced frontier; this is MAS-Orchestra's bar, a single agent given the same compute, and it is not cleared. The verifier is an alarm, not a judge, flagging 92% of wrong and 96% of correct episodes; an orchestration reward model on process features has an out-of-fold AUROC (area under the ROC curve, 0.5 being chance) of 0.469 against 0.821 for the task category alone.

**Priced self-refinement is dominated by buying a better tier up front** (Appendix E): the cheap probe that decomposes an answer into claims with self-reported confidences barely predicts a wrong answer (AUROC 0.65), a cheap refinement round breaks as many answers as it fixes, and the mid tier at the first turn scores 0.66 at \$0.115 where the best cheap-refinement policy at that price scores 0.49.

## 5 Discussion

**The signal is the bottleneck.** The same pattern appears in every experiment. On CRMArena-Pro the per-task oracle is far above every arm, but the only observable the controller has at step 0 is the category; on $\tau$-bench it is the domain alone. The orchestration reward model finds no out-of-fold signal in process features while the category has AUROC 0.82; the verifier flags nearly everything; the self-refinement probe barely sees whether the cheap answer is wrong; the LLM controller's GRPO stage had no advantage signal because its rollout groups were identical. In the continual study the gate's quality criterion has too little signal at $n \approx 500$ to tell an acceptable candidate from the incumbent, while the cost criterion, whose signal is a sum of logged dollars, works. The learners are not the limiting factor; the observables at the decision point are. Three practical consequences follow. Log richer state at the decision point, which for $\tau$-bench means the conversation so far and for the CRM tasks means the first query's result. Certify cost and treat quality as a floor against regression rather than as an improvement test, because the cost interval closes at a few hundred episodes and the quality interval does not. Keep candidates close to the behaviour policy, since the estimator's bias, not its variance, is what over-stated the one far-from-behaviour arm by $+0.68$, and a local non-inferiority rule cannot stop a chain of small, individually acceptable losses.

**When does a learned orchestrator earn its keep?** Only when a harness change moves the right fixed policy. A repricing moves a fixed policy's cost but not its ranking; a new specialist or tool moves the ranking, and only a policy that can see the new capability can use it. If the harness is stable and someone knows the right fixed mode, the learner's whole-stream regret is its cold start, its recovery days and its gate delays, and the fixed mode wins; once the pool has grown past what the fixed mode can use, the learner wins while paying an exploration tax the fixed mode does not. Which fixed mode is right depends on the harness, and that is the argument for learning it: with the measured verifier the right mode is never to verify, with an informative one and a looser cap it is always to verify, and the budgeted learner lands between them under every variant. The meta-learned initialisation of Appendix H halves the cold start on seen

stages and does nothing on the unseen one, which is the shape one would expect from a design-time loop that learns from past generations; Appendix J states what a real-traffic continuation would need.

**Limitations.** The real-harness evidence is 450 CRMArena-Pro tasks, 109 $\tau$-bench tasks and 150 EvoHarnessBench tasks, each on three tiers, from one seed of each collection; held-out differences between policies are of the order of the across-fold SDs below 300 tasks. The continual study is a simulator calibrated to 130 real multi-agent episodes, with its stage effect sizes assumed; its all-arms run is one seed per schedule and only the ablation and the follow-ups have five. Each GPU run ran once. The same tier on the same tasks moved by 0.12 between two runs a day apart, which bounds what any held-out comparison at this scale can certify. Appendix L lists every threat to validity we identified, and Appendix N every setting of every run.

## Acknowledgements

The authors of CRMArena-Pro released the benchmark, its prompts, evaluator and read-only sandbox that made the real-harness experiments possible; the authors of EvoHarnessBench made their hosted service available for the tools-axis collection.

## References

[1] Alekh Agarwal, Sarah Bird, Markus Cozowicz, Luong Hoang, John Langford, Stephen Lee, Jiaji Li, Dan Melamed, Gal Oshri, Oswaldo Ribas, Siddhartha Sen, and Alex Slivkins. Making contextual decisions with low technical debt. *arXiv preprint arXiv:1606.03966*, 2016.

[2] Lakshya A. Agrawal, Shangyin Tan, Dilara Soylu, Noah Ziems, Rishi Khare, Krista Opsahl-Ong, Arnav Singhvi, Herumb Shandilya, Michael J. Ryan, Meng Jiang, Christopher Potts, Koushik Sen, Alexandros G. Dimakis, Ion Stoica, Dan Klein, Matei Zaharia, and Omar Khattab. GEPA: Reflective prompt evolution can outperform reinforcement learning. *arXiv preprint arXiv:2507.19457*, 2025.

[3] Yavuz Bakman, Duygu Nur Yaldiz, Sungmin Kang, Tuo Zhang, Baturalp Buyukates, Salman Avestimehr, and Sai Praneeth Karimireddy. Reconsidering LLM Uncertainty Estimation Methods in the Wild. *arXiv preprint arXiv:2506.01114*, 2025.

[4] Léon Bottou, Jonas Peters, Joaquin Quiñonero-Candela, Denis X. Charles, D. Max Chickering, Elon Portugaly, Dipankar Ray, Patrice Simard, and Ed Snelson. Counterfactual reasoning and learning systems: The example of computational advertising. *Journal of Machine Learning Research*, 14:3207–3260, 2013. arXiv:1209.2355.

[5] Lingjiao Chen, Matei Zaharia, and James Zou. FrugalGPT: How to use large language models while reducing cost and improving performance. *arXiv preprint arXiv:2305.05176*, 2023.

[6] Tingyang Chen, Shuo Lu, Kang Zhao, Weicheng Meng, Hanlin Teng, Tianhao Li, Chao Li, Xule Liu, Jian Liang, Zhizhong Zhang, Yuan Xie, Heng Qu, Kun Shao, and Jian Luan. HarnessX: A Composable, Adaptive, and Evolvable Agent Harness Foundry. *arXiv preprint arXiv:2606.14249*, 2026.

[7] Victor Chernozhukov, Denis Chetverikov, Mert Demirer, Esther Duflo, Christian Hansen, Whitney Newey, and James Robins. Double/debiased machine learning for treatment and structural parameters. *The Econometrics Journal*, 21(1):C1–C68, 2018. arXiv:1608.00060.

[8] Miroslav Dudík, John Langford, and Lihong Li. Doubly robust policy evaluation and learning. In *Proceedings of the 28th International Conference on Machine Learning (ICML)*, 2011. arXiv:1103.4601.

[9] Apurva Gandhi, Satyaki Chakraborty, Xiangjun Wang, Aviral Kumar, and Graham Neubig. Recursive Agent Optimization. *arXiv preprint arXiv:2605.06639*, 2026.

[10] Jason Gauci, Edoardo Conti, Yitao Liang, Kittipat Virochsiri, Yuchen He, Zachary Kaden, Vivek Narayanan, Xiaohui Ye, Zhengxing Chen, and Scott Fujimoto. Horizon: An open source applied reinforcement learning platform. *arXiv preprint arXiv:1811.00260*, 2018.

[11] Edward J. Hu, Yelong Shen, Phillip Wallis, Zeyuan Allen-Zhu, Yuanzhi Li, Shean Wang, Lu Wang, and Weizhu Chen. LoRA: Low-rank adaptation of large language models. In *International Conference on Learning Representations (ICLR)*, 2022. arXiv:2106.09685.

[12] Chengsong Huang, Zifeng Wang, Rujun Han, Jun Yan, Yanfei Chen, Zoey CuiZhu, Ke Jiang, Peng Xia, Han Yu, Yufan Zhuang, Yifei Ming, Jiaqi Pan, Bhavana Dalvi Mishra, Jiaxin Huang, Burak Gokturk, Tomas Pfister, and Chen-Yu Lee. EnvHarness: Awakening Static Worlds for Agent Learning. *arXiv preprint arXiv:2608.19880*, 2026.

[13] Kung-Hsiang Huang, Akshara Prabhakar, Onkar Thorat, Divyansh Agarwal, Prafulla Kumar Choubey, Yixin Mao, Silvio Savarese, Caiming Xiong, and Chien-Sheng Wu. CRMArena-Pro: Holistic assessment of LLM agents across diverse business scenarios and interactions. *arXiv preprint arXiv:2505.18878*, 2025.

[14] Nan Jiang and Lihong Li. Doubly robust off-policy value evaluation for reinforcement learning. In *Proceedings of the 33rd International Conference on Machine Learning (ICML)*, 2016. arXiv:1511.03722.

[15] Zixuan Ke, Yifei Ming, Austin Xu, Ryan Chin, Xuan-Phi Nguyen, Prathyusha Jwalapuram, Jiayu Wang, Semih Yavuz, Caiming Xiong, and Shafiq Joty. MAS-Orchestra: Understanding and Improving Multi-Agent Reasoning Through Holistic Orchestration and Controlled Benchmarks. *arXiv preprint arXiv:2601.14652*, 2026.

[16] Zixuan Ke, Vaidehi Patil, Haizhou Shi, Yang Li, Ye Liu, Sarath Shekkizhar, Anurag Koul, Jiayu Wang, Xuan Phi Nguyen, Semih Yavuz, Mohit Bansal, and Shafiq Joty. EvoHarnessBench: Can Your Agents Keep Pace with an Evolving Harness? *arXiv preprint arXiv:2609.04280*, 2026.

[17] Leslie Kish. *Survey Sampling*. John Wiley & Sons, 1965.

[18] Ilya Kostrikov, Ashvin Nair, and Sergey Levine. Offline reinforcement learning with implicit Q-learning. *arXiv preprint arXiv:2110.06169*, 2021.

[19] Aviral Kumar, Aurick Zhou, George Tucker, and Sergey Levine. Conservative Q-learning for offline reinforcement learning. In *Advances in Neural Information Processing Systems 33*, 2020. arXiv:2006.04779.

[20] Hoang M. Le, Cameron Voloshin, and Yisong Yue. Batch policy learning under constraints. In *Proceedings of the 36th International Conference on Machine Learning (ICML)*, 2019. arXiv:1903.08738.

[21] Yoonho Lee, Roshen Nair, Qizheng Zhang, Kangwook Lee, Omar Khattab, and Chelsea Finn. Meta-Harness: End-to-End Optimization of Model Harnesses. *arXiv preprint arXiv:2603.28052*, 2026.

[22] Lihong Li, Wei Chu, John Langford, and Xuanhui Wang. Unbiased offline evaluation of contextual-bandit-based news article recommendation algorithms. In *Proceedings of the 4th ACM International Conference on Web Search and Data Mining (WSDM)*, 2011. arXiv:1003.5956.

[23] David Lopez-Paz and Marc'Aurelio Ranzato. Gradient episodic memory for continual learning. In *Advances in Neural Information Processing Systems 30*, 2017. arXiv:1706.08840.

[24] Xufang Luo, Yuge Zhang, Zhiyuan He, Zilong Wang, Siyun Zhao, Dongsheng Li, Luna K. Qiu, and Yuqing Yang. Agent Lightning: Train ANY AI Agents with Reinforcement Learning. *arXiv preprint arXiv:2508.03680*, 2025.

[25] Angelia Nedić and Asuman Ozdaglar. Subgradient methods for saddle-point problems. *Journal of Optimization Theory and Applications*, 142(1):205–228, 2009.

[26] Isaac Ong, Amjad Almahairi, Vincent Wu, Wei-Lin Chiang, Tianhao Wu, Joseph E. Gonzalez, M. Waleed Kadous, and Ion Stoica. RouteLLM: Learning to route LLMs with preference data. *arXiv preprint arXiv:2406.18665*, 2024.

[27] Xue Bin Peng, Aviral Kumar, Grace Zhang, and Sergey Levine. Advantage-weighted regression: Simple and scalable off-policy reinforcement learning. *arXiv preprint arXiv:1910.00177*, 2019.

[28] Doina Precup, Richard S. Sutton, and Satinder Singh. Eligibility traces for off-policy policy evaluation. In *Proceedings of the 17th International Conference on Machine Learning (ICML)*, 2000.

[29] Cheng Qian, Zuxin Liu, Shirley Kokane, Akshara Prabhakar, Jielin Qiu, Haolin Chen, Zhiwei Liu, Heng Ji, Weiran Yao, Shelby Heinecke, Silvio Savarese, Caiming Xiong, and Huan Wang. xRouter: Training Cost-Aware LLMs Orchestration System via Reinforcement Learning. *arXiv preprint arXiv:2510.08439*, 2025.

[30] Qwen Team. Qwen3 technical report. *arXiv preprint arXiv:2505.09388*, 2025.

[31] Zhihong Shao, Peiyi Wang, Qihao Zhu, Runxin Xu, Junxiao Song, Xiao Bi, Haowei Zhang, Mingchuan Zhang, Y. K. Li, Y. Wu, and Daya Guo. DeepSeekMath: Pushing the limits of mathematical reasoning in open language models. *arXiv preprint arXiv:2402.03300*, 2024.

[32] Haizhou Shi, Ye Liu, Bo Pang, Zeyu Leo Liu, Hao Wang, Silvio Savarese, Caiming Xiong, Yingbo Zhou, and Semih Yavuz. SSR: Socratic Self-Refine for Large Language Model Reasoning. *arXiv preprint arXiv:2511.10621*, 2025.

[33] Adam Stooke, Joshua Achiam, and Pieter Abbeel. Responsive safety in reinforcement learning by PID lagrangian methods. In *Proceedings of the 37th International Conference on Machine Learning (ICML)*, 2020. arXiv:2007.03964.

[34] Hongjin Su, Shizhe Diao, Ximing Lu, Mingjie Liu, Jiacheng Xu, Xin Dong, Yonggan Fu, Peter Belcak, Hanrong Ye, Hongxu Yin, Yi Dong, Evelina Bakhturina, Tao Yu, Yejin Choi, Jan Kautz, and Pavlo Molchanov. ToolOrchestra: Elevating Intelligence via Efficient Model and Tool Orchestration. *arXiv preprint arXiv:2511.21689*, 2025.

[35] Adith Swaminathan and Thorsten Joachims. The self-normalized estimator for counterfactual learning. In *Advances in Neural Information Processing Systems 28*, 2015.

[36] Arnuv Tandon, Karan Dalal, Xinhao Li, Daniel Koceja, Marcel Rød, Sam Buchanan, Xiaolong Wang, Jure Leskovec, Sanmi Koyejo, Tatsunori Hashimoto, Carlos Guestrin, Jed McCaleb, Yejin Choi, and Yu Sun. End-to-End Test-Time Training for Long Context. *arXiv preprint arXiv:2512.23675*, 2025.

[37] Chen Tessler, Daniel J. Mankowitz, and Shie Mannor. Reward constrained policy optimization. *arXiv preprint arXiv:1805.11074*, 2018.

[38] Philip S. Thomas and Emma Brunskill. Data-efficient off-policy policy evaluation for reinforcement learning. In *Proceedings of the 33rd International Conference on Machine Learning (ICML)*, 2016. arXiv:1604.00923.

[39] King Yeung Tsang, Zihao Zhao, Vishal Venkataramani, Haizhou Shi, Zixuan Ke, Semih Yavuz, Shafiq Joty, and Hao Wang. Reward Modeling for Multi-Agent Orchestration. *arXiv preprint arXiv:2606.13598*, 2026.

[40] Vishal Venkataramani, Haizhou Shi, Zixuan Ke, Austin Xu, Xiaoxiao He, Yingbo Zhou, Semih Yavuz, Hao Wang, and Shafiq Joty. MAS-ProVe: Understanding the Process Verification of Multi-Agent Systems. *arXiv preprint arXiv:2602.03053*, 2026.

[41] Jiayu Wang, Yifei Ming, Zixuan Ke, Shafiq Joty, Aws Albarghouthi, and Frederic Sala. SkillOrchestra: Learning to Route Agents via Skill Transfer. *arXiv preprint arXiv:2602.19672*, 2026.

[42] Ran Yan, Wei Fu, Jiale Li, Shusheng Xu, Zhiyu Mei, Jiaxuan Gao, Jiarui Zhang, Wentai Zhang, Hao Dai, Xujie Shen, Chuyi He, Zhen Pu, Jun Mei, Zhiyao Lin, Haitao Wang, Zhiqiang Ding, Jiawei Zhang, Huaijie Wang, Ruida Xu, Honghua Dong, Youhe Jiang, Yi Wu, Tongkai Yang, and Binhang Yuan. Next-Generation Agentic Reinforcement Learning Systems Enable Self-Evolving Agents. *arXiv preprint arXiv:2607.01120*, 2026.

[43] Shunyu Yao, Jeffrey Zhao, Dian Yu, Nan Du, Izhak Shafran, Karthik Narasimhan, and Yuan Cao. ReAct: Synergizing reasoning and acting in language models. In *International Conference on Learning Representations (ICLR)*, 2023. arXiv:2210.03629.

[44] Shunyu Yao, Noah Shinn, Pedram Razavi, and Karthik Narasimhan. $\tau$-bench: A Benchmark for Tool-Agent-User Interaction in Real-World Domains. *arXiv preprint arXiv:2406.12045*, 2024.

[45] Qiying Yu, Zheng Zhang, Ruofei Zhu, Yufeng Yuan, Xiaochen Zuo, Yu Yue, Tiantian Fan, Gaohong Liu, Lingjun Liu, Xin Liu, et al. DAPO: An Open-Source LLM Reinforcement Learning System at Scale. *arXiv preprint arXiv:2503.14476*, 2025.

[46] Jenny Zhang, Shengran Hu, Cong Lu, Robert Lange, and Jeff Clune. Darwin gödel machine: Open-ended evolution of self-improving agents. *arXiv preprint arXiv:2505.22954*, 2025.

[47] Yifan Zhang, Yutong Dai, Juntao Tan, Luyu Yang, Rishi Mullur, Thai Hoang, Zhiyuan Hu, James Zhu, Phil Mui, Silvio Savarese, Ran Xu, and Zeyuan Chen. DarwinX: Evolving Agent Harnesses Through Natural Selection. *arXiv preprint arXiv:2608.07545*, 2026.

# Appendix

The appendices report every experiment in full, in the order of the body: the simulator pipeline (Appendix A); the 50-task CRMArena-Pro collection and the gate's sample-size study (B); the LLM controller (C); the multi-agent (D) and self-refinement (E) experiments; the continual orchestrator (F); the two further suites (G); the follow-ups (H); the AWR trainer (I); what a real-traffic continuation would need (J); the extended related work (K); the full limitations (L); then every experimental setting (N), a worked logged episode (O), the prompts (P), the estimator derivations (Q), the simulator parameters (R), the per-day tables (S), the reproduction commands (T) and the data license note (U).

## A Simulator pipeline: gate, drift, gated retrain

The simulator exercises the whole loop where the truth is known. Tasks have a latent difficulty (easy with probability 0.65, hard 0.35) that the controller never sees; it sees a proxy that is correct 85% of the time. Twelve actions, $\{\textsc{answer}, \textsc{retrieve}, \textsc{verify}, \textsc{escalate}\} \times \{\text{cheap}, \text{mid}, \text{frontier}\}$, each have their own cost, latency and quality tables; episodes have at most four steps, with terminal ops forced on the last. Version $v_2$, the drift event, adds CACHED_RETRIEVE, near-free evidence that works only on easy tasks; ages the verifier so that VERIFY adds nothing on hard tasks; and reprices the frontier tier by $1.5\times$. Costs are in simulator units.

**Setup.** 3,000 episodes on $v_1$ under a uniform behaviour policy; constrained GRPO on replay at budget $B = 0.30$; the candidate gated against the behaviour log. Then drift: $v_2$ plus a scripted reprice(mid, 1.2); 6,000 fresh $v_2$ episodes served by the frozen policy with $\epsilon = 0.3$; a retrain warm-started from the frozen policy; the adapted policy gated against the frozen one with the quality bar taken from the frozen policy's $v_1$ promotion. Ground truth is Monte Carlo over 20,000 fresh tasks with expected success probability. The whole pipeline is repeated over five replicate seeds (seed $s$ draws every collection, training and bootstrap seed from $s$; Table 25); numbers are mean $\pm$ SE over seeds and the per-seed values are in Table 31.

**Results.** Figure 7 shows both gates. On $v_1$ the learned price is $\bar{\lambda} = 0.358 \pm 0.027$. DR puts the candidate at quality $0.884 \pm 0.009$ (mean 90% CI $[0.851, 0.910]$) and cost $0.308 \pm 0.001$ (upper bound 0.311); the decision is PROMOTE in 5 of 5 seeds, and the ground truth ($0.878 \pm 0.001$ at $0.306 \pm 0.002$) lies inside the DR interval in 4 of 5 (in the fifth it is 0.001 below the lower bound). IPS and SNIPS sit low ($0.760 \pm 0.022$ and $0.797 \pm 0.014$): a uniform behaviour over 12 actions and up to 4 steps gives cumulative ratios in the hundreds against a near-deterministic candidate, and the clip at 50 truncates them. After the drift the frozen policy keeps its quality ($0.869 \pm 0.001$) but its cost rises to $0.413 \pm 0.003$, over budget, so priced-BWT is $-0.047 \pm 0.003$ (Table 2). The adapted policy is scored at $0.869 \pm 0.004$ and cost $0.298 \pm 0.004$ (truth $0.867 \pm 0.001$ at $0.299 \pm 0.004$, inside the DR interval in 5 of 5); served, it would recover $+0.039 \pm 0.003$. The gate promotes it in only 2 of 5 seeds. Every revert fails on quality alone, and all three are false alarms: the bar is the DR quality recorded at the $v_1$ promotion minus $\epsilon_q$, and in those seeds that estimate was high (0.901, 0.883, 0.903 against truths of 0.877–0.878), so a candidate within 0.01 of the frozen policy's quality and inside the budget could not clear it. The served recovery is therefore $+0.015 \pm 0.009$ ($+0.033$ and $+0.042$ where the gate promoted, zero elsewhere). Drift hits cost, not quality: the frozen controller keeps paying for an aged verifier and a repriced frontier, the retrain restores the budget at equal quality, and the quality bar inherited from an optimistic earlier estimate is what keeps it out of service. The continual study finds the same false-alarm mode at larger scale (Appendix F).

**Table 2:** Simulator drift table, ground truth, mean $\pm$ SE over 5 seeds ($J$ at each seed's own $\bar{\lambda}$). priced-BWT $= J(\text{ii}) - J(\text{i}) = -0.047 \pm 0.003$; recovery $= J(\text{iii}) - J(\text{ii}) = +0.015 \pm 0.009$ as served after the gate, $+0.039 \pm 0.003$ for the adapted policy.

| condition | quality | cost | within budget | $J$ |
|---|---|---|---|---|
| (i) frozen on $v_1$ | $0.878 \pm 0.001$ | $0.306 \pm 0.002$ | 5/5 | $0.768 \pm 0.008$ |
| (ii) frozen on $v_2$ | $0.869 \pm 0.001$ | $0.413 \pm 0.003$ | 0/5 | $0.721 \pm 0.011$ |
| (iii-a) adapted on $v_2$ (whether or not promoted) | $0.867 \pm 0.001$ | $0.299 \pm 0.004$ | 5/5 | $0.760 \pm 0.008$ |
| (iii) served on $v_2$ after the gate (2/5 promoted) | $0.868 \pm 0.001$ | $0.369 \pm 0.028$ | 2/5 | $0.737 \pm 0.014$ |

**Limitations.** The simulator's difficulty structure, success tables and drift event are hand-written; the run demonstrates the mechanics, not effect sizes. Five seeds are enough to show that the second gate's decision depends on the seed, not to estimate its promotion rate. The simulator gate fits its direct model in-sample, which is defensible there because its buckets hold hundreds of transitions; the real-log gates cross-fit.





**Figure 7:** Simulator gates over 5 seeds. Left: the constrained-GRPO candidate scored against 3,000 uniform-behaviour episodes on $v_1$; right: the adapted policy scored against 6,000 $v_2$ episodes served by the frozen policy. Points are means over seeds of each estimate with SE bars; thin lines are the mean 90% bootstrap CI; the star is Monte Carlo ground truth (for $v_2$, the adapted policy whether or not promoted). The gate decides on DR (blue). From `results/sim_seeds/`.

## B CRMArena-Pro: the initial 50-task collection and the gate's sample-size study

The 300-task results of Section 4.1 are the same code, on the same seeded sample, as the 50-task collection reported here. This first collection is kept in full because it is where the controller memorised and the gate said so, and because the sample-size study of the gate was done on it.

### B.1 The counterfactual collection

**Setup.** 50 B2B tasks (2–3 per category, all 22 categories), each run on all three tiers with a fixed continuation (`CONTINUE` on that tier until the agent answers, `ANSWER` forced at the cap), so that each task's first-step tier is a contextual bandit with a fully observed reward table and the held-out value of any tier policy is an exact lookup. The log holds 150 episodes from 832 model calls; episodes average 5.0 turns and 16 of 150 hit the 12-turn cap. The behaviour is uniform over tiers (propensity $1/3$ at step 0, 1 after). The learned decision is the first-step tier from the 43-dimensional step-0 features. Policies are trained under 5-fold category-stratified cross-validation over task ids (train on 40, evaluate on the held-out 10, seed 0), at fixed $\lambda \in \{2, 5, 10\}$ per dollar with AWR+IPS, and under a budget $B = \$0.10$ with constrained GRPO on the lookup table (learned $\lambda$).





**Figure 8:** CRMArena-Pro B2B at 50 tasks: held-out quality against cost per task (5-fold means, exact lookups). The per-task oracle beats every fixed arm on both axes; no learned policy does. The open triangle is the constrained policy in-sample (0.669 at \$0.099), the filled one held-out (0.553 at \$0.131).

**Results.** Table 3 and Figure 8. No learned linear rule clearly beats the best fixed arm held-out. The served AWR policy has lower $J$ than the best fixed arm at every $\lambda$ (0.350 vs mid 0.368; 0.045 vs cheap 0.104; $-0.414$ vs cheap

**Table 3:** Held-out first-step tier policies on CRMArena-Pro B2B at 50 tasks (5-fold means; cost in USD per task; across-fold SD of $J$ in brackets, 0.05–0.3 throughout, as large as the gaps between rows).

| policy (held-out) | $\lambda = 2$: $J$ | $\lambda = 5$: $J$ | $\lambda = 10$: $J$ | $B = \$0.10$: quality / cost |
|---|---|---|---|---|
| AWR+IPS linear, served (stochastic) | 0.350 [0.047] | 0.045 [0.126] | −0.414 [0.246] | – |
| AWR+IPS linear, greedy | 0.384 [0.076] | 0.186 [0.126] | −0.273 [0.272] | – |
| per-category plug-in rule | 0.415 [0.066] | 0.161 [0.104] | −0.214 [0.154] | – |
| constrained cgrpo-lookup (iterate mix) | – | – | – | 0.553 / 0.131 (over) |
| uniform behaviour | 0.337 [0.066] | −0.015 [0.164] | −0.601 [0.340] | 0.571 / 0.117 |
| fixed cheap | 0.308 [0.179] | 0.104 [0.227] | −0.236 [0.308] | 0.444 / 0.068 |
| fixed mid | 0.368 [0.092] | 0.010 [0.124] | −0.588 [0.298] | 0.608 / 0.120 |
| fixed frontier | 0.334 [0.133] | −0.159 [0.317] | −0.980 [0.633] | 0.663 / 0.164 |
| per-task oracle | 0.639 [0.056] | 0.452 [0.080] | 0.148 [0.168] | 0.769 / 0.092 |

$-0.236$), and its greedy version and the per-category rule beat the best arm by at most $0.08$, inside the fold SDs. The features memorise: AWR's $J$ at $\lambda = 2$ is $0.475$ in-sample against $0.350$ held-out; the constrained policy meets the budget in-sample ($0.669$ at \$0.099) and overspends held-out ($0.553$ at \$0.131), where the uniform behaviour ($0.571$ at \$0.117) dominates it. Even the context-free arm mixture tuned to $B$ on 40 tasks costs \$0.115 on the held-out 10. The per-task oracle reaches $0.769$ at \$0.092 and beats every arm on both quality and cost: the headroom is per task, not per category, and the missing piece is an observable that predicts which tier a task needs. Repricing events (frontier $\times 1.5$, cheap $\times 3$), with costs recomputed from logged tokens, push the frozen all-50 policy ($\bar{\lambda} = 1.36$ per dollar) over budget by $+\$0.029$ and $+\$0.035$: priced-BWT $-0.040$ and $-0.048$, in-sample recovery $+0.069$ and $+0.091$; held-out, the retrained policies still overspend (about \$0.125), and the gate on the repriced realised log REVERTS all three retrains, which the held-out table says is the right call (recovery $-0.012$ for frontier $\times 1.5$).

**Limitations.** Fifty tasks, one organisation, one seed; one task moves a fold's quality by $0.1$. Only the first-step tier is learned, because the continuation was fixed at collection. The log holds one harness version, so version drift cannot be measured on it. Prompt caching was not used, so the roughly 5k-token system prompt is paid on every turn.

### B.2 The gate's sample-size study at 50 tasks

**Setup.** The candidate is the constrained policy trained on all 50 tasks (exact value: quality $0.665$, cost \$0.0987, within $B+\text{tol} = \$0.105$). The realised behaviour log is one uniformly drawn arm per task (50 episodes). The gate (cross-fitted DR, $\epsilon_q = 0.03$) is run once, then over 200 independent redraws of the realised log with a 200-resample bootstrap in each.

**Results.** On the single realised log DR estimates quality $0.740$ $[0.627, 0.855]$ and cost \$0.0960 $[0.0750, 0.1200]$; the quality criterion passes and the cost criterion fails ($0.1200 > 0.105$): REVERT. On the full counterfactual log all three estimators reduce to the exact value (the weights over a task's three arms sum to 3) and the interval is pure task-sampling uncertainty from 50 tasks; the cost upper bound is still \$0.1122 and the decision is still REVERT. Over the 200 redraws (Table 4) DR halves IPS's quality RMSE ($0.048$ vs $0.094$) with 99% coverage of its 90% interval, but its cost interval is \$0.046 wide on average, so the candidate, whose exact cost is \$0.0013 under $B+\text{tol}$, is PROMOTED in only $12/200 = 6\%$ of redraws. The gate errs on the safe side; buying power means more tasks or a wider tolerance. With interval width scaling as $1/\sqrt{n}$, certifying a \$0.005 margin needs an interval near \$0.01, roughly twenty times the tasks, about 1,000. Section 4.2 reports how this projection fared at 150 and 300 tasks.

**Table 4:** Estimators over 200 redraws of the realised CRMArena-Pro log ($n = 50$, one arm per task). Cross-fitted direct model. PROMOTE in 12/200 redraws (6%).

| metric | estimator | bias | RMSE | mean 90% CI width | CI covers exact |
|---|---|---|---|---|---|
| quality | IPS | $+0.011$ | 0.094 | 0.338 | 94% |
| quality | SNIPS | $+0.001$ | 0.048 | 0.238 | 100% |
| quality | DR | $+0.004$ | 0.048 | 0.256 | 99% |
| cost | IPS | $+0.0001$ | 0.0114 | 0.0414 | 92% |
| cost | SNIPS | $-0.0009$ | 0.0102 | 0.0381 | 92% |
| cost | DR | $-0.0018$ | 0.0114 | 0.0461 | 92% |

**Limitations.** An in-sample direct model covers 96%/94% with a $-0.006$ quality bias, a difference inside the noise at $n = 50$; the redraw study reports bias and coverage empirically rather than assuming them.

## C LLM controller: GRPO with LoRA on a 1.7B model

The linear controller of Section 3.2 can be replaced by a small language model that reads the state as text and emits the action as a tag. This experiment trains such a controller with GRPO under the same learned price and asks whether it finds the budgeted optimum.

**Setup.** The controller is Qwen3-1.7B [30] with a LoRA adapter [11] ($r = 16$ on the attention and MLP projections, bf16), trained with GRPO. The agent models stay frozen; the tiers are the arms. The prompt shows the difficulty proxy, the state, per-tier prices, the budget and the legal actions, and the completion must be exactly one tag `<action>TIER OP</action>`; anything else is invalid (reward $-1$, cost booked as the cheapest safe action). After the first action a fixed continuation answers on the same tier; the reward is $q - \lambda C$ with $\lambda$ learned by the same damped dual ascent, once per step from the batch mean cost. Each step generates 64 completions (8 prompts $\times$ 8 generations in phases 1 and 1b; 4 $\times$ 16 in 1c), of length 16, at learning rate $10^{-5}$, over 2,000 seeded simulator tasks with the legal-action order shuffled per task (with a fixed order the base model only ever sampled one or two arms). Three runs on the simulator, each run once on one A100-40GB: `phase1` ($\lambda$ learning rate 0.1, $k_p$ 2.0, $\beta_{\mathrm{KL}}$ 0.02, 300 steps); `phase1b` (a slower dual step: learning rate 0.02, $k_p$ 0.5, EMA 0.95; $\beta_{\mathrm{KL}}$ 0.05; entropy 0.01); `phase1c` (150 SFT steps on per-difficulty oracle labels at a price shown in the prompt and drawn from $\{0.0, 0.1, \ldots, 2.0\}$, the adapter merged so that the KL reference is the SFT policy, then 200 GRPO steps with 16 generations, temperature 1.2, $\lambda_0 = 0.5$). A fourth run (`crm_phase2`) applies the same recipe to CRMArena-Pro fold 0 in lookup mode. Per-run settings are in Appendix N.





**Figure 9:** GRPO training logs. `phase1`'s price orbits once and decays to 0 as the policy collapses onto `mid RETRIEVE`; `phase1b`'s price is still rising at step 300 while cost stays above budget; `phase1c`'s price settles at $\lambda \approx 0.44$ with the batch cost alternating between two deterministic rules. Degenerate groups (all completions identical, hence zero advantage) dominate every run.

**Table 5:** LLM controller on simulator $v_1$ (2,000 fresh tasks, seed 777; budget $B = 0.30$; the policy's first action then `ANSWER` on the same tier). "Within" means cost $\leq B + 0.02$.

| policy | quality | cost | within | invalid |
|---|---|---|---|---|
| Qwen3-1.7B zero-shot (greedy, no adapter) | 0.586 | 0.048 | yes | 18.9% |
| `phase1`, steps 100 / 200 / 300 | 0.748–0.749 | 0.155 | yes | 0% |
| `phase1b`, step 100 | 0.885 | 0.603 | no | 0% |
| `phase1b`, step 300 | 0.832 | 0.434 | no | 0.1% |
| `phase1c`: SFT only, and GRPO steps 100 and 200 (all identical) | 0.848 | 0.330 | no | 0% |
| linear controller (`policy_v1_sim.json`), first action only | 0.573 | 0.035 | yes | 0% |
| fixed `ANSWER` on cheap / mid / frontier | 0.522 / 0.688 / 0.820 | 0.020 / 0.100 / 0.400 | yes / yes / no | 0% |
| best deterministic per-proxy rule (easy: mid ESCALATE; hard: frontier ANSWER) | 0.814 | 0.250 | yes | – |
| best randomised policy at cost exactly $B$ (LP) | 0.835 | 0.300 | yes | – |
| *derived:* `phase1c` served with the price drawn as in training's last 100 steps | 0.837 | 0.305 | yes | – |

**Results.** Table 5 and Figure 9. GRPO alone never found the budgeted optimum, for two reasons that the logs make visible. *Group degeneracy*: within a prompt group the completions are almost always identical, 83.5% of groups on average in `phase1b`, which gives zero group-relative advantage, and it gives zero for every value of $\lambda$, since a common shift of the group's rewards is removed by the group mean. A moving price therefore cannot create a within-group signal; what it does is change the sign of the advantage in the few non-degenerate groups from one step to the next, and, in `phase1c`, change the price shown in the prompt and with it the sampled output. The weight updates came from those non-degenerate groups and from the KL and entropy terms, and the policy jumped between near-deterministic arms instead of learning the per-proxy split. *Primal–dual orbit*: in `phase1` the policy swings to `frontier RETRIEVE` (cost 0.60), $\lambda$ climbs to 1.02 by step 67, the policy collapses onto `mid RETRIEVE` (0.155), and $\lambda$ decays to 0 with nothing to pull it back; in `phase1b` $\lambda$ is still rising at step 300 (1.37) and the policy has not reached the budget. Mixing is not the bottleneck: a deterministic per-proxy rule reaches $0.814$ at $0.250$ and randomisation adds only $0.021$; what the runs failed to do is condition on the proxy. In `phase1c` the SFT stage reached 100% held-out agreement with the oracle labels (1,000 prompts, 0% invalid) and splits by difficulty where the oracle does; GRPO then left the policy unchanged on all 2,000 evaluation tasks (the degenerate-group rate averaged 93% over steps 1–100 and 97% over 101–200, even after the rollout temperature was raised from 1.2 to 1.5 at step 20). GRPO's contribution is the price: $\lambda$ settles at $0.44$ (mean $0.443$ over the last 100 steps), which is the slope at which the hard-proxy action flips, and at that price the SFT policy ($J = 0.702$) ties the oracle rule ($0.703$) and the LP ($0.702$). No single greedy policy meets $B = 0.30$: at any one shown price the policy is a deterministic rule costing $0.33$ or $0.15$; training met the budget by alternating the shown price over time (batch cost $0.301$ and $0.296$ over the two halves), and serving can reach it by drawing the shown price, the price-conditioned analogue of iterate averaging: $0.837$ at $0.305$, derived from the two greedy rules rather than decoded end to end. On CRMArena-Pro fold 0 the SFT policy ignores the shown price (the same per-category rule at every $\lambda$, about \$0.075, under budget) and GRPO again leaves it unchanged.

**The platform controls.** The `phase1b` failure was reproduced on three stacks, TRL 1.15, verl 0.9.1 on Ray with vLLM, and NeMo-RL, with the same model, adapter, data and dual-ascent settings, and then run again with the price held fixed at $\lambda = 0.44$ (Appendix N, Table 29; `results/llm/backends/COMPARISON.md`). With the price moving, every stack reproduces the collapse. With the price fixed, every stack learns the per-proxy split, and the three agree within 0.001 in priced value ($J$ 0.681 / 0.682 / 0.682 at cost 0.333 / 0.334 / 0.333); a fixed-price TRL control without dynamic sampling also splits ($J$ 0.679, within budget), and DAPO's dynamic sampling [45], which drops the degenerate groups from the batch, sharpens the hard-task split from 53% to 98–100% frontier for $+0.065$ cost. The cause of the failure was the moving price, not the sampler or the platform.

**Limitations.** Each GPU run ran once; there is no seed variance. The phase-1 table truncates the linear policy's continuation (its first action is `cheap RETRIEVE` because it was trained to keep going; with its own continuation it scored $0.876$ at $0.301$ in the run that produced that file), so its row is not its real performance. Showing $\lambda$ rounded to 0.1 puts $\bar{\lambda} = 0.443$ on the over-budget side of the flip point.

## D Process-verified multi-agent orchestration

This experiment asks whether a planner/worker/verifier decomposition of the CRM task clears the compute-matched single-agent bar that MAS-Orchestra [15] reports, and whether per-step verification of the kind MAS-ProVe [40] studies carries information on this log.

**Setup.** A planner (cheap tier) decomposes a CRM request into 1–3 sub-queries; a data worker (mid) runs one sub-query at a time through the harness's own step path; a verifier (cheap) checks a sub-result against its goal (a structural pre-check fails at \$0 on query errors); the answer is the harness's forced `ANSWER@mid`. After every worker step an orchestration policy chooses $\{\textsc{verify}, \textsc{skip_verify}, \textsc{replan}, \textsc{answer}\} \times$ tier; a fail retries the sub-query once; at most 8 role calls per episode. Fixed modes `always_verify` and `never_verify`, plus a uniform exploration mode with logged propensities, were run on the same 50 B2B tasks as the counterfactual log: 130 episodes (50 + 50 + 30). An orchestration reward model (ORM: logistic regression and a 16-unit MLP over process features) is evaluated out of fold over tasks.

**Results.** The headline is negative (Table 6): the decomposition scores below the single mid-tier agent ($0.480$ vs $0.608$) at lower cost and is dominated on the priced frontier at both prices (by mid at $\lambda = 2$, by cheap at $\lambda = 5$); paired on the 50 tasks the single mid agent wins 11 and loses 5. The compute-matched single-agent bar is not cleared. Three mechanisms are visible in the log. The plan is fixed up front by a cheap model with no data in hand, while the single agent picks each query after seeing the last result. `never_verify` gives the strong model about 2.7 worker turns and a

**Table 6:** Decomposition against the single ReAct agent on the same 50 CRMArena-Pro B2B tasks (single-agent rows are exact lookups of the counterfactual log). The six confidentiality tasks score 0 for every system, so the ceiling is 0.88.

| system | accuracy / quality | cost / task | $J(\lambda = 2)$ | $J(\lambda = 5)$ |
|---|---|---|---|---|
| single agent, fixed cheap | 0.444 | \$0.0680 | 0.308 | 0.104 |
| single agent, fixed mid | 0.608 | \$0.1196 | 0.368 | 0.010 |
| single agent, fixed frontier | 0.663 | \$0.1642 | 0.334 | $-0.159$ |
| single agent, per-task oracle (max quality, cheapest) | 0.769 | \$0.0916 | 0.586 | 0.311 |
| MAS `always_verify` | 0.480 | \$0.0906 | 0.299 | 0.027 |
| MAS `never_verify` | 0.461 | \$0.0821 | 0.297 | 0.051 |
| MAS `controller:uniform` (30 tasks, exploration) | 0.535 | \$0.0758 | 0.384 | 0.156 |

*Paired, same 50 tasks:* `always_verify` vs `never_verify`: 6 wrong→right, 5 right→wrong, net $+1$ ($\Delta q = +0.019 \pm 0.067$ SE, $+\$0.0086$). `always_verify` vs single mid: both right 19, MAS right / mid wrong 5, MAS wrong / mid right 11, both wrong 15 (net $-6$).

**Table 7:** Orchestration reward model, out of fold over tasks (130 episodes, base rate $P(\text{correct}) = 0.485$, base-rate Brier 0.250).

| model | features | AUROC | Brier | ECE (5 bins) |
|---|---|---|---|---|
| logreg | process features (default) | 0.469 | 0.281 | 0.114 |
| logreg | process − verifier features | 0.451 | 0.280 | 0.140 |
| logreg | process + category one-hot | 0.831 | 0.165 | 0.040 |
| mlp | process features (default) | 0.456 | 0.263 | 0.053 |
| mlp | process + category one-hot | 0.831 | 0.164 | 0.035 |
| – | category alone, no process feature | 0.821 | 0.166 | – |

forced answer, against the single agent's about 5. Under `always_verify`, 47 of 50 episodes hit the 8-call cap, because 65% of verifier calls fail and each fail spends a retry. Verification bought $+1$ task for $+10\%$ cost, and the paired table says that is noise (6 flips each way, all through a fail and a retry). The verifier is an alarm, not a judge: it flags 24 of 26 wrong episodes ($P(\text{flag} \mid \text{wrong}) = 0.92$, silent failures $2/50$) and 23 of 24 correct ones ($P(\text{flag} \mid \text{correct}) = 0.96$), so $P(\text{wrong} \mid \text{flagged}) = 0.51$ against a base rate of $0.52$. The ORM (Table 7) finds that process features carry no out-of-fold signal (AUROC $0.469$, Brier above the base rate) and that the task category carries most of it (0.821 alone; 0.831 with process features); the cross-validation is over tasks, so this is category-level difficulty transferring to unseen tasks, resting on 2–3 training tasks per category. The priced-controller hook was exercised, not evaluated: AWR on the 30-episode ORM-relabelled exploration log changes nothing detectable per decision (per-decision SNIPS $0.563$ $[0.373, 0.701]$ against the behaviour's $0.567$, ESS 55 of 64), and the episode-level estimate has ESS 7 of 30. The per-decision estimator's unit matters and is now explicit: flattening decision records weights a ten-decision episode ten times a one-decision episode and averages overlapping cost-to-go values, which is not cost per task. Re-weighting each episode's rows by $1/n_{\text{decisions}}$ (the task unit, with total episode cost as the cost estimand) changes the DR outcome lift of that policy from $-0.062$ to $+0.038$, both inside intervals 0.3–0.5 wide (`results/mas/perdecision_units.md`); neither unit supports a quality claim, and the body makes none.

**Limitations.** The verifier is a cheap model of the same family checking a mid model; there is no human process label. The 8-call cap interacts with a high-fail verifier, so a higher cap or a better verifier is a different system; the ablation of Appendix F.2 varies exactly those two things. Sub-queries run sequentially in one growing context.

## E Priced Socratic self-refinement

Test-time refinement is a purchase: a probe, some re-solving, a rewrite. This experiment asks whether a priced gate can decide when to buy it, and whether buying it beats buying a better tier at the first turn.

**Setup.** One Socratic self-refinement round [32] on a CRMArena-Pro answer: a cheap probe decomposes the answer into 1–3 claims with self-reported confidences (about \$0.003, so a gate can look before it pays); each claim is resolved by $k = 2$ worker mini-episodes on the chosen tier ($\leq 3$ turns, with the SOQL run on the live organisation); a rewrite on that tier produces the refined answer; the benchmark's evaluator scores it. The initial answers are the cheap-tier episodes of the counterfactual log (already scored and paid). The run logged a tree, a refinement on every tier for every task, so every policy over $\{\text{STOP}, \text{REFINE@cheap}, \text{REFINE@mid}\}$ is an exact lookup: `never`, `always_1:t`, `uncertainty_gated:`$\tau$`:t` ($\tau$ swept 0.3–0.9 on the minimum claim confidence), and a softmax-linear priced controller over 36 features trained by exact policy gradient on the tree (budget $B = \$0.10$ with learned $\lambda$, or fixed $\lambda \in \{2, 5\}$;

5-fold cross-validation over tasks). Of 42 tasks probed, 41 completed on both tiers. One task is 0.024 of quality.





**Figure 10:** Self-refinement policies on the logged tree (41 tasks; cost includes the initial cheap episode), from `frontier.csv`. Open circles are mid-tier gates, filled are cheap-tier. The single-agent mid arm at $0.115 dominates every refinement policy.

**Table 8:** Refinement harm after one round (41 tasks). "fix" is wrong→right out of initially wrong, "harm" right→wrong out of initially correct.

| tier | changed | fix | harm | mean $\Delta q$ | round cost | worker turns |
|---|---|---|---|---|---|---|
| cheap | 85% (35/41) | 13% (3/23) | 28% (5/18) | $-0.049$ | $0.0962 | 14.7 |
| mid | 44% (18/41) | 13% (3/23) | 6% (1/18) | $+0.049$ | $0.2380 | 13.9 |

**Results.** The probe's confidence is weakly informative: AUROC 0.65 (90% CI 0.51–0.79, $n = 41$) of $1 -$ min claim confidence for predicting a wrong initial answer. The decomposer is pessimistic about everything (minimum claim confidence never above 0.75, below 0.4 on 26 of 41 tasks whether right or wrong), the re-solve signal (AUROC 0.67 cheap, 0.55 mid) is no better than the free one, and 22% of mid worker samples are "None". Refinement harms as often as it helps (Table 8): a cheap round fixes 3 of 23 and breaks 5 of 18 ($\Delta q = -0.049 \pm 0.069$), a mid round fixes 3 and breaks 1 ($+0.049 \pm 0.049$), both within one SE of zero. Policies (Figure 10): `never` $0.440 \pm 0.078$ at $0.068; `always_1:cheap` 0.391 at $0.167; `always_1:mid` 0.489 at $0.309; the best fixed cheap gate ($\tau = 0.3$) 0.489 at $0.120; the budgeted controller $0.480 \pm 0.077$ at $0.101 held-out (paired $+0.040 \pm 0.033$ over `never`, refining 20% of tasks, $\bar{\lambda} = 0.09$ per dollar because it sits under budget; 0.533 at $0.100 in-sample); the fixed-$\lambda$ controllers learn `never`. Even the clairvoyant choice among the three logged answers per task reaches only 0.537 at $0.084. Of the three hypotheses, refine-where-confidence-is-low is not established; always-refine-is-dominated-under-a-budget is supported, on the cheap tier by `never` itself; a-priced-gate-reaches-the-frontier holds only in the weak sense that the held-out controller sits on the frontier by learning to refine rarely. The comparison that matters is refine-the-cheap-answer against buy-mid-up-front, and buying the tier wins by a wide margin: the single-agent mid arm on the same 41 tasks scores $0.663 \pm 0.074$ at $0.115; the best cheap-refinement policy at that price is $-0.174 \pm 0.085$ paired for $+$0.004; `always_1:cheap` is $-0.272 \pm 0.099$; refining on mid at 2.7× the cost is still $-0.174 \pm 0.092$; and the frontier tier up front (0.686 at $0.156) beats every refinement policy by 0.17–0.30. The sub-questions need the same schema reasoning that made the cheap agent fail, and the workers inherit it.

**Limitations.** One round, 41 tasks, one initial arm; the $\tau$ sweep is tuned on the tasks it is evaluated on. The in-sample controller row shows what 22 category one-hots memorise on 41 tasks. Agreement with $k = 2$ is weak, and no sampling parameters are sent.

## F The continual orchestrator: complete results

Section 4.3 states the findings; this appendix gives the harness, the simulator and its calibration, the pre-registered stages, the day loop and comparators, every result table, the mild-schedule sensitivity run and the verifier ablation.

**Harness definition.** The multi-agent structure of Appendix D is expressed as a typed harness in the terms of SkillOrchestra and EvoHarnessBench: an agent pool of typed specialists (agent id, tier, mode, stage) with modes planner,

data-worker, verifier and answer; tools the orchestrator can `call@`; skills it can `engage@`; and a competence handbook over the 22 task categories, the axis the real run found carries the signal. The harness $H_t = \{\text{tools}, \text{skills}, \text{agents}\}$ grows monotonically by stages, $H_1 \subseteq H_2 \subseteq \cdots$, plus a price axis. The structure at each stage is frozen and the *policy* at the decision point is what adapts, so the question is EvoHarnessBench's turned around: when $H$ expands under an orchestrator that keeps learning, what happens to the policy's backward and forward transfer, and does the gate keep it safe without making it too slow to matter? There are eighteen actions, `delegate@data-1..4`, `verify@verify-1,2`, `replan@plan-1..3`, `answer@answer-1..4`, `call@schema_lookup`, `call@aggregate_calc`, `engage@soql_aggregate`, `engage@date_window` and `engage@decompose_fine`, and 88 features: the real orchestrator's 66, computed by its own feature function on a view of the simulated state, plus availability flags, tools called, skills engaged, stage and a last-fail flag. Unavailable capabilities have fixed zero feature slots and zero logits, so a policy trained at stage $g$ keeps its weights when stage $g + 1$ arrives.

**Simulator and calibration.** Days of traffic under several harness changes are beyond what the real collection covers, so the logged process is re-expressed as a seeded simulator whose decision points, legal-set rules and feature layout are the real orchestrator's. Every parameter is either measured from the two committed logs (130 multi-agent episodes, 150 single-agent episodes), with its count, or marked assumed (Appendix R). Measured: the plan-length distribution (4/22/104 of 130), worker step kinds per tier, the retry re-draw, the verifier's per-call fail rates by step kind (72 of 124 on rows, 23 of 24 on empty, 12 of 12 structural at $0) and its episode-level $P(\text{flag} \mid \text{wrong}) = 0.92$ and $P(\text{flag} \mid \text{correct}) = 0.96$, token means per role and tier, per-category accuracy, and the configuration. Assumed: whether a rows step is the *right* rows ($P(\text{good} \mid \text{rows}) = 0.60/0.75/0.85$ by tier), the logit slope from plan coverage to the answer (1.5, centred so that `never_verify` reproduces the category base rates), a task-level logit noise (sd 0.4), and everything that arrives after stage 0. On the stage-0 harness the two fixed modes reproduce the real run's process numbers (Table 9).

**Table 9:** Simulator calibration check: stage-0 harness, 1,000 simulated tasks per mode against the real run's 50 tasks per mode (sim / measured).

| mode | accuracy | cost/task | role calls | verifier calls | cap hits | $P(\text{flag} \mid \text{wrong})$ | $P(\text{flag} \mid \text{correct})$ |
|---|---|---|---|---|---|---|---|
| `always_verify` | 0.446 / 0.480 | $0.0894 / $0.0906 | 7.87 / 7.88 | 2.94 / 2.94 | 95% / 94% | 0.95 / 0.92 | 0.93 / 0.96 |
| `never_verify` | 0.459 / 0.460 | $0.0827 / $0.0821 | 4.75 / 4.74 | 0 / 0 | 0% / 0% | – | – |

**Pre-registered stages.** Both schedules were written down before the first full run and not changed afterwards (Table 10). The `mild` schedule keeps the days and axes with smaller effects: reprice mid $\times 0.8$ / frontier $\times 1.2$, `verify-2` at $P(\text{flag} \mid \text{correct}) = 0.60$, `data-4` at rows 0.78 / good 0.75, `answer-4` mid-grade on 3 categories, half the tool and skill bonuses, planner v2 at 1–3 sub-queries.

**Table 10:** The pre-registered default schedule: 40 days, events on days 9 / 17 / 25 / 33.

| stage | day | axis | what changed |
|---|---|---|---|
| g0 baseline | 1 | – | the real run's pool: plan-1, data-1..3, verify-1, answer-1..3; list prices |
| g1 reprice | 9 | price | mid $\times 0.5$, frontier $\times 1.5$ |
| g2 agents | 17 | agents | +verify-2 (a better verifier: $P(\text{flag} \mid \text{correct})$ 0.96 $\rightarrow$ 0.30 at the same recall), +data-4 (database specialist, cheap), +answer-4 (reporting specialist, cheap) |
| g3 tools | 25 | tools | +schema_lookup (the next worker step cannot error), +aggregate_calc |
| g4 skills | 33 | skills | +soql_aggregate, date_window, decompose_fine; the planner now decomposes into 1–4 sub-queries |

**The day loop and comparators.** Each day is 96 seeded tasks, the same for every arm. The continual arm serves its incumbent with $\epsilon = 0.1$ and logs propensities; a learner trains every day by constrained GRPO on replay from the last 5 days of logged states (60 iterations, batch 16, group 6; $\lambda$ learned against $B = \$0.090$ per task; iterate averaging), warm-started from itself; the gate (sequential DR with 200 bootstrap resamples, $\epsilon_q = 0.05$, tol $= \$0.005$) scores the learner against the incumbent on the log served since the last harness event (up to 5 days), with the budget net of the policy-independent prefix (planner plus first worker call, $0.022 at list prices). An AWR+IPS variant (fixed $\lambda = 2$, 200 epochs) runs the same loop. Baselines on the same traffic: `frozen` (the learner as of day 5, served without $\epsilon$, restricted to stage-0 actions); `so_static`, a SkillOrchestra-style router whose handbook is the literal rule competence$[(a, \text{category})] - \lambda_c \cdot \overline{\text{cost}}[a]$ with cost tie-break, learned from the warm-up exploration traces (days 1–4)

with $\lambda_c$ chosen on day 5 by episode-level SN-IPS and never updated (new capabilities scored at the handbook's prior); `so_relearn`, the same router re-fitted after every stage (3 days served with $\epsilon = 0.3$, then a refit and re-tune, the lag counted); `always_verify`; `never_verify`; and a per-stage `oracle` (constrained GRPO on 200 fresh exploration episodes of that stage, 300 iterations, no gate: a reference, not a proven optimum). Held-out evaluation uses 150 fixed tasks per stage, scored by simulator expected quality and never seen by the gate; $J_g = \text{quality} - \bar{\lambda}_g \cdot \text{cost}$ with $\bar{\lambda}_g$ the stage oracle's learned price (1.25 / 0.85 / 0.81 / 0.66 / 0.73 per dollar for g0–g4), at which the budgeted optimum maximises the Lagrangian, so that $J_g$ has a ceiling and regret is well defined. Metrics follow Eq. (11); in addition, $\text{hit}_j$ is the event-day policy's $J$ on stage $j$ minus on stage $j-1$, $\text{recovery}_j = R_{j,j} - R_{j-1,j}$, days-to-recover is the first day of the stage within 0.02 of the oracle, stationary $J$ the mean over the stage's last four days, and cumulative regret the sum over days 6–40 of the oracle's $J$ minus the serving policy's on the day's stage. One seed; five seeds for the arms covered by the ablation below.

### F.1 Results

*(1) The fixed mode `never_verify` wins the whole stream; against the learned alternatives the continual orchestrator wins on every metric.* Cumulative regret over days 6–40 (Table 12, Figure 4): `never_verify` 0.56, continual (constrained GRPO on replay, written cgrpo in the tables; gated) 1.26, `always_verify` 1.99, frozen 2.60, router re-learned per stage 3.03, static router 3.46, continual AWR 3.90. `never_verify`, the all-mid fixed mode, is at the oracle on g1 (0.466 vs 0.460) and within 0.02–0.04 on g2–g4 without learning anything: after the mid repricing, running every sub-query and the answer on the half-price mid tier is the budgeted optimum or near it in this simulator. The continual arm ends every stage within 0.001–0.014 of the oracle and is the only learned arm that recovers at all (days to recover 6 / 6 / 1 / 1); the frozen controller, the static router and the re-learned router never come within 0.02 of the oracle on any stage. The continual arm beats `never_verify` only in the stationary periods of the capability-adding stages (g2 0.429 vs 0.423, g3 0.453 vs 0.434, g4 0.448 vs 0.428) and loses that back during the recovery days. Over 5 seeds of the same configuration (variant A of the ablation below; mean $\pm$ SE), the continual-minus-`never_verify` stationary $J$ is $-0.050 \pm 0.011$ (g0), $-0.009 \pm 0.002$ (g1), $-0.014 \pm 0.007$ (g2), $+0.011 \pm 0.010$ (g3) and $+0.031 \pm 0.007$ (g4), and the whole-stream regret is continual $1.06 \pm 0.21$, `never_verify` $0.74 \pm 0.08$, `always_verify` $1.97 \pm 0.09$: the fixed mode's whole-stream win and the learner's margin at the last stage are both outside seed noise; the g2–g3 margins are not. The honest answer to "does the learner beat the alternatives" is that it beats every design-time learner, and the thing that beats it is knowing the right fixed policy in advance, which the growing pool makes less likely with every stage: the fixed mode's gap to the oracle grows from $-0.006$ at g1 to $-0.038$ at g4.

**Table 11:** Per-event transfer on the default schedule (held-out $J$ of the policy in service; oracle $J$ per stage g1–g4: 0.460 / 0.445 / 0.458 / 0.466; uniform 0.351 / 0.324 / 0.317 / 0.318). Stationary $J$ per stage and BWT per stage are in Appendix S and Figure 12.

| arm | hit at event g1/g2/g3/g4 | FWT g1/g2/g3/g4 | days to recover | gap to oracle at stage end g1/g2/g3/g4 |
|---|---|---|---|---|
| continual (cgrpo, gated) | $+.048/-.050/+.012/-.008$ | $-.020/+.085/+.130/+.128$ | 6/6/1/1 | $-.001/-.010/-.004/-.014$ |
| continual (AWR+IPS, gated) | $+.071/-.019/-.007/-.004$ | $+.012/+.016/+.014/+.006$ | –/–/–/– | $-.102/-.107/-.130/-.155$ |
| frozen (days 1–5) | $+.067/-.041/+.004/-.024$ | $+.060/+.046/+.057/+.032$ | –/–/–/– | $-.050/-.075/-.084/-.116$ |
| static router | $+.053/-.033/-.002/-.033$ | $+.034/+.028/+.032/-.002$ | –/–/–/– | $-.075/-.093/-.109/-.150$ |
| router re-learned per stage | $+.053/-.041/+.015/-.026$ | $+.034/+.024/+.066/+.002$ | –/–/–/– | $-.071/-.076/-.112/-.103$ |
| `always_verify` | $+.097/-.037/+.008/-.021$ | $+.075/+.065/+.080/+.057$ | –/–/–/– | $-.034/-.056/-.062/-.090$ |
| `never_verify` | $+.098/-.043/+.011/-.006$ | $+.115/+.099/+.117/+.109$ | 1/–/–/– | $+.006/-.022/-.024/-.038$ |

**Table 12:** Whole-stream summary, default schedule (mild schedule in parentheses).

| arm | mean BWT | mean FWT | regret, days 6–40 |
|---|---|---|---|
| continual (cgrpo on replay, gated, learned $\lambda$) | $+0.031$ ($+0.035$) | $+0.081$ ($+0.075$) | 1.262 (1.100) |
| continual (AWR+IPS, gated, $\lambda = 2$) | $-0.006$ ($-0.005$) | $+0.012$ ($+0.002$) | 3.896 (3.668) |
| frozen (trained days 1–5) | 0 | $+0.049$ ($+0.053$) | 2.597 (1.970) |
| SkillOrchestra-style static router | 0 | $+0.023$ ($+0.025$) | 3.459 (2.902) |
| SkillOrchestra-style router, re-learned per stage | $+0.019$ ($+0.017$) | $+0.032$ ($+0.014$) | 3.029 (3.057) |
| `always_verify` | 0 | $+0.069$ ($+0.062$) | 1.988 (1.731) |
| `never_verify` | 0 | $+0.110$ ($+0.100$) | 0.559 (0.394) |

*(2) The whole-stream headline is a cold-start artefact: the learner crosses `never_verify` around day 22–25 and wins every stage window after that, while `never_verify` falls further below the oracle at each capability stage.*

Figure 5 in the body. Served $J$, continual minus `never_verify`, by 8-day stage window: g0 $-0.073$, g1 $-0.070$, g2 $-0.021$, g3 $+0.024$, g4 $+0.035$; on the held-out sets $-0.085$, $-0.087$, $-0.004$, $+0.016$, $+0.019$. The served gap is positive from day 24 on and stays positive. Cumulative held-out regret to the oracle restricted to days 17–40 is $0.42$ (continual) against $0.68$ (`never_verify`); restricted to days 25–40 it is $0.22$ against $0.50$, and every other arm is further behind (frozen $1.60$, re-learned router $1.74$, static $2.07$, AWR $2.14$ from day 25). The learner's served $J$ includes its $\epsilon = 0.1$ exploration mass, a tax the fixed policy does not pay, and it still wins after the crossover. The whole deficit in the whole-stream number is the 12 days on the uniform policy before the first promotion (finding 3) plus the repricing recovery (days 9–13, where the half-price mid tier makes `never_verify` the optimum before the learner has moved): `never_verify` is above the reference oracle at g0 and g1 ($+0.023$, $+0.006$ on the held-out sets at stage end) and falls to $-0.022$, $-0.024$, $-0.038$ at g2–g4 as capabilities it cannot use arrive. The post-crossover margin at g4 holds over 5 seeds ($+0.031 \pm 0.007$, above); the stage-2+ capabilities are assumed parameters (Appendix R), so its size is the simulator's.

*(3) The gate's price is larger than its benefit on this stream: 32 of 40 candidates reverted, 9 rightly and 23 as false alarms, first promotion on day 13.* Figure 11 and Table 13. Every one of the 9 correct REVERTS was a budget violation (candidate true cost \$0.095–0.101 against $B+\text{tol} = \$0.095$) and no promoted candidate was bad. The DR cost estimate is the criterion that works: RMSE \$0.006 against the simulator's truth, and the set of candidates it stopped is exactly the set of over-budget candidates. The quality criterion produces the false alarms: 18 of the 32 REVERTS failed on quality alone with the candidate acceptable. At $n \approx 500$–$1{,}000$ logged episodes the DR quality 90% interval is $0.20$ wide and covers the truth 63% of the time, so a candidate whose lower bound must reach the incumbent's point estimate minus $0.05$ passes only when it is visibly better. During days 1–12 the served policy was therefore the uniform $\epsilon$-policy while the learner was already good: the frozen arm, which is the learner's day-5 snapshot, scores $0.411$ on g1 against the served incumbent's $0.247$ on day 9. This is the same sample-size finding as Appendix B.2: the cost side is certifiable at about 500 episodes a day, the quality side is not.





**Figure 11:** Gate history of the continual arm (from `gates.jsonl`). Top: DR quality with its 90% CI against the bar (incumbent's DR quality minus $\epsilon_q$); bottom: DR cost against the budget net of the prefix plus tolerance. Green is PROMOTE, red REVERT; triangles mark candidates the simulator says were truly over budget. The cost criterion catches every bad candidate; the quality criterion rejects acceptable ones until they are visibly better.

*(4) The AWR+IPS variant is the cautionary row, and the caution is about the estimator and the local rule, not about a recorded false promotion.* It was promoted 14 times and is the worst learned arm (stationary $J$ 0.32–0.36). The gate's sequential DR over-estimated its quality by $+0.68$ on average (coverage 6% against the held-out reference).

**Table 13:** Gate history and estimator accuracy against the held-out reference (the candidate's reference value on the current stage). The decision counts, ESS and interval widths are over all 40 gates (mean $n = 360$ episodes per gate); the bias, RMSE and coverage rows are over the 35 gates after warm-up (days 6–40, mean $n = 370$). Appendix M.6 gives both windows for every quantity.

| | continual (cgrpo on replay) | continual (AWR+IPS) |
|---|---|---|
| candidates: PROMOTE / REVERT | 8 / 32 | 14 / 26 |
| REVERT right (candidate bad) / false alarm | 9 / 23 | 0 / 26 |
| PROMOTE right / missed (candidate bad) | 8 / 0 | 14 / 0 |
| mean per-decision ESS / $n$ | 0.54 | 0.25 |
| mean DR quality CI width / cost CI width | 0.200 / \$0.0079 | 0.653 / \$0.0144 |
| DR quality: bias / RMSE / CI covers truth | $-0.005$ / 0.067 / 63% | $+0.676$ / 0.809 / 6% |
| DR cost: bias / RMSE / CI covers truth | $+0.0003$ / \$0.0061 / 54% | $+0.0000$ / \$0.0056 / 69% |
| per-decision SNIPS quality: bias / RMSE | $-0.020$ / 0.053 | $+0.178$ / 0.187 |

Yet an audit of the stored gate records (Appendix M.6) finds that none of its 14 promotions violated the gate's own rule under the reference: each promoted candidate was within $\epsilon_q$ of its incumbent and within budget. The arm's poor aggregate value is what a local non-inferiority rule permits, a chain of individually acceptable candidates that drift by up to $\epsilon_q$ each against a weak starting incumbent, compounded by estimates that could not have stopped a bad one. AWR's exponentiated inverse-propensity weights move the policy far from the behaviour in one full-batch step; the cumulative ratios (clipped at 50) then carry the estimate with a per-decision ESS of 25% and a bias the clip does not remove. The per-decision estimators' bias on the same candidates is $+0.18$, better but not a safe bar. The cgrpo candidates, trained on rollouts sampled from the $\epsilon$-mixed served policy, stay close to the behaviour (ESS 54%) and the same estimator is nearly unbiased on them ($-0.005$). The gate is only as good as the overlap between candidate and behaviour, and a trainer that preserves that overlap is part of the safety story. One confound applies: the AWR arm's logits saturate the soft clip (Appendix M.6), so its deficit mixes the update rule with a loss of plasticity, and under the paired-difference gate with an overlap guard it is simply declared unevaluable on most days.





**Figure 12:** Orchestrator-level backward and forward transfer per stage, Eq. (11), computed from `days.jsonl`. The fixed arms have BWT 0 by construction. The continual arm's large g0 BWT is the day-8 incumbent being the uniform policy (finding 3), not transfer.

*(5) Orchestrator-level BWT is bounded and mostly positive.* Figure 12. The continual arm's BWT per stage is $+0.111$ (g0), $+0.023$ (g1), $+0.009$ (g2), $-0.019$ (g3); the mild schedule gives $+0.120$, $+0.026$, $+0.002$, $-0.009$. Later training did not undo earlier behaviour, and the growing harness makes that easier but does not guarantee it: a capability that arrives at stage $g$ has a zero feature slot and a zero logit before it, but later updates still move the shared weights of the old actions and old features, and those updated weights are what runs on the old stages (a unit test in the repository shows that masking new actions does not freeze old behaviour). Positive BWT here is a measurement, not a consequence of monotone growth. Contrast EvoHarnessBench's $-34.7\%$ BWT for agent-pool expansion under a fixed policy: here the pool expansion costs the fixed policies at the event (frozen hit $-0.041$, static $-0.033$ at g2) and they never recover (stationary $J$ falls from $0.411$ / $0.385$ at g1 to $0.350$ / $0.316$ at g4), while the policy that moves loses nothing on the old stages.

*(6) FWT is a property of the policy in service, not of anticipation.* New capabilities arrive with zero logits, so the

event-day policy is the previous stage's; the continual arm's FWT on g2–g4 ($+0.085$ / $+0.130$ / $+0.128$) exceeds the frozen arm's ($+0.046$ / $+0.057$ / $+0.032$) because it is a better policy, and the static router's FWT falls to $-0.002$ at g4 because its handbook prices unseen capabilities at a prior. Hits at the events are small for every arm except the price event, where the halved mid price lifts every mid-heavy policy by $+0.05$ to $+0.10$.

*(7) The SkillOrchestra-style router is the weakest design-time baseline here, and the reason is diagnostic.* The competence of an action is the mean outcome of episodes in which it was taken, which under per-step exploration is confounded by everything else in the episode: the handbook over-selects `verify@verify-1` (28% of decisions), an action the real run showed buys nothing. And $\lambda_c$ is tuned by episode-level SN-IPS of a deterministic router against $\epsilon = 0.1$ traffic, whose ESS is 1–8 of 96, so the choice of $\lambda_c$ is noise and the re-learned router's $\lambda_c$ swings between 0 and 20 across stages. Re-learning per stage recovers some of the agent-pool loss ($+0.043$ at g4) at the price of three exploration days per stage, and still ends $0.07$–$0.11$ below the oracle. This is a statement about applying the competence-minus-priced-cost rule to multi-step orchestration traces with a per-step router, not about SkillOrchestra's own handbook learning from richer per-skill traces on its own benchmarks.

**Mild-schedule sensitivity.** Figure 13 and Table 12: the ordering is unchanged with smaller gaps (continual 1.10, `never_verify` 0.39, frozen 1.97, static 2.90). In the mild run a learner exceeds the oracle at g1 (gap $+0.006$), a reminder that the oracle is a reference, not a proven optimum.





**Figure 13:** Cumulative regret under the default and the mild schedule. Same ordering, smaller gaps.

### F.2 Verifier ablation: when does verification help?

Is "`never_verify` beats everything" an artefact of the measured verifier (uninformative: $P(\text{flag} \mid \text{wrong}) = 0.92$ against $P(\text{flag} \mid \text{correct}) = 0.96$) and of the 8-call cap that a verify-and-retry process fills? Four controlled variants of the same 40-day stream, 5 seeds each (seeds 0–4; arms: continual cgrpo, `always_verify`, `never_verify`, per-stage oracle): A, the committed configuration (verify-1, cap 8), which also supplies the seed error bars above; B, the informative verify-2 for every arm from day 1 (per-call $P(\text{fail} \mid \text{good rows})$ $0.58 \to 0.114$, recall unchanged); C, B plus cap 12; D, C plus verifier calls exempt from the cap. Served numbers are means over all 40 days (the fixed modes do not learn); $J$ uses the stage oracle's $\bar{\lambda}_g$.

**Table 14:** Verifier ablation: `always_verify` minus `never_verify`, served, mean $\pm$ SE over 5 seeds.

| variant | $\Delta$ expected quality | $\Delta J$ | $\Delta$ cost / task | cap hits (always) | retries / ep. (always) | verifier calls / ep. (always) |
|---|---|---|---|---|---|---|
| A: verify-1, cap 8 (committed) | $-0.033 \pm 0.001$ | $-0.036 \pm 0.001$ | $+\$0.0036$ | 95% | 0.89 | 2.94 |
| B: verify-2 for every arm | $-0.004 \pm 0.001$ | $-0.007 \pm 0.001$ | $+\$0.0030$ | 91% | 0.64 | 2.90 |
| C: B + cap 12 | $+0.029 \pm 0.001$ | $+0.011 \pm 0.001$ | $+\$0.0148$ | 9% | 0.76 | 3.65 |
| D: C + verifier exempt from cap | $+0.028 \pm 0.001$ | $+0.010 \pm 0.001$ | $+\$0.0148$ | 0% | 0.77 | 3.64 |

Table 14 and Figure 14. Under the committed configuration verification *hurts*: `always_verify` is below `never_verify` by $0.033 \pm 0.001$ in expected quality and $0.036 \pm 0.001$ in $J$ for $+\$0.0036$ per task, consistent with the real run's $+1$ task ($+0.019 \pm 0.067$ SE at $n = 50$). The informative verifier alone (B) closes the gap to $-0.004 \pm 0.001$ but does not reverse it, because 91% of `always_verify` episodes still hit the cap and the plan is truncated. Raising the cap to 12 (C) flips the sign: $+0.029 \pm 0.001$ quality and $+0.011 \pm 0.001$ $J$ for $+\$0.0148$ per task ($+18\%$), with 3.65 verifier calls and 0.76 retries per episode and 9% cap hits (the stage-4 four-step plans). Exempting verifier calls from





**Figure 14:** Verifier ablation (from the ablation summary file): `always_verify` minus `never_verify` in expected quality, priced $J$ and cost, and `always_verify`'s cap-hit share, under the four variants; bars are means over 5 seeds with SE. The sign flips only when the verifier is informative *and* the retries do not come out of the plan's call budget.

the cap (D) changes nothing beyond removing the last cap hits ($+0.028$ / $+0.010$): with one retry per sub-query a three-step plan already fits in 12 calls. In summary, verification helps only when the verifier's fail is informative *and* the retry does not come out of the plan's call budget, and then it is worth about $+0.03$ accuracy for $+18\%$ cost, a priced gain of $+0.01$ $J$ at the stage prices. Under C and D the fixed `always_verify` costs \$0.098–0.105 per task, above the learner's $B + \text{tol} = \$0.095$, so it can exceed the budget-constrained oracle at a stage (g1 in C: $0.443$ vs $0.434$); the learner's verify share rises from $0.03$–$0.09$ (A) to $0.10$–$0.13$ (B–D) of its decisions and no further, and within budget it still ends the last stage above `never_verify` under every variant (g4: A $+0.031 \pm 0.007$, B $+0.017 \pm 0.011$, C $+0.016 \pm 0.007$, D $+0.013 \pm 0.010$). The whole-stream regret ordering under C and D is `always_verify` $0.30 <$ `never_verify` $0.60 <$ continual $1.05$–$1.20$: with a verifier worth using and a cap that does not truncate, the right fixed mode is `always_verify`, it is over budget, and the budgeted learner is third, its cold start still the whole deficit. Two caveats. The informative verifier's episode-level $P(\text{flag} \mid \text{correct})$ in the simulator is $0.71$, not the $0.30$ its per-call parameter was derived from, because correct episodes still contain empty and wrong steps that are rightly flagged; the per-call parameter is what the ablation sets. And the effect size rests on the assumed link from a step's latent quality to the answer.

**Table 15:** The real log (130 MAS episodes): what a flagged step's retry did. Observation kind before the flag (rows) against after the retry (columns).

| before → after | rows | empty | error | invalid | respond | total |
|---|---|---|---|---|---|---|
| rows | 26 | 2 | 5 | 0 | 0 | 33 |
| empty | 5 | 7 | 0 | 1 | 0 | 13 |
| error | 5 | 1 | 0 | 0 | 0 | 6 |
| invalid | 0 | 0 | 0 | 0 | 1 | 1 |

The real log gives the per-step number beside the per-episode one (Table 15): 107 verifier fails, 53 followed by a retry of the same sub-query (the rest hit the cap or the one-retry limit). The retry changed the observation kind in 10 of 53 cases (19%), always from empty or error to rows: a flagged empty, error or invalid step became rows in 10 of 20 cases, so the retry does repair malformed or empty steps; but 33 of the 53 retries were of a step that had returned rows, and 26 of those returned rows again. When the retried step was verified again it passed 11 of 47 times (23%) against 42 of 114 (37%) for first attempts. Paired with `never_verify` on the same tasks, the 44 `always_verify` episodes that retried flipped 6 wrong→right and 5 right→wrong, with 16 unchanged right and 17 unchanged wrong (25% flipped, symmetric). Per step and per episode say the same thing: the measured verifier's flag is not information about correctness.

**What this does not show.** Effect sizes are the simulator's: the stage-2+ capabilities are assumed, as is the link from a worker step's latent quality to the answer. One schedule plus a mild one; the all-arms run is one seed, with 5-seed error bars for the continual, `always_verify`, `never_verify` and oracle arms from the ablation. The per-stage oracle

is constrained GRPO on fresh exploration, not a proven optimum. Nothing here calls a model API; what a real-traffic run would require is in Appendix J.

## G $\tau$-bench and EvoHarnessBench: complete results

Section 4.4 states the findings; this appendix gives the setups and the per-suite tables. Both suites follow the counterfactual protocol of Section 4; their settings are in Table 27.

### G.1 $\tau$-bench

The agent is the tier model; the user simulator is fixed to the cheap tier for every arm, its cost logged and excluded from the agent cost. Quality is the benchmark's own reward, pass$^1$ per task. Episodes are long, 13–15 agent turns, each resending the policy document and tool schemas, so the cost column is three to four times the CRMArena-Pro column and the tier spread is wider. The budget for the constrained policies is the uniform behaviour's own mean agent cost ($0.277 retail, $0.294 airline), since no product budget exists for this suite.

| $\tau$-bench retail, 60 tasks $\times$ 3 tiers | pass$^1$ | agent cost/task | held-out $J$ ($\lambda = 2$) [fold SD] |
|---|---|---|---|
| fixed cheap | 0.583 | \$0.117 | 0.350 [0.135] |
| fixed mid | 0.683 | \$0.229 | 0.226 [0.154] |
| fixed frontier | 0.717 | \$0.487 | $-0.257$ [0.176] |
| uniform behaviour | 0.661 | \$0.277 | 0.107 [0.146] |
| AWR+IPS linear, served | 0.626 | \$0.186 | 0.255 [0.135] |
| per-category rule / constrained ($B = \$0.28$), greedy | 0.583 / 0.683 | \$0.117 / \$0.229 | = fixed cheap / = fixed mid |
| per-task oracle (max reward, cheapest among ties) | 0.867 | \$0.171 | 0.524 [0.080] |

**Table 16:** $\tau$-bench retail: fixed tiers, the oracle, and first-step policies (5-fold cross-validation over task ids). 52 of 60 tasks are solved by at least one tier and 26 by all three. The first-step feature vector is the domain one-hot only, so every learned first-step policy collapses to a fixed arm.

| $\tau$-bench airline, 49 tasks $\times$ 3 tiers | pass$^1$ | agent cost/task | held-out $J$ ($\lambda = 2$) [fold SD] |
|---|---|---|---|
| fixed cheap | 0.449 | \$0.099 | 0.251 [0.176] |
| fixed mid | 0.551 | \$0.261 | 0.027 [0.153] |
| fixed frontier | 0.531 | \$0.523 | $-0.516$ [0.121] |
| uniform behaviour | 0.509 | \$0.294 | $-0.079$ [0.121] |
| AWR+IPS linear, served | 0.490 | \$0.203 | 0.084 [0.134] |
| per-category rule / constrained ($B = \$0.29$), greedy | 0.449 / 0.551 | \$0.099 / \$0.262 | = fixed cheap / = fixed mid |
| per-task oracle (max reward, cheapest among ties) | 0.735 | \$0.159 | 0.428 [0.064] |

**Table 17:** $\tau$-bench airline, collected to 49 of its 50 sampled tasks (the ledger cap bound before the last). 36 of 49 tasks are solved by at least one tier and 14 by all three; the mid tier beats the frontier tier at half its cost.

On both domains the realised-log gate on the all-task constrained policy REVERTS on the quality bar (retail: DR 0.753 [0.613, 0.876] against a bar of 0.620; airline: 0.559 [0.346, 0.758] against 0.460) and 5% of redraws promote; with a binary reward and 49–60 tasks the DR quality interval is 0.30–0.40 wide. The decision that would capture the oracle's headroom is a mid-episode tier switch conditioned on the conversation so far, which this protocol does not log.

### G.2 EvoHarnessBench, tools axis

The service exposes a harness that grows its tool set across six stages, $H_1 \subset H_2 \subset \cdots$; each task is run under the tool allowlist of its own stage, on all three tiers, with prompt caching on the fixed prefix (so the cost column is at cached prices and is not comparable to the other suites'). Score is the service's partial-credit grade, the fraction of hidden verifiers passed; pass requires all of them. Tasks were sampled by a seeded round-robin over (domain, split, cohort) groups covering both the held-out and the adaptation split, 50 per stage at stages 1, 2 and 4; stages 3, 5 and 6 were not collected.

At every stage the mid tier beats the frontier tier on score at about half its cost, and the oracle beats every single tier at or below mid-tier cost, choosing the frontier tier for only 4 tasks in 50. The ordering is the same at each of the three harness sizes, so growing the tool set did not change which tier is worth buying. Two limits of this collection should be

| stage | | cheap | mid | frontier | per-task oracle | oracle picks c/m/f |
|---|---|---|---|---|---|---|
| | score | 0.491 | **0.702** | 0.619 | 0.753 | |
| $H_1$ (50) | pass | 0.24 | 0.42 | 0.40 | 0.52 | 26 / 20 / 4 |
| | cost | \$0.062 | \$0.146 | \$0.298 | \$0.136 | |
| | score | 0.370 | **0.699** | 0.610 | 0.741 | |
| $H_2$ (50) | pass | 0.16 | 0.40 | 0.30 | 0.48 | 21 / 25 / 4 |
| | cost | \$0.044 | \$0.114 | \$0.227 | \$0.106 | |
| | score | 0.403 | **0.643** | 0.631 | 0.738 | |
| $H_4$ (50) | pass | 0.14 | 0.28 | 0.30 | 0.38 | 18 / 28 / 4 |
| | cost | \$0.056 | \$0.147 | \$0.262 | \$0.138 | |

**Table 18:** EvoHarnessBench tools axis, 150 tasks with all three tiers (held-out and adaptation splits pooled; 34–36 held-out per stage). Score is the mean verifier pass rate; cost is per task at cached prices. The oracle picks the cheapest tier among those with the best score.

noted: every task ran under its own stage's harness, so all held-out tasks feed the benchmark's forward-transfer group and none of its backward-transfer cells (earlier-stage tasks re-run under later allowlists); and no controller was trained on these logs, since the stage-wise logs are of a size at which Appendix B.1 found first-step policies memorising. What the suite adds is the tier-level replication under a growing harness, on a scorer that is not ours.

# H Follow-up experiments: delegation credit, meta-learned initialisation, and a skill handbook

Each follow-up changes one thing in the continual study or the first collection and is run over five seeds; each has the control that its result needed.

**RAO-style delegation credit (negative).** We added the node reward of Gandhi et al. [9] to the continual orchestrator's trainer: for a `delegate` decision, the per-decision reward is the episode's priced outcome plus $\lambda_d$ times the mean success of the sub-call it spawned, with a leave-one-out baseline anchored on the root reward. Over five seeds on the committed simulator and schedule, the delegation share rose at every stage (from 0.17/0.44/0.50/0.51/0.55 across the five stages without credit to 0.26/0.47/0.57/0.62/0.62 with $\lambda_d$=0.5) and served regret over days 6–40 rose from $0.94 \pm 0.27$ to $1.74 \pm 0.18$; stationary priced $J$ fell by 0.02–0.04 at every stage after the baseline. Because the credit mode also changes the baseline, we ran the same mode with $\lambda_d$=0: regret $0.99 \pm 0.24$ and unchanged shares. The credit, not the baseline, buys over-delegation. The learner without credit already delegated to new specialists from the stage they appeared; a bonus outside the baseline turns that into a habit.

**Meta-learned controller initialisation (positive, caveated).** The learner's deficit against the fixed policy was its cold start. Following the meta-learned initialisation of Tandon et al. [36], we learned the controller's initial weights by a first-order meta-loop over the simulator's stage definitions $g_0$–$g_3$ (never $g_4$, never a held-out set; audited per run), then ran the continual arm from that initialisation. Over five seeds, served regret over days 6–40 fell from $1.06 \pm 0.21$ to $0.47 \pm 0.08$ (paired $-0.59 \pm 0.15$) and over days 17–40 from $0.76 \pm 0.18$ to $0.43 \pm 0.07$; the learner now has lower regret than `never_verify` ($0.74 \pm 0.08$) on the full stream. The gain comes from what is served before and between promotions, not from earlier promotion (the first-promotion day is unchanged at 5.2 in this arm set), and there is no gain on $g_4$, the one stage the meta-initialisation never saw. The caveat is structural: the initialisation was trained on the simulator's own stage definitions; on real traffic it would have to be learned from past harness generations, which is the design-time loop of Figure 2.

**Skill handbook for the cheap tier (null, with the control that showed it).** The cheap tier scores 0.444 on the first 50 real tasks because it fails schema reasoning, while the mid and frontier tiers solve many of the same tasks. We distilled per-category procedural notes from those successful SOQL episodes with the mid-tier model as writer (leave-one-task-out, so no task saw notes from its own solution; 49 writer calls) and served the cheap tier with the notes in its prompt. Quality rose to 0.581 ($+0.137 \pm 0.070$ paired). But the 14 tasks that received no notes improved by the same amount as the 36 that did, so we re-ran the cheap tier with no notes: 0.561, a difference from the skilled arm of $+0.020 \pm 0.067$. The handbook did nothing measurable; the original 0.444 was a low draw. What survives is the size of that draw: the same tier on the same 50 tasks moved by $+0.117 \pm 0.062$ between two runs a day apart, which is as large as the gap between tiers in Appendix B.1, and a second, independent reason the gate of Appendix B.2 refused to certify a margin

of that size.

## I Advantage-weighted regression with inverse propensities

When no replay exists, so that a logged state cannot be re-rolled, the trainer is advantage-weighted regression [27] on logged steps with return $R_i = q_i - \lambda C_i^{\rightarrow}$ (cost-to-go from the step), a per-bucket value baseline $\hat{V}$, and weights corrected by the logged propensity and self-normalised over the batch:

$$A_i = R_i - \hat{V}(b(x_i)), \qquad w_i = \frac{\exp(A_i/\beta)/\mu_i}{\sum_j \exp(A_j/\beta)/\mu_j}, \qquad \max_W \sum_i w_i \log \pi(a_i \mid x_i). \tag{12}$$

Here $\lambda$ is a fixed price. Logged counterfactual arms, when present, are added as extra records; offline RL can only reweight what the log contains. The AWR arm appears in the first CRMArena-Pro collection (Appendix B.1), the 300-task results (Section 4.1), the $\tau$-bench tables (Appendix G) and the continual study, where it is the cautionary row: with the largest distance from the behaviour policy (effective sample size 25% against 54% for the replay trainer) it is the arm whose quality the gate's estimator over-stated most. One further caveat concerns the weights: $1/\mu_i$ corrects the action propensity at the logged step, not the distribution of states the behaviour policy visited nor the behaviour continuation inside the logged return, and exponentiating a noisy return is not the same as exponentiating its expectation. The objective is therefore a propensity-corrected imitation of high-return logged actions, useful as a logs-only trainer, and not an unbiased optimiser of the candidate's full-policy value.

## J Requirements for a real-traffic continuation

The same loop on the real orchestrator: days of 20 B2B tasks, the learner trained with AWR+IPS on the day's log (no replay exists on the real harness) and gated with the per-decision estimators, held-out evaluation by re-serving a fixed 20-task set per stage. Stages that can be induced for real: a repricing (free, with costs recomputed from logged tokens); a better verifier (swap its prompt or tier); a new worker or answer backbone (any priced model); a worker swap by tier; a schema-lookup tool (one describe call) or a local aggregation tool; skills as steering text (tokens only). Such a run needs about 500 served episodes per gate for the cost criterion to bind, as the simulator study found, a quality bar on the paired difference rather than the incumbent's point estimate, a stated label contract (which outcome counts as $q$, when it arrives, and how missing labels are treated, since a missing label is neither a success nor a failure), and a separate ledger for exploration, training, evaluation and failed runs, so that the traffic needed to amortise adaptation is a number rather than an assumption. The gate's quality criterion will not certify improvements at that size; it will only reject regressions, which is the use the discussion recommends.

## K Extended related work

**Cost-aware routing.** FrugalGPT [5] cascades models by a learned score to cut cost; RouteLLM [26] learns a router between a strong and a weak model from preference data; xRouter [29] trains a cost-aware orchestration system with reinforcement learning. These choose a model per query at the first turn. This paper prices every decision point inside a frozen harness, learns the price as a dual variable against a budget, and gates deployment off-policy. SkillOrchestra [41] routes each query to a typed agent in a pool by a learned competence profile with an explicit cost penalty, learned once from traces and then served statically; the continual study implements its literal routing rule as a baseline and finds, in finding (7) of Appendix F, why a competence learned from per-step exploration traces of a multi-step orchestrator is confounded.

**Self-evolving agent systems and the deployment seam.** A position paper from the AReaL group [42] argues that enterprise self-evolving agents are blocked not by RL algorithms but by systems: a step-level episode-log protocol, a data proxy that turns production workloads into governed learning material, and a unified *evolution control plane* that selects, from log statistics, drift indicators and cost, among memory updates, skill updates, harness edits, weight updates, rollback or no-op, each behind replay-first evaluation, regression tests and canary rollout. This paper instantiates part of that architecture: the gate is a measured, interval-valued form of their replay-first check; priced backward and forward transfer are the drift indicators they call for; and the continual orchestrator is a per-request learner inside the harness surface they name, with the harness-edit surface left to the slow loop. Their prototype realises the weight-update path by redirecting deployed agents' inference calls through managed workers, the same seam that Agent Lightning [24] uses to make training harness-agnostic through a proxy that emulates the inference APIs. Placing the controller

in that proxy is the deployment path we would take, since tier choice, verification and stopping are decisions at the API boundary, while re-planning and delegation still need a hook inside the orchestrator. Production precedent for the cadence exists: online RL after deployment has shipped with checkpoints refreshed from user interaction every few hours.

**Recursive delegation and priced effort.** Recursive Agent Optimization [9] trains agents that spawn instances of themselves through a `launch_subagent` call, with a local node reward equal to the node's own success plus $\lambda_d$ times the *mean* success of its children (averaging rather than counting, which removes the incentive to spawn), a leave-one-out baseline anchored on the root reward, and depth-level inverse-frequency weighting so that deep sub-tasks do not dominate the update. Four points carry over. That node reward is the principled process reward for the delegate action of Appendix D, where our process rewards were definitional; the follow-up of Appendix H adopts its form and finds that it buys over-delegation under a price. Depth weighting is the recursive counterpart of the per-decision estimators used here. Delegation in RAO is unpriced, with depth and step caps standing in for a budget, so adding $\lambda \cdot$ cost and $\mu \cdot$ latency to the node reward is the one-line extension that turns the caps into a learned price. And RAO's generalisation from medium to hard tasks concerns the learned decomposition skill, not drift of the harness around it, which is what the transfer metrics here measure. On the shaping of the price itself, the Composer 2 report describes a nonlinear effort penalty over tokens, tool calls and turns whose slope is steeper on easy tasks than on long-horizon ones; the objective here uses a single linear $\lambda$, and a difficulty-conditioned price, $\lambda$ per task category or a concave cost curve, is a direct extension that the logs here are too small to fit.

**Contextual bandits in production.** The Decision Service [1] and Horizon [10] established the logging discipline (propensities with exploration), the offline evaluation [4, 22] and the promotion workflow that the gate follows; the estimators are those of Dudík et al. [8], Jiang and Li [14], Swaminathan and Joachims [35], Thomas and Brunskill [38], with cross-fitting after Chernozhukov et al. [7].

**Test-time compute and self-refinement.** Socratic Self-Refine [32] decomposes an answer into verifiable sub-questions and rewrites where confidence is low; the uncertainty signals (verbalised confidence, sample agreement) follow Bakman et al. [3]. Appendix E treats how much of it to buy per request as a priced decision and finds that, on a CRM benchmark, a better tier up front dominates.

**Process verification and reward modelling for multi-agent systems.** MAS-ProVe [40] verifies multi-agent executions at the level of the individual agent call or of one iteration, online, by sampling three candidates and keeping the one the verifier ranks highest, across six frameworks and five benchmarks; it finds the gains inconsistent and high-variance, generative judges ahead of reward models, and step-only context as good as the full history. Its unit of verification is the decision point studied here, and its finding is one this paper reproduces on a priced log: the verification itself is a purchased action, three calls for one, and whether it pays is a per-decision question. Reward modelling for orchestration [39] scores an orchestration plan before any sub-agent runs, with a Bradley–Terry model trained on preference pairs mined from execution logs, so that best-of-$N$ selection and orchestrator training avoid full rollouts; it is a reward model, not an estimator, and the natural combination with the gate is as the direct model inside DR. MAS-Orchestra [15] trains a holistic orchestrator with an outcome-only reward and asks when a multi-agent system beats a compute-matched single agent. ToolOrchestra [34] trains a stepwise orchestrator over tools and models with a composite reward that includes an efficiency term, the closest prior use of a priced orchestration reward, though unpriced at the per-decision level and without an off-policy gate. Appendix D measures the first three on one log and finds the verifier uninformative, the process features without out-of-fold signal, and the single agent ahead.

**Harness evolution and continual-learning metrics.** The design-time line [2, 6, 12, 21, 46, 47] and EvoHarnessBench [16] evolve or grow the harness; the BWT and FWT definitions are those of Lopez-Paz and Ranzato [23], applied here to a priced objective at the orchestrator level. Meta-Harness in particular proposes a new harness by reading the full execution history of the previous ones; it is the natural producer of $H_{t+1}$ in the design-time loop of Figure 2, and the gate here is what would decide whether a controller trained on $H_t$ still serves under it.

**Offline and constrained RL.** CQL [19] and IQL [18] are the standard pessimistic offline learners; AWR [27] is the simpler weighted-regression trainer used here with inverse propensities; GRPO [31] supplies the group-relative advantage and DAPO [45] the dynamic-sampling and clipping variants used in the platform controls; the learned price follows RCPO [37] and the PID-Lagrangian [33], with iterate averaging after Nedić and Ozdaglar [25].

## L Threats to validity

- **Sample sizes.** The real-harness evidence is 300 B2B and 150 B2C tasks on CRMArena-Pro, 60 and 49 tasks on the two $\tau$-bench domains, and 50 tasks at each of three EvoHarnessBench stages, every task on every tier. The held-out numbers of Appendix B.1 are means over 10 tasks per fold, where one task is $0.1$ of quality and the across-fold SDs are as large as the differences between policies; the 300-task section is where the orderings become stable, and the gate's intervals are still five times the budget margin there. The multi-agent run has 130 episodes on the first 50 tasks; the self-refinement run 41 tasks. The negative results for the ORM, the refinement gate and the first-step policies on $\tau$-bench are statements about these sample sizes and observables, not about the approaches.
- **Seeds.** The simulator pipeline reports 5 seeds; the CRMArena folds one split, and each GPU run ran once; the continual study's all-arms run is one seed per schedule, and only the verifier ablation and the follow-ups (continual, the two fixed modes and the oracle) report 5-seed error bars. The router and AWR arms carry no seed variance.
- **Simulators calibrated to the project's own logs.** The simulator of Appendix A is hand-written. The continual simulator's process statistics are measured on 130 episodes, but the link from a step's latent quality to the answer and every capability that arrives after stage 0 are assumed (Appendix R); the transfer effect sizes are the simulator's, not CRMArena's. The calibration check reproduces the fixed modes' cost and call counts but lands accuracy at $0.446/0.459$ against $0.480/0.460$, because the simulated verifier is uninformative, as the measured one is.
- **Assumed stage parameters.** $P(\text{good} \mid \text{rows}) = 0.60/0.75/0.85$ by tier; coverage-to-answer logit slope 1.5; task-level logit noise sd 0.4; `verify-2` at $P(\text{flag} \mid \text{correct}) = 0.30$ with the same recall; `data-4` at rows 0.85 / good 0.80; `answer-4` mid-grade on 8 categories; `schema_lookup` removes error mass from the next step; `aggregate_calc` adds $+0.34$ coverage on aggregation categories; the three skills add $+0.15$ $P(\text{good} \mid \text{rows})$ on their categories or re-plan into 3–4 sub-queries; planner v2 plan length $(0.0, 0.1, 0.4, 0.5)$. Tools and skills are priced as a verifier-sized cheap call (711/62 tokens).
- **The SkillOrchestra baseline is the literal rule, not their system.** Competence minus $\lambda_c$ times mean logged cost, over task categories as skills, learned from per-step exploration traces of a multi-step orchestrator. Their handbook learning from richer per-skill traces on their own benchmarks is not reproduced.
- **The oracle is a reference.** Constrained GRPO on fresh exploration with more iterations, not a proven optimum; regret can be slightly negative.
- **Gate design.** The simulator gate fits its direct model in-sample; the bandit gate cross-fits by task; the continual gate uses the sequential DR with cumulative ratios clipped at 50, whose bias on far-from-behaviour candidates is what finding (4) of Appendix F exposes.
- **The $\tau$-bench first-step policies.** With the domain one-hot as the only step-0 feature, the learned first-step policies cannot differ from a fixed arm; the suite bounds the headroom and says what to log next, and nothing more.
- **EvoHarnessBench pricing and coverage.** Its cost column is at cached prices; stages 3, 5 and 6 and the backward-transfer cells were not collected; no controller was trained on its logs.
- **Run-to-run variation of a tier.** The same tier on the same 50 tasks moved by $+0.117 \pm 0.062$ between two runs a day apart (Appendix H), which bounds what any held-out comparison at that scale can certify.
- **Fold SD and exact lookups.** The across-fold SD describes the spread of five overlapping training sets and is not a confidence interval; a lookup is exact for the stored outcome table and removes none of the task-sampling, outcome-sampling or run-to-run variation. No number in this paper treats folds or redraws of one table as independent repetitions of the whole procedure.
- **Budget semantics.** $B$ is an expected per-task cost, not a per-request cap or a latency guarantee; exploration imposes a cost floor over the legal set, so some budgets are infeasible under a mandated $\epsilon$, and an increasing multiplier cannot manufacture a feasible policy. The collection spend cap protects the experiment, not a request.
- **Baseline confounds in the continual study.** The frozen arm is restricted to stage-0 actions, so its deficit combines missing capabilities with absent learning; the per-stage reference policy receives fresh exploration and more optimisation; the lookup trainer sees every arm where a production log would not. Each comparison isolates one factor only where stated.
- **Quality labels in deployment.** Every quality here is a benchmark evaluator's. On real traffic quality is delayed, sparse or a judge's proxy; logging propensities does not supply labels, and the gate's quality criterion depends on their meaning and availability.
- **Data terms.** CRMArena-Pro is CC BY-NC 4.0 (research use), fetched at setup and not copied; the committed traces are derived research artefacts under the same terms (Appendix U).

# M Robustness analyses

This appendix collects analyses that test assumptions made in the body or bound quantities that the body reports as upper bounds; each names the script that produces it.

## M.1 Iterate averaging and budget feasibility of the served policy

The served policy is the statewise average of weight snapshots, $\bar{\pi}(a \mid s) = \frac{1}{|\mathcal{S}|} \sum_W \pi_W(a \mid s)$. For a one-decision bandit the expected quality and cost of $\bar{\pi}$ are the averages over snapshots, because the context is exogenous. In a multi-step harness this fails in general. A two-step counterexample, implemented as a regression test in the repository: the first action chooses a branch at zero cost; at the second step the action that matches the branch costs 1 and the other costs 9. One snapshot prefers action $a$ everywhere and the other prefers $b$ everywhere ($W_2 = -W_1$, logit clip 3, $\epsilon = 0.1$). Each snapshot's expected episode cost is 1.79, as is a mixture that picks one snapshot per episode; the statewise average costs 5.00, because it takes the branch of one snapshot and the second action of the other. A budget of 2 is met by both snapshots and violated by their average. The iterate-averaging argument from convex optimisation [25] therefore does not establish the budget for this implementation, and it is not relied upon here: the served mixture's cost is measured on the served log. For the continual study, the measured mean cost per task of the served policy by stage, against $B + \text{tol}$, is given in Appendix M.6. Changing the mixing semantics to an episode-level choice of snapshot would require logging the latent snapshot choice, since the trajectory probability under the mixture is no longer a product of per-state mixture probabilities.

## M.2 Anchor distribution of the replay trainer

The replay trainer draws half of each batch's anchors from episode starts and half from all logged states, with the restart distribution held fixed within an update. Its primal step therefore ascends $F_\rho = (1-\rho)\,\mathbb{E}_{s\sim d_0}[V_\pi(s)] + \rho\,\mathbb{E}_{s\sim d_L}[V_\pi(s)]$, where $d_0$ is the task-start distribution and $d_L$ the distribution of logged states, while the dual step tracks full-episode cost from start-state rollouts; the two Lagrangians coincide only if the policy class can be optimal at every state at once. At $\rho = 0.5$ about 77% of the restart mass falls on episode starts, because logged states include the starts. To measure what the mixing does, the simulator pipeline was run with $\rho = 0.5$ (the committed default) and $\rho = 0$ under a matched budget of simulator transitions (start-only training consumes about 8% more transitions per iteration, so it ran 281 iterations against 300), over seeds 0–4, with ground truth over 20,000 fresh tasks (`scripts/restart_ablation.py`).

| arm | transitions | $\bar{\lambda}$ | truth quality | truth cost | $J$ | gate |
|---|---|---|---|---|---|---|
| $\rho = 0.5$ (default) | $181{,}097 \pm 3{,}465$ | $0.358 \pm 0.027$ | $0.878 \pm 0.001$ | $0.306 \pm 0.002$ | $0.768 \pm 0.008$ | 5/5 PROMOTE |
| $\rho = 0$, matched transitions | $181{,}473 \pm 3{,}455$ | $0.391 \pm 0.014$ | $0.880 \pm 0.001$ | $0.308 \pm 0.002$ | $0.770 \pm 0.008$ | 5/5 PROMOTE |
| $\rho = 0$, 300 iterations | $196{,}204 \pm 4{,}624$ | $0.392 \pm 0.013$ | $0.879 \pm 0.001$ | $0.307 \pm 0.002$ | $0.770 \pm 0.009$ | 4/5 PROMOTE |

**Table 19:** Mixed against start-only anchoring, mean $\pm$ SE over 5 seeds; $J$ at the default arm's $\bar{\lambda}$. The paired difference in $J$ is $+0.0014 \pm 0.0008$. The one REVERT in the third row is a knife edge, a DR cost upper bound of 0.32000 against a threshold of 0.32.

On this simulator the mixing is neither a help nor a harm at matched compute. Interior anchoring is therefore described as the mechanism that gives the trainer per-decision anchors, not as a solution of the episode-start objective; the derivation above states what it optimises.

## M.3 Hindsight component of the realised-outcome oracle

The per-task oracle selects the best realised arm, so part of its gap to any policy is luck over stochastic outcomes rather than predictable heterogeneity. One repeated run exists: the cheap tier was run twice on the first 50 B2B tasks, a day apart (Appendix H). Correctness agrees between the two runs on 80% of tasks (10 flips: 8 wrong-to-right, 2 right-to-wrong; accuracy 0.44 then 0.56, so drift between runs cannot be excluded), the mean per-task outcome variance is 0.10, and the test–retest correlation is 0.62 (90% bootstrap interval 0.45–0.79). On these 50 tasks the realised oracle scores 0.76 against 0.66 for the best single tier. Under a mean-preserving shrinkage model that borrows the cheap tier's repeatability for the mid and frontier tiers, whose noise was not measured, the expected probability oracle is 0.72–0.74, so the hindsight component is about 0.02–0.04 of the 0.10 gap (`scripts/crmarena_hindsight_oracle.py`). Treating the three tiers' outcomes as independent would put the component at 0.10–0.16, but that model predicts a realised oracle of 0.83–0.89, above the observed 0.76, so it is an upper bound rather than an estimate. On this evidence, most of the oracle gap on this benchmark is predictable heterogeneity, with the caveat that it rests on one repeated arm; the identical-arms example of Section 4 shows why the caveat is needed.

### M.4 The promotion gate under a train–evaluate split

The gate experiments of Section 4.2 and Appendix B.2 fix a candidate trained on the full outcome table and then mask that table to one arm per task; they test the estimators on a fixed table and a fixed candidate. The end-to-end protocol separates candidate learning from evaluation: for each of the five folds the constrained policy is trained on the training folds only, then gated on the held-out fold's realised one-arm log (60 tasks per fold on B2B, 30 on B2C), over 200 redraws with a 200-resample bootstrap each, with the direct model cross-fitted within the held-out fold (`scripts/crmarena_cv_gate.py`).

| | B2B | B2C |
|---|---|---|
| correct decision by fold (exact held-out value) | promote $\times 4$, revert $\times 1$ | promote $\times 4$, revert $\times 1$ |
| promotion rate over redraws, by fold | 0.04, 0.06, 0.17, 0.00, 0.10 | 0.07, 0.01, 0.01, 0.00, 0.04 |
| pooled promotion rate | 0.073 | 0.023 |
| pooled decision accuracy | 0.27 | 0.22 |
| DR quality: bias / RMSE / interval width / coverage | $+0.001$ / 0.061 / 0.29 / 98% | $+0.003$ / 0.088 / 0.40 / 97% |
| DR cost: bias / RMSE / interval width / coverage | $-0.000$ / 0.015 / 0.050 / 91% | $-0.000$ / 0.018 / 0.068 / 93% |

**Table 20:** The end-to-end gate: candidate trained on training folds, gated on the held-out fold's realised log. The one fold whose candidate is over budget (exact cost \$0.138 on both organisations) is correctly reverted; the four acceptable candidates are mostly reverted too.

The limitation is the sample rather than the estimator: DR is unbiased and its intervals cover, but at 30–60 tasks the quality interval is three to five times the true gain, so the gate reverts almost everything and its decision accuracy is about one in four. Compared with the fixed-candidate experiment of Section 4.2, whose candidate had seen every task and whose redraws promoted 30% of the time at 300 tasks, this is the relevant figure for a candidate that must be learned from the traffic on which it is judged: the sample-size result of the body applies to the held-out fold, not to the whole log.

### M.5 Exact-gradient and linear-programming baselines

With every arm of every task logged, the empirical objective $\sum_a \pi_\theta(a \mid x)\,[Q(x,a) - \lambda C(x,a)]$ can be differentiated exactly, and a category policy can be found by a small linear programme over category-by-tier probabilities on training-fold means under the budget. Both were run under the same folds as Table 1 (`pace/train_exact.py`, `scripts/crmarena_exact_vs_sampled.py`).

| held-out, $J$ at $\lambda = 2$ | B2B q / cost / $J$ | folds $\leq B$+tol | B2C q / cost / $J$ | folds $\leq B$+tol |
|---|---|---|---|---|
| sampled constrained GRPO, served | 0.596 / \$0.102 / 0.393 | 4/5 | 0.617 / \$0.103 / 0.411 | 4/5 |
| sampled, greedy | 0.644 / \$0.103 / 0.438 | 4/5 | 0.677 / \$0.105 / 0.466 | 4/5 |
| exact gradient, full batch, served | 0.610 / \$0.103 / 0.405 | 4/5 | 0.628 / \$0.104 / 0.421 | 4/5 |
| exact gradient, greedy | 0.640 / \$0.101 / 0.438 | 4/5 | 0.677 / \$0.103 / 0.471 | 4/5 |
| budgeted per-category LP (train-fold means) | 0.644 / \$0.094 / 0.455 | 4/5 | 0.634 / \$0.094 / 0.446 | 4/5 |

**Table 21:** Sampled against exact training on the fully observed table. The exact gradient lifts the served policy by about 0.01 in $J$ and learns a lower multiplier (0.66 and 0.95 per dollar against 1.22 and 1.21); the greedy decodings coincide. The LP's budget is slack in every fold, so it reduces to the highest-quality tier per category, and it is the only constrained policy at or below $B$ on the mean. Every method trains in well under a second per fold.

The sampled trainer is kept in the body because it is the trainer the replay experiments need; on this table it is neither better nor cheaper than the exact one.

### M.6 Gate-record audit and a paired-difference gate variant

**Audit of the committed run.** Every gate record of the default run was re-read against the simulator's held-out reference (`pace/experiments/mas_continual/gate_audit.py`; Table 22). Two facts follow from it. First, Table 13 reports its counts over all 40 gates and its estimator statistics over the 35 after warm-up. Second, no promotion of either arm violated the gate's own rule under the reference: every one of the nine correct REVERTS of the replay arm was a budget violation (days 2, 3, 18, 19, 20, 22, 34, 35, 40), and the AWR arm's fourteen promotions were each within $\epsilon_q$ of their incumbent and within budget. The AWR arm's poor value is therefore not a recorded false promotion; it is what a local

non-inferiority rule permits, compounded by an estimator that over-states that arm by $+0.68$ and so could not have stopped a bad candidate had one come.

| arm | window | gates | PROMOTE/REVERT | unacceptable promoted | REVERT of acceptable | REVERT of unacceptable | DR quality bias / width / coverage |
|---|---|---|---|---|---|---|---|
| replay | 1–40 | 40 | 8 / 32 | 0 | 23 | 9 | $-0.005$ / 0.200 / 68% |
| replay | 6–40 | 35 | 8 / 27 | 0 | 20 | 7 | $-0.005$ / 0.190 / 63% |
| AWR | 1–40 | 40 | 14 / 26 | 0 | 26 | 0 | $+0.788$ / 0.653 / 5% |
| AWR | 6–40 | 35 | 12 / 23 | 0 | 23 | 0 | $+0.676$ / 0.627 / 6% |

**Table 22:** The committed run's gate records by window, scored against the held-out reference. "Acceptable" means within $\epsilon_q$ of the incumbent's reference quality and within $B$ + tol in reference cost.

**The served mixture's budget.** The served policy is the statewise iterate mixture (Appendix M.1), so its cost is measured rather than inherited. In the committed run the replay arm's realised mean served cost per task by stage is \$0.0813, \$0.0811, \$0.0771, \$0.0881 and \$0.0945 against $B + \text{tol} = \$0.095$, with 4 of 40 days over (one in stage g3, three in g4); its held-out expected cost peaks at \$0.0934 and is never over. The AWR arm serves at or below \$0.079 in every stage.

**New actions at introduction.** A capability that arrives with a zero-logit row receives roughly a uniform share of the softmax, not only the exploration floor: on the first day of stages g2, g3 and g4 the replay arm placed 0.23, 0.05 and 0.10 of its mass on the new actions, 4–10 times the $\epsilon$ floor, and the AWR arm 0.44, 0.55 and 0.68, 18–48 times the floor (`results/mas_continual/new_action_mass.md`). Old logs cannot certify an action they never contain; what the harness growth provides is exposure, and what the stage's served log then provides is evidence.

**Loss of plasticity in the AWR arm.** A saturation diagnostic on every policy the runs produced (`scripts/saturation_report.py`) finds the replay arm's logits inside the steerable range (at most 7% of action–input pairs beyond $|Wx|/L = 2.5$) and the AWR arm's far outside it, up to 61% of pairs with a gradient factor below $10^{-3}$, because it warm-starts daily from itself and its exponentiated weights drive the logits into the flat region of the clip. The AWR-against-replay comparison in the continual study therefore confounds the update rule with the AWR arm's loss of plasticity. Of the ten committed policies of the other experiments, one (the MAS reward-model policy) enters the regime mildly; the rest do not.

**A paired-difference gate with an overlap guard (v2).** The gate of Section 3.3 compares the candidate's lower bound with the incumbent's point estimate and bounds the cost net of a sample-mean prefix. A second version bootstraps candidate and incumbent jointly on the same resampled episodes and tests the lower bound of their quality difference, bounds the candidate's total cost with the prefix inside the resampling, and returns a third outcome, UNEVALUABLE, when the per-decision effective sample size falls below 20% of $n$ or more than 10% of cumulative ratios hit the clip. A held-out option splits each day's served log 70/30 by task so that the trainer and the gate never see the same episodes. All four combinations were run over seeds 0–4 on the default schedule (`pace/experiments/mas_continual/gate_lifecycle.py`; Table 23).

| gate | arm | regret 6–40 | PROMOTE/REVERT/UNEV. | unacceptable promotions | seeds with $\geq 1$ | days in unacceptable state | false REVERTS | first promotion day |
|---|---|---|---|---|---|---|---|---|
| v1 (body) | replay | $1.34 \pm 0.25$ | 8.4 / 31.6 / 0 | $0.2 \pm 0.2$ | 1/5 | 0.0 | $27.2 \pm 2.7$ | $5.4 \pm 1.9$ |
| v1 | AWR | $3.96 \pm 0.10$ | 15.4 / 24.6 / 0 | 0 | 0/5 | 0 | 24.4 | 2.6 |
| v1 + held-out gate log | replay | $1.74 \pm 0.23$ | 1.8 / 38.2 / 0 | $0.2 \pm 0.2$ | 1/5 | $1.0 \pm 1.0$ | 34.6 | 10.0 |
| v2 (paired difference, guard) | replay | $\mathbf{0.70 \pm 0.11}$ | 22.8 / 17.2 / 0 | $1.0 \pm 0.4$ | 3/5 | $1.6 \pm 0.7$ | $14.2 \pm 2.1$ | 3.6 |
| v2 | AWR | $3.89 \pm 0.09$ | 11.8 / 4.4 / 23.8 | 0 | 0/5 | 0 | 4.2 | 2.6 |
| v2 + held-out gate log | replay | $1.52 \pm 0.33$ | 7.8 / 29.6 / 2.6 | 0 | 0/5 | 0 | 26.0 | 9.2 |

**Table 23:** Lifecycle error rates over 5 seeds (mean $\pm$ SE; counts over 40 gates). References on the same traffic: `never_verify` regret $0.74 \pm 0.08$, `always_verify` $1.97 \pm 0.09$. Every unacceptable promotion in the grid (seven in all) is a marginal budget overshoot, \$0.0951–0.1012 against \$0.095; none regressed quality.

The paired-difference gate is the most powerful: it promotes three times as often, halves the replay arm's regret to $0.70 \pm 0.11$, below the fixed mode's $0.74 \pm 0.08$, and its difference interval is 0.085 wide against 0.19 for the candidate interval of v1. It is also the only configuration that overshoots the budget with any regularity, in 3 of 5 seeds, by at most 0.6 cents per task. Holding out a gate slice removes every violation in both versions and costs most of the power, since the gate then sees about 29 episodes a day. The overlap guard fires on the AWR arm (effective sample size 21–28% of $n$) and almost never on the replay arm, so the AWR arm becomes UNEVALUABLE on most days under v2, which is the appropriate verdict for a candidate that the log cannot support. On coverage, one fact bounds what the diagnostic can show: the held-out reference is itself an estimate with a standard error of about \$0.0032 in cost, larger than the gate's total-cost interval half-width of \$0.0026, so a perfectly calibrated 90% interval would cover the reference only about

56% of the time; the cost "under-coverage" of 50–69% is mostly reference noise, and the over-budget labels above are within one or two reference standard errors of the threshold. The quality side's 63–71% coverage is not explained this way and remains a limitation.

### M.7 Summary of claims and supporting evidence

**Table 24:** Each claim of the paper, the comparison that supports it, and the boundary of that support.

| claim | evidence | boundary |
|---|---|---|
| A learned first-step tier policy has higher priced value than every fixed tier | CRMArena-Pro B2B 300 and B2C 150 tasks, 5-fold CV over task ids, exact lookups, $J$ at $\lambda = 2$ (Table 1) | one decision per episode with fixed continuation; one seed per collection; fold SD descriptive; quality tie with frontier on B2C |
| The gate's decision depends on the logged draw and its interval narrows as $1/\sqrt{n}$ | 200 redraws of the realised log at 50, 150 and 300 tasks; promotion rate, width, coverage (Section 4.2) | candidate fixed before masking; coverage conditional on one outcome table; end-to-end protocol in Appendix M.4 |
| The mid tier matches or beats the frontier tier at about half the cost on three further suites | $\tau$-bench retail and airline, EvoHarnessBench stages 1, 2, 4, every task on every tier (Appendix G) | 49–60 tasks per domain; EvoHarnessBench at cached prices and FWT cells only; no controller trained there |
| Per-task headroom exists above every fixed tier | realised-outcome oracle on every suite | includes hindsight over stochastic outcomes; bound in Appendix M.3; one run per (task, tier) except the cheap-tier repeat |
| The continual orchestrator has the lowest regret of every learned arm and recovers after every stage | simulator calibrated to 130 real episodes; 40 days, 4 pre-registered stages; 1 seed all arms, 5 seeds for four arms (Appendix F) | stage-2+ effects assumed; frozen arm lacks new capabilities; reference policy not a proven optimum |
| Orchestrator-level BWT is bounded and mostly positive | same study, Eq. (11) per stage | empirical; not guaranteed by monotone growth (Appendix F, finding 5) |
| Verification helps only with an informative verifier and a cap the retries do not consume | four-variant ablation, 5 seeds (Appendix F.2) | simulator-conditional; the measured real verifier is uninformative |
| The gate is conservative: most reverts are false alarms | 40 gates of the committed run, audited against the held-out reference (Appendix M.6) | local rule; reference is a finite held-out evaluation; gates overlap in data |
| A GRPO-trained 1.7B controller failed because of the moving price | three stacks reproduce the failure; fixed-price controls learn the split (Appendix C) | one run each; one model size; simulator tasks |
| Decomposition, process verification and self-refinement do not pay on this log | 50-task MAS run, 41-task SSR run with the single agent as comparator (Appendices D, E) | 50 tasks; cheap verifier of the same model family; one round of refinement |

## N Experimental details

One table per experiment. Values are taken from the run metadata files, the command-line defaults of the scripts that produced each result, and `results/llm/backends/COMPARISON.md`; a setting that none of these records is marked "not recorded". Costs in the CRMArena-Pro rows are token counts times the list prices given in Table 26; simulator costs are in simulator units.

**Table 25:** Simulator pipeline (Appendix A; `scripts/run_v0.sh`, `scripts/run_sim_seeds.sh`).

| setting | value |
|---|---|
| harness | simulator $v_1$; drift event $v_2$ plus reprice(mid, 1.2); at most 4 steps; 12 actions |
| policy class | softmax-linear, Eq. (4); 48 features; logit clip $L = 3$; served exploration $\epsilon = 0.05$ |
| trainer | constrained GRPO on replay (`pace.train_offline --method cgrpo`; NumPy, no RL library) |
| group size / batch | $G = 8$ continuations per state; 32 logged states per iteration |
| iterations | 300 on $v_1$; 300 for the $v_2$ retrain, warm-started from the $v_1$ policy |
| learning rate | 1.5 (code default) |
| ratio clip; KL | none; none (on-policy group-relative gradient, Eq. (5)) |
| reward | realised 0/1 outcome minus $\lambda C$ |
| $\lambda$ learning | dual step $\eta = 0.1$, cost EMA $\rho = 0.9$, damping $k_p = 2.0$ (Eq. (3); inferred from the logged $\lambda$ and cost EMA of the first iterations, not stored as settings); served $\bar{\lambda}$ and policy averaged over 30 snapshots from the second half |
| budget | $B = 0.30$ |
| behaviour data | $v_1$: 3,000 episodes, uniform behaviour; $v_2$: 6,000 episodes served by the frozen $v_1$ policy with $\epsilon = 0.3$; propensities logged with exploration |
| gate | IPS, SNIPS, DR (in-sample bucketed direct model); cumulative ratio clip 50; 200 bootstrap resamples, 90% percentile intervals; $\epsilon_q = 0.03$, tol 0.02; $v_2$ bar from the $v_1$ promotion |
| ground truth | Monte Carlo over 20,000 fresh tasks, expected success probability |
| seeds | replicate $s \in \{0, \ldots, 4\}$: collect / train / collect / train seeds $10s{+}1, \ldots, 10s{+}4$; gate bootstrap and ground-truth seed $s$ ($s = 0$ is `run_v0.sh`) |

**Table 26:** CRMArena-Pro collections and the offline analyses on them (Appendices B.1, B.2, D, E, 4.1).

| setting | value |
|---|---|
| benchmark | CRMArena-Pro, b2b and b2c orgs, evaluator in `aided` mode (exact match, F1 for fuzzy categories, privacy judge) |
| tiers and list prices | cheap `claude-haiku-4-5`, mid `claude-sonnet-5-5`, frontier `claude-opus-5-5`; USD per million input / output tokens: 1.00 / 5.00, 2.00 / 10.00, 4.00 / 20.00; no prompt caching |
| counterfactual collection | b2b: 50 tasks (2–3 per category, all 22), extended on the same seeded, category-stratified sample to 150 and then 300; b2c: 150 tasks on the same protocol; every task on all three tiers; fixed continuation on the chosen tier; seed 0 |
| propensity | $1/3$ at step 0 (uniform over tiers), 1 after |
| episode limits | 12 agent turns (`ANSWER` forced at the last); 2,048 output tokens per agent turn, 1,024 for the forced answer; observations truncated to 20,000 characters; reasoning effort `low` for mid and frontier; no sampling parameters sent |
| offline learning on the log | AWR+IPS at $\lambda \in \{2, 5, 10\}$ per USD; constrained GRPO on the lookup table at $B = \$0.10$ with learned $\lambda$; 300 AWR epochs and 300 constrained-GRPO iterations (code default); 5-fold category-stratified CV over task ids, seed 0 |
| gate on the realised log | bandit DR with cross-fitted direct model; 200 bootstrap resamples; 200 redraws of the one-arm log; $\epsilon_q = 0.03$, tol \$0.005 |
| multi-agent run | same 50 tasks; planner cheap (600 output tokens, 1–3 sub-queries), data worker mid (one agent turn per sub-query), verifier cheap (200 output tokens, output shown truncated to 3,000 characters), answer mid; at most 8 role calls, 1 re-plan, 1 retry per sub-query; modes `always_verify` (50 episodes), `never_verify` (50), uniform exploration with logged propensities (30) |
| orchestration reward model | logistic regression and a 16-unit MLP; out-of-fold over tasks |
| self-refinement run | initial answers: the cheap-tier episodes of the counterfactual log; decompose on cheap (600 output tokens, at most 3 claims); $k = 2$ re-solve samples per claim, at most 3 turns each; refine (512 output tokens) on cheap and on mid; 42 tasks probed, 41 complete; controller: softmax-linear over 36 features, exact policy gradient on the logged tree, $B = \$0.10$ or $\lambda \in \{2, 5\}$, 5-fold CV over tasks |
| hardware | models served by the provider's API |

**Table 27:** The two further suites (Appendix G; `pace.experiments.taubench`, `pace.experiments.evoharness`).

| setting | value |
|---|---|
| $\tau$-bench | retail domain, 60 tasks, and airline domain, 49 of 50 sampled tasks (the ledger cap bound before the last); seeded shuffle of the task ids (seed 0); agent on the tier model, user simulator fixed to the cheap tier for every arm with its cost logged separately; reward the benchmark's own pass$^1$ from its environment checker; at most 30 agent turns, 2,048 output tokens per turn, 512 for the user turn; reasoning effort `low`; same tiers and list prices as Table 26, no prompt caching |
| $\tau$-bench offline analysis | as Table 26: AWR+IPS at $\lambda \in \{2, 5, 10\}$, constrained GRPO on the lookup table at $B$ = the uniform behaviour's cost ($0.277), 5-fold cross-validation over task ids; first-step features are the domain one-hot |
| EvoHarnessBench | hosted service, tools axis, stages 1, 2 and 4, 50 tasks each from a seeded round-robin over (domain, split, cohort) groups covering both the held-out and the adaptation split; each task under its own stage's tool allowlist on all three tiers; score the service's hidden-verifier pass rate, pass = all verifiers; at most 20 agent turns, 2,048 output tokens; reasoning effort `low` |
| EvoHarnessBench pricing | prompt caching on the system prompt (domain policy, action protocol, stage tool schemas) and the last message; cache writes priced at $1.25\times$ and reads at $0.1\times$ the input price; the cost column is therefore at cached prices and is reported separately from the other suites |
| hardware | models served by the provider's API |

**Table 28:** LLM controller, GRPO with LoRA (Appendix C; `results/llm/run_meta_phase1*.json`). The CRMArena-Pro run `crm_phase2` uses the `phase1c` recipe in lookup mode on fold 0.

| setting | `phase1` | `phase1b` | `phase1c` |
|---|---|---|---|
| model | Qwen3-1.7B, bf16, LoRA $r = 16$, $\alpha = 32$, dropout 0.05 on q, k, v, o, gate, up, down projections (all three phases) | | |
| library | TRL 1.15.0 (loss type `dapo`, group-scaled rewards), Transformers 5.19.0, PEFT 0.21.2, PyTorch 2.14.1 (all three phases) | | |
| prompts $\times$ group size | $8 \times 8$ | $8 \times 8$ | $4 \times 16$ |
| completions per step; micro-batch | 64; 16 | 64; 16 | 64; 16 |
| steps per generation | 4 | 4 | 4 |
| max completion length | 16 tokens | 16 tokens | 16 tokens |
| learning rate | $10^{-5}$ | $10^{-5}$ | $10^{-5}$ (SFT $2 \times 10^{-4}$) |
| clip (low / high) | 0.2 / 0.2 (library default) | 0.2 / 0.2 (library default) | 0.2 / 0.2 (library default) |
| KL coefficient; reference | 0.02; base model | 0.05; base model | 0.05; SFT model (adapter merged) |
| entropy coefficient | 0.0 (code default) | 0.01 | 0.01 |
| temperature | 1.0 (code default) | 1.0 | 1.2, raised to 1.5 at step 20 |
| GRPO steps | 300 | 300 | 200, after 150 SFT steps |
| SFT data | – | – | oracle labels on 2,000 tasks at shown prices $\{0.0, 0.1, \ldots, 2.0\}$; 1,000 held-out prompts |
| $\lambda$: dual step / EMA / $k_p$ | 0.1 / 0.9 / 2.0 | 0.02 / 0.95 / 0.5 | 0.02 / 0.95 / 0.5, $\lambda_0 = 0.5$, shown in prompt |
| budget | $B = 0.30$ | $B = 0.30$ | $B = 0.30$ |
| training tasks | 2,000 seeded simulator tasks (seed 0), legal-action order shuffled per task | | |
| evaluation set | 2,000 fresh simulator tasks, seed 777, greedy decoding | | |
| seeds; hardware | one run each, seed 0; one NVIDIA A100-SXM4-40GB | | |

**Table 29:** Platform and recipe controls on the phase-1b setup (Appendix C, platform controls; `results/llm/backends/COMPARISON.md`). Shared by all arms: Qwen3-1.7B with LoRA $r = 16$, $\alpha = 32$; temperature 1.0; KL coefficient 0.05 against the base model (k3 estimator in the loss for verl and NeMo-RL); entropy coefficient 0.01; learning rate $10^{-5}$; at most 16 completion tokens; price fixed at $\lambda = 0.44$ in the prompt and the reward; the phase-1c task pool (2,000 tasks, seed 0); one A100-40GB; one run each. Evaluation for every adapter: one evaluator (HF `generate`), greedy and sampled at $T = 1$, on the 2,000 seed-777 tasks with the $\lambda = 0.44$ prompt.

| setting | TRL, fixed price | TRL + dynamic sampling | verl, DAPO recipe | NeMo-RL, DAPO recipe |
|---|---|---|---|---|
| version | TRL 1.15 (phase-1b stack) | TRL 1.15, HF `generate` | verl 0.9.1, vLLM 0.24 | NeMo-RL NGC v0.7.0, vLLM 0.20 |
| prompts × group size | $4 \times 16$ (code default) | $4 \times 16$ | $4 \times 16$ | $4 \times 16$ |
| clip (low / high) | symmetric; 0.2 / 0.2 (code default) | 0.2 / 0.28 | 0.2 / 0.28 | 0.2 / 0.28 |
| dynamic sampling | no | yes (up to 8 generation rounds) | yes (`filter_groups`) | yes |
| loss aggregation | token mean over the accumulated batch, `dapo` (library default) | token mean over the accumulated batch, `dapo` (library default) | token mean | token level |
| steps completed | 150 | 186 (adapter at step 150 evaluated) | 117 (checkpoint at step 100 evaluated) | 25 (training curves only, not evaluated) |

**Table 30:** Continual orchestrator (Appendix F; `pace.experiments.mas_continual`). Simulator parameters are in Appendix R.

| setting | value |
|---|---|
| stream | 40 days × 96 seeded tasks per day, the same tasks for every arm; warm-up 5 days |
| stage schedule | g1 reprice (day 9), g2 agents (day 17), g3 tools (day 25), g4 skills (day 33); default and mild schedules (Table 10) |
| held-out set | 150 fixed tasks per stage, simulator expected quality, never seen by the gate |
| policy class | softmax-linear over 18 actions and 88 features; served $\epsilon = 0.1$; zero feature slots and logits for capabilities not yet present |
| trainer (continual) | constrained GRPO on replay from the last 5 days of logged states; 60 iterations per day, batch 16, group 6; warm start from itself; iterate averaging |
| trainer (AWR variant) | AWR+IPS, fixed $\lambda = 2$ per USD, 200 epochs |
| learning rate; ratio clip; KL | 1.5 constrained GRPO, 2.0 AWR (code default); none; none |
| $\lambda$ learning | learned against $B = \$0.090$ per task; dual step 20, cost EMA 0.9, damping $k_p = 40$, per USD of cost gap (code default) |
| gate | sequential DR, cumulative ratios clipped at 50; 200 bootstrap resamples; $\epsilon_q = 0.05$, tol \$0.005; log since the last harness event, at most 5 days; budget net of the policy-independent prefix |
| per-stage oracle | constrained GRPO on 200 fresh exploration episodes, 300 iterations, batch 24, group 8, no gate |
| SkillOrchestra-style router | handbook from warm-up exploration (days 1–4), $\lambda_c$ chosen on day 5 by episode-level SN-IPS; re-learned variant: 3 days at $\epsilon = 0.3$ per stage, then refit |
| prices | list prices of Table 26, scaled by the stage's repricing |
| metrics | recovery tolerance 0.02; stationary window 4 days; regret over days 6–40 |
| seeds | all arms seed 0 (default and mild); verifier ablation and the follow-ups seeds 0–4 |

**Table 31:** Simulator pipeline, per seed (`results/sim_seeds/RESULTS.md`). DR quality with its 90% CI; "cost hi" is the DR cost upper bound against $B + \text{tol} = 0.32$; truth is Monte Carlo over 20,000 tasks (for $v_2$, the adapted policy); recovery as served after the gate and for the adapted policy.

| seed | $\bar{\lambda}$ | gate $v_1$ DR quality | cost hi | decision | truth $v_1$ q / c | gate $v_2$ DR quality | cost hi | decision | truth adapted q / c | priced-BWT | recovery (served) | recovery (adapted) |
|---|---|---|---|---|---|---|---|---|---|---|---|---|
| 0 | 0.343 | 0.851 [0.815, 0.887] | 0.309 | PROMOTE | 0.880 / 0.303 | 0.873 [0.854, 0.889] | 0.311 | PROMOTE | 0.871 / 0.312 | −0.045 | +0.033 | +0.033 |
| 1 | 0.379 | 0.880 [0.848, 0.911] | 0.310 | PROMOTE | 0.877 / 0.310 | 0.871 [0.851, 0.892] | 0.292 | PROMOTE | 0.864 / 0.292 | −0.049 | +0.042 | +0.042 |
| 2 | 0.278 | 0.901 [0.878, 0.921] | 0.313 | PROMOTE | 0.877 / 0.309 | 0.879 [0.860, 0.895] | 0.304 | REVERT | 0.869 / 0.304 | −0.041 | −0.000 | +0.034 |
| 3 | 0.443 | 0.883 [0.845, 0.905] | 0.313 | PROMOTE | 0.878 / 0.306 | 0.855 [0.825, 0.881] | 0.290 | REVERT | 0.864 / 0.288 | −0.057 | +0.001 | +0.051 |
| 4 | 0.346 | 0.903 [0.870, 0.925] | 0.308 | PROMOTE | 0.877 / 0.302 | 0.867 [0.847, 0.887] | 0.296 | REVERT | 0.866 / 0.296 | −0.042 | +0.000 | +0.033 |

## O A worked example from the log

One task from the B2B counterfactual log, `b2b-1755` (category `lead_routing`: which sales user a lead in a given state should be routed to), as the platform recorded it. Every step carries the action as an (op, tier) pair, the propensity the behaviour policy assigned to it, the realised cost and latency, the 43-dimensional feature vector and the legal action set. The mid-tier arm:

```
t=0  CONTINUE@mid   propensity 0.333   $0.0141   1.4 s
t=1  CONTINUE@mid   propensity 1.0     $0.0146   1.6 s
t=2  CONTINUE@mid   propensity 1.0     $0.0186   2.9 s
t=3  CONTINUE@mid   propensity 1.0     $0.0172   1.2 s
quality 1.0   total cost $0.0645   latency 7.1 s   end: agent_respond
```

The agent's logged tool calls at those steps: a query for the territory whose description matches the state; a query for the users assigned to that territory; a count of accepted quotes per owner among those users; the answer, one user id, which matched the reference exactly. The propensity is $1/3$ at $t = 0$ because the collection's behaviour policy drew the tier uniformly, and 1 afterwards because the continuation is fixed on the chosen tier (Appendix B.1); the controller's decision is the first step only, so later steps carry no weight in any estimator.

| arm | steps | answer | quality | cost |
|---|---|---|---|---|
| cheap | 7 | a different user id | 0.0 | $0.049 |
| mid | 4 | correct | 1.0 | $0.065 |
| frontier | 4 | correct | 1.0 | $0.128 |

**Table 32:** The same task on the three arms. The per-task oracle is the mid tier: best quality, cheapest among the correct arms.

**What the controller does with it.** At $t = 0$ the feature vector has two non-zero entries, the task category and the harness version. The constrained policy of Section 4.1 (trained on all 300 tasks, $\bar{\lambda} = 1.09$ per dollar) maps it through a $3 \times 43$ weight matrix with logit clip 3 to

$$\pi(\text{cheap} \mid x) = 0.054, \qquad \pi(\text{mid} \mid x) = 0.009, \qquad \pi(\text{frontier} \mid x) = 0.937.$$

It has learned that `lead_routing` tasks, on average over the log, are worth the frontier tier under its budget; on this task that spends twice what the mid tier needed. The gap between the learned policy and the per-task oracle in Table 1 is this gap: the policy conditions on the category, the oracle on the outcome.

**What the gate does with it.** On a realised one-arm log that drew the mid tier for this task, the candidate's importance weight is $\pi(\text{mid} \mid x)/(1/3) \approx 0.03$, so the episode barely enters the IPS term; a task whose log drew the frontier tier carries weight 2.8. The doubly-robust estimator (Appendix Q) first predicts the task's quality and cost from its category with a direct model fitted on the other tasks, then adds the weighted residual. Over the 300 tasks this gives quality $0.607$ $[0.525, 0.668]$ and cost $\$0.095$ $[0.087, 0.113]$; the quality lower bound clears $q_{\text{prev}} - \epsilon = 0.484$, the cost upper bound does not clear $B + \text{tol} = \$0.105$, and the gate REVERTS. The policy's exact cost on the full log is $\$0.098$, inside the budget by less than the tolerance, which is the case the interval cannot certify at this sample size (Appendix B.2).

## P Prompts

The templates below are copied from the code. Text in braces, `{like_this}`, is filled at run time; everything else is literal. Where a prompt is assembled by a function rather than stored as a constant, the listing is the exact output of that function on a seeded example, with the variable fields named in the paragraph heading. The CRMArena-Pro agent's own system prompt (the benchmark's ReAct prompt with the rendered org schema and metadata, built by `system_prompt()` in `pace/harness/crmarena.py` from the vendored `crm_sandbox.agents.prompts`) is the benchmark's text under its licence and is not reproduced; the planner and the worker run inside that system prompt, and the verifier and the self-refinement roles do not.

**Controller, system message (`pace/llm/env_text.py`, `SYSTEM`).**

```
You are the routing controller of an agent harness. You pick which model tier runs the next operation. Reply with exactly one
     action tag and nothing else.
```

**Controller, simulator user message (`sim_prompt`; rendered for sim task 0, seed 0, $B = 0.30$; difficulty proxy, state, prices, the shuffled legal list and the example action vary per task).**

```
Task: answer one question. Observed difficulty: hard (a noisy estimate, right about 85% of the time).
State: step 0, evidence 0, verified no, cost so far 0.000.
Budget: average cost per task must stay at or below 0.30.
```

```
Price of one ANSWER call by tier: cheap 0.020, mid 0.100, frontier 0.400. RETRIEVE and VERIFY cost 0.5x (RETRIEVE adds a 0.005
      search fee), ESCALATE costs 1.5x.
Ops: ANSWER = answer now; RETRIEVE = fetch evidence; VERIFY = check with a judge; ESCALATE = answer now with extra compute.
After a non-final op the harness answers on the same tier.
Legal actions: mid ANSWER, cheap ESCALATE, frontier VERIFY, frontier RETRIEVE, mid ESCALATE, frontier ANSWER, cheap RETRIEVE,
     mid VERIFY, mid RETRIEVE, cheap ANSWER, frontier ESCALATE, cheap VERIFY.
Choose the action that maximizes expected answer quality within the budget.
Reply with exactly one tag, for example <action>frontier VERIFY</action>.
```

**Controller, price-conditioned variant (phase 1c and the backend runs): the lines that differ, at $\lambda = 0.44$ (shown rounded to 0.1).**

```
Price of cost: λ=0.4 (your reward is quality − λ·cost).
Choose the action that maximizes expected quality − λ·cost.
```

**Controller, CRMArena-Pro lookup mode (`lookup_prompt`; $B = \$0.10$, typical episode costs from the 50-task log, legal list unshuffled; an optional `Query:` line follows the first line when the task text is included).**

```
Task: a CRM agent task (org {org}, category {category}, scored by {reward_metric}).
Budget: average cost per task must stay at or below $0.100.
Typical cost of a full episode by tier: cheap $0.0680, mid $0.1196, frontier $0.1642.
CONTINUE = run the agent on that tier until it answers.
Legal actions: cheap CONTINUE, mid CONTINUE, frontier CONTINUE.
Choose the tier that maximizes expected answer quality within the budget.
Reply with exactly one tag of the form <action>TIER OP</action> naming one legal action.
```

**Planner, user message (`pace/experiments/mas/roles.py`; system message: the benchmark's ReAct prompt).**

```
Request: {query}

[MAS PLANNER] You are the planner of a CRM data team. Decompose the user's request into 1 to 3 sub-queries that a data worker
     will run one at a time against the Salesforce instance described above. Each sub-query has a `goal` (what it should
     establish) and a candidate `soql` (SOQL or SOSL text; leave it empty if the worker should write it). Order them so later
     sub-queries can use earlier results. Reply with JSON only:
{"subqueries": [{"goal": "...", "soql": "..."}], "rationale": "one sentence"}
```

**Planner, re-plan user message.**

```
Request: {query}

Evidence so far:
- {evidence item, at most 400 characters}
...

[MAS PLANNER] You are re-planning. The evidence gathered so far is listed below, with the verifier's findings. Produce the
     REMAINING sub-queries (1 to 3) needed to answer the request; do not repeat sub-queries whose results were verified. Same
     JSON format.
```

**Worker, steering text appended to the agent's running ReAct context (the `Candidate SOQL` line only when the plan gave one).**

```
[MAS WORKER] Sub-query {k} of {n}: {goal}
Candidate SOQL: {soql}
Run exactly one query now with <execute>...</execute> (adapt the candidate if needed).
```

**Worker, steering text on a retry after a verifier fail.**

```
[MAS WORKER] Sub-query {k} of {n}: {goal}
Candidate SOQL: {soql}
The verifier found a problem with your previous attempt: {reason}. Fix the query and run it again.
Run exactly one query now with <execute>...</execute> (adapt the candidate if needed).
```

**Verifier, single user message (no system message).**

```
Request: {query}
Sub-query goal: {goal}
Query run: {executed query}
Output: {Salesforce output, truncated to 3,000 characters}
```

```
[MAS VERIFIER] You verify one step of a CRM data worker. Given the user's request, the sub-query goal, the query that was run
     and the Salesforce output, decide whether this step's result is usable: well-formed, non-empty when the goal needs rows,
     and consistent with the goal (right object, right filter, right field). Reply with JSON only: {"pass": true|false, "
     reason": "one sentence"}
```

**Answer: the harness's `ANSWER@tier` op appends this to the last user turn of the agent's context (`pace/harness/crmarena.py`, `FORCE_ANSWER`).**

```
You must give your final answer now, without running more queries. Output only <respond> your final answer </respond>.
```

**Self-refinement, decompose: system message (`pace/experiments/ssr/refine.py`).**

```
You audit answers produced by a CRM assistant that queries a Salesforce instance with SOQL/SOSL. You do not run queries
     yourself. You decompose a proposed answer into verifiable sub-claims and estimate how likely each is to be true. Be
     calibrated: a confidence of 0.9 should be wrong about one time in ten.
```

**Self-refinement, decompose: user message (a Python format string: single braces are fields, doubled braces are literal braces).**

```
Task: {task_id}
Question asked of the assistant:
{query}

Queries the assistant ran before answering ({n_queries}):
{queries}

Proposed answer:
{answer}

Decompose the proposed answer into 1 to {max_claims} sub-claims that together imply the answer. For each sub-claim write one
     Socratic question that a worker can settle by running SOQL/SOSL on the same Salesforce instance, the value the sub-claim
     asserts (short, literal), and your confidence in [0, 1] that the sub-claim is true. Then give your confidence that the
     proposed answer as a whole is correct. If the proposed answer is a refusal or "None", make the single claim "the request
     should be refused / cannot be answered" with a question that checks whether the data is accessible.
Output JSON only, no prose:
{{"claims": [{{"claim": "...", "question": "...", "expected": "...", "confidence": 0.0}}], "answer_confidence": 0.0}}
```

**Self-refinement, re-solve: suffix appended to each Socratic question run as a worker mini-episode.**

```
Answer this sub-question only. Run the queries you need, then reply with <respond> the value </respond> and nothing else in
     the response.
```

**Self-refinement, refine: system message.**

```
You finalize answers produced by a CRM assistant that queries a Salesforce instance. You are given the question, the proposed
     answer, and the findings of independent workers who re-checked each sub-claim with their own queries. Keep the proposed
     answer when the findings support it; correct it when they contradict it; keep a refusal when the request concerns
     confidential data. Do not hedge, do not run queries, and output exactly one <respond> ... </respond> block with the final
      answer in the same format as the proposed answer.
```

**Self-refinement, refine: user message (format string).**

```
Task: {task_id}
Question:
{query}

Proposed answer:
{answer}

Sub-claims and worker findings:
{findings}

Give the final answer now. Output only <respond> final answer </respond>.
```

## Q Estimator derivations

**Unbiasedness of per-decision IPS.** For a logged episode drawn from $\mu$, and any step $t$, $\mathbb{E}_\mu[\rho_{0:t}\, r_t] = \sum_{a_{0:t}} \prod_{k\le t} \mu(a_k \mid s_k) \prod_{k\le t} \frac{\pi(a_k|s_k)}{\mu(a_k|s_k)}\, r_t = \mathbb{E}_\pi[r_t]$, whenever $\mu(a \mid s) > 0$ wherever $\pi(a \mid s) > 0$; the $\epsilon$-mixture of Eq. (4) guarantees the support condition for every served log. Summing over $t$ gives Eq. (7). The clip at $\rho_{\max}$ trades this unbiasedness for variance.

**The doubly-robust decomposition.** Write $\delta_t = r_t + \hat{V}(s_{t+1}) - \hat{Q}(s_t, a_t)$, the temporal-difference residual of the direct model under the candidate. Eq. (8) is $\hat{V}(s_0) + \sum_t \rho_{0:t}\delta_t$. If $\hat{Q} = Q^\pi$ then $\mathbb{E}_\mu[\rho_{0:t}\delta_t \mid s_t, a_t] = 0$ step by step and the estimate equals $\hat{V}(s_0) = V^\pi(s_0)$ regardless of the ratios; if instead the ratios are exact (no clip) then telescoping the $\hat{V}$ and $\hat{Q}$ terms recovers IPS regardless of $\hat{Q}$. Either model being right is enough [14]. With a clip, the error is $\sum_t(\rho_{0:t} - \tilde{\rho}_{0:t})\delta_t$, which is small when the direct model's residuals are small: the clip biases DR only through the direct model, as stated in Section 3.1.

**Bandit DR with cross-fitting.** In Eq. (9), the direct-model term $\sum_a \pi(a \mid x_i)\hat{Q}^{(-i)}(x_i, a)$ is evaluated on a model that did not see task $i$'s reward, so $\mathbb{E}[w_i(r_i - \hat{Q}^{(-i)}(x_i, a_i)) \mid x_i]$ is the reward model's error under $\pi$, not a term correlated with $r_i$ by construction. With an in-sample model, $\hat{Q}(x_i, a_i)$ contains $r_i$ itself; with buckets of a few samples the correction term shrinks toward zero and the estimate is pulled toward the direct model. Appendix B.2 reports both choices empirically (coverage 99%/92% cross-fitted against 96%/94% in-sample with a $-0.006$ quality bias).

**Why every arm logged makes the estimators exact.** With three arms per task each at propensity $1/3$, the weights over a task's three episodes are $3\pi(a \mid x)$ and sum to $3\sum_a \pi(a \mid x) = 3$; IPS over the 150 episodes is therefore $\frac{1}{50}\sum_i \sum_a \pi(a \mid x_i) r(x_i, a)$, the exact value, and SNIPS and DR coincide with it. The remaining interval is task-sampling uncertainty.

**The $\epsilon$-mixture score.** From $\pi_\epsilon = (1-\epsilon)\pi + \epsilon/|\mathcal{A}|$, $\nabla\pi_\epsilon = (1-\epsilon)\nabla\pi = (1-\epsilon)\pi\nabla\log\pi$, so $\nabla\log\pi_\epsilon = \frac{(1-\epsilon)\pi}{\pi_\epsilon}\nabla\log\pi$, Eq. (5). Using the bare score would weight exploration draws as if the policy had chosen them.

**Effective sample size.** For self-normalised weights, the variance of $\sum_i w_i r_i / \sum_i w_i$ behaves like that of a simple mean over $\text{ESS} = (\sum_i w_i)^2 / \sum_i w_i^2$ draws [17]; the report flags any estimate with $\text{ESS} < 0.1\, n$.

# R Continual simulator: calibrated and assumed parameters

**Table 33:** Every parameter of the continual simulator with its status (measured from the committed logs, with the count, or assumed).

| parameter | value | status | source / note |
|---|---|---|---|
| initial plan length $P(1, 2, 3)$ | 0.031 / 0.169 / 0.800 | measured | 130 planner calls (4 / 22 / 104) |
| re-plan length | 1 sub-query | measured | 15 re-plans, all emitted 1 |
| data-2 (mid) step kind rows/empty/error/invalid/respond | 0.761 / 0.151 / 0.057 / 0.027 / 0.003 | measured | 331 worker calls |
| data-1 (cheap) step kind | 0.36 / 0.09 / 0.09 / 0.00 / 0.45 | measured, thin | 11 worker calls |
| data-3 (frontier) step kind | 0.80 / 0.10 / 0.10 / 0.00 / 0.00 | measured, thin | 10 worker calls |
| retried step: same kind distribution as a first attempt | rows 0.68 vs 0.76 | measured-consistent | 53 retries vs 299 first attempts |
| tokens planner / worker / verifier / answer (in, out) | 5,029/279; 8,369/158; 711/62; 12,250/91 | measured | call-log means per role |
| worker input tokens by position | $6833 + 1748k$ | measured | positions 0/1/2: 6,833 / 8,571 / 10,330 |
| cheap / frontier tokens per role | planner 6,996/159; 6,902/311; worker 6,647/115; 9,598/196; answer 7,393/245; 15,227/332 | measured, thin | 5–15 calls each; list prices |
| verifier $P(\text{fail} \mid \text{empty step})$ | 0.958 | measured | 23 of 24 |
| verifier $P(\text{fail} \mid \text{rows step})$ | 0.581 | measured | 72 of 124; the same whether the step was good or bad |
| verifier structural fail on error / invalid steps | 1.0 at \$0 | measured | 12 of 12 |
| answer competence per (agent, category) | logit of MAS per-category accuracy + single-agent (category, tier) offset | measured, shrunk | 130 MAS + 150 single-agent episodes; pseudo-count 2.0 |
| max role calls / replans / retries | 8 / 1 / 1 | measured (configuration) | the real orchestrator's defaults |
| $P(\text{good} \mid \text{rows})$ per data agent | 0.60 / 0.75 / 0.85 | assumed | not identifiable from the logs; ordered like the tier accuracies |
| coverage $\rightarrow$ answer logit | $1.5 \times (\text{coverage} - 0.571)$ | assumed (slope); centre self-calibrated | centre = `never_verify`'s expected coverage |
| task-level logit noise | sd 0.4 | assumed | |
| worker "respond" on the prefix call | disallowed | assumed | first worker call is always data-2 and always queries |
| verify-2 (stage 2) | $P(\text{flag} \mid \text{correct})$ 0.30, same recall | assumed | |
| data-4 (stage 2) | rows 0.85 / good 0.80, cheap price | assumed | |
| answer-4 (stage 2) | mid-grade on 8 categories, cheap price | assumed | |
| schema_lookup (stage 3) | next worker step cannot error | assumed | priced as a verifier-sized cheap call |
| aggregate_calc (stage 3) | $+0.34$ coverage on aggregation categories | assumed | same price |
| soql_aggregate, date_window (stage 4) | $+0.15$ $P(\text{good} \mid \text{rows})$ on their categories | assumed | same price |
| decompose_fine (stage 4) | re-plan into 3–4 finer sub-queries | assumed | same price |
| planner v2 plan length $P(1..4)$ | (0.0, 0.1, 0.4, 0.5) | assumed | stage 4 |

The run configuration is in Table 30.

# S Per-day results of the continual study

**Table 34:** The continual (cgrpo) arm day by day, generated from `days.jsonl` and `gates.jsonl`. * marks an event day. Served quality is the simulator's expected quality; $\bar{\lambda}$ is the served policy's learned price; ESS is the per-decision effective sample size over logged decisions; "truth" is whether the candidate was acceptable on the simulator.

| day | stage | served $q$ | cost | $J$ | $\bar{\lambda}$ | gate | DR quality [90% CI] | DR cost hi | ESS | truth |
|---|---|---|---|---|---|---|---|---|---|---|
| 1 | g0-baseline | 0.405 | 0.0821 | 0.302 | 0.00 | REVERT | 0.311 [0.198, 0.489] | 0.0410 | 61/199 | ok |
| 2 | g0-baseline | 0.375 | 0.0776 | 0.277 | 0.00 | REVERT | 0.583 [0.353, 0.832] | 0.0790 | 130/394 | BAD |
| 3 | g0-baseline | 0.361 | 0.0834 | 0.256 | 0.00 | REVERT | 0.484 [0.358, 0.621] | 0.0763 | 199/606 | BAD |
| 4 | g0-baseline | 0.403 | 0.0797 | 0.303 | 0.00 | REVERT | 0.401 [0.321, 0.495] | 0.0483 | 298/805 | ok |
| 5 | g0-baseline | 0.408 | 0.0824 | 0.305 | 0.00 | REVERT | 0.389 [0.309, 0.474] | 0.0494 | 356/991 | ok |
| 6 | g0-baseline | 0.334 | 0.0813 | 0.233 | 0.00 | REVERT | 0.308 [0.213, 0.415] | 0.0572 | 302/999 | ok |
| 7 | g0-baseline | 0.402 | 0.0822 | 0.299 | 0.00 | REVERT | 0.292 [0.186, 0.411] | 0.0547 | 292/1013 | ok |
| 8 | g0-baseline | 0.343 | 0.0814 | 0.241 | 0.00 | REVERT | 0.312 [0.228, 0.415] | 0.0703 | 259/1002 | ok |
| 9* | g1-reprice | 0.439 | 0.0802 | 0.371 | 0.00 | REVERT | 0.406 [0.094, 0.784] | 0.1109 | 42/192 | ok |
| 10 | g1-reprice | 0.375 | 0.0718 | 0.315 | 0.00 | REVERT | 0.594 [0.377, 0.802] | 0.0863 | 81/386 | ok |
| 11 | g1-reprice | 0.379 | 0.0805 | 0.311 | 0.00 | REVERT | 0.483 [0.259, 0.690] | 0.0741 | 116/587 | ok |
| 12 | g1-reprice | 0.385 | 0.0755 | 0.321 | 0.00 | REVERT | 0.488 [0.342, 0.637] | 0.0763 | 158/788 | ok |
| 13 | g1-reprice | 0.381 | 0.0772 | 0.316 | 0.00 | PROMOTE | 0.552 [0.415, 0.694] | 0.0790 | 190/995 | ok |
| 14 | g1-reprice | 0.482 | 0.0898 | 0.407 | 0.81 | REVERT | 0.553 [0.433, 0.687] | 0.0759 | 254/1070 | ok |
| 15 | g1-reprice | 0.491 | 0.0874 | 0.417 | 0.81 | REVERT | 0.536 [0.436, 0.629] | 0.0761 | 347/1143 | ok |
| 16 | g1-reprice | 0.479 | 0.0864 | 0.406 | 0.81 | REVERT | 0.550 [0.459, 0.645] | 0.0757 | 473/1200 | ok |
| 17* | g2-agents | 0.472 | 0.0645 | 0.419 | 0.81 | REVERT | 0.528 [0.372, 0.658] | 0.0744 | 143/283 | ok |
| 18 | g2-agents | 0.420 | 0.0756 | 0.359 | 0.81 | REVERT | 0.484 [0.378, 0.597] | 0.0812 | 199/561 | BAD |
| 19 | g2-agents | 0.449 | 0.0700 | 0.392 | 0.81 | REVERT | 0.422 [0.344, 0.525] | 0.0763 | 236/829 | BAD |
| 20 | g2-agents | 0.458 | 0.0699 | 0.401 | 0.81 | REVERT | 0.443 [0.364, 0.518] | 0.0788 | 307/1101 | BAD |
| 21 | g2-agents | 0.470 | 0.0768 | 0.408 | 0.81 | PROMOTE | 0.442 [0.370, 0.518] | 0.0747 | 408/1395 | ok |
| 22 | g2-agents | 0.531 | 0.0870 | 0.461 | 0.75 | REVERT | 0.445 [0.380, 0.504] | 0.0805 | 509/1461 | BAD |
| 23 | g2-agents | 0.531 | 0.0857 | 0.461 | 0.75 | PROMOTE | 0.501 [0.443, 0.556] | 0.0751 | 570/1507 | ok |
| 24 | g2-agents | 0.552 | 0.0869 | 0.482 | 1.03 | REVERT | 0.537 [0.482, 0.579] | 0.0735 | 900/1593 | ok |
| 25* | g3-tools | 0.519 | 0.0883 | 0.461 | 1.03 | REVERT | 0.561 [0.483, 0.641] | 0.0830 | 339/345 | ok |
| 26 | g3-tools | 0.524 | 0.0875 | 0.466 | 1.03 | REVERT | 0.558 [0.503, 0.638] | 0.0775 | 665/680 | ok |
| 27 | g3-tools | 0.559 | 0.0914 | 0.499 | 1.03 | PROMOTE | 0.568 [0.515, 0.615] | 0.0753 | 997/1022 | ok |
| 28 | g3-tools | 0.511 | 0.0788 | 0.459 | 0.77 | PROMOTE | 0.541 [0.499, 0.590] | 0.0778 | 1275/1371 | ok |
| 29 | g3-tools | 0.548 | 0.0971 | 0.484 | 0.66 | REVERT | 0.560 [0.519, 0.612] | 0.0814 | 1410/1736 | ok |
| 30 | g3-tools | 0.535 | 0.0910 | 0.475 | 0.66 | PROMOTE | 0.572 [0.516, 0.626] | 0.0802 | 1363/1747 | ok |
| 31 | g3-tools | 0.543 | 0.0832 | 0.488 | 0.53 | PROMOTE | 0.576 [0.519, 0.659] | 0.0801 | 1368/1774 | ok |
| 32 | g3-tools | 0.561 | 0.0872 | 0.503 | 0.41 | REVERT | 0.581 [0.527, 0.651] | 0.0765 | 1459/1809 | ok |
| 33* | g4-skills | 0.518 | 0.0941 | 0.449 | 0.41 | REVERT | 0.472 [0.394, 0.583] | 0.0830 | 412/432 | ok |
| 34 | g4-skills | 0.470 | 0.0874 | 0.407 | 0.41 | REVERT | 0.452 [0.390, 0.518] | 0.0811 | 810/848 | BAD |
| 35 | g4-skills | 0.585 | 0.1041 | 0.509 | 0.41 | REVERT | 0.478 [0.418, 0.537] | 0.0818 | 1165/1277 | BAD |
| 36 | g4-skills | 0.542 | 0.0986 | 0.471 | 0.41 | REVERT | 0.512 [0.465, 0.574] | 0.0829 | 1540/1720 | ok |
| 37 | g4-skills | 0.539 | 0.1012 | 0.465 | 0.41 | REVERT | 0.522 [0.480, 0.573] | 0.0825 | 1959/2164 | ok |
| 38 | g4-skills | 0.506 | 0.0900 | 0.441 | 0.41 | REVERT | 0.570 [0.512, 0.630] | 0.0842 | 1824/2145 | ok |
| 39 | g4-skills | 0.505 | 0.0926 | 0.437 | 0.41 | PROMOTE | 0.600 [0.536, 0.666] | 0.0771 | 1765/2142 | ok |
| 40 | g4-skills | 0.555 | 0.0881 | 0.491 | 0.88 | REVERT | 0.603 [0.547, 0.661] | 0.0816 | 1789/2103 | BAD |

**Table 35:** Stationary held-out $J$ (mean over the last four days of each stage), default schedule.

| arm | g0 | g1 | g2 | g3 | g4 |
|---|---|---|---|---|---|
| oracle | 0.345 | 0.460 | 0.445 | 0.458 | 0.466 |
| continual (cgrpo on replay, gated) | 0.283 | 0.427 | 0.429 | 0.453 | 0.448 |
| continual (AWR+IPS, gated) | 0.294 | 0.363 | 0.342 | 0.330 | 0.321 |
| frozen (trained days 1–5) | – | 0.411 | 0.370 | 0.374 | 0.350 |
| static router | – | 0.385 | 0.352 | 0.349 | 0.316 |
| router re-learned per stage | – | 0.389 | 0.369 | 0.346 | 0.363 |
| `always_verify` | 0.329 | 0.426 | 0.389 | 0.397 | 0.376 |
| `never_verify` | 0.368 | 0.466 | 0.423 | 0.434 | 0.428 |

**Table 36:** Candidates the gate stopped that were in fact over budget (continual cgrpo arm; the AWR arm had none).

| day | stage | candidate true quality / cost | incumbent true quality / cost | over budget | gate said |
|---|---|---|---|---|---|
| 2 | g0 | 0.482 / $0.1009 | 0.382 / $0.0794 | yes | REVERT |
| 3 | g0 | 0.470 / $0.0981 | 0.382 / $0.0794 | yes | REVERT |
| 18 | g2 | 0.515 / $0.0974 | 0.467 / $0.0721 | yes | REVERT |
| 19 | g2 | 0.508 / $0.0953 | 0.467 / $0.0721 | yes | REVERT |
| 20 | g2 | 0.528 / $0.0996 | 0.467 / $0.0721 | yes | REVERT |
| 22 | g2 | 0.527 / $0.0962 | 0.512 / $0.0926 | yes | REVERT |
| 34 | g4 | 0.521 / $0.0966 | 0.513 / $0.0914 | yes | REVERT |
| 35 | g4 | 0.522 / $0.0951 | 0.513 / $0.0914 | yes | REVERT |
| 40 | g4 | 0.523 / $0.0954 | 0.517 / $0.0904 | yes | REVERT |

**Table 37:** SkillOrchestra-style handbooks: when fitted, on how many episodes, the chosen $\lambda_c$ and the SN-IPS estimate that chose it (its ESS of 96 shows why the choice is noise).

| handbook | fitted on day | episodes (learn / tune) | $\lambda_c$ | SN-IPS quality / cost at $\lambda_c$ (ESS) |
|---|---|---|---|---|
| static | 5 | 384 / 96 | 0.0 | 1.000 / $0.0787 (4/96) |
| relearn g1 | 11 | 192 / 96 | 0.0 | 0.597 / $0.0911 (7/96) |
| relearn g2 | 19 | 192 / 96 | 20.0 | 1.000 / $0.0278 (1/96) |
| relearn g3 | 27 | 192 / 96 | 0.0 | 0.705 / $0.0407 (3/96) |
| relearn g4 | 35 | 192 / 96 | 0.0 | 0.750 / $0.0690 (8/96) |

# T Reproduction

All offline pipelines are seeded end to end and need only `numpy`; the CRMArena-Pro offline script is byte-for-byte deterministic on the committed log. From the repository root:

```
pip install -r requirements.txt
bash scripts/run_v0.sh              # sim: collect -> train -> gate -> drift -> retrain -> gate
bash scripts/run_sim_seeds.sh 0 1 2 3 4   # the same pipeline over five replicate seeds
head -150 traces/crmarena_b2b_counterfactual.jsonl > /tmp/b2b_50.jsonl   # the first 50 tasks
python scripts/crmarena_offline.py --log /tmp/b2b_50.jsonl --out results/crmarena   # no API calls
python scripts/crmarena_offline.py --log traces/crmarena_b2b_counterfactual.jsonl \
    --spend traces/crmarena_b2b_counterfactual.spend.jsonl --out results/crmarena_300
python scripts/crmarena_offline.py --log traces/crmarena_b2c_counterfactual.jsonl \
    --spend traces/b2c/spend.jsonl --out results/crmarena_b2c
python -m pace.experiments.taubench.run analyze \
    --log traces/taubench_retail_counterfactual.jsonl --out results/taubench/retail_RESULTS.md
python -m pace.experiments.taubench.run analyze \
    --log traces/taubench_airline_counterfactual.jsonl --out results/taubench/airline_RESULTS.md
python -m pace.experiments.evoharness.run analyze --traces-dir traces/evoharness \
    --out results/evoharness/tools_axis_150.json
python -m pace.experiments.mas.run analyze --log results/mas/mas_b2b.jsonl \
    --single-agent-log traces/crmarena_b2b_counterfactual.jsonl --out results/mas/RESULTS.md
python -m pace.experiments.ssr.run analyze --log traces/ssr/ssr_b2b_tree.jsonl \
    --out results/ssr/RESULTS.md --csv results/ssr/frontier.csv
python -m pace.experiments.mas_continual.run_continual --out results/mas_continual
python -m pace.experiments.mas_continual.run_continual --schedule mild \
    --out results/mas_continual/mild
python -m pace.experiments.mas_continual.analyze --run results/mas_continual \
    --mild results/mas_continual/mild --out results/mas_continual/RESULTS.md
python -m pytest tests -q
```

The GPU runs (`pace/llm/`) each ran once in one A100-40GB container; their training logs, run metadata, SFT reports and evaluation tables are committed under `results/llm/`. The real-harness collections (`pace.collect --harness crmarena --mode counterfactual`, the MAS and SSR `run` commands) require the benchmark checkout, its sandbox credentials and a model API key, and run under the budget check of Section 3.5. The figures in this paper are regenerated by `python paper/make_figures.py` from the committed result files, and the paper by `make` in `paper/`.

## U Data licences

CRMArena-Pro is released under CC BY-NC 4.0 for research use. It is fetched at setup and never copied into the repository. The committed B2B and B2C traces (`traces/crmarena_*_counterfactual.jsonl`) are derived research artefacts (per-episode features, actions, costs, the agent's answers and queries, and the benchmark's gold answers for every task) under the same non-commercial terms; the matching call log contains token counts and prices and no benchmark data. The multi-agent and self-refinement logs are derived artefacts of the same kind. The $\tau$-bench tasks are MIT-licensed and fetched at setup; the EvoHarnessBench logs contain our agent's actions and the service's scores and none of the service's data.