



SHENZHEN MAGIC CHIP TECHNOLOGY CO.,LTD



Model:MCIPCD3

CPU	Optional Intel 2955U, 4th/6th/7th/8th Gen Core i3/i5/i7 CPU
Video	1 x HDMI
RAM	1 x DDR3L SO-DIMM slot, maximum support 16GB
Materia	Aluminum
USB	4 x USB
Power	12V DC Input
NIC	6 x GbE RJ45 Intel i210/i211
COM	1 x DB-9 RS232, 1 x RJ45 RS-232 (Cisco standard)
Storage	1 x MSATA, 1 x HDD/SSD
Expansion	1 x Mini-PCIe full card (with SIM slot, supports 3G/4G, WiFi/Bluetooth) Supports Watchdog Timer (1~255 sec)
Size	209(L) x 150(W) x 57(H) mm
Weight	1.35 Kg
System	Windows 7/8/10, Linux
Working Environment	Working Temp: -20°C to 70°C Storage Temp: -30°C to 70°C Storage Humidity: 95% @40°C, non-condensing

Front I/O connector

1 x Power Button, 1 x Reset Button
4 x USB
1 x HDMI
1 x DB-9 RS232 (COM2)
1 x RJ45 RS-232 Cisco standard (COM1)

Rear I/O connector

6 x GbE RJ45 LAN
1 x 12V DC Power Input
2 x Antenna connectors (for WIFI/3G/4G)
1 x Power LED, 1 x HDD LED



mail:
Contact@szmagicchip.com



web:
www.szmagicchip.com



office:
5E, JinDa City, Central Road,
Xinqiao Street, Baoan District,
Shenzhen City, China 518125