



tmux

tmux

- Many-in-one
- Various layouts
- Session separate from emulator
- Scriptable

wat?

```

18         io_loop.add_handler(sock.fileno(), callback, io
17         io_loop.start()
16
15     .. testoutput::
14         :hide:
13
12     By default, a newly-constructed `IOLoop` becomes the th
11     `IOLoop`, unless there already is a current `IOLoop`. T
10     can be controlled with the ``make_current`` argument to
9     constructor: if ``make_current=True``, the new `IOLoop`
8     try to become current and it raises an error if there i
7     current instance. If ``make_current=False``, the new `I
6     not try to become current.
5
4     .. versionchanged:: 4.2
3         Added the ``make_current`` keyword argument to the `
2         constructor.
1         """
127 # Constants from the epoll module
1     _EPOLLIN = 0x001
2     _EPOLLPRI = 0x002
3     _EPOLLOUT = 0x004
4     _EPOLLERR = 0x008
5     _EPOLLHUP = 0x010
6     _EPOLLRDHUP = 0x2000
7     _EPOLLONESHOT = (1 << 30)
8     _EPOLLET = (1 << 31)
9
10     # Our events map exactly to the epoll events
11     NONE = 0
12     READ = _EPOLLIN
13     WRITE = _EPOLLOUT
14     ERROR = _EPOLLERR | _EPOLLHUP
15
16     # Global lock for creating global IOLoop instance
17     _instance_lock = threading.Lock()
18
19     _current = threading.local()
20
21     @staticmethod
22     def instance():
23         """Returns a global `IOLoop` instance.

```

```

ioloop.py 127,23 10%

```

```

draje@sol:/h/draje/Code/GitHub/tornadoweb/tornado/tornado/iostream.py
.git concurrent.pyc 19.8 K #!/usr/bin/env python
demos curl_httpclien~ 21.7 K #
docs escape.py 14.1 K # Copyright 2009 Facebook
maint gen.py 43.1 K #
torna~ http1connectio~ 30.6 K # Licensed under the Apache License,
.cove~ httpclient.py 26.5 K # not use this file except in compli
.giti~ httpserver.py 11.6 K # a copy of the License at
.trav~ httputil.py 28.5 K #
appve~ ioloop.py 40.3 K # http://www.apache.org/licenses
LICEN~ iostream.py 63.7 K #
MANIF~ locale.py 19.8 K # Unless required by applicable law
READM~ locks.py 14.9 K # distributed under the License is d
runte~ log.py 10.8 K # WARRANTIES OR CONDITIONS OF ANY KI
setup~ netutil.py 20 K # License for the specific language
tox.i~ options.py 20.8 K # under the License.
process.py 12 K
queues.py 9.78 K """An I/O event loop for non-blockin
simple_httpcli~ 24.1 K
speedups.c 1.05 K Typical applications will use a sing
speedups.pyi 59 B `IOLoop.instance` singleton. The `I
stack_context~ 12.9 K be called at the end of the ``main()
tcpclient.py 6.64 K use more than one `IOLoop`, such as
tcpserver.py 11.3 K case.
template.py 34.5 K
-rw-r--r-- 1 draje users 40.3K 804K sum, 208G free 17/37 62%

```


```
draje.sol
```

panes

windows

sessions

Status Bar



The *Prefix*

- Entered before tmux shortcuts
 - Creating new window
 - Switching panes
 - Etc.
- Typically *Control+b*
- Often remapped to *Control+a*

begin



nvllsvm