


[Home](#) [DBMS](#) [SQL](#) [PL/SQL](#) [SQLite](#) [MongoDB](#) [Cassandra](#) [MySQL](#) [Oracle](#) [CouchDB](#) [Neo4j](#) [DB2](#) [C](#) [Java](#) [Projects](#)

[↑ SCROLL TO TOP](#)

Relational Algebra

Relational algebra is a procedural query language. It gives a step by step process to obtain the result of the query. It uses operators to perform queries.

Types of Relational operation



1. Select Operation:

- The select operation selects tuples that satisfy a given predicate.
- It is denoted by sigma (σ).

Notation: $\sigma p(r)$

Where:

σ is used for selection prediction

r is used for relation

p is used as a propositional logic formula which may use connectors like: AND OR and NOT. These relational can use as relational operators like $=$, \neq , \geq , $<$, $>$, \leq .

For example: LOAN Relation

Programming with C



```
struct TCS
{
    int x: 1;
    int y: 2;
    int z: 4;
    int w: 8;
}A;
```



A	4	B	16
C	8	D	15

```
int main()
{
    printf("%d", sizeof(A));
    return 0;
}
```

What will be the output of above code in bytes? , if size of integer variable is consider to be as 4 bytes

BRANCH_NAME	LOAN_NO	AMOUNT
Downtown	L-17	1000
Redwood	L-23	2000
Perryride	L-15	1500
Downtown	L-14	1500

Mianus	L-13	500
Roundhill	L-11	900
Perryride	L-16	1300

Input:

σ BRANCH_NAME="perryride" (LOAN)

Output:

BRANCH_NAME	LOAN_NO	AMOUNT
Perryride	L-15	1500
Perryride	L-16	1300

2. Project Operation:

- This operation shows the list of those attributes that we wish to appear in the result. Rest of the attributes are eliminated from the table.
- It is denoted by π .

Notation: π A1, A2, An (r)

Where

A1, A2, A3 is used as an attribute name of relation **r**.

Example: CUSTOMER RELATION

NAME	STREET	CITY
Jones	Main	Harrison
Smith	North	Rye
Hays	Main	Harrison
Curry	North	Rye
Johnson	Alma	Brooklyn
Brooks	Senator	Brooklyn

Input:

□ NAME, CITY (CUSTOMER)

Output:

NAME	CITY
Jones	Harrison
Smith	Rye

Hays	Harrison
Curry	Rye
Johnson	Brooklyn
Brooks	Brooklyn

3. Union Operation:

- Suppose there are two tuples R and S. The union operation contains all the tuples that are either in R or S or both in R & S.
- It eliminates the duplicate tuples. It is denoted by \cup .

Notation: $R \cup S$

A union operation must hold the following condition:

- R and S must have the attribute of the same number.
- Duplicate tuples are eliminated automatically.

Example:

DEPOSITOR RELATION

CUSTOMER_NAME	ACCOUNT_NO
Johnson	A-101
Smith	A-121
Mayes	A-321
Turner	A-176
Johnson	A-273
Jones	A-472
Lindsay	A-284

BORROW RELATION

CUSTOMER_NAME	LOAN_NO
Jones	L-17

Smith	L-23
Hayes	L-15
Jackson	L-14
Curry	L-93
Smith	L-11
Williams	L-17

Input: $\pi \text{ CUSTOMER_NAME (BORROW)} \cup \pi \text{ CUSTOMER_NAME (DEPOSITOR)}$ **Output:**

CUSTOMER_NAME
Johnson
Smith
Hayes
Turner
Jones

Lindsay
Jackson
Curry
Williams
Mayes

4. Set Intersection:

- Suppose there are two tuples R and S. The set intersection operation contains all tuples that are in both R & S.
- It is denoted by intersection \cap .

Notation: $R \cap S$

Example: Using the above DEPOSITOR table and BORROW table

Input: $\pi \text{ CUSTOMER_NAME (BORROW)} \cap \pi \text{ CUSTOMER_NAME (DEPOSITOR)}$ **Output:**

CUSTOMER_NAME
Smith
Jones

5. Set Difference:

- Suppose there are two tuples R and S. The set intersection operation contains all tuples that are in R but not in S.

- It is denoted by intersection minus (-).

Notation: $R - S$

Example: Using the above DEPOSITOR table and BORROW table

Input:

π CUSTOMER_NAME (BORROW) - π CUSTOMER_NAME (DEPOSITOR)

Output:

CUSTOMER_NAME
Jackson
Hayes
Willians
Curry

6. Cartesian product

- The Cartesian product is used to combine each row in one table with each row in the other table. It is also known as a cross product.
- It is denoted by X.

Notation: E X D

Example:

EMPLOYEE

EMP_ID	EMP_NAME	EMP_DEPT
1	Smith	A
2	Harry	C
3	John	B

DEPARTMENT

DEPT_NO	DEPT_NAME
A	Marketing
B	Sales

C	Legal
---	-------

Input:

EMPLOYEE X DEPARTMENT

Output:

EMP_ID	EMP_NAME	EMP_DEPT	DEPT_NO	DEPT_NAME
1	Smith	A	A	Marketing
1	Smith	A	B	Sales
1	Smith	A	C	Legal
2	Harry	C	A	Marketing
2	Harry	C	B	Sales
2	Harry	C	C	Legal
3	John	B	A	Marketing
3	John	B	B	Sales
3	John	B	C	Legal

7. Rename Operation:

The rename operation is used to rename the output relation. It is denoted by **ρ** (ρ).

Example: We can use the rename operator to rename STUDENT relation to STUDENT1.

$$\rho(\text{STUDENT1}, \text{STUDENT})$$

Note: Apart from these common operations Relational algebra can be used in Join operations.

[< Prev](#)[Next >](#)



For Videos Join Our Youtube Channel: [Join Now](#)

Feedback

- Send your Feedback to feedback@javatpoint.com


Help Others, Please Share




Learn Latest Tutorials




Reinforcement
Learning



R Programming



RxJS



React Native




Python Design
Patterns



tutorial



tutorial



Keras

Python Pillow

Python Turtle

Preparation



Aptitude

Aptitude

Logical
Reasoning

Reasoning



Verbal Ability

Verbal Ability

Interview
Questions

Interview Questions

Company
Interview
Questions

Company Questions


Trending Technologies

Artificial
Intelligence
TutorialArtificial
IntelligenceAWS Tutorial
AWSSelenium
tutorial


Selenium

Cloud
Computing
tutorialHadoop tutorial
HadoopReactJS
Tutorial


ReactJS




B.Tech / MCA




 Operating System tutorial Operating System	 Computer Network tutorial Computer Network	 Compiler Design tutorial Compiler Design
 Computer Organization and Architecture Computer Organization	 Discrete Mathematics Tutorial Discrete Mathematics	 Ethical Hacking Tutorial Ethical Hacking
 Computer Graphics Tutorial Computer Graphics	 Software Engineering Tutorial Software Engineering	 html tutorial Web Technology
 Cyber Security tutorial Cyber Security	 Automata Tutorial Automata	 C Language tutorial C Programming
 C++ tutorial C++	 Java tutorial Java	 .Net Framework tutorial .Net



Python tutorial
Python



List of
Programs
Programs



Control
Systems tutorial
Control System



Data Mining
Tutorial
Data Mining



Data
Warehouse
Tutorial
Data Warehouse