

E-TIMEOFFICE API DOCUMENTATION

❖ Overview

The e-time-office API provides attendance and punch data integration APIs for employee attendance systems.

These APIs allow you to:

- Download raw punch data
 - Download raw punch data with Machine ID (MCID)
 - Download IN/OUT attendance data
 - Download only latest punch records using Last record tracking
-

❖ Base URL

<https://api.etimeoffice.com/api/>

❖ Authentication

All APIs use **Basic Authentication**.

Authorization Header

Authorization: Basic <BASE64_ENCODED_VALUE>

Authentication Format

The Base64 encoded string must follow this format:

Corporateid:Username:Password:True

Example

support:support:support@1:true

Example Base64 Encoded Value

c3VwcG9ydDpzdBWb3J0OnN1cHBvcnQ6dHJ1ZTo=

❖ Common Headers

Authorization: Basic c3VwcG9ydDpzdBWb3J0OnN1cHBvcnQ6dHJ1ZTo=

Content-Type: application/json

❖ Date Format

All date parameters must use the following format:

dd/MM/yyyy_HH:mm

Example

01/01/2026_01:00

❖ API 1 — Download Raw Punch Data

Downloads raw employee punch data without IN/OUT flag.

Endpoint

GET /DownloadPunchData

Full URL

<https://api.etimeoffice.com/api/DownloadPunchData>

Query Parameters

Parameter	Type	Required	Description
Empcode	String	Yes	Employee code. Use ALL for all employees.
From Date	String	Yes	Start date and time.
To Date	String	Yes	End date and time.

Example Request

GET

https://api.etimeoffice.com/api/DownloadPunchData?Empcode=0001&FromDate=01/01/2026_01:00&ToDate=01/12/2026_00:00

Sample Response

```
[
  {
    "Empcode": "0001",
    "PunchDate": "01/01/2026 09:00:00"
  }
]
```

❖ API 2 — Download Punch Data with MCID

Downloads raw punch data including Machine ID (MCID).

Endpoint

GET /DownloadPunchDataMCID

Full URL

<https://api.etimeoffice.com/api/DownloadPunchDataMCID>

Example Request

GET

https://api.etimeoffice.com/api/DownloadPunchDataMCID?Empcode=0001&FromDate=01/01/2026_01:00&ToDate=01/12/2026_00:00

Sample Response

```
{
  "Error": false,
  "Msg": "Success",
  "IsAdmin": true,
  "PunchData": [
    {
      "Name": "JIGNESH PADHIYAR",
      "Empcode": "0001",
      "PunchDate": "01/01/2026 15:58:00",
      "M_Flag": null,
      "mcid": "3"
    }
  ]
}
```

❖ API 3 — Download IN/OUT Punch Data

Downloads attendance data with IN Time, OUT Time, Work Time, and Status.

Endpoint

GET /DownloadInOutPunchData

Full URL

<https://api.etimeoffice.com/api/DownloadInOutPunchData>

Example Request

GET

<https://api.etimeoffice.com/api/DownloadInOutPunchData?Empcode=ALL&FromDate=01/01/2026&ToDate=01/12/2026>

Sample Response

```
{
  "InOutPunchData": [
    {
      "Empcode": "0001",
      "INTime": "12:06",
      "OUTTime": "--:--",
      "WorkTime": "00:00",
      "OverTime": "00:00",
      "Status": "P/2",
      "DateString": "01/01/2026",
      "Remark": "MIS-LT",
      "Erl_Out": "00:00",
      "Late_In": "02:36",
      "Name": "JIGNESH PADHIYAR"
    }
  ],
  "Error": false,
  "Msg": "Success",
}
```

```
"IsAdmin": true
}
```

❖ API 4 — Download Latest Punch Data using LastRecord

Downloads only new/latest punch records after the provided LastRecord value.

This API is useful for incremental synchronization.

Endpoint

GET /DownloadLastPunchData

Full URL

<https://api.etimeoffice.com/api/DownloadLastPunchData>

Query Parameters

Parameter	Type	Required	Description
-----------	------	----------	-------------

Empcode	String	Yes	Employee code or ALL.
---------	--------	-----	-----------------------

LastRecord	String	Yes	Last synced record value in format MMyyyy\$ID.
------------	--------	-----	--

Important Notes

- During the first API call, pass the initial LastRecord value.
 - Save the returned MaxRecord value in your database.
 - Pass the saved MaxRecord value in the next API call.
 - This prevents duplicate data download.
-

Example Request

GET

[https://api.etimeoffice.com/api/DownloadLastPunchData?Empcode=ALL&LastRecord=042026\\$454](https://api.etimeoffice.com/api/DownloadLastPunchData?Empcode=ALL&LastRecord=042026$454)

Sample Response

```
{
```

```
"Error": false,
"Msg": "Success",
"IsAdmin": true,
"PunchData": [
  {
    "Name": "RAVI PARMAR",
    "Empcode": "0005",
    "PunchDate": "30/04/2026 09:46:00",
    "M_Flag": null,
    "ID": 455,
    "Table": "TextFileData042026",
    "EmpcardNo": "00000005"
  },
  {
    "Name": "TANAY MISTRY",
    "Empcode": "0010",
    "PunchDate": "30/04/2026 09:49:00",
    "M_Flag": null,
    "ID": 456,
    "Table": "TextFileData042026",
    "EmpcardNo": "00000010"
  }
],
"MaxRecord": "042026$456",
"TableName": "TextFileData092026"
}
```

HTTP Status Codes

Status Code Description

200	Request successful
400	Invalid request parameters

Status Code Description

401	Unauthorized
404	Resource not found
500	Internal server error

Best Practices

- Always store the MaxRecord value when using LastRecord API.
 - Use proper Base64 encoding for authentication.
 - Validate date formats before sending requests.
 - Use HTTPS endpoints only.
 - Large date ranges may increase response time.
-

Support

If you have queries regarding our API - respond/output please contact our technical support team @ [+91-99245 02024](tel:+919924502024).