



API Reference

AWS Global Networks for Transit Gateways



API Version 2019-07-05

Copyright © 2025 Amazon Web Services, Inc. and/or its affiliates. All rights reserved.

AWS Global Networks for Transit Gateways: API Reference

Copyright © 2025 Amazon Web Services, Inc. and/or its affiliates. All rights reserved.

Amazon's trademarks and trade dress may not be used in connection with any product or service that is not Amazon's, in any manner that is likely to cause confusion among customers, or in any manner that disparages or discredits Amazon. All other trademarks not owned by Amazon are the property of their respective owners, who may or may not be affiliated with, connected to, or sponsored by Amazon.

Table of Contents

Welcome	1
Actions	2
AcceptAttachment	6
Request Syntax	6
URI Request Parameters	6
Request Body	6
Response Syntax	6
Response Elements	8
Errors	8
See Also	9
AssociateConnectPeer	11
Request Syntax	11
URI Request Parameters	11
Request Body	11
Response Syntax	12
Response Elements	13
Errors	13
See Also	15
AssociateCustomerGateway	16
Request Syntax	16
URI Request Parameters	16
Request Body	16
Response Syntax	17
Response Elements	18
Errors	18
See Also	20
AssociateLink	22
Request Syntax	22
URI Request Parameters	22
Request Body	22
Response Syntax	23
Response Elements	23
Errors	24
See Also	26

AssociateTransitGatewayConnectPeer	27
Request Syntax	27
URI Request Parameters	27
Request Body	27
Response Syntax	28
Response Elements	29
Errors	29
See Also	31
CreateConnectAttachment	33
Request Syntax	33
URI Request Parameters	33
Request Body	33
Response Syntax	35
Response Elements	36
Errors	37
See Also	38
CreateConnection	40
Request Syntax	40
URI Request Parameters	40
Request Body	41
Response Syntax	42
Response Elements	43
Errors	43
See Also	45
CreateConnectPeer	46
Request Syntax	46
URI Request Parameters	46
Request Body	46
Response Syntax	48
Response Elements	49
Errors	50
See Also	51
CreateCoreNetwork	53
Request Syntax	53
URI Request Parameters	53
Request Body	53

Response Syntax	55
Response Elements	56
Errors	56
See Also	58
CreateDevice	59
Request Syntax	59
URI Request Parameters	59
Request Body	60
Response Syntax	62
Response Elements	63
Errors	63
See Also	65
CreateDirectConnectGatewayAttachment	67
Request Syntax	67
URI Request Parameters	67
Request Body	67
Response Syntax	69
Response Elements	70
Errors	70
See Also	72
CreateGlobalNetwork	73
Request Syntax	73
URI Request Parameters	73
Request Body	73
Response Syntax	74
Response Elements	74
Errors	74
See Also	76
CreateLink	78
Request Syntax	78
URI Request Parameters	78
Request Body	79
Response Syntax	80
Response Elements	81
Errors	81
See Also	83

CreateSite	85
Request Syntax	85
URI Request Parameters	85
Request Body	85
Response Syntax	86
Response Elements	87
Errors	87
See Also	89
CreateSiteToSiteVpnAttachment	91
Request Syntax	91
URI Request Parameters	91
Request Body	91
Response Syntax	92
Response Elements	94
Errors	94
See Also	96
CreateTransitGatewayPeering	97
Request Syntax	97
URI Request Parameters	97
Request Body	97
Response Syntax	98
Response Elements	99
Errors	99
See Also	101
CreateTransitGatewayRouteTableAttachment	102
Request Syntax	102
URI Request Parameters	102
Request Body	102
Response Syntax	103
Response Elements	105
Errors	105
See Also	107
CreateVpcAttachment	108
Request Syntax	108
URI Request Parameters	108
Request Body	108

Response Syntax	110
Response Elements	111
Errors	112
See Also	113
DeleteAttachment	115
Request Syntax	115
URI Request Parameters	115
Request Body	115
Response Syntax	115
Response Elements	117
Errors	117
See Also	118
DeleteConnection	120
Request Syntax	120
URI Request Parameters	120
Request Body	120
Response Syntax	120
Response Elements	121
Errors	121
See Also	123
DeleteConnectPeer	124
Request Syntax	124
URI Request Parameters	124
Request Body	124
Response Syntax	124
Response Elements	125
Errors	126
See Also	127
DeleteCoreNetwork	129
Request Syntax	129
URI Request Parameters	129
Request Body	129
Response Syntax	129
Response Elements	130
Errors	131
See Also	132

DeleteCoreNetworkPolicyVersion	134
Request Syntax	134
URI Request Parameters	134
Request Body	134
Response Syntax	134
Response Elements	135
Errors	135
See Also	137
DeleteDevice	138
Request Syntax	138
URI Request Parameters	138
Request Body	138
Response Syntax	138
Response Elements	139
Errors	140
See Also	141
DeleteGlobalNetwork	143
Request Syntax	143
URI Request Parameters	143
Request Body	143
Response Syntax	143
Response Elements	144
Errors	144
See Also	146
DeleteLink	147
Request Syntax	147
URI Request Parameters	147
Request Body	147
Response Syntax	147
Response Elements	148
Errors	148
See Also	150
DeletePeering	151
Request Syntax	151
URI Request Parameters	151
Request Body	151

Response Syntax	151
Response Elements	152
Errors	152
See Also	154
DeleteResourcePolicy	155
Request Syntax	155
URI Request Parameters	155
Request Body	155
Response Syntax	155
Response Elements	155
Errors	155
See Also	157
DeleteSite	158
Request Syntax	158
URI Request Parameters	158
Request Body	158
Response Syntax	158
Response Elements	159
Errors	159
See Also	161
DeregisterTransitGateway	162
Request Syntax	162
URI Request Parameters	162
Request Body	162
Response Syntax	162
Response Elements	163
Errors	163
See Also	165
DescribeGlobalNetworks	166
Request Syntax	166
URI Request Parameters	166
Request Body	166
Response Syntax	167
Response Elements	167
Errors	168
See Also	169

DisassociateConnectPeer	170
Request Syntax	170
URI Request Parameters	170
Request Body	170
Response Syntax	170
Response Elements	171
Errors	171
See Also	173
DisassociateCustomerGateway	174
Request Syntax	174
URI Request Parameters	174
Request Body	174
Response Syntax	174
Response Elements	175
Errors	175
See Also	177
DisassociateLink	178
Request Syntax	178
URI Request Parameters	178
Request Body	179
Response Syntax	179
Response Elements	179
Errors	179
See Also	181
DisassociateTransitGatewayConnectPeer	182
Request Syntax	182
URI Request Parameters	182
Request Body	182
Response Syntax	182
Response Elements	183
Errors	183
See Also	185
ExecuteCoreNetworkChangeSet	186
Request Syntax	186
URI Request Parameters	186
Request Body	186

Response Syntax	186
Response Elements	186
Errors	187
See Also	188
GetConnectAttachment	190
Request Syntax	190
URI Request Parameters	190
Request Body	190
Response Syntax	190
Response Elements	192
Errors	192
See Also	193
GetConnections	195
Request Syntax	195
URI Request Parameters	195
Request Body	196
Response Syntax	196
Response Elements	197
Errors	197
See Also	198
GetConnectPeer	200
Request Syntax	200
URI Request Parameters	200
Request Body	200
Response Syntax	200
Response Elements	201
Errors	202
See Also	203
GetConnectPeerAssociations	204
Request Syntax	204
URI Request Parameters	204
Request Body	205
Response Syntax	205
Response Elements	205
Errors	206
See Also	207

GetCoreNetwork	209
Request Syntax	209
URI Request Parameters	209
Request Body	209
Response Syntax	209
Response Elements	210
Errors	211
See Also	212
GetCoreNetworkChangeEvents	213
Request Syntax	213
URI Request Parameters	213
Request Body	214
Response Syntax	214
Response Elements	214
Errors	215
See Also	216
GetCoreNetworkChangeSet	217
Request Syntax	217
URI Request Parameters	217
Request Body	218
Response Syntax	218
Response Elements	220
Errors	220
See Also	222
GetCoreNetworkPolicy	223
Request Syntax	223
URI Request Parameters	223
Request Body	223
Response Syntax	223
Response Elements	224
Errors	224
See Also	226
GetCustomerGatewayAssociations	227
Request Syntax	227
URI Request Parameters	227
Request Body	228

Response Syntax	228
Response Elements	228
Errors	229
See Also	230
GetDevices	232
Request Syntax	232
URI Request Parameters	232
Request Body	233
Response Syntax	233
Response Elements	234
Errors	234
See Also	236
GetDirectConnectGatewayAttachment	237
Request Syntax	237
URI Request Parameters	237
Request Body	237
Response Syntax	237
Response Elements	239
Errors	239
See Also	240
GetLinkAssociations	242
Request Syntax	242
URI Request Parameters	242
Request Body	243
Response Syntax	243
Response Elements	243
Errors	244
See Also	245
GetLinks	246
Request Syntax	246
URI Request Parameters	246
Request Body	247
Response Syntax	247
Response Elements	248
Errors	248
See Also	250

GetNetworkResourceCounts	251
Request Syntax	251
URI Request Parameters	251
Request Body	252
Response Syntax	252
Response Elements	253
Errors	253
See Also	254
GetNetworkResourceRelationships	256
Request Syntax	256
URI Request Parameters	256
Request Body	258
Response Syntax	258
Response Elements	259
Errors	259
See Also	260
GetNetworkResources	262
Request Syntax	262
URI Request Parameters	262
Request Body	264
Response Syntax	264
Response Elements	265
Errors	266
See Also	267
GetNetworkRoutes	268
Request Syntax	268
URI Request Parameters	268
Request Body	269
Response Syntax	271
Response Elements	272
Errors	273
See Also	274
GetNetworkTelemetry	276
Request Syntax	276
URI Request Parameters	276
Request Body	277

Response Syntax	278
Response Elements	278
Errors	279
See Also	280
GetResourcePolicy	281
Request Syntax	281
URI Request Parameters	281
Request Body	281
Response Syntax	281
Response Elements	281
Errors	282
See Also	283
GetRouteAnalysis	284
Request Syntax	284
URI Request Parameters	284
Request Body	284
Response Syntax	284
Response Elements	286
Errors	286
See Also	288
GetSites	289
Request Syntax	289
URI Request Parameters	289
Request Body	290
Response Syntax	290
Response Elements	290
Errors	291
See Also	292
GetSiteToSiteVpnAttachment	294
Request Syntax	294
URI Request Parameters	294
Request Body	294
Response Syntax	294
Response Elements	296
Errors	296
See Also	297

GetTransitGatewayConnectPeerAssociations	299
Request Syntax	299
URI Request Parameters	299
Request Body	300
Response Syntax	300
Response Elements	300
Errors	301
See Also	302
GetTransitGatewayPeering	304
Request Syntax	304
URI Request Parameters	304
Request Body	304
Response Syntax	304
Response Elements	305
Errors	305
See Also	307
GetTransitGatewayRegistrations	308
Request Syntax	308
URI Request Parameters	308
Request Body	309
Response Syntax	309
Response Elements	309
Errors	310
See Also	311
GetTransitGatewayRouteTableAttachment	312
Request Syntax	312
URI Request Parameters	312
Request Body	312
Response Syntax	312
Response Elements	314
Errors	314
See Also	315
GetVpcAttachment	317
Request Syntax	317
URI Request Parameters	317
Request Body	317

Response Syntax	317
Response Elements	319
Errors	319
See Also	320
ListAttachments	322
Request Syntax	322
URI Request Parameters	322
Request Body	323
Response Syntax	323
Response Elements	324
Errors	325
See Also	326
ListConnectPeers	327
Request Syntax	327
URI Request Parameters	327
Request Body	328
Response Syntax	328
Response Elements	328
Errors	329
See Also	330
ListCoreNetworkPolicyVersions	331
Request Syntax	331
URI Request Parameters	331
Request Body	331
Response Syntax	332
Response Elements	332
Errors	333
See Also	334
ListCoreNetworks	335
Request Syntax	335
URI Request Parameters	335
Request Body	335
Response Syntax	335
Response Elements	336
Errors	336
See Also	337

ListOrganizationServiceAccessStatus	339
Request Syntax	339
URI Request Parameters	339
Request Body	339
Response Syntax	339
Response Elements	340
Errors	340
See Also	340
ListPeerings	342
Request Syntax	342
URI Request Parameters	342
Request Body	343
Response Syntax	343
Response Elements	344
Errors	344
See Also	345
ListTagsForResource	347
Request Syntax	347
URI Request Parameters	347
Request Body	347
Response Syntax	347
Response Elements	348
Errors	348
See Also	349
PutCoreNetworkPolicy	351
Request Syntax	351
URI Request Parameters	351
Request Body	351
Response Syntax	352
Response Elements	353
Errors	353
See Also	355
PutResourcePolicy	356
Request Syntax	356
URI Request Parameters	356
Request Body	356

Response Syntax	357
Response Elements	357
Errors	357
See Also	359
RegisterTransitGateway	360
Request Syntax	360
URI Request Parameters	360
Request Body	360
Response Syntax	361
Response Elements	361
Errors	361
See Also	363
RejectAttachment	364
Request Syntax	364
URI Request Parameters	364
Request Body	364
Response Syntax	364
Response Elements	366
Errors	366
See Also	367
RestoreCoreNetworkPolicyVersion	369
Request Syntax	369
URI Request Parameters	369
Request Body	369
Response Syntax	369
Response Elements	370
Errors	370
See Also	372
StartOrganizationServiceAccessUpdate	373
Request Syntax	373
URI Request Parameters	373
Request Body	373
Response Syntax	373
Response Elements	374
Errors	374
See Also	376

StartRouteAnalysis	377
Request Syntax	377
URI Request Parameters	377
Request Body	377
Response Syntax	378
Response Elements	380
Errors	380
See Also	382
TagResource	383
Request Syntax	383
URI Request Parameters	383
Request Body	383
Response Syntax	384
Response Elements	384
Errors	384
See Also	386
UntagResource	387
Request Syntax	387
URI Request Parameters	387
Request Body	387
Response Syntax	387
Response Elements	388
Errors	388
See Also	389
UpdateConnection	391
Request Syntax	391
URI Request Parameters	391
Request Body	391
Response Syntax	392
Response Elements	393
Errors	393
See Also	395
UpdateCoreNetwork	396
Request Syntax	396
URI Request Parameters	396
Request Body	396

Response Syntax	397
Response Elements	398
Errors	398
See Also	400
UpdateDevice	401
Request Syntax	401
URI Request Parameters	401
Request Body	402
Response Syntax	404
Response Elements	405
Errors	405
See Also	407
UpdateDirectConnectGatewayAttachment	408
Request Syntax	408
URI Request Parameters	408
Request Body	408
Response Syntax	409
Response Elements	410
Errors	410
See Also	412
UpdateGlobalNetwork	413
Request Syntax	413
URI Request Parameters	413
Request Body	413
Response Syntax	414
Response Elements	414
Errors	414
See Also	416
UpdateLink	417
Request Syntax	417
URI Request Parameters	417
Request Body	418
Response Syntax	419
Response Elements	419
Errors	420
See Also	422

UpdateNetworkResourceMetadata	423
Request Syntax	423
URI Request Parameters	423
Request Body	423
Response Syntax	424
Response Elements	424
Errors	425
See Also	426
UpdateSite	428
Request Syntax	428
URI Request Parameters	428
Request Body	429
Response Syntax	429
Response Elements	430
Errors	430
See Also	432
UpdateVpcAttachment	433
Request Syntax	433
URI Request Parameters	433
Request Body	433
Response Syntax	434
Response Elements	436
Errors	436
See Also	438
Data Types	439
AccountStatus	442
Contents	442
See Also	442
Attachment	443
Contents	443
See Also	447
AttachmentError	448
Contents	448
See Also	449
AWSLocation	450
Contents	450

See Also	450
Bandwidth	451
Contents	451
See Also	451
BgpOptions	452
Contents	452
See Also	452
ConnectAttachment	453
Contents	453
See Also	453
ConnectAttachmentOptions	455
Contents	455
See Also	455
Connection	456
Contents	456
See Also	458
ConnectionHealth	459
Contents	459
See Also	459
ConnectPeer	461
Contents	461
See Also	463
ConnectPeerAssociation	464
Contents	464
See Also	465
ConnectPeerBgpConfiguration	466
Contents	466
See Also	467
ConnectPeerConfiguration	468
Contents	468
See Also	469
ConnectPeerError	470
Contents	470
See Also	471
ConnectPeerSummary	472
Contents	472

See Also	474
CoreNetwork	475
Contents	475
See Also	477
CoreNetworkChange	478
Contents	478
See Also	479
CoreNetworkChangeEvent	480
Contents	480
See Also	481
CoreNetworkChangeEventValues	482
Contents	482
See Also	483
CoreNetworkChangeValues	484
Contents	484
See Also	486
CoreNetworkEdge	488
Contents	488
See Also	488
CoreNetworkNetworkFunctionGroup	490
Contents	490
See Also	490
CoreNetworkNetworkFunctionGroupIdentifier	492
Contents	492
See Also	493
CoreNetworkPolicy	494
Contents	494
See Also	495
CoreNetworkPolicyError	497
Contents	497
See Also	498
CoreNetworkPolicyVersion	499
Contents	499
See Also	500
CoreNetworkSegment	501
Contents	501

See Also	502
CoreNetworkSegmentEdgeIdentifier	503
Contents	503
See Also	504
CoreNetworkSummary	505
Contents	505
See Also	506
CustomerGatewayAssociation	508
Contents	508
See Also	509
Device	510
Contents	510
See Also	513
DirectConnectGatewayAttachment	514
Contents	514
See Also	514
EdgeOverride	515
Contents	515
See Also	515
GlobalNetwork	516
Contents	516
See Also	517
Link	518
Contents	518
See Also	520
LinkAssociation	521
Contents	521
See Also	522
Location	523
Contents	523
See Also	524
NetworkFunctionGroup	525
Contents	525
See Also	525
NetworkResource	526
Contents	526

See Also	529
NetworkResourceCount	530
Contents	530
See Also	530
NetworkResourceSummary	531
Contents	531
See Also	532
NetworkRoute	533
Contents	533
See Also	534
NetworkRouteDestination	535
Contents	535
See Also	536
NetworkTelemetry	538
Contents	538
See Also	540
OrganizationStatus	541
Contents	541
See Also	542
PathComponent	543
Contents	543
See Also	543
Peering	545
Contents	545
See Also	547
PeeringError	548
Contents	548
See Also	549
PermissionsErrorContext	550
Contents	550
See Also	550
ProposedNetworkFunctionGroupChange	551
Contents	551
See Also	551
ProposedSegmentChange	553
Contents	553

See Also	553
Relationship	555
Contents	555
See Also	555
RouteAnalysis	556
Contents	556
See Also	558
RouteAnalysisCompletion	559
Contents	559
See Also	560
RouteAnalysisEndpointOptions	561
Contents	561
See Also	562
RouteAnalysisEndpointOptionsSpecification	563
Contents	563
See Also	563
RouteAnalysisPath	564
Contents	564
See Also	564
RouteTableIdentifier	565
Contents	565
See Also	565
ServiceInsertionAction	567
Contents	567
See Also	568
ServiceInsertionSegments	569
Contents	569
See Also	569
Site	570
Contents	570
See Also	571
SiteToSiteVpnAttachment	573
Contents	573
See Also	573
Tag	574
Contents	574

See Also	574
TransitGatewayConnectPeerAssociation	576
Contents	576
See Also	577
TransitGatewayPeering	578
Contents	578
See Also	578
TransitGatewayRegistration	580
Contents	580
See Also	580
TransitGatewayRegistrationStateReason	582
Contents	582
See Also	582
TransitGatewayRouteTableAttachment	583
Contents	583
See Also	584
ValidationExceptionField	585
Contents	585
See Also	585
Via	586
Contents	586
See Also	586
VpcAttachment	587
Contents	587
See Also	587
VpcOptions	589
Contents	589
See Also	589
WhenSentTo	591
Contents	591
See Also	591
Common Parameters	592
Common Errors	595

Welcome

Amazon Web Services enables you to centrally manage your AWS Cloud WAN core network and your Transit Gateway network across AWS accounts, Regions, and on-premises locations.

This document was last published on November 15, 2025.

Actions

The following actions are supported:

- [AcceptAttachment](#)
- [AssociateConnectPeer](#)
- [AssociateCustomerGateway](#)
- [AssociateLink](#)
- [AssociateTransitGatewayConnectPeer](#)
- [CreateConnectAttachment](#)
- [CreateConnection](#)
- [CreateConnectPeer](#)
- [CreateCoreNetwork](#)
- [CreateDevice](#)
- [CreateDirectConnectGatewayAttachment](#)
- [CreateGlobalNetwork](#)
- [CreateLink](#)
- [CreateSite](#)
- [CreateSiteToSiteVpnAttachment](#)
- [CreateTransitGatewayPeering](#)
- [CreateTransitGatewayRouteTableAttachment](#)
- [CreateVpcAttachment](#)
- [DeleteAttachment](#)
- [DeleteConnection](#)
- [DeleteConnectPeer](#)
- [DeleteCoreNetwork](#)
- [DeleteCoreNetworkPolicyVersion](#)
- [DeleteDevice](#)
- [DeleteGlobalNetwork](#)
- [DeleteLink](#)
- [DeletePeering](#)

- [DeleteResourcePolicy](#)
- [DeleteSite](#)
- [DeregisterTransitGateway](#)
- [DescribeGlobalNetworks](#)
- [DisassociateConnectPeer](#)
- [DisassociateCustomerGateway](#)
- [DisassociateLink](#)
- [DisassociateTransitGatewayConnectPeer](#)
- [ExecuteCoreNetworkChangeSet](#)
- [GetConnectAttachment](#)
- [GetConnections](#)
- [GetConnectPeer](#)
- [GetConnectPeerAssociations](#)
- [GetCoreNetwork](#)
- [GetCoreNetworkChangeEvents](#)
- [GetCoreNetworkChangeSet](#)
- [GetCoreNetworkPolicy](#)
- [GetCustomerGatewayAssociations](#)
- [GetDevices](#)
- [GetDirectConnectGatewayAttachment](#)
- [GetLinkAssociations](#)
- [GetLinks](#)
- [GetNetworkResourceCounts](#)
- [GetNetworkResourceRelationships](#)
- [GetNetworkResources](#)
- [GetNetworkRoutes](#)
- [GetNetworkTelemetry](#)
- [GetResourcePolicy](#)
- [GetRouteAnalysis](#)
- [GetSites](#)

- [GetSiteToSiteVpnAttachment](#)
- [GetTransitGatewayConnectPeerAssociations](#)
- [GetTransitGatewayPeering](#)
- [GetTransitGatewayRegistrations](#)
- [GetTransitGatewayRouteTableAttachment](#)
- [GetVpcAttachment](#)
- [ListAttachments](#)
- [ListConnectPeers](#)
- [ListCoreNetworkPolicyVersions](#)
- [ListCoreNetworks](#)
- [ListOrganizationServiceAccessStatus](#)
- [ListPeerings](#)
- [ListTagsForResource](#)
- [PutCoreNetworkPolicy](#)
- [PutResourcePolicy](#)
- [RegisterTransitGateway](#)
- [RejectAttachment](#)
- [RestoreCoreNetworkPolicyVersion](#)
- [StartOrganizationServiceAccessUpdate](#)
- [StartRouteAnalysis](#)
- [TagResource](#)
- [UntagResource](#)
- [UpdateConnection](#)
- [UpdateCoreNetwork](#)
- [UpdateDevice](#)
- [UpdateDirectConnectGatewayAttachment](#)
- [UpdateGlobalNetwork](#)
- [UpdateLink](#)
- [UpdateNetworkResourceMetadata](#)
- [UpdateSite](#)

- [UpdateVpcAttachment](#)

AcceptAttachment

Accepts a core network attachment request.

Once the attachment request is accepted by a core network owner, the attachment is created and connected to a core network.

Request Syntax

```
POST /attachments/attachmentId/accept HTTP/1.1
```

URI Request Parameters

The request uses the following URI parameters.

attachmentId

The ID of the attachment.

Length Constraints: Minimum length of 0. Maximum length of 50.

Pattern: `^attachment-([0-9a-f]{8,17})$`

Required: Yes

Request Body

The request does not have a request body.

Response Syntax

```
HTTP/1.1 200
```

```
Content-type: application/json
```

```
{
  "Attachment": {
    "AttachmentId": "string",
    "AttachmentPolicyRuleNumber": number,
    "AttachmentType": "string",
    "CoreNetworkArn": "string",
    "CoreNetworkId": "string",
```

```

    "CreatedAt": number,
    "EdgeLocation": "string",
    "EdgeLocations": [ "string" ],
    "LastModificationErrors": [
      {
        "Code": "string",
        "Message": "string",
        "RequestId": "string",
        "ResourceArn": "string"
      }
    ],
    "NetworkFunctionGroupName": "string",
    "OwnerAccountId": "string",
    "ProposedNetworkFunctionGroupChange": {
      "AttachmentPolicyRuleNumber": number,
      "NetworkFunctionGroupName": "string",
      "Tags": [
        {
          "Key": "string",
          "Value": "string"
        }
      ]
    },
    "ProposedSegmentChange": {
      "AttachmentPolicyRuleNumber": number,
      "SegmentName": "string",
      "Tags": [
        {
          "Key": "string",
          "Value": "string"
        }
      ]
    },
    "ResourceArn": "string",
    "SegmentName": "string",
    "State": "string",
    "Tags": [
      {
        "Key": "string",
        "Value": "string"
      }
    ],
    "UpdatedAt": number
  }

```

```
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

Attachment

The response to the attachment request.

Type: [Attachment](#) object

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

AccessDeniedException

You do not have sufficient access to perform this action.

HTTP Status Code: 403

ConflictException

There was a conflict processing the request. Updating or deleting the resource can cause an inconsistent state.

ResourceId

The ID of the resource.

ResourceType

The resource type.

HTTP Status Code: 409

InternalServerError

The request has failed due to an internal error.

RetryAfterSeconds

Indicates when to retry the request.

HTTP Status Code: 500

ResourceNotFoundException

The specified resource could not be found.

Context

The specified resource could not be found.

ResourceId

The ID of the resource.

ResourceType

The resource type.

HTTP Status Code: 404

ThrottlingException

The request was denied due to request throttling.

RetryAfterSeconds

Indicates when to retry the request.

HTTP Status Code: 429

ValidationException

The input fails to satisfy the constraints.

Fields

The fields that caused the error, if applicable.

Reason

The reason for the error.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

AssociateConnectPeer

Associates a core network Connect peer with a device and optionally, with a link.

If you specify a link, it must be associated with the specified device. You can only associate core network Connect peers that have been created on a core network Connect attachment on a core network.

Request Syntax

```
POST /global-networks/globalNetworkId/connect-peer-associations HTTP/1.1
Content-type: application/json
```

```
{
  "ConnectPeerId": "string",
  "DeviceId": "string",
  "LinkId": "string"
}
```

URI Request Parameters

The request uses the following URI parameters.

globalNetworkId

The ID of your global network.

Length Constraints: Minimum length of 0. Maximum length of 50.

Pattern: `[\s\S]*`

Required: Yes

Request Body

The request accepts the following data in JSON format.

ConnectPeerId

The ID of the Connect peer.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 50.

Pattern: `^connect-peer-([0-9a-f]{8,17})$`

Required: Yes

DeviceId

The ID of the device.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 50.

Pattern: `[\s\S]*`

Required: Yes

LinkId

The ID of the link.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 50.

Pattern: `[\s\S]*`

Required: No

Response Syntax

```
HTTP/1.1 200
```

```
Content-type: application/json
```

```
{
  "ConnectPeerAssociation": {
    "ConnectPeerId": "string",
    "DeviceId": "string",
    "GlobalNetworkId": "string",
    "LinkId": "string",
```

```
    "State": "string"  
  }  
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

ConnectPeerAssociation

The response to the Connect peer request.

Type: [ConnectPeerAssociation](#) object

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

AccessDeniedException

You do not have sufficient access to perform this action.

HTTP Status Code: 403

ConflictException

There was a conflict processing the request. Updating or deleting the resource can cause an inconsistent state.

ResourceId

The ID of the resource.

ResourceType

The resource type.

HTTP Status Code: 409

InternalServerError

The request has failed due to an internal error.

RetryAfterSeconds

Indicates when to retry the request.

HTTP Status Code: 500

ResourceNotFoundException

The specified resource could not be found.

Context

The specified resource could not be found.

ResourceId

The ID of the resource.

ResourceType

The resource type.

HTTP Status Code: 404

ServiceQuotaExceededException

A service limit was exceeded.

LimitCode

The limit code.

Message

The error message.

ResourceId

The ID of the resource.

ResourceType

The resource type.

ServiceCode

The service code.

HTTP Status Code: 402

ThrottlingException

The request was denied due to request throttling.

RetryAfterSeconds

Indicates when to retry the request.

HTTP Status Code: 429

ValidationException

The input fails to satisfy the constraints.

Fields

The fields that caused the error, if applicable.

Reason

The reason for the error.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

AssociateCustomerGateway

Associates a customer gateway with a device and optionally, with a link. If you specify a link, it must be associated with the specified device.

You can only associate customer gateways that are connected to a VPN attachment on a transit gateway or core network registered in your global network. When you register a transit gateway or core network, customer gateways that are connected to the transit gateway are automatically included in the global network. To list customer gateways that are connected to a transit gateway, use the [DescribeVpnConnections](#) EC2 API and filter by `transit-gateway-id`.

You cannot associate a customer gateway with more than one device and link.

Request Syntax

```
POST /global-networks/globalNetworkId/customer-gateway-associations HTTP/1.1
Content-type: application/json

{
  "CustomerGatewayArn": "string",
  "DeviceId": "string",
  "LinkId": "string"
}
```

URI Request Parameters

The request uses the following URI parameters.

[globalNetworkId](#)

The ID of the global network.

Length Constraints: Minimum length of 0. Maximum length of 50.

Pattern: `[\s\S]*`

Required: Yes

Request Body

The request accepts the following data in JSON format.

CustomerGatewayArn

The Amazon Resource Name (ARN) of the customer gateway.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 500.

Pattern: `[\s\S]*`

Required: Yes

DeviceId

The ID of the device.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 50.

Pattern: `[\s\S]*`

Required: Yes

LinkId

The ID of the link.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 50.

Pattern: `[\s\S]*`

Required: No

Response Syntax

```
HTTP/1.1 200
Content-type: application/json

{
  "CustomerGatewayAssociation": {
    "CustomerGatewayArn": "string",
```

```
"DeviceId": "string",  
"GlobalNetworkId": "string",  
"LinkId": "string",  
"State": "string"  
}  
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

[CustomerGatewayAssociation](#)

The customer gateway association.

Type: [CustomerGatewayAssociation](#) object

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

AccessDeniedException

You do not have sufficient access to perform this action.

HTTP Status Code: 403

ConflictException

There was a conflict processing the request. Updating or deleting the resource can cause an inconsistent state.

ResourceId

The ID of the resource.

ResourceType

The resource type.

HTTP Status Code: 409

InternalServerErrorException

The request has failed due to an internal error.

RetryAfterSeconds

Indicates when to retry the request.

HTTP Status Code: 500

ResourceNotFoundException

The specified resource could not be found.

Context

The specified resource could not be found.

ResourceId

The ID of the resource.

ResourceType

The resource type.

HTTP Status Code: 404

ServiceQuotaExceededException

A service limit was exceeded.

LimitCode

The limit code.

Message

The error message.

ResourceId

The ID of the resource.

ResourceType

The resource type.

ServiceCode

The service code.

HTTP Status Code: 402

ThrottlingException

The request was denied due to request throttling.

RetryAfterSeconds

Indicates when to retry the request.

HTTP Status Code: 429

ValidationException

The input fails to satisfy the constraints.

Fields

The fields that caused the error, if applicable.

Reason

The reason for the error.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

AssociateLink

Associates a link to a device. A device can be associated to multiple links and a link can be associated to multiple devices. The device and link must be in the same global network and the same site.

Request Syntax

```
POST /global-networks/globalNetworkId/link-associations HTTP/1.1
Content-type: application/json

{
  "DeviceId": "string",
  "LinkId": "string"
}
```

URI Request Parameters

The request uses the following URI parameters.

globalNetworkId

The ID of the global network.

Length Constraints: Minimum length of 0. Maximum length of 50.

Pattern: [*\s\S*]*

Required: Yes

Request Body

The request accepts the following data in JSON format.

DeviceId

The ID of the device.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 50.

Pattern: `[\s\S]*`

Required: Yes

LinkId

The ID of the link.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 50.

Pattern: `[\s\S]*`

Required: Yes

Response Syntax

```
HTTP/1.1 200
Content-type: application/json

{
  "LinkAssociation": {
    "DeviceId": "string",
    "GlobalNetworkId": "string",
    "LinkAssociationState": "string",
    "LinkId": "string"
  }
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

LinkAssociation

The link association.

Type: LinkAssociation object

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

AccessDeniedException

You do not have sufficient access to perform this action.

HTTP Status Code: 403

ConflictException

There was a conflict processing the request. Updating or deleting the resource can cause an inconsistent state.

ResourceId

The ID of the resource.

ResourceType

The resource type.

HTTP Status Code: 409

InternalServerError

The request has failed due to an internal error.

RetryAfterSeconds

Indicates when to retry the request.

HTTP Status Code: 500

ResourceNotFoundException

The specified resource could not be found.

Context

The specified resource could not be found.

ResourceId

The ID of the resource.

ResourceType

The resource type.

HTTP Status Code: 404

ServiceQuotaExceededException

A service limit was exceeded.

LimitCode

The limit code.

Message

The error message.

ResourceId

The ID of the resource.

ResourceType

The resource type.

ServiceCode

The service code.

HTTP Status Code: 402

ThrottlingException

The request was denied due to request throttling.

RetryAfterSeconds

Indicates when to retry the request.

HTTP Status Code: 429

ValidationException

The input fails to satisfy the constraints.

Fields

The fields that caused the error, if applicable.

Reason

The reason for the error.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

AssociateTransitGatewayConnectPeer

Associates a transit gateway Connect peer with a device, and optionally, with a link. If you specify a link, it must be associated with the specified device.

You can only associate transit gateway Connect peers that have been created on a transit gateway that's registered in your global network.

You cannot associate a transit gateway Connect peer with more than one device and link.

Request Syntax

```
POST /global-networks/globalNetworkId/transit-gateway-connect-peer-associations
HTTP/1.1
Content-type: application/json

{
  "DeviceId": "string",
  "LinkId": "string",
  "TransitGatewayConnectPeerArn": "string"
}
```

URI Request Parameters

The request uses the following URI parameters.

globalNetworkId

The ID of the global network.

Length Constraints: Minimum length of 0. Maximum length of 50.

Pattern: `[\s\S]*`

Required: Yes

Request Body

The request accepts the following data in JSON format.

DeviceId

The ID of the device.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 50.

Pattern: `[\s\S]*`

Required: Yes

LinkId

The ID of the link.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 50.

Pattern: `[\s\S]*`

Required: No

TransitGatewayConnectPeerArn

The Amazon Resource Name (ARN) of the Connect peer.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 500.

Pattern: `[\s\S]*`

Required: Yes

Response Syntax

```
HTTP/1.1 200
Content-type: application/json

{
  "TransitGatewayConnectPeerAssociation": {
    "DeviceId": "string",
```

```
"GlobalNetworkId": "string",  
"LinkId": "string",  
"State": "string",  
"TransitGatewayConnectPeerArn": "string"  
}  
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

TransitGatewayConnectPeerAssociation

The transit gateway Connect peer association.

Type: [TransitGatewayConnectPeerAssociation](#) object

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

AccessDeniedException

You do not have sufficient access to perform this action.

HTTP Status Code: 403

ConflictException

There was a conflict processing the request. Updating or deleting the resource can cause an inconsistent state.

ResourceId

The ID of the resource.

ResourceType

The resource type.

HTTP Status Code: 409

InternalServerErrorException

The request has failed due to an internal error.

RetryAfterSeconds

Indicates when to retry the request.

HTTP Status Code: 500

ResourceNotFoundException

The specified resource could not be found.

Context

The specified resource could not be found.

ResourceId

The ID of the resource.

ResourceType

The resource type.

HTTP Status Code: 404

ServiceQuotaExceededException

A service limit was exceeded.

LimitCode

The limit code.

Message

The error message.

ResourceId

The ID of the resource.

ResourceType

The resource type.

ServiceCode

The service code.

HTTP Status Code: 402

ThrottlingException

The request was denied due to request throttling.

RetryAfterSeconds

Indicates when to retry the request.

HTTP Status Code: 429

ValidationException

The input fails to satisfy the constraints.

Fields

The fields that caused the error, if applicable.

Reason

The reason for the error.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

CreateConnectAttachment

Creates a core network Connect attachment from a specified core network attachment.

A core network Connect attachment is a GRE-based tunnel attachment that you can use to establish a connection between a core network and an appliance. A core network Connect attachment uses an existing VPC attachment as the underlying transport mechanism.

Request Syntax

```
POST /connect-attachments HTTP/1.1
Content-type: application/json

{
  "ClientToken": "string",
  "CoreNetworkId": "string",
  "EdgeLocation": "string",
  "Options": {
    "Protocol": "string"
  },
  "Tags": [
    {
      "Key": "string",
      "Value": "string"
    }
  ],
  "TransportAttachmentId": "string"
}
```

URI Request Parameters

The request does not use any URI parameters.

Request Body

The request accepts the following data in JSON format.

ClientToken

The client token associated with the request.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 256.

Pattern: `[\s\S]*`

Required: No

CoreNetworkId

The ID of a core network where you want to create the attachment.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 50.

Pattern: `^core-network-([0-9a-f]{8,17})$`

Required: Yes

EdgeLocation

The Region where the edge is located.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 63.

Pattern: `[\s\S]*`

Required: Yes

Options

Options for creating an attachment.

Type: [ConnectAttachmentOptions](#) object

Required: Yes

Tags

The list of key-value tags associated with the request.

Type: Array of [Tag](#) objects

Required: No

TransportAttachmentId

The ID of the attachment between the two connections.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 50.

Pattern: ^attachment-([0-9a-f]{8,17})\$

Required: Yes

Response Syntax

HTTP/1.1 200

Content-type: application/json

```
{
  "ConnectAttachment": {
    "Attachment": {
      "AttachmentId": "string",
      "AttachmentPolicyRuleNumber": number,
      "AttachmentType": "string",
      "CoreNetworkArn": "string",
      "CoreNetworkId": "string",
      "CreatedAt": number,
      "EdgeLocation": "string",
      "EdgeLocations": [ "string" ],
      "LastModificationErrors": [
        {
          "Code": "string",
          "Message": "string",
          "RequestId": "string",
          "ResourceArn": "string"
        }
      ],
      "NetworkFunctionGroupName": "string",
      "OwnerAccountId": "string",
      "ProposedNetworkFunctionGroupChange": {
        "AttachmentPolicyRuleNumber": number,
        "NetworkFunctionGroupName": "string",
        "Tags": [
          {
```

```

        "Key": "string",
        "Value": "string"
      }
    ]
  },
  "ProposedSegmentChange": {
    "AttachmentPolicyRuleNumber": number,
    "SegmentName": "string",
    "Tags": [
      {
        "Key": "string",
        "Value": "string"
      }
    ]
  },
  "ResourceArn": "string",
  "SegmentName": "string",
  "State": "string",
  "Tags": [
    {
      "Key": "string",
      "Value": "string"
    }
  ],
  "UpdatedAt": number
},
"Options": {
  "Protocol": "string"
},
"TransportAttachmentId": "string"
}
}

```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

ConnectAttachment

The response to a Connect attachment request.

Type: [ConnectAttachment](#) object

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

AccessDeniedException

You do not have sufficient access to perform this action.

HTTP Status Code: 403

ConflictException

There was a conflict processing the request. Updating or deleting the resource can cause an inconsistent state.

ResourceId

The ID of the resource.

ResourceType

The resource type.

HTTP Status Code: 409

InternalServerError

The request has failed due to an internal error.

RetryAfterSeconds

Indicates when to retry the request.

HTTP Status Code: 500

ResourceNotFoundException

The specified resource could not be found.

Context

The specified resource could not be found.

ResourceId

The ID of the resource.

ResourceType

The resource type.

HTTP Status Code: 404

ThrottlingException

The request was denied due to request throttling.

RetryAfterSeconds

Indicates when to retry the request.

HTTP Status Code: 429

ValidationException

The input fails to satisfy the constraints.

Fields

The fields that caused the error, if applicable.

Reason

The reason for the error.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)

- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

CreateConnection

Creates a connection between two devices. The devices can be a physical or virtual appliance that connects to a third-party appliance in a VPC, or a physical appliance that connects to another physical appliance in an on-premises network.

Request Syntax

```
POST /global-networks/globalNetworkId/connections HTTP/1.1
```

```
Content-type: application/json
```

```
{
  "ConnectedDeviceId": "string",
  "ConnectedLinkId": "string",
  "Description": "string",
  "DeviceId": "string",
  "LinkId": "string",
  "Tags": [
    {
      "Key": "string",
      "Value": "string"
    }
  ]
}
```

URI Request Parameters

The request uses the following URI parameters.

globalNetworkId

The ID of the global network.

Length Constraints: Minimum length of 0. Maximum length of 50.

Pattern: `[\s\S]*`

Required: Yes

Request Body

The request accepts the following data in JSON format.

ConnectedDeviceId

The ID of the second device in the connection.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 50.

Pattern: `[\s\S]*`

Required: Yes

ConnectedLinkId

The ID of the link for the second device.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 50.

Pattern: `[\s\S]*`

Required: No

Description

A description of the connection.

Length Constraints: Maximum length of 256 characters.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 256.

Pattern: `[\s\S]*`

Required: No

DeviceId

The ID of the first device in the connection.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 50.

Pattern: `[\s\S]*`

Required: Yes

[LinkId](#)

The ID of the link for the first device.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 50.

Pattern: `[\s\S]*`

Required: No

[Tags](#)

The tags to apply to the resource during creation.

Type: Array of [Tag](#) objects

Required: No

Response Syntax

```
HTTP/1.1 200
```

```
Content-type: application/json
```

```
{
  "Connection": {
    "ConnectedDeviceId": "string",
    "ConnectedLinkId": "string",
    "ConnectionArn": "string",
    "ConnectionId": "string",
    "CreatedAt": number,
    "Description": "string",
    "DeviceId": "string",
    "GlobalNetworkId": "string",
    "LinkId": "string",
```

```
  "State": "string",
  "Tags": [
    {
      "Key": "string",
      "Value": "string"
    }
  ]
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

Connection

Information about the connection.

Type: [Connection](#) object

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

AccessDeniedException

You do not have sufficient access to perform this action.

HTTP Status Code: 403

ConflictException

There was a conflict processing the request. Updating or deleting the resource can cause an inconsistent state.

ResourceId

The ID of the resource.

ResourceType

The resource type.

HTTP Status Code: 409

InternalServerError

The request has failed due to an internal error.

RetryAfterSeconds

Indicates when to retry the request.

HTTP Status Code: 500

ServiceQuotaExceededException

A service limit was exceeded.

LimitCode

The limit code.

Message

The error message.

ResourceId

The ID of the resource.

ResourceType

The resource type.

ServiceCode

The service code.

HTTP Status Code: 402

ThrottlingException

The request was denied due to request throttling.

RetryAfterSeconds

Indicates when to retry the request.

HTTP Status Code: 429

ValidationException

The input fails to satisfy the constraints.

Fields

The fields that caused the error, if applicable.

Reason

The reason for the error.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

CreateConnectPeer

Creates a core network Connect peer for a specified core network connect attachment between a core network and an appliance. The peer address and transit gateway address must be the same IP address family (IPv4 or IPv6).

Request Syntax

```
POST /connect-peers HTTP/1.1
Content-type: application/json
```

```
{
  "BgpOptions": {
    "PeerAsn": number
  },
  "ClientToken": "string",
  "ConnectAttachmentId": "string",
  "CoreNetworkAddress": "string",
  "InsideCidrBlocks": [ "string" ],
  "PeerAddress": "string",
  "SubnetArn": "string",
  "Tags": [
    {
      "Key": "string",
      "Value": "string"
    }
  ]
}
```

URI Request Parameters

The request does not use any URI parameters.

Request Body

The request accepts the following data in JSON format.

BgpOptions

The Connect peer BGP options. This only applies only when the protocol is GRE.

Type: BgpOptions object

Required: No

ClientToken

The client token associated with the request.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 256.

Pattern: `[\s\S]*`

Required: No

ConnectAttachmentId

The ID of the connection attachment.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 50.

Pattern: `^attachment-([0-9a-f]{8,17})$`

Required: Yes

CoreNetworkAddress

A Connect peer core network address. This only applies only when the protocol is GRE.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 50.

Pattern: `[\s\S]*`

Required: No

InsideCidrBlocks

The inside IP addresses used for BGP peering.

Type: Array of strings

Length Constraints: Minimum length of 0. Maximum length of 256.

Pattern: `[\s\S]*`

Required: No

PeerAddress

The Connect peer address.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 50.

Pattern: `[\s\S]*`

Required: Yes

SubnetArn

The subnet ARN for the Connect peer. This only applies only when the protocol is NO_ENCAP.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 500.

Pattern: `^arn:[^:]{1,63}:ec2:[^:]{0,63}:[^:]{0,63}:subnet\/subnet-[0-9a-f]{8,17}$|^$`

Required: No

Tags

The tags associated with the peer request.

Type: Array of [Tag](#) objects

Required: No

Response Syntax

```
HTTP/1.1 200
Content-type: application/json

{
  "ConnectPeer": {
    "Configuration": {
      "BgpConfigurations": [
        {
          "CoreNetworkAddress": "string",
```



```

        "CoreNetworkAsn": number,
        "PeerAddress": "string",
        "PeerAsn": number
    }
],
"CoreNetworkAddress": "string",
"InsideCidrBlocks": [ "string" ],
"PeerAddress": "string",
"Protocol": "string"
},
"ConnectAttachmentId": "string",
"ConnectPeerId": "string",
"CoreNetworkId": "string",
"CreatedAt": number,
"EdgeLocation": "string",
"LastModificationErrors": [
    {
        "Code": "string",
        "Message": "string",
        "RequestId": "string",
        "ResourceArn": "string"
    }
],
"State": "string",
"SubnetArn": "string",
"Tags": [
    {
        "Key": "string",
        "Value": "string"
    }
]
}
}

```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

ConnectPeer

The response to the request.

Type: [ConnectPeer](#) object

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

AccessDeniedException

You do not have sufficient access to perform this action.

HTTP Status Code: 403

ConflictException

There was a conflict processing the request. Updating or deleting the resource can cause an inconsistent state.

ResourceId

The ID of the resource.

ResourceType

The resource type.

HTTP Status Code: 409

InternalServerError

The request has failed due to an internal error.

RetryAfterSeconds

Indicates when to retry the request.

HTTP Status Code: 500

ResourceNotFoundException

The specified resource could not be found.

Context

The specified resource could not be found.

ResourceId

The ID of the resource.

ResourceType

The resource type.

HTTP Status Code: 404

ThrottlingException

The request was denied due to request throttling.

RetryAfterSeconds

Indicates when to retry the request.

HTTP Status Code: 429

ValidationException

The input fails to satisfy the constraints.

Fields

The fields that caused the error, if applicable.

Reason

The reason for the error.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)

- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

CreateCoreNetwork

Creates a core network as part of your global network, and optionally, with a core network policy.

Request Syntax

```
POST /core-networks HTTP/1.1
Content-type: application/json
```

```
{
  "ClientToken": "string",
  "Description": "string",
  "GlobalNetworkId": "string",
  "PolicyDocument": "string",
  "Tags": [
    {
      "Key": "string",
      "Value": "string"
    }
  ]
}
```

URI Request Parameters

The request does not use any URI parameters.

Request Body

The request accepts the following data in JSON format.

ClientToken

The client token associated with a core network request.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 256.

Pattern: `[\s\S]*`

Required: No

Description

The description of a core network.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 256.

Pattern: `[\s\S]*`

Required: No

GlobalNetworkId

The ID of the global network that a core network will be a part of.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 50.

Pattern: `[\s\S]*`

Required: Yes

PolicyDocument

The policy document for creating a core network.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 10000000.

Pattern: `[\s\S]*`

Required: No

Tags

Key-value tags associated with a core network request.

Type: Array of [Tag](#) objects

Required: No

Response Syntax

HTTP/1.1 200

Content-type: application/json

```
{
  "CoreNetwork": {
    "CoreNetworkArn": "string",
    "CoreNetworkId": "string",
    "CreatedAt": number,
    "Description": "string",
    "Edges": [
      {
        "Asn": number,
        "EdgeLocation": "string",
        "InsideCidrBlocks": [ "string" ]
      }
    ],
    "GlobalNetworkId": "string",
    "NetworkFunctionGroups": [
      {
        "EdgeLocations": [ "string" ],
        "Name": "string",
        "Segments": {
          "SendTo": [ "string" ],
          "SendVia": [ "string" ]
        }
      }
    ],
    "Segments": [
      {
        "EdgeLocations": [ "string" ],
        "Name": "string",
        "SharedSegments": [ "string" ]
      }
    ],
    "State": "string",
    "Tags": [
      {
        "Key": "string",
        "Value": "string"
      }
    ]
  }
}
```

```
}  
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

CoreNetwork

Returns details about a core network.

Type: [CoreNetwork](#) object

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

AccessDeniedException

You do not have sufficient access to perform this action.

HTTP Status Code: 403

ConflictException

There was a conflict processing the request. Updating or deleting the resource can cause an inconsistent state.

ResourceId

The ID of the resource.

ResourceType

The resource type.

HTTP Status Code: 409

CoreNetworkPolicyException

Describes a core network policy exception.

Errors

Describes a core network policy exception.

HTTP Status Code: 400

InternalServerError

The request has failed due to an internal error.

RetryAfterSeconds

Indicates when to retry the request.

HTTP Status Code: 500

ServiceQuotaExceededException

A service limit was exceeded.

LimitCode

The limit code.

Message

The error message.

ResourceId

The ID of the resource.

ResourceType

The resource type.

ServiceCode

The service code.

HTTP Status Code: 402

ThrottlingException

The request was denied due to request throttling.

RetryAfterSeconds

Indicates when to retry the request.

HTTP Status Code: 429

ValidationException

The input fails to satisfy the constraints.

Fields

The fields that caused the error, if applicable.

Reason

The reason for the error.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

CreateDevice

Creates a new device in a global network. If you specify both a site ID and a location, the location of the site is used for visualization in the Network Manager console.

Request Syntax

```
POST /global-networks/globalNetworkId/devices HTTP/1.1
Content-type: application/json
```

```
{
  "AWSLocation": {
    "SubnetArn": "string",
    "Zone": "string"
  },
  "Description": "string",
  "Location": {
    "Address": "string",
    "Latitude": "string",
    "Longitude": "string"
  },
  "Model": "string",
  "SerialNumber": "string",
  "SiteId": "string",
  "Tags": [
    {
      "Key": "string",
      "Value": "string"
    }
  ],
  "Type": "string",
  "Vendor": "string"
}
```

URI Request Parameters

The request uses the following URI parameters.

globalNetworkId

The ID of the global network.

Length Constraints: Minimum length of 0. Maximum length of 50.

Pattern: `[\s\S]*`

Required: Yes

Request Body

The request accepts the following data in JSON format.

AWSLocation

The AWS location of the device, if applicable. For an on-premises device, you can omit this parameter.

Type: [AWSLocation](#) object

Required: No

Description

A description of the device.

Constraints: Maximum length of 256 characters.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 256.

Pattern: `[\s\S]*`

Required: No

Location

The location of the device.

Type: [Location](#) object

Required: No

Model

The model of the device.

Constraints: Maximum length of 128 characters.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 256.

Pattern: `[\s\S]*`

Required: No

SerialNumber

The serial number of the device.

Constraints: Maximum length of 128 characters.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 256.

Pattern: `[\s\S]*`

Required: No

Siteld

The ID of the site.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 50.

Pattern: `[\s\S]*`

Required: No

Tags

The tags to apply to the resource during creation.

Type: Array of [Tag](#) objects

Required: No

Type

The type of the device.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 256.

Pattern: `[\s\S]*`

Required: No

Vendor

The vendor of the device.

Constraints: Maximum length of 128 characters.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 256.

Pattern: `[\s\S]*`

Required: No

Response Syntax

```
HTTP/1.1 200
Content-type: application/json

{
  "Device": {
    "AWSLocation": {
      "SubnetArn": "string",
      "Zone": "string"
    },
    "CreatedAt": number,
    "Description": "string",
    "DeviceArn": "string",
    "DeviceId": "string",
    "GlobalNetworkId": "string",
    "Location": {
      "Address": "string",
      "Latitude": "string",
      "Longitude": "string"
    },
    "Model": "string",
```

```
  "SerialNumber": "string",
  "SiteId": "string",
  "State": "string",
  "Tags": [
    {
      "Key": "string",
      "Value": "string"
    }
  ],
  "Type": "string",
  "Vendor": "string"
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

Device

Information about the device.

Type: [Device](#) object

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

AccessDeniedException

You do not have sufficient access to perform this action.

HTTP Status Code: 403

ConflictException

There was a conflict processing the request. Updating or deleting the resource can cause an inconsistent state.

ResourceId

The ID of the resource.

ResourceType

The resource type.

HTTP Status Code: 409

InternalServerError

The request has failed due to an internal error.

RetryAfterSeconds

Indicates when to retry the request.

HTTP Status Code: 500

ResourceNotFoundException

The specified resource could not be found.

Context

The specified resource could not be found.

ResourceId

The ID of the resource.

ResourceType

The resource type.

HTTP Status Code: 404

ServiceQuotaExceededException

A service limit was exceeded.

LimitCode

The limit code.

Message

The error message.

ResourceId

The ID of the resource.

ResourceType

The resource type.

ServiceCode

The service code.

HTTP Status Code: 402

ThrottlingException

The request was denied due to request throttling.

RetryAfterSeconds

Indicates when to retry the request.

HTTP Status Code: 429

ValidationException

The input fails to satisfy the constraints.

Fields

The fields that caused the error, if applicable.

Reason

The reason for the error.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)

- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

CreateDirectConnectGatewayAttachment

Creates an AWS Direct Connect gateway attachment

Request Syntax

```
POST /direct-connect-gateway-attachments HTTP/1.1
Content-type: application/json
```

```
{
  "ClientToken": "string",
  "CoreNetworkId": "string",
  "DirectConnectGatewayArn": "string",
  "EdgeLocations": [ "string" ],
  "Tags": [
    {
      "Key": "string",
      "Value": "string"
    }
  ]
}
```

URI Request Parameters

The request does not use any URI parameters.

Request Body

The request accepts the following data in JSON format.

ClientToken

client token

Type: String

Length Constraints: Minimum length of 0. Maximum length of 256.

Pattern: `[\s\S]*`

Required: No

CoreNetworkId

The ID of the Cloud WAN core network that the Direct Connect gateway attachment should be attached to.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 50.

Pattern: `^core-network-([0-9a-f]{8,17})$`

Required: Yes

DirectConnectGatewayArn

The ARN of the Direct Connect gateway attachment.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 500.

Pattern: `^arn:[^:]{1,63}:directconnect:[^:]{0,63}:dx-gateway\/[0-9a-f]{8}-([0-9a-f]{4}-){3}[0-9a-f]{12}$`

Required: Yes

EdgeLocations

One or more core network edge locations that the Direct Connect gateway attachment is associated with.

Type: Array of strings

Length Constraints: Minimum length of 1. Maximum length of 63.

Pattern: `[\s\S]*`

Required: Yes

Tags

The key value tags to apply to the Direct Connect gateway attachment during creation.

Type: Array of [Tag](#) objects

Required: No

Response Syntax

HTTP/1.1 200

Content-type: application/json

```
{
  "DirectConnectGatewayAttachment": {
    "Attachment": {
      "AttachmentId": "string",
      "AttachmentPolicyRuleNumber": number,
      "AttachmentType": "string",
      "CoreNetworkArn": "string",
      "CoreNetworkId": "string",
      "CreatedAt": number,
      "EdgeLocation": "string",
      "EdgeLocations": [ "string" ],
      "LastModificationErrors": [
        {
          "Code": "string",
          "Message": "string",
          "RequestId": "string",
          "ResourceArn": "string"
        }
      ],
      "NetworkFunctionGroupName": "string",
      "OwnerAccountId": "string",
      "ProposedNetworkFunctionGroupChange": {
        "AttachmentPolicyRuleNumber": number,
        "NetworkFunctionGroupName": "string",
        "Tags": [
          {
            "Key": "string",
            "Value": "string"
          }
        ]
      }
    },
    "ProposedSegmentChange": {
      "AttachmentPolicyRuleNumber": number,
      "SegmentName": "string",
      "Tags": [
        {
          "Key": "string",
          "Value": "string"
        }
      ]
    }
  }
}
```

```
    }
  ]
},
"ResourceArn": "string",
"SegmentName": "string",
"State": "string",
"Tags": [
  {
    "Key": "string",
    "Value": "string"
  }
],
"UpdatedAt": number
},
"DirectConnectGatewayArn": "string"
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

DirectConnectGatewayAttachment

Describes the details of a CreateDirectConnectGatewayAttachment request.

Type: [DirectConnectGatewayAttachment](#) object

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

AccessDeniedException

You do not have sufficient access to perform this action.

HTTP Status Code: 403

ConflictException

There was a conflict processing the request. Updating or deleting the resource can cause an inconsistent state.

ResourceId

The ID of the resource.

ResourceType

The resource type.

HTTP Status Code: 409

InternalServerErrorException

The request has failed due to an internal error.

RetryAfterSeconds

Indicates when to retry the request.

HTTP Status Code: 500

ResourceNotFoundException

The specified resource could not be found.

Context

The specified resource could not be found.

ResourceId

The ID of the resource.

ResourceType

The resource type.

HTTP Status Code: 404

ThrottlingException

The request was denied due to request throttling.

RetryAfterSeconds

Indicates when to retry the request.

HTTP Status Code: 429

ValidationException

The input fails to satisfy the constraints.

Fields

The fields that caused the error, if applicable.

Reason

The reason for the error.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

CreateGlobalNetwork

Creates a new, empty global network.

Request Syntax

```
POST /global-networks HTTP/1.1
Content-type: application/json
```

```
{
  "Description": "string",
  "Tags": [
    {
      "Key": "string",
      "Value": "string"
    }
  ]
}
```

URI Request Parameters

The request does not use any URI parameters.

Request Body

The request accepts the following data in JSON format.

Description

A description of the global network.

Constraints: Maximum length of 256 characters.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 256.

Pattern: `[\s\S]*`

Required: No

Tags

The tags to apply to the resource during creation.

Type: Array of [Tag](#) objects

Required: No

Response Syntax

```
HTTP/1.1 200
Content-type: application/json

{
  "GlobalNetwork": {
    "CreatedAt": number,
    "Description": "string",
    "GlobalNetworkArn": "string",
    "GlobalNetworkId": "string",
    "State": "string",
    "Tags": [
      {
        "Key": "string",
        "Value": "string"
      }
    ]
  }
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

[GlobalNetwork](#)

Information about the global network object.

Type: [GlobalNetwork](#) object

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

AccessDeniedException

You do not have sufficient access to perform this action.

HTTP Status Code: 403

ConflictException

There was a conflict processing the request. Updating or deleting the resource can cause an inconsistent state.

ResourceId

The ID of the resource.

ResourceType

The resource type.

HTTP Status Code: 409

InternalServerError

The request has failed due to an internal error.

RetryAfterSeconds

Indicates when to retry the request.

HTTP Status Code: 500

ServiceQuotaExceededException

A service limit was exceeded.

LimitCode

The limit code.

Message

The error message.

ResourceId

The ID of the resource.

ResourceType

The resource type.

ServiceCode

The service code.

HTTP Status Code: 402

ThrottlingException

The request was denied due to request throttling.

RetryAfterSeconds

Indicates when to retry the request.

HTTP Status Code: 429

ValidationException

The input fails to satisfy the constraints.

Fields

The fields that caused the error, if applicable.

Reason

The reason for the error.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)

- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

CreateLink

Creates a new link for a specified site.

Request Syntax

```
POST /global-networks/globalNetworkId/links HTTP/1.1
Content-type: application/json
```

```
{
  "Bandwidth": {
    "DownloadSpeed": number,
    "UploadSpeed": number
  },
  "Description": "string",
  "Provider": "string",
  "SiteId": "string",
  "Tags": [
    {
      "Key": "string",
      "Value": "string"
    }
  ],
  "Type": "string"
}
```

URI Request Parameters

The request uses the following URI parameters.

globalNetworkId

The ID of the global network.

Length Constraints: Minimum length of 0. Maximum length of 50.

Pattern: `[\s\S]*`

Required: Yes

Request Body

The request accepts the following data in JSON format.

Bandwidth

The upload speed and download speed in Mbps.

Type: [Bandwidth](#) object

Required: Yes

Description

A description of the link.

Constraints: Maximum length of 256 characters.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 256.

Pattern: `[\s\S]*`

Required: No

Provider

The provider of the link.

Constraints: Maximum length of 128 characters. Cannot include the following characters: `| \ ^`

Type: String

Length Constraints: Minimum length of 0. Maximum length of 256.

Pattern: `[\s\S]*`

Required: No

Siteld

The ID of the site.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 50.

Pattern: `[\s\S]*`

Required: Yes

Tags

The tags to apply to the resource during creation.

Type: Array of [Tag](#) objects

Required: No

Type

The type of the link.

Constraints: Maximum length of 128 characters. Cannot include the following characters: `| \ ^`

Type: String

Length Constraints: Minimum length of 0. Maximum length of 256.

Pattern: `[\s\S]*`

Required: No

Response Syntax

```
HTTP/1.1 200
Content-type: application/json

{
  "Link": {
    "Bandwidth": {
      "DownloadSpeed": number,
      "UploadSpeed": number
    },
    "CreatedAt": number,
    "Description": "string",
    "GlobalNetworkId": "string",
    "LinkArn": "string",
    "LinkId": "string",
```



```
  "Provider": "string",
  "SiteId": "string",
  "State": "string",
  "Tags": [
    {
      "Key": "string",
      "Value": "string"
    }
  ],
  "Type": "string"
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

[Link](#)

Information about the link.

Type: [Link](#) object

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

AccessDeniedException

You do not have sufficient access to perform this action.

HTTP Status Code: 403

ConflictException

There was a conflict processing the request. Updating or deleting the resource can cause an inconsistent state.

ResourceId

The ID of the resource.

ResourceType

The resource type.

HTTP Status Code: 409

InternalServerError

The request has failed due to an internal error.

RetryAfterSeconds

Indicates when to retry the request.

HTTP Status Code: 500

ResourceNotFoundException

The specified resource could not be found.

Context

The specified resource could not be found.

ResourceId

The ID of the resource.

ResourceType

The resource type.

HTTP Status Code: 404

ServiceQuotaExceededException

A service limit was exceeded.

LimitCode

The limit code.

Message

The error message.

ResourceId

The ID of the resource.

ResourceType

The resource type.

ServiceCode

The service code.

HTTP Status Code: 402

ThrottlingException

The request was denied due to request throttling.

RetryAfterSeconds

Indicates when to retry the request.

HTTP Status Code: 429

ValidationException

The input fails to satisfy the constraints.

Fields

The fields that caused the error, if applicable.

Reason

The reason for the error.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)

- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

CreateSite

Creates a new site in a global network.

Request Syntax

```
POST /global-networks/globalNetworkId/sites HTTP/1.1
Content-type: application/json
```

```
{
  "Description": "string",
  "Location": {
    "Address": "string",
    "Latitude": "string",
    "Longitude": "string"
  },
  "Tags": [
    {
      "Key": "string",
      "Value": "string"
    }
  ]
}
```

URI Request Parameters

The request uses the following URI parameters.

globalNetworkId

The ID of the global network.

Length Constraints: Minimum length of 0. Maximum length of 50.

Pattern: `[\s\S]*`

Required: Yes

Request Body

The request accepts the following data in JSON format.

Description

A description of your site.

Constraints: Maximum length of 256 characters.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 256.

Pattern: `[\s\S]*`

Required: No

Location

The site location. This information is used for visualization in the Network Manager console. If you specify the address, the latitude and longitude are automatically calculated.

- Address: The physical address of the site.
- Latitude: The latitude of the site.
- Longitude: The longitude of the site.

Type: [Location](#) object

Required: No

Tags

The tags to apply to the resource during creation.

Type: Array of [Tag](#) objects

Required: No

Response Syntax

```
HTTP/1.1 200
Content-type: application/json

{
```

```
"Site": {
  "CreatedAt": number,
  "Description": "string",
  "GlobalNetworkId": "string",
  "Location": {
    "Address": "string",
    "Latitude": "string",
    "Longitude": "string"
  },
  "SiteArn": "string",
  "SiteId": "string",
  "State": "string",
  "Tags": [
    {
      "Key": "string",
      "Value": "string"
    }
  ]
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

Site

Information about the site.

Type: [Site](#) object

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

AccessDeniedException

You do not have sufficient access to perform this action.

HTTP Status Code: 403

ConflictException

There was a conflict processing the request. Updating or deleting the resource can cause an inconsistent state.

ResourceId

The ID of the resource.

ResourceType

The resource type.

HTTP Status Code: 409

InternalServerErrorException

The request has failed due to an internal error.

RetryAfterSeconds

Indicates when to retry the request.

HTTP Status Code: 500

ResourceNotFoundException

The specified resource could not be found.

Context

The specified resource could not be found.

ResourceId

The ID of the resource.

ResourceType

The resource type.

HTTP Status Code: 404

ServiceQuotaExceededException

A service limit was exceeded.

LimitCode

The limit code.

Message

The error message.

ResourceId

The ID of the resource.

ResourceType

The resource type.

ServiceCode

The service code.

HTTP Status Code: 402

ThrottlingException

The request was denied due to request throttling.

RetryAfterSeconds

Indicates when to retry the request.

HTTP Status Code: 429

ValidationException

The input fails to satisfy the constraints.

Fields

The fields that caused the error, if applicable.

Reason

The reason for the error.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)

- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

CreateSiteToSiteVpnAttachment

Creates an Amazon Web Services site-to-site VPN attachment on an edge location of a core network.

Request Syntax

```
POST /site-to-site-vpn-attachments HTTP/1.1
```

```
Content-type: application/json
```

```
{
  "ClientToken": "string",
  "CoreNetworkId": "string",
  "Tags": [
    {
      "Key": "string",
      "Value": "string"
    }
  ],
  "VpnConnectionArn": "string"
}
```

URI Request Parameters

The request does not use any URI parameters.

Request Body

The request accepts the following data in JSON format.

ClientToken

The client token associated with the request.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 256.

Pattern: `[\s\S]*`

Required: No

CoreNetworkId

The ID of a core network where you're creating a site-to-site VPN attachment.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 50.

Pattern: `^core-network-([0-9a-f]{8,17})$`

Required: Yes

Tags

The tags associated with the request.

Type: Array of [Tag](#) objects

Required: No

VpnConnectionArn

The ARN identifying the VPN attachment.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 500.

Pattern: `^arn:[^:]{1,63}:ec2:[^:]{0,63}:[^:]{0,63}:vpn-connection\/vpn-[0-9a-f]{8,17}$`

Required: Yes

Response Syntax

```
HTTP/1.1 200
Content-type: application/json

{
  "SiteToSiteVpnAttachment": {
    "Attachment": {
      "AttachmentId": "string",
      "AttachmentPolicyRuleNumber": number,
      "AttachmentType": "string",
      "CoreNetworkArn": "string",
```

```
"CoreNetworkId": "string",
"CreatedAt": number,
"EdgeLocation": "string",
"EdgeLocations": [ "string" ],
"LastModificationErrors": [
  {
    "Code": "string",
    "Message": "string",
    "RequestId": "string",
    "ResourceArn": "string"
  }
],
"NetworkFunctionGroupName": "string",
"OwnerAccountId": "string",
"ProposedNetworkFunctionGroupChange": {
  "AttachmentPolicyRuleNumber": number,
  "NetworkFunctionGroupName": "string",
  "Tags": [
    {
      "Key": "string",
      "Value": "string"
    }
  ]
},
"ProposedSegmentChange": {
  "AttachmentPolicyRuleNumber": number,
  "SegmentName": "string",
  "Tags": [
    {
      "Key": "string",
      "Value": "string"
    }
  ]
},
"ResourceArn": "string",
"SegmentName": "string",
"State": "string",
"Tags": [
  {
    "Key": "string",
    "Value": "string"
  }
],
"UpdatedAt": number
```

```
    },  
    "VpnConnectionArn": "string"  
  }  
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

SiteToSiteVpnAttachment

Details about a site-to-site VPN attachment.

Type: [SiteToSiteVpnAttachment](#) object

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

AccessDeniedException

You do not have sufficient access to perform this action.

HTTP Status Code: 403

ConflictException

There was a conflict processing the request. Updating or deleting the resource can cause an inconsistent state.

ResourceId

The ID of the resource.

ResourceType

The resource type.

HTTP Status Code: 409

InternalServerError

The request has failed due to an internal error.

RetryAfterSeconds

Indicates when to retry the request.

HTTP Status Code: 500

ResourceNotFoundException

The specified resource could not be found.

Context

The specified resource could not be found.

ResourceId

The ID of the resource.

ResourceType

The resource type.

HTTP Status Code: 404

ThrottlingException

The request was denied due to request throttling.

RetryAfterSeconds

Indicates when to retry the request.

HTTP Status Code: 429

ValidationException

The input fails to satisfy the constraints.

Fields

The fields that caused the error, if applicable.

Reason

The reason for the error.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

CreateTransitGatewayPeering

Creates a transit gateway peering connection.

Request Syntax

```
POST /transit-gateway-peerings HTTP/1.1
Content-type: application/json
```

```
{
  "ClientToken": "string",
  "CoreNetworkId": "string",
  "Tags": [
    {
      "Key": "string",
      "Value": "string"
    }
  ],
  "TransitGatewayArn": "string"
}
```

URI Request Parameters

The request does not use any URI parameters.

Request Body

The request accepts the following data in JSON format.

ClientToken

The client token associated with the request.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 256.

Pattern: `[\s\S]*`

Required: No

CoreNetworkId

The ID of a core network.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 50.

Pattern: `^core-network-([0-9a-f]{8,17})$`

Required: Yes

Tags

The list of key-value tags associated with the request.

Type: Array of [Tag](#) objects

Required: No

TransitGatewayArn

The ARN of the transit gateway for the peering request.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 500.

Pattern: `[\s\S]*`

Required: Yes

Response Syntax

```
HTTP/1.1 200
Content-type: application/json

{
  "TransitGatewayPeering": {
    "Peering": {
      "CoreNetworkArn": "string",
      "CoreNetworkId": "string",
      "CreatedAt": number,
      "EdgeLocation": "string",
      "LastModificationErrors": [
```

```
{
  {
    "Code": "string",
    "Message": "string",
    "MissingPermissionsContext": {
      "MissingPermission": "string"
    },
    "RequestId": "string",
    "ResourceArn": "string"
  },
  "OwnerAccountId": "string",
  "PeeringId": "string",
  "PeeringType": "string",
  "ResourceArn": "string",
  "State": "string",
  "Tags": [
    {
      "Key": "string",
      "Value": "string"
    }
  ],
  "TransitGatewayArn": "string",
  "TransitGatewayPeeringAttachmentId": "string"
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

[TransitGatewayPeering](#)

Returns information about the transit gateway peering connection request.

Type: [TransitGatewayPeering](#) object

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

AccessDeniedException

You do not have sufficient access to perform this action.

HTTP Status Code: 403

ConflictException

There was a conflict processing the request. Updating or deleting the resource can cause an inconsistent state.

ResourceId

The ID of the resource.

ResourceType

The resource type.

HTTP Status Code: 409

InternalServerErrorException

The request has failed due to an internal error.

RetryAfterSeconds

Indicates when to retry the request.

HTTP Status Code: 500

ResourceNotFoundException

The specified resource could not be found.

Context

The specified resource could not be found.

ResourceId

The ID of the resource.

ResourceType

The resource type.

HTTP Status Code: 404

ThrottlingException

The request was denied due to request throttling.

RetryAfterSeconds

Indicates when to retry the request.

HTTP Status Code: 429

ValidationException

The input fails to satisfy the constraints.

Fields

The fields that caused the error, if applicable.

Reason

The reason for the error.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

CreateTransitGatewayRouteTableAttachment

Creates a transit gateway route table attachment.

Request Syntax

```
POST /transit-gateway-route-table-attachments HTTP/1.1
Content-type: application/json
```

```
{
  "ClientToken": "string",
  "PeeringId": "string",
  "Tags": [
    {
      "Key": "string",
      "Value": "string"
    }
  ],
  "TransitGatewayRouteTableArn": "string"
}
```

URI Request Parameters

The request does not use any URI parameters.

Request Body

The request accepts the following data in JSON format.

ClientToken

The client token associated with the request.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 256.

Pattern: `[\s\S]*`

Required: No

PeeringId

The ID of the peer for the

Type: String

Length Constraints: Minimum length of 0. Maximum length of 50.

Pattern: `^peering-([0-9a-f]{8,17})$`

Required: Yes

Tags

The list of key-value tags associated with the request.

Type: Array of [Tag](#) objects

Required: No

TransitGatewayRouteTableArn

The ARN of the transit gateway route table for the attachment request. For example, "TransitGatewayRouteTableArn": "arn:aws:ec2:us-west-2:123456789012:transit-gateway-route-table/tgw-rtb-9876543210123456".

Type: String

Length Constraints: Minimum length of 0. Maximum length of 500.

Pattern: `[\s\S]*`

Required: Yes

Response Syntax

```
HTTP/1.1 200
Content-type: application/json

{
  "TransitGatewayRouteTableAttachment": {
    "Attachment": {
      "AttachmentId": "string",
      "AttachmentPolicyRuleNumber": number,
      "AttachmentType": "string",
      "CoreNetworkArn": "string",
      "CoreNetworkId": "string",
      "CreatedAt": number,
```

```

    "EdgeLocation": "string",
    "EdgeLocations": [ "string" ],
    "LastModificationErrors": [
      {
        "Code": "string",
        "Message": "string",
        "RequestId": "string",
        "ResourceArn": "string"
      }
    ],
    "NetworkFunctionGroupName": "string",
    "OwnerAccountId": "string",
    "ProposedNetworkFunctionGroupChange": {
      "AttachmentPolicyRuleNumber": number,
      "NetworkFunctionGroupName": "string",
      "Tags": [
        {
          "Key": "string",
          "Value": "string"
        }
      ]
    },
    "ProposedSegmentChange": {
      "AttachmentPolicyRuleNumber": number,
      "SegmentName": "string",
      "Tags": [
        {
          "Key": "string",
          "Value": "string"
        }
      ]
    },
    "ResourceArn": "string",
    "SegmentName": "string",
    "State": "string",
    "Tags": [
      {
        "Key": "string",
        "Value": "string"
      }
    ],
    "UpdatedAt": number
  },
  "PeeringId": "string",

```



```
    "TransitGatewayRouteTableArn": "string"
  }
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

TransitGatewayRouteTableAttachment

The route table associated with the create transit gateway route table attachment request.

Type: [TransitGatewayRouteTableAttachment](#) object

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

AccessDeniedException

You do not have sufficient access to perform this action.

HTTP Status Code: 403

ConflictException

There was a conflict processing the request. Updating or deleting the resource can cause an inconsistent state.

ResourceId

The ID of the resource.

ResourceType

The resource type.

HTTP Status Code: 409

InternalServerError

The request has failed due to an internal error.

RetryAfterSeconds

Indicates when to retry the request.

HTTP Status Code: 500

ResourceNotFoundException

The specified resource could not be found.

Context

The specified resource could not be found.

ResourceId

The ID of the resource.

ResourceType

The resource type.

HTTP Status Code: 404

ThrottlingException

The request was denied due to request throttling.

RetryAfterSeconds

Indicates when to retry the request.

HTTP Status Code: 429

ValidationException

The input fails to satisfy the constraints.

Fields

The fields that caused the error, if applicable.

Reason

The reason for the error.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

CreateVpcAttachment

Creates a VPC attachment on an edge location of a core network.

Request Syntax

```
POST /vpc-attachments HTTP/1.1
Content-type: application/json
```

```
{
  "ClientToken": "string",
  "CoreNetworkId": "string",
  "Options": {
    "ApplianceModeSupport": boolean,
    "DnsSupport": boolean,
    "Ipv6Support": boolean,
    "SecurityGroupReferencingSupport": boolean
  },
  "SubnetArns": [ "string" ],
  "Tags": [
    {
      "Key": "string",
      "Value": "string"
    }
  ],
  "VpcArn": "string"
}
```

URI Request Parameters

The request does not use any URI parameters.

Request Body

The request accepts the following data in JSON format.

ClientToken

The client token associated with the request.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 256.

Pattern: `[\s\S]*`

Required: No

CoreNetworkId

The ID of a core network for the VPC attachment.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 50.

Pattern: `^core-network-([0-9a-f]{8,17})$`

Required: Yes

Options

Options for the VPC attachment.

Type: [VpcOptions](#) object

Required: No

SubnetArns

The subnet ARN of the VPC attachment.

Type: Array of strings

Length Constraints: Minimum length of 0. Maximum length of 500.

Pattern: `^arn:[^:]{1,63}:ec2:[^:]{0,63}:[^:]{0,63}:subnet\\/subnet-[0-9a-f]{8,17}$|^$`

Required: Yes

Tags

The key-value tags associated with the request.

Type: Array of [Tag](#) objects

Required: No

VpcArn

The ARN of the VPC.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 500.

Pattern: `^arn:[^:]{1,63}:ec2:[^:]{0,63}:[^:]{0,63}:vpc\/vpc-[0-9a-f]{8,17}$`

Required: Yes

Response Syntax

HTTP/1.1 200

Content-type: application/json

```
{
  "VpcAttachment": {
    "Attachment": {
      "AttachmentId": "string",
      "AttachmentPolicyRuleNumber": number,
      "AttachmentType": "string",
      "CoreNetworkArn": "string",
      "CoreNetworkId": "string",
      "CreatedAt": number,
      "EdgeLocation": "string",
      "EdgeLocations": [ "string" ],
      "LastModificationErrors": [
        {
          "Code": "string",
          "Message": "string",
          "RequestId": "string",
          "ResourceArn": "string"
        }
      ],
      "NetworkFunctionGroupName": "string",
      "OwnerAccountId": "string",
      "ProposedNetworkFunctionGroupChange": {
        "AttachmentPolicyRuleNumber": number,
        "NetworkFunctionGroupName": "string",

```

```

    "Tags": [
      {
        "Key": "string",
        "Value": "string"
      }
    ],
    "ProposedSegmentChange": {
      "AttachmentPolicyRuleNumber": number,
      "SegmentName": "string",
      "Tags": [
        {
          "Key": "string",
          "Value": "string"
        }
      ],
      "ResourceArn": "string",
      "SegmentName": "string",
      "State": "string",
      "Tags": [
        {
          "Key": "string",
          "Value": "string"
        }
      ],
      "UpdatedAt": number
    },
    "Options": {
      "ApplianceModeSupport": boolean,
      "DnsSupport": boolean,
      "Ipv6Support": boolean,
      "SecurityGroupReferencingSupport": boolean
    },
    "SubnetArns": [ "string" ]
  }
}

```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

VpcAttachment

Provides details about the VPC attachment.

Type: [VpcAttachment](#) object

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

AccessDeniedException

You do not have sufficient access to perform this action.

HTTP Status Code: 403

ConflictException

There was a conflict processing the request. Updating or deleting the resource can cause an inconsistent state.

ResourceId

The ID of the resource.

ResourceType

The resource type.

HTTP Status Code: 409

InternalServerErrorException

The request has failed due to an internal error.

RetryAfterSeconds

Indicates when to retry the request.

HTTP Status Code: 500

ResourceNotFoundException

The specified resource could not be found.

Context

The specified resource could not be found.

ResourceId

The ID of the resource.

ResourceType

The resource type.

HTTP Status Code: 404

ThrottlingException

The request was denied due to request throttling.

RetryAfterSeconds

Indicates when to retry the request.

HTTP Status Code: 429

ValidationException

The input fails to satisfy the constraints.

Fields

The fields that caused the error, if applicable.

Reason

The reason for the error.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)

- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

DeleteAttachment

Deletes an attachment. Supports all attachment types.

Request Syntax

```
DELETE /attachments/attachmentId HTTP/1.1
```

URI Request Parameters

The request uses the following URI parameters.

attachmentId

The ID of the attachment to delete.

Length Constraints: Minimum length of 0. Maximum length of 50.

Pattern: ^attachment-([0-9a-f]{8,17})\$

Required: Yes

Request Body

The request does not have a request body.

Response Syntax

```
HTTP/1.1 200
```

```
Content-type: application/json
```

```
{
  "Attachment": {
    "AttachmentId": "string",
    "AttachmentPolicyRuleNumber": number,
    "AttachmentType": "string",
    "CoreNetworkArn": "string",
    "CoreNetworkId": "string",
    "CreatedAt": number,
    "EdgeLocation": "string",
    "EdgeLocations": [ "string" ],
    "LastModificationErrors": [
```

```

    {
      "Code": "string",
      "Message": "string",
      "RequestId": "string",
      "ResourceArn": "string"
    }
  ],
  "NetworkFunctionGroupName": "string",
  "OwnerAccountId": "string",
  "ProposedNetworkFunctionGroupChange": {
    "AttachmentPolicyRuleNumber": number,
    "NetworkFunctionGroupName": "string",
    "Tags": [
      {
        "Key": "string",
        "Value": "string"
      }
    ]
  },
  "ProposedSegmentChange": {
    "AttachmentPolicyRuleNumber": number,
    "SegmentName": "string",
    "Tags": [
      {
        "Key": "string",
        "Value": "string"
      }
    ]
  },
  "ResourceArn": "string",
  "SegmentName": "string",
  "State": "string",
  "Tags": [
    {
      "Key": "string",
      "Value": "string"
    }
  ],
  "UpdatedAt": number
}

```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

Attachment

Information about the deleted attachment.

Type: [Attachment](#) object

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

AccessDeniedException

You do not have sufficient access to perform this action.

HTTP Status Code: 403

ConflictException

There was a conflict processing the request. Updating or deleting the resource can cause an inconsistent state.

ResourceId

The ID of the resource.

ResourceType

The resource type.

HTTP Status Code: 409

InternalServerError

The request has failed due to an internal error.

RetryAfterSeconds

Indicates when to retry the request.

HTTP Status Code: 500

ResourceNotFoundException

The specified resource could not be found.

Context

The specified resource could not be found.

ResourceId

The ID of the resource.

ResourceType

The resource type.

HTTP Status Code: 404

ThrottlingException

The request was denied due to request throttling.

RetryAfterSeconds

Indicates when to retry the request.

HTTP Status Code: 429

ValidationException

The input fails to satisfy the constraints.

Fields

The fields that caused the error, if applicable.

Reason

The reason for the error.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

DeleteConnection

Deletes the specified connection in your global network.

Request Syntax

```
DELETE /global-networks/globalNetworkId/connections/connectionId HTTP/1.1
```

URI Request Parameters

The request uses the following URI parameters.

connectionId

The ID of the connection.

Length Constraints: Minimum length of 0. Maximum length of 50.

Pattern: `[\s\S]*`

Required: Yes

globalNetworkId

The ID of the global network.

Length Constraints: Minimum length of 0. Maximum length of 50.

Pattern: `[\s\S]*`

Required: Yes

Request Body

The request does not have a request body.

Response Syntax

```
HTTP/1.1 200  
Content-type: application/json
```



```
{
  "Connection": {
    "ConnectedDeviceId": "string",
    "ConnectedLinkId": "string",
    "ConnectionArn": "string",
    "ConnectionId": "string",
    "CreatedAt": number,
    "Description": "string",
    "DeviceId": "string",
    "GlobalNetworkId": "string",
    "LinkId": "string",
    "State": "string",
    "Tags": [
      {
        "Key": "string",
        "Value": "string"
      }
    ]
  }
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

Connection

Information about the connection.

Type: [Connection](#) object

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

AccessDeniedException

You do not have sufficient access to perform this action.

HTTP Status Code: 403

ConflictException

There was a conflict processing the request. Updating or deleting the resource can cause an inconsistent state.

ResourceId

The ID of the resource.

ResourceType

The resource type.

HTTP Status Code: 409

InternalServerErrorException

The request has failed due to an internal error.

RetryAfterSeconds

Indicates when to retry the request.

HTTP Status Code: 500

ResourceNotFoundException

The specified resource could not be found.

Context

The specified resource could not be found.

ResourceId

The ID of the resource.

ResourceType

The resource type.

HTTP Status Code: 404

ThrottlingException

The request was denied due to request throttling.

RetryAfterSeconds

Indicates when to retry the request.

HTTP Status Code: 429

ValidationException

The input fails to satisfy the constraints.

Fields

The fields that caused the error, if applicable.

Reason

The reason for the error.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

DeleteConnectPeer

Deletes a Connect peer.

Request Syntax

```
DELETE /connect-peers/connectPeerId HTTP/1.1
```

URI Request Parameters

The request uses the following URI parameters.

connectPeerId

The ID of the deleted Connect peer.

Length Constraints: Minimum length of 0. Maximum length of 50.

Pattern: `^connect-peer-([0-9a-f]{8,17})$`

Required: Yes

Request Body

The request does not have a request body.

Response Syntax

```
HTTP/1.1 200
Content-type: application/json

{
  "ConnectPeer": {
    "Configuration": {
      "BgpConfigurations": [
        {
          "CoreNetworkAddress": "string",
          "CoreNetworkAsn": number,
          "PeerAddress": "string",
```

```

        "PeerAsn": number
      }
    ],
    "CoreNetworkAddress": "string",
    "InsideCidrBlocks": [ "string" ],
    "PeerAddress": "string",
    "Protocol": "string"
  },
  "ConnectAttachmentId": "string",
  "ConnectPeerId": "string",
  "CoreNetworkId": "string",
  "CreatedAt": number,
  "EdgeLocation": "string",
  "LastModificationErrors": [
    {
      "Code": "string",
      "Message": "string",
      "RequestId": "string",
      "ResourceArn": "string"
    }
  ],
  "State": "string",
  "SubnetArn": "string",
  "Tags": [
    {
      "Key": "string",
      "Value": "string"
    }
  ]
}

```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

ConnectPeer

Information about the deleted Connect peer.

Type: ConnectPeer object

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

AccessDeniedException

You do not have sufficient access to perform this action.

HTTP Status Code: 403

ConflictException

There was a conflict processing the request. Updating or deleting the resource can cause an inconsistent state.

ResourceId

The ID of the resource.

ResourceType

The resource type.

HTTP Status Code: 409

InternalServerErrorException

The request has failed due to an internal error.

RetryAfterSeconds

Indicates when to retry the request.

HTTP Status Code: 500

ResourceNotFoundException

The specified resource could not be found.

Context

The specified resource could not be found.

ResourceId

The ID of the resource.

ResourceType

The resource type.

HTTP Status Code: 404

ThrottlingException

The request was denied due to request throttling.

RetryAfterSeconds

Indicates when to retry the request.

HTTP Status Code: 429

ValidationException

The input fails to satisfy the constraints.

Fields

The fields that caused the error, if applicable.

Reason

The reason for the error.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)

- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

DeleteCoreNetwork

Deletes a core network along with all core network policies. This can only be done if there are no attachments on a core network.

Request Syntax

```
DELETE /core-networks/coreNetworkId HTTP/1.1
```

URI Request Parameters

The request uses the following URI parameters.

coreNetworkId

The network ID of the deleted core network.

Length Constraints: Minimum length of 0. Maximum length of 50.

Pattern: `^core-network-([0-9a-f]{8,17})$`

Required: Yes

Request Body

The request does not have a request body.

Response Syntax

```
HTTP/1.1 200
Content-type: application/json

{
  "CoreNetwork": {
    "CoreNetworkArn": "string",
    "CoreNetworkId": "string",
    "CreatedAt": number,
    "Description": "string",
    "Edges": [
```

```

    {
      "Asn": number,
      "EdgeLocation": "string",
      "InsideCidrBlocks": [ "string" ]
    }
  ],
  "GlobalNetworkId": "string",
  "NetworkFunctionGroups": [
    {
      "EdgeLocations": [ "string" ],
      "Name": "string",
      "Segments": {
        "SendTo": [ "string" ],
        "SendVia": [ "string" ]
      }
    }
  ],
  "Segments": [
    {
      "EdgeLocations": [ "string" ],
      "Name": "string",
      "SharedSegments": [ "string" ]
    }
  ],
  "State": "string",
  "Tags": [
    {
      "Key": "string",
      "Value": "string"
    }
  ]
}

```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

CoreNetwork

Information about the deleted core network.

Type: [CoreNetwork](#) object

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

AccessDeniedException

You do not have sufficient access to perform this action.

HTTP Status Code: 403

ConflictException

There was a conflict processing the request. Updating or deleting the resource can cause an inconsistent state.

ResourceId

The ID of the resource.

ResourceType

The resource type.

HTTP Status Code: 409

InternalServerError

The request has failed due to an internal error.

RetryAfterSeconds

Indicates when to retry the request.

HTTP Status Code: 500

ResourceNotFoundException

The specified resource could not be found.

Context

The specified resource could not be found.

ResourceId

The ID of the resource.

ResourceType

The resource type.

HTTP Status Code: 404

ThrottlingException

The request was denied due to request throttling.

RetryAfterSeconds

Indicates when to retry the request.

HTTP Status Code: 429

ValidationException

The input fails to satisfy the constraints.

Fields

The fields that caused the error, if applicable.

Reason

The reason for the error.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)

- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

DeleteCoreNetworkPolicyVersion

Deletes a policy version from a core network. You can't delete the current LIVE policy.

Request Syntax

```
DELETE /core-networks/coreNetworkId/core-network-policy-versions/policyVersionId
HTTP/1.1
```

URI Request Parameters

The request uses the following URI parameters.

coreNetworkId

The ID of a core network for the deleted policy.

Length Constraints: Minimum length of 0. Maximum length of 50.

Pattern: `^core-network-([0-9a-f]{8,17})$`

Required: Yes

policyVersionId

The version ID of the deleted policy.

Required: Yes

Request Body

The request does not have a request body.

Response Syntax

```
HTTP/1.1 200
Content-type: application/json

{
  "CoreNetworkPolicy": {
```

```
"Alias": "string",
"ChangeSetState": "string",
"CoreNetworkId": "string",
"CreatedAt": number,
"Description": "string",
"PolicyDocument": "string",
"PolicyErrors": [
  {
    "ErrorCode": "string",
    "Message": "string",
    "Path": "string"
  }
],
"PolicyVersionId": number
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

CoreNetworkPolicy

Returns information about the deleted policy version.

Type: [CoreNetworkPolicy](#) object

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

AccessDeniedException

You do not have sufficient access to perform this action.

HTTP Status Code: 403

ConflictException

There was a conflict processing the request. Updating or deleting the resource can cause an inconsistent state.

ResourceId

The ID of the resource.

ResourceType

The resource type.

HTTP Status Code: 409

InternalServerError

The request has failed due to an internal error.

RetryAfterSeconds

Indicates when to retry the request.

HTTP Status Code: 500

ResourceNotFoundException

The specified resource could not be found.

Context

The specified resource could not be found.

ResourceId

The ID of the resource.

ResourceType

The resource type.

HTTP Status Code: 404

ThrottlingException

The request was denied due to request throttling.

RetryAfterSeconds

Indicates when to retry the request.

HTTP Status Code: 429

ValidationException

The input fails to satisfy the constraints.

Fields

The fields that caused the error, if applicable.

Reason

The reason for the error.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

DeleteDevice

Deletes an existing device. You must first disassociate the device from any links and customer gateways.

Request Syntax

```
DELETE /global-networks/globalNetworkId/devices/deviceId HTTP/1.1
```

URI Request Parameters

The request uses the following URI parameters.

deviceId

The ID of the device.

Length Constraints: Minimum length of 0. Maximum length of 50.

Pattern: `[\s\S]*`

Required: Yes

globalNetworkId

The ID of the global network.

Length Constraints: Minimum length of 0. Maximum length of 50.

Pattern: `[\s\S]*`

Required: Yes

Request Body

The request does not have a request body.

Response Syntax

```
HTTP/1.1 200  
Content-type: application/json
```

```
{
  "Device": {
    "AWSLocation": {
      "SubnetArn": "string",
      "Zone": "string"
    },
    "CreatedAt": number,
    "Description": "string",
    "DeviceArn": "string",
    "DeviceId": "string",
    "GlobalNetworkId": "string",
    "Location": {
      "Address": "string",
      "Latitude": "string",
      "Longitude": "string"
    },
    "Model": "string",
    "SerialNumber": "string",
    "SiteId": "string",
    "State": "string",
    "Tags": [
      {
        "Key": "string",
        "Value": "string"
      }
    ],
    "Type": "string",
    "Vendor": "string"
  }
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

Device

Information about the device.

Type: Device object

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

AccessDeniedException

You do not have sufficient access to perform this action.

HTTP Status Code: 403

ConflictException

There was a conflict processing the request. Updating or deleting the resource can cause an inconsistent state.

ResourceId

The ID of the resource.

ResourceType

The resource type.

HTTP Status Code: 409

InternalServerError

The request has failed due to an internal error.

RetryAfterSeconds

Indicates when to retry the request.

HTTP Status Code: 500

ResourceNotFoundException

The specified resource could not be found.

Context

The specified resource could not be found.

ResourceId

The ID of the resource.

ResourceType

The resource type.

HTTP Status Code: 404

ThrottlingException

The request was denied due to request throttling.

RetryAfterSeconds

Indicates when to retry the request.

HTTP Status Code: 429

ValidationException

The input fails to satisfy the constraints.

Fields

The fields that caused the error, if applicable.

Reason

The reason for the error.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)

- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

DeleteGlobalNetwork

Deletes an existing global network. You must first delete all global network objects (devices, links, and sites), deregister all transit gateways, and delete any core networks.

Request Syntax

```
DELETE /global-networks/globalNetworkId HTTP/1.1
```

URI Request Parameters

The request uses the following URI parameters.

globalNetworkId

The ID of the global network.

Length Constraints: Minimum length of 0. Maximum length of 50.

Pattern: `[\s\S]*`

Required: Yes

Request Body

The request does not have a request body.

Response Syntax

```
HTTP/1.1 200
Content-type: application/json

{
  "GlobalNetwork": {
    "CreatedAt": number,
    "Description": "string",
    "GlobalNetworkArn": "string",
    "GlobalNetworkId": "string",
    "State": "string",
    "Tags": [
```

```
{
  {
    "Key": "string",
    "Value": "string"
  }
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

GlobalNetwork

Information about the global network.

Type: [GlobalNetwork](#) object

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

AccessDeniedException

You do not have sufficient access to perform this action.

HTTP Status Code: 403

ConflictException

There was a conflict processing the request. Updating or deleting the resource can cause an inconsistent state.

ResourceId

The ID of the resource.

ResourceType

The resource type.

HTTP Status Code: 409

InternalServerErrorException

The request has failed due to an internal error.

RetryAfterSeconds

Indicates when to retry the request.

HTTP Status Code: 500

ResourceNotFoundException

The specified resource could not be found.

Context

The specified resource could not be found.

ResourceId

The ID of the resource.

ResourceType

The resource type.

HTTP Status Code: 404

ThrottlingException

The request was denied due to request throttling.

RetryAfterSeconds

Indicates when to retry the request.

HTTP Status Code: 429

ValidationException

The input fails to satisfy the constraints.

Fields

The fields that caused the error, if applicable.

Reason

The reason for the error.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

DeleteLink

Deletes an existing link. You must first disassociate the link from any devices and customer gateways.

Request Syntax

```
DELETE /global-networks/globalNetworkId/links/linkId HTTP/1.1
```

URI Request Parameters

The request uses the following URI parameters.

globalNetworkId

The ID of the global network.

Length Constraints: Minimum length of 0. Maximum length of 50.

Pattern: `[\s\S]*`

Required: Yes

linkId

The ID of the link.

Length Constraints: Minimum length of 0. Maximum length of 50.

Pattern: `[\s\S]*`

Required: Yes

Request Body

The request does not have a request body.

Response Syntax

```
HTTP/1.1 200  
Content-type: application/json
```

```
{
  "Link": {
    "Bandwidth": {
      "DownloadSpeed": number,
      "UploadSpeed": number
    },
    "CreatedAt": number,
    "Description": "string",
    "GlobalNetworkId": "string",
    "LinkArn": "string",
    "LinkId": "string",
    "Provider": "string",
    "SiteId": "string",
    "State": "string",
    "Tags": [
      {
        "Key": "string",
        "Value": "string"
      }
    ],
    "Type": "string"
  }
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

[Link](#)

Information about the link.

Type: [Link](#) object

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

AccessDeniedException

You do not have sufficient access to perform this action.

HTTP Status Code: 403

ConflictException

There was a conflict processing the request. Updating or deleting the resource can cause an inconsistent state.

ResourceId

The ID of the resource.

ResourceType

The resource type.

HTTP Status Code: 409

InternalServerErrorException

The request has failed due to an internal error.

RetryAfterSeconds

Indicates when to retry the request.

HTTP Status Code: 500

ResourceNotFoundException

The specified resource could not be found.

Context

The specified resource could not be found.

ResourceId

The ID of the resource.

ResourceType

The resource type.

HTTP Status Code: 404

ThrottlingException

The request was denied due to request throttling.

RetryAfterSeconds

Indicates when to retry the request.

HTTP Status Code: 429

ValidationException

The input fails to satisfy the constraints.

Fields

The fields that caused the error, if applicable.

Reason

The reason for the error.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

DeletePeering

Deletes an existing peering connection.

Request Syntax

```
DELETE /peerings/peeringId HTTP/1.1
```

URI Request Parameters

The request uses the following URI parameters.

peeringId

The ID of the peering connection to delete.

Length Constraints: Minimum length of 0. Maximum length of 50.

Pattern: `^peering-([0-9a-f]{8,17})$`

Required: Yes

Request Body

The request does not have a request body.

Response Syntax

```
HTTP/1.1 200
```

```
Content-type: application/json
```

```
{
  "Peering": {
    "CoreNetworkArn": "string",
    "CoreNetworkId": "string",
    "CreatedAt": number,
    "EdgeLocation": "string",
    "LastModificationErrors": [
      {
        "Code": "string",
        "Message": "string",
```

```
    "MissingPermissionsContext": {
      "MissingPermission": "string"
    },
    "RequestId": "string",
    "ResourceArn": "string"
  }
],
"OwnerAccountId": "string",
"PeeringId": "string",
"PeeringType": "string",
"ResourceArn": "string",
"State": "string",
"Tags": [
  {
    "Key": "string",
    "Value": "string"
  }
]
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

[Peering](#)

Information about a deleted peering connection.

Type: [Peering](#) object

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

AccessDeniedException

You do not have sufficient access to perform this action.

HTTP Status Code: 403

ConflictException

There was a conflict processing the request. Updating or deleting the resource can cause an inconsistent state.

ResourceId

The ID of the resource.

ResourceType

The resource type.

HTTP Status Code: 409

InternalServerErrorException

The request has failed due to an internal error.

RetryAfterSeconds

Indicates when to retry the request.

HTTP Status Code: 500

ResourceNotFoundException

The specified resource could not be found.

Context

The specified resource could not be found.

ResourceId

The ID of the resource.

ResourceType

The resource type.

HTTP Status Code: 404

ThrottlingException

The request was denied due to request throttling.

RetryAfterSeconds

Indicates when to retry the request.

HTTP Status Code: 429

ValidationException

The input fails to satisfy the constraints.

Fields

The fields that caused the error, if applicable.

Reason

The reason for the error.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

DeleteResourcePolicy

Deletes a resource policy for the specified resource. This revokes the access of the principals specified in the resource policy.

Request Syntax

```
DELETE /resource-policy/resourceArn HTTP/1.1
```

URI Request Parameters

The request uses the following URI parameters.

resourceArn

The ARN of the policy to delete.

Length Constraints: Minimum length of 0. Maximum length of 1500.

Pattern: `[\s\S]*`

Required: Yes

Request Body

The request does not have a request body.

Response Syntax

```
HTTP/1.1 200
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response with an empty HTTP body.

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

AccessDeniedException

You do not have sufficient access to perform this action.

HTTP Status Code: 403

ConflictException

There was a conflict processing the request. Updating or deleting the resource can cause an inconsistent state.

ResourceId

The ID of the resource.

ResourceType

The resource type.

HTTP Status Code: 409

InternalServerError

The request has failed due to an internal error.

RetryAfterSeconds

Indicates when to retry the request.

HTTP Status Code: 500

ThrottlingException

The request was denied due to request throttling.

RetryAfterSeconds

Indicates when to retry the request.

HTTP Status Code: 429

ValidationException

The input fails to satisfy the constraints.

Fields

The fields that caused the error, if applicable.

Reason

The reason for the error.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

DeleteSite

Deletes an existing site. The site cannot be associated with any device or link.

Request Syntax

```
DELETE /global-networks/globalNetworkId/sites/siteId HTTP/1.1
```

URI Request Parameters

The request uses the following URI parameters.

globalNetworkId

The ID of the global network.

Length Constraints: Minimum length of 0. Maximum length of 50.

Pattern: `[\s\S]*`

Required: Yes

siteId

The ID of the site.

Length Constraints: Minimum length of 0. Maximum length of 50.

Pattern: `[\s\S]*`

Required: Yes

Request Body

The request does not have a request body.

Response Syntax

```
HTTP/1.1 200  
Content-type: application/json
```

```
{
  "Site": {
    "CreatedAt": number,
    "Description": "string",
    "GlobalNetworkId": "string",
    "Location": {
      "Address": "string",
      "Latitude": "string",
      "Longitude": "string"
    },
    "SiteArn": "string",
    "SiteId": "string",
    "State": "string",
    "Tags": [
      {
        "Key": "string",
        "Value": "string"
      }
    ]
  }
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

[Site](#)

Information about the site.

Type: [Site](#) object

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

AccessDeniedException

You do not have sufficient access to perform this action.

HTTP Status Code: 403

ConflictException

There was a conflict processing the request. Updating or deleting the resource can cause an inconsistent state.

ResourceId

The ID of the resource.

ResourceType

The resource type.

HTTP Status Code: 409

InternalServerErrorException

The request has failed due to an internal error.

RetryAfterSeconds

Indicates when to retry the request.

HTTP Status Code: 500

ResourceNotFoundException

The specified resource could not be found.

Context

The specified resource could not be found.

ResourceId

The ID of the resource.

ResourceType

The resource type.

HTTP Status Code: 404

ThrottlingException

The request was denied due to request throttling.

RetryAfterSeconds

Indicates when to retry the request.

HTTP Status Code: 429

ValidationException

The input fails to satisfy the constraints.

Fields

The fields that caused the error, if applicable.

Reason

The reason for the error.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

DeregisterTransitGateway

Deregisters a transit gateway from your global network. This action does not delete your transit gateway, or modify any of its attachments. This action removes any customer gateway associations.

Request Syntax

```
DELETE /global-networks/globalNetworkId/transit-gateway-registrations/transitGatewayArn
HTTP/1.1
```

URI Request Parameters

The request uses the following URI parameters.

globalNetworkId

The ID of the global network.

Length Constraints: Minimum length of 0. Maximum length of 50.

Pattern: `[\s\S]*`

Required: Yes

transitGatewayArn

The Amazon Resource Name (ARN) of the transit gateway.

Length Constraints: Minimum length of 0. Maximum length of 500.

Pattern: `[\s\S]*`

Required: Yes

Request Body

The request does not have a request body.

Response Syntax

```
HTTP/1.1 200
```

```
Content-type: application/json

{
  "TransitGatewayRegistration": {
    "GlobalNetworkId": "string",
    "State": {
      "Code": "string",
      "Message": "string"
    },
    "TransitGatewayArn": "string"
  }
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

[TransitGatewayRegistration](#)

The transit gateway registration information.

Type: [TransitGatewayRegistration](#) object

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

AccessDeniedException

You do not have sufficient access to perform this action.

HTTP Status Code: 403

ConflictException

There was a conflict processing the request. Updating or deleting the resource can cause an inconsistent state.

ResourceId

The ID of the resource.

ResourceType

The resource type.

HTTP Status Code: 409

InternalServerError

The request has failed due to an internal error.

RetryAfterSeconds

Indicates when to retry the request.

HTTP Status Code: 500

ResourceNotFoundException

The specified resource could not be found.

Context

The specified resource could not be found.

ResourceId

The ID of the resource.

ResourceType

The resource type.

HTTP Status Code: 404

ThrottlingException

The request was denied due to request throttling.

RetryAfterSeconds

Indicates when to retry the request.

HTTP Status Code: 429

ValidationException

The input fails to satisfy the constraints.

Fields

The fields that caused the error, if applicable.

Reason

The reason for the error.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

DescribeGlobalNetworks

Describes one or more global networks. By default, all global networks are described. To describe the objects in your global network, you must use the appropriate Get * action. For example, to list the transit gateways in your global network, use [GetTransitGatewayRegistrations](#).

Request Syntax

```
GET /global-networks?
globalNetworkIds=GlobalNetworkIds&maxResults=MaxResults&nextToken=NextToken HTTP/1.1
```

URI Request Parameters

The request uses the following URI parameters.

[GlobalNetworkIds](#)

The IDs of one or more global networks. The maximum is 10.

Length Constraints: Minimum length of 0. Maximum length of 50.

Pattern: `[\s\S]*`

[MaxResults](#)

The maximum number of results to return.

Valid Range: Minimum value of 1. Maximum value of 500.

[NextToken](#)

The token for the next page of results.

Length Constraints: Minimum length of 0. Maximum length of 2048.

Pattern: `[\s\S]*`

Request Body

The request does not have a request body.

Response Syntax

```
HTTP/1.1 200
Content-type: application/json

{
  "GlobalNetworks": [
    {
      "CreatedAt": number,
      "Description": "string",
      "GlobalNetworkArn": "string",
      "GlobalNetworkId": "string",
      "State": "string",
      "Tags": [
        {
          "Key": "string",
          "Value": "string"
        }
      ]
    }
  ],
  "NextToken": "string"
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

GlobalNetworks

Information about the global networks.

Type: Array of [GlobalNetwork](#) objects

NextToken

The token for the next page of results.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 2048.

Pattern: `[\s\S]*`

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

AccessDeniedException

You do not have sufficient access to perform this action.

HTTP Status Code: 403

InternalServerError

The request has failed due to an internal error.

RetryAfterSeconds

Indicates when to retry the request.

HTTP Status Code: 500

ResourceNotFoundException

The specified resource could not be found.

Context

The specified resource could not be found.

ResourceId

The ID of the resource.

ResourceType

The resource type.

HTTP Status Code: 404

ThrottlingException

The request was denied due to request throttling.

RetryAfterSeconds

Indicates when to retry the request.

HTTP Status Code: 429

ValidationException

The input fails to satisfy the constraints.

Fields

The fields that caused the error, if applicable.

Reason

The reason for the error.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

DisassociateConnectPeer

Disassociates a core network Connect peer from a device and a link.

Request Syntax

```
DELETE /global-networks/globalNetworkId/connect-peer-associations/connectPeerId
HTTP/1.1
```

URI Request Parameters

The request uses the following URI parameters.

connectPeerId

The ID of the Connect peer to disassociate from a device.

Length Constraints: Minimum length of 0. Maximum length of 50.

Pattern: ^connect-peer-([0-9a-f]{8,17})\$

Required: Yes

globalNetworkId

The ID of the global network.

Length Constraints: Minimum length of 0. Maximum length of 50.

Pattern: [\s\S]*

Required: Yes

Request Body

The request does not have a request body.

Response Syntax

```
HTTP/1.1 200
Content-type: application/json
```

```
{
  "ConnectPeerAssociation": {
    "ConnectPeerId": "string",
    "DeviceId": "string",
    "GlobalNetworkId": "string",
    "LinkId": "string",
    "State": "string"
  }
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

ConnectPeerAssociation

Describes the Connect peer association.

Type: [ConnectPeerAssociation](#) object

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

AccessDeniedException

You do not have sufficient access to perform this action.

HTTP Status Code: 403

ConflictException

There was a conflict processing the request. Updating or deleting the resource can cause an inconsistent state.

ResourceId

The ID of the resource.

ResourceType

The resource type.

HTTP Status Code: 409

InternalServerErrorException

The request has failed due to an internal error.

RetryAfterSeconds

Indicates when to retry the request.

HTTP Status Code: 500

ResourceNotFoundException

The specified resource could not be found.

Context

The specified resource could not be found.

ResourceId

The ID of the resource.

ResourceType

The resource type.

HTTP Status Code: 404

ThrottlingException

The request was denied due to request throttling.

RetryAfterSeconds

Indicates when to retry the request.

HTTP Status Code: 429

ValidationException

The input fails to satisfy the constraints.

Fields

The fields that caused the error, if applicable.

Reason

The reason for the error.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

DisassociateCustomerGateway

Disassociates a customer gateway from a device and a link.

Request Syntax

```
DELETE /global-networks/globalNetworkId/customer-gateway-associations/customerGatewayArn HTTP/1.1
```

URI Request Parameters

The request uses the following URI parameters.

customerGatewayArn

The Amazon Resource Name (ARN) of the customer gateway.

Length Constraints: Minimum length of 0. Maximum length of 500.

Pattern: `[\s\S]*`

Required: Yes

globalNetworkId

The ID of the global network.

Length Constraints: Minimum length of 0. Maximum length of 50.

Pattern: `[\s\S]*`

Required: Yes

Request Body

The request does not have a request body.

Response Syntax

```
HTTP/1.1 200  
Content-type: application/json
```

```
{
  "CustomerGatewayAssociation": {
    "CustomerGatewayArn": "string",
    "DeviceId": "string",
    "GlobalNetworkId": "string",
    "LinkId": "string",
    "State": "string"
  }
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

CustomerGatewayAssociation

Information about the customer gateway association.

Type: [CustomerGatewayAssociation](#) object

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

AccessDeniedException

You do not have sufficient access to perform this action.

HTTP Status Code: 403

ConflictException

There was a conflict processing the request. Updating or deleting the resource can cause an inconsistent state.

ResourceId

The ID of the resource.

ResourceType

The resource type.

HTTP Status Code: 409

InternalServerErrorException

The request has failed due to an internal error.

RetryAfterSeconds

Indicates when to retry the request.

HTTP Status Code: 500

ResourceNotFoundException

The specified resource could not be found.

Context

The specified resource could not be found.

ResourceId

The ID of the resource.

ResourceType

The resource type.

HTTP Status Code: 404

ThrottlingException

The request was denied due to request throttling.

RetryAfterSeconds

Indicates when to retry the request.

HTTP Status Code: 429

ValidationException

The input fails to satisfy the constraints.

Fields

The fields that caused the error, if applicable.

Reason

The reason for the error.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

DisassociateLink

Disassociates an existing device from a link. You must first disassociate any customer gateways that are associated with the link.

Request Syntax

```
DELETE /global-networks/globalNetworkId/link-associations?  
deviceId=DeviceId&linkId=LinkId HTTP/1.1
```

URI Request Parameters

The request uses the following URI parameters.

DeviceId

The ID of the device.

Length Constraints: Minimum length of 0. Maximum length of 50.

Pattern: `[\s\S]*`

Required: Yes

globalNetworkId

The ID of the global network.

Length Constraints: Minimum length of 0. Maximum length of 50.

Pattern: `[\s\S]*`

Required: Yes

LinkId

The ID of the link.

Length Constraints: Minimum length of 0. Maximum length of 50.

Pattern: `[\s\S]*`

Required: Yes

Request Body

The request does not have a request body.

Response Syntax

```
HTTP/1.1 200
Content-type: application/json

{
  "LinkAssociation": {
    "DeviceId": "string",
    "GlobalNetworkId": "string",
    "LinkAssociationState": "string",
    "LinkId": "string"
  }
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

LinkAssociation

Information about the link association.

Type: [LinkAssociation](#) object

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

AccessDeniedException

You do not have sufficient access to perform this action.

HTTP Status Code: 403

ConflictException

There was a conflict processing the request. Updating or deleting the resource can cause an inconsistent state.

ResourceId

The ID of the resource.

ResourceType

The resource type.

HTTP Status Code: 409

InternalServerErrorException

The request has failed due to an internal error.

RetryAfterSeconds

Indicates when to retry the request.

HTTP Status Code: 500

ResourceNotFoundException

The specified resource could not be found.

Context

The specified resource could not be found.

ResourceId

The ID of the resource.

ResourceType

The resource type.

HTTP Status Code: 404

ThrottlingException

The request was denied due to request throttling.

RetryAfterSeconds

Indicates when to retry the request.

HTTP Status Code: 429

ValidationException

The input fails to satisfy the constraints.

Fields

The fields that caused the error, if applicable.

Reason

The reason for the error.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

DisassociateTransitGatewayConnectPeer

Disassociates a transit gateway Connect peer from a device and link.

Request Syntax

```
DELETE /global-networks/globalNetworkId/transit-gateway-connect-peer-associations/transitGatewayConnectPeerArn HTTP/1.1
```

URI Request Parameters

The request uses the following URI parameters.

globalNetworkId

The ID of the global network.

Length Constraints: Minimum length of 0. Maximum length of 50.

Pattern: `[\s\S]*`

Required: Yes

transitGatewayConnectPeerArn

The Amazon Resource Name (ARN) of the transit gateway Connect peer.

Length Constraints: Minimum length of 0. Maximum length of 500.

Pattern: `[\s\S]*`

Required: Yes

Request Body

The request does not have a request body.

Response Syntax

```
HTTP/1.1 200  
Content-type: application/json
```

```
{
  "TransitGatewayConnectPeerAssociation": {
    "DeviceId": "string",
    "GlobalNetworkId": "string",
    "LinkId": "string",
    "State": "string",
    "TransitGatewayConnectPeerArn": "string"
  }
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

TransitGatewayConnectPeerAssociation

The transit gateway Connect peer association.

Type: [TransitGatewayConnectPeerAssociation](#) object

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

AccessDeniedException

You do not have sufficient access to perform this action.

HTTP Status Code: 403

ConflictException

There was a conflict processing the request. Updating or deleting the resource can cause an inconsistent state.

ResourceId

The ID of the resource.

ResourceType

The resource type.

HTTP Status Code: 409

InternalServerErrorException

The request has failed due to an internal error.

RetryAfterSeconds

Indicates when to retry the request.

HTTP Status Code: 500

ResourceNotFoundException

The specified resource could not be found.

Context

The specified resource could not be found.

ResourceId

The ID of the resource.

ResourceType

The resource type.

HTTP Status Code: 404

ThrottlingException

The request was denied due to request throttling.

RetryAfterSeconds

Indicates when to retry the request.

HTTP Status Code: 429

ValidationException

The input fails to satisfy the constraints.

Fields

The fields that caused the error, if applicable.

Reason

The reason for the error.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

ExecuteCoreNetworkChangeSet

Executes a change set on your core network. Deploys changes globally based on the policy submitted..

Request Syntax

```
POST /core-networks/coreNetworkId/core-network-change-sets/policyVersionId/execute
HTTP/1.1
```

URI Request Parameters

The request uses the following URI parameters.

coreNetworkId

The ID of a core network.

Length Constraints: Minimum length of 0. Maximum length of 50.

Pattern: `^core-network-([0-9a-f]{8,17})$`

Required: Yes

policyVersionId

The ID of the policy version.

Required: Yes

Request Body

The request does not have a request body.

Response Syntax

```
HTTP/1.1 200
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response with an empty HTTP body.

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

AccessDeniedException

You do not have sufficient access to perform this action.

HTTP Status Code: 403

ConflictException

There was a conflict processing the request. Updating or deleting the resource can cause an inconsistent state.

ResourceId

The ID of the resource.

ResourceType

The resource type.

HTTP Status Code: 409

InternalServerError

The request has failed due to an internal error.

RetryAfterSeconds

Indicates when to retry the request.

HTTP Status Code: 500

ResourceNotFoundException

The specified resource could not be found.

Context

The specified resource could not be found.

ResourceId

The ID of the resource.

ResourceType

The resource type.

HTTP Status Code: 404

ThrottlingException

The request was denied due to request throttling.

RetryAfterSeconds

Indicates when to retry the request.

HTTP Status Code: 429

ValidationException

The input fails to satisfy the constraints.

Fields

The fields that caused the error, if applicable.

Reason

The reason for the error.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)

- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

GetConnectAttachment

Returns information about a core network Connect attachment.

Request Syntax

```
GET /connect-attachments/attachmentId HTTP/1.1
```

URI Request Parameters

The request uses the following URI parameters.

attachmentId

The ID of the attachment.

Length Constraints: Minimum length of 0. Maximum length of 50.

Pattern: ^attachment-([0-9a-f]{8,17})\$

Required: Yes

Request Body

The request does not have a request body.

Response Syntax

```
HTTP/1.1 200
Content-type: application/json

{
  "ConnectAttachment": {
    "Attachment": {
      "AttachmentId": "string",
      "AttachmentPolicyRuleNumber": number,
      "AttachmentType": "string",
      "CoreNetworkArn": "string",
      "CoreNetworkId": "string",
      "CreatedAt": number,
      "EdgeLocation": "string",
      "EdgeLocations": [ "string" ],
```

```
    "LastModificationErrors": [
      {
        "Code": "string",
        "Message": "string",
        "RequestId": "string",
        "ResourceArn": "string"
      }
    ],
    "NetworkFunctionGroupName": "string",
    "OwnerAccountId": "string",
    "ProposedNetworkFunctionGroupChange": {
      "AttachmentPolicyRuleNumber": number,
      "NetworkFunctionGroupName": "string",
      "Tags": [
        {
          "Key": "string",
          "Value": "string"
        }
      ]
    },
    "ProposedSegmentChange": {
      "AttachmentPolicyRuleNumber": number,
      "SegmentName": "string",
      "Tags": [
        {
          "Key": "string",
          "Value": "string"
        }
      ]
    },
    "ResourceArn": "string",
    "SegmentName": "string",
    "State": "string",
    "Tags": [
      {
        "Key": "string",
        "Value": "string"
      }
    ],
    "UpdatedAt": number
  },
  "Options": {
    "Protocol": "string"
  },
}
```

```
    "TransportAttachmentId": "string"  
  }  
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

[ConnectAttachment](#)

Details about the Connect attachment.

Type: [ConnectAttachment](#) object

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

AccessDeniedException

You do not have sufficient access to perform this action.

HTTP Status Code: 403

InternalServerError

The request has failed due to an internal error.

RetryAfterSeconds

Indicates when to retry the request.

HTTP Status Code: 500

ResourceNotFoundException

The specified resource could not be found.

Context

The specified resource could not be found.

ResourceId

The ID of the resource.

ResourceType

The resource type.

HTTP Status Code: 404

ThrottlingException

The request was denied due to request throttling.

RetryAfterSeconds

Indicates when to retry the request.

HTTP Status Code: 429

ValidationException

The input fails to satisfy the constraints.

Fields

The fields that caused the error, if applicable.

Reason

The reason for the error.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)

- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

GetConnections

Gets information about one or more of your connections in a global network.

Request Syntax

```
GET /global-networks/globalNetworkId/connections?  
connectionIds=ConnectionIds&deviceId=DeviceId&maxResults=MaxResults&nextToken=NextToken  
HTTP/1.1
```

URI Request Parameters

The request uses the following URI parameters.

ConnectionIds

One or more connection IDs.

Length Constraints: Minimum length of 0. Maximum length of 50.

Pattern: `[\s\S]*`

DeviceId

The ID of the device.

Length Constraints: Minimum length of 0. Maximum length of 50.

Pattern: `[\s\S]*`

globalNetworkId

The ID of the global network.

Length Constraints: Minimum length of 0. Maximum length of 50.

Pattern: `[\s\S]*`

Required: Yes

MaxResults

The maximum number of results to return.

Valid Range: Minimum value of 1. Maximum value of 500.

NextToken

The token for the next page of results.

Length Constraints: Minimum length of 0. Maximum length of 2048.

Pattern: `[\s\S]*`

Request Body

The request does not have a request body.

Response Syntax

```
HTTP/1.1 200
Content-type: application/json

{
  "Connections": [
    {
      "ConnectedDeviceId": "string",
      "ConnectedLinkId": "string",
      "ConnectionArn": "string",
      "ConnectionId": "string",
      "CreatedAt": number,
      "Description": "string",
      "DeviceId": "string",
      "GlobalNetworkId": "string",
      "LinkId": "string",
      "State": "string",
      "Tags": [
        {
          "Key": "string",
          "Value": "string"
        }
      ]
    }
  ],
  "NextToken": "string"
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

Connections

Information about the connections.

Type: Array of [Connection](#) objects

NextToken

The token to use for the next page of results.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 2048.

Pattern: `[\s\S]*`

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

AccessDeniedException

You do not have sufficient access to perform this action.

HTTP Status Code: 403

InternalServerError

The request has failed due to an internal error.

RetryAfterSeconds

Indicates when to retry the request.

HTTP Status Code: 500

ResourceNotFoundException

The specified resource could not be found.

Context

The specified resource could not be found.

ResourceId

The ID of the resource.

ResourceType

The resource type.

HTTP Status Code: 404

ThrottlingException

The request was denied due to request throttling.

RetryAfterSeconds

Indicates when to retry the request.

HTTP Status Code: 429

ValidationException

The input fails to satisfy the constraints.

Fields

The fields that caused the error, if applicable.

Reason

The reason for the error.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)

- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

GetConnectPeer

Returns information about a core network Connect peer.

Request Syntax

```
GET /connect-peers/connectPeerId HTTP/1.1
```

URI Request Parameters

The request uses the following URI parameters.

connectPeerId

The ID of the Connect peer.

Length Constraints: Minimum length of 0. Maximum length of 50.

Pattern: `^connect-peer-([0-9a-f]{8,17})$`

Required: Yes

Request Body

The request does not have a request body.

Response Syntax

```
HTTP/1.1 200
Content-type: application/json

{
  "ConnectPeer": {
    "Configuration": {
      "BgpConfigurations": [
        {
          "CoreNetworkAddress": "string",
          "CoreNetworkAsn": number,
          "PeerAddress": "string",
```



```

        "PeerAsn": number
      }
    ],
    "CoreNetworkAddress": "string",
    "InsideCidrBlocks": [ "string" ],
    "PeerAddress": "string",
    "Protocol": "string"
  },
  "ConnectAttachmentId": "string",
  "ConnectPeerId": "string",
  "CoreNetworkId": "string",
  "CreatedAt": number,
  "EdgeLocation": "string",
  "LastModificationErrors": [
    {
      "Code": "string",
      "Message": "string",
      "RequestId": "string",
      "ResourceArn": "string"
    }
  ],
  "State": "string",
  "SubnetArn": "string",
  "Tags": [
    {
      "Key": "string",
      "Value": "string"
    }
  ]
}

```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

ConnectPeer

Returns information about a core network Connect peer.

Type: ConnectPeer object

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

AccessDeniedException

You do not have sufficient access to perform this action.

HTTP Status Code: 403

InternalServerError

The request has failed due to an internal error.

RetryAfterSeconds

Indicates when to retry the request.

HTTP Status Code: 500

ResourceNotFoundException

The specified resource could not be found.

Context

The specified resource could not be found.

ResourceId

The ID of the resource.

ResourceType

The resource type.

HTTP Status Code: 404

ThrottlingException

The request was denied due to request throttling.

RetryAfterSeconds

Indicates when to retry the request.

HTTP Status Code: 429

ValidationException

The input fails to satisfy the constraints.

Fields

The fields that caused the error, if applicable.

Reason

The reason for the error.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

GetConnectPeerAssociations

Returns information about a core network Connect peer associations.

Request Syntax

```
GET /global-networks/globalNetworkId/connect-peer-associations?  
connectPeerIds=ConnectPeerIds&maxResults=MaxResults&nextToken=NextToken HTTP/1.1
```

URI Request Parameters

The request uses the following URI parameters.

ConnectPeerIds

The IDs of the Connect peers.

Length Constraints: Minimum length of 0. Maximum length of 50.

Pattern: `^connect-peer-([0-9a-f]{8,17})$`

globalNetworkId

The ID of the global network.

Length Constraints: Minimum length of 0. Maximum length of 50.

Pattern: `[\s\S]*`

Required: Yes

MaxResults

The maximum number of results to return.

Valid Range: Minimum value of 1. Maximum value of 500.

NextToken

The token for the next page of results.

Length Constraints: Minimum length of 0. Maximum length of 2048.

Pattern: `[\s\S]*`

Request Body

The request does not have a request body.

Response Syntax

```
HTTP/1.1 200
Content-type: application/json

{
  "ConnectPeerAssociations": [
    {
      "ConnectPeerId": "string",
      "DeviceId": "string",
      "GlobalNetworkId": "string",
      "LinkId": "string",
      "State": "string"
    }
  ],
  "NextToken": "string"
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

ConnectPeerAssociations

Displays a list of Connect peer associations.

Type: Array of [ConnectPeerAssociation](#) objects

NextToken

The token for the next page of results.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 2048.

Pattern: `[\s\S]*`

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

AccessDeniedException

You do not have sufficient access to perform this action.

HTTP Status Code: 403

ConflictException

There was a conflict processing the request. Updating or deleting the resource can cause an inconsistent state.

ResourceId

The ID of the resource.

ResourceType

The resource type.

HTTP Status Code: 409

InternalServerError

The request has failed due to an internal error.

RetryAfterSeconds

Indicates when to retry the request.

HTTP Status Code: 500

ResourceNotFoundException

The specified resource could not be found.

Context

The specified resource could not be found.

ResourceId

The ID of the resource.

ResourceType

The resource type.

HTTP Status Code: 404

ThrottlingException

The request was denied due to request throttling.

RetryAfterSeconds

Indicates when to retry the request.

HTTP Status Code: 429

ValidationException

The input fails to satisfy the constraints.

Fields

The fields that caused the error, if applicable.

Reason

The reason for the error.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)

- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

GetCoreNetwork

Returns information about the LIVE policy for a core network.

Request Syntax

```
GET /core-networks/coreNetworkId HTTP/1.1
```

URI Request Parameters

The request uses the following URI parameters.

coreNetworkId

The ID of a core network.

Length Constraints: Minimum length of 0. Maximum length of 50.

Pattern: `^core-network-([0-9a-f]{8,17})$`

Required: Yes

Request Body

The request does not have a request body.

Response Syntax

```
HTTP/1.1 200
Content-type: application/json

{
  "CoreNetwork": {
    "CoreNetworkArn": "string",
    "CoreNetworkId": "string",
    "CreatedAt": number,
    "Description": "string",
    "Edges": [
      {
        "Asn": number,
```

```

        "EdgeLocation": "string",
        "InsideCidrBlocks": [ "string" ]
    },
    ],
    "GlobalNetworkId": "string",
    "NetworkFunctionGroups": [
        {
            "EdgeLocations": [ "string" ],
            "Name": "string",
            "Segments": {
                "SendTo": [ "string" ],
                "SendVia": [ "string" ]
            }
        }
    ],
    "Segments": [
        {
            "EdgeLocations": [ "string" ],
            "Name": "string",
            "SharedSegments": [ "string" ]
        }
    ],
    "State": "string",
    "Tags": [
        {
            "Key": "string",
            "Value": "string"
        }
    ]
}

```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

CoreNetwork

Details about a core network.

Type: CoreNetwork object

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

AccessDeniedException

You do not have sufficient access to perform this action.

HTTP Status Code: 403

InternalServerError

The request has failed due to an internal error.

RetryAfterSeconds

Indicates when to retry the request.

HTTP Status Code: 500

ResourceNotFoundException

The specified resource could not be found.

Context

The specified resource could not be found.

ResourceId

The ID of the resource.

ResourceType

The resource type.

HTTP Status Code: 404

ThrottlingException

The request was denied due to request throttling.

RetryAfterSeconds

Indicates when to retry the request.

HTTP Status Code: 429

ValidationException

The input fails to satisfy the constraints.

Fields

The fields that caused the error, if applicable.

Reason

The reason for the error.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

GetCoreNetworkChangeEvents

Returns information about a core network change event.

Request Syntax

```
GET /core-networks/coreNetworkId/core-network-change-events/policyVersionId?  
maxResults=MaxResults&nextToken=NextToken HTTP/1.1
```

URI Request Parameters

The request uses the following URI parameters.

coreNetworkId

The ID of a core network.

Length Constraints: Minimum length of 0. Maximum length of 50.

Pattern: `^core-network-([0-9a-f]{8,17})$`

Required: Yes

MaxResults

The maximum number of results to return.

Valid Range: Minimum value of 1. Maximum value of 500.

NextToken

The token for the next page of results.

Length Constraints: Minimum length of 0. Maximum length of 2048.

Pattern: `[\s\S]*`

policyVersionId

The ID of the policy version.

Required: Yes

Request Body

The request does not have a request body.

Response Syntax

```
HTTP/1.1 200
Content-type: application/json

{
  "CoreNetworkChangeEvents": [
    {
      "Action": "string",
      "EventTime": number,
      "IdentifierPath": "string",
      "Status": "string",
      "Type": "string",
      "Values": {
        "AttachmentId": "string",
        "Cidr": "string",
        "EdgeLocation": "string",
        "NetworkFunctionGroupName": "string",
        "SegmentName": "string"
      }
    }
  ],
  "NextToken": "string"
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

CoreNetworkChangeEvents

The response to GetCoreNetworkChangeEventsRequest.

Type: Array of [CoreNetworkChangeEvent](#) objects

NextToken

The token for the next page of results.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 2048.

Pattern: `[\s\S]*`

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

AccessDeniedException

You do not have sufficient access to perform this action.

HTTP Status Code: 403

InternalServerError

The request has failed due to an internal error.

RetryAfterSeconds

Indicates when to retry the request.

HTTP Status Code: 500

ResourceNotFoundException

The specified resource could not be found.

Context

The specified resource could not be found.

ResourceId

The ID of the resource.

ResourceType

The resource type.

HTTP Status Code: 404

ThrottlingException

The request was denied due to request throttling.

RetryAfterSeconds

Indicates when to retry the request.

HTTP Status Code: 429

ValidationException

The input fails to satisfy the constraints.

Fields

The fields that caused the error, if applicable.

Reason

The reason for the error.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

GetCoreNetworkChangeSet

Returns a change set between the LIVE core network policy and a submitted policy.

Request Syntax

```
GET /core-networks/coreNetworkId/core-network-change-sets/policyVersionId?
maxResults=MaxResults&nextToken=NextToken HTTP/1.1
```

URI Request Parameters

The request uses the following URI parameters.

coreNetworkId

The ID of a core network.

Length Constraints: Minimum length of 0. Maximum length of 50.

Pattern: `^core-network-([0-9a-f]{8,17})$`

Required: Yes

MaxResults

The maximum number of results to return.

Valid Range: Minimum value of 1. Maximum value of 500.

NextToken

The token for the next page of results.

Length Constraints: Minimum length of 0. Maximum length of 2048.

Pattern: `[\s\S]*`

policyVersionId

The ID of the policy version.

Required: Yes

Request Body

The request does not have a request body.

Response Syntax

HTTP/1.1 200

Content-type: application/json

```
{
  "CoreNetworkChanges": [
    {
      "Action": "string",
      "Identifier": "string",
      "IdentifierPath": "string",
      "NewValues": {
        "Asn": number,
        "Cidr": "string",
        "DestinationIdentifier": "string",
        "DnsSupport": boolean,
        "EdgeLocations": [ "string" ],
        "InsideCidrBlocks": [ "string" ],
        "NetworkFunctionGroupName": "string",
        "SecurityGroupReferencingSupport": boolean,
        "SegmentName": "string",
        "ServiceInsertionActions": [
          {
            "Action": "string",
            "Mode": "string",
            "Via": {
              "NetworkFunctionGroups": [
                {
                  "Name": "string"
                }
              ],
            "WithEdgeOverrides": [
              {
                "EdgeSets": [
                  [ "string" ]
                ],
                "UseEdge": "string"
              }
            ]
          }
        ]
      }
    }
  ]
}
```

```

        },
        "WhenSentTo": {
            "WhenSentToSegmentsList": [ "string" ]
        }
    ],
    "SharedSegments": [ "string" ],
    "VpnEcmpSupport": boolean
},
"PreviousValues": {
    "Asn": number,
    "Cidr": "string",
    "DestinationIdentifier": "string",
    "DnsSupport": boolean,
    "EdgeLocations": [ "string" ],
    "InsideCidrBlocks": [ "string" ],
    "NetworkFunctionGroupName": "string",
    "SecurityGroupReferencingSupport": boolean,
    "SegmentName": "string",
    "ServiceInsertionActions": [
        {
            "Action": "string",
            "Mode": "string",
            "Via": {
                "NetworkFunctionGroups": [
                    {
                        "Name": "string"
                    }
                ],
                "WithEdgeOverrides": [
                    {
                        "EdgeSets": [
                            [ "string" ]
                        ],
                        "UseEdge": "string"
                    }
                ]
            }
        }
    ],
    "WhenSentTo": {
        "WhenSentToSegmentsList": [ "string" ]
    }
}
],
"SharedSegments": [ "string" ],

```

```
        "VpnEcmpSupport": boolean
      },
      "Type": "string"
    }
  ],
  "NextToken": "string"
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

CoreNetworkChanges

Describes a core network changes.

Type: Array of [CoreNetworkChange](#) objects

NextToken

The token for the next page of results.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 2048.

Pattern: `[\s\S]*`

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

AccessDeniedException

You do not have sufficient access to perform this action.

HTTP Status Code: 403

InternalServerError

The request has failed due to an internal error.

RetryAfterSeconds

Indicates when to retry the request.

HTTP Status Code: 500

ResourceNotFoundException

The specified resource could not be found.

Context

The specified resource could not be found.

ResourceId

The ID of the resource.

ResourceType

The resource type.

HTTP Status Code: 404

ThrottlingException

The request was denied due to request throttling.

RetryAfterSeconds

Indicates when to retry the request.

HTTP Status Code: 429

ValidationException

The input fails to satisfy the constraints.

Fields

The fields that caused the error, if applicable.

Reason

The reason for the error.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

GetCoreNetworkPolicy

Returns details about a core network policy. You can get details about your current live policy or any previous policy version.

Request Syntax

```
GET /core-networks/coreNetworkId/core-network-policy?  
alias=Alias&policyVersionId=PolicyVersionId HTTP/1.1
```

URI Request Parameters

The request uses the following URI parameters.

Alias

The alias of a core network policy

Valid Values: LIVE | LATEST

coreNetworkId

The ID of a core network.

Length Constraints: Minimum length of 0. Maximum length of 50.

Pattern: ^core-network-([0-9a-f]{8,17})\$

Required: Yes

PolicyVersionId

The ID of a core network policy version.

Request Body

The request does not have a request body.

Response Syntax

```
HTTP/1.1 200
```

Content-type: application/json

```
{
  "CoreNetworkPolicy": {
    "Alias": "string",
    "ChangeSetState": "string",
    "CoreNetworkId": "string",
    "CreatedAt": number,
    "Description": "string",
    "PolicyDocument": "string",
    "PolicyErrors": [
      {
        "ErrorCode": "string",
        "Message": "string",
        "Path": "string"
      }
    ],
    "PolicyVersionId": number
  }
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

CoreNetworkPolicy

The details about a core network policy.

Type: [CoreNetworkPolicy](#) object

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

AccessDeniedException

You do not have sufficient access to perform this action.

HTTP Status Code: 403

InternalServerError

The request has failed due to an internal error.

RetryAfterSeconds

Indicates when to retry the request.

HTTP Status Code: 500

ResourceNotFoundException

The specified resource could not be found.

Context

The specified resource could not be found.

ResourceId

The ID of the resource.

ResourceType

The resource type.

HTTP Status Code: 404

ThrottlingException

The request was denied due to request throttling.

RetryAfterSeconds

Indicates when to retry the request.

HTTP Status Code: 429

ValidationException

The input fails to satisfy the constraints.

Fields

The fields that caused the error, if applicable.

Reason

The reason for the error.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

GetCustomerGatewayAssociations

Gets the association information for customer gateways that are associated with devices and links in your global network.

Request Syntax

```
GET /global-networks/globalNetworkId/customer-gateway-associations?
customerGatewayArns=CustomerGatewayArns&maxResults=MaxResults&nextToken=NextToken
HTTP/1.1
```

URI Request Parameters

The request uses the following URI parameters.

CustomerGatewayArns

One or more customer gateway Amazon Resource Names (ARNs). The maximum is 10.

Length Constraints: Minimum length of 0. Maximum length of 500.

Pattern: `[\s\S]*`

globalNetworkId

The ID of the global network.

Length Constraints: Minimum length of 0. Maximum length of 50.

Pattern: `[\s\S]*`

Required: Yes

MaxResults

The maximum number of results to return.

Valid Range: Minimum value of 1. Maximum value of 500.

NextToken

The token for the next page of results.

Length Constraints: Minimum length of 0. Maximum length of 2048.

Pattern: `[\s\S]*`

Request Body

The request does not have a request body.

Response Syntax

```
HTTP/1.1 200
Content-type: application/json

{
  "CustomerGatewayAssociations": [
    {
      "CustomerGatewayArn": "string",
      "DeviceId": "string",
      "GlobalNetworkId": "string",
      "LinkId": "string",
      "State": "string"
    }
  ],
  "NextToken": "string"
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

[CustomerGatewayAssociations](#)

The customer gateway associations.

Type: Array of [CustomerGatewayAssociation](#) objects

[NextToken](#)

The token for the next page of results.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 2048.

Pattern: `[\s\S]*`

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

AccessDeniedException

You do not have sufficient access to perform this action.

HTTP Status Code: 403

ConflictException

There was a conflict processing the request. Updating or deleting the resource can cause an inconsistent state.

ResourceId

The ID of the resource.

ResourceType

The resource type.

HTTP Status Code: 409

InternalServerErrorException

The request has failed due to an internal error.

RetryAfterSeconds

Indicates when to retry the request.

HTTP Status Code: 500

ResourceNotFoundException

The specified resource could not be found.

Context

The specified resource could not be found.

ResourceId

The ID of the resource.

ResourceType

The resource type.

HTTP Status Code: 404

ThrottlingException

The request was denied due to request throttling.

RetryAfterSeconds

Indicates when to retry the request.

HTTP Status Code: 429

ValidationException

The input fails to satisfy the constraints.

Fields

The fields that caused the error, if applicable.

Reason

The reason for the error.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)

- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

GetDevices

Gets information about one or more of your devices in a global network.

Request Syntax

```
GET /global-networks/globalNetworkId/devices?  
deviceIds=DeviceIds&maxResults=MaxResults&nextToken=NextToken&siteId=SiteId HTTP/1.1
```

URI Request Parameters

The request uses the following URI parameters.

DeviceIds

One or more device IDs. The maximum is 10.

Length Constraints: Minimum length of 0. Maximum length of 50.

Pattern: `[\s\S]*`

globalNetworkId

The ID of the global network.

Length Constraints: Minimum length of 0. Maximum length of 50.

Pattern: `[\s\S]*`

Required: Yes

MaxResults

The maximum number of results to return.

Valid Range: Minimum value of 1. Maximum value of 500.

NextToken

The token for the next page of results.

Length Constraints: Minimum length of 0. Maximum length of 2048.

Pattern: `[\s\S]*`

SiteId

The ID of the site.

Length Constraints: Minimum length of 0. Maximum length of 50.

Pattern: `[\s\S]*`

Request Body

The request does not have a request body.

Response Syntax

```
HTTP/1.1 200
Content-type: application/json

{
  "Devices": [
    {
      "AWSLocation": {
        "SubnetArn": "string",
        "Zone": "string"
      },
      "CreatedAt": number,
      "Description": "string",
      "DeviceArn": "string",
      "DeviceId": "string",
      "GlobalNetworkId": "string",
      "Location": {
        "Address": "string",
        "Latitude": "string",
        "Longitude": "string"
      },
      "Model": "string",
      "SerialNumber": "string",
      "SiteId": "string",
      "State": "string",
      "Tags": [
        {
          "Key": "string",
          "Value": "string"
        }
      ]
    }
  ]
}
```

```
    }  
  ],  
  "Type": "string",  
  "Vendor": "string"  
}  
],  
"NextToken": "string"  
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

Devices

The devices.

Type: Array of [Device](#) objects

NextToken

The token for the next page of results.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 2048.

Pattern: `[\s\S]*`

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

AccessDeniedException

You do not have sufficient access to perform this action.

HTTP Status Code: 403

InternalServerError

The request has failed due to an internal error.

RetryAfterSeconds

Indicates when to retry the request.

HTTP Status Code: 500

ResourceNotFoundException

The specified resource could not be found.

Context

The specified resource could not be found.

ResourceId

The ID of the resource.

ResourceType

The resource type.

HTTP Status Code: 404

ThrottlingException

The request was denied due to request throttling.

RetryAfterSeconds

Indicates when to retry the request.

HTTP Status Code: 429

ValidationException

The input fails to satisfy the constraints.

Fields

The fields that caused the error, if applicable.

Reason

The reason for the error.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

GetDirectConnectGatewayAttachment

Returns information about a specific AWS Direct Connect gateway attachment.

Request Syntax

```
GET /direct-connect-gateway-attachments/attachmentId HTTP/1.1
```

URI Request Parameters

The request uses the following URI parameters.

attachmentId

The ID of the Direct Connect gateway attachment that you want to see details about.

Length Constraints: Minimum length of 0. Maximum length of 50.

Pattern: `^attachment-([0-9a-f]{8,17})$`

Required: Yes

Request Body

The request does not have a request body.

Response Syntax

```
HTTP/1.1 200
Content-type: application/json

{
  "DirectConnectGatewayAttachment": {
    "Attachment": {
      "AttachmentId": "string",
      "AttachmentPolicyRuleNumber": number,
      "AttachmentType": "string",
      "CoreNetworkArn": "string",
      "CoreNetworkId": "string",
      "CreatedAt": number,
      "EdgeLocation": "string",
      "EdgeLocations": [ "string" ],
```

```

    "LastModificationErrors": [
      {
        "Code": "string",
        "Message": "string",
        "RequestId": "string",
        "ResourceArn": "string"
      }
    ],
    "NetworkFunctionGroupName": "string",
    "OwnerAccountId": "string",
    "ProposedNetworkFunctionGroupChange": {
      "AttachmentPolicyRuleNumber": number,
      "NetworkFunctionGroupName": "string",
      "Tags": [
        {
          "Key": "string",
          "Value": "string"
        }
      ]
    },
    "ProposedSegmentChange": {
      "AttachmentPolicyRuleNumber": number,
      "SegmentName": "string",
      "Tags": [
        {
          "Key": "string",
          "Value": "string"
        }
      ]
    },
    "ResourceArn": "string",
    "SegmentName": "string",
    "State": "string",
    "Tags": [
      {
        "Key": "string",
        "Value": "string"
      }
    ],
    "UpdatedAt": number
  },
  "DirectConnectGatewayArn": "string"
}

```

```
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

DirectConnectGatewayAttachment

Shows details about the Direct Connect gateway attachment.

Type: [DirectConnectGatewayAttachment](#) object

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

AccessDeniedException

You do not have sufficient access to perform this action.

HTTP Status Code: 403

InternalServerError

The request has failed due to an internal error.

RetryAfterSeconds

Indicates when to retry the request.

HTTP Status Code: 500

ResourceNotFoundException

The specified resource could not be found.

Context

The specified resource could not be found.

ResourceId

The ID of the resource.

ResourceType

The resource type.

HTTP Status Code: 404

ThrottlingException

The request was denied due to request throttling.

RetryAfterSeconds

Indicates when to retry the request.

HTTP Status Code: 429

ValidationException

The input fails to satisfy the constraints.

Fields

The fields that caused the error, if applicable.

Reason

The reason for the error.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)

- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

GetLinkAssociations

Gets the link associations for a device or a link. Either the device ID or the link ID must be specified.

Request Syntax

```
GET /global-networks/globalNetworkId/link-associations?  
deviceId=DeviceId&linkId=LinkId&maxResults=MaxResults&nextToken=NextToken HTTP/1.1
```

URI Request Parameters

The request uses the following URI parameters.

DeviceId

The ID of the device.

Length Constraints: Minimum length of 0. Maximum length of 50.

Pattern: `[\s\S]*`

globalNetworkId

The ID of the global network.

Length Constraints: Minimum length of 0. Maximum length of 50.

Pattern: `[\s\S]*`

Required: Yes

LinkId

The ID of the link.

Length Constraints: Minimum length of 0. Maximum length of 50.

Pattern: `[\s\S]*`

MaxResults

The maximum number of results to return.

Valid Range: Minimum value of 1. Maximum value of 500.

[NextToken](#)

The token for the next page of results.

Length Constraints: Minimum length of 0. Maximum length of 2048.

Pattern: `[\s\S]*`

Request Body

The request does not have a request body.

Response Syntax

```
HTTP/1.1 200
Content-type: application/json

{
  "LinkAssociations": [
    {
      "DeviceId": "string",
      "GlobalNetworkId": "string",
      "LinkAssociationState": "string",
      "LinkId": "string"
    }
  ],
  "NextToken": "string"
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

[LinkAssociations](#)

The link associations.

Type: Array of [LinkAssociation](#) objects

NextToken

The token for the next page of results.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 2048.

Pattern: `[\s\S]*`

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

AccessDeniedException

You do not have sufficient access to perform this action.

HTTP Status Code: 403

InternalServerError

The request has failed due to an internal error.

RetryAfterSeconds

Indicates when to retry the request.

HTTP Status Code: 500

ResourceNotFoundException

The specified resource could not be found.

Context

The specified resource could not be found.

ResourceId

The ID of the resource.

ResourceType

The resource type.

HTTP Status Code: 404

ThrottlingException

The request was denied due to request throttling.

RetryAfterSeconds

Indicates when to retry the request.

HTTP Status Code: 429

ValidationException

The input fails to satisfy the constraints.

Fields

The fields that caused the error, if applicable.

Reason

The reason for the error.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

GetLinks

Gets information about one or more links in a specified global network.

If you specify the site ID, you cannot specify the type or provider in the same request. You can specify the type and provider in the same request.

Request Syntax

```
GET /global-networks/globalNetworkId/links?  
linkIds=LinkIds&maxResults=MaxResults&nextToken=NextToken&provider=Provider&siteId=SiteId&type=  
HTTP/1.1
```

URI Request Parameters

The request uses the following URI parameters.

globalNetworkId

The ID of the global network.

Length Constraints: Minimum length of 0. Maximum length of 50.

Pattern: `[\s\S]*`

Required: Yes

LinkIds

One or more link IDs. The maximum is 10.

Length Constraints: Minimum length of 0. Maximum length of 50.

Pattern: `[\s\S]*`

MaxResults

The maximum number of results to return.

Valid Range: Minimum value of 1. Maximum value of 500.

NextToken

The token for the next page of results.

Length Constraints: Minimum length of 0. Maximum length of 2048.

Pattern: `[\s\S]*`

Provider

The link provider.

Length Constraints: Minimum length of 0. Maximum length of 256.

Pattern: `[\s\S]*`

Siteld

The ID of the site.

Length Constraints: Minimum length of 0. Maximum length of 50.

Pattern: `[\s\S]*`

Type

The link type.

Length Constraints: Minimum length of 0. Maximum length of 256.

Pattern: `[\s\S]*`

Request Body

The request does not have a request body.

Response Syntax

```
HTTP/1.1 200
Content-type: application/json

{
  "Links": [
    {
      "Bandwidth": {
        "DownloadSpeed": number,
        "UploadSpeed": number
      },
      "CreatedAt": number,
```

```
  "Description": "string",
  "GlobalNetworkId": "string",
  "LinkArn": "string",
  "LinkId": "string",
  "Provider": "string",
  "SiteId": "string",
  "State": "string",
  "Tags": [
    {
      "Key": "string",
      "Value": "string"
    }
  ],
  "Type": "string"
},
"NextToken": "string"
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

[Links](#)

The links.

Type: Array of [Link](#) objects

[NextToken](#)

The token for the next page of results.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 2048.

Pattern: `[\s\S]*`

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

AccessDeniedException

You do not have sufficient access to perform this action.

HTTP Status Code: 403

InternalServerError

The request has failed due to an internal error.

RetryAfterSeconds

Indicates when to retry the request.

HTTP Status Code: 500

ResourceNotFoundException

The specified resource could not be found.

Context

The specified resource could not be found.

ResourceId

The ID of the resource.

ResourceType

The resource type.

HTTP Status Code: 404

ThrottlingException

The request was denied due to request throttling.

RetryAfterSeconds

Indicates when to retry the request.

HTTP Status Code: 429

ValidationException

The input fails to satisfy the constraints.

Fields

The fields that caused the error, if applicable.

Reason

The reason for the error.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

GetNetworkResourceCounts

Gets the count of network resources, by resource type, for the specified global network.

Request Syntax

```
GET /global-networks/globalNetworkId/network-resource-count?  
maxResults=MaxResults&nextToken=NextToken&resourceType=ResourceType HTTP/1.1
```

URI Request Parameters

The request uses the following URI parameters.

globalNetworkId

The ID of the global network.

Length Constraints: Minimum length of 0. Maximum length of 50.

Pattern: `[\s\S]*`

Required: Yes

MaxResults

The maximum number of results to return.

Valid Range: Minimum value of 1. Maximum value of 500.

NextToken

The token for the next page of results.

Length Constraints: Minimum length of 0. Maximum length of 2048.

Pattern: `[\s\S]*`

ResourceType

The resource type.

The following are the supported resource types for AWS Direct Connect:

- `dxcon`

- dx-gateway
- dx-vif

The following are the supported resource types for Network Manager:

- attachment
- connect-peer
- connection
- core-network
- device
- link
- peering
- site

The following are the supported resource types for Amazon VPC:

- customer-gateway
- transit-gateway
- transit-gateway-attachment
- transit-gateway-connect-peer
- transit-gateway-route-table
- vpn-connection

Length Constraints: Minimum length of 0. Maximum length of 256.

Pattern: `[\s\S]*`

Request Body

The request does not have a request body.

Response Syntax

```
HTTP/1.1 200
Content-type: application/json

{
```

```
"NetworkResourceCounts": [  
  {  
    "Count": number,  
    "ResourceType": "string"  
  }  
],  
"NextToken": "string"  
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

NetworkResourceCounts

The count of resources.

Type: Array of [NetworkResourceCount](#) objects

NextToken

The token for the next page of results.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 2048.

Pattern: `[\s\S]*`

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

AccessDeniedException

You do not have sufficient access to perform this action.

HTTP Status Code: 403

InternalServerError

The request has failed due to an internal error.

RetryAfterSeconds

Indicates when to retry the request.

HTTP Status Code: 500

ThrottlingException

The request was denied due to request throttling.

RetryAfterSeconds

Indicates when to retry the request.

HTTP Status Code: 429

ValidationException

The input fails to satisfy the constraints.

Fields

The fields that caused the error, if applicable.

Reason

The reason for the error.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)

- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

GetNetworkResourceRelationships

Gets the network resource relationships for the specified global network.

Request Syntax

```
GET /global-networks/globalNetworkId/network-resource-relationships?  
accountId=AccountId&awsRegion=AwsRegion&coreNetworkId=CoreNetworkId&maxResults=MaxResults&nextToken=NextToken  
HTTP/1.1
```

URI Request Parameters

The request uses the following URI parameters.

AccountId

The AWS account ID.

Length Constraints: Fixed length of 12.

Pattern: `[\s\S]*`

AwsRegion

The AWS Region.

Length Constraints: Minimum length of 1. Maximum length of 63.

Pattern: `[\s\S]*`

CoreNetworkId

The ID of a core network.

Length Constraints: Minimum length of 0. Maximum length of 50.

Pattern: `^core-network-([0-9a-f]{8,17})$`

globalNetworkId

The ID of the global network.

Length Constraints: Minimum length of 0. Maximum length of 50.

Pattern: `[\s\S]*`

Required: Yes

MaxResults

The maximum number of results to return.

Valid Range: Minimum value of 1. Maximum value of 500.

NextToken

The token for the next page of results.

Length Constraints: Minimum length of 0. Maximum length of 2048.

Pattern: `[\s\S]*`

RegisteredGatewayArn

The ARN of the registered gateway.

Length Constraints: Minimum length of 0. Maximum length of 1500.

Pattern: `[\s\S]*`

ResourceArn

The ARN of the gateway.

Length Constraints: Minimum length of 0. Maximum length of 1500.

Pattern: `[\s\S]*`

ResourceType

The resource type.

The following are the supported resource types for AWS Direct Connect:

- dxcon
- dx-gateway
- dx-vif

The following are the supported resource types for Network Manager:

- attachment

- `connect-peer`
- `connection`
- `core-network`
- `device`
- `link`
- `peering`
- `site`

The following are the supported resource types for Amazon VPC:

- `customer-gateway`
- `transit-gateway`
- `transit-gateway-attachment`
- `transit-gateway-connect-peer`
- `transit-gateway-route-table`
- `vpn-connection`

Length Constraints: Minimum length of 0. Maximum length of 256.

Pattern: `[\s\S]*`

Request Body

The request does not have a request body.

Response Syntax

```
HTTP/1.1 200
Content-type: application/json
```

```
{
  "NextToken": "string",
  "Relationships": [
    {
      "From": "string",
      "To": "string"
    }
  ]
}
```

```
]
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

[NextToken](#)

The token for the next page of results.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 2048.

Pattern: `[\s\S]*`

[Relationships](#)

The resource relationships.

Type: Array of [Relationship](#) objects

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

AccessDeniedException

You do not have sufficient access to perform this action.

HTTP Status Code: 403

InternalServerError

The request has failed due to an internal error.

RetryAfterSeconds

Indicates when to retry the request.

HTTP Status Code: 500

ResourceNotFoundException

The specified resource could not be found.

Context

The specified resource could not be found.

ResourceId

The ID of the resource.

ResourceType

The resource type.

HTTP Status Code: 404

ThrottlingException

The request was denied due to request throttling.

RetryAfterSeconds

Indicates when to retry the request.

HTTP Status Code: 429

ValidationException

The input fails to satisfy the constraints.

Fields

The fields that caused the error, if applicable.

Reason

The reason for the error.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)

- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

GetNetworkResources

Describes the network resources for the specified global network.

The results include information from the corresponding Describe call for the resource, minus any sensitive information such as pre-shared keys.

Request Syntax

```
GET /global-networks/globalNetworkId/network-resources?  
accountId=AccountId&awsRegion=AwsRegion&coreNetworkId=CoreNetworkId&maxResults=MaxResults&nextToken=NextToken  
HTTP/1.1
```

URI Request Parameters

The request uses the following URI parameters.

AccountId

The AWS account ID.

Length Constraints: Fixed length of 12.

Pattern: `[\s\S]*`

AwsRegion

The AWS Region.

Length Constraints: Minimum length of 1. Maximum length of 63.

Pattern: `[\s\S]*`

CoreNetworkId

The ID of a core network.

Length Constraints: Minimum length of 0. Maximum length of 50.

Pattern: `^core-network-([0-9a-f]{8,17})$`

globalNetworkId

The ID of the global network.

Length Constraints: Minimum length of 0. Maximum length of 50.

Pattern: `[\s\S]*`

Required: Yes

MaxResults

The maximum number of results to return.

Valid Range: Minimum value of 1. Maximum value of 500.

NextToken

The token for the next page of results.

Length Constraints: Minimum length of 0. Maximum length of 2048.

Pattern: `[\s\S]*`

RegisteredGatewayArn

The ARN of the gateway.

Length Constraints: Minimum length of 0. Maximum length of 1500.

Pattern: `[\s\S]*`

ResourceArn

The ARN of the resource.

Length Constraints: Minimum length of 0. Maximum length of 1500.

Pattern: `[\s\S]*`

ResourceType

The resource type.

The following are the supported resource types for AWS Direct Connect:

- `dxcon`
- `dx-gateway`
- `dx-vif`

The following are the supported resource types for Network Manager:

- attachment
- connect-peer
- connection
- core-network
- device
- link
- peering
- site

The following are the supported resource types for Amazon VPC:

- customer-gateway
- transit-gateway
- transit-gateway-attachment
- transit-gateway-connect-peer
- transit-gateway-route-table
- vpn-connection

Length Constraints: Minimum length of 0. Maximum length of 256.

Pattern: `[\s\S]*`

Request Body

The request does not have a request body.

Response Syntax

```
HTTP/1.1 200
Content-type: application/json

{
  "NetworkResources": [
    {
      "AccountId": "string",
```



```
"AwsRegion": "string",
"CoreNetworkId": "string",
"Definition": "string",
"DefinitionTimestamp": number,
"Metadata": {
  "string" : "string"
},
"RegisteredGatewayArn": "string",
"ResourceArn": "string",
"ResourceId": "string",
"ResourceType": "string",
"Tags": [
  {
    "Key": "string",
    "Value": "string"
  }
]
},
"NextToken": "string"
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

[NetworkResources](#)

The network resources.

Type: Array of [NetworkResource](#) objects

[NextToken](#)

The token for the next page of results.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 2048.

Pattern: `[\s\S]*`

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

AccessDeniedException

You do not have sufficient access to perform this action.

HTTP Status Code: 403

InternalServerError

The request has failed due to an internal error.

RetryAfterSeconds

Indicates when to retry the request.

HTTP Status Code: 500

ResourceNotFoundException

The specified resource could not be found.

Context

The specified resource could not be found.

ResourceId

The ID of the resource.

ResourceType

The resource type.

HTTP Status Code: 404

ThrottlingException

The request was denied due to request throttling.

RetryAfterSeconds

Indicates when to retry the request.

HTTP Status Code: 429

ValidationException

The input fails to satisfy the constraints.

Fields

The fields that caused the error, if applicable.

Reason

The reason for the error.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

GetNetworkRoutes

Gets the network routes of the specified global network.

Request Syntax

```
POST /global-networks/globalNetworkId/network-routes HTTP/1.1
Content-type: application/json
```

```
{
  "DestinationFilters": {
    "string" : [ "string" ]
  },
  "ExactCidrMatches": [ "string" ],
  "LongestPrefixMatches": [ "string" ],
  "PrefixListIds": [ "string" ],
  "RouteTableIdentifier": {
    "CoreNetworkNetworkFunctionGroup": {
      "CoreNetworkId": "string",
      "EdgeLocation": "string",
      "NetworkFunctionGroupName": "string"
    },
    "CoreNetworkSegmentEdge": {
      "CoreNetworkId": "string",
      "EdgeLocation": "string",
      "SegmentName": "string"
    },
    "TransitGatewayRouteTableArn": "string"
  },
  "States": [ "string" ],
  "SubnetOfMatches": [ "string" ],
  "SupernetOfMatches": [ "string" ],
  "Types": [ "string" ]
}
```

URI Request Parameters

The request uses the following URI parameters.

globalNetworkId

The ID of the global network.

Length Constraints: Minimum length of 0. Maximum length of 50.

Pattern: `[\s\S]*`

Required: Yes

Request Body

The request accepts the following data in JSON format.

DestinationFilters

Filter by route table destination. Possible Values: TRANSIT_GATEWAY_ATTACHMENT_ID, RESOURCE_ID, or RESOURCE_TYPE.

Type: String to array of strings map

Key Length Constraints: Maximum length of 128.

Key Pattern: `^[0-9a-zA-Z\.-]*$`

Length Constraints: Maximum length of 255.

Pattern: `^[0-9a-zA-Z*\.\|\/\?-\]*$`

Required: No

ExactCidrMatches

An exact CIDR block.

Type: Array of strings

Length Constraints: Minimum length of 0. Maximum length of 256.

Pattern: `[\s\S]*`

Required: No

LongestPrefixMatches

The most specific route that matches the traffic (longest prefix match).

Type: Array of strings

Length Constraints: Minimum length of 0. Maximum length of 256.

Pattern: `[\s\S]*`

Required: No

PrefixListIds

The IDs of the prefix lists.

Type: Array of strings

Length Constraints: Minimum length of 0. Maximum length of 256.

Pattern: `[\s\S]*`

Required: No

RouteTableIdentifier

The ID of the route table.

Type: [RouteTableIdentifier](#) object

Required: Yes

States

The route states.

Type: Array of strings

Valid Values: ACTIVE | BLACKHOLE

Required: No

SubnetOfMatches

The routes with a subnet that match the specified CIDR filter.

Type: Array of strings

Length Constraints: Minimum length of 0. Maximum length of 256.

Pattern: `[\s\S]*`

Required: No

SupernetOfMatches

The routes with a CIDR that encompasses the CIDR filter. Example: If you specify 10.0.1.0/30, then the result returns 10.0.1.0/29.

Type: Array of strings

Length Constraints: Minimum length of 0. Maximum length of 256.

Pattern: `[\s\S]*`

Required: No

Types

The route types.

Type: Array of strings

Valid Values: PROPAGATED | STATIC

Required: No

Response Syntax

```
HTTP/1.1 200
Content-type: application/json

{
  "CoreNetworkSegmentEdge": {
    "CoreNetworkId": "string",
    "EdgeLocation": "string",
    "SegmentName": "string"
  },
  "NetworkRoutes": [
    {
      "DestinationCidrBlock": "string",
      "Destinations": [
        {
          "CoreNetworkAttachmentId": "string",
          "EdgeLocation": "string",
```

```
        "NetworkFunctionGroupName": "string",
        "ResourceId": "string",
        "ResourceType": "string",
        "SegmentName": "string",
        "TransitGatewayAttachmentId": "string"
    }
],
"PrefixListId": "string",
"State": "string",
"Type": "string"
}
],
"RouteTableArn": "string",
"RouteTableTimestamp": number,
"RouteTableType": "string"
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

CoreNetworkSegmentEdge

Describes a core network segment edge.

Type: [CoreNetworkSegmentEdgeIdentifier](#) object

NetworkRoutes

The network routes.

Type: Array of [NetworkRoute](#) objects

RouteTableArn

The ARN of the route table.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 1500.

Pattern: `[\s\S]*`

RouteTableTimestamp

The route table creation time.

Type: Timestamp

RouteTableType

The route table type.

Type: String

Valid Values: TRANSIT_GATEWAY_ROUTE_TABLE | CORE_NETWORK_SEGMENT | NETWORK_FUNCTION_GROUP

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

AccessDeniedException

You do not have sufficient access to perform this action.

HTTP Status Code: 403

InternalServerError

The request has failed due to an internal error.

RetryAfterSeconds

Indicates when to retry the request.

HTTP Status Code: 500

ResourceNotFoundException

The specified resource could not be found.

Context

The specified resource could not be found.

ResourceId

The ID of the resource.

ResourceType

The resource type.

HTTP Status Code: 404

ThrottlingException

The request was denied due to request throttling.

RetryAfterSeconds

Indicates when to retry the request.

HTTP Status Code: 429

ValidationException

The input fails to satisfy the constraints.

Fields

The fields that caused the error, if applicable.

Reason

The reason for the error.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)

- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

GetNetworkTelemetry

Gets the network telemetry of the specified global network.

Request Syntax

```
GET /global-networks/globalNetworkId/network-telemetry?  
accountId=AccountId&awsRegion=AwsRegion&coreNetworkId=CoreNetworkId&maxResults=MaxResults&nextToken=NextToken  
HTTP/1.1
```

URI Request Parameters

The request uses the following URI parameters.

AccountId

The AWS account ID.

Length Constraints: Fixed length of 12.

Pattern: `[\s\S]*`

AwsRegion

The AWS Region.

Length Constraints: Minimum length of 1. Maximum length of 63.

Pattern: `[\s\S]*`

CoreNetworkId

The ID of a core network.

Length Constraints: Minimum length of 0. Maximum length of 50.

Pattern: `^core-network-([0-9a-f]{8,17})$`

globalNetworkId

The ID of the global network.

Length Constraints: Minimum length of 0. Maximum length of 50.

Pattern: `[\s\S]*`

Required: Yes

MaxResults

The maximum number of results to return.

Valid Range: Minimum value of 1. Maximum value of 500.

NextToken

The token for the next page of results.

Length Constraints: Minimum length of 0. Maximum length of 2048.

Pattern: `[\s\S]*`

RegisteredGatewayArn

The ARN of the gateway.

Length Constraints: Minimum length of 0. Maximum length of 1500.

Pattern: `[\s\S]*`

ResourceArn

The ARN of the resource.

Length Constraints: Minimum length of 0. Maximum length of 1500.

Pattern: `[\s\S]*`

ResourceType

The resource type. The following are the supported resource types:

- `connect-peer`
- `transit-gateway-connect-peer`
- `vpn-connection`

Length Constraints: Minimum length of 0. Maximum length of 256.

Pattern: `[\s\S]*`

Request Body

The request does not have a request body.

Response Syntax

```
HTTP/1.1 200
Content-type: application/json

{
  "NetworkTelemetry": [
    {
      "AccountId": "string",
      "Address": "string",
      "AwsRegion": "string",
      "CoreNetworkId": "string",
      "Health": {
        "Status": "string",
        "Timestamp": number,
        "Type": "string"
      },
      "RegisteredGatewayArn": "string",
      "ResourceArn": "string",
      "ResourceId": "string",
      "ResourceType": "string"
    }
  ],
  "NextToken": "string"
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

NetworkTelemetry

The network telemetry.

Type: Array of [NetworkTelemetry](#) objects

NextToken

The token for the next page of results.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 2048.

Pattern: `[\s\S]*`

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

AccessDeniedException

You do not have sufficient access to perform this action.

HTTP Status Code: 403

InternalServerError

The request has failed due to an internal error.

RetryAfterSeconds

Indicates when to retry the request.

HTTP Status Code: 500

ResourceNotFoundException

The specified resource could not be found.

Context

The specified resource could not be found.

ResourceId

The ID of the resource.

ResourceType

The resource type.

HTTP Status Code: 404

ThrottlingException

The request was denied due to request throttling.

RetryAfterSeconds

Indicates when to retry the request.

HTTP Status Code: 429

ValidationException

The input fails to satisfy the constraints.

Fields

The fields that caused the error, if applicable.

Reason

The reason for the error.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

GetResourcePolicy

Returns information about a resource policy.

Request Syntax

```
GET /resource-policy/resourceArn HTTP/1.1
```

URI Request Parameters

The request uses the following URI parameters.

resourceArn

The ARN of the resource.

Length Constraints: Minimum length of 0. Maximum length of 1500.

Pattern: `[\s\S]*`

Required: Yes

Request Body

The request does not have a request body.

Response Syntax

```
HTTP/1.1 200
Content-type: application/json

{
  "PolicyDocument": "string"
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

PolicyDocument

The resource policy document.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 10000000.

Pattern: `[\s\S]*`

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

AccessDeniedException

You do not have sufficient access to perform this action.

HTTP Status Code: 403

InternalServerError

The request has failed due to an internal error.

RetryAfterSeconds

Indicates when to retry the request.

HTTP Status Code: 500

ThrottlingException

The request was denied due to request throttling.

RetryAfterSeconds

Indicates when to retry the request.

HTTP Status Code: 429

ValidationException

The input fails to satisfy the constraints.

Fields

The fields that caused the error, if applicable.

Reason

The reason for the error.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

GetRouteAnalysis

Gets information about the specified route analysis.

Request Syntax

```
GET /global-networks/globalNetworkId/route-analyses/routeAnalysisId HTTP/1.1
```

URI Request Parameters

The request uses the following URI parameters.

globalNetworkId

The ID of the global network.

Length Constraints: Minimum length of 0. Maximum length of 50.

Pattern: `[\s\S]*`

Required: Yes

routeAnalysisId

The ID of the route analysis.

Length Constraints: Minimum length of 0. Maximum length of 256.

Pattern: `[\s\S]*`

Required: Yes

Request Body

The request does not have a request body.

Response Syntax

```
HTTP/1.1 200
Content-type: application/json

{
  "RouteAnalysis": {
```

```

    "Destination": {
      "IpAddress": "string",
      "TransitGatewayArn": "string",
      "TransitGatewayAttachmentArn": "string"
    },
    "ForwardPath": {
      "CompletionStatus": {
        "ReasonCode": "string",
        "ReasonContext": {
          "string": "string"
        },
        "ResultCode": "string"
      },
      "Path": [
        {
          "DestinationCidrBlock": "string",
          "Resource": {
            "Definition": "string",
            "IsMiddlebox": boolean,
            "NameTag": "string",
            "RegisteredGatewayArn": "string",
            "ResourceArn": "string",
            "ResourceType": "string"
          },
          "Sequence": number
        }
      ]
    },
    "GlobalNetworkId": "string",
    "IncludeReturnPath": boolean,
    "OwnerAccountId": "string",
    "ReturnPath": {
      "CompletionStatus": {
        "ReasonCode": "string",
        "ReasonContext": {
          "string": "string"
        },
        "ResultCode": "string"
      },
      "Path": [
        {
          "DestinationCidrBlock": "string",
          "Resource": {
            "Definition": "string",

```

```
        "IsMiddlebox": boolean,
        "NameTag": "string",
        "RegisteredGatewayArn": "string",
        "ResourceArn": "string",
        "ResourceType": "string"
    },
    "Sequence": number
}
]
},
"RouteAnalysisId": "string",
"Source": {
    "IpAddress": "string",
    "TransitGatewayArn": "string",
    "TransitGatewayAttachmentArn": "string"
},
"StartTimestamp": number,
"Status": "string",
"UseMiddleboxes": boolean
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

RouteAnalysis

The route analysis.

Type: [RouteAnalysis](#) object

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

AccessDeniedException

You do not have sufficient access to perform this action.

HTTP Status Code: 403

InternalServerErrorException

The request has failed due to an internal error.

RetryAfterSeconds

Indicates when to retry the request.

HTTP Status Code: 500

ResourceNotFoundException

The specified resource could not be found.

Context

The specified resource could not be found.

ResourceId

The ID of the resource.

ResourceType

The resource type.

HTTP Status Code: 404

ThrottlingException

The request was denied due to request throttling.

RetryAfterSeconds

Indicates when to retry the request.

HTTP Status Code: 429

ValidationException

The input fails to satisfy the constraints.

Fields

The fields that caused the error, if applicable.

Reason

The reason for the error.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

GetSites

Gets information about one or more of your sites in a global network.

Request Syntax

```
GET /global-networks/globalNetworkId/sites?  
maxResults=MaxResults&nextToken=NextToken&siteIds=SiteIds HTTP/1.1
```

URI Request Parameters

The request uses the following URI parameters.

globalNetworkId

The ID of the global network.

Length Constraints: Minimum length of 0. Maximum length of 50.

Pattern: `[\s\S]*`

Required: Yes

MaxResults

The maximum number of results to return.

Valid Range: Minimum value of 1. Maximum value of 500.

NextToken

The token for the next page of results.

Length Constraints: Minimum length of 0. Maximum length of 2048.

Pattern: `[\s\S]*`

SiteIds

One or more site IDs. The maximum is 10.

Length Constraints: Minimum length of 0. Maximum length of 50.

Pattern: `[\s\S]*`

Request Body

The request does not have a request body.

Response Syntax

```
HTTP/1.1 200
Content-type: application/json

{
  "NextToken": "string",
  "Sites": [
    {
      "CreatedAt": number,
      "Description": "string",
      "GlobalNetworkId": "string",
      "Location": {
        "Address": "string",
        "Latitude": "string",
        "Longitude": "string"
      },
      "SiteArn": "string",
      "SiteId": "string",
      "State": "string",
      "Tags": [
        {
          "Key": "string",
          "Value": "string"
        }
      ]
    }
  ]
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

NextToken

The token for the next page of results.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 2048.

Pattern: `[\s\S]*`

Sites

The sites.

Type: Array of [Site](#) objects

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

AccessDeniedException

You do not have sufficient access to perform this action.

HTTP Status Code: 403

InternalServerError

The request has failed due to an internal error.

RetryAfterSeconds

Indicates when to retry the request.

HTTP Status Code: 500

ResourceNotFoundException

The specified resource could not be found.

Context

The specified resource could not be found.

ResourceId

The ID of the resource.

ResourceType

The resource type.

HTTP Status Code: 404

ThrottlingException

The request was denied due to request throttling.

RetryAfterSeconds

Indicates when to retry the request.

HTTP Status Code: 429

ValidationException

The input fails to satisfy the constraints.

Fields

The fields that caused the error, if applicable.

Reason

The reason for the error.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)

- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

GetSiteToSiteVpnAttachment

Returns information about a site-to-site VPN attachment.

Request Syntax

```
GET /site-to-site-vpn-attachments/attachmentId HTTP/1.1
```

URI Request Parameters

The request uses the following URI parameters.

attachmentId

The ID of the attachment.

Length Constraints: Minimum length of 0. Maximum length of 50.

Pattern: ^attachment-([0-9a-f]{8,17})\$

Required: Yes

Request Body

The request does not have a request body.

Response Syntax

```
HTTP/1.1 200
Content-type: application/json

{
  "SiteToSiteVpnAttachment": {
    "Attachment": {
      "AttachmentId": "string",
      "AttachmentPolicyRuleNumber": number,
      "AttachmentType": "string",
      "CoreNetworkArn": "string",
      "CoreNetworkId": "string",
      "CreatedAt": number,
      "EdgeLocation": "string",
      "EdgeLocations": [ "string" ],
```

```

    "LastModificationErrors": [
      {
        "Code": "string",
        "Message": "string",
        "RequestId": "string",
        "ResourceArn": "string"
      }
    ],
    "NetworkFunctionGroupName": "string",
    "OwnerAccountId": "string",
    "ProposedNetworkFunctionGroupChange": {
      "AttachmentPolicyRuleNumber": number,
      "NetworkFunctionGroupName": "string",
      "Tags": [
        {
          "Key": "string",
          "Value": "string"
        }
      ]
    },
    "ProposedSegmentChange": {
      "AttachmentPolicyRuleNumber": number,
      "SegmentName": "string",
      "Tags": [
        {
          "Key": "string",
          "Value": "string"
        }
      ]
    },
    "ResourceArn": "string",
    "SegmentName": "string",
    "State": "string",
    "Tags": [
      {
        "Key": "string",
        "Value": "string"
      }
    ],
    "UpdatedAt": number
  },
  "VpnConnectionArn": "string"
}

```

```
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

SiteToSiteVpnAttachment

Describes the site-to-site attachment.

Type: [SiteToSiteVpnAttachment](#) object

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

AccessDeniedException

You do not have sufficient access to perform this action.

HTTP Status Code: 403

InternalServerError

The request has failed due to an internal error.

RetryAfterSeconds

Indicates when to retry the request.

HTTP Status Code: 500

ResourceNotFoundException

The specified resource could not be found.

Context

The specified resource could not be found.

ResourceId

The ID of the resource.

ResourceType

The resource type.

HTTP Status Code: 404

ThrottlingException

The request was denied due to request throttling.

RetryAfterSeconds

Indicates when to retry the request.

HTTP Status Code: 429

ValidationException

The input fails to satisfy the constraints.

Fields

The fields that caused the error, if applicable.

Reason

The reason for the error.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)

- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

GetTransitGatewayConnectPeerAssociations

Gets information about one or more of your transit gateway Connect peer associations in a global network.

Request Syntax

```
GET /global-networks/globalNetworkId/transit-gateway-connect-peer-associations?
maxResults=MaxResults&nextToken=NextToken&transitGatewayConnectPeerArns=TransitGatewayConnectPe
HTTP/1.1
```

URI Request Parameters

The request uses the following URI parameters.

globalNetworkId

The ID of the global network.

Length Constraints: Minimum length of 0. Maximum length of 50.

Pattern: `[\s\S]*`

Required: Yes

MaxResults

The maximum number of results to return.

Valid Range: Minimum value of 1. Maximum value of 500.

NextToken

The token for the next page of results.

Length Constraints: Minimum length of 0. Maximum length of 2048.

Pattern: `[\s\S]*`

TransitGatewayConnectPeerArns

One or more transit gateway Connect peer Amazon Resource Names (ARNs).

Length Constraints: Minimum length of 0. Maximum length of 500.

Pattern: `[\s\S]*`

Request Body

The request does not have a request body.

Response Syntax

```
HTTP/1.1 200
Content-type: application/json

{
  "NextToken": "string",
  "TransitGatewayConnectPeerAssociations": [
    {
      "DeviceId": "string",
      "GlobalNetworkId": "string",
      "LinkId": "string",
      "State": "string",
      "TransitGatewayConnectPeerArn": "string"
    }
  ]
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

NextToken

The token to use for the next page of results.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 2048.

Pattern: `[\s\S]*`

TransitGatewayConnectPeerAssociations

Information about the transit gateway Connect peer associations.

Type: Array of [TransitGatewayConnectPeerAssociation](#) objects

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

AccessDeniedException

You do not have sufficient access to perform this action.

HTTP Status Code: 403

ConflictException

There was a conflict processing the request. Updating or deleting the resource can cause an inconsistent state.

ResourceId

The ID of the resource.

ResourceType

The resource type.

HTTP Status Code: 409

InternalServerError

The request has failed due to an internal error.

RetryAfterSeconds

Indicates when to retry the request.

HTTP Status Code: 500

ResourceNotFoundException

The specified resource could not be found.

Context

The specified resource could not be found.

ResourceId

The ID of the resource.

ResourceType

The resource type.

HTTP Status Code: 404

ThrottlingException

The request was denied due to request throttling.

RetryAfterSeconds

Indicates when to retry the request.

HTTP Status Code: 429

ValidationException

The input fails to satisfy the constraints.

Fields

The fields that caused the error, if applicable.

Reason

The reason for the error.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)

- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

GetTransitGatewayPeering

Returns information about a transit gateway peer.

Request Syntax

```
GET /transit-gateway-peering/peeringId HTTP/1.1
```

URI Request Parameters

The request uses the following URI parameters.

peeringId

The ID of the peering request.

Length Constraints: Minimum length of 0. Maximum length of 50.

Pattern: `^peering-([0-9a-f]{8,17})$`

Required: Yes

Request Body

The request does not have a request body.

Response Syntax

```
HTTP/1.1 200
Content-type: application/json

{
  "TransitGatewayPeering": {
    "Peering": {
      "CoreNetworkArn": "string",
      "CoreNetworkId": "string",
      "CreatedAt": number,
      "EdgeLocation": "string",
      "LastModificationErrors": [
```



```

    {
      "Code": "string",
      "Message": "string",
      "MissingPermissionsContext": {
        "MissingPermission": "string"
      },
      "RequestId": "string",
      "ResourceArn": "string"
    }
  ],
  "OwnerAccountId": "string",
  "PeeringId": "string",
  "PeeringType": "string",
  "ResourceArn": "string",
  "State": "string",
  "Tags": [
    {
      "Key": "string",
      "Value": "string"
    }
  ]
},
"TransitGatewayArn": "string",
"TransitGatewayPeeringAttachmentId": "string"
}
}

```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

TransitGatewayPeering

Returns information about a transit gateway peering.

Type: [TransitGatewayPeering](#) object

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

AccessDeniedException

You do not have sufficient access to perform this action.

HTTP Status Code: 403

InternalServerError

The request has failed due to an internal error.

RetryAfterSeconds

Indicates when to retry the request.

HTTP Status Code: 500

ResourceNotFoundException

The specified resource could not be found.

Context

The specified resource could not be found.

ResourceId

The ID of the resource.

ResourceType

The resource type.

HTTP Status Code: 404

ThrottlingException

The request was denied due to request throttling.

RetryAfterSeconds

Indicates when to retry the request.

HTTP Status Code: 429

ValidationException

The input fails to satisfy the constraints.

Fields

The fields that caused the error, if applicable.

Reason

The reason for the error.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

GetTransitGatewayRegistrations

Gets information about the transit gateway registrations in a specified global network.

Request Syntax

```
GET /global-networks/globalNetworkId/transit-gateway-registrations?  
maxResults=MaxResults&nextToken=NextToken&transitGatewayArns=TransitGatewayArns  
HTTP/1.1
```

URI Request Parameters

The request uses the following URI parameters.

globalNetworkId

The ID of the global network.

Length Constraints: Minimum length of 0. Maximum length of 50.

Pattern: `[\s\S]*`

Required: Yes

MaxResults

The maximum number of results to return.

Valid Range: Minimum value of 1. Maximum value of 500.

NextToken

The token for the next page of results.

Length Constraints: Minimum length of 0. Maximum length of 2048.

Pattern: `[\s\S]*`

TransitGatewayArns

The Amazon Resource Names (ARNs) of one or more transit gateways. The maximum is 10.

Length Constraints: Minimum length of 0. Maximum length of 500.

Pattern: `[\s\S]*`

Request Body

The request does not have a request body.

Response Syntax

```
HTTP/1.1 200
Content-type: application/json

{
  "NextToken": "string",
  "TransitGatewayRegistrations": [
    {
      "GlobalNetworkId": "string",
      "State": {
        "Code": "string",
        "Message": "string"
      },
      "TransitGatewayArn": "string"
    }
  ]
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

NextToken

The token for the next page of results.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 2048.

Pattern: `[\s\S]*`

TransitGatewayRegistrations

The transit gateway registrations.

Type: Array of [TransitGatewayRegistration](#) objects

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

AccessDeniedException

You do not have sufficient access to perform this action.

HTTP Status Code: 403

InternalServerError

The request has failed due to an internal error.

RetryAfterSeconds

Indicates when to retry the request.

HTTP Status Code: 500

ResourceNotFoundException

The specified resource could not be found.

Context

The specified resource could not be found.

ResourceId

The ID of the resource.

ResourceType

The resource type.

HTTP Status Code: 404

ThrottlingException

The request was denied due to request throttling.

RetryAfterSeconds

Indicates when to retry the request.

HTTP Status Code: 429

ValidationException

The input fails to satisfy the constraints.

Fields

The fields that caused the error, if applicable.

Reason

The reason for the error.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

GetTransitGatewayRouteTableAttachment

Returns information about a transit gateway route table attachment.

Request Syntax

```
GET /transit-gateway-route-table-attachments/attachmentId HTTP/1.1
```

URI Request Parameters

The request uses the following URI parameters.

attachmentId

The ID of the transit gateway route table attachment.

Length Constraints: Minimum length of 0. Maximum length of 50.

Pattern: ^attachment-([0-9a-f]{8,17})\$

Required: Yes

Request Body

The request does not have a request body.

Response Syntax

```
HTTP/1.1 200
```

```
Content-type: application/json
```

```
{
  "TransitGatewayRouteTableAttachment": {
    "Attachment": {
      "AttachmentId": "string",
      "AttachmentPolicyRuleNumber": number,
      "AttachmentType": "string",
      "CoreNetworkArn": "string",
      "CoreNetworkId": "string",
      "CreatedAt": number,
      "EdgeLocation": "string",
      "EdgeLocations": [ "string" ],
```



```

    "LastModificationErrors": [
      {
        "Code": "string",
        "Message": "string",
        "RequestId": "string",
        "ResourceArn": "string"
      }
    ],
    "NetworkFunctionGroupName": "string",
    "OwnerAccountId": "string",
    "ProposedNetworkFunctionGroupChange": {
      "AttachmentPolicyRuleNumber": number,
      "NetworkFunctionGroupName": "string",
      "Tags": [
        {
          "Key": "string",
          "Value": "string"
        }
      ]
    },
    "ProposedSegmentChange": {
      "AttachmentPolicyRuleNumber": number,
      "SegmentName": "string",
      "Tags": [
        {
          "Key": "string",
          "Value": "string"
        }
      ]
    },
    "ResourceArn": "string",
    "SegmentName": "string",
    "State": "string",
    "Tags": [
      {
        "Key": "string",
        "Value": "string"
      }
    ],
    "UpdatedAt": number
  },
  "PeeringId": "string",
  "TransitGatewayRouteTableArn": "string"
}

```

```
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

TransitGatewayRouteTableAttachment

Returns information about the transit gateway route table attachment.

Type: [TransitGatewayRouteTableAttachment](#) object

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

AccessDeniedException

You do not have sufficient access to perform this action.

HTTP Status Code: 403

InternalServerError

The request has failed due to an internal error.

RetryAfterSeconds

Indicates when to retry the request.

HTTP Status Code: 500

ResourceNotFoundException

The specified resource could not be found.

Context

The specified resource could not be found.

ResourceId

The ID of the resource.

ResourceType

The resource type.

HTTP Status Code: 404

ThrottlingException

The request was denied due to request throttling.

RetryAfterSeconds

Indicates when to retry the request.

HTTP Status Code: 429

ValidationException

The input fails to satisfy the constraints.

Fields

The fields that caused the error, if applicable.

Reason

The reason for the error.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)

- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

GetVpcAttachment

Returns information about a VPC attachment.

Request Syntax

```
GET /vpc-attachments/attachmentId HTTP/1.1
```

URI Request Parameters

The request uses the following URI parameters.

attachmentId

The ID of the attachment.

Length Constraints: Minimum length of 0. Maximum length of 50.

Pattern: ^attachment-([0-9a-f]{8,17})\$

Required: Yes

Request Body

The request does not have a request body.

Response Syntax

```
HTTP/1.1 200
Content-type: application/json

{
  "VpcAttachment": {
    "Attachment": {
      "AttachmentId": "string",
      "AttachmentPolicyRuleNumber": number,
      "AttachmentType": "string",
      "CoreNetworkArn": "string",
      "CoreNetworkId": "string",
      "CreatedAt": number,
      "EdgeLocation": "string",
      "EdgeLocations": [ "string" ],
```

```
"LastModificationErrors": [
  {
    "Code": "string",
    "Message": "string",
    "RequestId": "string",
    "ResourceArn": "string"
  }
],
"NetworkFunctionGroupName": "string",
"OwnerAccountId": "string",
"ProposedNetworkFunctionGroupChange": {
  "AttachmentPolicyRuleNumber": number,
  "NetworkFunctionGroupName": "string",
  "Tags": [
    {
      "Key": "string",
      "Value": "string"
    }
  ]
},
"ProposedSegmentChange": {
  "AttachmentPolicyRuleNumber": number,
  "SegmentName": "string",
  "Tags": [
    {
      "Key": "string",
      "Value": "string"
    }
  ]
},
"ResourceArn": "string",
"SegmentName": "string",
"State": "string",
"Tags": [
  {
    "Key": "string",
    "Value": "string"
  }
],
"UpdatedAt": number
},
"Options": {
  "ApplianceModeSupport": boolean,
  "DnsSupport": boolean,
```

```
    "Ipv6Support": boolean,
    "SecurityGroupReferencingSupport": boolean
  },
  "SubnetArns": [ "string" ]
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

VpcAttachment

Returns details about a VPC attachment.

Type: [VpcAttachment](#) object

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

AccessDeniedException

You do not have sufficient access to perform this action.

HTTP Status Code: 403

InternalServerError

The request has failed due to an internal error.

RetryAfterSeconds

Indicates when to retry the request.

HTTP Status Code: 500

ResourceNotFoundException

The specified resource could not be found.

Context

The specified resource could not be found.

ResourceId

The ID of the resource.

ResourceType

The resource type.

HTTP Status Code: 404

ThrottlingException

The request was denied due to request throttling.

RetryAfterSeconds

Indicates when to retry the request.

HTTP Status Code: 429

ValidationException

The input fails to satisfy the constraints.

Fields

The fields that caused the error, if applicable.

Reason

The reason for the error.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)

- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

ListAttachments

Returns a list of core network attachments.

Request Syntax

```
GET /attachments?  
attachmentType=AttachmentType&coreNetworkId=CoreNetworkId&edgeLocation=EdgeLocation&maxResults=  
HTTP/1.1
```

URI Request Parameters

The request uses the following URI parameters.

AttachmentType

The type of attachment.

Valid Values: CONNECT | SITE_TO_SITE_VPN | VPC | DIRECT_CONNECT_GATEWAY | TRANSIT_GATEWAY_ROUTE_TABLE

CoreNetworkId

The ID of a core network.

Length Constraints: Minimum length of 0. Maximum length of 50.

Pattern: ^core-network-([0-9a-f]{8,17})\$

EdgeLocation

The Region where the edge is located.

Length Constraints: Minimum length of 1. Maximum length of 63.

Pattern: [\\s\\S]*

MaxResults

The maximum number of results to return.

Valid Range: Minimum value of 1. Maximum value of 500.

NextToken

The token for the next page of results.

Length Constraints: Minimum length of 0. Maximum length of 2048.

Pattern: `[\s\S]*`

State

The state of the attachment.

Valid Values: REJECTED | PENDING_ATTACHMENT_ACCEPTANCE | CREATING | FAILED | AVAILABLE | UPDATING | PENDING_NETWORK_UPDATE | PENDING_TAG_ACCEPTANCE | DELETING

Request Body

The request does not have a request body.

Response Syntax

```
HTTP/1.1 200
Content-type: application/json

{
  "Attachments": [
    {
      "AttachmentId": "string",
      "AttachmentPolicyRuleNumber": number,
      "AttachmentType": "string",
      "CoreNetworkArn": "string",
      "CoreNetworkId": "string",
      "CreatedAt": number,
      "EdgeLocation": "string",
      "EdgeLocations": [ "string" ],
      "LastModificationErrors": [
        {
          "Code": "string",
          "Message": "string",
          "RequestId": "string",
          "ResourceArn": "string"
        }
      ],
      "NetworkFunctionGroupName": "string",
      "OwnerAccountId": "string",
      "ProposedNetworkFunctionGroupChange": {
```

```

    "AttachmentPolicyRuleNumber": number,
    "NetworkFunctionGroupName": "string",
    "Tags": [
      {
        "Key": "string",
        "Value": "string"
      }
    ],
  },
  "ProposedSegmentChange": {
    "AttachmentPolicyRuleNumber": number,
    "SegmentName": "string",
    "Tags": [
      {
        "Key": "string",
        "Value": "string"
      }
    ]
  },
  "ResourceArn": "string",
  "SegmentName": "string",
  "State": "string",
  "Tags": [
    {
      "Key": "string",
      "Value": "string"
    }
  ],
  "UpdatedAt": number
}
],
"NextToken": "string"
}

```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

Attachments

Describes the list of attachments.

Type: Array of [Attachment](#) objects

NextToken

The token for the next page of results.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 2048.

Pattern: `[\s\S]*`

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

AccessDeniedException

You do not have sufficient access to perform this action.

HTTP Status Code: 403

InternalServerError

The request has failed due to an internal error.

RetryAfterSeconds

Indicates when to retry the request.

HTTP Status Code: 500

ThrottlingException

The request was denied due to request throttling.

RetryAfterSeconds

Indicates when to retry the request.

HTTP Status Code: 429

ValidationException

The input fails to satisfy the constraints.

Fields

The fields that caused the error, if applicable.

Reason

The reason for the error.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

ListConnectPeers

Returns a list of core network Connect peers.

Request Syntax

```
GET /connect-peers?
connectAttachmentId=ConnectAttachmentId&coreNetworkId=CoreNetworkId&maxResults=MaxResults&nextToken=NextToken
HTTP/1.1
```

URI Request Parameters

The request uses the following URI parameters.

ConnectAttachmentId

The ID of the attachment.

Length Constraints: Minimum length of 0. Maximum length of 50.

Pattern: ^attachment-([0-9a-f]{8,17})\$

CoreNetworkId

The ID of a core network.

Length Constraints: Minimum length of 0. Maximum length of 50.

Pattern: ^core-network-([0-9a-f]{8,17})\$

MaxResults

The maximum number of results to return.

Valid Range: Minimum value of 1. Maximum value of 500.

NextToken

The token for the next page of results.

Length Constraints: Minimum length of 0. Maximum length of 2048.

Pattern: `[\s\S]*`

Request Body

The request does not have a request body.

Response Syntax

```
HTTP/1.1 200
Content-type: application/json

{
  "ConnectPeers": [
    {
      "ConnectAttachmentId": "string",
      "ConnectPeerId": "string",
      "ConnectPeerState": "string",
      "CoreNetworkId": "string",
      "CreatedAt": number,
      "EdgeLocation": "string",
      "SubnetArn": "string",
      "Tags": [
        {
          "Key": "string",
          "Value": "string"
        }
      ]
    }
  ],
  "NextToken": "string"
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

ConnectPeers

Describes the Connect peers.

Type: Array of [ConnectPeerSummary](#) objects

NextToken

The token for the next page of results.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 2048.

Pattern: `[\s\S]*`

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

AccessDeniedException

You do not have sufficient access to perform this action.

HTTP Status Code: 403

InternalServerError

The request has failed due to an internal error.

RetryAfterSeconds

Indicates when to retry the request.

HTTP Status Code: 500

ThrottlingException

The request was denied due to request throttling.

RetryAfterSeconds

Indicates when to retry the request.

HTTP Status Code: 429

ValidationException

The input fails to satisfy the constraints.

Fields

The fields that caused the error, if applicable.

Reason

The reason for the error.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

ListCoreNetworkPolicyVersions

Returns a list of core network policy versions.

Request Syntax

```
GET /core-networks/coreNetworkId/core-network-policy-versions?  
maxResults=MaxResults&nextToken=NextToken HTTP/1.1
```

URI Request Parameters

The request uses the following URI parameters.

coreNetworkId

The ID of a core network.

Length Constraints: Minimum length of 0. Maximum length of 50.

Pattern: `^core-network-([0-9a-f]{8,17})$`

Required: Yes

MaxResults

The maximum number of results to return.

Valid Range: Minimum value of 1. Maximum value of 500.

NextToken

The token for the next page of results.

Length Constraints: Minimum length of 0. Maximum length of 2048.

Pattern: `[\s\S]*`

Request Body

The request does not have a request body.

Response Syntax

```
HTTP/1.1 200
Content-type: application/json

{
  "CoreNetworkPolicyVersions": [
    {
      "Alias": "string",
      "ChangeSetState": "string",
      "CoreNetworkId": "string",
      "CreatedAt": number,
      "Description": "string",
      "PolicyVersionId": number
    }
  ],
  "NextToken": "string"
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

CoreNetworkPolicyVersions

Describes core network policy versions.

Type: Array of [CoreNetworkPolicyVersion](#) objects

NextToken

The token for the next page of results.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 2048.

Pattern: `[\s\S]*`

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

AccessDeniedException

You do not have sufficient access to perform this action.

HTTP Status Code: 403

InternalServerError

The request has failed due to an internal error.

RetryAfterSeconds

Indicates when to retry the request.

HTTP Status Code: 500

ResourceNotFoundException

The specified resource could not be found.

Context

The specified resource could not be found.

ResourceId

The ID of the resource.

ResourceType

The resource type.

HTTP Status Code: 404

ThrottlingException

The request was denied due to request throttling.

RetryAfterSeconds

Indicates when to retry the request.

HTTP Status Code: 429

ValidationException

The input fails to satisfy the constraints.

Fields

The fields that caused the error, if applicable.

Reason

The reason for the error.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

ListCoreNetworks

Returns a list of owned and shared core networks.

Request Syntax

```
GET /core-networks?maxResults=MaxResults&nextToken=NextToken HTTP/1.1
```

URI Request Parameters

The request uses the following URI parameters.

MaxResults

The maximum number of results to return.

Valid Range: Minimum value of 1. Maximum value of 500.

NextToken

The token for the next page of results.

Length Constraints: Minimum length of 0. Maximum length of 2048.

Pattern: `[\s\S]*`

Request Body

The request does not have a request body.

Response Syntax

```
HTTP/1.1 200
Content-type: application/json

{
  "CoreNetworks": [
    {
      "CoreNetworkArn": "string",
      "CoreNetworkId": "string",
      "Description": "string",
```

```
"GlobalNetworkId": "string",
"OwnerAccountId": "string",
"State": "string",
"Tags": [
  {
    "Key": "string",
    "Value": "string"
  }
],
"NextToken": "string"
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

CoreNetworks

Describes the list of core networks.

Type: Array of [CoreNetworkSummary](#) objects

NextToken

The token for the next page of results.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 2048.

Pattern: `[\s\S]*`

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

AccessDeniedException

You do not have sufficient access to perform this action.

HTTP Status Code: 403

InternalServerError

The request has failed due to an internal error.

RetryAfterSeconds

Indicates when to retry the request.

HTTP Status Code: 500

ThrottlingException

The request was denied due to request throttling.

RetryAfterSeconds

Indicates when to retry the request.

HTTP Status Code: 429

ValidationException

The input fails to satisfy the constraints.

Fields

The fields that caused the error, if applicable.

Reason

The reason for the error.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)

- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

ListOrganizationServiceAccessStatus

Gets the status of the Service Linked Role (SLR) deployment for the accounts in a given Amazon Web Services Organization.

Request Syntax

```
GET /organizations/service-access?maxResults=MaxResults&nextToken=NextToken HTTP/1.1
```

URI Request Parameters

The request uses the following URI parameters.

MaxResults

The maximum number of results to return.

Valid Range: Minimum value of 1. Maximum value of 500.

NextToken

The token for the next page of results.

Length Constraints: Minimum length of 0. Maximum length of 2048.

Pattern: `[\s\S]*`

Request Body

The request does not have a request body.

Response Syntax

```
HTTP/1.1 200
Content-type: application/json

{
  "NextToken": "string",
  "OrganizationStatus": {
    "AccountStatusList": [
      {
```

```
        "AccountId": "string",
        "SLRDeploymentStatus": "string"
    },
    ],
    "OrganizationAwsServiceAccessStatus": "string",
    "OrganizationId": "string",
    "SLRDeploymentStatus": "string"
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

NextToken

The token for the next page of results.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 2048.

Pattern: `[\s\S]*`

OrganizationStatus

Displays the status of an Amazon Web Services Organization.

Type: [OrganizationStatus](#) object

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)

- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

ListPeerings

Lists the peerings for a core network.

Request Syntax

```
GET /peerings?  
coreNetworkId=CoreNetworkId&edgeLocation=EdgeLocation&maxResults=MaxResults&nextToken=NextToken  
HTTP/1.1
```

URI Request Parameters

The request uses the following URI parameters.

CoreNetworkId

The ID of a core network.

Length Constraints: Minimum length of 0. Maximum length of 50.

Pattern: `^core-network-([0-9a-f]{8,17})$`

EdgeLocation

Returns a list edge locations for the

Length Constraints: Minimum length of 1. Maximum length of 63.

Pattern: `[\s\S]*`

MaxResults

The maximum number of results to return.

Valid Range: Minimum value of 1. Maximum value of 500.

NextToken

The token for the next page of results.

Length Constraints: Minimum length of 0. Maximum length of 2048.

Pattern: `[\s\S]*`

PeeringType

Returns a list of a peering requests.

Valid Values: TRANSIT_GATEWAY

State

Returns a list of the peering request states.

Valid Values: CREATING | FAILED | AVAILABLE | DELETING

Request Body

The request does not have a request body.

Response Syntax

```
HTTP/1.1 200
Content-type: application/json

{
  "NextToken": "string",
  "Peerings": [
    {
      "CoreNetworkArn": "string",
      "CoreNetworkId": "string",
      "CreatedAt": number,
      "EdgeLocation": "string",
      "LastModificationErrors": [
        {
          "Code": "string",
          "Message": "string",
          "MissingPermissionsContext": {
            "MissingPermission": "string"
          },
          "RequestId": "string",
          "ResourceArn": "string"
        }
      ],
      "OwnerAccountId": "string",
      "PeeringId": "string",
      "PeeringType": "string",
```

```
    "ResourceArn": "string",
    "State": "string",
    "Tags": [
      {
        "Key": "string",
        "Value": "string"
      }
    ]
  }
]
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

NextToken

The token for the next page of results.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 2048.

Pattern: `[\s\S]*`

Peerings

Lists the transit gateway peerings for the `ListPeerings` request.

Type: Array of [Peering](#) objects

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

AccessDeniedException

You do not have sufficient access to perform this action.

HTTP Status Code: 403

InternalServerError

The request has failed due to an internal error.

RetryAfterSeconds

Indicates when to retry the request.

HTTP Status Code: 500

ThrottlingException

The request was denied due to request throttling.

RetryAfterSeconds

Indicates when to retry the request.

HTTP Status Code: 429

ValidationException

The input fails to satisfy the constraints.

Fields

The fields that caused the error, if applicable.

Reason

The reason for the error.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)

- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

ListTagsForResource

Lists the tags for a specified resource.

Request Syntax

```
GET /tags/resourceArn HTTP/1.1
```

URI Request Parameters

The request uses the following URI parameters.

resourceArn

The Amazon Resource Name (ARN) of the resource.

Length Constraints: Minimum length of 0. Maximum length of 1500.

Pattern: `[\s\S]*`

Required: Yes

Request Body

The request does not have a request body.

Response Syntax

```
HTTP/1.1 200
Content-type: application/json
```

```
{
  "TagList": [
    {
      "Key": "string",
      "Value": "string"
    }
  ]
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

TagList

The list of tags.

Type: Array of [Tag](#) objects

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

AccessDeniedException

You do not have sufficient access to perform this action.

HTTP Status Code: 403

InternalServerError

The request has failed due to an internal error.

RetryAfterSeconds

Indicates when to retry the request.

HTTP Status Code: 500

ResourceNotFoundException

The specified resource could not be found.

Context

The specified resource could not be found.

ResourceId

The ID of the resource.

ResourceType

The resource type.

HTTP Status Code: 404

ThrottlingException

The request was denied due to request throttling.

RetryAfterSeconds

Indicates when to retry the request.

HTTP Status Code: 429

ValidationException

The input fails to satisfy the constraints.

Fields

The fields that caused the error, if applicable.

Reason

The reason for the error.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

PutCoreNetworkPolicy

Creates a new, immutable version of a core network policy. A subsequent change set is created showing the differences between the LIVE policy and the submitted policy.

Request Syntax

```
POST /core-networks/coreNetworkId/core-network-policy HTTP/1.1
Content-type: application/json
```

```
{
  "ClientToken": "string",
  "Description": "string",
  "LatestVersionId": number,
  "PolicyDocument": "string"
}
```

URI Request Parameters

The request uses the following URI parameters.

coreNetworkId

The ID of a core network.

Length Constraints: Minimum length of 0. Maximum length of 50.

Pattern: ^core-network-([0-9a-f]{8,17})\$

Required: Yes

Request Body

The request accepts the following data in JSON format.

ClientToken

The client token associated with the request.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 256.

Pattern: `[\s\S]*`

Required: No

Description

a core network policy description.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 256.

Pattern: `[\s\S]*`

Required: No

LatestVersionId

The ID of a core network policy.

Type: Integer

Required: No

PolicyDocument

The policy document.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 10000000.

Pattern: `[\s\S]*`

Required: Yes

Response Syntax

```
HTTP/1.1 200
Content-type: application/json

{
  "CoreNetworkPolicy": {
```



```
"Alias": "string",
"ChangeSetState": "string",
"CoreNetworkId": "string",
"CreatedAt": number,
"Description": "string",
"PolicyDocument": "string",
"PolicyErrors": [
  {
    "ErrorCode": "string",
    "Message": "string",
    "Path": "string"
  }
],
"PolicyVersionId": number
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

CoreNetworkPolicy

Describes the changed core network policy.

Type: [CoreNetworkPolicy](#) object

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

AccessDeniedException

You do not have sufficient access to perform this action.

HTTP Status Code: 403

ConflictException

There was a conflict processing the request. Updating or deleting the resource can cause an inconsistent state.

ResourceId

The ID of the resource.

ResourceType

The resource type.

HTTP Status Code: 409

CoreNetworkPolicyException

Describes a core network policy exception.

Errors

Describes a core network policy exception.

HTTP Status Code: 400

InternalServerError

The request has failed due to an internal error.

RetryAfterSeconds

Indicates when to retry the request.

HTTP Status Code: 500

ResourceNotFoundException

The specified resource could not be found.

Context

The specified resource could not be found.

ResourceId

The ID of the resource.

ResourceType

The resource type.

HTTP Status Code: 404

ThrottlingException

The request was denied due to request throttling.

RetryAfterSeconds

Indicates when to retry the request.

HTTP Status Code: 429

ValidationException

The input fails to satisfy the constraints.

Fields

The fields that caused the error, if applicable.

Reason

The reason for the error.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

PutResourcePolicy

Creates or updates a resource policy.

Request Syntax

```
POST /resource-policy/resourceArn HTTP/1.1
Content-type: application/json

{
  "PolicyDocument": "string"
}
```

URI Request Parameters

The request uses the following URI parameters.

resourceArn

The ARN of the resource policy.

Length Constraints: Minimum length of 0. Maximum length of 1500.

Pattern: `[\s\S]*`

Required: Yes

Request Body

The request accepts the following data in JSON format.

PolicyDocument

The JSON resource policy document.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 10000000.

Pattern: `[\s\S]*`

Required: Yes

Response Syntax

```
HTTP/1.1 200
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response with an empty HTTP body.

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

AccessDeniedException

You do not have sufficient access to perform this action.

HTTP Status Code: 403

ConflictException

There was a conflict processing the request. Updating or deleting the resource can cause an inconsistent state.

ResourceId

The ID of the resource.

ResourceType

The resource type.

HTTP Status Code: 409

InternalServerError

The request has failed due to an internal error.

RetryAfterSeconds

Indicates when to retry the request.

HTTP Status Code: 500

ServiceQuotaExceededException

A service limit was exceeded.

LimitCode

The limit code.

Message

The error message.

ResourceId

The ID of the resource.

ResourceType

The resource type.

ServiceCode

The service code.

HTTP Status Code: 402

ThrottlingException

The request was denied due to request throttling.

RetryAfterSeconds

Indicates when to retry the request.

HTTP Status Code: 429

ValidationException

The input fails to satisfy the constraints.

Fields

The fields that caused the error, if applicable.

Reason

The reason for the error.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

RegisterTransitGateway

Registers a transit gateway in your global network. Not all Regions support transit gateways for global networks. For a list of the supported Regions, see [Region Availability](#) in the *AWS Transit Gateways for Global Networks User Guide*. The transit gateway can be in any of the supported AWS Regions, but it must be owned by the same AWS account that owns the global network. You cannot register a transit gateway in more than one global network.

Request Syntax

```
POST /global-networks/globalNetworkId/transit-gateway-registrations HTTP/1.1
Content-type: application/json
```

```
{
  "TransitGatewayArn": "string"
}
```

URI Request Parameters

The request uses the following URI parameters.

[globalNetworkId](#)

The ID of the global network.

Length Constraints: Minimum length of 0. Maximum length of 50.

Pattern: `[\s\S]*`

Required: Yes

Request Body

The request accepts the following data in JSON format.

[TransitGatewayArn](#)

The Amazon Resource Name (ARN) of the transit gateway.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 500.

Pattern: `[\s\S]*`

Required: Yes

Response Syntax

```
HTTP/1.1 200
Content-type: application/json

{
  "TransitGatewayRegistration": {
    "GlobalNetworkId": "string",
    "State": {
      "Code": "string",
      "Message": "string"
    },
    "TransitGatewayArn": "string"
  }
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

TransitGatewayRegistration

Information about the transit gateway registration.

Type: [TransitGatewayRegistration](#) object

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

AccessDeniedException

You do not have sufficient access to perform this action.

HTTP Status Code: 403

ConflictException

There was a conflict processing the request. Updating or deleting the resource can cause an inconsistent state.

ResourceId

The ID of the resource.

ResourceType

The resource type.

HTTP Status Code: 409

InternalServerErrorException

The request has failed due to an internal error.

RetryAfterSeconds

Indicates when to retry the request.

HTTP Status Code: 500

ResourceNotFoundException

The specified resource could not be found.

Context

The specified resource could not be found.

ResourceId

The ID of the resource.

ResourceType

The resource type.

HTTP Status Code: 404

ThrottlingException

The request was denied due to request throttling.

RetryAfterSeconds

Indicates when to retry the request.

HTTP Status Code: 429

ValidationException

The input fails to satisfy the constraints.

Fields

The fields that caused the error, if applicable.

Reason

The reason for the error.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

RejectAttachment

Rejects a core network attachment request.

Request Syntax

```
POST /attachments/attachmentId/reject HTTP/1.1
```

URI Request Parameters

The request uses the following URI parameters.

attachmentId

The ID of the attachment.

Length Constraints: Minimum length of 0. Maximum length of 50.

Pattern: ^attachment-([0-9a-f]{8,17})\$

Required: Yes

Request Body

The request does not have a request body.

Response Syntax

```
HTTP/1.1 200
```

```
Content-type: application/json
```

```
{
  "Attachment": {
    "AttachmentId": "string",
    "AttachmentPolicyRuleNumber": number,
    "AttachmentType": "string",
    "CoreNetworkArn": "string",
    "CoreNetworkId": "string",
    "CreatedAt": number,
    "EdgeLocation": "string",
    "EdgeLocations": [ "string" ],
    "LastModificationErrors": [
```

```

    {
      "Code": "string",
      "Message": "string",
      "RequestId": "string",
      "ResourceArn": "string"
    }
  ],
  "NetworkFunctionGroupName": "string",
  "OwnerAccountId": "string",
  "ProposedNetworkFunctionGroupChange": {
    "AttachmentPolicyRuleNumber": number,
    "NetworkFunctionGroupName": "string",
    "Tags": [
      {
        "Key": "string",
        "Value": "string"
      }
    ]
  },
  "ProposedSegmentChange": {
    "AttachmentPolicyRuleNumber": number,
    "SegmentName": "string",
    "Tags": [
      {
        "Key": "string",
        "Value": "string"
      }
    ]
  },
  "ResourceArn": "string",
  "SegmentName": "string",
  "State": "string",
  "Tags": [
    {
      "Key": "string",
      "Value": "string"
    }
  ],
  "UpdatedAt": number
}

```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

Attachment

Describes the rejected attachment request.

Type: [Attachment](#) object

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

AccessDeniedException

You do not have sufficient access to perform this action.

HTTP Status Code: 403

ConflictException

There was a conflict processing the request. Updating or deleting the resource can cause an inconsistent state.

ResourceId

The ID of the resource.

ResourceType

The resource type.

HTTP Status Code: 409

InternalServerError

The request has failed due to an internal error.

RetryAfterSeconds

Indicates when to retry the request.

HTTP Status Code: 500

ResourceNotFoundException

The specified resource could not be found.

Context

The specified resource could not be found.

ResourceId

The ID of the resource.

ResourceType

The resource type.

HTTP Status Code: 404

ThrottlingException

The request was denied due to request throttling.

RetryAfterSeconds

Indicates when to retry the request.

HTTP Status Code: 429

ValidationException

The input fails to satisfy the constraints.

Fields

The fields that caused the error, if applicable.

Reason

The reason for the error.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

RestoreCoreNetworkPolicyVersion

Restores a previous policy version as a new, immutable version of a core network policy. A subsequent change set is created showing the differences between the LIVE policy and restored policy.

Request Syntax

```
POST /core-networks/coreNetworkId/core-network-policy-versions/policyVersionId/restore
HTTP/1.1
```

URI Request Parameters

The request uses the following URI parameters.

coreNetworkId

The ID of a core network.

Length Constraints: Minimum length of 0. Maximum length of 50.

Pattern: `^core-network-([0-9a-f]{8,17})$`

Required: Yes

policyVersionId

The ID of the policy version to restore.

Required: Yes

Request Body

The request does not have a request body.

Response Syntax

```
HTTP/1.1 200
Content-type: application/json

{
  "CoreNetworkPolicy": {
```

```
"Alias": "string",
"ChangeSetState": "string",
"CoreNetworkId": "string",
"CreatedAt": number,
"Description": "string",
"PolicyDocument": "string",
"PolicyErrors": [
  {
    "ErrorCode": "string",
    "Message": "string",
    "Path": "string"
  }
],
"PolicyVersionId": number
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

CoreNetworkPolicy

Describes the restored core network policy.

Type: [CoreNetworkPolicy](#) object

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

AccessDeniedException

You do not have sufficient access to perform this action.

HTTP Status Code: 403

ConflictException

There was a conflict processing the request. Updating or deleting the resource can cause an inconsistent state.

ResourceId

The ID of the resource.

ResourceType

The resource type.

HTTP Status Code: 409

InternalServerError

The request has failed due to an internal error.

RetryAfterSeconds

Indicates when to retry the request.

HTTP Status Code: 500

ResourceNotFoundException

The specified resource could not be found.

Context

The specified resource could not be found.

ResourceId

The ID of the resource.

ResourceType

The resource type.

HTTP Status Code: 404

ThrottlingException

The request was denied due to request throttling.

RetryAfterSeconds

Indicates when to retry the request.

HTTP Status Code: 429

ValidationException

The input fails to satisfy the constraints.

Fields

The fields that caused the error, if applicable.

Reason

The reason for the error.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

StartOrganizationServiceAccessUpdate

Enables the Network Manager service for an Amazon Web Services Organization. This can only be called by a management account within the organization.

Request Syntax

```
POST /organizations/service-access HTTP/1.1
Content-type: application/json

{
  "Action": "string"
}
```

URI Request Parameters

The request does not use any URI parameters.

Request Body

The request accepts the following data in JSON format.

[Action](#)

The action to take for the update request. This can be either ENABLE or DISABLE.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 50.

Required: Yes

Response Syntax

```
HTTP/1.1 200
Content-type: application/json

{
  "OrganizationStatus": {
    "AccountStatusList": [
      {
```

```
        "AccountId": "string",
        "SLRDeploymentStatus": "string"
    },
    ],
    "OrganizationAwsServiceAccessStatus": "string",
    "OrganizationId": "string",
    "SLRDeploymentStatus": "string"
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

OrganizationStatus

The status of the service access update request for an Amazon Web Services Organization.

Type: [OrganizationStatus](#) object

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

AccessDeniedException

You do not have sufficient access to perform this action.

HTTP Status Code: 403

ConflictException

There was a conflict processing the request. Updating or deleting the resource can cause an inconsistent state.

ResourceId

The ID of the resource.

ResourceType

The resource type.

HTTP Status Code: 409

InternalServerError

The request has failed due to an internal error.

RetryAfterSeconds

Indicates when to retry the request.

HTTP Status Code: 500

ServiceQuotaExceededException

A service limit was exceeded.

LimitCode

The limit code.

Message

The error message.

ResourceId

The ID of the resource.

ResourceType

The resource type.

ServiceCode

The service code.

HTTP Status Code: 402

ThrottlingException

The request was denied due to request throttling.

RetryAfterSeconds

Indicates when to retry the request.

HTTP Status Code: 429

ValidationException

The input fails to satisfy the constraints.

Fields

The fields that caused the error, if applicable.

Reason

The reason for the error.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

StartRouteAnalysis

Starts analyzing the routing path between the specified source and destination. For more information, see [Route Analyzer](#).

Request Syntax

```
POST /global-networks/globalNetworkId/route-analyses HTTP/1.1
Content-type: application/json
```

```
{
  "Destination": {
    "IpAddress": "string",
    "TransitGatewayAttachmentArn": "string"
  },
  "IncludeReturnPath": boolean,
  "Source": {
    "IpAddress": "string",
    "TransitGatewayAttachmentArn": "string"
  },
  "UseMiddleboxes": boolean
}
```

URI Request Parameters

The request uses the following URI parameters.

globalNetworkId

The ID of the global network.

Length Constraints: Minimum length of 0. Maximum length of 50.

Pattern: `[\s\S]*`

Required: Yes

Request Body

The request accepts the following data in JSON format.

Destination

The destination.

Type: [RouteAnalysisEndpointOptionsSpecification](#) object

Required: Yes

IncludeReturnPath

Indicates whether to analyze the return path. The default is false.

Type: Boolean

Required: No

Source

The source from which traffic originates.

Type: [RouteAnalysisEndpointOptionsSpecification](#) object

Required: Yes

UseMiddleboxes

Indicates whether to include the location of middlebox appliances in the route analysis. The default is false.

Type: Boolean

Required: No

Response Syntax

```
HTTP/1.1 200
Content-type: application/json

{
  "RouteAnalysis": {
    "Destination": {
      "IpAddress": "string",
      "TransitGatewayArn": "string",
      "TransitGatewayAttachmentArn": "string"
    },
    "ForwardPath": {
```

```

    "CompletionStatus": {
      "ReasonCode": "string",
      "ReasonContext": {
        "string" : "string"
      },
      "ResultCode": "string"
    },
    "Path": [
      {
        "DestinationCidrBlock": "string",
        "Resource": {
          "Definition": "string",
          "IsMiddlebox": boolean,
          "NameTag": "string",
          "RegisteredGatewayArn": "string",
          "ResourceArn": "string",
          "ResourceType": "string"
        },
        "Sequence": number
      }
    ]
  },
  "GlobalNetworkId": "string",
  "IncludeReturnPath": boolean,
  "OwnerAccountId": "string",
  "ReturnPath": {
    "CompletionStatus": {
      "ReasonCode": "string",
      "ReasonContext": {
        "string" : "string"
      },
      "ResultCode": "string"
    },
    "Path": [
      {
        "DestinationCidrBlock": "string",
        "Resource": {
          "Definition": "string",
          "IsMiddlebox": boolean,
          "NameTag": "string",
          "RegisteredGatewayArn": "string",
          "ResourceArn": "string",
          "ResourceType": "string"
        },

```

```
        "Sequence": number
      }
    ]
  },
  "RouteAnalysisId": "string",
  "Source": {
    "IpAddress": "string",
    "TransitGatewayArn": "string",
    "TransitGatewayAttachmentArn": "string"
  },
  "StartTimestamp": number,
  "Status": "string",
  "UseMiddleboxes": boolean
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

[RouteAnalysis](#)

The route analysis.

Type: [RouteAnalysis](#) object

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

AccessDeniedException

You do not have sufficient access to perform this action.

HTTP Status Code: 403

ConflictException

There was a conflict processing the request. Updating or deleting the resource can cause an inconsistent state.

ResourceId

The ID of the resource.

ResourceType

The resource type.

HTTP Status Code: 409

InternalServerError

The request has failed due to an internal error.

RetryAfterSeconds

Indicates when to retry the request.

HTTP Status Code: 500

ResourceNotFoundException

The specified resource could not be found.

Context

The specified resource could not be found.

ResourceId

The ID of the resource.

ResourceType

The resource type.

HTTP Status Code: 404

ThrottlingException

The request was denied due to request throttling.

RetryAfterSeconds

Indicates when to retry the request.

HTTP Status Code: 429

ValidationException

The input fails to satisfy the constraints.

Fields

The fields that caused the error, if applicable.

Reason

The reason for the error.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

TagResource

Tags a specified resource.

Request Syntax

```
POST /tags/resourceArn HTTP/1.1
Content-type: application/json
```

```
{
  "Tags": [
    {
      "Key": "string",
      "Value": "string"
    }
  ]
}
```

URI Request Parameters

The request uses the following URI parameters.

resourceArn

The Amazon Resource Name (ARN) of the resource.

Length Constraints: Minimum length of 0. Maximum length of 1500.

Pattern: `[\s\S]*`

Required: Yes

Request Body

The request accepts the following data in JSON format.

Tags

The tags to apply to the specified resource.

Type: Array of [Tag](#) objects

Required: Yes

Response Syntax

```
HTTP/1.1 200
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response with an empty HTTP body.

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

AccessDeniedException

You do not have sufficient access to perform this action.

HTTP Status Code: 403

ConflictException

There was a conflict processing the request. Updating or deleting the resource can cause an inconsistent state.

ResourceId

The ID of the resource.

ResourceType

The resource type.

HTTP Status Code: 409

InternalServerError

The request has failed due to an internal error.

RetryAfterSeconds

Indicates when to retry the request.

HTTP Status Code: 500

ResourceNotFoundException

The specified resource could not be found.

Context

The specified resource could not be found.

ResourceId

The ID of the resource.

ResourceType

The resource type.

HTTP Status Code: 404

ServiceQuotaExceededException

A service limit was exceeded.

LimitCode

The limit code.

Message

The error message.

ResourceId

The ID of the resource.

ResourceType

The resource type.

ServiceCode

The service code.

HTTP Status Code: 402

ThrottlingException

The request was denied due to request throttling.

RetryAfterSeconds

Indicates when to retry the request.

HTTP Status Code: 429

ValidationException

The input fails to satisfy the constraints.

Fields

The fields that caused the error, if applicable.

Reason

The reason for the error.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

UntagResource

Removes tags from a specified resource.

Request Syntax

```
DELETE /tags/resourceArn?tagKeys=TagKeys HTTP/1.1
```

URI Request Parameters

The request uses the following URI parameters.

resourceArn

The Amazon Resource Name (ARN) of the resource.

Length Constraints: Minimum length of 0. Maximum length of 1500.

Pattern: `[\s\S]*`

Required: Yes

TagKeys

The tag keys to remove from the specified resource.

Length Constraints: Minimum length of 0. Maximum length of 10000000.

Pattern: `[\s\S]*`

Required: Yes

Request Body

The request does not have a request body.

Response Syntax

```
HTTP/1.1 200
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response with an empty HTTP body.

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

AccessDeniedException

You do not have sufficient access to perform this action.

HTTP Status Code: 403

ConflictException

There was a conflict processing the request. Updating or deleting the resource can cause an inconsistent state.

ResourceId

The ID of the resource.

ResourceType

The resource type.

HTTP Status Code: 409

InternalServerError

The request has failed due to an internal error.

RetryAfterSeconds

Indicates when to retry the request.

HTTP Status Code: 500

ResourceNotFoundException

The specified resource could not be found.

Context

The specified resource could not be found.

ResourceId

The ID of the resource.

ResourceType

The resource type.

HTTP Status Code: 404

ThrottlingException

The request was denied due to request throttling.

RetryAfterSeconds

Indicates when to retry the request.

HTTP Status Code: 429

ValidationException

The input fails to satisfy the constraints.

Fields

The fields that caused the error, if applicable.

Reason

The reason for the error.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)

- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

UpdateConnection

Updates the information for an existing connection. To remove information for any of the parameters, specify an empty string.

Request Syntax

```
PATCH /global-networks/globalNetworkId/connections/connectionId HTTP/1.1
Content-type: application/json
```

```
{
  "ConnectedLinkId": "string",
  "Description": "string",
  "LinkId": "string"
}
```

URI Request Parameters

The request uses the following URI parameters.

connectionId

The ID of the connection.

Length Constraints: Minimum length of 0. Maximum length of 50.

Pattern: `[\s\S]*`

Required: Yes

globalNetworkId

The ID of the global network.

Length Constraints: Minimum length of 0. Maximum length of 50.

Pattern: `[\s\S]*`

Required: Yes

Request Body

The request accepts the following data in JSON format.

ConnectedLinkId

The ID of the link for the second device in the connection.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 50.

Pattern: `[\s\S]*`

Required: No

Description

A description of the connection.

Length Constraints: Maximum length of 256 characters.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 256.

Pattern: `[\s\S]*`

Required: No

LinkId

The ID of the link for the first device in the connection.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 50.

Pattern: `[\s\S]*`

Required: No

Response Syntax

```
HTTP/1.1 200
Content-type: application/json
```



```
{
  "Connection": {
    "ConnectedDeviceId": "string",
    "ConnectedLinkId": "string",
    "ConnectionArn": "string",
    "ConnectionId": "string",
    "CreatedAt": number,
    "Description": "string",
    "DeviceId": "string",
    "GlobalNetworkId": "string",
    "LinkId": "string",
    "State": "string",
    "Tags": [
      {
        "Key": "string",
        "Value": "string"
      }
    ]
  }
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

Connection

Information about the connection.

Type: [Connection](#) object

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

AccessDeniedException

You do not have sufficient access to perform this action.

HTTP Status Code: 403

ConflictException

There was a conflict processing the request. Updating or deleting the resource can cause an inconsistent state.

ResourceId

The ID of the resource.

ResourceType

The resource type.

HTTP Status Code: 409

InternalServerErrorException

The request has failed due to an internal error.

RetryAfterSeconds

Indicates when to retry the request.

HTTP Status Code: 500

ResourceNotFoundException

The specified resource could not be found.

Context

The specified resource could not be found.

ResourceId

The ID of the resource.

ResourceType

The resource type.

HTTP Status Code: 404

ThrottlingException

The request was denied due to request throttling.

RetryAfterSeconds

Indicates when to retry the request.

HTTP Status Code: 429

ValidationException

The input fails to satisfy the constraints.

Fields

The fields that caused the error, if applicable.

Reason

The reason for the error.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

UpdateCoreNetwork

Updates the description of a core network.

Request Syntax

```
PATCH /core-networks/coreNetworkId HTTP/1.1
Content-type: application/json

{
  "Description": "string"
}
```

URI Request Parameters

The request uses the following URI parameters.

coreNetworkId

The ID of a core network.

Length Constraints: Minimum length of 0. Maximum length of 50.

Pattern: ^core-network-([0-9a-f]{8,17})\$

Required: Yes

Request Body

The request accepts the following data in JSON format.

Description

The description of the update.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 256.

Pattern: [\\s\\S]*

Required: No

Response Syntax

HTTP/1.1 200

Content-type: application/json

```
{
  "CoreNetwork": {
    "CoreNetworkArn": "string",
    "CoreNetworkId": "string",
    "CreatedAt": number,
    "Description": "string",
    "Edges": [
      {
        "Asn": number,
        "EdgeLocation": "string",
        "InsideCidrBlocks": [ "string" ]
      }
    ],
    "GlobalNetworkId": "string",
    "NetworkFunctionGroups": [
      {
        "EdgeLocations": [ "string" ],
        "Name": "string",
        "Segments": {
          "SendTo": [ "string" ],
          "SendVia": [ "string" ]
        }
      }
    ],
    "Segments": [
      {
        "EdgeLocations": [ "string" ],
        "Name": "string",
        "SharedSegments": [ "string" ]
      }
    ],
    "State": "string",
    "Tags": [
      {
        "Key": "string",
        "Value": "string"
      }
    ]
  }
}
```

```
}  
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

CoreNetwork

Returns information about a core network update.

Type: [CoreNetwork](#) object

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

AccessDeniedException

You do not have sufficient access to perform this action.

HTTP Status Code: 403

ConflictException

There was a conflict processing the request. Updating or deleting the resource can cause an inconsistent state.

ResourceId

The ID of the resource.

ResourceType

The resource type.

HTTP Status Code: 409

InternalServerError

The request has failed due to an internal error.

RetryAfterSeconds

Indicates when to retry the request.

HTTP Status Code: 500

ResourceNotFoundException

The specified resource could not be found.

Context

The specified resource could not be found.

ResourceId

The ID of the resource.

ResourceType

The resource type.

HTTP Status Code: 404

ThrottlingException

The request was denied due to request throttling.

RetryAfterSeconds

Indicates when to retry the request.

HTTP Status Code: 429

ValidationException

The input fails to satisfy the constraints.

Fields

The fields that caused the error, if applicable.

Reason

The reason for the error.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

UpdateDevice

Updates the details for an existing device. To remove information for any of the parameters, specify an empty string.

Request Syntax

```
PATCH /global-networks/globalNetworkId/devices/deviceId HTTP/1.1
Content-type: application/json
```

```
{
  "AWSLocation": {
    "SubnetArn": "string",
    "Zone": "string"
  },
  "Description": "string",
  "Location": {
    "Address": "string",
    "Latitude": "string",
    "Longitude": "string"
  },
  "Model": "string",
  "SerialNumber": "string",
  "SiteId": "string",
  "Type": "string",
  "Vendor": "string"
}
```

URI Request Parameters

The request uses the following URI parameters.

deviceId

The ID of the device.

Length Constraints: Minimum length of 0. Maximum length of 50.

Pattern: `[\s\S]*`

Required: Yes

globalNetworkId

The ID of the global network.

Length Constraints: Minimum length of 0. Maximum length of 50.

Pattern: `[\s\S]*`

Required: Yes

Request Body

The request accepts the following data in JSON format.

AWSLocation

The AWS location of the device, if applicable. For an on-premises device, you can omit this parameter.

Type: [AWSLocation](#) object

Required: No

Description

A description of the device.

Constraints: Maximum length of 256 characters.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 256.

Pattern: `[\s\S]*`

Required: No

Location

Describes a location.

Type: [Location](#) object

Required: No

Model

The model of the device.

Constraints: Maximum length of 128 characters.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 256.

Pattern: `[\s\S]*`

Required: No

SerialNumber

The serial number of the device.

Constraints: Maximum length of 128 characters.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 256.

Pattern: `[\s\S]*`

Required: No

Siteld

The ID of the site.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 50.

Pattern: `[\s\S]*`

Required: No

Type

The type of the device.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 256.

Pattern: `[\s\S]*`

Required: No

Vendor

The vendor of the device.

Constraints: Maximum length of 128 characters.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 256.

Pattern: `[\s\S]*`

Required: No

Response Syntax

HTTP/1.1 200

Content-type: application/json

```
{
  "Device": {
    "AWSLocation": {
      "SubnetArn": "string",
      "Zone": "string"
    },
    "CreatedAt": number,
    "Description": "string",
    "DeviceArn": "string",
    "DeviceId": "string",
    "GlobalNetworkId": "string",
    "Location": {
      "Address": "string",
      "Latitude": "string",
      "Longitude": "string"
    },
    "Model": "string",
    "SerialNumber": "string",
```

```
  "SiteId": "string",
  "State": "string",
  "Tags": [
    {
      "Key": "string",
      "Value": "string"
    }
  ],
  "Type": "string",
  "Vendor": "string"
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

[Device](#)

Information about the device.

Type: [Device](#) object

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

AccessDeniedException

You do not have sufficient access to perform this action.

HTTP Status Code: 403

ConflictException

There was a conflict processing the request. Updating or deleting the resource can cause an inconsistent state.

ResourceId

The ID of the resource.

ResourceType

The resource type.

HTTP Status Code: 409

InternalServerError

The request has failed due to an internal error.

RetryAfterSeconds

Indicates when to retry the request.

HTTP Status Code: 500

ResourceNotFoundException

The specified resource could not be found.

Context

The specified resource could not be found.

ResourceId

The ID of the resource.

ResourceType

The resource type.

HTTP Status Code: 404

ThrottlingException

The request was denied due to request throttling.

RetryAfterSeconds

Indicates when to retry the request.

HTTP Status Code: 429

ValidationException

The input fails to satisfy the constraints.

Fields

The fields that caused the error, if applicable.

Reason

The reason for the error.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

UpdateDirectConnectGatewayAttachment

Updates the edge locations associated with an AWS Direct Connect gateway attachment.

Request Syntax

```
PATCH /direct-connect-gateway-attachments/attachmentId HTTP/1.1
Content-type: application/json

{
  "EdgeLocations": [ "string" ]
}
```

URI Request Parameters

The request uses the following URI parameters.

attachmentId

The ID of the Direct Connect gateway attachment for the updated edge locations.

Length Constraints: Minimum length of 0. Maximum length of 50.

Pattern: ^attachment-([0-9a-f]{8,17})\$

Required: Yes

Request Body

The request accepts the following data in JSON format.

EdgeLocations

One or more edge locations to update for the Direct Connect gateway attachment. The updated array of edge locations overwrites the previous array of locations. EdgeLocations is only used for Direct Connect gateway attachments.

Type: Array of strings

Length Constraints: Minimum length of 1. Maximum length of 63.

Pattern: `[\s\S]*`

Required: No

Response Syntax

HTTP/1.1 200

Content-type: application/json

```
{
  "DirectConnectGatewayAttachment": {
    "Attachment": {
      "AttachmentId": "string",
      "AttachmentPolicyRuleNumber": number,
      "AttachmentType": "string",
      "CoreNetworkArn": "string",
      "CoreNetworkId": "string",
      "CreatedAt": number,
      "EdgeLocation": "string",
      "EdgeLocations": [ "string" ],
      "LastModificationErrors": [
        {
          "Code": "string",
          "Message": "string",
          "RequestId": "string",
          "ResourceArn": "string"
        }
      ],
      "NetworkFunctionGroupName": "string",
      "OwnerAccountId": "string",
      "ProposedNetworkFunctionGroupChange": {
        "AttachmentPolicyRuleNumber": number,
        "NetworkFunctionGroupName": "string",
        "Tags": [
          {
            "Key": "string",
            "Value": "string"
          }
        ]
      },
      "ProposedSegmentChange": {
        "AttachmentPolicyRuleNumber": number,
        "SegmentName": "string",
```

```
    "Tags": [
      {
        "Key": "string",
        "Value": "string"
      }
    ],
    "ResourceArn": "string",
    "SegmentName": "string",
    "State": "string",
    "Tags": [
      {
        "Key": "string",
        "Value": "string"
      }
    ],
    "UpdatedAt": number
  },
  "DirectConnectGatewayArn": "string"
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

DirectConnectGatewayAttachment

Returns details of the Direct Connect gateway attachment with the updated edge locations.

Type: [DirectConnectGatewayAttachment](#) object

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

AccessDeniedException

You do not have sufficient access to perform this action.

HTTP Status Code: 403

ConflictException

There was a conflict processing the request. Updating or deleting the resource can cause an inconsistent state.

ResourceId

The ID of the resource.

ResourceType

The resource type.

HTTP Status Code: 409

InternalServerErrorException

The request has failed due to an internal error.

RetryAfterSeconds

Indicates when to retry the request.

HTTP Status Code: 500

ResourceNotFoundException

The specified resource could not be found.

Context

The specified resource could not be found.

ResourceId

The ID of the resource.

ResourceType

The resource type.

HTTP Status Code: 404

ThrottlingException

The request was denied due to request throttling.

RetryAfterSeconds

Indicates when to retry the request.

HTTP Status Code: 429

ValidationException

The input fails to satisfy the constraints.

Fields

The fields that caused the error, if applicable.

Reason

The reason for the error.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

UpdateGlobalNetwork

Updates an existing global network. To remove information for any of the parameters, specify an empty string.

Request Syntax

```
PATCH /global-networks/globalNetworkId HTTP/1.1
Content-type: application/json

{
  "Description": "string"
}
```

URI Request Parameters

The request uses the following URI parameters.

globalNetworkId

The ID of your global network.

Length Constraints: Minimum length of 0. Maximum length of 50.

Pattern: `[\s\S]*`

Required: Yes

Request Body

The request accepts the following data in JSON format.

Description

A description of the global network.

Constraints: Maximum length of 256 characters.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 256.

Pattern: `[\s\S]*`

Required: No

Response Syntax

```
HTTP/1.1 200
Content-type: application/json

{
  "GlobalNetwork": {
    "CreatedAt": number,
    "Description": "string",
    "GlobalNetworkArn": "string",
    "GlobalNetworkId": "string",
    "State": "string",
    "Tags": [
      {
        "Key": "string",
        "Value": "string"
      }
    ]
  }
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

GlobalNetwork

Information about the global network object.

Type: [GlobalNetwork](#) object

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

AccessDeniedException

You do not have sufficient access to perform this action.

HTTP Status Code: 403

ConflictException

There was a conflict processing the request. Updating or deleting the resource can cause an inconsistent state.

ResourceId

The ID of the resource.

ResourceType

The resource type.

HTTP Status Code: 409

InternalServerError

The request has failed due to an internal error.

RetryAfterSeconds

Indicates when to retry the request.

HTTP Status Code: 500

ResourceNotFoundException

The specified resource could not be found.

Context

The specified resource could not be found.

ResourceId

The ID of the resource.

ResourceType

The resource type.

HTTP Status Code: 404

ThrottlingException

The request was denied due to request throttling.

RetryAfterSeconds

Indicates when to retry the request.

HTTP Status Code: 429

ValidationException

The input fails to satisfy the constraints.

Fields

The fields that caused the error, if applicable.

Reason

The reason for the error.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

UpdateLink

Updates the details for an existing link. To remove information for any of the parameters, specify an empty string.

Request Syntax

```
PATCH /global-networks/globalNetworkId/links/linkId HTTP/1.1
Content-type: application/json
```

```
{
  "Bandwidth": {
    "DownloadSpeed": number,
    "UploadSpeed": number
  },
  "Description": "string",
  "Provider": "string",
  "Type": "string"
}
```

URI Request Parameters

The request uses the following URI parameters.

globalNetworkId

The ID of the global network.

Length Constraints: Minimum length of 0. Maximum length of 50.

Pattern: `[\s\S]*`

Required: Yes

linkId

The ID of the link.

Length Constraints: Minimum length of 0. Maximum length of 50.

Pattern: `[\s\S]*`

Required: Yes

Request Body

The request accepts the following data in JSON format.

Bandwidth

The upload and download speed in Mbps.

Type: [Bandwidth](#) object

Required: No

Description

A description of the link.

Constraints: Maximum length of 256 characters.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 256.

Pattern: `[\s\S]*`

Required: No

Provider

The provider of the link.

Constraints: Maximum length of 128 characters.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 256.

Pattern: `[\s\S]*`

Required: No

Type

The type of the link.

Constraints: Maximum length of 128 characters.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 256.

Pattern: `[\s\S]*`

Required: No

Response Syntax

```
HTTP/1.1 200
Content-type: application/json

{
  "Link": {
    "Bandwidth": {
      "DownloadSpeed": number,
      "UploadSpeed": number
    },
    "CreatedAt": number,
    "Description": "string",
    "GlobalNetworkId": "string",
    "LinkArn": "string",
    "LinkId": "string",
    "Provider": "string",
    "SiteId": "string",
    "State": "string",
    "Tags": [
      {
        "Key": "string",
        "Value": "string"
      }
    ],
    "Type": "string"
  }
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

[Link](#)

Information about the link.

Type: [Link](#) object

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

AccessDeniedException

You do not have sufficient access to perform this action.

HTTP Status Code: 403

ConflictException

There was a conflict processing the request. Updating or deleting the resource can cause an inconsistent state.

ResourceId

The ID of the resource.

ResourceType

The resource type.

HTTP Status Code: 409

InternalServerError

The request has failed due to an internal error.

RetryAfterSeconds

Indicates when to retry the request.

HTTP Status Code: 500

ResourceNotFoundException

The specified resource could not be found.

Context

The specified resource could not be found.

ResourceId

The ID of the resource.

ResourceType

The resource type.

HTTP Status Code: 404

ServiceQuotaExceededException

A service limit was exceeded.

LimitCode

The limit code.

Message

The error message.

ResourceId

The ID of the resource.

ResourceType

The resource type.

ServiceCode

The service code.

HTTP Status Code: 402

ThrottlingException

The request was denied due to request throttling.

RetryAfterSeconds

Indicates when to retry the request.

HTTP Status Code: 429

ValidationException

The input fails to satisfy the constraints.

Fields

The fields that caused the error, if applicable.

Reason

The reason for the error.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

UpdateNetworkResourceMetadata

Updates the resource metadata for the specified global network.

Request Syntax

```
PATCH /global-networks/globalNetworkId/network-resources/resourceArn/metadata HTTP/1.1
Content-type: application/json
```

```
{
  "Metadata": {
    "string" : "string"
  }
}
```

URI Request Parameters

The request uses the following URI parameters.

[globalNetworkId](#)

The ID of the global network.

Length Constraints: Minimum length of 0. Maximum length of 50.

Pattern: `[\s\S]*`

Required: Yes

[resourceArn](#)

The ARN of the resource.

Length Constraints: Minimum length of 0. Maximum length of 1500.

Pattern: `[\s\S]*`

Required: Yes

Request Body

The request accepts the following data in JSON format.

Metadata

The resource metadata.

Type: String to string map

Key Length Constraints: Minimum length of 0. Maximum length of 256.

Key Pattern: `[\s\S]*`

Value Length Constraints: Minimum length of 0. Maximum length of 256.

Value Pattern: `[\s\S]*`

Required: Yes

Response Syntax

```
HTTP/1.1 200
Content-type: application/json
```

```
{
  "Metadata": {
    "string" : "string"
  },
  "ResourceArn": "string"
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

Metadata

The updated resource metadata.

Type: String to string map

Key Length Constraints: Minimum length of 0. Maximum length of 256.

Key Pattern: `[\s\S]*`

Value Length Constraints: Minimum length of 0. Maximum length of 256.

Value Pattern: `[\s\S]*`

ResourceArn

The ARN of the resource.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 1500.

Pattern: `[\s\S]*`

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

AccessDeniedException

You do not have sufficient access to perform this action.

HTTP Status Code: 403

ConflictException

There was a conflict processing the request. Updating or deleting the resource can cause an inconsistent state.

ResourceId

The ID of the resource.

ResourceType

The resource type.

HTTP Status Code: 409

InternalServerError

The request has failed due to an internal error.

RetryAfterSeconds

Indicates when to retry the request.

HTTP Status Code: 500

ResourceNotFoundException

The specified resource could not be found.

Context

The specified resource could not be found.

ResourceId

The ID of the resource.

ResourceType

The resource type.

HTTP Status Code: 404

ThrottlingException

The request was denied due to request throttling.

RetryAfterSeconds

Indicates when to retry the request.

HTTP Status Code: 429

ValidationException

The input fails to satisfy the constraints.

Fields

The fields that caused the error, if applicable.

Reason

The reason for the error.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

UpdateSite

Updates the information for an existing site. To remove information for any of the parameters, specify an empty string.

Request Syntax

```
PATCH /global-networks/globalNetworkId/sites/siteId HTTP/1.1
Content-type: application/json

{
  "Description": "string",
  "Location": {
    "Address": "string",
    "Latitude": "string",
    "Longitude": "string"
  }
}
```

URI Request Parameters

The request uses the following URI parameters.

globalNetworkId

The ID of the global network.

Length Constraints: Minimum length of 0. Maximum length of 50.

Pattern: `[\s\S]*`

Required: Yes

siteId

The ID of your site.

Length Constraints: Minimum length of 0. Maximum length of 50.

Pattern: `[\s\S]*`

Required: Yes

Request Body

The request accepts the following data in JSON format.

Description

A description of your site.

Constraints: Maximum length of 256 characters.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 256.

Pattern: `[\s\S]*`

Required: No

Location

The site location:

- Address: The physical address of the site.
- Latitude: The latitude of the site.
- Longitude: The longitude of the site.

Type: [Location](#) object

Required: No

Response Syntax

```
HTTP/1.1 200
Content-type: application/json

{
  "Site": {
    "CreatedAt": number,
    "Description": "string",
    "GlobalNetworkId": "string",
    "Location": {
      "Address": "string",
      "Latitude": "string",
```

```
    "Longitude": "string",
  },
  "SiteArn": "string",
  "SiteId": "string",
  "State": "string",
  "Tags": [
    {
      "Key": "string",
      "Value": "string"
    }
  ]
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

Site

Information about the site.

Type: [Site](#) object

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

AccessDeniedException

You do not have sufficient access to perform this action.

HTTP Status Code: 403

ConflictException

There was a conflict processing the request. Updating or deleting the resource can cause an inconsistent state.

ResourceId

The ID of the resource.

ResourceType

The resource type.

HTTP Status Code: 409

InternalServerError

The request has failed due to an internal error.

RetryAfterSeconds

Indicates when to retry the request.

HTTP Status Code: 500

ResourceNotFoundException

The specified resource could not be found.

Context

The specified resource could not be found.

ResourceId

The ID of the resource.

ResourceType

The resource type.

HTTP Status Code: 404

ThrottlingException

The request was denied due to request throttling.

RetryAfterSeconds

Indicates when to retry the request.

HTTP Status Code: 429

ValidationException

The input fails to satisfy the constraints.

Fields

The fields that caused the error, if applicable.

Reason

The reason for the error.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

UpdateVpcAttachment

Updates a VPC attachment.

Request Syntax

```
PATCH /vpc-attachments/attachmentId HTTP/1.1
Content-type: application/json

{
  "AddSubnetArns": [ "string" ],
  "Options": {
    "ApplianceModeSupport": boolean,
    "DnsSupport": boolean,
    "Ipv6Support": boolean,
    "SecurityGroupReferencingSupport": boolean
  },
  "RemoveSubnetArns": [ "string" ]
}
```

URI Request Parameters

The request uses the following URI parameters.

attachmentId

The ID of the attachment.

Length Constraints: Minimum length of 0. Maximum length of 50.

Pattern: ^attachment-([0-9a-f]{8,17})\$

Required: Yes

Request Body

The request accepts the following data in JSON format.

AddSubnetArns

Adds a subnet ARN to the VPC attachment.

Type: Array of strings

Length Constraints: Minimum length of 0. Maximum length of 500.

Pattern: `^arn:[^:]{1,63}:ec2:[^:]{0,63}:[^:]{0,63}:subnet\\/subnet-[0-9a-f]{8,17}$|^$`

Required: No

Options

Additional options for updating the VPC attachment.

Type: [VpcOptions](#) object

Required: No

RemoveSubnetArns

Removes a subnet ARN from the attachment.

Type: Array of strings

Length Constraints: Minimum length of 0. Maximum length of 500.

Pattern: `^arn:[^:]{1,63}:ec2:[^:]{0,63}:[^:]{0,63}:subnet\\/subnet-[0-9a-f]{8,17}$|^$`

Required: No

Response Syntax

HTTP/1.1 200

Content-type: application/json

```
{
  "VpcAttachment": {
    "Attachment": {
      "AttachmentId": "string",
      "AttachmentPolicyRuleNumber": number,
      "AttachmentType": "string",
      "CoreNetworkArn": "string",
      "CoreNetworkId": "string",
      "CreatedAt": number,
      "EdgeLocation": "string",
```

```
"EdgeLocations": [ "string" ],
"LastModificationErrors": [
  {
    "Code": "string",
    "Message": "string",
    "RequestId": "string",
    "ResourceArn": "string"
  }
],
"NetworkFunctionGroupName": "string",
"OwnerAccountId": "string",
"ProposedNetworkFunctionGroupChange": {
  "AttachmentPolicyRuleNumber": number,
  "NetworkFunctionGroupName": "string",
  "Tags": [
    {
      "Key": "string",
      "Value": "string"
    }
  ]
},
"ProposedSegmentChange": {
  "AttachmentPolicyRuleNumber": number,
  "SegmentName": "string",
  "Tags": [
    {
      "Key": "string",
      "Value": "string"
    }
  ]
},
"ResourceArn": "string",
"SegmentName": "string",
"State": "string",
"Tags": [
  {
    "Key": "string",
    "Value": "string"
  }
],
"UpdatedAt": number
},
"Options": {
  "ApplianceModeSupport": boolean,
```

```
    "DnsSupport": boolean,
    "Ipv6Support": boolean,
    "SecurityGroupReferencingSupport": boolean
  },
  "SubnetArns": [ "string" ]
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

VpcAttachment

Describes the updated VPC attachment.

Type: [VpcAttachment](#) object

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

AccessDeniedException

You do not have sufficient access to perform this action.

HTTP Status Code: 403

ConflictException

There was a conflict processing the request. Updating or deleting the resource can cause an inconsistent state.

ResourceId

The ID of the resource.

ResourceType

The resource type.

HTTP Status Code: 409

InternalServerError

The request has failed due to an internal error.

RetryAfterSeconds

Indicates when to retry the request.

HTTP Status Code: 500

ResourceNotFoundException

The specified resource could not be found.

Context

The specified resource could not be found.

ResourceId

The ID of the resource.

ResourceType

The resource type.

HTTP Status Code: 404

ThrottlingException

The request was denied due to request throttling.

RetryAfterSeconds

Indicates when to retry the request.

HTTP Status Code: 429

ValidationException

The input fails to satisfy the constraints.

Fields

The fields that caused the error, if applicable.

Reason

The reason for the error.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

Data Types

The AWS Network Manager API contains several data types that various actions use. This section describes each data type in detail.

Note

The order of each element in a data type structure is not guaranteed. Applications should not assume a particular order.

The following data types are supported:

- [AccountStatus](#)
- [Attachment](#)
- [AttachmentError](#)
- [AWSLocation](#)
- [Bandwidth](#)
- [BgpOptions](#)
- [ConnectAttachment](#)
- [ConnectAttachmentOptions](#)
- [Connection](#)
- [ConnectionHealth](#)
- [ConnectPeer](#)
- [ConnectPeerAssociation](#)
- [ConnectPeerBgpConfiguration](#)
- [ConnectPeerConfiguration](#)
- [ConnectPeerError](#)
- [ConnectPeerSummary](#)
- [CoreNetwork](#)
- [CoreNetworkChange](#)
- [CoreNetworkChangeEvent](#)
- [CoreNetworkChangeEventValues](#)

- [CoreNetworkChangeValues](#)
- [CoreNetworkEdge](#)
- [CoreNetworkNetworkFunctionGroup](#)
- [CoreNetworkNetworkFunctionGroupIdentifier](#)
- [CoreNetworkPolicy](#)
- [CoreNetworkPolicyError](#)
- [CoreNetworkPolicyVersion](#)
- [CoreNetworkSegment](#)
- [CoreNetworkSegmentEdgeIdentifier](#)
- [CoreNetworkSummary](#)
- [CustomerGatewayAssociation](#)
- [Device](#)
- [DirectConnectGatewayAttachment](#)
- [EdgeOverride](#)
- [GlobalNetwork](#)
- [Link](#)
- [LinkAssociation](#)
- [Location](#)
- [NetworkFunctionGroup](#)
- [NetworkResource](#)
- [NetworkResourceCount](#)
- [NetworkResourceSummary](#)
- [NetworkRoute](#)
- [NetworkRouteDestination](#)
- [NetworkTelemetry](#)
- [OrganizationStatus](#)
- [PathComponent](#)
- [Peering](#)
- [PeeringError](#)
- [PermissionsErrorContext](#)

- [ProposedNetworkFunctionGroupChange](#)
- [ProposedSegmentChange](#)
- [Relationship](#)
- [RouteAnalysis](#)
- [RouteAnalysisCompletion](#)
- [RouteAnalysisEndpointOptions](#)
- [RouteAnalysisEndpointOptionsSpecification](#)
- [RouteAnalysisPath](#)
- [RouteTableIdentifier](#)
- [ServiceInsertionAction](#)
- [ServiceInsertionSegments](#)
- [Site](#)
- [SiteToSiteVpnAttachment](#)
- [Tag](#)
- [TransitGatewayConnectPeerAssociation](#)
- [TransitGatewayPeering](#)
- [TransitGatewayRegistration](#)
- [TransitGatewayRegistrationStateReason](#)
- [TransitGatewayRouteTableAttachment](#)
- [ValidationExceptionField](#)
- [Via](#)
- [VpcAttachment](#)
- [VpcOptions](#)
- [WhenSentTo](#)

AccountStatus

Describes the current status of an account within an Amazon Web Services Organization, including service-linked roles (SLRs).

Contents

AccountId

The ID of an account within the Amazon Web Services Organization.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 50.

Required: No

SLRDeploymentStatus

The status of SLR deployment for the account.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 50.

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

Attachment

Describes a core network attachment.

Contents

AttachmentId

The ID of the attachment.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 50.

Pattern: `^attachment-([0-9a-f]{8,17})$`

Required: No

AttachmentPolicyRuleNumber

The policy rule number associated with the attachment.

Type: Integer

Required: No

AttachmentType

The type of attachment.

Type: String

Valid Values: CONNECT | SITE_TO_SITE_VPN | VPC | DIRECT_CONNECT_GATEWAY | TRANSIT_GATEWAY_ROUTE_TABLE

Required: No

CoreNetworkArn

The ARN of a core network.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 500.

Pattern: `[\s\S]*`

Required: No

CoreNetworkId

The ID of a core network.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 50.

Pattern: `^core-network-([0-9a-f]{8,17})$`

Required: No

CreatedAt

The timestamp when the attachment was created.

Type: Timestamp

Required: No

EdgeLocation

The Region where the edge is located. This is returned for all attachment types except a Direct Connect gateway attachment, which instead returns `EdgeLocations`.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 63.

Pattern: `[\s\S]*`

Required: No

EdgeLocations

The edge locations that the Direct Connect gateway is associated with. This is returned only for Direct Connect gateway attachments. All other attachment types return `EdgeLocation`.

Type: Array of strings

Length Constraints: Minimum length of 1. Maximum length of 63.

Pattern: `[\s\S]*`

Required: No

LastModificationErrors

Describes the error associated with the attachment request.

Type: Array of [AttachmentError](#) objects

Array Members: Minimum number of 0 items. Maximum number of 20 items.

Required: No

NetworkFunctionGroupName

The name of the network function group.

Type: String

Pattern: `[\s\S]*`

Required: No

OwnerAccountId

The ID of the attachment account owner.

Type: String

Length Constraints: Fixed length of 12.

Pattern: `[\s\S]*`

Required: No

ProposedNetworkFunctionGroupChange

Describes a proposed change to a network function group associated with the attachment.

Type: [ProposedNetworkFunctionGroupChange](#) object

Required: No

ProposedSegmentChange

The attachment to move from one segment to another.

Type: [ProposedSegmentChange](#) object

Required: No

ResourceArn

The attachment resource ARN.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 1500.

Pattern: `[\s\S]*`

Required: No

SegmentName

The name of the segment attachment.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 256.

Pattern: `[\s\S]*`

Required: No

State

The state of the attachment.

Type: String

Valid Values: REJECTED | PENDING_ATTACHMENT_ACCEPTANCE | CREATING | FAILED | AVAILABLE | UPDATING | PENDING_NETWORK_UPDATE | PENDING_TAG_ACCEPTANCE | DELETING

Required: No

Tags

The tags associated with the attachment.

Type: Array of [Tag](#) objects

Required: No

UpdatedAt

The timestamp when the attachment was last updated.

Type: Timestamp

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

AttachmentError

Describes the error associated with an attachment request.

Contents

Code

The error code for the attachment request.

Type: String

Valid Values: VPC_NOT_FOUND | SUBNET_NOT_FOUND | SUBNET_DUPLICATED_IN_AVAILABILITY_ZONE | SUBNET_NO_FREE_ADDRESSES | SUBNET_UNSUPPORTED_AVAILABILITY_ZONE | SUBNET_NO_IPV6_CIDRS | VPN_CONNECTION_NOT_FOUND | MAXIMUM_NO_ENCAP_LIMIT_EXCEEDED | DIRECT_CONNECT_GATEWAY_NOT_FOUND | DIRECT_CONNECT_GATEWAY_EXISTING_ATTACHMENTS | DIRECT_CONNECT_GATEWAY_NO_PRIVATE_VIF

Required: No

Message

The message associated with the error code.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 10000000.

Pattern: `[\s\S]*`

Required: No

RequestId

The ID of the attachment request.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 10000000.

Pattern: `[\s\S]*`

Required: No

ResourceArn

The ARN of the requested attachment resource.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 1500.

Pattern: `[\s\S]*`

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

AWSLocation

Specifies a location in AWS.

Contents

SubnetArn

The Amazon Resource Name (ARN) of the subnet that the device is located in.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 500.

Pattern: `^arn:[^:]{1,63}:ec2:[^:]{0,63}:[^:]{0,63}:subnet\./subnet-[0-9a-f]{8,17}$|^$`

Required: No

Zone

The Zone that the device is located in. Specify the ID of an Availability Zone, Local Zone, Wavelength Zone, or an Outpost.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 256.

Pattern: `[\s\S]*`

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

Bandwidth

Describes bandwidth information.

Contents

DownloadSpeed

Download speed in Mbps.

Type: Integer

Required: No

UploadSpeed

Upload speed in Mbps.

Type: Integer

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

BgpOptions

Describes the BGP options.

Contents

PeerAsn

The Peer ASN of the BGP.

Type: Long

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

ConnectAttachment

Describes a core network Connect attachment.

Contents

Attachment

The attachment details.

Type: [Attachment](#) object

Required: No

Options

Options for connecting an attachment.

Type: [ConnectAttachmentOptions](#) object

Required: No

TransportAttachmentId

The ID of the transport attachment.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 50.

Pattern: ^attachment-([0-9a-f]{8,17})\$

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

ConnectAttachmentOptions

Describes a core network Connect attachment options.

Contents

Protocol

The protocol used for the attachment connection.

Type: String

Valid Values: GRE | NO_ENCAP

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

Connection

Describes a connection.

Contents

ConnectedDeviceId

The ID of the second device in the connection.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 50.

Pattern: `[\s\S]*`

Required: No

ConnectedLinkId

The ID of the link for the second device in the connection.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 50.

Pattern: `[\s\S]*`

Required: No

ConnectionArn

The Amazon Resource Name (ARN) of the connection.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 500.

Pattern: `[\s\S]*`

Required: No

ConnectionId

The ID of the connection.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 50.

Pattern: `[\s\S]*`

Required: No

CreatedAt

The date and time that the connection was created.

Type: Timestamp

Required: No

Description

The description of the connection.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 256.

Pattern: `[\s\S]*`

Required: No

DeviceId

The ID of the first device in the connection.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 50.

Pattern: `[\s\S]*`

Required: No

GlobalNetworkId

The ID of the global network.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 50.

Pattern: `[\s\S]*`

Required: No

LinkId

The ID of the link for the first device in the connection.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 50.

Pattern: `[\s\S]*`

Required: No

State

The state of the connection.

Type: String

Valid Values: PENDING | AVAILABLE | DELETING | UPDATING

Required: No

Tags

The tags for the connection.

Type: Array of [Tag](#) objects

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

ConnectionHealth

Describes connection health.

Contents

Status

The connection status.

Type: String

Valid Values: UP | DOWN

Required: No

Timestamp

The time the status was last updated.

Type: Timestamp

Required: No

Type

The connection type.

Type: String

Valid Values: BGP | IPSEC

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

ConnectPeer

Describes a core network Connect peer.

Contents

Configuration

The configuration of the Connect peer.

Type: [ConnectPeerConfiguration](#) object

Required: No

ConnectAttachmentId

The ID of the attachment to connect.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 50.

Pattern: `^attachment-([0-9a-f]{8,17})$`

Required: No

ConnectPeerId

The ID of the Connect peer.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 50.

Pattern: `^connect-peer-([0-9a-f]{8,17})$`

Required: No

CoreNetworkId

The ID of a core network.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 50.

Pattern: `^core-network-([0-9a-f]{8,17})$`

Required: No

CreatedAt

The timestamp when the Connect peer was created.

Type: Timestamp

Required: No

EdgeLocation

The Connect peer Regions where edges are located.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 63.

Pattern: `[\s\S]*`

Required: No

LastModificationErrors

Describes the error associated with the attachment request.

Type: Array of [ConnectPeerError](#) objects

Array Members: Minimum number of 0 items. Maximum number of 20 items.

Required: No

State

The state of the Connect peer.

Type: String

Valid Values: CREATING | FAILED | AVAILABLE | DELETING

Required: No

SubnetArn

The subnet ARN for the Connect peer. This only applies only when the protocol is NO_ENCAP.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 500.

Pattern: `^arn:[^:]{1,63}:ec2:[^:]{0,63}:[^:]{0,63}:subnet\\/subnet-[0-9a-f]{8,17}$|^$`

Required: No

Tags

The list of key-value tags associated with the Connect peer.

Type: Array of [Tag](#) objects

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

ConnectPeerAssociation

Describes a core network Connect peer association.

Contents

ConnectPeerId

The ID of the Connect peer.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 50.

Pattern: `^connect-peer-([0-9a-f]{8,17})$`

Required: No

DeviceId

The ID of the device to connect to.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 50.

Pattern: `[\s\S]*`

Required: No

GlobalNetworkId

The ID of the global network.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 50.

Pattern: `[\s\S]*`

Required: No

LinkId

The ID of the link.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 50.

Pattern: `[\s\S]*`

Required: No

State

The state of the Connect peer association.

Type: String

Valid Values: PENDING | AVAILABLE | DELETING | DELETED

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

ConnectPeerBgpConfiguration

Describes a core network BGP configuration.

Contents

CoreNetworkAddress

The address of a core network.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 50.

Pattern: `[\s\S]*`

Required: No

CoreNetworkAsn

The ASN of the Core Network.

Type: Long

Required: No

PeerAddress

The address of a core network Connect peer.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 50.

Pattern: `[\s\S]*`

Required: No

PeerAsn

The ASN of the Connect peer.

Type: Long

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

ConnectPeerConfiguration

Describes a core network Connect peer configuration.

Contents

BgpConfigurations

The Connect peer BGP configurations.

Type: Array of [ConnectPeerBgpConfiguration](#) objects

Required: No

CoreNetworkAddress

The IP address of a core network.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 50.

Pattern: `[\s\S]*`

Required: No

InsideCidrBlocks

The inside IP addresses used for a Connect peer configuration.

Type: Array of strings

Length Constraints: Minimum length of 0. Maximum length of 256.

Pattern: `[\s\S]*`

Required: No

PeerAddress

The IP address of the Connect peer.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 50.

Pattern: `[\s\S]*`

Required: No

Protocol

The protocol used for a Connect peer configuration.

Type: String

Valid Values: GRE | NO_ENCAP

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

ConnectPeerError

Describes an error associated with a Connect peer request

Contents

Code

The error code for the Connect peer request.

Type: String

Valid Values: `EDGE_LOCATION_NO_FREE_IPS` | `EDGE_LOCATION_PEER_DUPLICATE` | `SUBNET_NOT_FOUND` | `IP_OUTSIDE_SUBNET_CIDR_RANGE` | `INVALID_INSIDE_CIDR_BLOCK` | `NO_ASSOCIATED_CIDR_BLOCK`

Required: No

Message

The message associated with the error code.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 10000000.

Pattern: `[\s\S]*`

Required: No

RequestId

The ID of the Connect peer request.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 10000000.

Pattern: `[\s\S]*`

Required: No

ResourceArn

The ARN of the requested Connect peer resource.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 1500.

Pattern: `[\s\S]*`

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

ConnectPeerSummary

Summary description of a Connect peer.

Contents

ConnectAttachmentId

The ID of a Connect peer attachment.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 50.

Pattern: `^attachment-([0-9a-f]{8,17})$`

Required: No

ConnectPeerId

The ID of a Connect peer.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 50.

Pattern: `^connect-peer-([0-9a-f]{8,17})$`

Required: No

ConnectPeerState

The state of a Connect peer.

Type: String

Valid Values: CREATING | FAILED | AVAILABLE | DELETING

Required: No

CoreNetworkId

The ID of a core network.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 50.

Pattern: `^core-network-([0-9a-f]{8,17})$`

Required: No

CreatedAt

The timestamp when a Connect peer was created.

Type: Timestamp

Required: No

EdgeLocation

The Region where the edge is located.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 63.

Pattern: `[\s\S]*`

Required: No

SubnetArn

The subnet ARN for the Connect peer summary.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 500.

Pattern: `^arn:[^:]{1,63}:ec2:[^:]{0,63}:[^:]{0,63}:subnet\\/subnet-[0-9a-f]{8,17}$|^$`

Required: No

Tags

The list of key-value tags associated with the Connect peer summary.

Type: Array of [Tag](#) objects

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

CoreNetwork

Describes a core network.

Contents

CoreNetworkArn

The ARN of a core network.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 500.

Pattern: `[\s\S]*`

Required: No

CoreNetworkId

The ID of a core network.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 50.

Pattern: `^core-network-([0-9a-f]{8,17})$`

Required: No

CreatedAt

The timestamp when a core network was created.

Type: Timestamp

Required: No

Description

The description of a core network.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 256.

Pattern: `[\s\S]*`

Required: No

Edges

The edges within a core network.

Type: Array of [CoreNetworkEdge](#) objects

Required: No

GlobalNetworkId

The ID of the global network that your core network is a part of.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 50.

Pattern: `[\s\S]*`

Required: No

NetworkFunctionGroups

The network function groups associated with a core network.

Type: Array of [CoreNetworkNetworkFunctionGroup](#) objects

Required: No

Segments

The segments within a core network.

Type: Array of [CoreNetworkSegment](#) objects

Required: No

State

The current state of a core network.

Type: String

Valid Values: CREATING | UPDATING | AVAILABLE | DELETING

Required: No

Tags

The list of key-value tags associated with a core network.

Type: Array of [Tag](#) objects

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

CoreNetworkChange

Details describing a core network change.

Contents

Action

The action to take for a core network.

Type: String

Valid Values: ADD | MODIFY | REMOVE

Required: No

Identifier

The resource identifier.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 256.

Pattern: [`\s\S`]*

Required: No

IdentifierPath

Uniquely identifies the path for a change within the changeset. For example, the IdentifierPath for a core network segment change might be "CORE_NETWORK_SEGMENT/us-east-1/devsegment".

Type: String

Length Constraints: Minimum length of 0. Maximum length of 256.

Pattern: [`\s\S`]*

Required: No

NewValues

The new value for a core network

Type: [CoreNetworkChangeValues](#) object

Required: No

PreviousValues

The previous values for a core network.

Type: [CoreNetworkChangeValues](#) object

Required: No

Type

The type of change.

Type: String

Valid Values: CORE_NETWORK_SEGMENT | NETWORK_FUNCTION_GROUP |
CORE_NETWORK_EDGE | ATTACHMENT_MAPPING | ATTACHMENT_ROUTE_PROPAGATION
| ATTACHMENT_ROUTE_STATIC | CORE_NETWORK_CONFIGURATION |
SEGMENTS_CONFIGURATION | SEGMENT_ACTIONS_CONFIGURATION |
ATTACHMENT_POLICIES_CONFIGURATION

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

CoreNetworkChangeEvent

Describes a core network change event. This can be a change to a segment, attachment, route, etc.

Contents

Action

The action taken for the change event.

Type: String

Valid Values: ADD | MODIFY | REMOVE

Required: No

EventTime

The timestamp for an event change in status.

Type: Timestamp

Required: No

IdentifierPath

Uniquely identifies the path for a change within the changeset. For example, the `IdentifierPath` for a core network segment change might be "CORE_NETWORK_SEGMENT/us-east-1/devsegment".

Type: String

Length Constraints: Minimum length of 0. Maximum length of 256.

Pattern: `[\s\S]*`

Required: No

Status

The status of the core network change event.

Type: String

Valid Values: NOT_STARTED | IN_PROGRESS | COMPLETE | FAILED

Required: No

Type

Describes the type of change event.

Type: String

Valid Values: CORE_NETWORK_SEGMENT | NETWORK_FUNCTION_GROUP |
CORE_NETWORK_EDGE | ATTACHMENT_MAPPING | ATTACHMENT_ROUTE_PROPAGATION
| ATTACHMENT_ROUTE_STATIC | CORE_NETWORK_CONFIGURATION |
SEGMENTS_CONFIGURATION | SEGMENT_ACTIONS_CONFIGURATION |
ATTACHMENT_POLICIES_CONFIGURATION

Required: No

Values

Details of the change event.

Type: [CoreNetworkChangeEventValues](#) object

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

CoreNetworkChangeEventValues

Describes a core network change event.

Contents

AttachmentId

The ID of the attachment if the change event is associated with an attachment.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 50.

Pattern: `^attachment-([0-9a-f]{8,17})$`

Required: No

Cidr

For a `STATIC_ROUTE` event, this is the IP address.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 256.

Pattern: `[\s\S]*`

Required: No

EdgeLocation

The edge location for the core network change event.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 63.

Pattern: `[\s\S]*`

Required: No

NetworkFunctionGroupName

The changed network function group name.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 256.

Pattern: `[\s\S]*`

Required: No

SegmentName

The segment name if the change event is associated with a segment.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 256.

Pattern: `[\s\S]*`

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

CoreNetworkChangeValues

Describes a core network change.

Contents

Asn

The ASN of a core network.

Type: Long

Required: No

Cidr

The IP addresses used for a core network.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 256.

Pattern: `[\s\S]*`

Required: No

DestinationIdentifier

The ID of the destination.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 256.

Pattern: `[\s\S]*`

Required: No

DnsSupport

Indicates whether public DNS support is supported. The default is `true`.

Type: Boolean

Required: No

EdgeLocations

The Regions where edges are located in a core network.

Type: Array of strings

Length Constraints: Minimum length of 1. Maximum length of 63.

Pattern: `[\s\S]*`

Required: No

InsideCidrBlocks

The inside IP addresses used for core network change values.

Type: Array of strings

Length Constraints: Minimum length of 0. Maximum length of 256.

Pattern: `[\s\S]*`

Required: No

NetworkFunctionGroupName

The network function group name if the change event is associated with a network function group.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 256.

Pattern: `[\s\S]*`

Required: No

SecurityGroupReferencingSupport

Indicates whether security group referencing is enabled for the core network.

Type: Boolean

Required: No

SegmentName

The names of the segments in a core network.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 256.

Pattern: `[\s\S]*`

Required: No

ServiceInsertionActions

Describes the service insertion action.

Type: Array of [ServiceInsertionAction](#) objects

Required: No

SharedSegments

The shared segments for a core network change value.

Type: Array of strings

Length Constraints: Minimum length of 0. Maximum length of 256.

Pattern: `[\s\S]*`

Required: No

VpnEcmpSupport

Indicates whether Equal Cost Multipath (ECMP) is enabled for the core network.

Type: Boolean

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

CoreNetworkEdge

Describes a core network edge.

Contents

Asn

The ASN of a core network edge.

Type: Long

Required: No

EdgeLocation

The Region where a core network edge is located.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 63.

Pattern: `[\s\S]*`

Required: No

InsideCidrBlocks

The inside IP addresses used for core network edges.

Type: Array of strings

Length Constraints: Minimum length of 0. Maximum length of 256.

Pattern: `[\s\S]*`

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

CoreNetworkNetworkFunctionGroup

Describes a network function group.

Contents

EdgeLocations

The core network edge locations.

Type: Array of strings

Length Constraints: Minimum length of 1. Maximum length of 63.

Pattern: `[\s\S]*`

Required: No

Name

The name of the network function group.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 256.

Pattern: `[\s\S]*`

Required: No

Segments

The segments associated with the network function group.

Type: [ServiceInsertionSegments](#) object

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

CoreNetworkNetworkFunctionGroupIdentifier

Describes a core network

Contents

CoreNetworkId

The ID of the core network.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 50.

Pattern: `^core-network-([0-9a-f]{8,17})$`

Required: No

EdgeLocation

The location for the core network edge.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 63.

Pattern: `[\s\S]*`

Required: No

NetworkFunctionGroupName

The network function group name.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 256.

Pattern: `[\s\S]*`

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

CoreNetworkPolicy

Describes a core network policy. You can have only one LIVE Core Policy.

Contents

Alias

Whether a core network policy is the current LIVE policy or the most recently submitted policy.

Type: String

Valid Values: LIVE | LATEST

Required: No

ChangeSetState

The state of a core network policy.

Type: String

Valid Values: PENDING_GENERATION | FAILED_GENERATION | READY_TO_EXECUTE | EXECUTING | EXECUTION_SUCCEEDED | OUT_OF_DATE

Required: No

CoreNetworkId

The ID of a core network.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 50.

Pattern: ^core-network-([0-9a-f]{8,17})\$

Required: No

CreatedAt

The timestamp when a core network policy was created.

Type: Timestamp

Required: No

Description

The description of a core network policy.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 256.

Pattern: `[\s\S]*`

Required: No

PolicyDocument

Describes a core network policy.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 10000000.

Pattern: `[\s\S]*`

Required: No

PolicyErrors

Describes any errors in a core network policy.

Type: Array of [CoreNetworkPolicyError](#) objects

Required: No

PolicyVersionId

The ID of the policy version.

Type: Integer

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

CoreNetworkPolicyError

Provides details about an error in a core network policy.

Contents

ErrorCode

The error code associated with a core network policy error.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 10000000.

Pattern: `[\s\S]*`

Required: Yes

Message

The message associated with a core network policy error code.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 10000000.

Pattern: `[\s\S]*`

Required: Yes

Path

The JSON path where the error was discovered in the policy document.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 10000000.

Pattern: `[\s\S]*`

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

CoreNetworkPolicyVersion

Describes a core network policy version.

Contents

Alias

Whether a core network policy is the current policy or the most recently submitted policy.

Type: String

Valid Values: LIVE | LATEST

Required: No

ChangeSetState

The status of the policy version change set.

Type: String

Valid Values: PENDING_GENERATION | FAILED_GENERATION | READY_TO_EXECUTE | EXECUTING | EXECUTION_SUCCEEDED | OUT_OF_DATE

Required: No

CoreNetworkId

The ID of a core network.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 50.

Pattern: ^core-network-([0-9a-f]{8,17})\$

Required: No

CreatedAt

The timestamp when a core network policy version was created.

Type: Timestamp

Required: No

Description

The description of a core network policy version.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 256.

Pattern: `[\s\S]*`

Required: No

PolicyVersionId

The ID of the policy version.

Type: Integer

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

CoreNetworkSegment

Describes a core network segment, which are dedicated routes. Only attachments within this segment can communicate with each other.

Contents

EdgeLocations

The Regions where the edges are located.

Type: Array of strings

Length Constraints: Minimum length of 1. Maximum length of 63.

Pattern: `[\s\S]*`

Required: No

Name

The name of a core network segment.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 256.

Pattern: `[\s\S]*`

Required: No

SharedSegments

The shared segments of a core network.

Type: Array of strings

Length Constraints: Minimum length of 0. Maximum length of 256.

Pattern: `[\s\S]*`

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

CoreNetworkSegmentEdgeIdentifier

Returns details about a core network edge.

Contents

CoreNetworkId

The ID of a core network.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 50.

Pattern: `^core-network-([0-9a-f]{8,17})$`

Required: No

EdgeLocation

The Region where the segment edge is located.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 63.

Pattern: `[\s\S]*`

Required: No

SegmentName

The name of the segment edge.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 256.

Pattern: `[\s\S]*`

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

CoreNetworkSummary

Returns summary information about a core network.

Contents

CoreNetworkArn

a core network ARN.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 500.

Pattern: `[\s\S]*`

Required: No

CoreNetworkId

The ID of a core network.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 50.

Pattern: `^core-network-([0-9a-f]{8,17})$`

Required: No

Description

The description of a core network.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 256.

Pattern: `[\s\S]*`

Required: No

GlobalNetworkId

The global network ID.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 50.

Pattern: `[\s\S]*`

Required: No

OwnerAccountId

The ID of the account owner.

Type: String

Length Constraints: Fixed length of 12.

Pattern: `[\s\S]*`

Required: No

State

The state of a core network.

Type: String

Valid Values: CREATING | UPDATING | AVAILABLE | DELETING

Required: No

Tags

The key-value tags associated with a core network summary.

Type: Array of [Tag](#) objects

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)

- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

CustomerGatewayAssociation

Describes the association between a customer gateway, a device, and a link.

Contents

CustomerGatewayArn

The Amazon Resource Name (ARN) of the customer gateway.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 500.

Pattern: `[\s\S]*`

Required: No

DeviceId

The ID of the device.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 50.

Pattern: `[\s\S]*`

Required: No

GlobalNetworkId

The ID of the global network.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 50.

Pattern: `[\s\S]*`

Required: No

LinkId

The ID of the link.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 50.

Pattern: `[\s\S]*`

Required: No

State

The association state.

Type: String

Valid Values: PENDING | AVAILABLE | DELETING | DELETED

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

Device

Describes a device.

Contents

AWSLocation

The AWS location of the device.

Type: [AWSLocation](#) object

Required: No

CreatedAt

The date and time that the site was created.

Type: Timestamp

Required: No

Description

The description of the device.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 256.

Pattern: `[\s\S]*`

Required: No

DeviceArn

The Amazon Resource Name (ARN) of the device.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 500.

Pattern: `[\s\S]*`

Required: No

DeviceId

The ID of the device.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 50.

Pattern: `[\s\S]*`

Required: No

GlobalNetworkId

The ID of the global network.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 50.

Pattern: `[\s\S]*`

Required: No

Location

The site location.

Type: [Location](#) object

Required: No

Model

The device model.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 256.

Pattern: `[\s\S]*`

Required: No

SerialNumber

The device serial number.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 256.

Pattern: `[\s\S]*`

Required: No

Siteld

The site ID.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 50.

Pattern: `[\s\S]*`

Required: No

State

The device state.

Type: String

Valid Values: PENDING | AVAILABLE | DELETING | UPDATING

Required: No

Tags

The tags for the device.

Type: Array of [Tag](#) objects

Required: No

Type

The device type.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 256.

Pattern: `[\s\S]*`

Required: No

Vendor

The device vendor.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 256.

Pattern: `[\s\S]*`

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

DirectConnectGatewayAttachment

Describes a Direct Connect gateway attachment.

Contents

Attachment

Describes a core network attachment.

Type: [Attachment](#) object

Required: No

DirectConnectGatewayArn

The Direct Connect gateway attachment ARN.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 500.

Pattern: `^arn:[^:]{1,63}:directconnect:[^:]{0,63}:dx-gateway\/[0-9a-f]{8}-([0-9a-f]{4}-){3}[0-9a-f]{12}$`

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

EdgeOverride

Describes the edge that's used for the override.

Contents

EdgeSets

The list of edge locations.

Type: Array of arrays of strings

Length Constraints: Minimum length of 0. Maximum length of 256.

Pattern: `[\s\S]*`

Required: No

UseEdge

The edge that should be used when overriding the current edge order.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 256.

Pattern: `[\s\S]*`

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

GlobalNetwork

Describes a global network. This is a single private network acting as a high-level container for your network objects, including an AWS-managed Core Network.

Contents

CreatedAt

The date and time that the global network was created.

Type: Timestamp

Required: No

Description

The description of the global network.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 256.

Pattern: `[\s\S]*`

Required: No

GlobalNetworkArn

The Amazon Resource Name (ARN) of the global network.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 500.

Pattern: `[\s\S]*`

Required: No

GlobalNetworkId

The ID of the global network.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 50.

Pattern: `[\s\S]*`

Required: No

State

The state of the global network.

Type: String

Valid Values: PENDING | AVAILABLE | DELETING | UPDATING

Required: No

Tags

The tags for the global network.

Type: Array of [Tag](#) objects

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

Link

Describes a link.

Contents

Bandwidth

The bandwidth for the link.

Type: [Bandwidth](#) object

Required: No

CreatedAt

The date and time that the link was created.

Type: Timestamp

Required: No

Description

The description of the link.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 256.

Pattern: `[\s\S]*`

Required: No

GlobalNetworkId

The ID of the global network.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 50.

Pattern: `[\s\S]*`

Required: No

LinkArn

The Amazon Resource Name (ARN) of the link.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 500.

Pattern: `[\s\S]*`

Required: No

LinkId

The ID of the link.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 50.

Pattern: `[\s\S]*`

Required: No

Provider

The provider of the link.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 256.

Pattern: `[\s\S]*`

Required: No

Siteld

The ID of the site.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 50.

Pattern: `[\s\S]*`

Required: No

State

The state of the link.

Type: String

Valid Values: PENDING | AVAILABLE | DELETING | UPDATING

Required: No

Tags

The tags for the link.

Type: Array of [Tag](#) objects

Required: No

Type

The type of the link.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 256.

Pattern: `[\s\S]*`

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

LinkAssociation

Describes the association between a device and a link.

Contents

DeviceId

The device ID for the link association.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 50.

Pattern: `[\s\S]*`

Required: No

GlobalNetworkId

The ID of the global network.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 50.

Pattern: `[\s\S]*`

Required: No

LinkAssociationState

The state of the association.

Type: String

Valid Values: PENDING | AVAILABLE | DELETING | DELETED

Required: No

LinkId

The ID of the link.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 50.

Pattern: `[\s\S]*`

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

Location

Describes a location.

Contents

Address

The physical address.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 256.

Pattern: `[\s\S]*`

Required: No

Latitude

The latitude.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 256.

Pattern: `[\s\S]*`

Required: No

Longitude

The longitude.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 256.

Pattern: `[\s\S]*`

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

NetworkFunctionGroup

Describes a network function group for service insertion.

Contents

Name

The name of the network function group.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 256.

Pattern: `[\s\S]*`

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

NetworkResource

Describes a network resource.

Contents

AccountId

The AWS account ID.

Type: String

Length Constraints: Fixed length of 12.

Pattern: `[\s\S]*`

Required: No

AwsRegion

The AWS Region.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 63.

Pattern: `[\s\S]*`

Required: No

CoreNetworkId

The ID of a core network.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 50.

Pattern: `^core-network-([0-9a-f]{8,17})$`

Required: No

Definition

Information about the resource, in JSON format. Network Manager gets this information by describing the resource using its Describe API call.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 256.

Pattern: `[\s\S]*`

Required: No

DefinitionTimestamp

The time that the resource definition was retrieved.

Type: Timestamp

Required: No

Metadata

The resource metadata.

Type: String to string map

Key Length Constraints: Minimum length of 0. Maximum length of 256.

Key Pattern: `[\s\S]*`

Value Length Constraints: Minimum length of 0. Maximum length of 256.

Value Pattern: `[\s\S]*`

Required: No

RegisteredGatewayArn

The ARN of the gateway.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 1500.

Pattern: `[\s\S]*`

Required: No

ResourceArn

The ARN of the resource.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 1500.

Pattern: `[\s\S]*`

Required: No

ResourceId

The ID of the resource.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 256.

Pattern: `[\s\S]*`

Required: No

ResourceType

The resource type.

The following are the supported resource types for AWS Direct Connect:

- `dxcon`
- `dx-gateway`
- `dx-vif`

The following are the supported resource types for Network Manager:

- `attachment`
- `connect-peer`
- `connection`
- `core-network`
- `device`
- `link`
- `peering`
- `site`

The following are the supported resource types for Amazon VPC:

- `customer-gateway`
- `transit-gateway`
- `transit-gateway-attachment`
- `transit-gateway-connect-peer`
- `transit-gateway-route-table`
- `vpn-connection`

Type: String

Length Constraints: Minimum length of 0. Maximum length of 256.

Pattern: `[\s\S]*`

Required: No

Tags

The tags.

Type: Array of [Tag](#) objects

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

NetworkResourceCount

Describes a resource count.

Contents

Count

The resource count.

Type: Integer

Required: No

ResourceType

The resource type.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 256.

Pattern: `[\s\S]*`

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

NetworkResourceSummary

Describes a network resource.

Contents

Definition

Information about the resource, in JSON format. Network Manager gets this information by describing the resource using its Describe API call.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 256.

Pattern: `[\s\S]*`

Required: No

IsMiddlebox

Indicates whether this is a middlebox appliance.

Type: Boolean

Required: No

NameTag

The value for the Name tag.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 256.

Pattern: `[\s\S]*`

Required: No

RegisteredGatewayArn

The ARN of the gateway.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 1500.

Pattern: `[\s\S]*`

Required: No

ResourceArn

The ARN of the resource.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 1500.

Pattern: `[\s\S]*`

Required: No

ResourceType

The resource type.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 256.

Pattern: `[\s\S]*`

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

NetworkRoute

Describes a network route.

Contents

DestinationCidrBlock

A unique identifier for the route, such as a CIDR block.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 256.

Pattern: `[\s\S]*`

Required: No

Destinations

The destinations.

Type: Array of [NetworkRouteDestination](#) objects

Required: No

PrefixListId

The ID of the prefix list.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 256.

Pattern: `[\s\S]*`

Required: No

State

The route state. The possible values are `active` and `blackhole`.

Type: String

Valid Values: `ACTIVE` | `BLACKHOLE`

Required: No

Type

The route type. The possible values are `propagated` and `static`.

Type: String

Valid Values: `PROPAGATED` | `STATIC`

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

NetworkRouteDestination

Describes the destination of a network route.

Contents

CoreNetworkAttachmentId

The ID of a core network attachment.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 50.

Pattern: `^attachment-([0-9a-f]{8,17})$`

Required: No

EdgeLocation

The edge location for the network destination.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 63.

Pattern: `[\s\S]*`

Required: No

NetworkFunctionGroupName

The network function group name associated with the destination.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 256.

Pattern: `[\s\S]*`

Required: No

ResourceId

The ID of the resource.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 256.

Pattern: `[\s\S]*`

Required: No

ResourceType

The resource type.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 256.

Pattern: `[\s\S]*`

Required: No

SegmentName

The name of the segment.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 256.

Pattern: `[\s\S]*`

Required: No

TransitGatewayAttachmentId

The ID of the transit gateway attachment.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 50.

Pattern: `[\s\S]*`

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

NetworkTelemetry

Describes the telemetry information for a resource.

Contents

AccountId

The AWS account ID.

Type: String

Length Constraints: Fixed length of 12.

Pattern: `[\s\S]*`

Required: No

Address

The address.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 256.

Pattern: `[\s\S]*`

Required: No

AwsRegion

The AWS Region.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 63.

Pattern: `[\s\S]*`

Required: No

CoreNetworkId

The ID of a core network.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 50.

Pattern: `^core-network-([0-9a-f]{8,17})$`

Required: No

Health

The connection health.

Type: [ConnectionHealth](#) object

Required: No

RegisteredGatewayArn

The ARN of the gateway.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 1500.

Pattern: `[\s\S]*`

Required: No

ResourceArn

The ARN of the resource.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 1500.

Pattern: `[\s\S]*`

Required: No

ResourceId

The ID of the resource.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 256.

Pattern: `[\s\S]*`

Required: No

ResourceType

The resource type.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 256.

Pattern: `[\s\S]*`

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

OrganizationStatus

The status of an Amazon Web Services Organization and the accounts within that organization.

Contents

AccountStatusList

The current service-linked role (SLR) deployment status for an Amazon Web Services Organization's accounts. This will be either SUCCEEDED or IN_PROGRESS.

Type: Array of [AccountStatus](#) objects

Required: No

OrganizationAwsServiceAccessStatus

The status of the organization's AWS service access. This will be ENABLED or DISABLED.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 50.

Required: No

OrganizationId

The ID of an Amazon Web Services Organization.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 50.

Pattern: `^o-([0-9a-f]{8,17})$`

Required: No

SLRDeploymentStatus

The status of the SLR deployment for the account. This will be either SUCCEEDED or IN_PROGRESS.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 50.

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

PathComponent

Describes a path component.

Contents

DestinationCidrBlock

The destination CIDR block in the route table.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 256.

Pattern: `[\s\S]*`

Required: No

Resource

The resource.

Type: [NetworkResourceSummary](#) object

Required: No

Sequence

The sequence number in the path. The destination is 0.

Type: Integer

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

Peering

Describes a peering connection.

Contents

CoreNetworkArn

The ARN of a core network.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 500.

Pattern: `[\s\S]*`

Required: No

CoreNetworkId

The ID of the core network for the peering request.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 50.

Pattern: `^core-network-([0-9a-f]{8,17})$`

Required: No

CreatedAt

The timestamp when the attachment peer was created.

Type: Timestamp

Required: No

EdgeLocation

The edge location for the peer.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 63.

Pattern: `[\s\S]*`

Required: No

LastModificationErrors

Describes the error associated with the Connect peer request.

Type: Array of [PeeringError](#) objects

Array Members: Minimum number of 0 items. Maximum number of 20 items.

Required: No

OwnerAccountId

The ID of the account owner.

Type: String

Length Constraints: Fixed length of 12.

Pattern: `[\s\S]*`

Required: No

PeeringId

The ID of the peering attachment.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 50.

Pattern: `^peering-([0-9a-f]{8,17})$`

Required: No

PeeringType

The type of peering. This will be TRANSIT_GATEWAY.

Type: String

Valid Values: TRANSIT_GATEWAY

Required: No

ResourceArn

The resource ARN of the peer.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 1500.

Pattern: `[\s\S]*`

Required: No

State

The current state of the peering connection.

Type: String

Valid Values: CREATING | FAILED | AVAILABLE | DELETING

Required: No

Tags

The list of key-value tags associated with the peering.

Type: Array of [Tag](#) objects

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

PeeringError

Describes an error associated with a peering request.

Contents

Code

The error code for the peering request.

Type: String

Valid Values: TRANSIT_GATEWAY_NOT_FOUND |
TRANSIT_GATEWAY_PEERS_LIMIT_EXCEEDED | MISSING_PERMISSIONS
| INTERNAL_ERROR | EDGE_LOCATION_PEER_DUPLICATE |
INVALID_TRANSIT_GATEWAY_STATE

Required: No

Message

The message associated with the error code.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 10000000.

Pattern: [`\s\S`]*

Required: No

MissingPermissionsContext

Provides additional information about missing permissions for the peering error.

Type: [PermissionsErrorContext](#) object

Required: No

RequestId

The ID of the Peering request.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 10000000.

Pattern: `[\s\S]*`

Required: No

ResourceArn

The ARN of the requested peering resource.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 1500.

Pattern: `[\s\S]*`

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

PermissionsErrorContext

Describes additional information about missing permissions.

Contents

MissingPermission

The missing permissions.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 10000000.

Pattern: `[\s\S]*`

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

ProposedNetworkFunctionGroupChange

Describes proposed changes to a network function group.

Contents

AttachmentPolicyRuleNumber

The proposed new attachment policy rule number for the network function group.

Type: Integer

Required: No

NetworkFunctionGroupName

The proposed name change for the network function group name.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 256.

Pattern: `[\s\S]*`

Required: No

Tags

The list of proposed changes to the key-value tags associated with the network function group.

Type: Array of [Tag](#) objects

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

ProposedSegmentChange

Describes a proposed segment change. In some cases, the segment change must first be evaluated and accepted.

Contents

AttachmentPolicyRuleNumber

The rule number in the policy document that applies to this change.

Type: Integer

Required: No

SegmentName

The name of the segment to change.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 256.

Pattern: `[\s\S]*`

Required: No

Tags

The list of key-value tags that changed for the segment.

Type: Array of [Tag](#) objects

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)

- [AWS SDK for Ruby V3](#)

Relationship

Describes a resource relationship.

Contents

From

The ARN of the resource.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 256.

Pattern: `[\s\S]*`

Required: No

To

The ARN of the resource.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 256.

Pattern: `[\s\S]*`

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

RouteAnalysis

Describes a route analysis.

Contents

Destination

The destination.

Type: [RouteAnalysisEndpointOptions](#) object

Required: No

ForwardPath

The forward path.

Type: [RouteAnalysisPath](#) object

Required: No

GlobalNetworkId

The ID of the global network.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 50.

Pattern: `[\s\S]*`

Required: No

IncludeReturnPath

Indicates whether to analyze the return path. The return path is not analyzed if the forward path analysis does not succeed.

Type: Boolean

Required: No

OwnerAccountId

The ID of the AWS account that created the route analysis.

Type: String

Length Constraints: Fixed length of 12.

Pattern: `[\s\S]*`

Required: No

ReturnPath

The return path.

Type: [RouteAnalysisPath](#) object

Required: No

RouteAnalysisId

The ID of the route analysis.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 256.

Pattern: `[\s\S]*`

Required: No

Source

The source.

Type: [RouteAnalysisEndpointOptions](#) object

Required: No

StartTimestamp

The time that the analysis started.

Type: Timestamp

Required: No

Status

The status of the route analysis.

Type: String

Valid Values: RUNNING | COMPLETED | FAILED

Required: No

UseMiddleboxes

Indicates whether to include the location of middlebox appliances in the route analysis.

Type: Boolean

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

RouteAnalysisCompletion

Describes the status of an analysis at completion.

Contents

ReasonCode

The reason code. Available only if a connection is not found.

- `BLACKHOLE_ROUTE_FOR_DESTINATION_FOUND` - Found a black hole route with the destination CIDR block.
- `CYCLIC_PATH_DETECTED` - Found the same resource multiple times while traversing the path.
- `INACTIVE_ROUTE_FOR_DESTINATION_FOUND` - Found an inactive route with the destination CIDR block.
- `MAX_HOPS_EXCEEDED` - Analysis exceeded 64 hops without finding the destination.
- `ROUTE_NOT_FOUND` - Cannot find a route table with the destination CIDR block.
- `TGW_ATTACH_ARN_NO_MATCH` - Found an attachment, but not with the correct destination ARN.
- `TGW_ATTACH_NOT_FOUND` - Cannot find an attachment.
- `TGW_ATTACH_NOT_IN_TGW` - Found an attachment, but not to the correct transit gateway.
- `TGW_ATTACH_STABLE_ROUTE_TABLE_NOT_FOUND` - The state of the route table association is not associated.

Type: String

Valid Values: `TRANSIT_GATEWAY_ATTACHMENT_NOT_FOUND` | `TRANSIT_GATEWAY_ATTACHMENT_NOT_IN_TRANSIT_GATEWAY` | `CYCLIC_PATH_DETECTED` | `TRANSIT_GATEWAY_ATTACHMENT_STABLE_ROUTE_TABLE_NOT_FOUND` | `ROUTE_NOT_FOUND` | `BLACKHOLE_ROUTE_FOR_DESTINATION_FOUND` | `INACTIVE_ROUTE_FOR_DESTINATION_FOUND` | `TRANSIT_GATEWAY_ATTACHMENT_ATTACH_ARN_NO_MATCH` | `MAX_HOPS_EXCEEDED` | `POSSIBLE_MIDDLEBOX` | `NO_DESTINATION_ARN_PROVIDED`

Required: No

ReasonContext

Additional information about the path. Available only if a connection is not found.

Type: String to string map

Key Length Constraints: Minimum length of 0. Maximum length of 10000000.

Key Pattern: `[\s\S]*`

Value Length Constraints: Minimum length of 0. Maximum length of 10000000.

Value Pattern: `[\s\S]*`

Required: No

ResultCode

The result of the analysis. If the status is `NOT_CONNECTED`, check the reason code.

Type: String

Valid Values: `CONNECTED` | `NOT_CONNECTED`

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

RouteAnalysisEndpointOptions

Describes a source or a destination.

Contents

IpAddress

The IP address.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 50.

Pattern: `[\s\S]*`

Required: No

TransitGatewayArn

The ARN of the transit gateway.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 500.

Pattern: `[\s\S]*`

Required: No

TransitGatewayAttachmentArn

The ARN of the transit gateway attachment.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 500.

Pattern: `[\s\S]*`

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

RouteAnalysisEndpointOptionsSpecification

Describes a source or a destination.

Contents

IpAddress

The IP address.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 50.

Pattern: `[\s\S]*`

Required: No

TransitGatewayAttachmentArn

The ARN of the transit gateway attachment.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 500.

Pattern: `[\s\S]*`

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

RouteAnalysisPath

Describes a route analysis path.

Contents

CompletionStatus

The status of the analysis at completion.

Type: [RouteAnalysisCompletion](#) object

Required: No

Path

The route analysis path.

Type: Array of [PathComponent](#) objects

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

RouteTableIdentifier

Describes a route table.

Contents

CoreNetworkNetworkFunctionGroup

The route table identifier associated with the network function group.

Type: [CoreNetworkNetworkFunctionGroupIdentifier](#) object

Required: No

CoreNetworkSegmentEdge

The segment edge in a core network.

Type: [CoreNetworkSegmentEdgeIdentifier](#) object

Required: No

TransitGatewayRouteTableArn

The ARN of the transit gateway route table for the attachment request. For example, "TransitGatewayRouteTableArn": "arn:aws:ec2:us-west-2:123456789012:transit-gateway-route-table/tgw-rtb-9876543210123456".

Type: String

Length Constraints: Minimum length of 0. Maximum length of 500.

Pattern: `[\s\S]*`

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)

- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

ServiceInsertionAction

Describes the action that the service insertion will take for any segments associated with it.

Contents

Action

The action the service insertion takes for traffic. `send-via` sends east-west traffic between attachments. `send-to` sends north-south traffic to the security appliance, and then from that to either the Internet or to an on-premises location.

Type: String

Valid Values: `send-via` | `send-to`

Required: No

Mode

Describes the mode packets take for the `send-via` action. This is not used when the action is `send-to`. `dual-hop` packets traverse attachments in both the source to the destination core network edges. This mode requires that an inspection attachment must be present in all Regions of the service insertion-enabled segments. For `single-hop`, packets traverse a single intermediate inserted attachment. You can use `EdgeOverride` to specify a specific edge to use.

Type: String

Valid Values: `dual-hop` | `single-hop`

Required: No

Via

The list of network function groups and any edge overrides for the chosen service insertion action. Used for both `send-to` or `send-via`.

Type: [Via](#) object

Required: No

WhenSentTo

The list of destination segments if the service insertion action is `send-via`.

Type: [WhenSentTo](#) object

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

ServiceInsertionSegments

Describes the segments associated with the service insertion action.

Contents

SendTo

The list of segments associated with the send-to action.

Type: Array of strings

Length Constraints: Minimum length of 0. Maximum length of 256.

Pattern: `[\s\S]*`

Required: No

SendVia

The list of segments associated with the send-via action.

Type: Array of strings

Length Constraints: Minimum length of 0. Maximum length of 256.

Pattern: `[\s\S]*`

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

Site

Describes a site.

Contents

CreatedAt

The date and time that the site was created.

Type: Timestamp

Required: No

Description

The description of the site.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 256.

Pattern: `[\s\S]*`

Required: No

GlobalNetworkId

The ID of the global network.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 50.

Pattern: `[\s\S]*`

Required: No

Location

The location of the site.

Type: [Location](#) object

Required: No

SiteArn

The Amazon Resource Name (ARN) of the site.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 500.

Pattern: `[\s\S]*`

Required: No

Siteld

The ID of the site.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 50.

Pattern: `[\s\S]*`

Required: No

State

The state of the site.

Type: String

Valid Values: PENDING | AVAILABLE | DELETING | UPDATING

Required: No

Tags

The tags for the site.

Type: Array of [Tag](#) objects

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

SiteToSiteVpnAttachment

Creates a site-to-site VPN attachment.

Contents

Attachment

Provides details about a site-to-site VPN attachment.

Type: [Attachment](#) object

Required: No

VpnConnectionArn

The ARN of the site-to-site VPN attachment.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 500.

Pattern: `^arn:[^:]{1,63}:ec2:[^:]{0,63}:[^:]{0,63}:vpn-connection[/vpn-[0-9a-f]{8,17}]$`

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

Tag

Describes a tag.

Contents

Key

The tag key.

Constraints: Maximum length of 128 characters.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 10000000.

Pattern: `[\s\S]*`

Required: No

Value

The tag value.

Constraints: Maximum length of 256 characters.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 10000000.

Pattern: `[\s\S]*`

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

TransitGatewayConnectPeerAssociation

Describes a transit gateway Connect peer association.

Contents

DeviceId

The ID of the device.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 50.

Pattern: `[\s\S]*`

Required: No

GlobalNetworkId

The ID of the global network.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 50.

Pattern: `[\s\S]*`

Required: No

LinkId

The ID of the link.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 50.

Pattern: `[\s\S]*`

Required: No

State

The state of the association.

Type: String

Valid Values: PENDING | AVAILABLE | DELETING | DELETED

Required: No

TransitGatewayConnectPeerArn

The Amazon Resource Name (ARN) of the transit gateway Connect peer.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 500.

Pattern: `[\s\S]*`

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

TransitGatewayPeering

Describes a transit gateway peering attachment.

Contents

Peering

Describes a transit gateway peer connection.

Type: [Peering](#) object

Required: No

TransitGatewayArn

The ARN of the transit gateway.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 500.

Pattern: `[\s\S]*`

Required: No

TransitGatewayPeeringAttachmentId

The ID of the transit gateway peering attachment.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 50.

Pattern: `^tgw-attach-([0-9a-f]{8,17})$`

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

TransitGatewayRegistration

Describes the registration of a transit gateway to a global network.

Contents

GlobalNetworkId

The ID of the global network.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 50.

Pattern: `[\s\S]*`

Required: No

State

The state of the transit gateway registration.

Type: [TransitGatewayRegistrationStateReason](#) object

Required: No

TransitGatewayArn

The Amazon Resource Name (ARN) of the transit gateway.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 500.

Pattern: `[\s\S]*`

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

TransitGatewayRegistrationStateReason

Describes the status of a transit gateway registration.

Contents

Code

The code for the state reason.

Type: String

Valid Values: PENDING | AVAILABLE | DELETING | DELETED | FAILED

Required: No

Message

The message for the state reason.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 256.

Pattern: `[\s\S]*`

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

TransitGatewayRouteTableAttachment

Describes a transit gateway route table attachment.

Contents

Attachment

Describes a core network attachment.

Type: [Attachment](#) object

Required: No

PeeringId

The ID of the peering attachment.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 50.

Pattern: `^peering-([0-9a-f]{8,17})$`

Required: No

TransitGatewayRouteTableArn

The ARN of the transit gateway attachment route table. For example, "TransitGatewayRouteTableArn": "arn:aws:ec2:us-west-2:123456789012:transit-gateway-route-table/tgw-rtb-9876543210123456".

Type: String

Length Constraints: Minimum length of 0. Maximum length of 500.

Pattern: `[\s\S]*`

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

ValidationExceptionField

Describes a validation exception for a field.

Contents

Message

The message for the field.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 10000000.

Pattern: `[\s\S]*`

Required: Yes

Name

The name of the field.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 10000000.

Pattern: `[\s\S]*`

Required: Yes

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

Via

The list of network function groups and edge overrides for the service insertion action. Used for both the `send-to` and `send-via` actions.

Contents

NetworkFunctionGroups

The list of network function groups associated with the service insertion action.

Type: Array of [NetworkFunctionGroup](#) objects

Required: No

WithEdgeOverrides

Describes any edge overrides. An edge override is a specific edge to be used for traffic.

Type: Array of [EdgeOverride](#) objects

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

VpcAttachment

Describes a VPC attachment.

Contents

Attachment

Provides details about the VPC attachment.

Type: [Attachment](#) object

Required: No

Options

Provides details about the VPC attachment.

Type: [VpcOptions](#) object

Required: No

SubnetArns

The subnet ARNs.

Type: Array of strings

Length Constraints: Minimum length of 0. Maximum length of 500.

Pattern: `^arn:[^:]{1,63}:ec2:[^:]{0,63}:[^:]{0,63}:subnet\\/subnet-[0-9a-f]{8,17}$|^$`

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)

- [AWS SDK for Ruby V3](#)

VpcOptions

Describes the VPC options.

Contents

ApplianceModeSupport

Indicates whether appliance mode is supported. If enabled, traffic flow between a source and destination use the same Availability Zone for the VPC attachment for the lifetime of that flow. The default value is `false`.

Type: Boolean

Required: No

DnsSupport

Indicates whether DNS is supported.

Type: Boolean

Required: No

Ipv6Support

Indicates whether IPv6 is supported.

Type: Boolean

Required: No

SecurityGroupReferencingSupport

Indicates whether security group referencing is enabled for this VPC attachment. The default is `true`. However, at the core network policy-level the default is set to `false`.

Type: Boolean

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

WhenSentTo

Displays a list of the destination segments. Used only when the service insertion action is send-to.

Contents

WhenSentToSegmentsList

The list of destination segments when the service insertion action is send-to.

Type: Array of strings

Length Constraints: Minimum length of 0. Maximum length of 256.

Pattern: `[\s\S]*`

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

Common Parameters

The following list contains the parameters that all actions use for signing Signature Version 4 requests with a query string. Any action-specific parameters are listed in the topic for that action. For more information about Signature Version 4, see [Signing AWS API requests](#) in the *IAM User Guide*.

Action

The action to be performed.

Type: string

Required: Yes

Version

The API version that the request is written for, expressed in the format YYYY-MM-DD.

Type: string

Required: Yes

X-Amz-Algorithm

The hash algorithm that you used to create the request signature.

Condition: Specify this parameter when you include authentication information in a query string instead of in the HTTP authorization header.

Type: string

Valid Values: AWS4-HMAC-SHA256

Required: Conditional

X-Amz-Credential

The credential scope value, which is a string that includes your access key, the date, the region you are targeting, the service you are requesting, and a termination string ("aws4_request"). The value is expressed in the following format: *access_key/YYYYMMDD/region/service/aws4_request*.

For more information, see [Create a signed AWS API request](#) in the *IAM User Guide*.

Condition: Specify this parameter when you include authentication information in a query string instead of in the HTTP authorization header.

Type: string

Required: Conditional

X-Amz-Date

The date that is used to create the signature. The format must be ISO 8601 basic format (YYYYMMDD'T'HHMMSS'Z'). For example, the following date time is a valid X-Amz-Date value: 20120325T120000Z.

Condition: X-Amz-Date is optional for all requests; it can be used to override the date used for signing requests. If the Date header is specified in the ISO 8601 basic format, X-Amz-Date is not required. When X-Amz-Date is used, it always overrides the value of the Date header. For more information, see [Elements of an AWS API request signature](#) in the *IAM User Guide*.

Type: string

Required: Conditional

X-Amz-Security-Token

The temporary security token that was obtained through a call to AWS Security Token Service (AWS STS). For a list of services that support temporary security credentials from AWS STS, see [AWS services that work with IAM](#) in the *IAM User Guide*.

Condition: If you're using temporary security credentials from AWS STS, you must include the security token.

Type: string

Required: Conditional

X-Amz-Signature

Specifies the hex-encoded signature that was calculated from the string to sign and the derived signing key.

Condition: Specify this parameter when you include authentication information in a query string instead of in the HTTP authorization header.

Type: string

Required: Conditional

X-Amz-SignedHeaders

Specifies all the HTTP headers that were included as part of the canonical request. For more information about specifying signed headers, see [Create a signed AWS API request](#) in the *IAM User Guide*.

Condition: Specify this parameter when you include authentication information in a query string instead of in the HTTP authorization header.

Type: string

Required: Conditional

Common Errors

This section lists the errors common to the API actions of all AWS services. For errors specific to an API action for this service, see the topic for that API action.

AccessDeniedException

You do not have sufficient access to perform this action.

HTTP Status Code: 403

ExpiredTokenException

The security token included in the request is expired

HTTP Status Code: 403

IncompleteSignature

The request signature does not conform to AWS standards.

HTTP Status Code: 403

InternalFailure

The request processing has failed because of an unknown error, exception or failure.

HTTP Status Code: 500

MalformedHttpRequestException

Problems with the request at the HTTP level, e.g. we can't decompress the body according to the decompression algorithm specified by the content-encoding.

HTTP Status Code: 400

NotAuthorized

You do not have permission to perform this action.

HTTP Status Code: 401

OptInRequired

The AWS access key ID needs a subscription for the service.

HTTP Status Code: 403

RequestAbortedException

Convenient exception that can be used when a request is aborted before a reply is sent back (e.g. client closed connection).

HTTP Status Code: 400

RequestEntityTooLargeException

Problems with the request at the HTTP level. The request entity is too large.

HTTP Status Code: 413

RequestExpired

The request reached the service more than 15 minutes after the date stamp on the request or more than 15 minutes after the request expiration date (such as for pre-signed URLs), or the date stamp on the request is more than 15 minutes in the future.

HTTP Status Code: 400

RequestTimeoutException

Problems with the request at the HTTP level. Reading the Request timed out.

HTTP Status Code: 408

ServiceUnavailable

The request has failed due to a temporary failure of the server.

HTTP Status Code: 503

ThrottlingException

The request was denied due to request throttling.

HTTP Status Code: 400

UnrecognizedClientException

The X.509 certificate or AWS access key ID provided does not exist in our records.

HTTP Status Code: 403

UnknownOperationException

The action or operation requested is invalid. Verify that the action is typed correctly.

HTTP Status Code: 404

ValidationError

The input fails to satisfy the constraints specified by an AWS service.

HTTP Status Code: 400