



Abhiruchulu — Database Schema

v1.0 · May 2026

Restaurant website & admin panel · Relational schema · 11 tables · Sheffield, UK

TABLE OVERVIEW

restaurants

id · name · tagline · address
phone · email · est_year
delivery settings · toggles

restaurant_hours

id · restaurant_id (FK)
day_label · open_time
close_time

menu_categories

id · name
display_order
created_at

menu_items

id · category_id (FK)
name · description · price
emoji · flags · timestamps

customers

id · name · email · phone
loyalty_points · status
joined_at · last_order_at

orders

id · customer_id (FK)
status · payment · totals
address · timestamps

order_items

id · order_id (FK)
menu_item_id (FK) · name
snapshot
price snapshot · qty ·
line_total

coupons

id · code · title
discount_type ·
discount_value
min_order · uses ·
expires_at

coupon_redemptions

id · coupon_id (FK)
order_id (FK)
discount_applied ·
redeemed_at

reviews

id · customer_id (FK)
menu_item_id (FK, nullable)
rating · text · status

inventory_items

id · name · category
current_stock · unit
min_stock · max_stock

TABLE DEFINITIONS

restaurants

Top-level restaurant configuration — one row per restaurant

[CONFIG](#)

COLUMN	TYPE	FLAGS	DESCRIPTION
id	INT	PK NOT NULL	Auto-increment primary key
name	VARCHAR(120)	NOT NULL	Restaurant display name (e.g. "Abhiruchulu")
tagline	VARCHAR(255)	NULLABLE	Short strapline shown in header/footer
established_year	SMALLINT	NULLABLE	Year founded (e.g. 2000)
address	VARCHAR(255)	NOT NULL	Full street address
phone	VARCHAR(30)	NOT NULL	Contact phone number
email	VARCHAR(120)	NOT NULL UNIQUE	Contact / booking email
min_order_amount	DECIMAL(8,2)	DEFAULT 15.00	Minimum order value for delivery
delivery_charge	DECIMAL(8,2)	DEFAULT 2.99	Flat delivery fee
free_delivery_threshold	DECIMAL(8,2)	DEFAULT 35.00	Order total above which delivery is free
tax_rate	DECIMAL(5,2)	DEFAULT 0.00	Applicable tax percentage
loyalty_points_rate	SMALLINT	DEFAULT 2	Points awarded per £1 spent
delivery_enabled	BOOLEAN	DEFAULT TRUE	Toggle delivery orders on/off
online_orders_enabled	BOOLEAN	DEFAULT TRUE	Toggle the full ordering flow
maintenance_mode	BOOLEAN	DEFAULT FALSE	Show maintenance page to all visitors
reviews_public_by_default	BOOLEAN	DEFAULT FALSE	Auto-publish reviews without manual approval
delivery_radius_miles	SMALLINT	DEFAULT 5	Max delivery distance from restaurant
updated_at	TIMESTAMP	DEFAULT NOW()	Last settings update timestamp

restaurant_hours

Operating hours per day-band (e.g. "Mon–Thu: 12pm–10pm")

[CONFIG](#)

COLUMN	TYPE	FLAGS	DESCRIPTION
id	INT	PK NOT NULL	Auto-increment primary key
restaurant_id	INT	FK NOT NULL	→ restaurants.id
day_label	VARCHAR(40)	NOT NULL	Display label (e.g. "Mon – Thu", "Sunday")
open_time	TIME	NOT NULL	Opening time (24h)
close_time	TIME	NOT NULL	Closing time (24h)
display_order	SMALLINT	DEFAULT 0	Sort order for display

menu_categories Menu sections (Starters, Mains, Breads, Rice, Desserts, Drinks) MENU			
COLUMN	TYPE	FLAGS	DESCRIPTION
id	INT	PK NOT NULL	Auto-increment primary key
name	VARCHAR(80)	NOT NULL UNIQUE	Category name (e.g. "Starters")
display_order	SMALLINT	DEFAULT 0	Sort position in the menu filter bar
created_at	TIMESTAMP	DEFAULT NOW()	Row creation timestamp

menu_items Individual dishes available for order — core menu catalogue MENU			
COLUMN	TYPE	FLAGS	DESCRIPTION
id	VARCHAR(60)	PK NOT NULL	Slug key (e.g. "hyderabadi-biryani")
category_id	INT	FK NOT NULL	→ menu_categories.id
name	VARCHAR(120)	NOT NULL	Display name of the dish
description	TEXT	NULLABLE	Short description shown on the menu card
price	DECIMAL(8,2)	NOT NULL	Selling price in GBP
emoji	VARCHAR(10)	NULLABLE	Representative emoji character
is_vegetarian	BOOLEAN	DEFAULT FALSE	Veg/non-veg indicator for green/red badge
is_popular	BOOLEAN	DEFAULT FALSE	Shows "Popular" badge on card
is_hero	BOOLEAN	DEFAULT FALSE	Featured in home-page hero section
is_available	BOOLEAN	DEFAULT TRUE	Whether the item is currently on sale
created_at	TIMESTAMP	DEFAULT NOW()	Row creation timestamp
updated_at	TIMESTAMP	DEFAULT NOW()	Last modification timestamp

customers Registered customer accounts with loyalty programme tracking CUSTOMERS			
COLUMN	TYPE	FLAGS	DESCRIPTION
id	VARCHAR(10)	PK NOT NULL	Customer identifier (e.g. "C001")
name	VARCHAR(120)	NOT NULL	Full name
email	VARCHAR(180)	NOT NULL UNIQUE	Login email — must be unique
phone	VARCHAR(30)	NULLABLE	Contact phone number
loyalty_points	INT	DEFAULT 0	Accumulated loyalty points balance
total_spent	DECIMAL(10,2)	DEFAULT 0.00	Lifetime spend — updated on every completed order
total_orders	INT	DEFAULT 0	Completed order count
status	ENUM	NOT NULL	'active' 'inactive'
joined_at	TIMESTAMP	DEFAULT NOW()	Account registration date
last_order_at	TIMESTAMP	NULLABLE	Timestamp of most recent order

orders				ORDERS
Customer order records — header-level data; line items in order_items				
COLUMN	TYPE	FLAGS	DESCRIPTION	
id	VARCHAR(10)	PK NOT NULL	Order reference number (e.g. "#1042")	
customer_id	VARCHAR(10)	FK NULLABLE	→ customers.id (NULL for guest orders)	
order_type	ENUM	NOT NULL	'delivery' 'collection'	
status	ENUM	NOT NULL INDEX	'confirmed' 'preparing' 'out-for-delivery' 'delivered' 'cancelled' 'pending'	
payment_status	ENUM	NOT NULL	'paid' 'pending' 'refunded'	
payment_method	ENUM	NOT NULL	'card' 'applepay' 'cash'	
subtotal	DECIMAL(10,2)	NOT NULL	Pre-discount item total	
discount_amount	DECIMAL(10,2)	DEFAULT 0.00	Coupon discount applied	
delivery_fee	DECIMAL(8,2)	DEFAULT 0.00	Delivery charge for this order	
total	DECIMAL(10,2)	NOT NULL	Final amount charged (subtotal – discount + delivery)	
customer_name	VARCHAR(120)	NOT NULL	Snapshot of customer name at order time	
customer_email	VARCHAR(180)	NOT NULL	Snapshot of email at order time	
customer_phone	VARCHAR(30)	NULLABLE	Contact phone at order time	
delivery_address	VARCHAR(255)	NULLABLE	Full street address (NULL for collection)	
delivery_postcode	VARCHAR(10)	NULLABLE	Postcode for geo-validation	
special_instructions	TEXT	NULLABLE	Free-text notes from the customer	
time_preference	ENUM	DEFAULT 'asap'	'asap' 'scheduled'	
scheduled_time	TIMESTAMP	NULLABLE	Requested delivery/collection time (if scheduled)	
estimated_minutes	SMALLINT	NULLABLE	ETA given to customer (minutes from placement)	
placed_at	TIMESTAMP	INDEX DEFAULT NOW()	Timestamp when order was confirmed	
updated_at	TIMESTAMP	DEFAULT NOW()	Last status change timestamp	

order_items				ORDERS
Line items for each order — price/name snapshotted to preserve history				
COLUMN	TYPE	FLAGS	DESCRIPTION	
id	INT	PK NOT NULL	Auto-increment primary key	
order_id	VARCHAR(10)	FK NOT NULL INDEX	→ orders.id (CASCADE DELETE)	
menu_item_id	VARCHAR(60)	FK NULLABLE	→ menu_items.id (SET NULL on delete)	
item_name	VARCHAR(120)	NOT NULL	Name snapshot at time of order	
item_emoji	VARCHAR(10)	NULLABLE	Emoji snapshot	
unit_price	DECIMAL(8,2)	NOT NULL	Price per item at time of order	
quantity	SMALLINT	NOT NULL	Number of units ordered	
line_total	DECIMAL(10,2)	NOT NULL	unit_price × quantity	

coupons				MARKETING
Discount codes and promotional offers managed via admin panel				
COLUMN	TYPE	FLAGS	DESCRIPTION	
id	INT	PK NOT NULL	Auto-increment primary key	
code	VARCHAR(30)	NOT NULL UNIQUE INDEX	Coupon code entered by customer (e.g. "BIRYANI20")	
title	VARCHAR(160)	NOT NULL	Human-readable offer description	
discount_type	ENUM	NOT NULL	'percent' 'flat'	
discount_value	DECIMAL(8,2)	NOT NULL	Percentage or fixed £ amount	
min_order_amount	DECIMAL(8,2)	DEFAULT 0.00	Minimum basket value to unlock the coupon	
max_uses	INT	NULLABLE	Global redemption cap (NULL = unlimited)	
current_uses	INT	DEFAULT 0	Total times this coupon has been redeemed	
is_active	BOOLEAN	DEFAULT TRUE	Admin toggle to enable / disable the coupon	
expires_at	DATE	NULLABLE	Expiry date (NULL = never expires)	
created_at	TIMESTAMP	DEFAULT NOW()	Row creation timestamp	

coupon_redemptions				MARKETING
Audit log of every coupon applied to an order — one row per redemption				
COLUMN	TYPE	FLAGS	DESCRIPTION	
id	INT	PK NOT NULL	Auto-increment primary key	
coupon_id	INT	FK NOT NULL	→ coupons.id	
order_id	VARCHAR(10)	FK NOT NULL UNIQUE	→ orders.id (one coupon per order)	
customer_id	VARCHAR(10)	FK NULLABLE	→ customers.id (NULL for guest checkout)	
discount_applied	DECIMAL(10,2)	NOT NULL	Actual £ discount given at redemption time	
redeemed_at	TIMESTAMP	DEFAULT NOW()	Redemption timestamp	

reviews				CONTENT
Customer ratings and text reviews with admin moderation workflow				
COLUMN	TYPE	FLAGS	DESCRIPTION	
id	VARCHAR(10)	PK NOT NULL	Review ID (e.g. "R001")	
customer_id	VARCHAR(10)	FK NULLABLE	→ customers.id (NULL = anonymous review)	
menu_item_id	VARCHAR(60)	FK NULLABLE	→ menu_items.id (NULL = general restaurant review)	
customer_name	VARCHAR(120)	NOT NULL	Display name (snapshot for anonymous)	
avatar_initials	VARCHAR(3)	NULLABLE	2-letter initials for avatar placeholder	
rating	TINYINT	NOT NULL	Star rating 1–5	
review_text	TEXT	NOT NULL	Full review body text	
helpful_count	INT	DEFAULT 0	Number of "helpful" upvotes	
status	ENUM	NOT NULL INDEX	'published' 'pending' 'rejected'	
created_at	TIMESTAMP	DEFAULT NOW()	Submission timestamp	
published_at	TIMESTAMP	NULLABLE	Moderation approval timestamp	

inventory_items			
Kitchen stock levels with low-stock alerts configurable per ingredient			
INVENTORY			
COLUMN	TYPE	FLAGS	DESCRIPTION
id	VARCHAR(10)	PK NOT NULL	Item ID (e.g. "I001")
name	VARCHAR(120)	NOT NULL	Ingredient or supply name
category	VARCHAR(60)	NOT NULL	Group (Grains, Protein, Dairy, Spices, etc.)
current_stock	DECIMAL(10,3)	NOT NULL	Current quantity in stock
unit	VARCHAR(20)	NOT NULL	Unit of measure (kg, L, cans, etc.)
min_stock_level	DECIMAL(10,3)	NOT NULL	Reorder threshold — triggers low-stock alert
max_stock_level	DECIMAL(10,3)	NOT NULL	Maximum storage capacity
updated_at	TIMESTAMP	DEFAULT NOW()	Last stock adjustment timestamp

RELATIONSHIPS & FOREIGN KEYS

CONFIG <code>restaurants</code> → <code>restaurant_hours</code> 1:N <i>One restaurant has many opening-hour bands</i>	MENU <code>menu_categories</code> → <code>menu_items</code> 1:N <i>Each item belongs to exactly one category</i>
ORDERS — CUSTOMER <code>customers</code> → <code>orders</code> 1:N <i>One customer may have many orders (nullable for guest checkout)</i>	ORDERS — LINE ITEMS <code>orders</code> → <code>order_items</code> 1:N <i>One order contains one or more line items (CASCADE DELETE)</i>
ORDER ITEMS — MENU <code>menu_items</code> → <code>order_items</code> 1:N <i>FK SET NULL on delete to preserve order history if dish removed</i>	COUPONS — REDEMPTIONS <code>coupons</code> → <code>coupon_redemptions</code> 1:N <i>One coupon code may be redeemed many times (up to max_uses)</i>
ORDERS — REDEMPTIONS <code>orders</code> → <code>coupon_redemptions</code> 1:1 <i>An order can have at most one coupon applied (UNIQUE on order_id)</i>	REVIEWS <code>customers</code> → <code>reviews</code> 1:N <code>menu_items</code> → <code>reviews</code> 1:N <i>Reviews optionally link to a specific dish; both FKs are nullable</i>

ENUMERATED TYPES

<code>orders.status</code> confirmed preparing out-for-delivery delivered cancelled pending	<code>orders.payment_status</code> paid pending refunded	<code>orders.payment_method</code> card applepay cash
<code>orders.order_type</code> delivery collection	<code>orders.time_preference</code> asap scheduled	<code>coupons.discount_type</code> percent flat

customers.status

activeinactive

reviews.status

publishedpendingrejected

Flag Legend

PK

 Primary Key

FK

 Foreign Key

UNIQUE

 Unique Required

NOT NULL

INDEX

 Indexed

DEFAULT

 Has default

NULLABLE

 Optional