

Vector Network Coding Gap Sizes for the Generalized Combination Network

Ha Nguyen, Sven Puchinger, Antonia Wachter-Zeh
ha.nguyen@tum.de, sven.puchinger@tum.de, antonia.wachter-zeh@tum.de

August 17, 2019

Outline

- 1 Motivation
- 2 Topic-Mainsection 1
 - Topic-Subsection 1
 - Topic-Subsection 2
- 3 Conclusions

Outline

- 1 Motivation
- 2 Topic-Mainsection 1
 - Topic-Subsection 1
 - Topic-Subsection 2
- 3 Conclusions

Motivation

- Item 1
- Item 2
- Item 3
- Item 4
- Item 5

Example (Wonderful Example...)

This is the example environment...

⇒ Item after the example...

Motivation continued

Outline

- 1 Motivation
- 2 Topic-Mainsection 1
 - Topic-Subsection 1
 - Topic-Subsection 2
- 3 Conclusions

Topic 2.1

- Item 1
- Item 2
- Item 3

Definition (A Definition... e.g. the *Fourier-Transform*)

$$A(\omega) = \int_{t=-\infty}^{+\infty} a(t) \cdot e^{-j\omega t} dt \quad (1)$$

Topic 2.2

- Item 1
- Item 2
- Item 3

Outline

- 1 Motivation
- 2 Topic-Mainsection 1
 - Topic-Subsection 1
 - Topic-Subsection 2
- 3 Conclusions

Conclusions and Outlook

- Item 1 [1]
- Item 2
- Item 3

Thank you! Questions?

References:



J. Ebrahimi and C. Fragouli, "Algebraic algorithms for vector network coding," *IEEE Transactions on Information Theory*, vol. 57, no. 2, pp. 996–1007, Feb 2011.