


Community structure in hypergraphs and the emergence of polarization

Nicholas W. Landry, Juan G. Restrepo, University of Colorado Boulder

Background

Society has become increasingly divided in politics, social media, and ideology.



Republican (red) and Democrat (blue) representatives with edges drawn between members who agree above a threshold value of votes.
Andris et al. 2015

Polarization, the phenomenon where a community reinforces its own beliefs while another community does the same with a different set of beliefs, is often the result of “echo chambers”.

A *hypergraph* is an extension of a pairwise network that includes interactions of arbitrary size. An m -uniform hypergraph contains only m -hyperedges, i.e., interactions of size m . The average connection strength or *degree* is denoted $\langle k^{(m)} \rangle$.




Illustration of a hypergraph. Infected nodes (red) infect a healthy node (gray) via hyperedges of sizes 2 and 3 with rates β_2 and β_3 , respectively. Landry and Restrepo 2020.

(Uniform) hypergraph models

Stochastic Block Model (SBM)

m -uniform hypergraph with N nodes, each with a community label g_i .

m -dimensional tensor P specifying the probability that a hyperedge with nodes i_1, \dots, i_m and group memberships g_{i_1}, \dots, g_{i_m} are connected. (Supersymmetric tensor).

Planted Partition Model

SBM with two equally-sized communities and one parameter ϵ_m controlling community strength. ($\epsilon_m = 0$ is no communities, $\epsilon_m = \langle k^{(m)} \rangle$ is completely disconnected communities)

Degree-Corrected Stochastic Block Model (DCSBM)

Nodes i_1, \dots, i_m with degrees k_{i_1}, \dots, k_{i_m} are connected with probability proportional to $k_{i_1} \dots k_{i_m} \omega(g_{i_1}, \dots, g_{i_m})$, where ω is a tensor specifying the connection strengths between communities.

ODE Model

2-variable mean-field equation:

$-x_1$ is the fraction of community 1 infected and x_2 is the fraction of community 2 infected.


Denote link degrees as k and triangles as q .

$$\frac{dx_1}{dt} = -\gamma x_1 \quad \text{Healing}$$

$$+ \frac{\beta_2}{2} (1 - x_1) (\langle k \rangle (x_1 + x_2) + \epsilon_2 (x_1 - x_2)) \quad \text{Pairwise infection}$$

$$+ \frac{\beta_3}{4} (1 - x_1) (\langle q \rangle (x_1 + x_2)^2 + \epsilon_3 (3x_1^2 - 2x_1x_2 - x_2^2)) \quad \text{Triangle infection}$$

For the x_2 equation we substitute $x_2 \rightarrow x_1$.




Symmetric fixed points (Erdős-Rényi)

Asymmetric fixed points (Polarization exists)

Stable fixed points with polarization!

Numerical Results


Stability plot for planted partition model




Link community strength

Planted partition model

$$\epsilon_2 = 0, \langle k \rangle = \langle q \rangle = 20$$



Congress cosponsorship dataset



Conclusions

- When community structure is strong enough, stable polarized states exist.
- Higher-order interactions enable these polarized states.
- Degree heterogeneity strongly influences the magnitude of polarization.

Manuscript in preparation!