

Discussion 03

Pattern Matching

Kenneth Fang (kwf37), Newton Ni (cn279)

Feb. 3, 2019

Agenda

1. Review concept of pattern matching
2. Explore pattern matching with three different data structures:
 - ▶ Lists $v1::v2:: \dots ::vn::[]$
 - ▶ Records $\{\text{label1}=v1, \text{label2}=v2, \dots, \text{labeln} = vn\}$
 - ▶ Tuples $(v1,v2,\dots,vn)$
3. Recitation 4

What is Pattern Matching?

What is Pattern Matching?

- ▶ How do we access data in arrays in an object-oriented language?

What is Pattern Matching?

- ▶ How do we access data in arrays in an object-oriented language?
- ▶ How do we access data in objects in an object-oriented language?

What is Pattern Matching?

- ▶ How do we access data in arrays in an object-oriented language?
- ▶ How do we access data in objects in an object-oriented language?
- ▶ What if we extracted data by leveraging the *structure* of the data?

What is Pattern Matching?

- ▶ How do we access data in arrays in an object-oriented language?
- ▶ How do we access data in objects in an object-oriented language?
- ▶ What if we extracted data by leveraging the *structure* of the data?
- ▶ When pattern matching, we can ensure that our data accesses are exhaustive and that every branch in the pattern match is being used

Lists

Lists in OCaml are

- ▶ Singly-linked lists
- ▶ Immutable
- ▶ “First-class” data structures

Lists

Lists are defined to be either

- ▶ Nil []
- ▶ Cons $h :: t$

Lists

Lists are defined to be either

- ▶ Nil []
- ▶ Cons h :: t

Lists can be constructed using the following syntax:

- ▶ []
- ▶ e1 :: e2 :: e3 :: []
- ▶ [e1; e2; e3] (syntactic sugar for above syntax)

Lists in OCaml are

List Static Semantics

- ▶ The empty list Nil has type `'a list`

List Static Semantics

- ▶ The empty list `Nil` has type `'a list`
- ▶ The list `e1 :: []` has type `t list` if `e1 : t`

List Static Semantics

- ▶ The empty list `Nil` has type `'a list`
- ▶ The list `e1 :: []` has type `t list` if `e1 : t`
- ▶ All elements in a list must have the same type

List Static Semantics

- ▶ The empty list Nil has type `'a list`
- ▶ The list `e1 :: []` has type `t list` if `e1 : t`
- ▶ All elements in a list must have the same type
- ▶ For the cons operator `h :: t`, if `h:typ`, then it must be true that `t:typ list`

List Static Semantics

- ▶ The empty list Nil has type `'a list`
- ▶ The list `e1 :: []` has type `t list` if `e1 : t`
- ▶ All elements in a list must have the same type
- ▶ For the cons operator `h :: t`, if `h:typ`, then it must be true that `t:typ list`
- ▶ What is the type of the cons operator (`::`)?

List Pattern Matching

Typically a list can be broken down as follows:

```
match lst with
| [] -> (*Do something when list is empty*)
| h::t -> (*Do something with head or tail*)
```


List Length

```
let rec length lst =
```

List Length

```
let rec length lst =  
  match lst with  
  | [] -> 0  
  | h::t -> 1 + (length t)
```

List Length With Syntactic Sugar and Wildcard

```
let rec length = function  
  | [] -> 0  
  | _::t -> 1 + (length t)
```

Sum Last Two Elements of (Int) List

```
let rec sum_last_two = function
```

Sum Last Two Elements of (Int) List

```
let rec sum_last_two = function
  | x1::x2::[] -> x1 + x2
  | _::t -> sum_last_two t
  | _ -> raise LengthException
```

Records (By Name)

We can define record *types* that have multiple fields and then create record *expressions* that have that type. Data fields are structured by name.

Records (By Name)

We can define record *types* that have multiple fields and then create record *expressions* that have that type. Data fields are structured by name.

- ▶ Record type definition:

```
type student = {name:string; age:int; is_sleepy:bool}
```

Records (By Name)

We can define record *types* that have multiple fields and then create record *expressions* that have that type. Data fields are structured by name.

- ▶ Record type definition:

```
type student = {name:string; age:int; is_sleepy:bool}
```

- ▶ Record expression:

```
let kenneth = {name=kenneth; age=20; is_sleepy=true}
```


Records (By Name)

We can define record *types* that have multiple fields and then create record *expressions* that have that type. Data fields are structured by name.

- ▶ Record type definition:

```
type student = {name:string; age:int; is_sleepy:bool}
```

- ▶ Record expression:

```
let kenneth = {name=kenneth; age=20; is_sleepy=true}
```

- ▶ Record expression using `with` keyword:

```
{let newton = kenneth with name=newton; age=21}
```

Records (By Name)

How do we access data?

- ▶ Method 1: Dot Notation

`kenneth.name`

- ▶ Method 2: Pattern Matching

```
match kenneth with  
| {name=n;age=x;is_sleepy=s} -> n
```

Tuples (By Position)

Tuples are also data structures that have multiple fields, but they are not labelled. Instead, data is structured based on the *position*.

- ▶ Type definition:

- ▶ Tuple type definition:

- ```
type student = string * int * bool
```

# Tuples (By Position)

Tuples are also data structures that have multiple fields, but they are not labelled. Instead, data is structured based on the *position*.

- ▶ Type definition:

- ▶ Tuple type definition:

- ```
type student = string * int * bool
```

- ▶ Tuple expression:

- ```
let kenneth = (kenneth, 20, true)
```

# Tuples (By Position)

How do we access data?

- ▶ Method 1: Pattern Matching

```
match kenneth with
 | (name, age, is_sleepy_boi) -> name
```

- ▶ The standard library comes with the `fst` and `snd` functions, which can be used to extract the first and second fields of a tuple, respectively.

# List Equality

```
let rec list_equals l1 l2 =
```

# List Equality

```
let rec list_equals l1 l2 =
 match (l1,l2) with
 | ([],[]) -> true
 | (h1::t1, h2::t2) when h1 = h2 -> list_equals t1 t2
 | _ -> false
```

# Recitation Questions

