# Discussion 12 Balanced Trees

Kenneth Fang (kwf37), Newton Ni (cn279)

March 13, 2019



► Red-Black Trees

- ► Red-Black Trees
  - Invariants

- ► Red-Black Trees
  - Invariants
  - Insertion

- ► Red-Black Trees
  - Invariants
  - Insertion
  - Deletion

# Type

```
type color =
| R
| B


type 'a tree =
| Leaf
| Node of color * 'a * 'a tree * 'a tree
```





### **Invariants**

► Convention: root node is black












#### **Invariants**

▶ There are no two adjacent red nodes along any path












## **Invariants**

▶ Every path from root to leaf has equal number of **black** nodes







### Insertion


Assume invariants hold before insertion




### Insertion


- Assume invariants hold before insertion
- ► Fix invariants after insertion


















































# Insertion: Summary

► Similar to regular binary tree insertion

## Insertion: Summary

- Similar to regular binary tree insertion
- Reconstruct balanced tree as we insert

## Insertion: Summary

- ► Similar to regular binary tree insertion
- Reconstruct balanced tree as we insert
- ▶ insert l v |> balance |> rep\_ok

### Deletion

► See paper by Germane, Might



#### **Deletion**

- See paper by Germane, Might
- ► Central idea: introduce **double-black** node during deletion

#### Deletion

- See paper by Germane, Might
- ► Central idea: introduce **double-black** node during deletion
- ▶ type color = R | B | BB

