ELE HSM API Rev 1.0 NXP Copyright

Generated by Doxygen 1.8.17

1 ELE HSM API	1
2 Revision History	1
3 General concepts related to the API	2
3.1 Session	2
3.2 Service flow	2
3.3 Example	3
3.4 Key store	3
3.4.1 Key management	3
3.4.2 NVM writing	4
3.5 Implementation specificities	4
4 Module Index	4
4.1 Modules	4
5 Module Documentation	5
5.1 Session	5
5.1.1 Detailed Description	6
5.1.2 Data Structure Documentation	6
5.1.3 Typedef Documentation	6
5.1.4 Function Documentation	7
5.2 Key management	10
5.2.1 Detailed Description	12
5.2.2 Data Structure Documentation	12
5.2.3 Macro Definition Documentation	15
5.2.4 Typedef Documentation	16
5.2.5 Enumeration Type Documentation	17
5.2.6 Function Documentation	18
5.3 Ciphering	22
5.3.1 Detailed Description	22
5.3.2 Data Structure Documentation	22
5.3.3 Macro Definition Documentation	23
5.3.4 Typedef Documentation	24
5.3.5 Enumeration Type Documentation	24
5.3.6 Function Documentation	25
5.4 Signature generation	28
5.4.1 Detailed Description	29
5.4.2 Data Structure Documentation	29
5.4.3 Macro Definition Documentation	29
5.4.4 Typedef Documentation	30
5.4.5 Enumeration Type Documentation	30
5.4.6 Function Documentation	30
5.5 Signature verification	34

5.5.1 Detailed Description	3
5.5.2 Data Structure Documentation	34
5.5.3 Macro Definition Documentation	3
5.5.4 Typedef Documentation	30
5.5.5 Function Documentation	30
5.6 Random number generation	3
5.6.1 Detailed Description	3
5.6.2 Data Structure Documentation	3
5.6.3 Function Documentation	3
5.7 Hashing	4
5.7.1 Detailed Description	4
5.7.2 Data Structure Documentation	4
5.7.3 Macro Definition Documentation	4
5.7.4 Enumeration Type Documentation	4
5.7.5 Function Documentation	4
5.8 Data storage	4
5.8.1 Detailed Description	4
5.8.2 Data Structure Documentation	4
5.8.3 Typedef Documentation	4
5.8.4 Function Documentation	4
5.9 Authenticated Encryption	4
5.9.1 Detailed Description	4
5.9.2 Function Documentation	48
5.10 Mac	49
5.10.1 Detailed Description	49
5.10.2 Data Structure Documentation	49
5.10.3 Macro Definition Documentation	50
5.10.4 Typedef Documentation	50
5.10.5 Function Documentation	5
5.11 Dump Firmware Log	5
5.11.1 Detailed Description	5
5.11.2 Data Structure Documentation	5
5.11.3 Function Documentation	5
5.12 Dev attest	5
5.12.1 Detailed Description	5
5.12.2 Data Structure Documentation	5
5.12.3 Function Documentation	5
5.13 Dev Info	5
5.13.1 Detailed Description	5
5.13.2 Data Structure Documentation	5
5.13.3 Function Documentation	5
5.14 Generic Crypto: Asymmetric Crypto	59

1 ELE HSM API

Index		77
	5.20.2 Enumeration Type Documentation	74
	5.20.1 Detailed Description	74
5.20	Error codes	74
	5.19.4 Function Documentation	72
	5.19.3 Enumeration Type Documentation	72
	5.19.2 Data Structure Documentation	72
	5.19.1 Detailed Description	72
5.19	Life Cycle update	72
	5.18.5 Function Documentation	70
	5.18.4 Typedef Documentation	70
	5.18.3 Macro Definition Documentation	70
	5.18.2 Data Structure Documentation	69
	5.18.1 Detailed Description	69
5.18	Key store	69
	5.17.3 Function Documentation	67
	5.17.2 Data Structure Documentation	67
	5.17.1 Detailed Description	67
5.17	Public key recovery	67
	5.16.3 Function Documentation	65
	5.16.2 Data Structure Documentation	65
	5.16.1 Detailed Description	65
5.16	Get Info	65
	5.15.3 Function Documentation	63
	5.15.2 Data Structure Documentation	63
	5.15.1 Detailed Description	63
5.15	Generic Crypto Asymmetric Key Generate	63
	5.14.6 Function Documentation	62
	5.14.5 Enumeration Type Documentation	62
	5.14.4 Typedef Documentation	61
	5.14.3 Macro Definition Documentation	61
	5.14.2 Data Structure Documentation	60
	5.14.1 Detailed Description	60


1 ELE HSM API

This document is a software referece description of the API provided by the i.MX8ULP, i.MX93 HSM solutions for ELE Platform.

2 Revision History

Revision	date	description
0.1	Apr 27 2023	Preliminary draft

3 General concepts related to the API



3.1 Session

The API must be initialized by a potential requestor by opening a session.

The session establishes a route (MU, DomainID...) between the requester and the HSM. When a session is opened, the HSM returns a handle identifying the session to the requester.

3.2 Service flow

For a given category of services which require service handle, the requestor is expected to open a service flow by invoking the appropriate HSM API.

The session handle, as well as the control data needed for the service flow, are provided as parameters of the call. Upon reception of the open request, the HSM allocates a context in which the session handle, as well as the provided control parameters are stored and return a handle identifying the service flow.

The context is preserved until the service flow, or the session, are closed by the user and it is used by the HSM to proceed with the sub-sequent operations requested by the user on the service flow.

3.3 Example

3.3 Example

```
/* Open a session: create a route between the user and the HSM */
hsm_open_session(&open_session_args, &session_hdl);

/* Open a key store - user is authenticated */
hsm_open_key_store_service(session_hdl, &open_svc_key_store_args, &key_store_hdl);

/* Open cipher service - it grants access to ciphering operations */
hsm_open_cipher_service(key_store_hdl, &open_svc_cipher_args, &cipher_hdl);

/* Perform ECB, CCB ... */
hsm_cipher_one_go (cipher_hdl, &op_cipher_one_go_args);
/* Perform authenticate and encryption algos: e.g GCM */
hsm_auth_enc (cipher_hdl, &op_auth_enc_args);
/* Perform hashing operations: e.g SHA */
hsm_hash_one_go (hash_hdl, &op_hash_one_go_args);
/* Close the session and all the related services */
hsm_close_session(session_hdl);
```

3.4 Key store

A key store can be created by specifying the CREATE flag in the hsm_open_key_store_service API. Please note that the created key store will be not stored in the NVM till a key is generated or imported specyfing the "STRICT OPERATION" flag.

Only symmetric and private keys are stored into the key store. Public keys can be exported during the key pair generation operation or recalculated through the hsm_pub_key_recovery API.

Secret keys cannot be exported under any circumstances, while they can be imported in encrypted form.

3.4.1 Key management

Keys are divided in groups, keys belonging to the same group are written/read from the NVM as a monolitic block. Up to 3 key groups can be handled in the HSM local memory (those immediately available to perform crypto operations), while up to 1000 key groups can be handled in the external NVM and imported in the local memory as needed

If the local memory is full (3 key groups already reside in the HSM local memory) and a new key group is needed by an incoming user request, the HSM swaps one of the local key group with the one needed by the user request. The user can control which key group must be kept in the local memory (cached) through the manage_key_group API lock/unlock mechanism.

As general concept, frequently used keys should be kept, when possible, in the same key group and locked in the local memory for performance optimization.

3.4.2 NVM writing

All the APIs creating a key store (open key store API) or modyfing its content (key generation, key_management, key derivation functions) provide a "STRICT OPERATION" flag. If the flag is set, the HSM exports the relevant key store blocks into the external NVM and increments (blows one bit) the OTP monotonic counter used as roll back protection. In case of key generation/derivation /update the "STRICT OPERATION" has effect only on the target key group.

Any update to the key store must be considered as effective only after an operation specifying flag "STRICT OP ← ERATION" is aknowledged by the HSM. All the operations not specifying the "STRICT OPERATION" flags impact the HSM local memory only and will be lost in case of system reset

Due to the limited monotonic counter size, the user should, when possible, perform multiple udate before setting the "STRICT OPERATION" flag(i.e. keys to be updated should be kept in the same key group).

Once the monotonic counter is completely blown a warning is returned on each key store export to the NVM to inform the user that the new updates are not roll-back protected.

3.5 Implementation specificities

HSM API with common features are supported on i.MX8ULP and i.MX93. The details of supported features per chip will be listed in the platform specifities.

4 Module Index

4.1 Modules

Here is a list of all modules:

Session	5
Key management	10
Ciphering	22
Signature generation	28
Signature verification	34
Random number generation	39
Hashing	41
Data storage	44
Authenticated Encryption	48
Mac	49
Dump Firmware Log	54
Dev attest	55
Dev Info	57
Generic Crypto: Asymmetric Crypto	59
Generic Crypto Asymmetric Key Generate	63

5 Module Documentation 5

Get Info	65
Public key recovery	67
Key store	69
Life Cycle update	72
Error codes	74

5 Module Documentation

5.1 Session

The API must be initialized by a potential requestor by opening a session. Once a session is closed all the associated service flows are closed by the HSM.

Data Structures

- struct hsm_session_hdl_s
- struct hsm_service_hdl_s
- · struct open_session_args_t

Macros

• #define HSM MAX SESSIONS (8u)

Maximum sessions supported.

#define HSM_MAX_SERVICES (32u)

Maximum services supported.

#define HSM_OPEN_SESSION_PRIORITY_LOW (0x00U)

Low priority. default setting on platforms that doesn't support sessions priorities.

#define HSM_OPEN_SESSION_PRIORITY_HIGH (0x01U)

High Priority session.

#define HSM_OPEN_SESSION_FIPS_MODE_MASK (1u << 0)

Only FIPS certified operations authorized in this session.

#define HSM_OPEN_SESSION_EXCLUSIVE_MASK (1u << 1)

No other HSM session will be authorized on the same security enclave.

#define HSM OPEN SESSION LOW LATENCY MASK (1u << 3)

Use a low latency HSM implementation.

#define HSM_OPEN_SESSION_NO_KEY_STORE_MASK (1u << 4)

No key store will be attached to this session. May provide better performances on some operation depending on the implementation. Usage of the session will be restricted to operations that doesn't involve secret keys (e.g. hash, signature verification, random generation).

• #define $HSM_OPEN_SESSION_RESERVED_MASK$ ((1u << 2) | (1u << 5) | (1u << 6) | (1u << 7))

Bits reserved for future use. Should be set to 0.

Typedefs

• typedef uint32_t hsm_hdl_t

Functions

- hsm_err_t hsm_open_session (open_session_args_t *args, hsm_hdl_t *session_hdl)
- hsm_err_t hsm_close_session (hsm_hdl_t session_hdl)
- struct hsm session hdl s * session hdl to ptr (uint32 t hdl)
- struct hsm_service_hdl_s * service_hdl_to_ptr (uint32_t hdl)
- void delete_session (struct hsm_session_hdl_s *s_ptr)
- void delete_service (struct hsm_service_hdl_s *s_ptr)
- struct hsm_session_hdl_s * add_session (void)
- struct hsm_service_hdl_s * add_service (struct hsm_session_hdl_s *session)

5.1.1 Detailed Description

The API must be initialized by a potential requestor by opening a session. Once a session is closed all the associated service flows are closed by the HSM.

5.1.2 Data Structure Documentation

5.1.2.1 struct hsm_session_hdl_s Structure describing the session handle members

Data Fields

struct plat_os_abs_hdl *	phdl	Pointer to OS device node.
uint32_t	session_hdl	Session handle.
uint32_t	mu_type	Session MU type.

5.1.2.2 struct hsm_service_hdl_s Structure describing the service handle members

Data Fields

struct hsm_session_hdl_s *	session	Pointer to session handle.
uint32_t	service_hdl	Service handle.

5.1.2.3 struct open_session_args_t Structure detailing the open session operation member arguments

Data Fields

uint32_t	session_hdl	Session handle.
uint8_t	session_priority	Priority of the operations performed in this session.
uint8_t	operating_mode	Options for the session to be opened (bitfield).
uint8_t	interrupt_idx	Interrupt number of the MU used to indicate data availability.

5.1.3 Typedef Documentation

5.1 Session 7

5.1.3.1 hsm_hdl_t typedef uint32_t hsm_hdl_t

Define the HSM handle type

5.1.4 Function Documentation

Parameters

args	pointer to the structure containing the function arguments.
session_hdl	pointer to where the session handle must be written.

Returns

error_code error code.

Terminate a previously opened session. All the services opened under this session are closed as well

Parameters

session_hdl pointer to the handle identifying the

Returns

error_code error code.

Returns pointer to the session handle

Parameters

hdl	identifying the session handle.

Returns

pointer to the session handle.

```
5.1.4.4 service_hdl_to_ptr() struct hsm_service_hdl_s* service_hdl_to_ptr ( uint32_t hdl )
```

Returns pointer to the service handle

Parameters

hdl identify	ng the session handle.
--------------	------------------------

Returns

pointer to the service handle.

5.1.4.5 **delete_session()** void delete_session ($struct \ hsm_session_hdl_s * s_ptr$)

Delete the session

Parameters

```
s_ptr pointer identifying the session.
```


Delete the service

Parameters

s_ptr pointer identifying the service.

```
5.1.4.7 add_session() struct hsm_session_hdl_s* add_session ( void )
```

5.1 Session 9

Add the session

Returns

pointer to the session.

Add the service

Returns

pointer to the service.

5.2 Key management

Data Structures

```
    struct op_delete_key_args_t
```

- struct op_get_key_attr_args_t
- struct op_import_key_args_t
- struct kek_enc_key_hdr_t
- struct op_generate_key_ext_args_t
- struct op_generate_key_args_t
- struct open_svc_key_management_args_t

Macros

```
    #define HSM_OP_DEL_KEY_FLAGS_STRICT_OPERATION ((hsm_op_import_key_flags_t)(1u << 7))</li>
```

- #define HSM_OP_IMPORT_KEY_INPUT_E2GO_TLV ((hsm_op_import_key_flags_t)(1u << 0))
 - Bit 0: set 1 means input is E2GO_TLV.
- $\bullet \ \ \text{\#define HSM_OP_IMPORT_KEY_INPUT_SIGNED_MSG ((hsm_op_import_key_flags_t)(0u << 0))}\\$
 - Bit 0: set 0 means input is signed message.
- #define HSM_OP_IMPORT_KEY_FLAGS_STRICT_OPERATION ((hsm_op_import_key_flags_t)(1u << 7))

Bit 7: Strict: Request completed - New key written to NVM with updated MC.

- #define HSM_KEY_USAGE_EXPORT ((hsm_key_usage_t) (1u << 0))
- #define HSM KEY USAGE ENCRYPT ((hsm key usage t) (1u << 8))
- #define HSM_KEY_USAGE_DECRYPT ((hsm_key_usage_t) (1u << 9))
- #define HSM_KEY_USAGE_SIGN_MSG ((hsm_key_usage_t) (1u << 10))
- #define HSM KEY USAGE VERIFY MSG ((hsm key usage t) (1u << 11))
- #define HSM KEY USAGE SIGN HASH ((hsm key usage t) (1u << 12))
- #define HSM KEY USAGE VERIFY HASH ((hsm key usage t) (1u << 13))
- #define HSM_KEY_USAGE_DERIVE ((hsm_key_usage_t) (1u << 14))
- #define HSM_KEY_INFO_PERSISTENT ((hsm_key_info_t)(0u << 1))
- #define HSM_KEY_INFO_PERMANENT ((hsm_key_info_t)(1u << 0))
- #define HSM KEY INFO TRANSIENT ((hsm key info t)(1u << 1))
- #define HSM_KEY_INFO_MASTER ((hsm_key_info_t)(1u << 2))
- #define HSM_KEY_INFO_KEK ((hsm_key_info_t)(1u << 3))
- #define FLAG 0
- #define HSM_OP_KEY_GENERATION_FLAGS_STRICT_OPERATION ((hsm_op_key_gen_flags_t)(1u << 7))

Typedefs

- typedef uint8_t hsm_op_delete_key_flags_t
- typedef uint8_t hsm_op_import_key_flags_t
- typedef uint32 t hsm key usage t
- typedef uint16_t hsm_key_group_t
- typedef uint16_t hsm_key_info_t
- typedef uint8_t hsm_op_key_gen_flags_t

Reserverd Bits 0 - 6.

• typedef uint8_t hsm_svc_key_management_flags_t

Enumerations

```
enum hsm_storage_loc_t { HSM_SE_KEY_STORAGE = 0x000000000 }

    enum hsm storage persist lvl t {

 HSM VOLATILE STORAGE = 0x0
 HSM_PERSISTENT_STORAGE = 0x1,
 HSM_PERMANENT_STORAGE = 0xFF }

    enum hsm key lifetime t {

 HSM_SE_KEY_STORAGE_VOLATILE = HSM_SE_KEY_STORAGE | HSM_VOLATILE_STORAGE,
 HSM_SE_KEY_STORAGE_PERSISTENT = HSM_SE_KEY_STORAGE | HSM_PERSISTENT_STORAGE,
 HSM_SE_KEY_STORAGE_PERS_PERM = HSM_SE_KEY_STORAGE | HSM_PERMANENT_STORAGE
enum hsm pubkey type t {
 HSM PUBKEY TYPE RSA = 0x4001,
 HSM PUBKEY TYPE ECC BP R1 = 0x4130,
 HSM_PUBKEY_TYPE_ECC_NIST = 0x4112,
 HSM_PUBKEY_TYPE_ECC_BP_T1 = 0xC180 }
enum hsm_key_type_t {
 HSM_KEY_TYPE_HMAC = 0x1100,
 HSM_KEY_TYPE_AES = 0x2400,
 HSM KEY TYPE SM4 = 0x2405,
 HSM_KEY_TYPE_RSA = 0x7001,
 HSM_KEY_TYPE_ECC_BP_R1 = 0x7130,
 HSM KEY TYPE ECC NIST = 0x7112 }
enum hsm bit key sz t {
 HSM KEY SIZE HMAC 224 = 224,
 HSM KEY SIZE HMAC 256 = 256,
 HSM_KEY_SIZE_HMAC_384 = 384,
 HSM_KEY_SIZE_HMAC_512 = 512,
 HSM_KEY_SIZE_AES_128 = 128,
 HSM KEY SIZE AES 192 = 192,
 HSM KEY SIZE AES 256 = 256,
 HSM_KEY_SIZE_SM4_128 = 128,
 HSM KEY SIZE RSA 2048 = 2048,
 HSM_KEY_SIZE_RSA_3072 = 3072,
 HSM_KEY_SIZE_RSA_4096 = 4096,
 HSM_KEY_SIZE_ECC_BP_R1_224 = 224,
 HSM KEY SIZE ECC BP R1 256 = 256,
 HSM_KEY_SIZE_ECC_BP_R1_320 = 320,
 HSM_KEY_SIZE_ECC_BP_R1_384 = 384,
 HSM_KEY_SIZE_ECC_BP_R1_512 = 512,
 HSM KEY SIZE ECC NIST 224 = 224,
 HSM_KEY_SIZE_ECC_NIST_256 = 256,
 HSM KEY SIZE ECC NIST 384 = 384,
 HSM KEY SIZE ECC NIST 521 = 521,
 HSM_KEY_SIZE_ECC_BP_T1_224 = 224,
 HSM_KEY_SIZE_ECC_BP_T1_256 = 256,
 HSM KEY SIZE ECC BP_T1 320 = 320,
 HSM_KEY_SIZE_ECC_BP_T1_384 = 384 }
enum hsm_permitted_algo_t {
 PERMITTED ALGO SHA224 = ALGO HASH SHA224,
 PERMITTED ALGO SHA256 = ALGO HASH SHA256,
 PERMITTED_ALGO_SHA384 = ALGO_HASH_SHA384,
 PERMITTED ALGO SHA512 = ALGO HASH SHA512,
 PERMITTED ALGO SM3 = ALGO HASH SM3,
 PERMITTED ALGO HMAC SHA256 = ALGO HMAC SHA256,
 PERMITTED_ALGO_HMAC_SHA384 = ALGO_HMAC_SHA384,
 PERMITTED_ALGO_CMAC = ALGO_CMAC,
```

```
PERMITTED ALGO CTR = ALGO CIPHER CTR,
 PERMITTED ALGO CFB = ALGO CIPHER CFB,
 PERMITTED ALGO OFB = ALGO CIPHER OFB,
 PERMITTED_ALGO_ECB_NO_PADDING = ALGO_CIPHER ECB NO PAD,
 PERMITTED ALGO CBC NO PADDING = ALGO CIPHER CBC NO PAD,
 PERMITTED ALGO CCM = ALGO CCM,
 PERMITTED ALGO GCM = ALGO GCM,
 PERMITTED ALGO RSA PKCS1 V15 SHA224 = ALGO RSA PKCS1 V15 SHA224,
 PERMITTED ALGO RSA PKCS1 V15 SHA256 = ALGO RSA PKCS1 V15 SHA256,
 PERMITTED ALGO RSA PKCS1 V15 SHA384 = ALGO RSA PKCS1 V15 SHA384,
 PERMITTED_ALGO_RSA_PKCS1_V15_SHA512 = ALGO_RSA_PKCS1_V15_SHA512,
 PERMITTED_ALGO_RSA_PKCS1_PSS_MGF1_SHA224 = ALGO_RSA_PKCS1_PSS_MGF1_SHA224,
 PERMITTED_ALGO_RSA_PKCS1_PSS_MGF1_SHA256 = ALGO_RSA_PKCS1_PSS_MGF1_SHA256,
 PERMITTED ALGO RSA PKCS1 PSS MGF1 SHA384 = ALGO RSA PKCS1 PSS MGF1 SHA384,
 PERMITTED_ALGO_RSA_PKCS1_PSS_MGF1_SHA512 = ALGO_RSA_PKCS1_PSS_MGF1_SHA512,
 PERMITTED_ALGO_ECDSA_SHA224 = ALGO_ECDSA_SHA224,
 PERMITTED ALGO ECDSA SHA256 = ALGO ECDSA SHA256,
 PERMITTED ALGO ECDSA_SHA384 = ALGO_ECDSA_SHA384,
 PERMITTED ALGO ECDSA SHA512 = ALGO ECDSA SHA512,
 PERMITTED ALGO HMAC KDF SHA256 = ALGO HMAC KDF SHA256,
 PERMITTED ALGO ALL CIPHER = ALGO CIPHER ALL,
 PERMITTED_ALGO_ALL_AEAD = ALGO ALL AEAD,
 PERMITTED_ALGO_OTH_KEK_CBC = ALGO_CIPHER_KEK_CBC }
enum hsm_key_lifecycle_t {
 HSM_KEY_LIFECYCLE_OPEN = 0x1,
 HSM_KEY_LIFECYCLE_CLOSED = 0x2,
 HSM KEY LIFECYCLE CLOSED LOCKED = 0x4 }
```

Functions

- hsm err t hsm delete key (hsm hdl t key management hdl, op delete key args t *args)
- hsm err t hsm get key attr (hsm hdl t key management hdl, op get key attr args t *args)
- hsm err t hsm import key (hsm hdl t key management hdl, op import key args t *args)
- hsm_err_t hsm_generate_key_ext (hsm_hdl_t key_management_hdl, op_generate_key_ext_args_t *args)
- hsm_err_t hsm_generate_key (hsm_hdl_t key_management_hdl, op_generate_key_args_t *args)
- hsm_err_t hsm_open_key_management_service (hsm_hdl_t key_store_hdl, open_svc_key_management_args_t *args, hsm_hdl_t *key_management_hdl)
- · hsm err t hsm close key management service (hsm hdl t key management hdl)

5.2.1 Detailed Description

5.2.2 Data Structure Documentation

5.2.2.1 struct op delete key args t Structure detailing the delete key operation member arguments

Data Fields

uint32_t	key_identifier	identifier of the key to be used for the operation.
hsm_op_delete_key_flags_t	flags	bitmap specifying the operation properties.

5.2.2.2 struct op_get_key_attr_args_t Structure describing the get key attribute operation arguments

Data Fields

uint32_t	key_identifier	identifier of the key to be used for the operation.
hsm_key_type_t	key_type	indicates which type of key must be generated.
hsm_bit_key_sz_t	bit_key_sz	
hsm_key_lifetime_t	key_lifetime	
hsm_key_usage_t	key_usage	
hsm_permitted_algo_t	permitted_algo	
hsm_key_lifecycle_t	lifecycle	

5.2.2.3 struct op_import_key_args_t Structure detailing the import key operation member arguments

Data Fields

uint32_t	key_identifier	Identifier of the KEK used to encrypt the key to be imported (Ignored if KEK is not used as set as part of "flags" field).
uint8_t *	input_lsb_addr	Address in the requester space where:
		EdgeLock 2GO TLV can be found.Ignore this field if not E2GO_TLV.
uint32_t	input_size	Size in bytes of:
		EdgeLock 2GO TLV can be found.Ignore this field if not E2GO_TLV.
hsm_op_import_key_flags_t	flags	bitmap specifying the operation properties.

5.2.2.4 struct kek_enc_key_hdr_t Structure describing the encryption key header

Data Fields

uint8_t	iv[IV_LENGTH]	
uint8_t *	key	
uint32_t	tag	

5.2.2.5 struct op_generate_key_ext_args_t Structure detailing the key generate operation member arguments

Data Fields

uint32_t *	key_identifier	pointer to the identifier of the key to be used for the operation In case of create operation the new key identifier will be stored in this location
uint16_t	out_size	length in bytes of the generated key It must be 0 in case of symmetric keys
hsm_op_key_gen_flags_t	flags	bitmap specifying the operation properties
hsm_key_type_t	key_type	indicates which type of key must be generated

Data Fields

hsm_key_group_t	key_group	Key group of the generated key. It must be a value in the range 0-1023. Keys belonging to the same group can be cached in the HSM local memory through the hsm_manage_key_group API
hsm_key_info_t	key_info	bitmap specifying the properties of the key
uint8_t *	out_key	pointer to the output area where the generated public key must be written.
uint8_t	min_mac_len	min mac length in bits to be set for this key, value 0 indicates use default (see op_mac_one_go_args_t for more details). Only accepted for keys that can be used for mac operations, must not be larger than maximum mac size that can be performed with the key. When in FIPS approved mode values < 32 bits are not allowed.
uint8_t	reserved[3]	It must be 0.

$\textbf{5.2.2.6} \quad \textbf{struct op_generate_key_args_t} \quad \text{Structure describing the generate key operation member arguments}$

Data Fields

uint32_t *	key_identifier	pointer to the identifier of the key to be used for the operation. In case of create operation the new key identifier will be stored in this location.
uint16_t	out_size	length in bytes of the generated key.It must be 0 in case of symmetric keys.
hsm_op_key_gen_flags_t	flags	bitmap specifying the operation properties.
hsm_key_type_t	key_type	indicates which type of key must be generated.
hsm_key_group_t	key_group	Key group of the generated key. It must be a value in the range 0-1023. Keys belonging to the same group can be cached in the HSM local memory through the hsm_manage_key_group API.
uint8_t *	out_key	pointer to the output area where the generated public key must be written.
hsm_bit_key_sz_t	bit_key_sz	
hsm_key_lifecycle_t	key_lifecycle	defines the device lifecycle in which the key is usable. If it is set to 0, current device lifecycle is used.
hsm_key_lifetime_t	key_lifetime	
hsm_key_usage_t	key_usage	
hsm_permitted_algo_t	permitted_algo	

5.2.2.7 struct open_svc_key_management_args_t Structure detailing the key management open service member arguments

Data Fields

hsm_hdl_t	key_management_hdl	handle identifying the key management
		service flow
hsm_svc_key_management_flags_t	flags	bitmap specifying the services properties.

5.2 Key management 15

5.2.3 Macro Definition Documentation

```
5.2.3.1 HSM_OP_DEL_KEY_FLAGS_STRICT_OPERATION #define HSM_OP_DEL_KEY_FLAGS_STRICT_OP \leftarrow ERATION ((hsm_op_import_key_flags_t)(1u << 7))
```

Bitmap detailing the delete key operation properties. Bit 0-6: Reserved. Bit 7: Strict: Request completed - New key written to NVM with updated MC.

```
5.2.3.2 HSM_KEY_USAGE_EXPORT #define HSM_KEY_USAGE_EXPORT ((hsm_key_usage_t) (1u << 0))
```

Bit indicating the permission to export the key

```
5.2.3.3 HSM_KEY_USAGE_ENCRYPT #define HSM_KEY_USAGE_ENCRYPT ((hsm_key_usage_t) (1u << 8))
```

Bit indicating the permission to encrypt a message with the key

```
5.2.3.4 HSM_KEY_USAGE_DECRYPT #define HSM_KEY_USAGE_DECRYPT ((hsm_key_usage_t) (1u << 9))
```

Bit indicating the permission to decrypt a message with the key

```
5.2.3.5 HSM_KEY_USAGE_SIGN_MSG #define HSM_KEY_USAGE_SIGN_MSG ((hsm_key_usage_t) (1u << 10))
```

Bit indicating the permission to sign a message with the key

```
5.2.3.6 HSM_KEY_USAGE_VERIFY_MSG #define HSM_KEY_USAGE_VERIFY_MSG ((hsm_key_usage_t) (1u << 11))
```

Bit indicating the permission to verify a message signature with the key

```
5.2.3.7 HSM_KEY_USAGE_SIGN_HASH #define HSM_KEY_USAGE_SIGN_HASH ((hsm_key_usage_t) (1u << 12))
```

Bit indicating the permission to sign a hashed message with the key

Bit indicating the permission to verify a hashed message signature with the key

```
5.2.3.9 HSM_KEY_USAGE_DERIVE #define HSM_KEY_USAGE_DERIVE ((hsm_key_usage_t) (1u << 14))
```

Bit indicating the permission to derive other keys from this key

```
5.2.3.10 HSM_KEY_INFO_PERSISTENT #define HSM_KEY_INFO_PERSISTENT ((hsm_key_info_t) (Ou << 1))
```

Bit indicating persistent keys which are stored in the external NVM. The entire key group is written in the NVM at the next STRICT operation.

```
5.2.3.11 HSM_KEY_INFO_PERMANENT #define HSM_KEY_INFO_PERMANENT ((hsm_key_info_t) (lu << 0))
```

Bit indicating the key is permanent. When set, the key is permanent (write locked). Once created, it will not be possible to update or delete the key anymore. Transient keys will be anyway deleted after a PoR or when the corresponding key store service flow is closed. This bit can never be reset.

```
5.2.3.12 HSM_KEY_INFO_TRANSIENT #define HSM_KEY_INFO_TRANSIENT ((hsm_key_info_t) (lu << 1))
```

Bit indicating the key is transient. Transient keys are deleted when the corresponding key store service flow is closed or after a PoR. Transient keys cannot be in the same key group than persistent keys.

```
\textbf{5.2.3.13} \quad \textbf{HSM\_KEY\_INFO\_MASTER} \quad \texttt{\#define HSM\_KEY\_INFO\_MASTER} \quad \texttt{((hsm\_key\_info\_t) (lu << 2))}
```

Bit indicating the key is master key. When set, the key is considered as a master key. Only master keys can be used as input of key derivation functions (i.e butterfly key expansion).

```
\textbf{5.2.3.14} \quad \textbf{HSM\_KEY\_INFO\_KEK} \quad \texttt{\#define HSM\_KEY\_INFO\_KEK} \quad \texttt{((hsm\_key\_info\_t) (lu << 3))}
```

Bit indicating the key is key encryption key When set, the key is considered as a key encryption key. KEK keys can only be used to wrap and import other keys into the key store, all other operation are not allowed. Only keys imported in the key store through the hsm mange key API can get this attribute.

```
5.2.3.15 FLAG #define FLAG 0
```

structure defining

```
5.2.3.16 HSM_OP_KEY_GENERATION_FLAGS_STRICT_OPERATION #define HSM_OP_KEY_GENERATION \leftarrow FLAGS_STRICT_OPERATION ((hsm_op_key_gen_flags_t)(lu << 7))
```

The request is completed only when the new key has been written in the NVM. This applicable for persistent key only.

5.2.4 Typedef Documentation

5.2.4.1 hsm_op_delete_key_flags_t typedef uint8_t hsm_op_delete_key_flags_t

Bitmap describing the delete key operation properties

5.2.4.2 hsm_op_import_key_flags_t typedef uint8_t hsm_op_import_key_flags_t

Bitmap specifying the import key operation supported properties Bit 0: Defines input configuration Bit 1-6: Reserved Bit 7: Strict

5.2.4.3 hsm_key_usage_t typedef uint32_t hsm_key_usage_t

Bitmap indicating the cryptographic operations that key can execute

5.2.4.4 hsm_key_group_t typedef uint16_t hsm_key_group_t

Bit field indicating the key group

5.2.4.5 hsm_key_info_t typedef uint16_t hsm_key_info_t

Bit field indicating the key information

5.2.4.6 hsm_op_key_gen_flags_t typedef uint8_t hsm_op_key_gen_flags_t

Reserverd Bits 0 - 6.

Bitmap specifying the key generate operation supported properties.

5.2.4.7 hsm_svc_key_management_flags_t typedef uint8_t hsm_svc_key_management_flags_t

Bitmap specifying the key management service supported properties

5.2.5 Enumeration Type Documentation

5.2.5.1 hsm_storage_loc_t enum hsm_storage_loc_t

Enum Indicating the key location indicator.

5.2.5.2 hsm storage persist |v| t enum hsm_storage_persist_lvl_t

Enum Indicating the key persistent level indicator.

5.2.5.3 hsm_key_lifetime_t enum hsm_key_lifetime_t

Enum Indicating the key lifetime.

5.2.5.4 hsm_pubkey_type_t enum hsm_pubkey_type_t

Enum Indicating the public key type.

```
5.2.5.5 hsm_key_type_t enum hsm_key_type_t
```

Enum Indicating the key type.

```
5.2.5.6 hsm_bit_key_sz_t enum hsm_bit_key_sz_t
```

Enum Indicating the key security size in bits.

```
5.2.5.7 hsm_permitted_algo_t enum hsm_permitted_algo_t
```

Enum describing the permiteed algorithm

```
5.2.5.8 hsm_key_lifecycle_t enum hsm_key_lifecycle_t
```

Enum detailing Permitted key lifecycle

5.2.6 Function Documentation

This command is designed to perform the following operations:

· delete an existing key

Parameters

key_management_hdl	handle identifying the key management service flow.
args	pointer to the structure containing the function arguments.

Returns

error code

This command is designed to perform the following operations:

· get attributes of an existing key

Parameters

key_management_hdl	handle identifying the key management service flow.
args	pointer to the structure containing the function arguments.

Returns

error code

This API will be used to Import the key

Parameters

key_management_hdl	handle identifying the key management service flow.
args	pointer to the structure containing the function arguments.

Returns

error code

Generate a key or a key pair with extended settings. Basic operation is identical to hsm_generate_key, but accepts additional settings. Currently the min_mac_len is the only additional setting accepted.

Parameters

key_management_hdl	handle identifying the key management service flow.
args	pointer to the structure containing the function arguments.

Returns

Generate a key or a key pair. Only the confidential keys (symmetric and private keys) are stored in the internal key store, while the non-confidential keys (public key) are exported.

The generated key can be stored using a new or existing key identifier with the restriction that an existing key can be replaced only by a key of the same type.

Parameters

key_management_hdl	handle identifying the key management service flow.
args	pointer to the structure containing the function arguments.

Returns

error code

Open a key management service flow

User must open this service flow in order to perform operation on the key store keys (generate, update, delete)

Parameters

key_store_hdl	handle identifying the key store service flow.	
args	pointer to the structure containing the function arguments.	
key_management_hdl	pointer to where the key management service flow handle must be written.	

Returns

error_code error code.

```
5.2.6.7 hsm_close_key_management_service() hsm_err_t hsm_close_key_management_service ( hsm_hdl_t key_management_hdl )
```

Terminate a previously opened key management service flow

Parameters

key_management_hdl	handle identifying the key management service flow.

Returns

5.3 Ciphering

Data Structures

- · struct op auth enc args t
- struct open_svc_cipher_args_t
- · struct op cipher one go args t

Macros

- #define HSM AUTH ENC FLAGS DECRYPT ((hsm op auth enc flags t)(0u << 0))
- #define HSM AUTH ENC FLAGS ENCRYPT ((hsm op auth enc flags t)(1u << 0))
- #define HSM_AUTH_ENC_FLAGS_GENERATE_FULL_IV ((hsm_op_auth_enc_flags_t)(1u << 1))
- #define HSM AUTH ENC FLAGS GENERATE COUNTER IV ((hsm op auth enc flags t)(1u << 2))
- #define HSM_CIPHER_ONE_GO_FLAGS_DECRYPT ((hsm_op_cipher_one_go_flags_t)(0u << 0))
- #define HSM_CIPHER_ONE_GO_FLAGS_ENCRYPT ((hsm_op_cipher_one_go_flags_t)(1u << 0))

Typedefs

- typedef uint8_t hsm_op_auth_enc_flags_t
- typedef uint8 t hsm svc cipher flags t
- typedef uint8_t hsm_op_cipher_one_go_flags_t

Enumerations

```
    enum hsm op auth enc algo t { HSM AEAD ALGO CCM = ALGO CCM }

• enum hsm_op_cipher_one_go_algo_t {
 HSM_CIPHER_ONE_GO_ALGO_CTR = ALGO_CIPHER_CTR,
 HSM CIPHER ONE GO ALGO CFB = ALGO CIPHER CFB,
 HSM_CIPHER_ONE_GO_ALGO_OFB = ALGO_CIPHER_OFB,
```

HSM_CIPHER_ONE_GO_ALGO_ECB = ALGO_CIPHER_ECB_NO_PAD, HSM_CIPHER_ONE_GO_ALGO_CBC = ALGO_CIPHER_CBC_NO_PAD }

Functions

- hsm_err_t hsm_do_cipher (hsm_hdl_t cipher_hdl, op_cipher_one_go_args_t *cipher_one_go)
- hsm_err_t hsm_auth_enc (hsm_hdl_t cipher_hdl, op_auth_enc_args_t *args)
- hsm err t hsm open cipher service (hsm hdl t key store hdl, open svc cipher args t *args, hsm hdl t *cipher hdl)
- hsm err t hsm cipher one go (hsm hdl t cipher hdl, op cipher one go args t *args)
- hsm_err_t hsm_close_cipher_service (hsm_hdl_t cipher_hdl)

5.3.1 Detailed Description

5.3.2 Data Structure Documentation

5.3.2.1 struct op auth enc args t Structure describing the authenticated encryption operation arguments

5.3 Ciphering 23

Data Fields

uint32_t	key_identifier	< identifier of the key to be used for the operation pointer to the user supplied part of initialization vector or nonce,
uint8_t *	iv	length in bytes of the fixed part of the initialization vector for
uint16_t	iv_size	pointer to the additional authentication data
uint8_t *	aad	length in bytes of the additional authentication data
uint16_t	aad_size	algorithm to be used for the operation
hsm_op_auth_enc_algo_t	ae_algo	bitmap specifying the operation attributes
hsm_op_auth_enc_flags_t	flags	pointer to the input area plaintext for encryption
uint8_t *	input	pointer to the output area Ciphertext + Tag (16 bytes)
uint8_t *	output	length in bytes of the input
uint32_t	input_size	length in bytes of the output
uint32_t	output_size	

5.3.2.2 struct open_svc_cipher_args_t Structure describing the open cipher service members

Data Fields

hsm_hdl_t	cipher_hdl	handle identifying the cipher service flow
hsm_svc_cipher_flags_t	flags	bitmap specifying the services properties
uint8_t	reserved[3]	

5.3.2.3 struct op_cipher_one_go_args_t Structure describing the cipher one go operation arguments

Data Fields

uint32_t	key_identifier	< identifier of the key to be used for the operation pointer to the initialization vector (nonce in case of AES CCM)
uint8_t *	iv	length in bytes of the initialization vector.
uint16_t	iv_size	bitmap specifying the services properties.
hsm_svc_cipher_flags_t	svc_flags	bitmap specifying the operation attributes
hsm_op_cipher_one_go_flags_t	flags	algorithm to be used for the operation
hsm_op_cipher_one_go_algo_t	cipher_algo	pointer to the input area:
uint8_t *	input	pointer to the output area:
uint8_t *	output	length in bytes of the input.
uint32_t	input_size	length in bytes of the output
uint32_t	output_size	

5.3.3 Macro Definition Documentation

5.3.3.1 HSM_AUTH_ENC_FLAGS_DECRYPT #define HSM_AUTH_ENC_FLAGS_DECRYPT ((hsm_op_auth_enc_flags_t)(0u << 0))

Bit indicating the decryption operation

5.3.3.2 HSM_AUTH_ENC_FLAGS_ENCRYPT #define HSM_AUTH_ENC_FLAGS_ENCRYPT ((hsm_op_auth_enc_flags_t)(lu << 0))

Bit indicating the encryption operation

5.3.3.3 HSM_AUTH_ENC_FLAGS_GENERATE_FULL_IV #define HSM_AUTH_ENC_FLAGS_GENERATE_FULL_ \leftrightarrow IV ((hsm_op_auth_enc_flags_t)(1u << 1))

Bit indicating the Full IV is internally generated (only relevant for encryption)

5.3.3.4 HSM_AUTH_ENC_FLAGS_GENERATE_COUNTER_IV #define HSM_AUTH_ENC_FLAGS_GENERATE_ ← COUNTER_IV ((hsm_op_auth_enc_flags_t) (1u << 2))

Bit indicating 4 bytes supplied other bytes internally generated (only relevant for encryption)

5.3.3.5 HSM_CIPHER_ONE_GO_FLAGS_DECRYPT #define HSM_CIPHER_ONE_GO_FLAGS_DECRYPT ((hsm_op_cipher_one_go << 0))

Bit indicating the decrypt operation

5.3.3.6 HSM_CIPHER_ONE_GO_FLAGS_ENCRYPT #define HSM_CIPHER_ONE_GO_FLAGS_ENCRYPT ((hsm_op_cipher_one_go << 0))

Bit indicating the encrypt operation

5.3.4 Typedef Documentation

5.3.4.1 hsm_op_auth_enc_flags_t typedef uint8_t hsm_op_auth_enc_flags_t

Bit field indicating the authenticated encryption operations

5.3.4.2 hsm_svc_cipher_flags_t typedef uint8_t hsm_svc_cipher_flags_t

Bit field describing the open cipher service requested operation

5.3.4.3 hsm_op_cipher_one_go_flags_t typedef uint8_t hsm_op_cipher_one_go_flags_t

Bit field indicating the requested operations

5.3.5 Enumeration Type Documentation

$\textbf{5.3.5.1} \quad \textbf{hsm_op_auth_enc_algo_t} \quad \texttt{enum} \ \texttt{hsm_op_auth_enc_algo_t}$

Bit field indicating the supported algorithm

5.3 Ciphering 25

Enumerator

HSM_AEAD_ALGO_CCM	CCM (AES CCM)

5.3.5.2 hsm_op_cipher_one_go_algo_t enum hsm_op_cipher_one_go_algo_t

Enum describing the cipher one go operation algorithm

Enumerator

HSM_CIPHER_ONE_GO_ALGO_CTR	CTR (AES supported). CFB (AES supported).
HSM_CIPHER_ONE_GO_ALGO_CFB	OFB (AES supported).
HSM_CIPHER_ONE_GO_ALGO_OFB	ECB no padding (AES, SM4 supported).
HSM_CIPHER_ONE_GO_ALGO_ECB	CBC no padding (AES, SM4 supported).

5.3.6 Function Documentation

Secondary API to perform ciphering operation

This API does the following:

- 1. Open an Cipher Service Flow
- 2. Perform ciphering operation
- 3. Terminate a previously opened cipher service flow User can call this function only after having opened a cipher service flow.

Parameters

cipher_hdl	handle identifying the cipher service flow.
cipher_one_go	pointer to the structure containing the function arguments.

Returns

Perform authenticated encryption operation

User can call this function only after having opened a cipher service flow

For decryption operations, the full IV is supplied by the caller via the iv and iv_size parameters. HSM_AUTH_ENC_C_FLAGS_GENERATE_FULL_IV and HSM_AUTH_ENC_FLAGS_GENERATE_COUNTER_IV flags are ignored. For encryption operations, either HSM_AUTH_ENC_FLAGS_GENERATE_FULL_IV or HSM_AUTH_ENC_FLAGS_GENERATE_COUNTER_IV must be set when calling this function:

- When HSM_AUTH_ENC_FLAGS_GENERATE_FULL_IV is set, the full IV is internally generated, iv and iv_size must be set to 0
- When HSM_AUTH_ENC_FLAGS_GENERATE_COUNTER_IV is set, the user supplies a 4 byte fixed part of the IV. The other IV bytes are internally generated

Parameters

cipher_hdl	handle identifying the cipher service flow.
args	pointer to the structure containing the function arguments.

Returns

error code

- · Open a cipher service flow.
- · User can call this function only after having opened a key-store service flow.
- User must open this service in order to perform cipher operation.

Parameters

key_store_hdl	handle identifying the key store service flow.
args	pointer to the structure containing the function arguments.
cipher_hdl	pointer to where the cipher service flow handle must be written.

Returns

5.3 Ciphering 27

Perform ciphering operation

User can call this function only after having opened a cipher service flow

Parameters

cipher_hdl	handle identifying the cipher service flow.
args	pointer to the structure containing the function arguments.

Returns

error code

```
 \begin{array}{lll} \textbf{5.3.6.5} & \textbf{hsm\_close\_cipher\_service()} & \textbf{hsm\_err\_t} & \textbf{hsm\_close\_cipher\_service (} \\ & \textbf{hsm\_hdl\_t} & \textbf{cipher\_hdl} \end{array} )
```

Terminate a previously opened cipher service flow

Parameters

Returns

5.4 Signature generation

Data Structures

- struct open_svc_sign_gen_args_t
- · struct op_generate_sign_args_t
- struct op_prepare_sign_args_t

Macros

- #define HSM_OP_GENERATE_SIGN_FLAGS_INPUT_DIGEST ((hsm_op_generate_sign_flags_t)(0u <<<0))
- #define HSM_OP_GENERATE_SIGN_FLAGS_INPUT_MESSAGE ((hsm_op_generate_sign_flags_t)(1u << 0))
- #define HSM_OP_PREPARE_SIGN_INPUT_DIGEST ((hsm_op_prepare_signature_flags_t)(0u << 0))
 Bit indicating input digest.
- #define HSM_OP_PREPARE_SIGN_INPUT_MESSAGE ((hsm_op_prepare_signature_flags_t)(1u << 0))

 Bit indicating input message.
- #define HSM_OP_PREPARE_SIGN_COMPRESSED_POINT ((hsm_op_prepare_signature_flags_t)(1u << 1))

Bit indicating compressed point.

Typedefs

- · typedef uint8 t hsm op generate sign flags t
- typedef uint8_t hsm_op_prepare_signature_flags_t

Enumerations

```
• enum hsm signature scheme id t {
 HSM SIGNATURE SCHEME_RSA_PKCS1_V15_SHA224 = 0x06000208,
 HSM_SIGNATURE_SCHEME_RSA_PKCS1_V15_SHA256 = 0x06000209,
 HSM_SIGNATURE_SCHEME_RSA_PKCS1_V15_SHA384 = 0x0600020A,
 HSM_SIGNATURE_SCHEME_RSA_PKCS1_V15_SHA512 = 0x0600020B,
 HSM_SIGNATURE_SCHEME_RSA_PKCS1_V15_ANY_HASH = 0x0600002FF,
 HSM_SIGNATURE_SCHEME_RSA_PKCS1_PSS_MGF1_SHA224 = 0x06000308,
 HSM\_SIGNATURE\_SCHEME\_RSA\_PKCS1\_PSS\_MGF1\_SHA256 = 0x06000309,
 HSM SIGNATURE SCHEME RSA PKCS1 PSS MGF1 SHA384 = 0x0600030A,
 HSM SIGNATURE SCHEME RSA PKCS1 PSS MGF1 SHA512 = 0x0600030B,
 HSM SIGNATURE SCHEME RSA PKCS1 PSS MGF1 ANY HASH = 0x060003FF,
 HSM SIGNATURE SCHEME ECDSA ANY = 0 \times 06000600,
 HSM SIGNATURE SCHEME ECDSA SHA224 = 0x06000608.
 HSM_SIGNATURE_SCHEME_ECDSA_SHA256 = 0x06000609,
 HSM SIGNATURE SCHEME ECDSA SHA384 = 0x0600060A,
 HSM SIGNATURE SCHEME ECDSA SHA512 = 0x0600060B }
```

Functions

- hsm err t hsm do sign (hsm hdl t key store hdl, op generate sign args t *args)
- hsm_err_t hsm_open_signature_generation_service (hsm_hdl_t key_store_hdl, open_svc_sign_gen_args_t *args, hsm hdl t *signature gen hdl)
- hsm_err_t hsm_close_signature_generation_service (hsm_hdl_t signature_gen_hdl)
- hsm_err_t hsm_generate_signature (hsm_hdl_t signature_gen_hdl, op_generate_sign_args_t *args)
- hsm_err_t hsm_prepare_signature (hsm_hdl_t signature_gen_hdl, op_prepare_sign_args_t *args)

5.4.1 Detailed Description

5.4.2 Data Structure Documentation

5.4.2.1 struct open_svc_sign_gen_args_t Structure to represent the generate sign open service arguments

Data Fields

hsm_hdl_t signature_gen_hdl

5.4.2.2 struct op_generate_sign_args_t Structure to represent the generate sign operation arguments

Data Fields

uint32_t	key_identifier	< identifier of the key to be used for the operation pointer to the input (message or message digest) to be signed
uint8_t * message pointer to the output area where the be stored.		pointer to the output area where the signature must be stored.
uint8_t *	signature	length in bytes of the output. After signature generation operation,
uint16_t	signature_size	length in bytes of the input
uint32_t	message_size	identifier of the digital signature scheme to be used
hsm_signature_scheme_id_t	scheme_id	Salt length in bytes.
uint16_t	salt_len	expected signature buffer size for output, returned by FW in case
uint16_t	exp_signature_size	bitmap specifying the operation attributes
hsm_op_generate_sign_flags_t	flags	

5.4.2.3 struct op_prepare_sign_args_t Structure detailing the prepare signature operation member arguments

Data Fields

hsm_signature_scheme_id_t	scheme_id	heme_id identifier of the digital signature scheme to be used for the	
		operation.	
hsm_op_prepare_signature_flags_t flags		bitmap specifying the operation attributes	

5.4.3 Macro Definition Documentation

5.4.3.1 HSM_OP_GENERATE_SIGN_FLAGS_INPUT_DIGEST #define HSM_OP_GENERATE_SIGN_FLAGS_I \leftarrow NPUT_DIGEST ((hsm_op_generate_sign_flags_t) (0u << 0))

Bit field indicating the input is the message digest

```
5.4.3.2 HSM_OP_GENERATE_SIGN_FLAGS_INPUT_MESSAGE #define HSM_OP_GENERATE_SIGN_FLAGS ← _INPUT_MESSAGE ((hsm_op_generate_sign_flags_t)(1u << 0))
```

Bit field indicating the input is the actual message

5.4.4 Typedef Documentation

```
\textbf{5.4.4.1} \quad \textbf{hsm\_op\_generate\_sign\_flags\_t} \quad \texttt{typedef uint8\_t hsm\_op\_generate\_sign\_flags\_t}
```

Bit field indicating the requested operation

```
5.4.4.2 hsm_op_prepare_signature_flags_t typedef uint8_t hsm_op_prepare_signature_flags_t
```

Bitmap specifying the prepare signature operation supported attributes

5.4.5 Enumeration Type Documentation

```
5.4.5.1 hsm_signature_scheme_id_t enum hsm_signature_scheme_id_t
```

Bit field indicating the PSA compliant requested operations: Bit 2 to 7: Reserved.

5.4.6 Function Documentation

Secondary API to generate signature on the given message. This API does the following:

- 1. Open a service flow for signature generation.
- 2. Based on the flag to identify the type of message: Digest or actual message, generate the signature using the key corresponding to the key id.
- Post performing the operation, terminate the previously opened signature-generation service flow.
 User can call this function only after having opened a key-store.

Parameters

key_store_hdl	handle identifying the current key-store.	
args	pointer to the structure containing the function arguments.	

Returns

error code

Open a signature generation service flow

User can call this function only after having opened a key store service flow.

User must open this service in order to perform signature generation operations.

Parameters

key_store_hdl	handle identifying the key store service flow.	
args	pointer to the structure containing the function arguments.	
signature_gen_hdl	pointer to where the signature generation service flow handle must be written.	

Returns

error code

```
5.4.6.3 hsm_close_signature_generation_service() hsm_err_t hsm_close_signature_generation_\leftarrow service ( hsm_hdl_t signature_gen_hdl )
```

Terminate a previously opened signature generation service flow

Parameters

Returns

Generate a digital signature according to the signature scheme User can call this function only after having opened a signature generation service flow.

The signature S=(r,s) is stored in the format r||s||Ry where:

• Ry is an additional byte containing the lsb of y. Ry has to be considered valid only if the HSM_OP_GENE
RATE SIGN FLAGS COMPRESSED POINT is set.

In case of HSM_SIGNATURE_SCHEME_DSA_SM2_FP_256_SM3, message of op_generate_sign_args_t should be (as specified in GB/T 32918):

- equal to Z||M in case of HSM_OP_GENERATE_SIGN_FLAGS_INPUT_MESSAGE
- equal to SM3(Z||M) in case of HSM_OP_GENERATE_SIGN_FLAGS_INPUT_DIGEST

Parameters

signature_gen_hdl	handle identifying the signature generation service flow.
args	pointer to the structure containing the function arguments.

Returns

error code

Prepare the creation of a signature by pre-calculating the operations having not dependencies on the input message.

The pre-calculated value will be stored internally and used once call hsm_generate_signature. Up to 20 pre-calculated values can be stored, additional preparation operations will have no effects.

User can call this function only after having opened a signature generation service flow.

The signature S=(r,s) is stored in the format r||s||Ry where:

• Ry is an additional byte containing the lsb of y, Ry has to be considered valid only if the HSM_OP_PREPA← RE_SIGN_COMPRESSED_POINT is set.

Parameters

signature_gen_hdl	handle identifying the signature generation service flow
args	pointer to the structure containing the function arguments.

	- 4.		
к	eti	ırı	ns

5.5 Signature verification

Data Structures

- struct open_svc_sign_ver_args_t
- struct op_verify_sign_args_t

Macros

- #define HSM_OP_VERIFY_SIGN_FLAGS_INPUT_DIGEST ((hsm_op_verify_sign_flags_t)(0u << 0))
- #define HSM_OP_VERIFY_SIGN_FLAGS_INPUT_MESSAGE ((hsm_op_verify_sign_flags_t)(1u << 0))
- #define HSM_OP_VERIFY_SIGN_FLAGS_COMPRESSED_POINT ((hsm_op_verify_sign_flags_t)(1u <<< 1))
- #define HSM_OP_VERIFY_SIGN_FLAGS_KEY_INTERNAL ((hsm_op_verify_sign_flags_t)(1u << 2))
- #define HSM_VERIFICATION_STATUS_SUCCESS ((hsm_verification_status_t)(0x5A3CC3A5u))
- #define HSM_VERIFICATION_STATUS_FAILURE ((hsm_verification_status_t)(0x2B4DD4B2u))

Typedefs

- typedef uint32_t hsm_verification_status_t
- typedef uint8 t hsm op verify sign flags t

Functions

- hsm_err_t hsm_verify_sign (hsm_hdl_t session_hdl, op_verify_sign_args_t *args, hsm_verification_status_t *verification_status)
- hsm_err_t hsm_open_signature_verification_service (hsm_hdl_t session_hdl, open_svc_sign_ver_args_t *args, hsm_hdl_t *signature_ver_hdl)
- hsm_err_t hsm_close_signature_verification_service (hsm_hdl_t signature_ver_hdl)
- hsm_err_t hsm_verify_signature (hsm_hdl_t signature_ver_hdl, op_verify_sign_args_t *args, hsm_verification_status_t *status)

5.5.1 Detailed Description

5.5.2 Data Structure Documentation

5.5.2.1 struct open_svc_sign_ver_args_t Structure to represent verify sign open service arguments

Data Fields

hsm_hdl_t sig_ver_hdl

5.5.2.2 struct op_verify_sign_args_t Structure to represent verify signature operation arguments

Data Fields

uint8_t *	key	< pointer to the public key to be used for the verification.
		pointer to the input (message or message digest)

Data Fields

uint8_t *	message	pointer to the input signature. The signature S=(r,s) is expected
uint8_t *	signature	length in bytes of the input key
uint16_t	key_size	length in bytes of the output - it must contain one additional
uint16_t	signature_size	length in bytes of the input message
uint32_t	message_size	
hsm_verification_status_t	verification_status	identifier of the digital signature scheme to be used
hsm_signature_scheme_id_t	scheme_id	salt length in bytes
uint16_t	salt_len	
hsm_bit_key_sz_t	key_sz	
hsm_pubkey_type_t	pkey_type	bitmap specifying the operation attributes
hsm_op_verify_sign_flags_t	flags	

5.5.3 Macro Definition Documentation

```
5.5.3.1 HSM_OP_VERIFY_SIGN_FLAGS_INPUT_DIGEST #define HSM_OP_VERIFY_SIGN_FLAGS_INPUT_D \leftarrow IGEST ((hsm_op_verify_sign_flags_t)(0u << 0))
```

Verify signature bit indicating input is message digest

```
5.5.3.2 HSM_OP_VERIFY_SIGN_FLAGS_INPUT_MESSAGE #define HSM_OP_VERIFY_SIGN_FLAGS_INPUT \leftarrow _MESSAGE ((hsm_op_verify_sign_flags_t) (lu << 0))
```

Verify signature bit indicating input is actual message

Verify signature bit indicating input based on signature format

Verify signature bit indicating input is key argument

5.5.3.5 HSM_VERIFICATION_STATUS_SUCCESS #define HSM_VERIFICATION_STATUS_SUCCESS ((hsm_verification_status_A3CC3A5u))

Verify signature response success status

5.5.3.6 HSM_VERIFICATION_STATUS_FAILURE #define HSM_VERIFICATION_STATUS_FAILURE ((hsm_verification_status_B4DD4B2u))

Verify signature response failure status

5.5.4 Typedef Documentation

```
5.5.4.1 hsm_verification_status_t typedef uint32_t hsm_verification_status_t
```

Bit indicating the response verification status

```
5.5.4.2 hsm_op_verify_sign_flags_t typedef uint8_t hsm_op_verify_sign_flags_t
```

Bit indicating the requested operations

5.5.5 Function Documentation

Secondary API to verify a message signature.

This API does the following:

- 1. Open a flow for verification of the signature.
- 2. Based on the flag to identify the type of message: Digest or actual message, verification of the signature is done using the public key.
- Post performing the operation, terminate the previously opened signature-verification service flow.
 User can call this function only after having opened a session.

Parameters

session_hdl	handle identifying the current key-store.
args	pointer to the structure containing the function arguments.
verification_status	pointer for storing the verification status.

Returns

error code

User must open this service in order to perform signature verification operations. User can call this function only after having opened a session.

Parameters

session_hdl	handle identifying the current session.
args	pointer to the structure containing the function arguments.
signature_ver_hdl	pointer to where the signature verification service flow handle must be written.

Returns

error code

Terminate a previously opened signature verification service flow

Parameters

Returns

error code

Verify a digital signature according to the signature scheme User can call this function only after having opened a signature verification service flow.

The signature S=(r,s) is expected to be in format r||s||Ry where:

• Ry is an additional byte containing the lsb of y. Ry will be considered as valid only, if the HSM_OP_VERIF

Y_SIGN_FLAGS_COMPRESSED_POINT is set.

Only not-compressed keys (x,y) can be used by this command. Compressed keys can be decompressed by using the dedicated API.

In case of HSM_SIGNATURE_SCHEME_DSA_SM2_FP_256_SM3, message of op_verify_sign_args_t should be (as specified in GB/T 32918):

- equal to Z||M in case of HSM_OP_VERIFY_SIGN_FLAGS_INPUT_MESSAGE
- equal to SM3(Z||M) in case of HSM_OP_VERIFY_SIGN_FLAGS_INPUT_DIGEST

Parameters

signature_ver_hdl	handle identifying the signature verification service flow.	
args	pointer to the structure containing the function arguments.	
status	pointer to where the verification status must be stored if the verification succeed the value	
	HSM_VERIFICATION_STATUS_SUCCESS is returned.	

Returns

5.6 Random number generation

Data Structures

• struct op_get_random_args_t

Functions

- hsm_err_t hsm_do_rng (hsm_hdl_t session_hdl, op_get_random_args_t *args)
- hsm_err_t hsm_get_random (hsm_hdl_t rng_hdl, op_get_random_args_t *args)

5.6.1 Detailed Description

5.6.2 Data Structure Documentation

5.6.2.1 struct op_get_random_args_t Structure detailing the get random number operation member arguments

Data Fields

uint8	_t * output	pointer to the output area where the random number must be written
uint3	2_t random_s	length in bytes of the random number to be provided.

5.6.3 Function Documentation

Secondary API to fetch the Random Number

This API does the following: Get a freshly generated random number

Parameters

session_hdl	handle identifying the current session.
args	pointer to the structure containing the function arguments.

Returns

Get a freshly generated random number

User can call this function only after having opened a rng service flow

Parameters

rng_hdl	handle identifying the rng service flow.
args	pointer to the structure containing the function arguments.

Returns

5.7 Hashing 41

5.7 Hashing

Data Structures

• struct op_hash_one_go_args_t

Macros

• #define HSM_HASH_FLAG_ALLOWED

Enumerations

```
enum hsm_hash_algo_t {
    HSM_HASH_ALGO_SHA_224 = 0x02000008,
    HSM_HASH_ALGO_SHA_256 = 0x02000009,
    HSM_HASH_ALGO_SHA_384 = 0x02000000A,
    HSM_HASH_ALGO_SHA_512 = 0x02000000B }
enum hsm_hash_svc_flags_t {
    HSM_HASH_FLAG_ONE_SHOT = 0x1,
    HSM_HASH_FLAG_INIT = 0x2,
    HSM_HASH_FLAG_UPDATE = 0x4,
    HSM_HASH_FLAG_FINAL = 0x8,
    HSM_HASH_FLAG_GET_CONTEXT = 0x80 }
```

Functions

- hsm_err_t hsm_do_hash (hsm_hdl_t session_hdl, op_hash_one_go_args_t *args)
- hsm_err_t hsm_hash_one_go (hsm_hdl_t hash_hdl, op_hash_one_go_args_t *args)

5.7.1 Detailed Description

5.7.2 Data Structure Documentation

5.7.2.1 struct op_hash_one_go_args_t Structure describing the hash one go operation arguments

Data Fields

uint8_t *	msb	< pointer to the MSB of address in the requester space where buffers pointer to the context.
uint8_t *	ctx	pointer to the input data to be hashed
uint8_t *	input	pointer to the output area where the resulting digest must be written
uint8_t *	output	length in bytes of the input
uint32_t	input_size	length in bytes of the output
uint32_t	output_size	hash algorithm to be used for the operation
hsm_hash_algo_t	algo	flags identifying the operation init() update(), final() or one shot
hsm_hash_svc_flags_t	svc_flags	size of context buffer in bytes, ignored in case of one shot
uint16_t	ctx_size	expected output digest buffer size, returned by FW in case the
uint32_t	exp_output_size	expected context size to allocate in bytes, if flag Get context
uint16_t	context_size	

5.7.3 Macro Definition Documentation

5.7.3.1 HSM_HASH_FLAG_ALLOWED #define HSM_HASH_FLAG_ALLOWED

Value:

Bitmap indicating the allowed hash service operations

5.7.4 Enumeration Type Documentation

```
5.7.4.1 hsm_hash_algo_t enum hsm_hash_algo_t
```

Bitmap indicating the supported hash algorithm

```
5.7.4.2 hsm_hash_svc_flags_t enum hsm_hash_svc_flags_t
```

Bit field indicating the hash service operations

5.7.5 Function Documentation

Secondary API to digest a message.

This API does the following: Perform hash

Parameters

session_hdl	handle identifying the current session.
args	pointer to the structure containing the function arguments.

Returns

5.7 Hashing 43

Perform the hash operation on a given input User can call this function only after having opened a hash service flow

Parameters

hash_hdl	handle identifying the hash service flow.
args	pointer to the structure containing the function arguments.

Returns

5.8 Data storage

Data Structures

- struct open_svc_data_storage_args_t
- struct op_data_storage_args_t

Macros

- #define HSM_OP_DATA_STORAGE_FLAGS_STORE ((hsm_op_data_storage_flags_t)(1u << 0))
- #define HSM_OP_DATA_STORAGE_FLAGS_RETRIEVE ((hsm_op_data_storage_flags_t)(0u << 0))
 Retrieve data.

Typedefs

- typedef uint8_t hsm_svc_data_storage_flags_t
- typedef uint8_t hsm_op_data_storage_flags_t

Functions

- hsm_err_t hsm_data_ops (hsm_hdl_t key_store_hdl, op_data_storage_args_t *args)
- hsm_err_t hsm_open_data_storage_service (hsm_hdl_t key_store_hdl, open_svc_data_storage_args_t *args, hsm_hdl_t *data_storage_hdl)
- hsm_err_t hsm_data_storage (hsm_hdl_t data_storage_hdl, op_data_storage_args_t *args)
- hsm_err_t hsm_close_data_storage_service (hsm_hdl_t data_storage_hdl)

5.8.1 Detailed Description

5.8.2 Data Structure Documentation

5.8.2.1 struct open_svc_data_storage_args_t Structure specifying the data storage open service member arguments

Data Fields

hsm_hdl_t	data_storage_handle	
hsm_svc_data_storage_flags_t	flags	bitmap specifying the services properties.
uint8_t	reserved[3]	

5.8.2.2 struct op_data_storage_args_t Structure detailing the data storage operation member arguments

Data Fields

uint8_t *	data	< pointer to the data. In case of store request, length in bytes of the data
uint32_t	data_size	id of the data

5.8 Data storage 45

Data Fields

uint16_t	data_id	bitmap specifying the services properties.
hsm_svc_data_storage_flags_t	flags	flags bitmap specifying the operation attributes.
hsm_op_data_storage_flags_t	svc_flags	

5.8.3 Typedef Documentation

```
5.8.3.1 hsm_svc_data_storage_flags_t typedef uint8_t hsm_svc_data_storage_flags_t
```

Bitmap specifying the data storage open service supported properties

```
5.8.3.2 hsm_op_data_storage_flags_t typedef uint8_t hsm_op_data_storage_flags_t
```

Bitmap specifying the data storage operation supported attributes

5.8.4 Function Documentation

Secondary API to store and restoare data from the linux filesystem managed by EdgeLock Enclave Firmware.

This API does the following:

- 1. Open an data storage service Flow
- 2. Based on the flag for operation attribute: Store or Re-store,
 - · Store the data
 - Re-store the data, from the non-volatile storage.
- 3. Post performing the operation, terminate the previously opened data-storage service flow.

User can call this function only after having opened a key-store.

Parameters

key_store_hdl	handle identifying the current key-store.
args	pointer to the structure containing the function arguments.

Returns

error code

Open a data storage service flow

User must open this service flow in order to store/retrieve generic data in/from the HSM.

Parameters

key_store_hdl	handle identifying the key store service flow.
args	pointer to the structure containing the function arguments.
data_storage_hdl	pointer to where the data storage service flow handle must be written.

Returns

error_code error code.

Store or retrieve generic data identified by a data_id.

Parameters

data_storage_hdl	handle identifying the data storage service flow.
args	pointer to the structure containing the function arguments.

Returns

error code

```
5.8.4.4 hsm_close_data_storage_service() hsm_err_t hsm_close_data_storage_service ( hsm_hdl_t data_storage_hdl )
```

Terminate a previously opened data storage service flow

5.8 Data storage 47

Parameters

data storage hdl	handle identifying the data storage service flow.

Returns

5.9 Authenticated Encryption

Functions

hsm_err_t hsm_do_auth_enc (hsm_hdl_t key_store_hdl, op_auth_enc_args_t *auth_enc_args)

5.9.1 Detailed Description

5.9.2 Function Documentation

Secondary API to perform Authenticated Encryption This API does the following:

- 1. Opens Cipher Service Flow
- 2. Perform Authenticated Encryption operation
- 3. Terminates the previously opened Cipher service flow User can call this function only after having opened a key store service flow.

Parameters

key_store_hdl	handle identifying the key store service flow.
auth_enc_args	pointer to the structure containing the function arguments.

Returns

5.10 Mac 49

5.10 Mac

Data Structures

- struct open_svc_mac_args_t
- struct op_mac_one_go_args_t

Macros

- #define HSM_OP_MAC_ONE_GO_FLAGS_MAC_VERIFICATION ((hsm_op_mac_one_go_flags_t)(0u <<< 0))
- #define HSM_OP_MAC_ONE_GO_FLAGS_MAC_GENERATION ((hsm_op_mac_one_go_flags_t)(1u <<< 0))
- #define HSM_MAC_VERIFICATION_STATUS_SUCCESS ((hsm_mac_verification_status_t)(0x6C1AA1 ← C6u))

Typedefs

- typedef uint8_t hsm_op_mac_one_go_flags_t
- typedef uint32_t hsm_mac_verification_status_t
- typedef hsm_permitted_algo_t hsm_op_mac_one_go_algo_t
 - < Following three permitted algos are allowed:

Functions

- hsm_err_t hsm_do_mac (hsm_hdl_t key_store_hdl, op_mac_one_go_args_t *mac_one_go)
- hsm_err_t hsm_open_mac_service (hsm_hdl_t key_store_hdl, open_svc_mac_args_t *args, hsm_hdl_t *mac_hdl)
- hsm_err_t hsm_mac_one_go (hsm_hdl_t mac_hdl, op_mac_one_go_args_t *args, hsm_mac_verification_status_t *status)
- hsm_err_t hsm_close_mac_service (hsm_hdl_t mac_hdl)

5.10.1 Detailed Description

5.10.2 Data Structure Documentation

5.10.2.1 struct open_svc_mac_args_t Structure describing the mac open service member agruments

Data Fields

hsm_hdl_t mac_serv_hdl

5.10.2.2 struct op_mac_one_go_args_t Structure describing the mac one go operation member agruments

Data Fields

uint32_t key_identifier	< identifier of the key to be used for the operation algorithm to be used for the operation
-------------------------	---

Data Fields

hsm_op_mac_one_go_algo_t	algorithm	bitmap specifying the operation attributes
hsm_op_mac_one_go_flags_t	flags	pointer to the payload area
uint8_t *	payload	pointer to the tag area
uint8_t *	mac	length in bytes of the payload
uint32_t	payload_size	length of the tag.
uint16_t	mac_size	expected mac size for output, returned by FW in case
		the mac size
uint16_t	expected_mac_size	
hsm_mac_verification_status_t	verification_status	

5.10.3 Macro Definition Documentation

5.10.3.1 HSM_OP_MAC_ONE_GO_FLAGS_MAC_VERIFICATION #define HSM_OP_MAC_ONE_GO_FLAGS_M → AC_VERIFICATION ((hsm_op_mac_one_go_flags_t) (0u << 0))

Bit indicating mac one go verify operation

 $5.10.3.2 \;\; HSM_OP_MAC_ONE_GO_FLAGS_MAC_GENERATION \;\; \#define \;\; HSM_OP_MAC_ONE_GO_FLAGS_MACC_GENERATION \;\; ((hsm_op_mac_one_go_flags_t) \;\; (lu << 0))$

Bit indicating mac one go generate operation

5.10.3.3 HSM_MAC_VERIFICATION_STATUS_SUCCESS #define HSM_MAC_VERIFICATION_STATUS_SUCC← ESS ((hsm_mac_verification_status_t)(0x6C1AA1C6u))

Bit indicating mac verification success status

5.10.4 Typedef Documentation

 $\textbf{5.10.4.1} \quad \textbf{hsm_op_mac_one_go_flags_t} \quad \texttt{typedef uint8_t hsm_op_mac_one_go_flags_t}$

Bitmap describing the mac one go operation

5.10.4.2 hsm_mac_verification_status_t typedef uint32_t hsm_mac_verification_status_t

Bitmap describing the mac verification status

5.10 Mac 51

```
\textbf{5.10.4.3} \quad \textbf{hsm\_op\_mac\_one\_go\_algo\_t} \quad \texttt{typedef hsm\_permitted\_algo\_t hsm\_op\_mac\_one\_go\_algo\_t}
```

< Following three permitted algos are allowed:

Bitmap describing the mac one go operation permitted algorithm

5.10.5 Function Documentation

Secondary API to perform mac operation This API does the following:

- 1. Open an MAC Service Flow
- 2. Perform mac operation
- Terminate a previously opened mac service flow
 User can call this function only after having opened a key store service flow.

Parameters

key_store_hdl	handle identifying the key store service flow.
mac_one_go	pointer to the structure containing the function arguments.

Returns

error code

Open a mac service flow

User can call this function only after having opened a key store service flow. User must open this service in order to perform mac operation

Parameters

key_store_hdl	handle identifying the key store service flow.
args	pointer to the structure containing the function arguments.
mac hdl	pointer to where the mac service flow handle must be written.

Returns

error code

Perform mac operation

User can call this function only after having opened a mac service flow For CMAC algorithm, a key of type HSM_KEY_TYPE_AES_XXX must be used For HMAC algorithm, a key of type HSM_KEY_TYPE_HMAC_XXX must be used For mac verification operations, the verified mac length can be specified in:

- Bits by setting the HSM_OP_MAC_ONE_GO_FLAGS_MAC_LENGTH_IN_BITS flag,
- if this flag is clear then the mac_length is specified in bytes.

For mac generation operations:

- · mac length must be set in bytes, and
- HSM_OP_MAC_ONE_GO_FLAGS_MAC_LENGTH_IN_BITS flag must be 0

Parameters

mac_hdl	handle identifying the mac service flow.	
args	pointer to the structure containing the function arguments.	
status	pointer for storing the verification status.	

Returns

error code

```
5.10.5.4 hsm_close_mac_service() hsm_err_t hsm_close_mac_service ( hsm_hdl_t mac_hdl )
```

Terminate a previously opened mac service flow

Parameters

mac_hdl	pointer to handle identifying the mac service flow to be closed.
---------	--

5.10 Mac 53

Returns

5.11 Dump Firmware Log

Data Structures

• struct op_debug_dump_args_t

Functions

hsm_err_t dump_firmware_log (hsm_hdl_t session_hdl)

5.11.1 Detailed Description

5.11.2 Data Structure Documentation

5.11.2.1 struct op_debug_dump_args_t Structure detailing the debug dump operation member arguments

Data Fields

bool is_dump_pending			
	uint32_t	dump_buf_len	
	uint32_t	dump_buf[MAC_BUFF_LEN]	

5.11.3 Function Documentation

This command is designed to dump the firmware logs

Parameters

ı			
	session_hdl	handle identifying the session handle.	

Returns

5.12 Dev attest 55

5.12 Dev attest

Data Structures

• struct op_dev_attest_args_t

Functions

hsm_err_t hsm_dev_attest (hsm_hdl_t sess_hdl, op_dev_attest_args_t *args)

5.12.1 Detailed Description

5.12.2 Data Structure Documentation

5.12.2.1 struct op_dev_attest_args_t Structure describing the device attestation operation member arguments

Data Fields

SZ

5.12.3 Function Documentation

Perform device attestation operation

User can call this function only after having opened the session.

Parameters

sess_hdl	handle identifying the active session.	
args pointer to the structure containing the function argumen		

Returns

5.13 Dev Info 57

5.13 Dev Info

Data Structures

• struct op_dev_getinfo_args_t

Functions

hsm_err_t hsm_dev_getinfo (hsm_hdl_t sess_hdl, op_dev_getinfo_args_t *args)

5.13.1 Detailed Description

5.13.2 Data Structure Documentation

5.13.2.1 struct op_dev_getinfo_args_t Structure detailing the device getinfo operation member arguments

Data Fields

		_
uint16_t	soc_id	
uint16_t	soc_rev	
uint16_t	lmda_val	
uint8_t	ssm_state	
uint8_t	uid_sz	
uint8_t *	uid	
uint16_t	rom_patch_sha_sz	
uint16_t	sha_fw_sz	
uint8_t *	sha_rom_patch	
uint8_t *	sha_fw	
uint16_t	oem_srkh_sz	
uint8_t *	oem_srkh	
uint8_t	imem_state	
uint8_t	csal_state	
uint8_t	trng_state	

5.13.3 Function Documentation

Perform device attestation operation

User can call this function only after having opened the session.

Parameters

sess_hdl	handle identifying the active session.
aras	pointer to the structure containing the function arguments.
Concreted by D	

Returns

5.14 Generic Crypto: Asymmetric Crypto

Data Structures

struct op_gc_acrypto_args_t

Macros

- #define HSM_OP_GC_ACRYPTO_FLAGS_INPUT_MESSAGE ((hsm_op_gc_acrypto_flags_t)(1u << 0))

Typedefs

- typedef uint8_t hsm_op_gc_acrypto_flags_t
- typedef uint32_t hsm_gc_acrypto_verification_status_t

Enumerations

```
    enum hsm op gc acrypto algo t {

 HSM_GC_ACRYPTO_ALGO_ECDSA_SHA224 = ALGO_ECDSA_SHA224,
 HSM GC ACRYPTO ALGO ECDSA SHA256 = ALGO ECDSA SHA256,
 HSM GC ACRYPTO ALGO ECDSA SHA384 = ALGO ECDSA SHA384,
 HSM GC ACRYPTO ALGO ECDSA SHA512 = ALGO ECDSA SHA512,
 HSM_GC_ACRYPTO_ALGO_RSA_PKCS1_V15_SHA224 = ALGO_RSA_PKCS1_V15_SHA224,
 HSM_GC_ACRYPTO_ALGO_RSA_PKCS1_V15_SHA256 = ALGO_RSA_PKCS1_V15_SHA256,
 HSM_GC_ACRYPTO_ALGO_RSA_PKCS1_V15_SHA384 = ALGO_RSA_PKCS1_V15_SHA384,
 HSM GC ACRYPTO ALGO RSA PKCS1 V15 SHA512 = ALGO RSA PKCS1 V15 SHA512,
 HSM_GC_ACRYPTO_ALGO_RSA_PKCS1_PSS_MGF1_SHA224 = ALGO_RSA_PKCS1_PSS MGF1 ↔
 SHA224,
 HSM GC ACRYPTO ALGO RSA PKCS1 PSS MGF1 SHA256 = ALGO RSA PKCS1 PSS MGF1 ↔
 SHA256.
 HSM_GC_ACRYPTO_ALGO_RSA_PKCS1_PSS_MGF1_SHA384 = ALGO_RSA_PKCS1_PSS_MGF1_←
 SHA384,
 HSM GC ACRYPTO ALGO RSA PKCS1 PSS MGF1 SHA512 = ALGO RSA PKCS1 PSS MGF1 ↔
 SHA512.
 HSM_GC_ACRYPTO_ALGO_RSA_PKCS1_V15_CRYPT = ALGO_RSA_PKCS1_V15_CRYPT,
 HSM GC ACRYPTO ALGO RSA PKCS1 OAEP SHA1 = ALGO RSA PKCS1 OAEP SHA1,
 HSM GC ACRYPTO ALGO RSA PKCS1 OAEP SHA224 = ALGO RSA PKCS1 OAEP SHA224,
 HSM GC ACRYPTO ALGO RSA PKCS1 OAEP SHA256 = ALGO RSA PKCS1 OAEP SHA256,
 HSM GC ACRYPTO ALGO RSA PKCS1 OAEP SHA384 = ALGO RSA PKCS1 OAEP SHA384,
 HSM GC ACRYPTO ALGO RSA PKCS1 OAEP SHA512 = ALGO RSA PKCS1 OAEP SHA512 }
enum hsm_gc_acrypto_op_mode_t {
 HSM GC ACRYPTO OP MODE ENCRYPT = 0 \times 0.1,
 HSM GC ACRYPTO OP MODE DECRYPT = 0x02,
 HSM GC ACRYPTO OP MODE SIGN GEN = 0x03,
 HSM_GC_ACRYPTO_OP_MODE_SIGN_VER = 0x04 }
```

Functions

hsm_err_t hsm_gc_acrypto (hsm_hdl_t session_hdl, op_gc_acrypto_args_t *args)

- 5.14.1 Detailed Description
- 5.14.2 Data Structure Documentation
- **5.14.2.1 struct op_gc_acrypto_args_t** Structure describing the generic asymmetric crypto member arguments

Data Fields

hsm_op_gc_acrypto_algo_t	algorithm	< algorithm to use for the operation indicates the operation mode
hsm_gc_acrypto_op_mode_t	op_mode	indicates operation flags
hsm_op_gc_acrypto_flags_t	flags	key size in bits
hsm_bit_key_sz_t	bit_key_sz	pointer to the data buffer 1:
uint8_t *	data_buff1	pointer to the data buffer 2:
uint8_t *	data_buff2	size in bytes of data buffer 1
uint32_t	data_buff1_size	size in bytes of data buffer 2
uint32_t	data_buff2_size	pointer to the key modulus buffer
uint8_t *	key_buff1	pointer the key exponent, either private or public
uint8_t *	key_buff2	size in bytes of the key buffer 1
uint16_t	key_buff1_size	size in bytes of the key buffer 2
uint16_t	key_buff2_size	RSA label address.
uint8_t *	rsa_label	RSA label size in bytes.
uint16_t	rsa_label_size	RSA salt length in bytes.
uint16_t	rsa_salt_len	expected plaintext length in bytes, returned by FW in case of
uint32_t	exp_plaintext_len	signature verification status
hsm_gc_acrypto_verification_status_t	verification_status	

5.14.3 Macro Definition Documentation

5.14.3.1 HSM_OP_GC_ACRYPTO_FLAGS_INPUT_MESSAGE #define HSM_OP_GC_ACRYPTO_FLAGS_INPU \leftarrow T_MESSAGE ((hsm_op_gc_acrypto_flags_t)(1u << 0))

Bit indicating the generic asymmetric crypto input message operation

5.14.3.2 HSM_GC_ACRYPTO_VERIFICATION_SUCCESS #define HSM_GC_ACRYPTO_VERIFICATION_SUCC← ESS ((hsm_gc_acrypto_verification_status_t) (0x5A3CC3A5u))

Bit indicating the generic asymmetric crypto success verification status

5.14.3.3 HSM_GC_ACRYPTO_VERIFICATION_FAILURE #define HSM_GC_ACRYPTO_VERIFICATION_FAILU← RE ((hsm_gc_acrypto_verification_status_t) (0x2B4DD4B2u))

Bit indicating the generic asymmetric crypto failure verification status

5.14.4 Typedef Documentation

```
5.14.4.1 hsm_op_gc_acrypto_flags_t typedef uint8_t hsm_op_gc_acrypto_flags_t
```

Bitmap describing the generic asymmetric crypto supported operation

5.14.4.2 hsm_gc_acrypto_verification_status_t typedef uint32_t hsm_gc_acrypto_verification_status_t

Bitmap describing the generic asymmetric crypto verification status

5.14.5 Enumeration Type Documentation

```
{\bf 5.14.5.1} \quad hsm\_op\_gc\_acrypto\_algo\_t \quad \texttt{enum} \quad hsm\_op\_gc\_acrypto\_algo\_t
```

Enum detailing the generic asymmetric crypto supported algorithms

```
5.14.5.2 hsm_gc_acrypto_op_mode_t enum hsm_gc_acrypto_op_mode_t
```

Enum describing the generic asymmetric crypto supported operating modes

5.14.6 Function Documentation

This command is designed to perform the following operations: -Asymmetric crypto -encryption/decryption - signature generation/verification

Parameters

session_hdl	n_hdl handle identifying the current session.	
args	pointer to the structure containing the function arguments.	

Returns

5.15 Generic Crypto Asymmetric Key Generate

Data Structures

• struct op_gc_akey_gen_args_t

Functions

hsm_err_t hsm_gc_akey_gen (hsm_hdl_t session_hdl, op_gc_akey_gen_args_t *args)

5.15.1 Detailed Description

5.15.2 Data Structure Documentation

5.15.2.1 struct op_gc_akey_gen_args_t Structue detailing the generic crypto asymmetric key generate operation members

Data Fields

uint8_t *	modulus	pointer to the output buffer of key modulus
uint8_t *	priv_buff	pointer to the output buffer of key private exponent
uint8_t *	pub_buff	pointer to the input buffer containing key public exponent
uint16_t	modulus_size	size in bytes of the modulus buffer
uint16_t	priv_buff_size	size in bytes of the private exponent buffer
uint16_t	pub_buff_size	size in bytes of the public exponent buffer
hsm_key_type_t	key_type	indicates which type of keypair must be generated
hsm_bit_key_sz_t bit_key_sz		size in bits of the keypair to be generated

5.15.3 Function Documentation

This command is designed to perform the following operations: -Generate asymmetric keys, without using FW keystore

Parameters

session_hdl	handle identifying the current session.	
args	pointer to the structure containing the function arguments.	

Returns

5.16 Get Info 65

5.16 Get Info

Data Structures

• struct op_get_info_args_t

Functions

• hsm_err_t hsm_get_info (hsm_hdl_t sess_hdl, op_get_info_args_t *args)

5.16.1 Detailed Description

5.16.2 Data Structure Documentation

5.16.2.1 struct op_get_info_args_t Structure describing the get info operation member arguments

Data Fields

uint32_t	user_sab_id	< Stores User identifier (32bits) Stores the chip unique identifier
uint8_t *	chip_unique_id	Size of the chip unique identifier in bytes.
uint16_t	chip_unq_id_sz	Stores the chip monotonic counter value (16bits)
uint16_t	chip_monotonic_counter	Stores the chip current life cycle bitfield (16bits)
uint16_t	chip_life_cycle	Stores the module version (32bits)
uint32_t	version	Stores the module extended version (32bits)
uint32_t	version_ext	Stores the FIPS mode bitfield (8bits). Bitmask definition: bit0 - FIPS mode of operation:
		value 0 - part is running in FIPS non-approved mode.
		value 1 - part is running in FIPS approved mode. bit1 - FIPS certified part:
		value 0 - part is not FIPS certified.
		value 1 - part is FIPS certified. bit2-7: reserved
		• value 0.
uint8_t	fips_mode	

5.16.3 Function Documentation

Perform device attestation operation

User can call this function only after having opened the session.

Parameters

sess_hdl	handle identifying the active session.
args	pointer to the structure containing the function arguments.

Returns

5.17 Public key recovery

Public Key Recovery is now also known as Public Key Exportation, in PSA compliant APIs. The naming here has been kept unchanged, for backward compatibility and Non-PSA compliant APIs.

.

Data Structures

struct op_pub_key_recovery_args_t

Functions

hsm_err_t hsm_pub_key_recovery (hsm_hdl_t key_store_hdl, op_pub_key_recovery_args_t *args)

5.17.1 Detailed Description

Public Key Recovery is now also known as Public Key Exportation, in PSA compliant APIs. The naming here has been kept unchanged, for backward compatibility and Non-PSA compliant APIs.

.

5.17.2 Data Structure Documentation

5.17.2.1 struct op_pub_key_recovery_args_t Structure detailing the public key recovery opeation member arguments

Data Fields

uint32_t	key_identifier	< pointer to the identifier of the key to be used for the operation pointer to the output area where the generated public key must be written
uint8_t *	out_key	length in bytes of the output key
uint16_t	out_key_size	

5.17.3 Function Documentation

Recover Public key from private key present in key store User can call this function only after having opened a key store.

Parameters

key_store_hdl	handle identifying the current key store.
args	pointer to the structure containing the function arguments.

Returns

5.18 Key store 69

5.18 Key store

User must open a key store service flow in order to perform the following operations:

Data Structures

· struct open_svc_key_store_args_t

Macros

- #define HSM_SVC_KEY_STORE_FLAGS_LOAD ((hsm_svc_key_store_flags_t)(0u << 0))
 It must be specified to load a previously created key store.
- #define HSM_SVC_KEY_STORE_FLAGS_CREATE ((hsm_svc_key_store_flags_t)(1u << 0))
- #define HSM SVC KEY STORE FLAGS SET MAC LEN ((hsm svc key store flags t)(1u << 3))
- #define HSM_SVC_KEY_STORE_FLAGS_STRICT_OPERATION ((hsm_svc_key_store_flags_t)(1u << 7))

Typedefs

typedef uint8_t hsm_svc_key_store_flags_t

Functions

- hsm_err_t hsm_open_key_store_service (hsm_hdl_t session_hdl, open_svc_key_store_args_t *args, hsm hdl t *key store hdl)
- hsm_err_t hsm_close_key_store_service (hsm_hdl_t key_store_hdl)

5.18.1 Detailed Description

User must open a key store service flow in order to perform the following operations:

- · create a new key store
- · perform operations involving keys stored in the key store (ciphering, signature generation...)
- perform a key store reprovisioning using a signed message. A key store re-provisioning results in erasing all the key stores handled by the HSM.

To grant access to the key store, the caller is authenticated against the domain ID (DID) and Messaging Unit used at the keystore creation, additionally an authentication nonce can be provided.

5.18.2 Data Structure Documentation

5.18.2.1 struct open_svc_key_store_args_t Structure specifying the open key store service member arguments

Data Fields

hsm_hdl_t	key_store_hdl	< handle identifying the key store service flow user defined id identifying the key store.
uint32_t	key_store_identifier	user defined nonce used as authentication proof for accessing the
uint32_t	authentication_nonce	maximum number of updates authorized for the key store.
uint16_t	max_updates_number	bitmap specifying the services properties.
hsm_svc_key_store_flags_t	flags	pointer to signed_message to be sent only in case of
uint8_t *	signed_message	size of the signed_message to be sent only in case of
uint16_t	signed_msg_size	

5.18.3 Macro Definition Documentation

```
5.18.3.1 HSM_SVC_KEY_STORE_FLAGS_CREATE #define HSM_SVC_KEY_STORE_FLAGS_CREATE ((hsm_svc_key_store_flace << 0))
```

It must be specified to create a new key store. The key store will be stored in the NVM only if the STRICT OPER ← ATION flag is set.

```
5.18.3.2 HSM_SVC_KEY_STORE_FLAGS_SET_MAC_LEN #define HSM_SVC_KEY_STORE_FLAGS_SET_MAC ← _LEN ((hsm_svc_key_store_flags_t) (1u << 3))
```

If set, minimum mac length specified in min_mac_length field will be stored in the key store when creating the key store.

Must only be set at key store creation.

```
 \textbf{5.18.3.3} \quad \textbf{HSM\_SVC\_KEY\_STORE\_FLAGS\_STRICT\_OPERATION} \quad \texttt{\#define HSM\_SVC\_KEY\_STORE\_FLAGS\_ST} \\ \text{RICT\_OPERATION} \quad ((\texttt{hsm\_svc\_key\_store\_flags\_t}) \; (\texttt{lu} \; << \; 7) \; ) \\ \end{aligned}
```

The request is completed only when the new key store has been written in in the NVM. This applicable for CREATE operations only.

5.18.4 Typedef Documentation

```
5.18.4.1 hsm_svc_key_store_flags_t typedef uint8_t hsm_svc_key_store_flags_t
```

Bitmap specifying the open key store service supported attributes

5.18.5 Function Documentation

Open a service flow on the specified key store. Only one key store service can be opened on a given key store.

5.18 Key store 71

Parameters

session_hdl	pointer to the handle identifying the current session.
args	pointer to the structure containing the function arguments.
key_store_hdl	pointer to where the key store service flow handle must be written.

Returns

error_code error code.

```
    \textbf{5.18.5.2} \quad \textbf{hsm\_close\_key\_store\_service()} \quad \textbf{hsm\_err\_t} \quad \textbf{hsm\_close\_key\_store\_service} \quad ( \\ \quad \textbf{hsm\_hdl\_t} \quad \textbf{key\_store\_hdl} \quad )
```

Close a previously opened key store service flow. The key store is deleted from the HSM local memory, any update not written in the NVM is lost

Parameters

key_store_hdl	handle identifying the key store service flow to be closed.
---------------	---

Returns

error_code error code.

5.19 Life Cycle update

Data Structures

struct op_lc_update_msg_args_t

Enumerations

```
    enum hsm_lc_new_state_t {
    HSM_NXP_PROVISIONED_STATE = (1u << 0),</li>
    HSM_OEM_OPEN_STATE = (1u << 1),</li>
    HSM_OEM_CLOSE_STATE = (1u << 3),</li>
    HSM_OEM_FIELD_RET_STATE = (1u << 4),</li>
    HSM_NXP_FIELD_RET_STATE = (1u << 5),</li>
    HSM_OEM_LOCKED_STATE = (1u << 7) }</li>
```

Functions

• hsm_err_t hsm_lc_update (hsm_hdl_t session_hdl, op_lc_update_msg_args_t *args)

5.19.1 Detailed Description

5.19.2 Data Structure Documentation

5.19.2.1 struct op_lc_update_msg_args_t Structure specifying the life cycle update message arguments

Data Fields

```
hsm_lc_new_state_t | new_lc_state
```

5.19.3 Enumeration Type Documentation

```
\textbf{5.19.3.1} \quad \textbf{hsm\_lc\_new\_state\_t} \quad \texttt{enum} \ \texttt{hsm\_lc\_new\_state\_t}
```

Enum specifying the Life Cycle state

5.19.4 Function Documentation

This API will perform the Life Cycle update

Parameters

session_hdl	handle identifying the session handle.
args	pointer to the structure containing the function arguments.

Returns

error code

5.20 Error codes

Enumerations

```
enum hsm err t {
 HSM NO ERROR = 0x0,
 HSM_INVALID_MESSAGE = 0x1,
 HSM_INVALID_ADDRESS = 0x2,
 HSM UNKNOWN ID = 0x3,
 HSM INVALID PARAM = 0x4,
 HSM_NVM_ERROR = 0x5,
 HSM_OUT_OF_MEMORY = 0x6,
 HSM UNKNOWN HANDLE = 0x7,
 HSM_UNKNOWN_KEY_STORE = 0x8,
 HSM_KEY_STORE_AUTH = 0x9,
 HSM_KEY_STORE_ERROR = 0xA,
 HSM ID CONFLICT = 0xB,
 HSM_RNG_NOT_STARTED = 0xC,
 HSM CMD NOT SUPPORTED = 0xD,
 HSM INVALID LIFECYCLE = 0xE,
 HSM KEY STORE CONFLICT = 0xF,
 HSM_KEY_STORE_COUNTER = 0x10,
 HSM FEATURE NOT SUPPORTED = 0x11,
 HSM SELF TEST FAILURE = 0x12,
 HSM NOT READY RATING = 0x13,
 HSM_FEATURE_DISABLED = 0x14,
 HSM_KEY_GROUP_FULL = 0x19,
 HSM_CANNOT_RETRIEVE_KEY_GROUP = 0x1A,
 HSM_KEY_NOT_SUPPORTED = 0x1B,
 HSM CANNOT DELETE PERMANENT KEY = 0x1C,
 HSM_OUT_TOO_SMALL = 0x1D,
 HSM CRC CHECK ERR = 0xB9,
 HSM OEM CLOSED LC SIGNED MSG VERIFICATION FAIL = 0xF0,
 HSM_OEM_OPEN_LC_SIGNED_MSG_VERIFICATION_FAIL = 0xF0,
 HSM_FATAL_FAILURE = 0x29,
 HSM SERVICES DISABLED = 0xF4,
 HSM_UNKNOWN_WARNING = 0xFC,
 HSM_SIGNATURE_INVALID = 0xFD,
 HSM\_UNKNOWN\_ERROR = 0xFE,
 HSM GENERAL ERROR = 0xFF }
```

5.20.1 Detailed Description

5.20.2 Enumeration Type Documentation

5.20.2.1 hsm_err_t enum hsm_err_t

Error codes returned by HSM functions.

Enumerator

HSM_NO_ER	RROR Success. The received message is invalid or
	unknown.

5.20 Error codes 75

Enumerator

HSM_INVALID_MESSAGE	The provided address is invalid or doesn't respect the API requirements.
HSM_INVALID_ADDRESS	The provided identifier is not known.
HSM_UNKNOWN_ID	One of the parameter provided in the command is invalid.
HSM_INVALID_PARAM	NVM generic issue.
HSM_NVM_ERROR	There is not enough memory to handle the requested operation.
HSM_OUT_OF_MEMORY	Unknown session/service handle.
HSM_UNKNOWN_HANDLE	The key store identified by the provided "key store Id" doesn't exist and the "create" flag is not set.
HSM_UNKNOWN_KEY_STORE	Key store authentication fails.
HSM_KEY_STORE_AUTH	An error occurred in the key store internal processing.
HSM_KEY_STORE_ERROR	An element (key store, key) with the provided ID already exists.
HSM_ID_CONFLICT	The internal RNG is not started.
HSM_RNG_NOT_STARTED	The functionality is not supported for the current session/service/key store configuration.
HSM_CMD_NOT_SUPPORTED	Invalid lifecycle for requested operation.
HSM_INVALID_LIFECYCLE	A key store with the same attributes already exists.
HSM_KEY_STORE_CONFLICT	The current key store reaches the max number of monotonic counter updates, updates are still allowed but monotonic counter will not be blown.
HSM_KEY_STORE_COUNTER	The requested feature is not supported by the firwware.
HSM_FEATURE_NOT_SUPPORTED	Self tests report an issue
HSM_SELF_TEST_FAILURE	The HSM is not ready to handle the current request
HSM_NOT_READY_RATING	The required service/operation is disabled
HSM_FEATURE_DISABLED	Not enough space to store the key in the key group
HSM_KEY_GROUP_FULL	Impossible to retrieve key group
HSM_CANNOT_RETRIEVE_KEY_GROUP	Key not supported
HSM_KEY_NOT_SUPPORTED	Trying to delete a permanent key
HSM_CANNOT_DELETE_PERMANENT_KEY	Output buffer size is too small
HSM_OUT_TOO_SMALL	Command CRC check error
HSM_CRC_CHECK_ERR	In OEM closed lifecycle, Signed message signature verification failure
HSM_OEM_CLOSED_LC_SIGNED_MSG_VERIFI↔ CATION_FAIL	Warning: In OEM open lifecycles, Signed message signature verification failure
HSM_OEM_OPEN_LC_SIGNED_MSG_VERIFIC↔ ATION_FAIL	A fatal failure occurred, the HSM goes in unrecoverable error state not replying to further requests
HSM_FATAL_FAILURE	Message neither handled by ROM nor FW
HSM_SERVICES_DISABLED	Unknown warnings
HSM_UNKNOWN_WARNING	Failure in verification status of operations such as
	MAC verification, Signature verification.
HSM_SIGNATURE_INVALID	· ·

Index

add_service	HSM_CRC_CHECK_ERR, 75
Session, 9	hsm_err_t, 74
add_session	HSM_FATAL_FAILURE, 75
Session, 8	HSM_FEATURE_DISABLED, 75
Authenticated Encryption, 48	HSM_FEATURE_NOT_SUPPORTED, 75
hsm_do_auth_enc, 48	HSM_ID_CONFLICT, 75
/	HSM_INVALID_ADDRESS, 75
Ciphering, 22	HSM_INVALID_LIFECYCLE, 75
HSM_AEAD_ALGO_CCM, 25	HSM_INVALID_MESSAGE, 75
hsm_auth_enc, 25	HSM INVALID PARAM, 75
HSM_AUTH_ENC_FLAGS_DECRYPT, 23	HSM_KEY_GROUP_FULL, 75
HSM_AUTH_ENC_FLAGS_ENCRYPT, 24	HSM_KEY_NOT_SUPPORTED, 75
HSM_AUTH_ENC_FLAGS_GENERATE_COUNTER	R_IV, HSM KEY STORE AUTH, 75
24	HSM_KEY_STORE_CONFLICT, 75
HSM_AUTH_ENC_FLAGS_GENERATE_FULL_IV,	HSM_KEY_STORE_COUNTER, 75
24	HSM_KEY_STORE_ERROR, 75
hsm_cipher_one_go, 26	HSM_NO_ERROR, 74
HSM_CIPHER_ONE_GO_ALGO_CFB, 25	HSM NOT READY RATING, 75
HSM_CIPHER_ONE_GO_ALGO_CTR, 25	HSM NVM ERROR, 75
HSM_CIPHER_ONE_GO_ALGO_ECB, 25	HSM_OEM_CLOSED_LC_SIGNED_MSG_VERIFICATION_FAIL,
HSM_CIPHER_ONE_GO_ALGO_OFB, 25	75
HSM CIPHER ONE GO FLAGS DECRYPT, 24	HSM OEM OPEN LC SIGNED MSG VERIFICATION FAIL,
HSM_CIPHER_ONE_GO_FLAGS_ENCRYPT, 24	75
hsm_close_cipher_service, 27	HSM_OUT_OF_MEMORY, 75
hsm_do_cipher, 25	HSM_OUT_TOO_SMALL, 75
hsm_op_auth_enc_algo_t, 24	HSM_RNG_NOT_STARTED, 75
hsm_op_auth_enc_flags_t, 24	HSM_SELF_TEST_FAILURE, 75
hsm_op_cipher_one_go_algo_t, 25	HSM_SERVICES_DISABLED, 75
hsm_op_cipher_one_go_flags_t, 24	HSM SIGNATURE INVALID, 75
hsm_open_cipher_service, 26	HSM_UNKNOWN_ERROR, 75
hsm_svc_cipher_flags_t, 24	HSM_UNKNOWN_HANDLE, 75
<u></u>	HSM_UNKNOWN_ID, 75
Data storage, 44	HSM UNKNOWN KEY STORE, 75
hsm_close_data_storage_service, 46	HSM UNKNOWN WARNING, 75
hsm_data_ops, 45	TIOM_ONTO
hsm_data_storage, 46	FLAG
hsm_op_data_storage_flags_t, 45	Key management, 16
hsm_open_data_storage_service, 46	The state of the s
hsm_svc_data_storage_flags_t, 45	Generic Crypto Asymmetric Key Generate, 63
delete_service	hsm_gc_akey_gen, 63
Session, 8	Generic Crypto: Asymmetric Crypto, 59
delete_session	hsm_gc_acrypto, 62
Session, 8	hsm_gc_acrypto_op_mode_t, 62
Dev attest, 55	HSM GC ACRYPTO VERIFICATION FAILURE,
hsm dev attest, 55	61
Dev Info, 57	hsm_gc_acrypto_verification_status_t, 62
hsm dev getinfo, 57	HSM_GC_ACRYPTO_VERIFICATION_SUCCESS,
Dump Firmware Log, 54	61
dump firmware log, 54	hsm_op_gc_acrypto_algo_t, 62
dump_firmware_log	HSM_OP_GC_ACRYPTO_FLAGS_INPUT_MESSAGE,
Dump Firmware Log, 54	61
- I	hsm_op_gc_acrypto_flags_t, 61
Error codes, 74	Get Info, 65
HSM_CANNOT_DELETE_PERMANENT_KEY, 75	hsm_get_info, 65
HSM_CANNOT_RETRIEVE_KEY_GROUP, 75	
HSM_CMD_NOT_SUPPORTED, 75	Hashing, 41

hsm_do_hash, 42	Data storage, 45
hsm_hash_algo_t, 42	hsm_data_storage
HSM_HASH_FLAG_ALLOWED, 42	Data storage, 46
hsm_hash_one_go, 42	hsm_delete_key
hsm_hash_svc_flags_t, 42	Key management, 18
HSM_AEAD_ALGO_CCM	hsm_dev_attest
Ciphering, 25	Dev attest, 55
hsm_auth_enc	hsm_dev_getinfo
Ciphering, 25	Dev Info, 57
HSM_AUTH_ENC_FLAGS_DECRYPT	hsm_do_auth_enc
Ciphering, 23	Authenticated Encryption, 48
HSM AUTH ENC FLAGS ENCRYPT	hsm_do_cipher
Ciphering, 24	Ciphering, 25
HSM_AUTH_ENC_FLAGS_GENERATE_COUNTER_IV	hsm_do_hash
Ciphering, 24	Hashing, 42
HSM_AUTH_ENC_FLAGS_GENERATE_FULL_IV	hsm_do_mac
Ciphering, 24	 Mac, 51
hsm_bit_key_sz_t	hsm_do_rng
Key management, 18	Random number generation, 39
HSM_CANNOT_DELETE_PERMANENT_KEY	hsm_do_sign
Error codes, 75	Signature generation, 30
HSM_CANNOT_RETRIEVE_KEY_GROUP	hsm_err_t
Error codes, 75	Error codes, 74
hsm_cipher_one_go	HSM FATAL FAILURE
Ciphering, 26	Error codes, 75
HSM_CIPHER_ONE_GO_ALGO_CFB	HSM_FEATURE_DISABLED
Ciphering, 25	Error codes, 75
HSM_CIPHER_ONE_GO_ALGO_CTR	HSM_FEATURE_NOT_SUPPORTED
Ciphering, 25	Error codes, 75
HSM_CIPHER_ONE_GO_ALGO_ECB	hsm_gc_acrypto
Ciphering, 25	Generic Crypto: Asymmetric Crypto, 62
HSM_CIPHER_ONE_GO_ALGO_OFB	hsm_gc_acrypto_op_mode_t
Ciphering, 25	Generic Crypto: Asymmetric Crypto, 62
HSM_CIPHER_ONE_GO_FLAGS_DECRYPT	HSM_GC_ACRYPTO_VERIFICATION_FAILURE
Ciphering, 24	Generic Crypto: Asymmetric Crypto, 61
HSM_CIPHER_ONE_GO_FLAGS_ENCRYPT	hsm_gc_acrypto_verification_status_t
Ciphering, 24	Generic Crypto: Asymmetric Crypto, 62
hsm_close_cipher_service	HSM_GC_ACRYPTO_VERIFICATION_SUCCESS
Ciphering, 27	Generic Crypto: Asymmetric Crypto, 61
hsm_close_data_storage_service	hsm_gc_akey_gen
Data storage, 46	Generic Crypto Asymmetric Key Generate, 63
hsm_close_key_management_service	hsm_generate_key
Key management, 20	Key management, 19
hsm_close_key_store_service	hsm_generate_key_ext
Key store, 71	Key management, 19
hsm_close_mac_service	hsm_generate_signature
Mac, 52	Signature generation, 31
hsm_close_session	hsm_get_info
Session, 7	Get Info, 65
hsm_close_signature_generation_service	hsm_get_key_attr
Signature generation, 31	Key management, 18
hsm_close_signature_verification_service	hsm_get_random
Signature verification, 37	Random number generation, 39
HSM_CMD_NOT_SUPPORTED	hsm_hash_algo_t
Error codes, 75	Hashing, 42
HSM_CRC_CHECK_ERR	HSM_HASH_FLAG_ALLOWED
Error codes, 75	Hashing, 42
hsm_data_ops	hsm_hash_one_go

Hashing, 42	Key management, 15
hsm_hash_svc_flags_t	HSM_KEY_USAGE_SIGN_MSG
Hashing, 42	Key management, 15
hsm_hdl_t	hsm_key_usage_t
Session, 6	Key management, 17
HSM_ID_CONFLICT	HSM_KEY_USAGE_VERIFY_HASH
Error codes, 75	Key management, 15
hsm_import_key	HSM_KEY_USAGE_VERIFY_MSG
Key management, 19	Key management, 15
HSM_INVALID_ADDRESS	hsm_lc_new_state_t
Error codes, 75	Life Cycle update, 72
HSM_INVALID_LIFECYCLE	hsm_lc_update
Error codes, 75	Life Cycle update, 72
HSM_INVALID_MESSAGE	hsm_mac_one_go
Error codes, 75	Mac, 52
HSM_INVALID_PARAM	HSM_MAC_VERIFICATION_STATUS_SUCCESS
Error codes, 75	
HSM_KEY_GROUP_FULL	hsm_mac_verification_status_t
Error codes, 75	Mac, 50
hsm_key_group_t	HSM_NO_ERROR
Key management, 17	Error codes, 74
HSM KEY INFO KEK	HSM_NOT_READY_RATING
Key management, 16	Error codes, 75
HSM KEY INFO MASTER	
	HSM_NVM_ERROR
Key management, 16	Error codes, 75
HSM_KEY_INFO_PERMANENT	HSM_OEM_CLOSED_LC_SIGNED_MSG_VERIFICATION_FAI
Key management, 16	Error codes, 75
HSM_KEY_INFO_PERSISTENT	HSM_OEM_OPEN_LC_SIGNED_MSG_VERIFICATION_FAIL
Key management, 15	Error codes, 75
hsm_key_info_t	hsm_op_auth_enc_algo_t
Key management, 17	Ciphering, 24
HSM_KEY_INFO_TRANSIENT	hsm_op_auth_enc_flags_t
Key management, 16	Ciphering, 24
hsm_key_lifecycle_t	hsm_op_cipher_one_go_algo_t
Key management, 18	Ciphering, 25
hsm_key_lifetime_t	hsm_op_cipher_one_go_flags_t
Key management, 17	Ciphering, 24
HSM_KEY_NOT_SUPPORTED	hsm_op_data_storage_flags_t
Error codes, 75	Data storage, 45
HSM_KEY_STORE_AUTH	HSM_OP_DEL_KEY_FLAGS_STRICT_OPERATION
Error codes, 75	Key management, 15
HSM_KEY_STORE_CONFLICT	hsm_op_delete_key_flags_t
Error codes, 75	Key management, 16
HSM_KEY_STORE_COUNTER	hsm_op_gc_acrypto_algo_t
Error codes, 75	Generic Crypto: Asymmetric Crypto, 62
HSM_KEY_STORE_ERROR	HSM OP GC ACRYPTO FLAGS INPUT MESSAGE
Error codes, 75	Generic Crypto: Asymmetric Crypto, 61
hsm_key_type_t	hsm_op_gc_acrypto_flags_t
Key management, 17	Generic Crypto: Asymmetric Crypto, 61
HSM_KEY_USAGE_DECRYPT	HSM_OP_GENERATE_SIGN_FLAGS_INPUT_DIGEST
Key management, 15	Signature generation, 29
HSM_KEY_USAGE_DERIVE	HSM_OP_GENERATE_SIGN_FLAGS_INPUT_MESSAGE
Key management, 15	Signature generation, 29
HSM_KEY_USAGE_ENCRYPT	hsm_op_generate_sign_flags_t
Key management, 15	Signature generation, 30
HSM_KEY_USAGE_EXPORT	hsm_op_import_key_flags_t
Key management, 15	Key management, 16
HSM_KEY_USAGE_SIGN_HASH	hsm_op_key_gen_flags_t

Var. managamant 17	have acceion hall a C
Key management, 17	hsm_session_hdl_s, 6
HSM_OP_KEY_GENERATION_FLAGS_STRICT_OPER.	
Key management, 16	Error codes, 75
hsm_op_mac_one_go_algo_t	hsm_signature_scheme_id_t
Mac, 50	Signature generation, 30
HSM_OP_MAC_ONE_GO_FLAGS_MAC_GENERATION	
Mac, 50	Key management, 17
HSM_OP_MAC_ONE_GO_FLAGS_MAC_VERIFICATION	-
Mac, 50	Key management, 17
hsm_op_mac_one_go_flags_t	hsm_svc_cipher_flags_t
Mac, 50	Ciphering, 24
hsm_op_prepare_signature_flags_t	hsm_svc_data_storage_flags_t
Signature generation, 30	Data storage, 45
HSM_OP_VERIFY_SIGN_FLAGS_COMPRESSED_POI	N ի sm_svc_key_management_flags_t
Signature verification, 35	Key management, 17
HSM_OP_VERIFY_SIGN_FLAGS_INPUT_DIGEST	HSM_SVC_KEY_STORE_FLAGS_CREATE
Signature verification, 35	Key store, 70
	HSM_SVC_KEY_STORE_FLAGS_SET_MAC_LEN
HSM_OP_VERIFY_SIGN_FLAGS_INPUT_MESSAGE	Key store, 70
Signature verification, 35	HSM_SVC_KEY_STORE_FLAGS_STRICT_OPERATION
HSM_OP_VERIFY_SIGN_FLAGS_KEY_INTERNAL	
Signature verification, 35	Key store, 70
hsm_op_verify_sign_flags_t	hsm_svc_key_store_flags_t
Signature verification, 36	Key store, 70
hsm_open_cipher_service	HSM_UNKNOWN_ERROR
Ciphering, 26	Error codes, 75
hsm_open_data_storage_service	HSM_UNKNOWN_HANDLE
Data storage, 46	Error codes, 75
hsm_open_key_management_service	HSM_UNKNOWN_ID
Key management, 20	Error codes, 75
	HSM_UNKNOWN_KEY_STORE
hsm_open_key_store_service	Error codes, 75
Key store, 70	HSM_UNKNOWN_WARNING
hsm_open_mac_service	Error codes, 75
Mac, 51	HSM_VERIFICATION_STATUS_FAILURE
hsm_open_session	Signature verification, 35
Session, 7	
hsm_open_signature_generation_service	HSM_VERIFICATION_STATUS_SUCCESS
Signature generation, 31	Signature verification, 35
hsm open signature verification service	hsm_verification_status_t
Signature verification, 37	Signature verification, 36
HSM_OUT_OF_MEMORY	hsm_verify_sign
Error codes, 75	Signature verification, 36
•	hsm_verify_signature
HSM_OUT_TOO_SMALL	Signature verification, 37
Error codes, 75	
hsm_permitted_algo_t	kek_enc_key_hdr_t, 13
Key management, 18	Key management, 10
hsm_prepare_signature	FLAG, 16
Signature generation, 32	hsm bit key sz t, 18
hsm pub key recovery	hsm_close_key_management_service, 20
Public key recovery, 67	hsm_delete_key, 18
hsm_pubkey_type_t	hsm_generate_key, 19
Key management, 17	hsm_generate_key_ext, 19
HSM_RNG_NOT_STARTED	
	hsm_get_key_attr, 18
Error codes, 75	hsm_import_key, 19
HSM_SELF_TEST_FAILURE	hsm_key_group_t, 17
Error codes, 75	HSM_KEY_INFO_KEK, 16
hsm_service_hdl_s, 6	HSM_KEY_INFO_MASTER, 16
HSM_SERVICES_DISABLED	HSM_KEY_INFO_PERMANENT, 16
Error codes, 75	HSM_KEY_INFO_PERSISTENT, 15

```
hsm_key_info_t, 17
                                                  op_debug_dump_args_t, 54
    HSM KEY INFO TRANSIENT, 16
                                                  op_delete_key_args_t, 12
    hsm_key_lifecycle_t, 18
                                                  op_dev_attest_args_t, 55
    hsm_key_lifetime_t, 17
                                                  op_dev_getinfo_args_t, 57
    hsm_key_type_t, 17
                                                  op_gc_acrypto_args_t, 60
    HSM KEY USAGE DECRYPT, 15
                                                  op gc akey gen args t, 63
    HSM KEY USAGE DERIVE, 15
                                                  op generate key args t, 14
    HSM KEY USAGE ENCRYPT, 15
                                                  op_generate_key_ext_args_t, 13
    HSM KEY USAGE EXPORT, 15
                                                  op generate sign args t, 29
    HSM_KEY_USAGE_SIGN_HASH, 15
                                                  op_get_info_args_t, 65
    HSM_KEY_USAGE_SIGN_MSG, 15
                                                  op_get_key_attr_args_t, 12
    hsm_key_usage_t, 17
                                                  op_get_random_args_t, 39
    HSM KEY USAGE VERIFY HASH, 15
                                                  op hash one go args t, 41
    HSM KEY USAGE VERIFY MSG, 15
                                                  op_import_key_args_t, 13
    HSM_OP_DEL_KEY_FLAGS_STRICT_OPERATIONop_lc_update_msg_args_t, 72
                                                  op_mac_one_go_args_t, 49
    hsm op delete key flags t. 16
                                                  op prepare sign args t, 29
    hsm op import key flags t, 16
                                                  op_pub_key_recovery_args_t, 67
    hsm_op_key_gen_flags_t, 17
                                                  op verify sign args t, 34
    HSM OP KEY GENERATION FLAGS STRICT OPERATION args t, 6
                                                  open svc cipher args t, 23
    hsm_open_key_management_service, 20
                                                  open_svc_data_storage_args_t, 44
    hsm_permitted_algo_t, 18
                                                  open_svc_key_management_args_t, 14
    hsm_pubkey_type_t, 17
                                                  open_svc_key_store_args_t, 69
    hsm_storage_loc_t, 17
                                                  open_svc_mac_args_t, 49
    hsm_storage_persist_lvl_t, 17
                                                  open_svc_sign_gen_args_t, 29
    hsm svc key management flags t, 17
                                                  open svc sign ver args t, 34
Key store, 69
                                                  Public key recovery, 67
    hsm_close_key_store_service, 71
                                                      hsm pub key recovery, 67
    hsm open key store service, 70
    HSM SVC KEY STORE FLAGS CREATE, 70
                                                  Random number generation, 39
    HSM_SVC_KEY_STORE_FLAGS_SET_MAC_LEN,
                                                      hsm do rng, 39
        70
    HSM_SVC_KEY_STORE_FLAGS_STRICT_OPERATION, hsm_get_random, 39
                                                  service_hdl_to_ptr
    hsm_svc_key_store_flags_t, 70
                                                       Session, 8
                                                  Session, 5
Life Cycle update, 72
                                                      add_service, 9
    hsm Ic new state t, 72
                                                      add_session, 8
    hsm lc update, 72
                                                      delete_service, 8
                                                      delete session, 8
Mac, 49
                                                      hsm_close_session, 7
    hsm close mac service, 52
                                                      hsm hdl t, 6
    hsm do mac, 51
                                                      hsm open session, 7
    hsm_mac_one_go, 52
                                                      service_hdl_to_ptr, 8
    HSM_MAC_VERIFICATION_STATUS_SUCCESS,
                                                      session_hdl_to_ptr, 7
                                                  session hdl to ptr
    hsm_mac_verification_status_t, 50
                                                      Session, 7
    hsm_op_mac_one_go_algo_t, 50
    HSM_OP_MAC_ONE_GO_FLAGS_MAC_GENERAT (b) in a ture generation, 28
                                                       hsm_close_signature_generation_service, 31
    HSM_OP_MAC_ONE_GO_FLAGS_MAC_VERIFICATION,hsm_do_sign, 30
                                                      hsm generate signature, 31
        50
                                                      HSM OP GENERATE SIGN FLAGS INPUT DIGEST,
    hsm op mac one go flags t, 50
    hsm open mac service, 51
                                                      HSM OP GENERATE SIGN FLAGS INPUT MESSAGE,
op auth enc args t, 22
                                                           29
op_cipher_one_go_args_t, 23
                                                      hsm_op_generate_sign_flags_t, 30
op_data_storage_args_t, 44
                                                      hsm_op_prepare_signature_flags_t, 30
```

```
hsm_open_signature_generation_service, 31
    hsm_prepare_signature, 32
    hsm_signature_scheme_id_t, 30
Signature verification, 34
    hsm_close_signature_verification_service, 37
    HSM_OP_VERIFY_SIGN_FLAGS_COMPRESSED_POINT,
    HSM_OP_VERIFY_SIGN_FLAGS_INPUT_DIGEST,
    HSM_OP_VERIFY_SIGN_FLAGS_INPUT_MESSAGE,
    HSM_OP_VERIFY_SIGN_FLAGS_KEY_INTERNAL,
        35
    hsm_op_verify_sign_flags_t, 36
    hsm_open_signature_verification_service, 37
    HSM_VERIFICATION_STATUS_FAILURE, 35
    HSM_VERIFICATION_STATUS_SUCCESS, 35
    hsm_verification_status_t, 36
    hsm_verify_sign, 36
    hsm_verify_signature, 37
```