

Booklet of Code and Output
for
STAD29/STA 1007 Midterm Exam

List of Figures in this document by page:

List of Figures

1	Packages	2
2	Hospital infection risk data (some)	3
3	Regression	4
4	Drop-1 output from regression	4
5	Another model, and predictions	5
6	Flu shot data (some)	5
7	Logistic regression	6
8	Quartiles for age and awareness	6
9	LSYPE data, some, selected variables	7
10	Summary of data	8
11	Doing something	8
12	Model-fitting	9
13	Predictions for LSYPE English grade	9
14	Unemployment data (some)	10
15	Construction of response variable and display of first 20 values	10
16	Cox model	11
17	Predictions for job type	12
18	Rod extrusion data	13
19	ANOVA	13
20	Tukey for rod extrusion data	14
21	Further analysis of rod extrusion data	15
22	Plot of predictions for job type	16
23	Grouped boxplot for rod extrusion data	17
24	Interaction plot for rod extrusion data	18

```

library(MASS)
library(tidyverse)

## -- Attaching packages -----
tidyverse 1.2.1 --
## ✓ ggplot2 2.2.1.9000    ✓ purrr 0.2.4
## ✓ tibble 1.4.2          ✓ dplyr 0.7.4
## ✓ tidyr 0.8.0           ✓ stringr 1.3.0
## ✓ readr 1.1.1           ✓ forcats 0.3.0
## -- Conflicts -----
tidyverse_conflicts() --
## x dplyr::filter() masks stats::filter()
## x dplyr::lag()     masks stats::lag()
## x dplyr::select() masks MASS::select()

library(broom)
library(survival)
library(survminer)

## Loading required package: ggpubr
## Loading required package: magrittr
##
## Attaching package: 'magrittr'
## The following object is masked from 'package:purrr':
##
##   set_names
## The following object is masked from 'package:tidyr':
##
##   extract

```

Figure 1: Packages

```
infection=read_tsv("infectionrisk.txt")

## Parsed with column specification:
## cols(
##   ID = col_integer(),
##   Stay = col_double(),
##   Age = col_double(),
##   InfctRsk = col_double(),
##   Culture = col_double(),
##   Xray = col_double(),
##   Beds = col_integer(),
##   MedSchool = col_integer(),
##   Region = col_integer(),
##   Census = col_integer(),
##   Nurses = col_integer(),
##   Facilities = col_double()
## )

infection

## # A tibble: 113 x 12
##       ID Stay Age InfctRsk Culture Xray Beds MedSchool Region Census
##   <int> <dbl> <dbl>   <dbl>   <dbl> <dbl> <int>   <int>   <int>   <int>
## 1     1  7.13 55.7    4.10    9.00 39.6  279     2     4    207
## 2     2  8.82 58.2    1.60    3.80 51.7   80     2     2     51
## 3     3  8.34 56.9    2.70    8.10 74.0  107     2     3     82
## 4     4  8.95 53.7    5.60   18.9 123   147     2     4     53
## 5     5 11.2 56.5    5.70   34.5 88.9  180     2     1    134
## 6     6  9.76 50.9    5.10   21.9 97.0  150     2     2    147
## 7     7  9.68 57.8    4.60   16.7 79.0  186     2     3    151
## 8     8 11.2 45.7    5.40   60.5 85.8  640     1     2    399
## 9     9  8.67 48.2    4.30   24.4 90.8  182     2     3    130
## 10    10  8.84 56.3    6.30   29.6 82.6   85     2     1     59
## # ... with 103 more rows, and 2 more variables: Nurses <int>,
## #   Facilities <dbl>
```

Figure 2: Hospital infection risk data (some)

```
infection = infection %>% mutate(Region=factor(Region))
inf.1=lm(InfctRsk~Stay+Xray+Region,data=infection)
summary(inf.1)

##
## Call:
## lm(formula = InfctRsk ~ Stay + Xray + Region, data = infection)
##
## Residuals:
##      Min       1Q   Median       3Q      Max
## -2.75483 -0.64146  0.00862  0.67124  2.44950
##
## Coefficients:
##              Estimate Std. Error t value Pr(>|t|)
## (Intercept) -0.802903   0.775573  -1.035  0.302892
## Stay         0.349288   0.063845   5.471 2.97e-07 ***
## Xray         0.019663   0.005762   3.413 0.000909 ***
## Region2      0.178873   0.290077   0.617 0.538782
## Region3      0.043021   0.297064   0.145 0.885124
## Region4      0.832871   0.381718   2.182 0.031304 *
## ---
## Signif. codes:  0 '***' 0.001 '**' 0.01 '*' 0.05 '.' 0.1 ' ' 1
##
## Residual standard error: 1.068 on 107 degrees of freedom
## Multiple R-squared:  0.3938, Adjusted R-squared:  0.3655
## F-statistic: 13.9 on 5 and 107 DF, p-value: 1.839e-10
```

Figure 3: Regression for predicting infection risk

```
drop1(inf.1,test="F")

## Single term deletions
##
## Model:
## InfctRsk ~ Stay + Xray + Region
##           Df Sum of Sq  RSS   AIC F value    Pr(>F)
## <none>                 122.07 20.727
## Stay      1      34.147 156.22 46.598 29.9305 2.968e-07 ***
## Xray      1      13.287 135.36 30.402 11.6464 0.0009092 ***
## Region    3       7.334 129.41 21.320  2.1428 0.0991208 .
## ---
## Signif. codes:  0 '***' 0.001 '**' 0.01 '*' 0.05 '.' 0.1 ' ' 1
```

Figure 4: Drop-1 output from regression

```

inf.2=update(inf.1,.~-Region)
new=tibble(Stay=15,Xray=70,Region=1)
p=predict(inf.2,new,interval="p")
cbind(new,p)

##   Stay Xray Region      fit      lwr      upr
## 1    15   70      1 5.702933 3.44029 7.965575

```

Figure 5: Another model, and predictions

```

flu=read_table("flu-shots.txt")

## Parsed with column specification:
## cols(
##   shot = col_double(),
##   age = col_double(),
##   awareness = col_double()
## )

flu

## # A tibble: 50 x 3
##   shot    age awareness
##   <dbl> <dbl>   <dbl>
## 1     0   38.0    40.0
## 2   1.00  52.0    60.0
## 3     0   41.0    36.0
## 4   1.00  46.0    59.0
## 5   1.00  41.0    70.0
## 6     0   43.0    49.0
## 7   1.00  57.0    59.0
## 8     0   34.0    50.0
## 9     0   31.0    48.0
## 10  1.00  49.0    59.0
## # ... with 40 more rows

```

Figure 6: Flu shot data (some)

```

shot.1=glm(factor(shot)~age+awareness, family="binomial", data=flu)
summary(shot.1)

##
## Call:
## glm(formula = factor(shot) ~ age + awareness, family = "binomial",
##      data = flu)
##
## Deviance Residuals:
##      Min       1Q   Median       3Q      Max
## -1.5522  -0.2962  -0.1124   0.4208   2.3244
##
## Coefficients:
##              Estimate Std. Error z value Pr(>|z|)
## (Intercept) -21.58458     6.41824  -3.363 0.000771 ***
## age           0.22178     0.07436   2.983 0.002858 **
## awareness     0.20351     0.06273   3.244 0.001178 **
## ---
## Signif. codes:  0 '***' 0.001 '**' 0.01 '*' 0.05 '.' 0.1 ' ' 1
##
## (Dispersion parameter for binomial family taken to be 1)
##
##      Null deviance: 68.029  on 49  degrees of freedom
## Residual deviance: 32.416  on 47  degrees of freedom
## AIC: 38.416
##
## Number of Fisher Scoring iterations: 6

```

Figure 7: Logistic regression

```

flu %>%
  summarize(age_q1=quantile(age,0.25),
            age_q3=quantile(age,0.75),
            awareness_q1=quantile(awareness,0.25),
            awareness_q3=quantile(awareness,0.75))

## # A tibble: 1 x 4
##   age_q1 age_q3 awareness_q1 awareness_q3
##   <dbl> <dbl>         <dbl>         <dbl>
## 1   40.2   53.0          43.2          59.0

```

Figure 8: Quartiles for age and awareness

```

kids=read_csv("kids.csv")

## Parsed with column specification:
## cols(
##   .default = col_integer(),
##   pupilid = col_double(),
##   ks2score = col_double(),
##   ks3score = col_double(),
##   ks4score = col_double(),
##   IDACI_n = col_double(),
##   weighting = col_double()
## )
## See spec(...) for full column specifications.

kids = kids %>% select(k3en,gender,sec,ks2stand)
kids

## # A tibble: 15,770 x 4
##       k3en gender   sec ks2stand
##   <int> <int> <int>   <int>
## 1     3     0     2    -24
## 2     3     0     8     NA
## 3     3     1    NA     NA
## 4     3     0     2    -21
## 5     3     1    NA    -24
## 6     3     1    NA    -24
## 7     3     1    NA    -24
## 8     3     1    NA    -24
## 9     3     1     8     NA
## 10    3     1     2    -24
## # ... with 15,760 more rows

```

(Note: 0 is male and 1 is female)

Figure 9: LSYPE data, some, selected variables


```
summary(kids)
```

##	k3en	gender	sec	ks2stand
## Min.	:3.000	Min. :0.0000	Min. :1.000	Min. :-
	24.0000			
## 1st Qu.:	4.000	1st Qu.:0.0000	1st Qu.:2.000	1st Qu.: -
	7.0000			
## Median	:5.000	Median :0.0000	Median :4.000	Median : 0.0000
## Mean	:5.067	Mean :0.4912	Mean :4.114	Mean : 0.0119
## 3rd Qu.:	6.000	3rd Qu.:1.0000	3rd Qu.:6.000	3rd Qu.: 7.0000
## Max.	:7.000	Max. :1.0000	Max. :8.000	Max. : 39.0000
## NA's	:1307	NA's :339	NA's :2941	NA's :1469

Figure 10: Summary of data

```
kids = kids %>%
  filter(!is.na(k3en),
         !is.na(gender),
         !is.na(sec),
         !is.na(ks2stand))
summary(kids)
```

##	k3en	gender	sec	ks2stand
## Min.	:3.000	Min. :0.0000	Min. :1.000	Min. :-
	24.0000			
## 1st Qu.:	5.000	1st Qu.:0.0000	1st Qu.:2.000	1st Qu.: -
	6.0000			
## Median	:5.000	Median :0.0000	Median :4.000	Median : 1.0000
## Mean	:5.139	Mean :0.4889	Mean :4.119	Mean : 0.6265
## 3rd Qu.:	6.000	3rd Qu.:1.0000	3rd Qu.:6.000	3rd Qu.: 7.0000
## Max.	:7.000	Max. :1.0000	Max. :8.000	Max. : 39.0000

Figure 11: Doing something with our variables

```

en3.1=polr(en3~gender+sec+ks2stand,data=kids)
drop1(en3.1,test="Chisq")

## Single term deletions
##
## Model:
## en3 ~ gender + sec + ks2stand
##           Df    AIC    LRT  Pr(>Chi)
## <none>          22208
## gender      1 22911  704.4 < 2.2e-16 ***
## sec         1 22496  289.4 < 2.2e-16 ***
## ks2stand    1 30381 8174.3 < 2.2e-16 ***
## ---
## Signif. codes:  0 '***' 0.001 '**' 0.01 '*' 0.05 '.' 0.1 ' ' 1

```

Figure 12: Model-fitting

Probabilities of obtaining a Key Stage 3 English grade of 3, 4, 5, 6 or 7 from values of explanatory variables as shown. Code to obtain the predictions is not shown:

```

cbind(new,round(p,3))

##   gender sec ks2stand      3      4      5      6      7
## 1      0  1      -7 0.083 0.323 0.537 0.053 0.004
## 2      0  1       0 0.018 0.106 0.651 0.206 0.018
## 3      0  1       7 0.004 0.025 0.390 0.499 0.082
## 4      0  6     -7 0.162 0.432 0.378 0.026 0.002
## 5      0  6       0 0.039 0.195 0.647 0.111 0.009
## 6      0  6       7 0.008 0.052 0.547 0.353 0.040
## 7      1  1     -7 0.032 0.168 0.658 0.131 0.011
## 8      1  1       0 0.007 0.043 0.508 0.394 0.049
## 9      1  1       7 0.001 0.009 0.197 0.595 0.197
## 10     1  6     -7 0.066 0.282 0.580 0.067 0.005
## 11     1  6       0 0.014 0.086 0.629 0.247 0.023
## 12     1  6       7 0.003 0.020 0.337 0.537 0.103

```

Note that **round** rounds the variable (given first) to the given number of decimals (second).

Figure 13: Predictions for LSYPE English grade

```

unemp=read_csv("unemployment.csv")

## Parsed with column specification:
## cols(
##   spell = col_integer(),
##   event = col_integer(),
##   ui = col_integer(),
##   logwage = col_double(),
##   work_area = col_character()
## )

unemp

## # A tibble: 1,957 x 5
##   spell event    ui logwage work_area
##   <int> <int> <int>   <dbl> <chr>
## 1     1     1     0    6.41 mining
## 2     3     0     1    5.85 mining
## 3     2     1     0    6.57 mining
## 4     3     0     1    5.76 mining
## 5     2     0     1    5.38 mining
## 6     5     0     1    5.56 mining
## 7     7     0     1    6.11 mining
## 8     4     0     1    6.34 mining
## 9     3     0     1    5.99 mining
## 10    8     0     0    5.83 mining
## # ... with 1,947 more rows

```

Figure 14: Unemployment data (some)

```

y=with(unemp, Surv(spell, event))
y[1:20]

## [1] 1 3+ 2 3+ 2+ 5+ 7+ 4+ 3+ 8+ 2 13 11+ 12+ 1 17+ 4+
## [18] 7+ 7+ 5

```

Figure 15: Construction of response variable and display of first 20 values

```

y.1=coxph(y~ui+logwage+work_area,data=unemp)
summary(y.1)

## Call:
## coxph(formula = y ~ ui + logwage + work_area, data = unemp)
##
##      n= 1957, number of events= 658
##
##              coef exp(coef) se(coef)      z Pr(>|z|)
## ui             -0.99193   0.37086  0.08275 -11.987 < 2e-16 ***
## logwage         0.44326   1.55778  0.06979   6.352 2.13e-10 ***
## work_areafire    0.53674   1.71041  0.14922   3.597 0.000322 ***
## work_areamining  -0.13158   0.87671  0.21709  -0.606 0.544450
## work_areapubadmin -0.24263   0.78456  0.41874  -0.579 0.562301
## work_areaservices 0.34281   1.40889  0.11727   2.923 0.003465 **
## work_areatrade    0.18117   1.19861  0.11782   1.538 0.124133
## work_areatransp  -0.09024   0.91371  0.15395  -0.586 0.557740
## ---
## Signif. codes:  0 '***' 0.001 '**' 0.01 '*' 0.05 '.' 0.1 ' ' 1
##
##              exp(coef) exp(-coef) lower .95 upper .95
## ui                  0.3709      2.6964   0.3153   0.4362
## logwage             1.5578      0.6419   1.3586   1.7861
## work_areafire       1.7104      0.5847   1.2767   2.2915
## work_areamining     0.8767      1.1406   0.5729   1.3417
## work_areapubadmin   0.7846      1.2746   0.3453   1.7826
## work_areaservices   1.4089      0.7098   1.1196   1.7730
## work_areatrade      1.1986      0.8343   0.9515   1.5100
## work_areatransp     0.9137      1.0944   0.6757   1.2355
##
## Concordance= 0.697 (se = 0.014 )
## Rsquare= 0.09 (max possible= 0.99 )
## Likelihood ratio test= 184.1 on 8 df,  p=0
## Wald test              = 185 on 8 df,  p=0
## Score (logrank) test = 193.1 on 8 df,  p=0

drop1(y.1,test="Chisq")

## Single term deletions
##
## Model:
## y ~ ui + logwage + work_area
##              Df      AIC      LRT Pr(>Chi)
## <none>              8815.1
## ui                  1 8959.4 146.269 < 2.2e-16 ***
## logwage             1 8852.6  39.511 3.261e-10 ***
## work_area           6 8828.7  25.644 0.0002594 ***
## ---
## Signif. codes:  0 '***' 0.001 '**' 0.01 '*' 0.05 '.' 0.1 ' ' 1

```

Figure 16: Cox model

```

unemp %>% summarize(med=median(logwage))

## # A tibble: 1 x 1
##   med
##   <dbl>
## 1  5.69

work_areas = unemp %>% distinct(work_area) %>% pull(work_area)
work_areas

## [1] "mining" "constr" "transp" "trade" "fire" "services"
## [7] "pubadmin"

unemp_new=crossing(logwage=5.69,ui=1,work_area=work_areas)
unemp_new

## # A tibble: 7 x 3
##   logwage    ui work_area
##   <dbl> <dbl> <chr>
## 1  5.69  1.00 constr
## 2  5.69  1.00 fire
## 3  5.69  1.00 mining
## 4  5.69  1.00 pubadmin
## 5  5.69  1.00 services
## 6  5.69  1.00 trade
## 7  5.69  1.00 transp

s=survfit(y.1,unemp_new,data=unemp)

```

Figure 17: Predictions for job type

```

rods=read_csv("rod mold.csv")

## Parsed with column specification:
## cols(
##   temperature = col_integer(),
##   pressure = col_integer(),
##   batch = col_integer(),
##   extrusion_rate = col_double()
## )

rods = rods %>% mutate(pressure=factor(pressure),
                      temperature=factor(temperature))

rods

## # A tibble: 12 x 4
##   temperature pressure batch extrusion_rate
##   <fct>      <fct>    <int>      <dbl>
## 1 200        40        1        1.35
## 2 200        40        2        1.31
## 3 200        40        3        1.40
## 4 200        60        1        1.74
## 5 200        60        2        1.67
## 6 200        60        3        1.86
## 7 300        40        1        2.48
## 8 300        40        2        2.29
## 9 300        40        3        2.14
## 10 300       60        1        3.63
## 11 300       60        2        3.30
## 12 300       60        3        3.27

```

Figure 18: Rod extrusion data

```

extr.1=aov(extrusion_rate~temperature*pressure,data=rods)
summary(extr.1)

##               Df Sum Sq Mean Sq F value    Pr(>F)
## temperature     1  5.044    5.044  251.57 2.50e-07 ***
## pressure        1  1.687    1.687   84.17 1.61e-05 ***
## temperature:pressure  1  0.361    0.361   17.98 0.00284 **
## Residuals       8  0.160    0.020
## ---
## Signif. codes:  0 '***' 0.001 '**' 0.01 '*' 0.05 '.' 0.1 ' ' 1

```

Figure 19: Analysis of variance for rod extrusion data

Extrusion rate means for pressure and temperature combinations

```
rods %>% group_by(temperature,pressure) %>%
  summarize(m=mean(extrusion_rate))

## # A tibble: 4 x 3
## # Groups:   temperature [?]
##   temperature pressure     m
##   <fct>         <fct>   <dbl>
## 1 200           40       1.35
## 2 200           60       1.76
## 3 300           40       2.30
## 4 300           60       3.40
```

Tukey:

```
TukeyHSD(extr.1)

##   Tukey multiple comparisons of means
##     95% family-wise confidence level
##
## Fit: aov(formula = extrusion_rate ~ temperature * pressure, data = rods)
##
## $temperature
##           diff          lwr          upr p adj
## 300-200 1.296667 1.108147 1.485186 2e-07
##
## $pressure
##           diff          lwr          upr    p adj
## 60-40 0.75 0.5614803 0.9385197 1.61e-05
##
## $`temperature:pressure`
##           diff          lwr          upr    p adj
## 300:40-200:40 0.9500000 0.57976231 1.320238 0.0001661
## 200:60-200:40 0.4033333 0.03309564 0.773571 0.0334993
## 300:60-200:40 2.0466667 1.67642898 2.416904 0.0000005
## 200:60-300:40 -0.5466667 -0.91690436 -0.176429 0.0064699
## 300:60-300:40 1.0966667 0.72642898 1.466904 0.0000585
## 300:60-200:60 1.6433333 1.27309564 2.013571 0.0000028
```

Figure 20: Tukey for rod extrusion data

```

pval=function(x) {
  extr.2=aov(extrusion_rate~pressure,data=x)
  extr.3=glance(extr.2)
  extr.3$p.value
}
rods %>%
  group_by(temperature) %>%
  nest() %>%
  mutate(p_value=map_dbl(data,pval))

## # A tibble: 2 x 3
##   temperature data          p_value
##   <fct>         <list>         <dbl>
## 1 200          <tibble [6 x 3]> 0.00276
## 2 300          <tibble [6 x 3]> 0.00194

```

Figure 21: Further analysis of rod extrusion data


```
ggsurvplot(s,conf.int=F)
```




Figure 22: Plot of predictions for job type

```
ggplot(rods,aes(y=extrusion_rate,x=temperature,  
fill=pressure))+geom_boxplot()
```




Figure 23: Grouped boxplot for rod extrusion data

```

rods.mean = rods %>% group_by(temperature,pressure) %>%
  summarize(m=mean(extrusion_rate))
rods.mean

## # A tibble: 4 x 3
## # Groups:   temperature [?]
##   temperature pressure     m
##   <fct>         <fct>   <dbl>
## 1 200           40       1.35
## 2 200           60       1.76
## 3 300           40       2.30
## 4 300           60       3.40

ggplot(rods.mean,aes(y=m,x=temperature,colour=pressure,group=pressure))+
  geom_point()+geom_line()

```




Figure 24: Interaction plot for rod extrusion data