

Using Geofabrik and HOT Export

This guide may be downloaded as [Geofabrik and HOT Export en.odt](#) or [Geofabrik and HOT Export en.pdf](#)

Reviewed 2016-09-05

After learning how to add and edit data in OpenStreetMap (OSM), now maybe you would like to obtain the data as a backup or to process it using Geographic Information System software that is Open Source, such as Quantum GIS (www.qgis.org).

Getting OSM Data on Geofabrik Website

The OSM data can be obtained easily by downloading it from <http://download.geofabrik.de/openstreetmap/>

OpenStreetMap Data Extracts

New site layout - we've tried to make it so that any old saved links still work; do tell us if there's a problem!

Welcome to Geofabrik's free download server. This server has data extracts from the [OpenStreetMap project](#) which are normally updated every day. Select your continent and then your country of interest from the list below. (If you have been directed to this page from elsewhere and are not familiar with OpenStreetMap, we highly recommend that you read up on OSM before you use the data.) This download service is offered for free by Geofabrik GmbH.

Neue Webseiten-Struktur - Alle alten gespeicherten Links sollten aber trotzdem noch funktionieren.


Willkommen auf dem Geofabrik-Downloaddserver. Hier gibt es Daten-Auszüge aus dem [OpenStreetMap-Projekt](#), die normalerweise täglich aktualisiert werden. Wählen Sie aus dem Verzeichnis unten den Kontinent und ggf. das Land, für die Sie Daten benötigen. (Wenn Sie von anderswo auf dieser Seite gelandet sind und von OpenStreetMap nichts wissen, dann ist es empfehlenswert, sich mit dem Projekt vertraut zu machen, bevor Sie mit den Daten arbeiten.) Diese Downloads werden von der Geofabrik GmbH kostenlos angeboten.

Click on the region name to see the overview page for that region, or select one of the file extension links for quick access.

Sub-Region	.osm.pbf	Quick Links .shp.zip	.osm.bz2
Africa	[.osm.pbf]	X	[.osm.bz2]
Antarctica	[.osm.pbf]	[.shp.zip]	[.osm.bz2]
Asia	[.osm.pbf]	X	[.osm.bz2]
Australia and Oceania	[.osm.pbf]	X	[.osm.bz2]
Central America	[.osm.pbf]	X	[.osm.bz2]
Europe	[.osm.pbf]	X	[.osm.bz2]
North America	[.osm.pbf]	X	[.osm.bz2]
South America	[.osm.pbf]	X	[.osm.bz2]

[Technical details](#) about this download service.
[Old, CC-BY-SA licensed data](#) from before OpenStreetMap's license change.

GEOFABRIK[®]downloads



Not what you were looking for? Geofabrik is a consulting and software development firm based in Karlsruhe, Germany specializing in OpenStreetMap services. We're happy to help you with data preparation, processing, server setup and the like. [Check out our web site](#) and contact us if we can be of service.

Nicht das Richtige dabei? Die Geofabrik ist ein auf OpenStreetMap spezialisiertes Beratungs- und Softwareentwicklungsunternehmen in Karlsruhe. Gern helfen wir Ihnen bei der Datenaufbereitung, Datenkonvertierung, Serverinstallation und ähnlichen Aufgaben. [Besuchen Sie unsere Webseite](#) und sprechen Sie mit uns, wenn wir Ihnen helfen können.

Data/Maps Copyright 2013 [Geofabrik GmbH](#) and [OpenStreetMap Contributors](#) | [Map tiles](#) | [Creative Commons BY-SA 2.0 Data](#) | [ODBL 1.0](#) | [Contact](#)

The data is divided into several regions. Indonesia can be found as part of Asia by clicking on the Asia sub-region on the blue table, and then the page will appear like this.

Download OpenStreetMap data for this region:

Asia

[\[one level up\]](#)

Commonly Used Formats

- [asia-latest.osm.pbf](#), suitable for Osmium, Osmosis, imposm, osm2pgsql, mkgmap, and others. This file was last modified 8 hours ago and contains all OSM data up to 2013-08-18T19:48:02Z. File size: 2.3 GB; MD5 sum: 5b240124c6fe5f9c2c8096b13ce2bf90.

Other Formats and Auxiliary Files

- [asis:latest.osm.bz2](#), yields OSM XML which decompressed; use for programs that cannot process the .pbz format. This file was last modified 6 hours ago. File size: 3.6 GB; MD5 sum: 6291864d46f0144bec4b7b7706ad2a3fb.
[poly_file](#) that describes the extent of this region.
[.osm.gz files](#) that contain all changes in this region, suitable e.g. for Osmosis updates
[raw directory index](#) allowing you to see and download older files

Sub Regions

Click on the region name to see the overview page for that region, or select one of the file extension links for quick access.

Sub Region	Quick Links			
	.osm.pbf	.shp.zip	.osm.bz2	
Azerbaijan	[osm.pbf] (3.9 MB)	[shp.zip]	[osm.bz2]	
Bangladesh	[osm.pbf] (4.1 MB)	[shp.zip]	[osm.bz2]	
China	[osm.pbf] (104 MB)	[shp.zip]	[osm.bz2]	
GCC States	[osm.pbf] (30.1 MB)	[shp.zip]	[osm.bz2]	
India	[osm.pbf] (110 MB)	[shp.zip]	[osm.bz2]	
Indonesia	[osm.pbf] (89 MB)	[shp.zip]	[osm.bz2]	
Iran	[osm.pbf] (18.0 MB)	[shp.zip]	[osm.bz2]	
Iraq	[osm.pbf] (3.9 MB)	[shp.zip]	[osm.bz2]	
Israel and Palestine	[osm.pbf] (31.2 MB)	[shp.zip]	[osm.bz2]	
Japan	[osm.pbf] (857 MB)	[shp.zip]	[osm.bz2]	
Jordan	[osm.pbf] (4.5 MB)	[shp.zip]	[osm.bz2]	
Kazakhstan	[osm.pbf] (22.1 MB)	[shp.zip]	[osm.bz2]	



Not what you were looking for? Geofabrik is a consulting and software development firm based in Karlsruhe, Germany specializing in OpenStreetMap services. We're happy to help you with data preparation, processing, server setup and the like. [Check out our web site](#) and contact us if we can be of service.

🇩🇪 Nicht das Richtige dabei? Die Geofabrik ist ein auf OpenStreetMap spezialisiertes Beratungs- und Softwareentwicklungsunternehmen in Karlsruhe. Gern helfen wir Ihnen bei der Datenaufbereitung, Datenkonvertierung, Serverinstallation und ähnlichen Aufgaben. [Besuchen Sie unsere Webseite](#) und sprechen Sie mit uns, wenn wir Ihnen helfen können.

After appearing at the top of the page, see how the sub-region divides into countries of Asia. To get the data, you need to click the Indonesian state on the blue table, and it will appear like this.

[Download OpenStreetMap data for this region:](#)

Indonesia

[one level up]

Commonly Used Formats

- [Indonesia-latest.osm.pbf](#), suitable for Osmium, Osmosis, imposm, osm2pgsql, mkgmap, and others. This file was last modified 7 hours ago and contains all OSM data up to 2013-08-18T19:48:02Z. File size: 83 MB; MD5 sum: 9b13abafad7f1b665ef57cad6a31dd7.
- [Indonesia-latest.shp.zip](#), yields a number of ESRI compatible shape files when unzipped. This file was last modified 3 hours ago. File size: 147 MB.

Other Formats and Auxiliary Files


- **indonesia-testnet.com.bz2**, yields OSM XML when decompressed; use for programs that cannot process the .pbz format. This file has last modified 6 hours ago. File size: 150 MB; MD5 sum: 6a9480d4f8df00932109c676729b762d.
- **.poly file** that describes the extent of this region.
- **.osm file** that contains all changes in this region, suitable e.g. for Osmosis updates
- **extraction_index** allowing you to see and download older files

Sub Regions

No sub regions are defined for this region.



35 Not what you were looking for? Geofabrik is a consulting and software development firm based in Karlsruhe, Germany specializing in OpenStreetMap services. We're happy to help you with data preparation, processing, server setup and the like. [Check out our web site](#) and contact us if we can be of service.

 Nicht das Richtige dabei? Die Geofabrik ist ein auf OpenStreetMap spezialisiertes Beratungs- und Softwareentwicklungsunternehmen in Karlsruhe. Gern helfen wir Ihnen bei der Datenaufbereitung, Datenkonvertierung, Serverinstallation und ähnlichen Aufgaben. [Besuchen Sie unsere Webseite](#) und sprechen Sie mit uns, wenn wir Ihnen helfen können.

Then if you want to obtain the Indonesian data in shapefile (.shp) format, you click on the indonesia-latest.shp.zip link, and the file will be downloaded. There are several formats that can be downloaded. One popular format is shapefile (shp) with points, polyline, and polygon layer.

You can check the last time data was updated. Please note, the server usually updates the data once every 24 hours, so if you just upload data to OSM, the data does not appear automatically when you download it, but you have to wait for the latest updates from the server.

Getting OSM Data on HOT Export Tool Website

The [Humanitarian OpenStreetMap Team](https://openstreetmap.org/) (HOT) has created an online service that allows users to create custom OSM extracts anywhere in the world, by selecting an area of interest, map features and file formats. Within minutes, up-to-date OSM data is exported, filtered and converted. The following section will guide you on how to use the Export Tool. This information can also be found through the '[Learn](#)' section at export.hotosm.org.




QuickStart


Anyone can create a custom OpenStreetMap export with the Export Tool - just register an account. You can register with an OpenStreetMap account from openstreetmap.org, and a valid email address, which will be used to send a link to your export once it is complete.

Identify Area of Interest

There are multiple ways an Area of Interest (AOI) can be selected through the Export Tool. This includes the ability to type and search, specify the coordinates of a bounding box, draw a bounding box, free draw a polygon, use the current view or upload a geojson file.





Once you are 'Logged In' to the HOT Export Tool, the 'Create' tab will become available. The 'Create' tab is where you will set up your export, by describing it on the left hand side and selecting your AOI with the map on the right hand side.





Search Bar

There are 6 ways to define an AOI for your export. The first and second use the search bar, which can either find a place by typing in its name and selecting it from the options below, or by defining the bounding box coordinates. The minimum X, minimum Y, maximum X and maximum Y (West, South, East, North) coordinates of a country can be found [in a CSV list provided by the Humanitarian Data Exchange \(HDX\)](#).





Digitise

The third and fourth way that an AOI can be selected in the Export Tool, is by either drawing a bounding box by selecting the 'Box' option from the column of tools on the right of the screen. Or you can free draw a polygon directly on the map by selecting the 'Draw' tool.




Upload Polygon

The last two ways in which an AOI can be selected is through the 'This View' tool on the right hand side of the map, which captures the extent of the map's current view, or by the 'Import' tool which enables you to upload a polygon of the area.




The imported polygon must be a GeoJSON file in WGS84 geographic coordinates. One of the ways to create a GeoJSON file is to use the geojson.io site. Once the area has been selected in geojson.io, copy the text in the box to the right, paste it into an editor of choice, such as [Atom](#) and save your GeoJSON file.




The GeoJSON file needs to be edited slightly in order for it to be accepted by the Export Tool. Please note that the file can not be multipolygons. In the simplest form the file only needs to state that it is a “type: Polygon” and list the coordinates of the points/nodes that identify the area.

The GeoJSON file will then successfully be parsed by the tool and used to specify the AOI.




```
1 {
2   "type": "Polygon",
3   "coordinates": [
4     [
5       -68.016357421875,
6       18.161510984517324
7     ],
8     [
9       -68.02734375,
10      17.85851867611397
11     ],
12     [
13       -67.43408203124999,
14       17.821915515968854
15     ],
16     [
17       -67.0220947265625,
18       17.712060974461494
19     ],
20     [
21       -66.6925048828125,
22       17.769612247142653
23     ],
24     [
25       -66.368408203125,
26       17.748686651728807
27     ],
28     [
29       -65.8245849609375,
30       17.8747024306575
31     ]
32   ]
33 }
```



Select File Formats

The tool allows OSM data to be extracted through the Overpass API in its native Protocol Buffer Binary (PBF) file format, before filtering the data for the map features and associated tags specified by the user. Once the data has been filtered it is then converted into the file formats chosen by the user.






Currently the tool can convert OSM data into Shapefile .shp, GeoPackage .gpkg, Garmin .img, Google Earth .kml, OSM .pbf, MAPS.ME .mwm, OsmAnd .obf, and MBTiles .mbtiles. At least one of the file formats must be selected to create the export, but there is no restriction as to how many can be chosen, which can be done by ticking multiple boxes.



The screenshot shows the 'HOT EXPORT TOOL' interface. At the top, there's a red 'HOT' logo and the text 'EXPORT TOOL'. Below this is a navigation bar with four tabs: '1 Describe', '2 Formats', '3 Data', and '4 Summary'. The '2 Formats' tab is currently selected. Under the 'File Formats' section, there's a link to 'Learn (Export Formats)' for details. Below this, there's a list of file formats with checkboxes and their respective extensions: Shapefile (.shp), GeoPackage (.gpkg), Garmin (.img), Google Earth (.kml), OSM (.pbf), MAPS.ME (.mwm), OsmAnd (.obf), and MBTiles (.mbtiles). The 'Shapefile (.shp)' checkbox is checked.

Shapefile .shp

Shapefiles are a tabular format developed by Esri. They are the most popular file format for GIS data. A shapefile is actually 3-4 individual files, commonly bundled together as a ZIP archive. Shapefiles do have certain limitations, such as the file size, capping at 2 gigabytes (GB) and a column name length limit of 10 characters. Read more about [Shapefiles .shp](#) in the Learn section.

Name
 3.3_train_station_ALL_point.dbf
 3.3_train_station_ALL_point.prj
 3.3_train_station_ALL_point.qpj
 3.3_train_station_ALL_point.shp
 3.3_train_station_ALL_point.shx

Geopackage .gpkg

OGC Geopackages store geospatial data in a single SQLite database. Geopackages are very similar to Spatialite-enabled SQLite databases. They should be usable in most major GIS applications. Geopackages support practically unlimited file sizes and numbers of columns in tables, and have full support for Unicode. They are especially ideal if you need to run SQL queries over the data. Read more about [Geopackages.gpkg](#) in the Learn section.



Garmin .img

A .IMG file contains all information needed to render a map onto a Garmin GPS mobile device. Please note that the cartographic .img style and feature choices of the map are not dependent on the feature selection submitted to the Export Tool - instead, a default style based on all OSM data is used. Read more about [Garmin .img](#) in the Learn section.



Google Earth .kml

The Keyhole Markup Language (KML) is an XML-based format for modeling points, lines, polygons and associated attributes geographically. Google Earth is the most widely known earth view browsing platform using KML, which is also the reason why it was developed. Read more about [Google Earth .kml](#) in the Learn section.



OSM .pbf

The canonical data format of OSM is an XML document of nodes, ways and relations. The Protocol Buffer Binary Format (PBF) is an optimised representation of OSM XML, which is smaller on disk and faster to read. This format is only compatible with OSM specific tools, such as OSM editing software. Each .PBF provided by the export tool should be referentially complete - that is, any node, way or relation referenced by a way or relation will appear in the PBF. Learn more about [OSM.pbf](#) in the Learn section.

```
<?xml version="1.0" encoding="UTF-8"?>
<osm version="0.6" generator="CGImap 0.0.2">
  <bounds minlat="54.0889580" minlon="12.2487570" maxlat="54.0913900" maxlon="12.2524800"/>
  <node id="298884269" lat="54.0901746" lon="12.2482632" user="SvenHRO" uid="46882" visible="true"
version="1" changeset="676636" timestamp="2008-09-21T21:37:45Z"/>
  <node id="261728686" lat="54.0906309" lon="12.2441924" user="PikoWinter" uid="36744" visible="true"
version="1" changeset="323878" timestamp="2008-05-03T13:39:23Z"/>
  <node id="1831881213" version="1" changeset="12370172" lat="54.0900666" lon="12.2539381"
user="lafkor" uid="75625" visible="true" timestamp="2012-07-20T09:43:19Z">
    <tag k="name" v="Neu Broderstorf"/>
    <tag k="traffic_sign" v="city_limit"/>
  </node>
  ...
  <node id="298884272" lat="54.0901447" lon="12.2516513" user="SvenHRO" uid="46882" visible="true"
version="1" changeset="676636" timestamp="2008-09-21T21:37:45Z"/>
  <way id="26659127" user="Masch" uid="55988" visible="true" version="5" changeset="4142606"
timestamp="2010-03-16T11:47:08Z">
    <nd ref="292403538"/>
    <nd ref="298884289"/>
    ...
    <nd ref="261728686"/>
    <tag k="highway" v="unclassified"/>
    <tag k="name" v="Pastower Straße"/>
  </way>
```


MAPS.ME .mwm

Maps.me is a GPS Navigation and map application for Android and iOS smartphones and tablets, notably supporting offline mapping and navigation. Read more about [MAPS.ME .mwm](#) in the Learn section. To use a custom export with Maps.me on Android, please follow these steps: Open Maps.me and navigate to your region of interest Accept Maps.me's prompt and download the offered region Force close Maps.me Create an MWM export Download the export, unzip it, and copy the .mwm file to your device Using the Android File Manager, navigate to the location containing the .mwm file Long-press to select it and touch the "copy" or "cut" button Navigate to "MapsWithMe" and open the highest numbered folder (e.g. 170917) Copy/move your .mwm file into this directory by tapping the "paste" button Delete the existing .mwm file for your region of interest, taking note of its filename Rename your .mwm file to match the region that was downloaded by Maps.me (which you just deleted) by long-pressing (to select) and tapping the "more" button (3 vertical dots) Open Maps.me



OsmAnd .obf

OsmAnd is also a GPS Navigation and map application for Android and iOS smartphones, as well as tablets, notably supporting offline rendering, routing, and searching. Read more about the application and its numerous features of [OsmAnd .obf](#) from their main website.



MBTiles .mbtiles

MBTiles is a file format for storing map tiles in a single file. The Export Tool allows users to create MBTiles containing tiles from OSM, which can be used as sources of offline context within applications that support them. Please note that MBTiles will extract all the OSM features in the selected area of interest through the Export Tool, with the '3 Data' tab automatically switching to a dropdown source option and zoom range, in place of the standard tree tag and YAML feature selection option. Read more about [MBTiles .mbtiles](#) in the Learn section.



Additional file formats are continuously being suggested and added to the Export Tool. If there is a file format that you would like to see added in the future, please make a comment on the [GitHub](#) repository. For further detailed information regarding each file format type, please visit the 'File Formats' page in the '[Learn](#)' section on the tool website.

Customise Map Features

The tool allows the user to customise the data selected within the defined area of interest. The OSM data is defined by using tag filters and key selections, with the Tag Tree or YAML Form. The Tag Tree is for common use cases, presenting a curated set of filters and selections, where the YAML configuration provides complete control over filters and selections, using a SQL-like

filter definition.

The screenshot shows the HOT Export Tool interface. At the top, there is a red 'HOT' logo and the text 'EXPORT TOOL'. Below this, there are four tabs: '1 Describe', '2 Formats', '3 Data', and '4 Summary'. The '2 Formats' tab is active, and within it, the 'Tag Tree' option is selected and circled in orange. Below the tabs, there is a search bar with the placeholder text 'Search for a feature type...' and a 'Clear' button. A list of feature types is displayed, each with a checkbox and a right-pointing arrow: Buildings, Commercial, Communication, Education, Emergency, Financial, Government, Healthcare, Humanitarian, Land Use, Localities, and Natural. A tooltip box is visible over the 'Commercial' checkbox, containing the text 'Hover over a checkbox to see its definition.' Below the list, there is a 'Feature Selection' section with a text area containing the following YAML code:

```
buildings:
  types:
    - lines
    - polygons
  select:
    - name
    - building
  where: building IS NOT NULL
```

Below the text area, there is a button labeled 'Load from JOSM Preset .XML' and a blue 'Next' button.

OSM is an open global database of tagged geographic features, with three types of elements: Nodes, which represent a point on the surface of the earth Ways, which are sets of nodes that can form lines or polygons Relations, which are sets of nodes, ways or other relations

Each of these elements can have any number of key=value tags. For example, a post office may be represented by a way with the tags building=yes and amenity=post_office. Lets see how these tags can be defined in the Export Tool using the Tag Tree and YAML Form to filter OSM data.

Tag Tree

The Tag Tree is the simplest way to get started selecting features, simply by ticking the desired parent or child checkboxes. Please note that selecting a parent checkbox will add additional key=value tags associated to the theme, as well as the child checkboxes below it. Each parent checkbox has a different query to filter data, so it is highly recommended that the syntax for each theme is explored by hovering over the checkbox, which will provide an info box to the right.

[1 Describe](#) [2 Formats](#) [3 Data](#) [4 Summary](#)

Tag Tree

YAML

> ☐ Buildings

> ☐ Commercial

> ☐ Communication

> ☐ Education

> ☒ Emergency

☒ Police Station

☒ Ambulance Station

☒ Fire Station

> ☐ Financial

> ☐ Government

> ☐ Healthcare

> ☐ Humanitarian

Emergency
Geometry types: point, polygon
Keys:

- name
- amenity
- building
- emergency

Where: emergency IS NOT NULL
OR amenity IN ('police','fire_station')

For example selecting the 'Emergency' parent checkbox, will automatically select the 'Police Station', 'Ambulance Station' and 'Fire Station' child checkboxes below it, yet in addition to this it will also select all tags where emergency=yes, amenity=police and amenity=fire_station in the following SQL query:

```
emergency IS NOT NULL OR amenity IN ('police','fire_station')
```

The parent checkboxes do not always represent what is available as children below, to try and account for all possible tags associated with a theme. OSM tags are continuously evolving and we want to ensure that the tool can adapt to these changes. Only the most commonly used key=value tags are represented as child checkboxes, and the parent checkboxes are used to try and encompass those not used as frequently, but fall within a theme. If you have suggestions for modifications to these themes and tags, please comment on the [spreadsheet](#) used to populate the Tag Tree, and we will try to incorporate it where appropriate.

	A	B	C	D	E	
1	Category	Checkbox Name	Parent	Additional Search Term	Geom Types	Key Selections (exported)
2	Buildings	Buildings	yes			
3	Buildings	Building Names and Geometries			point, polygon	name, building
4	Buildings	Addresses			point, polygon	addr:housenumber,addr:street
5	Buildings	Materials and Condition			polygon	building:material,roof:material
6	Commercial	Commercial	yes			
7	Commercial	Shop			point, polygon	name, opening_hours, shop:amenity
8	Commercial	Supermarket			point, polygon	name, opening_hours, shop:amenity
9	Commercial	Restaurant			point, polygon	name, amenity
10	Commercial	Tourism			point, polygon	name, tourism
11	Commercial	Accommodation		hotel,hostel,motel	point, polygon	name, tourism, rooms, beds
12	Communication	Communication	yes			
13	Communication	Communication Office			point, polygon	name, office
14	Communication	Communication Tower		tower	point, polygon	name, man_made, tower, communication
15	Education	Education	yes			
16	Education	Kindergarten			point, polygon	name, amenity, isced:level
17	Education	School			point, polygon	name, amenity, isced:level
18	Education	College			point, polygon	name, amenity, isced:level
19	Education	University			point, polygon	name, amenity, isced:level
20	Emergency	Emergency	yes			
21	Emergency	Police Station			point, polygon	name, amenity, building
22	Emergency	Ambulance Station			point, polygon	name, amenity

YAML Form

Using a YAML configuration provides complete control over applying filters to the OSM data, by using a SQL-like filter definition to apply key=value tags. Please note that the Tag Tree also generates syntax on the YAML Form, so any parent and child checkboxes selected will automatically be applied in the YAML box. This acts as a starting point for the query which can be further edited.

1 Describe
2 Formats
3 Data
4 Summary

Tag Tree
YAML

Feature Selection

```

planet_osm_point:
  types:
    - points
  select:
    - amenity
    - building
    - emergency
    - name
  where:
    - 'emergency IS NOT NULL OR amenity IN

```

Load from JOSM Preset .XML
Next

The use of YAML was chosen due to its simplicity and compatibility with SQL. The YAML feature selection format is similar to style files used by programs such as osm2pgsql and imposm. It is whitespace sensitive, with each child element indented below its parent element, and preceded by a dash. This dash must have a space after it. Here is a basic example of a feature selection with 3 themes, buildings, waterways and hospitals:

```
buildings:
  types:
    - polygons
  select:
    - name
    - building
  where: building IS NOT NULL
waterways:
  types:
    - lines
    - polygons
  select:
    - name
    - waterway
  where: natural IN ('waterway')
hospitals:
  select:
    - name
    - amenity
  where: amenity = "hospital"
```

YAML has Themes, and two data structures, Mapping and Lists Theme in the above example is: buildings Mappings in the above example are: types and select Lists in the above example are: child elements of select and types

YAML: Themes Themes are the top level keys in the YAML document, with valid characters including letters, numbers and underscores.

YAML: Geometry Types The list values under the mapping types can be one or more of ‘- points’, ‘- lines’, ‘- polygons’. If the types key is omitted, all three geometry types will be included in the theme.

YAML: Column Selections List items under the mapping select key determines the columns for each theme. The following example will populate the ‘name’ and ‘amenity’ columns with their values from OSM:

```
select:
  - name
  - amenity
```

YAML: Filters Filters are under the where: key in each theme. They define what subset of OSM features belongs to that theme. The following example will filter the theme to only features

where the key natural has the value waterway:

```
where: natural IN ('waterway')
```

Please note It is almost always necessary to have some kind of filtering, otherwise the theme will simply include all OSM features for the given geometry types. A filter is specified using SQL-like syntax, with valid keywords IS NOT NULL, AND, OR, IN, =, !=.

```
where: natural = 'waterway'  
      where: 'addr:housenumber' IS NOT NULL  
      where: natural IN ('waterway', 'riverbank')
```

JOSM Presets Older versions of the Export Tool used JOSM Preset .XML files to define feature selections. The new version uses YAML as it is more flexible in how it transforms OSM data. The new Export Tool, however can help convert JOSM presets into YAML configurations, by selecting the 'Load from JOSM Preset .XML' button. Please note If the preset is more complex, it may need to be written as a new YAML configuration based on the 'item' elements contained in the XML.

1 Describe

2 Formats

3 Data

4 Summary

Tag Tree

YAML

Feature Selection

```
planet_osm_point:  
  types:  
    - points  
  select:  
    - amenity  
    - building  
    - emergency  
    - name  
  where:  
    - 'emergency IS NOT NULL OR amenity IN
```

Load from JOSM Preset .XML

Next

export-tool-load-preset

Configurations

YAML configurations can be defined and saved for future use through the ‘Configs’ page. It’s useful to create one configuration for a project, which can then be used on all exports related to that project. Give the configuration a ‘name’ and ‘description’ that will make it discoverable by other users. Unchecking the ‘Public’ checkbox will make the configuration visible to only the user.

Configurations

Create New Configuration

☐ Show all Configurations

Search

NAME	DESCRIPTION	TABLES	OWNER
HDX Configuration	YAML configuration used by the Humanitarian Data Exchange (HDX) to filter OSM datasets		mataharimhairi

Name

Description

Feature Selection

```
Buildings:
  hdx:
    tags: building, shelter, osm, openstreetmap
  caveats:
  types:
    - polygons
  select:
    - name
    - building
    - building:levels
    - building:materials
    - addr:full
```

Publish this Configuration

Please note that configurations can be edited, which is useful for evolving a feature selection during the course of a project. Saved YAML configurations can be selected via the ‘Stored Configuration’ option on the ‘3 Data’ tab when creating an export. Use the Search bar to find configurations related to your project.

HOT

EXPORT TOOL

A

1 Describe2 Formats3 Data4 Summary

Tag Tree

Configs

YAML

Name or description

Show all Configurations

Search

NAME	DESCRIPTION	
GED4ALL Complete	YAML configuration for the Global Exposure Database for All project to filter OSM datasets	Load YAML
GED4ALL Simplified	YAML configuration for the Global Exposure Database for All project to filter OSM datasets	Load YAML
HDX Configuration	YAML configuration used by the Humanitarian Data Exchange (HDX) to filter OSM datasets	Load YAML
PDC InAWARE 1.1 Bank	YAML configuration for the Pacific Disaster Centre InAWARE project to filter OSM bank data	Load YAML
PDC InAWARE 1.1 Bank	YAML configuration for the Pacific Disaster Centre InAWARE project to filter OSM bank data	Load YAML

For further detailed information regarding feature selections and YAML, please visit the ‘Selecting Features’ and ‘YAML Specification’ in the ‘[Learn](#)’ section on the tool website.