GAIDA - Voice / Acoustic Validation (Section C)

Clip labeling log for the voice-scoring pipeline

AI-based Anxiety Detection System · College Guidance · University of the East

Purpose. GAIDA's voice pipeline extracts prosody features (pitch, energy, jitter/shimmer, speech rate, pauses) and maps them to an emotion and a severity. Its real-world accuracy has never been measured against human-labeled audio - this log is how it is closed.

Status. As of this printing, no labeled audio clips exist yet (audio_samples/ is empty). This sheet documents the protocol and the worked-example format only; it becomes a live validation dataset after clips are collected and labeled.

Protocol. Have consenting volunteers read a small script while intentionally calm / anxious / sad / angry / neutral - the same words with different delivery, so the only difference is prosody. A phone recording is fine. **Target:** at least 10 clips per emotion (50 total).

How to label. For each clip, name the file and record the emotion it genuinely expresses and the distress severity you judge.

- **Emotion** - one of: anxious, sad, angry, calm, neutral
- **Severity** - one of: Normal, Low, Moderate, High (voice alone can never reach Crisis).
- The five shaded rows are worked examples of the format.

Filename	Emotion	Severity	Note
audio_samples/calm_01.wav	calm	Normal	Student describing a normal day at school
audio_samples/anxious_01.wav	anxious	Moderate	Trembling voice and fast speech
audio_samples/sad_01.wav	sad	Moderate	Slow monotone describing a breakup (text routing sends breakup to the loss protocol; this row only illustrates a sad delivery)
audio_samples/angry_01.wav	angry	Low	Angry rant about a group project (activating; Low distress)
audio_samples/neutral_01.wav	neutral	Normal	Neutral reading of a safe-phrase test

Filename	Emotion	Severity	Note

Rater name: _____ Date: _____

Signature: _____ Clips labeled: _____