

Introduction to SMTP

RES, Lecture 4

Olivier Liechti



HAUTE ÉCOLE
D'INGÉNIERIE ET DE GESTION
DU CANTON DE VAUD

www.heig-vd.ch

Warning 1

The slides and the webcasts contain examples and demos with **real SMTP servers**.

The behaviour of these servers may change over time. It may also change depending on the network you are connected to (internal, ISP, other ISP).

The main reason why a server might behave differently is the fight between mail administrators and **spammers**.

Warning 2

It is a good thing to experiment with real SMTP servers.

But remember that they are real servers and act responsibly.

Please avoid launching a **surprise denial of service attack** with your accidental infinite loop.

13



Labo SMTP, part 1

Olivier Liechti

14



Labo SMTP, part 2

Olivier Liechti

15



Labo SMTP, part 3

Olivier Liechti

16



Labo SMTP, part 4

Olivier Liechti

- SMTP demo & hints
- SMTP protocol
- Mock server
- Implementation walk-through

Lecture	Lab A	Lab B
01.04 SMTP	01.04 Labo SMTP	04.04 Labo SMTP
08.04 Labo SMTP	08.04 Labo SMTP	11.04 Labo SMTP
15.04 Travail écrit Tout, y compris SMTP	15.04 Labo SMTP Demos "option standard"	18.04 Labo SMTP Demos "option standard"

Démonstration (5 minutes MAX)	
Le labo est terminé et la démonstration est faite au plus tard la semaine du 15 avril.	1 pt
Le groupe arrive à démarrer un serveur mock dans un container Docker et à expliquer à quoi il sert. Le groupe a aussi configuré le service mailtrap.io	1 pt
Le groupe montre comment configurer la campagne de “pranks” et lance son programme dans un environnement de test (mock mock, mailtrap ou autre). Le groupe explique les résultats.	2 pt
Le groupe montre son repo GitHub. En regardant les commits, on voit que tout le monde a participé et qu’il n’y a pas seulement un gros commit à la fin.	1 pt
Une documentation de qualité et conforme aux exigences est fournie dans le repo GitHub.	2 pt



What happens when Bob wants
to **send an e-mail** to Alice?



Bob uses **Thunderbird** to write his mail.



Alice uses **MS Outlook** to check and read her mails.



In the technical specs (RFCs), these programs are called **Mail User Agents (MUA)**






Bob uses his professional e-mail address. His company runs a **MS Exchange Server**.



heig-vd



Alice uses her private address. She has an account (and a **mailbox**) on the **Google gmail** infrastructure.






Bob writes a message to “**alice.res@gmail.com**”. He pushes on the “Send” button.

The Exchange Server is made of **2 logical components**: the **MSA** and the **MTA**.

Bob's MUA asks Bob's MSA to deliver the mail. It uses the **SMTP** protocol for that purpose and (should) use TCP port 587.

After enforcing **usage policies**, the MSA delegates the work to the MTA. We don't know how.






Mail Transfer
Agent (MTA)



Mail Transfer
Agent (MTA)

TCP/25

DNS




Bob's MTA initially does not know where to forward the mail...

It issues a **DNS** query to get a list of **MX records** for Alice's domain (gmail.com).

When Bob's MTA knows the IP address of Alice's MTA, it uses the **SMTP** protocol once more to forward the message. **TCP port 25** is used in this case.

When Alice's MTA receives the mail, it stores it in Alice's **mailbox** (for later retrieval).

dig



```
admin — less * man dig — 120x30
DIG(1)                                BIND9                                DIG(1)

NAME
    dig - DNS lookup utility

SYNOPSIS
    dig [@server] [-b address] [-c class] [-f filename] [-k filename] [-m] [-p port#] [-q name] [-t type]
    [-x addr] [-y [hmac:]name:key] [-4] [-6] [name] [type] [class] [queryopt...]

    dig [-h]

    dig [global-queryopt...] [query...]

DESCRIPTION
    dig (domain information groper) is a flexible tool for interrogating DNS name servers. It performs
    DNS lookups and displays the answers that are returned from the name server(s) that were queried.
    Most DNS administrators use dig to troubleshoot DNS problems because of its flexibility, ease of use
    and clarity of output. Other lookup tools tend to have less functionality than dig.


    Although dig is normally used with command-line arguments, it also has a batch mode of operation for
    reading lookup requests from a file. A brief summary of its command-line arguments and options is
    printed when the -h option is given. Unlike earlier versions, the BIND 9 implementation of dig allows
    multiple lookups to be issued from the command line.

    Unless it is told to query a specific name server, dig will try each of the servers listed in
    /etc/resolv.conf.

    When no command line arguments or options are given, dig will perform an NS query for "." (the root).
```

nslookup is another command for querying DNS

dig -t ANY heig-vd.ch



```
$ dig -t ANY heig-vd.ch

; <<>> DiG 9.8.3-P1 <<>> -t ANY heig-vd.ch
;; global options: +cmd
;; Got answer:
;; ->>HEADER<<- opcode: QUERY, status: NOERROR, id: 62138
;; flags: qr aa rd ra; QUERY: 1, ANSWER: 9, AUTHORITY: 0, ADDITIONAL: 0

;; QUESTION SECTION:
;heig-vd.ch.                IN      ANY

;; ANSWER SECTION:
heig-vd.ch.                3600    IN      NS      ns01.heig-vd.ch.
heig-vd.ch.                3600    IN      NS      ns02.heig-vd.ch.
heig-vd.ch.                3600    IN      A       193.134.220.23
heig-vd.ch.                3600    IN      TXT     "MS=ms50694826"
heig-vd.ch.                3600    IN      TXT     "v=spf1 ip4:193.134.216.180/30 mx ~all"
heig-vd.ch.                3600    IN      MX      10 mailcl2.heig-vd.ch.
heig-vd.ch.                3600    IN      MX      10 mailcl1.heig-vd.ch.
heig-vd.ch.                3600    IN      MX      10 mailcl0.heig-vd.ch.
heig-vd.ch.                3600    IN      SOA     ns01.heig-vd.ch. domain.heig-vd.ch. 2014141923 10800 3600 2419200 900

;; Query time: 2 msec
;; SERVER: 10.192.22.5#53(10.192.22.5)
;; WHEN: Tue Apr  5 13:20:45 2016
;; MSG SIZE  rcvd: 273

$
```

MX records point to the SMTP servers for the domain



SMTP
587




In the last step, Alice's MUA uses another protocol (e.g. IMAP, POP3) to fetch mails from the mailbox.

SMTP
25




IMAP/POP3





Let's be human Exchange Servers
(and play the role of Bob's MTA).

But instead of forwarding the mail
to gmail, let's forward the mail via
the **HEIG-VD's SMTP** server.



```
dig -t MX heig-VD.ch  
heig-VD.ch. 600 IN MX 10 mail01.heig-VD.ch.
```

```
telnet mail01.heig-VD.ch 25
```

```
openssl s_client -starttls smtp -crlf -connect  
mail01.heig-VD.ch:25 (or use 465)
```

```
EHLO mycompany.com
```



```
$ telnet mailcl10.heig-vd.ch 25
mailcl10.heig-vd.ch: nodename nor servname provided, or not known
$ telnet mailcl0.heig-vd.ch 25
Trying 193.134.216.181...
Connected to mailcl0.heig-vd.ch.
Escape character is '^]'.
220 heig-vd.ch ESMTP MailCleaner (Enterprise Edition 2016.01) Tue, 05 Apr 2016 14:18:24
+0200
EHLO mycompany.com
250-heig-vd.ch Hello mbp-de-admin.einet.ad.eivd.ch [10.192.116.92]
250-SIZE 20480000
250-8BITMIME
250-PIPELINING
250-AUTH PLAIN LOGIN
250-STARTTLS
250 HELP
MAIL FROM: bob@bob.com
250 OK
RCPT TO: olivier.liechti@wasabi-tech.com
250 Accepted
DATA
354 Enter message, ending with "." on a line by itself
From: bob@areyousure.com
To: olivier.liechti@wasabi-tech.com
Subject: demo

Ok. Cool. Bye.
.
250 OK id=1anPx9-0003KC-BC
quit
221 heig-vd.ch closing connection
Connection closed by foreign host.
```

SMTP command
!=
Message header

<https://tools.ietf.org/html/rfc5321>

Table of Contents

RFC 5321

SMTP

October 2008

1.	Introduction	5	3.9.2.	List	31
1.1.	Transport of Electronic Mail	5	4.	The SMTP Specifications	32
1.2.	History and Context for This Document	5	4.1.	SMTP Commands	32
1.3.	Document Conventions	6	4.1.1.	Command Semantics and Syntax	32
2.	The SMTP Model	7	4.1.2.	Command Argument Syntax	41
2.1.	Basic Structure	7	4.1.3.	Address Literals	43
2.2.	The Extension Model	9	4.1.4.	Order of Commands	44
2.2.1.	Background	9	4.1.5.	Private-Use Commands	46
2.2.2.	Definition and Registration of Extensions	10	4.2.	SMTP Replies	46
2.2.3.	Special Issues with Extensions	11	4.2.1.	Reply Code Severities and Theory	40
2.3.	SMTP Terminology	11	4.2.2.	Reply Codes by Function Groups	50
2.3.1.	Mail Objects	11	4.2.3.	Reply Codes in Numeric Order	52
2.3.2.	Senders and Receivers	12	4.2.4.	Reply Code 502	53
2.3.3.	Mail Agents and Message Stores	12	4.2.5.	Reply Codes after DATA and the Subsequent <CRLF>.<CRLF>	53
2.3.4.	Host	13	4.3.	Sequencing of Commands and Replies	54
2.3.5.	Domain Names	13	4.3.1.	Sequencing Overview	54
2.3.6.	Buffer and State Table	14	4.3.2.	Command-Reply Sequences	55
2.3.7.	Commands and Replies	14	4.4.	Trace Information	57
2.3.8.	Lines	14	4.5.	Additional Implementation Issues	61
2.3.9.	Message Content and Mail Data	15	4.5.1.	Minimum Implementation	61
2.3.10.	Originator, Delivery, Relay, and Gateway Systems	15	4.5.2.	Transparency	62
2.3.11.	Mailbox and Address	15	4.5.3.	Sizes and Timeouts	62
2.4.	General Syntax Principles and Transaction Model	16	4.5.3.1.	Size Limits and Minimums	62
3.	The SMTP Procedures: An Overview	17	4.5.3.1.1.	Local-part	63
3.1.	Session Initiation	18	4.5.3.1.2.	Domain	63
3.2.	Client Initiation	18	4.5.3.1.3.	Path	63
3.3.	Mail Transactions	19	4.5.3.1.4.	Command Line	63
3.4.	Forwarding for Address Correction or Updating	21	4.5.3.1.5.	Reply Line	63
3.5.	Commands for Debugging Addresses	22	4.5.3.1.6.	Text Line	63
3.5.1.	Overview	22	4.5.3.1.7.	Message Content	63
3.5.2.	VRFY Normal Response	24	4.5.3.1.8.	Recipients Buffer	64
3.5.3.	Meaning of VRFY or EXPN Success Response	25	4.5.3.1.9.	Treatment When Limits Exceeded	64
3.5.4.	Semantics and Applications of EXPN	26	4.5.3.1.10.	Too Many Recipients Code	64
3.6.	Relaying and Mail Routing	26	4.5.3.2.	Timeouts	65
3.6.1.	Source Routes and Relaying	26	4.5.3.2.1.	Initial 220 Message: 5 Minutes	65
3.6.2.	Mail eXchange Records and Relaying	26	4.5.3.2.2.	MAIL Command: 5 Minutes	65
3.6.3.	Message Submission Servers as Relays	27	4.5.3.2.3.	RCPT Command: 5 Minutes	65
3.7.	Mail Gatewaying	28	4.5.3.2.4.	DATA Initiation: 2 Minutes	66
3.7.1.	Header Fields in Gatewaying	28	4.5.3.2.5.	Data Block: 3 Minutes	66
3.7.2.	Received Lines in Gatewaying	29	4.5.3.2.6.	DATA Termination: 10 Minutes	66
3.7.3.	Addresses in Gatewaying	29	4.5.3.2.7.	Server Timeout: 5 Minutes	66
3.7.4.	Other Header Fields in Gatewaying	29	4.5.4.	Retry Strategies	66
3.7.5.	Envelopes in Gatewaying	30	4.5.5.	Messages with a Null Reverse-Path	60
3.8.	Terminating Sessions and Connections	30	5.	Address Resolution and Mail Handling	69
3.9.	Mailing Lists and Aliases	31	5.1.	Locating the Target Host	69
3.9.1.	Alias	31	5.2.	IPv6 and MX Records	71
			6.	Problem Detection and Handling	71

<https://tools.ietf.org/html/rfc5321>

D.1. A Typical SMTP Transaction Scenario

This SMTP example shows mail sent by Smith at host bar.com, and to Jones, Green, and Brown at host foo.com. Here we assume that host bar.com contacts host foo.com directly. The mail is accepted for Jones and Brown. Green does not have a mailbox at host foo.com.


```
S: 220 foo.com Simple Mail Transfer Service Ready
C: EHLO bar.com
S: 250-foo.com greets bar.com
S: 250-8BITMIME
S: 250-SIZE
S: 250-DSN
S: 250 HELP
C: MAIL FROM:<Smith@bar.com>
S: 250 OK
C: RCPT TO:<Jones@foo.com>
S: 250 OK
C: RCPT TO:<Green@foo.com>
S: 550 No such user here
C: RCPT TO:<Brown@foo.com>
S: 250 OK
C: DATA
S: 354 Start mail input; end with <CRLF>.<CRLF>
C: Blah blah blah...
C: ...etc. etc. etc.
C: .
S: 250 OK
C: QUIT
S: 221 foo.com Service closing transmission channel
```

Mon site | Mes liens ▾ | Bienvenue LIECHTI Olivier ▾


**HAUTE ÉCOLE
D'INGÉNIERIE ET DE GESTION
DU CANTON DE VAUD**
www.heig-vd.ch

Quicklinks
La boîte à outils des services HEIG-VD 

Services | Départements | Ra&D | Académique | Campus | Infrastructure | Liens | Conseil représentatif

Rechercher 

Intranet HEIG-VD > Services > Informatique > Poste de travail > Messagerie > Configuration > **SMTP**

Webmail
Outlook
Configuration
Exchange
IMAP
POP
SMTP
LDAP
Archivage
Spam
Mailing
Réservation salles

Le protocole SMTP est utilisé lors de l'envoi des mails. Il est complémentaire aux protocoles POP et IMAP qui ne s'occupent que de la réception.

L'adresse de notre serveur SMTP est :

smtp.heig-vd.ch

Attention, pour lutter contre le spam ainsi que pour des raisons de sécurité, notre serveur smtp, comme bien d'autres, n'autorise l'envoi d'e-mails que depuis l'intérieur de notre réseau (ou via vpn). Depuis chez vous, il faut utiliser le serveur smtp de votre fournisseur d'accès internet.

Pour en savoir plus : wikipedia

ATTENTION !!

Pour le moment, la connexion IMAP impose d'activer le SSL.



With this default setup, you will not be able to login with your user id / password.

My Account

Sign-in & security

Welcome

Sign-in & security

- Signing in to Google
- Device activity & security events
- Apps with account access

Personal info & privacy

- Your personal info
- Contacts
- Manage your Google activity
- Ads Settings
- Control your content

Account preferences

- Payments
- Language & Input Tools
- Accessibility
- Your Google Drive storage

Allow less secure apps: OFF

Some apps and devices use less secure sign-in technology, which could leave your account vulnerable. You can turn off access for these apps (which we recommend) or choose to use them despite the risks.

Check your privacy settings →

Your security comes first in everything we do.

[LEARN MORE](#)

WORLDWIDE SMTP DELIVERY

Like a first-class courier, for email.

Easily send and track all of your emails, and forget headaches with email delivery.

[See Plans & Pricing](#)[Try SMTP2GO Free](#)

tweakers-dev / MockMock

Watch

10

Unstar

39

Fork

24

Code

Issues 2

Pull requests 4

Projects 0

Wiki

Insights

A mock SMTP server built with Java

MockMock

Home

MockMock on Github

I've got 24 mails for you. Nice!

Delete all

From	To	Subject
John Doe <someone@example.org>	Some Dude <dude@examp...	Well, this is a nice subject...
John Doe <someone@example.org>	Some Dude <dude@examp...	LOL omg!
John Doe <someone@example.org>	Some Dude <dude@examp...	The iPhone 5 is huge!
John Doe <someone@example.org>	Some Dude <dude@examp...	Did you see the new MockMock version already?
John Doe <someone@example.org>	Some Dude <dude@examp...	Well, this is a nice subject...
John Doe <someone@example.org>	Some Dude <dude@examp...	Well, this is a nice subject...
John Doe <someone@example.org>	Some Dude <dude@examp...	Did you see the new MockMock version already?