

Deep Learning and Temporal Data Processing

Linear Regression in TensorFlow

Andrea Palazzi

December 20, 2017

University of Modena and Reggio Emilia

Linear Regression

References

Linear Regression

TensorFlow fully unleashes its power when used for deep learning applications. However, this framework can be used to implement any gradient-based learning pipeline.

The goal of this first practice session is implementing a simple **linear regression** model in TensorFlow[1].

For this practice we'll use a small dataset which puts in relation the weight of brain and body for a number of mammal species.

The whole dataset can be found here:

<http://people.sc.fsu.edu/~jburkardt/datasets/regression/x01.txt>

The goal is to fit a simple linear regression model (*i.e.* a line) to this data.

I already downloaded the data for you. You'll find it in
`data/brain_body_weight.txt`.

Also, a function to load the data into python script is available in `lab_utils.py`.

Here's the outline of what you're expected to do:

1. Load data using `lab_utils/get_brain_body_data`
2. Define appropriate placeholders using `tf.placeholder`
3. Define weight and bias variables using `tf.Variable`
4. Define 1-d linear regression model $y_{pred} = xw + b$
5. Define an appropriate objective function, e.g. $(y_{pred} - y_{true})^2$
6. Create an Optimizer (e.g. `tf.train.AdamOptimizer`)
7. Define a train iteration as one step of loss minimization
8. Loop train iteration until convergence

```
# Read data
body_weight, brain_weight = # todo
n_samples = len(body_weight)

# Define placeholders (1-d)
x, y = # todo

# Define variables
w, b = # todo
```



```
# Linear regression model  
y_pred = # todo  
  
# Define objective function  
loss = # todo  
  
# Define optimizer  
optimizer = # todo  
  
# Define one training iteration  
train_step = # todo
```

```
with tf.Session() as sess:

    # Initialize all variables
    sess.run(tf.global_variables_initializer())

    for i in range(n_epochs):
        total_loss = 0
        for bo_w, br_w in zip(body_weight, brain_weight):
            _, l = sess.run([train_step, loss],
                            feed_dict={x: bo_w, y: br_w})
            total_loss += l
        print('Epoch {0}: {1}'.format(i, total_loss / n_samples))
```

References

- [1] M. Abadi, A. Agarwal, P. Barham, E. Brevdo, Z. Chen, C. Citro, G. S. Corrado, A. Davis, J. Dean, M. Devin, S. Ghemawat, I. Goodfellow, A. Harp, G. Irving, M. Isard, Y. Jia, R. Jozefowicz, L. Kaiser, M. Kudlur, J. Levenberg, D. Mané, R. Monga, S. Moore, D. Murray, C. Olah, M. Schuster, J. Shlens, B. Steiner, I. Sutskever, K. Talwar, P. Tucker, V. Vanhoucke, V. Vasudevan, F. Viégas, O. Vinyals, P. Warden, M. Wattenberg, M. Wicke, Y. Yu, and X. Zheng.

TensorFlow: Large-scale machine learning on heterogeneous systems, 2015.

Software available from [tensorflow.org](https://www.tensorflow.org).