

LU1823

FULLY SYNTHETIC COMPRESSOR OIL (PAO + ESTER)



Solutions you can count on!

PROPERTIES

ISO GRADE	S32	S46	S68
Density, kg/liter @ 15°C	0.830	0.843	0.848
Kinematic Viscosity, mm ² /s @ 40°C	32	32	32
Kinematic Viscosity, mm ² /s @ 100°C	6	7.7	10.2
Viscosity Index	136	135	135
Pour Point (°C)	-45	-45	-45
Pour Point (°C)	218	230	248
FZG Load Carrying Test	>12	>12	>12

Product Data reflects results of laboratory tests and is intended to indicate general characteristics only. Because Vance Chemicals Pte Ltd cannot anticipate or control the many different conditions under which this information and/or product may be used, it does not guarantee the applicability or the accuracy of this information or the suitability of its products in any given situation. Users of Vance Chemicals Pte Ltd products should conduct their own tests to determine the suitability of each product for their particular purposes. © 2009 Vance Chemicals Pte Ltd. All rights reserved.

Vance Chemicals Pte Ltd
No 24 Gul Lane Singapore 629418
Tel: (65) 6863 0863 Fax: (65) 6862 0862
Email: sales@mr-mckenic.com
Website: <http://www.mr-mckenic.com>
RCB No: 200918824E



VCPL -CAT-LU1809- R3
Revision Date: 1st July 2015