

Clustering and Latent Variable Models

Mengye Ren

(Slides credit to David Rosenberg, He He, et al.)

NYU

Dec 3, 2024



K-means Clustering

Unsupervised learning

Goal Discover interesting *structure* in the data.

Unsupervised learning

Goal Discover interesting *structure* in the data.

Formulation Density estimation: $p(x; \theta)$ (often with *latent* variables).


Unsupervised learning

Goal Discover interesting *structure* in the data.

Formulation Density estimation: $p(x; \theta)$ (often with *latent* variables).

- Examples**
- Discover *clusters*: cluster data into groups.
 - Discover *factors*: project high-dimensional data to a small number of “meaningful” dimensions, i.e. dimensionality reduction.
 - Discover *graph structures*: learn joint distribution of correlated variables, i.e. graphical models.


Example: Old Faithful Geyser



- Looks like two clusters.
- How to find these clusters algorithmically?

k-Means: By Example


- Standardize the data.
- Choose two cluster centers.



From Bishop's *Pattern recognition and machine learning*, Figure 9.1(a).

k-means: by example


- Assign each point to closest center.



From Bishop's *Pattern recognition and machine learning*, Figure 9.1(b).

k -means: by example


- Compute new cluster centers.



From Bishop's *Pattern recognition and machine learning*, Figure 9.1(c).

k-means: by example


- Assign points to closest center.



From Bishop's *Pattern recognition and machine learning*, Figure 9.1(d).

k -means: by example


- Compute cluster centers.



From Bishop's *Pattern recognition and machine learning*, Figure 9.1(e).

k-means: by example


- Iterate until convergence.




From Bishop's *Pattern recognition and machine learning*, Figure 9.1(i).

Suboptimal Local Minimum

- The clustering for $k = 3$ below is a local minimum, but suboptimal:



Would be better to have
one cluster here



... and two clusters here

Formalize k -Means

- Dataset $\mathcal{D} = \{x_1, \dots, x_n\} \subset \mathcal{X}$ where $\mathcal{X} = \mathbb{R}^d$.

Formalize k -Means

- Dataset $\mathcal{D} = \{x_1, \dots, x_n\} \subset \mathcal{X}$ where $\mathcal{X} = \mathbb{R}^d$.
- Goal: Partition data \mathcal{D} into k disjoint sets C_1, \dots, C_k .

Formalize k -Means

- Dataset $\mathcal{D} = \{x_1, \dots, x_n\} \subset \mathcal{X}$ where $\mathcal{X} = \mathbb{R}^d$.
- Goal: Partition data \mathcal{D} into k disjoint sets C_1, \dots, C_k .
- Let $c_i \in \{1, \dots, k\}$ be the cluster assignment of x_i .

Formalize k -Means

- Dataset $\mathcal{D} = \{x_1, \dots, x_n\} \subset \mathcal{X}$ where $\mathcal{X} = \mathbb{R}^d$.
- Goal: Partition data \mathcal{D} into k disjoint sets C_1, \dots, C_k .
- Let $c_i \in \{1, \dots, k\}$ be the cluster assignment of x_i .
- The **centroid** of C_i is defined to be

Formalize k -Means

- Dataset $\mathcal{D} = \{x_1, \dots, x_n\} \subset \mathcal{X}$ where $\mathcal{X} = \mathbb{R}^d$.
 - Goal: Partition data \mathcal{D} into k disjoint sets C_1, \dots, C_k .
 - Let $c_i \in \{1, \dots, k\}$ be the cluster assignment of x_i .
 - The **centroid** of C_i is defined to be
-
- The k -means objective is to minimize the distance between each example and its cluster centroid:

k -Means: Algorithm

- 1 Initialize: Randomly choose initial centroids $\mu_1, \dots, \mu_k \in \mathbb{R}^d$.

k -Means: Algorithm

- 1 Initialize: Randomly choose initial centroids $\mu_1, \dots, \mu_k \in \mathbb{R}^d$.
- 2 Repeat until convergence (i.e. c_i doesn't change anymore):

k -Means: Algorithm

- 1 Initialize: Randomly choose initial centroids $\mu_1, \dots, \mu_k \in \mathbb{R}^d$.
- 2 Repeat until convergence (i.e. c_i doesn't change anymore):
 - 1 For all i , set

$$c_i \leftarrow \arg \min_j \|x_i - \mu_j\|^2. \quad (1)$$

k-Means: Algorithm

- ➊ Initialize: Randomly choose initial centroids $\mu_1, \dots, \mu_k \in \mathbb{R}^d$.
- ➋ Repeat until convergence (i.e. c_i doesn't change anymore):
 - ➊ For all i , set

$$c_i \leftarrow \arg \min_j \|x_i - \mu_j\|^2. \quad (1)$$

- ➋ For all j , set

$$\mu_j \leftarrow \frac{1}{|C_j|} \sum_{x \in C_j} x. \quad (2)$$

k-Means: Algorithm

- ➊ Initialize: Randomly choose initial centroids $\mu_1, \dots, \mu_k \in \mathbb{R}^d$.
- ➋ Repeat until convergence (i.e. c_i doesn't change anymore):
 - ➊ For all i , set

$$c_i \leftarrow \arg \min_j \|x_i - \mu_j\|^2. \quad (1)$$

- ➋ For all j , set

$$\mu_j \leftarrow \frac{1}{|C_j|} \sum_{x \in C_j} x. \quad (2)$$

- Recall the objective: $J(c, \mu) = \sum_{i=1}^n \|x_i - \mu_{c_i}\|^2$.

k-Means: Algorithm

- 1 Initialize: Randomly choose initial centroids $\mu_1, \dots, \mu_k \in \mathbb{R}^d$.
- 2 Repeat until convergence (i.e. c_i doesn't change anymore):

- 1 For all i , set

$$c_i \leftarrow \arg \min_j \|x_i - \mu_j\|^2. \quad \text{Minimize } J \text{ w.r.t. } c \text{ while fixing } \mu \quad (1)$$

- 2 For all j , set

$$\mu_j \leftarrow \frac{1}{|C_j|} \sum_{x \in C_j} x. \quad (2)$$

- Recall the objective: $J(c, \mu) = \sum_{i=1}^n \|x_i - \mu_{c_i}\|^2$.

k-Means: Algorithm

- 1 Initialize: Randomly choose initial centroids $\mu_1, \dots, \mu_k \in \mathbb{R}^d$.
- 2 Repeat until convergence (i.e. c_i doesn't change anymore):

- 1 For all i , set

$$c_i \leftarrow \arg \min_j \|x_i - \mu_j\|^2. \quad \text{Minimize } J \text{ w.r.t. } c \text{ while fixing } \mu \quad (1)$$

- 2 For all j , set

$$\mu_j \leftarrow \frac{1}{|C_j|} \sum_{x \in C_j} x. \quad \text{Minimize } J \text{ w.r.t. } \mu \text{ while fixing } c. \quad (2)$$

- Recall the objective: $J(c, \mu) = \sum_{i=1}^n \|x_i - \mu_{c_i}\|^2$.

Avoid bad local minima

k -means converges to a local minimum.

- J is non-convex, thus no guarantee to converging to the global minimum.

Avoid getting stuck with bad local minima:

- Re-run with random initial centroids.

Avoid bad local minima

k -means converges to a local minimum.

- J is non-convex, thus no guarantee to converging to the global minimum.

Avoid getting stuck with bad local minima:

- Re-run with random initial centroids.
- **k -means++**: choose initial centroids that spread over all data points.

Avoid bad local minima

k -means converges to a local minimum.

- J is non-convex, thus no guarantee to converging to the global minimum.

Avoid getting stuck with bad local minima:

- Re-run with random initial centroids.
- **k -means++**: choose initial centroids that spread over all data points.
 - Randomly choose the first centroid from the data points \mathcal{D} .

Avoid bad local minima

k -means converges to a local minimum.

- J is non-convex, thus no guarantee to converging to the global minimum.

Avoid getting stuck with bad local minima:

- Re-run with random initial centroids.
- **k -means++**: choose initial centroids that spread over all data points.
 - Randomly choose the first centroid from the data points \mathcal{D} .
 - Sequentially choose subsequent centroids from points that are farther away from current centroids:

Avoid bad local minima

k -means converges to a local minimum.

- J is non-convex, thus no guarantee to converging to the global minimum.

Avoid getting stuck with bad local minima:

- Re-run with random initial centroids.
- **k -means++**: choose initial centroids that spread over all data points.
 - Randomly choose the first centroid from the data points \mathcal{D} .
 - Sequentially choose subsequent centroids from points that are farther away from current centroids:
 - Compute distance between each x_i and the closest already chosen centroids.

Avoid bad local minima

k -means converges to a local minimum.

- J is non-convex, thus no guarantee to converging to the global minimum.

Avoid getting stuck with bad local minima:

- Re-run with random initial centroids.
- **k -means++**: choose initial centroids that spread over all data points.
 - Randomly choose the first centroid from the data points \mathcal{D} .
 - Sequentially choose subsequent centroids from points that are farther away from current centroids:
 - Compute distance between each x_i and the closest already chosen centroids.
 - Randomly choose next centroid with probability proportional to the computed distance squared.

Summary

We've seen

- Clustering—an unsupervised learning problem that aims to discover group assignments.
- k -means:
 - Algorithm: alternating between assigning points to clusters and computing cluster centroids.
 - Objective: minimizing some loss function by coordinate descent.
 - Converge to a local minimum.

Summary

We've seen

- Clustering—an unsupervised learning problem that aims to discover group assignments.
- k -means:
 - Algorithm: alternating between assigning points to clusters and computing cluster centroids.
 - Objective: minimizing some loss function by coordinate descent.
 - Converge to a local minimum.

Next, probabilistic model of clustering.

- A generative model of x .
- Maximum likelihood estimation.

Gaussian Mixture Models

Gaussian mixture model (GMM)

Generative story of GMM with k mixture components:

Gaussian mixture model (GMM)

Generative story of GMM with k mixture components:

Probability density of x :

- Sum over (marginalize) the **latent variable** z .

Identifiability Issues for GMM

- Suppose we have found parameters

Cluster probabilities: $\pi = (\pi_1, \dots, \pi_k)$

Cluster means: $\mu = (\mu_1, \dots, \mu_k)$

Cluster covariance matrices: $\Sigma = (\Sigma_1, \dots, \Sigma_k)$

that are at a local minimum.

Identifiability Issues for GMM

- Suppose we have found parameters

Cluster probabilities: $\pi = (\pi_1, \dots, \pi_k)$

Cluster means: $\mu = (\mu_1, \dots, \mu_k)$

Cluster covariance matrices: $\Sigma = (\Sigma_1, \dots, \Sigma_k)$

that are at a local minimum.

- What happens if we shuffle the clusters? e.g. Switch the labels for clusters 1 and 2.

Identifiability Issues for GMM

- Suppose we have found parameters

Cluster probabilities: $\pi = (\pi_1, \dots, \pi_k)$

Cluster means: $\mu = (\mu_1, \dots, \mu_k)$

Cluster covariance matrices: $\Sigma = (\Sigma_1, \dots, \Sigma_k)$

that are at a local minimum.

- What happens if we shuffle the clusters? e.g. Switch the labels for clusters 1 and 2.
- We'll get the same likelihood. How many such equivalent settings are there?

Identifiability Issues for GMM

- Suppose we have found parameters

Cluster probabilities: $\pi = (\pi_1, \dots, \pi_k)$

Cluster means: $\mu = (\mu_1, \dots, \mu_k)$

Cluster covariance matrices: $\Sigma = (\Sigma_1, \dots, \Sigma_k)$

that are at a local minimum.

- What happens if we shuffle the clusters? e.g. Switch the labels for clusters 1 and 2.
- We'll get the same likelihood. How many such equivalent settings are there?
- Assuming all clusters are distinct, there are $k!$ equivalent solutions.

How to learn the parameters π_k, μ_k, Σ_k ?

Learning GMMs

How to learn the parameters π_k, μ_k, Σ_k ?

- MLE (also called maximize marginal likelihood).
- Log likelihood of data:

Learning GMMs

How to learn the parameters π_k, μ_k, Σ_k ?

- MLE (also called maximize marginal likelihood).
- Log likelihood of data:
- Cannot push log into the sum... z and x are coupled.
- No closed-form solution for GMM—try to compute the gradient yourself!

- What about running gradient descent or SGD on

$$J(\pi, \mu, \Sigma) = - \sum_{i=1}^n \log \left\{ \sum_{z=1}^k \pi_z \mathcal{N}(x_i \mid \mu_z, \Sigma_z) \right\}?$$

Gradient Descent / SGD for GMM

- What about running gradient descent or SGD on

$$J(\pi, \mu, \Sigma) = - \sum_{i=1}^n \log \left\{ \sum_{z=1}^k \pi_z \mathcal{N}(x_i \mid \mu_z, \Sigma_z) \right\}?$$

- Can be done, in principle – but need to be clever about it.

Gradient Descent / SGD for GMM

- What about running gradient descent or SGD on

$$J(\pi, \mu, \Sigma) = - \sum_{i=1}^n \log \left\{ \sum_{z=1}^k \pi_z \mathcal{N}(x_i \mid \mu_z, \Sigma_z) \right\}?$$

- Can be done, in principle – but need to be clever about it.
- For example, each covariance matrix $\Sigma_1, \dots, \Sigma_k$ has to be positive semidefinite.

Gradient Descent / SGD for GMM

- What about running gradient descent or SGD on

$$J(\pi, \mu, \Sigma) = - \sum_{i=1}^n \log \left\{ \sum_{z=1}^k \pi_z \mathcal{N}(x_i \mid \mu_z, \Sigma_z) \right\}?$$

- Can be done, in principle – but need to be clever about it.
- For example, each covariance matrix $\Sigma_1, \dots, \Sigma_k$ has to be positive semidefinite.
- How to maintain that constraint?

Gradient Descent / SGD for GMM

- What about running gradient descent or SGD on

$$J(\pi, \mu, \Sigma) = - \sum_{i=1}^n \log \left\{ \sum_{z=1}^k \pi_z \mathcal{N}(x_i \mid \mu_z, \Sigma_z) \right\}?$$

- Can be done, in principle – but need to be clever about it.
- For example, each covariance matrix $\Sigma_1, \dots, \Sigma_k$ has to be positive semidefinite.
- How to maintain that constraint?
 - Rewrite $\Sigma_i = M_i M_i^T$, where M_i is an unconstrained matrix.

Gradient Descent / SGD for GMM

- What about running gradient descent or SGD on

$$J(\pi, \mu, \Sigma) = - \sum_{i=1}^n \log \left\{ \sum_{z=1}^k \pi_z \mathcal{N}(x_i \mid \mu_z, \Sigma_z) \right\}?$$

- Can be done, in principle – but need to be clever about it.
- For example, each covariance matrix $\Sigma_1, \dots, \Sigma_k$ has to be positive semidefinite.
- How to maintain that constraint?
 - Rewrite $\Sigma_i = M_i M_i^T$, where M_i is an unconstrained matrix.
 - Then Σ_i is positive semidefinite.

Gradient Descent / SGD for GMM

- What about running gradient descent or SGD on

$$J(\pi, \mu, \Sigma) = - \sum_{i=1}^n \log \left\{ \sum_{z=1}^k \pi_z \mathcal{N}(x_i \mid \mu_z, \Sigma_z) \right\}?$$

- Can be done, in principle – but need to be clever about it.
- For example, each covariance matrix $\Sigma_1, \dots, \Sigma_k$ has to be positive semidefinite.
- How to maintain that constraint?
 - Rewrite $\Sigma_i = M_i M_i^T$, where M_i is an unconstrained matrix.
 - Then Σ_i is positive semidefinite.

Learning GMMs: observable case

Suppose we observe cluster assignments z . Then MLE is easy:

$$n_z = \sum_{i=1}^n \mathbb{1}[z_i = z] \quad \# \text{ examples in each cluster} \quad (3)$$

(6)

Learning GMMs: observable case

Suppose we observe cluster assignments z . Then MLE is easy:

$$n_z = \sum_{i=1}^n \mathbb{1}[z_i = z] \quad \# \text{ examples in each cluster} \quad (3)$$

$$\hat{\pi}(z) = \frac{n_z}{n} \quad \text{fraction of examples in each cluster} \quad (4)$$

(6)

Learning GMMs: observable case

Suppose we observe cluster assignments z . Then MLE is easy:

$$n_z = \sum_{i=1}^n \mathbb{1}[z_i = z] \quad \# \text{ examples in each cluster} \quad (3)$$

$$\hat{\pi}(z) = \frac{n_z}{n} \quad \text{fraction of examples in each cluster} \quad (4)$$

$$\hat{\mu}_z = \frac{1}{n_z} \sum_{i: z_i = z} x_i \quad \text{empirical cluster mean} \quad (5)$$

(6)

Learning GMMs: observable case

Suppose we observe cluster assignments z . Then MLE is easy:

$$n_z = \sum_{i=1}^n \mathbb{1}[z_i = z] \quad \# \text{ examples in each cluster} \quad (3)$$

$$\hat{\pi}(z) = \frac{n_z}{n} \quad \text{fraction of examples in each cluster} \quad (4)$$

$$\hat{\mu}_z = \frac{1}{n_z} \sum_{i: z_i = z} x_i \quad \text{empirical cluster mean} \quad (5)$$

$$\hat{\Sigma}_z = \frac{1}{n_z} \sum_{i: z_i = z} (x_i - \hat{\mu}_z)(x_i - \hat{\mu}_z)^T. \quad \text{empirical cluster covariance} \quad (6)$$

Learning GMMs: inference

The inference problem: observe x , want to know z .

Learning GMMs: inference

The inference problem: observe x , want to know z .

- $p(z | x)$ is a *soft assignment*.
- If we know the parameters μ, Σ, π , this would be easy to compute.

Let's compute the cluster assignments and the parameters iteratively.

Let's compute the cluster assignments and the parameters iteratively.

The expectation-minimization (EM) algorithm:

- 1 Initialize parameters μ, Σ, π randomly.
- 2 Run until convergence:

Let's compute the cluster assignments and the parameters iteratively.

The expectation-minimization (EM) algorithm:

- ① Initialize parameters μ, Σ, π randomly.
- ② Run until convergence:
 - ① E-step: fill in latent variables by inference.
 - compute soft assignments $p(z | x_i)$ for all i .

Let's compute the cluster assignments and the parameters iteratively.

The expectation-minimization (EM) algorithm:

- ① Initialize parameters μ, Σ, π randomly.
- ② Run until convergence:
 - ① E-step: fill in latent variables by inference.
 - compute soft assignments $p(z | x_i)$ for all i .
 - ② M-step: standard MLE for μ, Σ, π given “observed” variables.
 - Equivalent to MLE in the observable case on data weighted by $p(z | x_i)$.

M-step for GMM

- Let $p(z | x)$ be the soft assignments:

$$\gamma_i^j = \frac{\pi_j^{\text{old}} \mathcal{N}(x_i | \mu_j^{\text{old}}, \Sigma_j^{\text{old}})}{\sum_{c=1}^k \pi_c^{\text{old}} \mathcal{N}(x_i | \mu_c^{\text{old}}, \Sigma_c^{\text{old}})}.$$

- Exercise: show that

$$n_z = \sum_{i=1}^n \gamma_i^z$$


$$\mu_z^{\text{new}} = \frac{1}{n_z} \sum_{i=1}^n \gamma_i^z x_i$$

$$\Sigma_z^{\text{new}} = \frac{1}{n_z} \sum_{i=1}^n \gamma_i^z (x_i - \mu_z^{\text{new}}) (x_i - \mu_z^{\text{new}})^T$$

$$\pi_z^{\text{new}} = \frac{n_z}{n}.$$

EM for GMM


• Initialization



From Bishop's *Pattern recognition and machine learning*, Figure 9.8.

EM for GMM


• First soft assignment:



From Bishop's *Pattern recognition and machine learning*, Figure 9.8.

EM for GMM


- First soft assignment:



From Bishop's *Pattern recognition and machine learning*, Figure 9.8.

EM for GMM


- After 5 rounds of EM:



From Bishop's *Pattern recognition and machine learning*, Figure 9.8.

EM for GMM

- After 20 rounds of EM:



From Bishop's *Pattern recognition and machine learning*, Figure 9.8.

EM for GMM: Summary

- EM is a general algorithm for learning latent variable models.
- *Key idea*: if data was fully observed, then MLE is easy.
 - E-step: fill in latent variables by computing $p(z \mid x, \theta)$.
 - M-step: standard MLE given fully observed data.
- Simpler and more efficient than gradient methods.
- Can prove that EM monotonically improves the likelihood and converges to a local minimum.
- *k*-means is a special case of EM for GMM with *hard assignments*, also called hard-EM.

Latent Variable Models

General Latent Variable Model

- Two sets of random variables: z and x .
- z consists of unobserved **hidden variables**.
- x consists of **observed variables**.

General Latent Variable Model

- Two sets of random variables: z and x .
- z consists of unobserved **hidden variables**.
- x consists of **observed variables**.
- Joint probability model parameterized by $\theta \in \Theta$:

$$p(x, z \mid \theta)$$

General Latent Variable Model

- Two sets of random variables: z and x .
- z consists of unobserved **hidden variables**.
- x consists of **observed variables**.
- Joint probability model parameterized by $\theta \in \Theta$:

$$p(x, z \mid \theta)$$

Definition

A **latent variable model** is a probability model for which certain variables are never observed.

General Latent Variable Model

- Two sets of random variables: z and x .
- z consists of unobserved **hidden variables**.
- x consists of **observed variables**.
- Joint probability model parameterized by $\theta \in \Theta$:

$$p(x, z \mid \theta)$$

Definition

A **latent variable model** is a probability model for which certain variables are never observed.

e.g. The Gaussian mixture model is a latent variable model.

Complete and Incomplete Data

- Suppose we observe some data (x_1, \dots, x_n) .

Complete and Incomplete Data

- Suppose we observe some data (x_1, \dots, x_n) .
- To simplify notation, take x to represent the entire dataset

$$x = (x_1, \dots, x_n),$$

and z to represent the corresponding unobserved variables

$$z = (z_1, \dots, z_n).$$

- An observation of x is called an **incomplete data set**.
- An observation (x, z) is called a **complete data set**.

Our Objectives

- **Learning problem:** Given incomplete dataset x , find MLE

$$\hat{\theta} = \arg \max_{\theta} p(x | \theta).$$

Our Objectives

- **Learning problem:** Given incomplete dataset x , find MLE

$$\hat{\theta} = \arg \max_{\theta} p(x | \theta).$$

- **Inference problem:** Given x , find conditional distribution over z :

$$p(z | x, \theta).$$

Our Objectives

- **Learning problem:** Given incomplete dataset x , find MLE

$$\hat{\theta} = \arg \max_{\theta} p(x | \theta).$$

- **Inference problem:** Given x , find conditional distribution over z :

$$p(z | x, \theta).$$

- For Gaussian mixture model, learning is hard, inference is easy.
- For more complicated models, inference can also be hard.

Log-Likelihood and Terminology

- Note that

$$\arg \max_{\theta} p(x | \theta) = \arg \max_{\theta} [\log p(x | \theta)] .$$

Log-Likelihood and Terminology

- Note that

$$\arg \max_{\theta} p(x | \theta) = \arg \max_{\theta} [\log p(x | \theta)] .$$

- Often easier to work with this “**log-likelihood**”.

Log-Likelihood and Terminology

- Note that

$$\arg \max_{\theta} p(x | \theta) = \arg \max_{\theta} [\log p(x | \theta)] .$$

- Often easier to work with this “**log-likelihood**”.
- We often call $p(x)$ the **marginal likelihood**,
 - because it is $p(x, z)$ with z “marginalized out”:

$$p(x) = \sum_z p(x, z)$$

Log-Likelihood and Terminology

- Note that

$$\arg \max_{\theta} p(x | \theta) = \arg \max_{\theta} [\log p(x | \theta)].$$

- Often easier to work with this “**log-likelihood**”.
- We often call $p(x)$ the **marginal likelihood**,
 - because it is $p(x, z)$ with z “marginalized out”:

$$p(x) = \sum_z p(x, z)$$

- We often call $p(x, z)$ the **joint**. (for “joint distribution”)

Log-Likelihood and Terminology

- Note that

$$\arg \max_{\theta} p(x | \theta) = \arg \max_{\theta} [\log p(x | \theta)].$$

- Often easier to work with this “**log-likelihood**”.
- We often call $p(x)$ the **marginal likelihood**,
 - because it is $p(x, z)$ with z “marginalized out”:

$$p(x) = \sum_z p(x, z)$$

- We often call $p(x, z)$ the **joint**. (for “joint distribution”)
- Similarly, $\log p(x)$ is the **marginal log-likelihood**.

EM Algorithm

Intuition

Problem: marginal log-likelihood $\log p(x; \theta)$ is hard to optimize (observing only x)

Intuition

Problem: marginal log-likelihood $\log p(x; \theta)$ is hard to optimize (observing only x)

Observation: complete data log-likelihood $\log p(x, z; \theta)$ is easy to optimize (observing both x and z)

Intuition

Problem: marginal log-likelihood $\log p(x; \theta)$ is hard to optimize (observing only x)

Observation: complete data log-likelihood $\log p(x, z; \theta)$ is easy to optimize (observing both x and z)

Idea: guess a distribution of the latent variables $q(z)$ (soft assignments)

Intuition

Problem: marginal log-likelihood $\log p(x; \theta)$ is hard to optimize (observing only x)

Observation: complete data log-likelihood $\log p(x, z; \theta)$ is easy to optimize (observing both x and z)

Idea: guess a distribution of the latent variables $q(z)$ (soft assignments)

Maximize the **expected complete data log-likelihood**:

$$\max_{\theta} \sum_{z \in \mathcal{Z}} q(z) \log p(x, z; \theta)$$

Intuition

Problem: marginal log-likelihood $\log p(x; \theta)$ is hard to optimize (observing only x)

Observation: complete data log-likelihood $\log p(x, z; \theta)$ is easy to optimize (observing both x and z)

Idea: guess a distribution of the latent variables $q(z)$ (soft assignments)

Maximize the **expected complete data log-likelihood**:

$$\max_{\theta} \sum_{z \in \mathcal{Z}} q(z) \log p(x, z; \theta)$$

EM assumption: the expected complete data log-likelihood is easy to optimize

Why should this work?

Math Prerequisites

Jensen's Inequality

Theorem (Jensen's Inequality)

If $f : \mathbb{R} \rightarrow \mathbb{R}$ is a **convex** function, and x is a random variable, then

$$\mathbb{E}f(x) \geq f(\mathbb{E}x).$$

Jensen's Inequality

Theorem (Jensen's Inequality)

If $f : \mathbb{R} \rightarrow \mathbb{R}$ is a **convex** function, and x is a random variable, then

$$\mathbb{E}f(x) \geq f(\mathbb{E}x).$$

Moreover, if f is **strictly convex**, then equality implies that $x = \mathbb{E}x$ with probability 1 (i.e. x is a constant).

Jensen's Inequality

Theorem (Jensen's Inequality)

If $f : \mathbb{R} \rightarrow \mathbb{R}$ is a **convex** function, and x is a random variable, then

$$\mathbb{E}f(x) \geq f(\mathbb{E}x).$$

Moreover, if f is **strictly convex**, then equality implies that $x = \mathbb{E}x$ with probability 1 (i.e. x is a constant).

- e.g. $f(x) = x^2$ is convex. So $\mathbb{E}x^2 \geq (\mathbb{E}x)^2$. Thus

$$\text{Var}(x) = \mathbb{E}x^2 - (\mathbb{E}x)^2 \geq 0.$$

Kullback-Leibler Divergence

- Let $p(x)$ and $q(x)$ be probability mass functions (PMFs) on \mathcal{X} .
- How can we measure how “different” p and q are?

Kullback-Leibler Divergence

- Let $p(x)$ and $q(x)$ be probability mass functions (PMFs) on \mathcal{X} .
- How can we measure how “different” p and q are?
- The **Kullback-Leibler** or “**KL**” **Divergence** is defined by

$$\text{KL}(p\|q) = \sum_{x \in \mathcal{X}} p(x) \log \frac{p(x)}{q(x)}.$$

(Assumes $q(x) = 0$ implies $p(x) = 0$.)

Kullback-Leibler Divergence

- Let $p(x)$ and $q(x)$ be probability mass functions (PMFs) on \mathcal{X} .
- How can we measure how “different” p and q are?
- The **Kullback-Leibler** or “**KL**” **Divergence** is defined by

$$\text{KL}(p\|q) = \sum_{x \in \mathcal{X}} p(x) \log \frac{p(x)}{q(x)}.$$

(Assumes $q(x) = 0$ implies $p(x) = 0$.)

- Can also write this as

$$\text{KL}(p\|q) = \mathbb{E}_{x \sim p} \log \frac{p(x)}{q(x)}.$$

Gibbs Inequality ($\mathbf{KL}(p\|q) \geq 0$ and $\mathbf{KL}(p\|p) = 0$)

Theorem (Gibbs Inequality)

Let $p(x)$ and $q(x)$ be PMFs on \mathcal{X} . Then

$$KL(p\|q) \geq 0,$$

with equality iff $p(x) = q(x)$ for all $x \in \mathcal{X}$.

Gibbs Inequality ($\text{KL}(p\|q) \geq 0$ and $\text{KL}(p\|p) = 0$)

Theorem (Gibbs Inequality)

Let $p(x)$ and $q(x)$ be PMFs on \mathcal{X} . Then

$$\text{KL}(p\|q) \geq 0,$$

with equality iff $p(x) = q(x)$ for all $x \in \mathcal{X}$.

- KL divergence measures the “distance” between distributions.

Gibbs Inequality ($\text{KL}(p\|q) \geq 0$ and $\text{KL}(p\|p) = 0$)

Theorem (Gibbs Inequality)

Let $p(x)$ and $q(x)$ be PMFs on \mathcal{X} . Then

$$\text{KL}(p\|q) \geq 0,$$

with equality iff $p(x) = q(x)$ for all $x \in \mathcal{X}$.

- KL divergence measures the “distance” between distributions.
- Note:
 - KL divergence **not a metric**.
 - KL divergence is **not symmetric**.

Gibbs Inequality: Proof

$$\text{KL}(p\|q) = \mathbb{E}_p \left[-\log \left(\frac{q(x)}{p(x)} \right) \right]$$

Gibbs Inequality: Proof

$$\begin{aligned}\mathrm{KL}(p\|q) &= \mathbb{E}_p \left[-\log \left(\frac{q(x)}{p(x)} \right) \right] \\ &\geq -\log \left[\mathbb{E}_p \left(\frac{q(x)}{p(x)} \right) \right] \quad (\text{Jensen's})\end{aligned}$$

Gibbs Inequality: Proof

$$\begin{aligned}\text{KL}(p\|q) &= \mathbb{E}_p \left[-\log \left(\frac{q(x)}{p(x)} \right) \right] \\ &\geq -\log \left[\mathbb{E}_p \left(\frac{q(x)}{p(x)} \right) \right] \quad (\text{Jensen's}) \\ &= -\log \left[\sum_{\{x|p(x)>0\}} p(x) \frac{q(x)}{p(x)} \right]\end{aligned}$$

Gibbs Inequality: Proof

$$\begin{aligned}\mathrm{KL}(p\|q) &= \mathbb{E}_p \left[-\log \left(\frac{q(x)}{p(x)} \right) \right] \\ &\geq -\log \left[\mathbb{E}_p \left(\frac{q(x)}{p(x)} \right) \right] \quad (\text{Jensen's}) \\ &= -\log \left[\sum_{\{x|p(x)>0\}} p(x) \frac{q(x)}{p(x)} \right] \\ &= -\log \left[\sum_{x \in \mathcal{X}} q(x) \right]\end{aligned}$$

Gibbs Inequality: Proof

$$\begin{aligned}\text{KL}(p\|q) &= \mathbb{E}_p \left[-\log \left(\frac{q(x)}{p(x)} \right) \right] \\ &\geq -\log \left[\mathbb{E}_p \left(\frac{q(x)}{p(x)} \right) \right] \quad (\text{Jensen's}) \\ &= -\log \left[\sum_{\{x|p(x)>0\}} p(x) \frac{q(x)}{p(x)} \right] \\ &= -\log \left[\sum_{x \in \mathcal{X}} q(x) \right] \\ &= -\log 1 = 0.\end{aligned}$$

Gibbs Inequality: Proof

$$\begin{aligned}\mathrm{KL}(p\|q) &= \mathbb{E}_p \left[-\log \left(\frac{q(x)}{p(x)} \right) \right] \\ &\geq -\log \left[\mathbb{E}_p \left(\frac{q(x)}{p(x)} \right) \right] \quad (\text{Jensen's}) \\ &= -\log \left[\sum_{\{x|p(x)>0\}} p(x) \frac{q(x)}{p(x)} \right] \\ &= -\log \left[\sum_{x \in \mathcal{X}} q(x) \right] \\ &= -\log 1 = 0.\end{aligned}$$

- Since $-\log$ is strictly convex, we have strict equality iff $q(x)/p(x)$ is a constant, which implies $q = p$.

The ELBO: Family of Lower Bounds on $\log p(x | \theta)$

The Maximum Likelihood Estimator

Lower bound of the marginal log-likelihood

- The MLE is defined as a maximum over θ :

$$\hat{\theta}_{\text{MLE}} = \arg \max_{\theta} [\log p(x | \theta)] .$$

MLE, EM, and the ELBO

- The MLE is defined as a maximum over θ :

$$\hat{\theta}_{\text{MLE}} = \arg \max_{\theta} [\log p(x | \theta)].$$

- For any PMF $q(z)$, we have a lower bound on the marginal log-likelihood

$$\log p(x | \theta) \geq \mathcal{L}(q, \theta).$$

MLE, EM, and the ELBO

- The MLE is defined as a maximum over θ :

$$\hat{\theta}_{\text{MLE}} = \arg \max_{\theta} [\log p(x | \theta)].$$

- For any PMF $q(z)$, we have a lower bound on the marginal log-likelihood

$$\log p(x | \theta) \geq \mathcal{L}(q, \theta).$$

- In EM algorithm, we maximize the lower bound (ELBO) over θ and q :

$$\hat{\theta}_{\text{EM}} \approx \arg \max_{\theta} \left[\max_q \mathcal{L}(q, \theta) \right]$$

MLE, EM, and the ELBO

- The MLE is defined as a maximum over θ :

$$\hat{\theta}_{\text{MLE}} = \arg \max_{\theta} [\log p(x | \theta)].$$

- For any PMF $q(z)$, we have a lower bound on the marginal log-likelihood

$$\log p(x | \theta) \geq \mathcal{L}(q, \theta).$$

- In EM algorithm, we maximize the lower bound (ELBO) over θ and q :

$$\hat{\theta}_{\text{EM}} \approx \arg \max_{\theta} \left[\max_q \mathcal{L}(q, \theta) \right]$$

- In EM algorithm, q ranges over all distributions on z .

EM: Coordinate Ascent on Lower Bound

- Choose sequence of q 's and θ 's by “**coordinate ascent**” on $\mathcal{L}(q, \theta)$.

EM: Coordinate Ascent on Lower Bound

- Choose sequence of q 's and θ 's by “**coordinate ascent**” on $\mathcal{L}(q, \theta)$.
- EM Algorithm (high level):
 - 1 Choose initial θ^{old} .
 - 2 Let $q^* = \arg \max_q \mathcal{L}(q, \theta^{\text{old}})$


EM: Coordinate Ascent on Lower Bound

- Choose sequence of q 's and θ 's by “**coordinate ascent**” on $\mathcal{L}(q, \theta)$.
- EM Algorithm (high level):
 - ① Choose initial θ^{old} .
 - ② Let $q^* = \arg \max_q \mathcal{L}(q, \theta^{\text{old}})$
 - ③ Let $\theta^{\text{new}} = \arg \max_{\theta} \mathcal{L}(q^*, \theta)$.

EM: Coordinate Ascent on Lower Bound


- Choose sequence of q 's and θ 's by “**coordinate ascent**” on $\mathcal{L}(q, \theta)$.
- EM Algorithm (high level):
 - ① Choose initial θ^{old} .
 - ② Let $q^* = \arg \max_q \mathcal{L}(q, \theta^{\text{old}})$
 - ③ Let $\theta^{\text{new}} = \arg \max_{\theta} \mathcal{L}(q^*, \theta)$.
 - ④ Go to step 2, until converged.
- Will show: $p(x | \theta^{\text{new}}) \geq p(x | \theta^{\text{old}})$
- Get sequence of θ 's with monotonically increasing likelihood.

EM: Coordinate Ascent on Lower Bound




- 1 Start at θ^{old} .

EM: Coordinate Ascent on Lower Bound



- 1 Start at θ^{old} .
- 2 Find q giving best lower bound at $\theta^{\text{old}} \implies \mathcal{L}(q, \theta)$.

EM: Coordinate Ascent on Lower Bound



- 1 Start at θ^{old} .
- 2 Find q giving best lower bound at $\theta^{\text{old}} \implies \mathcal{L}(q, \theta)$.
- 3 $\theta^{\text{new}} = \arg \max_{\theta} \mathcal{L}(q, \theta)$.

From Bishop's *Pattern recognition and machine learning*, Figure 9.14.

Is ELBO a "good" lowerbound?

$$\begin{aligned}\mathcal{L}(q, \theta) &= \sum_{z \in \mathcal{Z}} q(z) \log \frac{p(x, z | \theta)}{q(z)} \\&= \sum_{z \in \mathcal{Z}} q(z) \log \frac{p(z | x, \theta) p(x | \theta)}{q(z)} \\&= - \sum_{z \in \mathcal{Z}} q(z) \log \frac{q(z)}{p(z | x, \theta)} + \sum_{z \in \mathcal{Z}} q(z) \log p(x | \theta) \\&= -\text{KL}(q(z) \| p(z | x, \theta)) + \underbrace{\log p(x | \theta)}_{\text{evidence}}\end{aligned}$$

- **KL divergence:** measures "distance" between two distributions (not symmetric!)
- $\text{KL}(q \| p) \geq 0$ with equality iff $q(z) = p(z | x)$.
- $\text{ELBO} = \text{evidence} - \text{KL} \leq \text{evidence}$

Maximizing over q for fixed θ .

- Find q maximizing

$$\mathcal{L}(q, \theta) = -\text{KL}[q(z), p(z | x, \theta)] + \log p(x | \theta)$$

Maximizing over q for fixed θ .

- Find q maximizing

$$\mathcal{L}(q, \theta) = -\text{KL}[q(z), p(z | x, \theta)] + \underbrace{\log p(x | \theta)}_{\text{no } q \text{ here}}$$

Maximizing over q for fixed θ .

- Find q maximizing

$$\mathcal{L}(q, \theta) = -\text{KL}[q(z), p(z | x, \theta)] + \underbrace{\log p(x | \theta)}_{\text{no } q \text{ here}}$$

- Recall $\text{KL}(p \| q) \geq 0$, and $\text{KL}(p \| p) = 0$.

Maximizing over q for fixed θ .

- Find q maximizing

$$\mathcal{L}(q, \theta) = -\text{KL}[q(z), p(z | x, \theta)] + \underbrace{\log p(x | \theta)}_{\text{no } q \text{ here}}$$

- Recall $\text{KL}(p||q) \geq 0$, and $\text{KL}(p||p) = 0$.
- Best q is $q^*(z) = p(z | x, \theta)$ and

Maximizing over q for fixed θ .

- Find q maximizing

$$\mathcal{L}(q, \theta) = -\text{KL}[q(z), p(z | x, \theta)] + \underbrace{\log p(x | \theta)}_{\text{no } q \text{ here}}$$

- Recall $\text{KL}(p \| q) \geq 0$, and $\text{KL}(p \| p) = 0$.

- Best q is $q^*(z) = p(z | x, \theta)$ and

$$\mathcal{L}(q^*, \theta) = -\underbrace{\text{KL}[p(z | x, \theta), p(z | x, \theta)]}_{=0} + \log p(x | \theta)$$

Maximizing over q for fixed θ .

- Find q maximizing

$$\mathcal{L}(q, \theta) = -\text{KL}[q(z), p(z | x, \theta)] + \underbrace{\log p(x | \theta)}_{\text{no } q \text{ here}}$$

- Recall $\text{KL}(p||q) \geq 0$, and $\text{KL}(p||p) = 0$.

- Best q is $q^*(z) = p(z | x, \theta)$ and

$$\mathcal{L}(q^*, \theta) = -\underbrace{\text{KL}[p(z | x, \theta), p(z | x, \theta)]}_{=0} + \log p(x | \theta)$$

- Summary:

$$\log p(x | \theta) = \sup_q \mathcal{L}(q, \theta) \quad \forall \theta$$

- For any θ , **sup is attained** at $q(z) = p(z | x, \theta)$.

Marginal Log-Likelihood **IS** the Supremum over Lower Bounds

Summary

Latent variable models: clustering, latent structure, missing labels etc.

Parameter estimation: maximum marginal log-likelihood

Challenge: directly maximize the **evidence** $\log p(x; \theta)$ is hard

Solution: maximize the **evidence lower bound**:

$$\text{ELBO} = \mathcal{L}(q, \theta) = -\text{KL}(q(z) \| p(z | x; \theta)) + \log p(x; \theta)$$

Why does it work?

$$\begin{aligned} q^*(z) &= p(z | x; \theta) \quad \forall \theta \in \Theta \\ \mathcal{L}(q^*, \theta^*) &= \max_{\theta} \log p(x; \theta) \end{aligned}$$

EM algorithm

Coordinate ascent on $\mathcal{L}(q, \theta)$

- 1 Random initialization: $\theta^{\text{old}} \leftarrow \theta_0$
- 2 Repeat until convergence
 - i $q(z) \leftarrow \arg \max_q \mathcal{L}(q, \theta^{\text{old}})$

Expectation (the E-step): $q^*(z) = p(z | x; \theta^{\text{old}})$
 $J(\theta) = \mathcal{L}(q^*, \theta)$

ii $\theta^{\text{new}} \leftarrow \arg \max_{\theta} \mathcal{L}(q^*, \theta)$

Maximization (the M-step): $\theta^{\text{new}} \leftarrow \arg \max_{\theta} J(\theta)$

① Expectation Step

- Let $q^*(z) = p(z \mid x, \theta^{\text{old}})$. [q^* gives best lower bound at θ^{old}]

① Expectation Step

- Let $q^*(z) = p(z | x, \theta^{\text{old}})$. [q^* gives best lower bound at θ^{old}]
- Let

$$J(\theta) := \mathcal{L}(q^*, \theta) = \underbrace{\sum_z q^*(z) \log \left(\frac{p(x, z | \theta)}{q^*(z)} \right)}_{\text{expectation w.r.t. } z \sim q^*(z)}$$

1 Expectation Step

- Let $q^*(z) = p(z | x, \theta^{\text{old}})$. [q^* gives best lower bound at θ^{old}]
- Let

$$J(\theta) := \mathcal{L}(q^*, \theta) = \underbrace{\sum_z q^*(z) \log \left(\frac{p(x, z | \theta)}{q^*(z)} \right)}_{\text{expectation w.r.t. } z \sim q^*(z)}$$

2 Maximization Step

$$\theta^{\text{new}} = \arg \max_{\theta} J(\theta).$$

1 Expectation Step

- Let $q^*(z) = p(z | x, \theta^{\text{old}})$. [q^* gives best lower bound at θ^{old}]
- Let

$$J(\theta) := \mathcal{L}(q^*, \theta) = \underbrace{\sum_z q^*(z) \log \left(\frac{p(x, z | \theta)}{q^*(z)} \right)}_{\text{expectation w.r.t. } z \sim q^*(z)}$$

2 Maximization Step

$$\theta^{\text{new}} = \arg \max_{\theta} J(\theta).$$

[Equivalent to maximizing expected complete log-likelihood.]

1 Expectation Step

- Let $q^*(z) = p(z | x, \theta^{\text{old}})$. [q^* gives best lower bound at θ^{old}]
- Let

$$J(\theta) := \mathcal{L}(q^*, \theta) = \underbrace{\sum_z q^*(z) \log \left(\frac{p(x, z | \theta)}{q^*(z)} \right)}_{\text{expectation w.r.t. } z \sim q^*(z)}$$


2 Maximization Step

$$\theta^{\text{new}} = \arg \max_{\theta} J(\theta).$$

[Equivalent to maximizing expected complete log-likelihood.]

EM puts no constraint on q in the E-step and assumes the M-step is easy. In general, both steps can be hard.

Monotonically increasing likelihood



Exercise: prove that EM increases the marginal likelihood monotonically

$$\log p(x; \theta^{\text{new}}) \geq \log p(x; \theta^{\text{old}}).$$

Does EM converge to a global maximum?

Variations on EM

EM Gives Us Two New Problems

- The “E” Step: Computing

$$J(\theta) := \mathcal{L}(q^*, \theta) = \sum_z q^*(z) \log \left(\frac{p(x, z | \theta)}{q^*(z)} \right)$$

EM Gives Us Two New Problems

- The “E” Step: Computing

$$J(\theta) := \mathcal{L}(q^*, \theta) = \sum_z q^*(z) \log \left(\frac{p(x, z | \theta)}{q^*(z)} \right)$$

- The “M” Step: Computing

$$\theta^{\text{new}} = \arg \max_{\theta} J(\theta).$$

EM Gives Us Two New Problems

- The “E” Step: Computing

$$J(\theta) := \mathcal{L}(q^*, \theta) = \sum_z q^*(z) \log \left(\frac{p(x, z | \theta)}{q^*(z)} \right)$$

- The “M” Step: Computing

$$\theta^{\text{new}} = \arg \max_{\theta} J(\theta).$$

EM Gives Us Two New Problems

- The “E” Step: Computing

$$J(\theta) := \mathcal{L}(q^*, \theta) = \sum_z q^*(z) \log \left(\frac{p(x, z | \theta)}{q^*(z)} \right)$$

- The “M” Step: Computing

$$\theta^{\text{new}} = \arg \max_{\theta} J(\theta).$$

- Either of these can be too hard to do in practice.

Generalized EM (GEM)

- Addresses the problem of a difficult “M” step.

Generalized EM (GEM)

- Addresses the problem of a difficult “M” step.
- Rather than finding

$$\theta^{\text{new}} = \arg \max_{\theta} J(\theta),$$

find **any** θ^{new} for which

$$J(\theta^{\text{new}}) > J(\theta^{\text{old}}).$$

Generalized EM (GEM)

- Addresses the problem of a difficult “M” step.
- Rather than finding

$$\theta^{\text{new}} = \arg \max_{\theta} J(\theta),$$

find **any** θ^{new} for which

$$J(\theta^{\text{new}}) > J(\theta^{\text{old}}).$$

- Can use a standard nonlinear optimization strategy
 - e.g. take a gradient step on J .

Generalized EM (GEM)

- Addresses the problem of a difficult “M” step.
- Rather than finding

$$\theta^{\text{new}} = \arg \max_{\theta} J(\theta),$$

find **any** θ^{new} for which

$$J(\theta^{\text{new}}) > J(\theta^{\text{old}}).$$

- Can use a standard nonlinear optimization strategy
 - e.g. take a gradient step on J .
- We still get monotonically increasing likelihood.

EM and More General Variational Methods

- Suppose “E” step is difficult:
 - Hard to take expectation w.r.t. $q^*(z) = p(z \mid x, \theta^{\text{old}})$.

EM and More General Variational Methods

- Suppose “E” step is difficult:
 - Hard to take expectation w.r.t. $q^*(z) = p(z \mid x, \theta^{\text{old}})$.
- Solution: Restrict to distributions \mathcal{Q} that are easy to work with.


EM and More General Variational Methods

- Suppose “E” step is difficult:
 - Hard to take expectation w.r.t. $q^*(z) = p(z | x, \theta^{\text{old}})$.
- Solution: Restrict to distributions \mathcal{Q} that are easy to work with.
- Lower bound now looser:

$$q^* = \arg \min_{q \in \mathcal{Q}} \text{KL}[q(z), p(z | x, \theta^{\text{old}})]$$


Deep Latent Variable Models

- Neural network is a flexible function class to represent transformation between random variables e.g., $q(z)$.




Deep Latent Variable Models

- Neural network is a flexible function class to represent transformation between random variables e.g., $q(z)$.
- In neural networks, the hidden activations do not have probabilistic interpretation as they are not random variables.




Deep Latent Variable Models

- Neural network is a flexible function class to represent transformation between random variables e.g., $q(z)$.
- In neural networks, the hidden activations do not have probabilistic interpretation as they are not random variables.
- What if we let the hidden represent some learned latent code?



Variational Autoencoders (VAE) ¹


- An autoencoder (AE) is a neural network that reconstructs the same input.



¹Diederik P Kingma, Max Welling. Auto-Encoding Variational Bayes. ICLR 2014.

Variational Autoencoders (VAE) ¹


- An autoencoder (AE) is a neural network that reconstructs the same input.
- The first half is an encoder, from input to latent. The second half is a decoder.



¹Diederik P Kingma, Max Welling. Auto-Encoding Variational Bayes. ICLR 2014.

Variational Autoencoders (VAE) ¹


- An autoencoder (AE) is a neural network that reconstructs the same input.
- The first half is an encoder, from input to latent. The second half is a decoder.
- How to make q a probability distribution?



¹Diederik P Kingma, Max Welling. Auto-Encoding Variational Bayes. ICLR 2014.


Reparameterization Trick

- Let's assume that $q(z|x)$ is a Gaussian distribution.




Reparameterization Trick

- Let's assume that $q(z|x)$ is a Gaussian distribution.
- Instead of letting the neural network to output a stochastic variable, we can let it predict deterministically the distribution parameters μ and σ .



Reparameterization Trick

- Let's assume that $q(z|x)$ is a Gaussian distribution.
- Instead of letting the neural network to output a stochastic variable, we can let it predict deterministically the distribution parameters μ and σ .
- A stochastic z can be sampled from $\mathcal{N}(\mu, \sigma^2)$: $z = \mu + \sigma \cdot \epsilon$, where $\epsilon \sim \mathcal{N}(0, 1)$.



Variational Lower Bound

- Encoder q weights: ϕ ; Decoder p weights: θ .

Variational Lower Bound

- Encoder q weights: ϕ ; Decoder p weights: θ .
- Now maximize ELBO:

(10)

Variational Lower Bound

- Encoder q weights: ϕ ; Decoder p weights: θ .
- Now maximize ELBO:

$$L(q; \phi, \theta) = \sum_z q(z) \log \frac{p_\theta(x, z)}{q_\phi(z|x)} \quad (7)$$

(10)

Variational Lower Bound

- Encoder q weights: ϕ ; Decoder p weights: θ .
- Now maximize ELBO:

$$L(q; \phi, \theta) = \sum_z q(z) \log \frac{p_\theta(x, z)}{q_\phi(z|x)} \quad (7)$$

$$= \mathbb{E}_{z \sim q} [-\log q_\phi(z|x) + \log p_\theta(x, z)] \quad (8)$$

$$(10)$$

Variational Lower Bound

- Encoder q weights: ϕ ; Decoder p weights: θ .
- Now maximize ELBO:

$$L(q; \phi, \theta) = \sum_z q(z) \log \frac{p_\theta(x, z)}{q_\phi(z|x)} \quad (7)$$

$$= \mathbb{E}_{z \sim q} [-\log q_\phi(z|x) + \log p_\theta(x, z)] \quad (8)$$

$$= \mathbb{E}_{z \sim q} [-\log q_\phi(z|x) + \log p_\theta(x|z) + \log p_\theta(z)] \quad (9)$$

$$(10)$$

Variational Lower Bound

- Encoder q weights: ϕ ; Decoder p weights: θ .
- Now maximize ELBO:

$$L(q; \phi, \theta) = \sum_z q(z) \log \frac{p_\theta(x, z)}{q_\phi(z|x)} \quad (7)$$

$$= \mathbb{E}_{z \sim q} [-\log q_\phi(z|x) + \log p_\theta(x, z)] \quad (8)$$


$$= \mathbb{E}_{z \sim q} [-\log q_\phi(z|x) + \log p_\theta(x|z) + \log p_\theta(z)] \quad (9)$$

$$= \underbrace{-KL(q_\phi(z|x) || p_\theta(z))}_{\text{Divergence between } q \text{ and the prior distribution}} + \underbrace{\mathbb{E}_{z \sim q}(\log p_\theta(x|z))}_{\text{Reconstruction based on } z} \quad (10)$$

Stochastic Gradient

- The loss function needs to take expectation over q :

$$L(q; \phi, \theta) = -KL(q_\phi(z|x) || p_\theta(z)) + \mathbb{E}_{z \sim q}(\log p_\theta(x|z))$$




Stochastic Gradient

- The loss function needs to take expectation over q :

$$L(q; \phi, \theta) = -KL(q_\phi(z|x) || p_\theta(z)) + \mathbb{E}_{z \sim q}(\log p_\theta(x|z))$$

- Turns out we just need to have a Monte Carlo sample size of 1:
 - For each x , sample one z from $q(z|x)$.




Stochastic Gradient

- The loss function needs to take expectation over q :

$$L(q; \phi, \theta) = -KL(q_\phi(z|x) || p_\theta(z)) + \mathbb{E}_{z \sim q}(\log p_\theta(x|z))$$

- Turns out we just need to have a Monte Carlo sample size of 1:
 - For each x , sample one z from $q(z|x)$.
- Backprop through reparameterization.



Learned Manifold

[illegible]

Today's Summary

- Motivation: Unsupervised learning

Today's Summary

- Motivation: Unsupervised learning
- K-means: A simple algorithm for discovering clusters

Today's Summary

- Motivation: Unsupervised learning
- K-means: A simple algorithm for discovering clusters
- Making k-means probabilistic: Gaussian mixture models

Today's Summary

- Motivation: Unsupervised learning
- K-means: A simple algorithm for discovering clusters
- Making k-means probabilistic: Gaussian mixture models
- More generally: Latent variable models

Today's Summary

- Motivation: Unsupervised learning
- K-means: A simple algorithm for discovering clusters
- Making k-means probabilistic: Gaussian mixture models
- More generally: Latent variable models
- Learning of latent variable models: EM

Today's Summary

- Motivation: Unsupervised learning
- K-means: A simple algorithm for discovering clusters
- Making k-means probabilistic: Gaussian mixture models
- More generally: Latent variable models
- Learning of latent variable models: EM
- Underlying principle: Maximizing ELBO

Today's Summary

- Motivation: Unsupervised learning
- K-means: A simple algorithm for discovering clusters
- Making k-means probabilistic: Gaussian mixture models
- More generally: Latent variable models
- Learning of latent variable models: EM
- Underlying principle: Maximizing ELBO
- VAE: Introducing variational inference to neural networks. A classic starting example for deep generative modeling.

Conclusion and Outlook

Acknowledgement

- Most content developed by David Rosenberg (now at Bloomberg).
- Later adapted by He He, Tal Linzen, and others.

Acknowledgement

- Most content developed by David Rosenberg (now at Bloomberg).
- Later adapted by He He, Tal Linzen, and others.
- This is a very challenging grad-level course.
- Congrats, you are almost done.

Next Lecture: Project Presentation

- Dec 10, in-person presentations.
- 22 groups, 120mins.
- Aim for **3 mins** per group, hard stop at 4 mins, and 1 min max for Q&A.
- Send your slides in PDF with your group number by Dec 9 11:59pm (via Google form).

Linear Perceptron, conditional probability models, SVMs

Models

Linear Perceptron, conditional probability models, SVMs

Non-linear Kernelized models, trees, basis function models, neural nets

Linear Perceptron, conditional probability models, SVMs

Non-linear Kernelized models, trees, basis function models, neural nets

How to choose the model family?

- Trade-offs:
 - approximation error and estimation error (bias and variance),
 - accuracy and efficiency (during both training and inference).

Linear Perceptron, conditional probability models, SVMs

Non-linear Kernelized models, trees, basis function models, neural nets

How to choose the model family?

- Trade-offs:
 - approximation error and estimation error (bias and variance),
 - accuracy and efficiency (during both training and inference).
- Start from the task requirements, e.g. amount of data, computation resource
- The best lesson is to practice!

Objectives

Loss functions How far off a prediction is from the target, e.g. 0-1 loss, margin-based loss, squared loss.

Objectives

Loss functions How far off a prediction is from the target, e.g. 0-1 loss, margin-based loss, squared loss.

Risk Expected loss - but expectation over what?

Objectives

Loss functions How far off a prediction is from the target, e.g. 0-1 loss, margin-based loss, squared loss.

Risk Expected loss - but expectation over what?

- Frequentist approach: expectation over data.
 - Empirical risk minimization, i.e. average loss on the training data.
 - Regularization: balance estimation error and generalization error.

Objectives

Loss functions How far off a prediction is from the target, e.g. 0-1 loss, margin-based loss, squared loss.

Risk Expected loss - but expectation over what?

- Frequentist approach: expectation over data.
 - Empirical risk minimization, i.e. average loss on the training data.
 - Regularization: balance estimation error and generalization error.
- Bayesian approach: expectation over parameters.
 - Posterior: prior belief updated by observed data.
 - Bayes action minimizes the posterior risk.

Learning Find model parameters—often an optimization problem.

- (Stochastic) (sub)gradient descent
- Functional gradient descent (gradient boosting)
- Convex vs non-convex objectives

Inference Answer questions given a learned model.

- Bayesian inference: compute various quantities given the posterior.
- Dynamic programming: compute $\arg \max$ in structured prediction.

Do We Still Need ML?

- Deep Learning (DL) has been overwhelmingly popular in the past few years.

Do We Still Need ML?

- Deep Learning (DL) has been overwhelmingly popular in the past few years.
- Many ML methods are considered out-dated.

Do We Still Need ML?

- Deep Learning (DL) has been overwhelmingly popular in the past few years.
- Many ML methods are considered out-dated.
- However, DL is not necessarily good for all types of data (data availability, data quality, data modality etc.). Classic methods may also have their sweet spots.

Do We Still Need ML?

- Deep Learning (DL) has been overwhelmingly popular in the past few years.
- Many ML methods are considered out-dated.
- However, DL is not necessarily good for all types of data (data availability, data quality, data modality etc.). Classic methods may also have their sweet spots.
- Classic ML sheds new insight into understand DL.

Do We Still Need ML?

- Deep Learning (DL) has been overwhelmingly popular in the past few years.
- Many ML methods are considered out-dated.
- However, DL is not necessarily good for all types of data (data availability, data quality, data modality etc.). Classic methods may also have their sweet spots.
- Classic ML sheds new insight into understand DL.
- Classic ML lays down foundation when we innovate in DL algorithms.

Other ML Related Advanced Courses in CS/DS

- Bayesian Machine Learning(Andrew Wilson)
- Computer Vision (Saining Xie)
- Deep Learning (Yann LeCun)
- Deep Reinforcement Learning (Lerrel Pinto)
- Embodied Learning and Vision (Mengye Ren)
- Foundations of Deep Learning Theory (Matus Telgarsky)
- Inference and Representation (Joan Bruna)
- Learning with Large Language and Vision Models (Saining Xie)
- Mathematics of Deep Learning (Joan Bruna)
- Natural Language Processing (He He)