

Semantics

He He

New York University

November 3, 2021

Table of Contents

Introduction to semantics

Logical languages

Semantic parsing

Syntax vs semantics

Syntax: does the string belong to the language?

Semantics: what is the meaning of the string?

Examples in programming languages:

Different syntax, same semantics

$$2 + 3 \quad 3 + 2$$

Same syntax, different semantics

$$3 / 2 \text{ (Python 2.7)} \quad 3 // 2 \text{ (Python 3)}$$

(Slide adapted from Stanford CS221 Lecture 16)

Model-theoretic semantics

An **expression** is a string of mere symbols.

A **model** defines meanings of symbols.

The output of an expression with respect to a model is its **denotation**.



expression	model	denotation
$3 + 2 * 4$	calculator	11
the red ball	an image	the red ball in the image
SELECT Name FROM Student WHERE Id = 0;	database	John
Book me a ticket from NYC to Seattle	database	[action]

We understand the expression if we know how to act (in a world).

Natural language as expressions

Motivating applications:

Question answering

What is the profit of Mulan?

Who is the 46th president of the US?

Personal assistant

Alexa, play my favorite song.

Siri, show me how to get home.

- ▶ But natural language is full of ambiguities
- ▶ Cannot be directly handled by a computer (unlike programming/formal languages)

Semantic analysis

Goal: convert natural language to meaning representation

John likes fruits. (*informal*)

$\forall x \text{ FRUIT}(x) \implies \text{LIKES}(x, \text{JOHN})$ (*formal*)

Main tool: first-order logic

Why logic?

- ▶ Unambiguity: one meaning per statement
- ▶ Knowledge: link symbols to knowledge (entities, relations, facts etc.) (*Take in complex information*)
- ▶ Inference: derive additional knowledge given statements (*Reason with the information*)

Logic and semantics: example

Natural language: “John likes Mary’s friends”

Logical form: $\forall x \text{ FRIENDS}(x, \text{MARY}) \implies \text{LIKES}(x, \text{JOHN})$

World model: state of affairs in the world

People = {John, Mary, Joe, Ted}

John is a friend of Mary.

Joe is a friend of Mary.

Given the world model,

- ▶ Is $\text{LIKES}(\text{JOE}, \text{JOHN})$ true?
- ▶ What else can we infer from the statement?

The value of the expression may change given a different world model.

Table of Contents

Introduction to semantics

Logical languages

Semantic parsing

Propositional logic

A **proposition** is a statement that is either true or false.

Propositional logic deals with propositions and their relations.

Syntax of propositional language:

- ▶ **Propositional symbols:** a *primitive* set of propositions

p_1 : John likes Mary

p_2 : John is a student

- ▶ **Logical connectives:** rules to build up **formulas**

symbol	read	meaning	formula
\neg	not	negation	$\neg p$
\vee	or	disjunction	$p \vee q$
\wedge	and	conjunction	$p \wedge q$
\implies	implies / if then	implication	$p \implies q$
\iff	equivalent to / iff	equivalence	$p \iff q$

- ▶ Parentheses: (,)



Parsing a formula

How would you check if a formula is valid (i.e. grammatical)?

A propositional formula is constructed by connecting propositions using the connectives.

- ▶ Formulas can be nested.
- ▶ Parentheses are used to disambiguate formulas.

Example:

$$((p \wedge q) \wedge \neg p)$$

$$((p \vee q) \wedge r) \implies p$$

Try to draw the parse trees of the formulas.

World model for propositional logic

Propositional symbols:

p_1 = hot

p_2 = John likes ice cream

p_3 = John ate an ice cream

Formula: $p_1 \wedge p_2 \implies p_3$ (Is this true?)

World model for propositional logic

Propositional symbols:

$p_1 = \text{hot}$

$p_2 = \text{John likes ice cream}$

$p_3 = \text{John ate an ice cream}$

Formula: $p_1 \wedge p_2 \implies p_3$ (Is this true?)

The **world model** in propositional logic is an *assignment* of truth values to propositional symbols.

	m_1	m_2	m_3	m_4	m_5	m_6	m_7	m_8
p_1	T	T	T	T	F	F	F	F
p_2	T	T	F	F	T	T	F	F
p_3	T	F	T	F	T	F	T	F

In which world(s) is the above formula false?

Meaning of a formula

Propositional symbols:

$p_1 = \text{hot}$

$p_2 = \text{John likes ice cream}$

$p_3 = \text{John ate an ice cream}$

Formula: $p_1 \wedge p_2 \implies p_3$ *Just symbols!*

Semantics is given by *interpreting* the formula against a world model.

A formula specifies *a set of world models* where it is true.

A set of formulas is a knowledge base (constraints on the world model).

Making inference given formulas and the world model: take a course in AI.

Limitations of propositional logic

How do we represent knowledge of a *collection* of objects?

“Everyone who likes ice cream ate an ice cream.”

p_{JOHN} (John likes ice cream) $\implies q_{\text{JOHN}}$ (John ate an ice cream)

p_{JOE} (Joe likes ice cream) $\implies q_{\text{JOE}}$ (Joe ate an ice cream)

p_{ALICE} (Alice likes ice cream) $\implies q_{\text{ALICE}}$ (Alice ate an ice cream)

p_{CAROL} (Carol likes ice cream) $\implies q_{\text{CAROL}}$ (Carol ate an ice cream)

...

[] likes ice cream \implies [] ate an ice cream

Need a compact way to represent a collection of objects!

First-order logic

First-order logic generalizes propositional logic with several new symbols:

Represent objects:

Constants Primitive objects, e.g. John

Variables Placeholder for some object, e.g. x

Functions A map from object(s) to an object, e.g. $\text{John} \rightarrow \text{John's father}$

Group objects:

Predicate Properties of a set of objects, e.g. students, couples

Quantify a (infinite) set of objects:

Quantifiers Specify the number of objects with a certain property, e.g. *all* people are mortal.

Constants, variables, functions

Constants refer to primitive objects such as named entities:

JOHN, ICECREAM, HOT

A **variable** refers to an unspecified object:

x, y, z

STUDENT(x)

FRIENDS(x , JOHN)

A n -ary **function** maps n objects to an object:

MOTHER(x)

FRIENDS(MOTHER(x), MOTHER(y))

Predicates

A **predicate** is an indicator function $P: X \rightarrow \{\text{true}, \text{false}\}$.

- ▶ Describes properties of object(s)
- ▶ $P(x)$ is an atomic formula

STUDENT(MARY)

SMALLER(DESK, COMPUTER)

FRIENDS(JOHN, MARY) \implies FRIENDS(MARY, JOHN)

Quantifiers

Universal quantifier \forall :

- ▶ The statement is true for *every* object
- ▶ $\forall x P(x)$ is equivalent to $P(A) \wedge P(B) \wedge \dots$
- ▶ All people are mortal: $\forall x \text{ PERSON}(x) \implies \text{MORTAL}(x)$

Existential quantifier \exists :

- ▶ The statement is true for *some* object
- ▶ $\exists x P(x)$ is equivalent to $P(A) \vee P(B) \vee \dots$
- ▶ Some people are mortal: $\exists x \text{ PERSON}(x) \wedge \text{MORTAL}(x)$

Order matters, e.g., “everyone speaks a language”:

$$\forall x \exists y \text{ SPEAKS}(x, y)$$

$$\exists y \forall x \text{ SPEAKS}(x, y)$$

Syntax of first-order logic

Terms refer to objects:

- ▶ Constant symbol, e.g. JOHN
- ▶ Variable symbol, e.g. x
- ▶ Function of terms, e.g. MOTHER(x), CAPITAL(NY)

Formula evaluates to true or false:

- ▶ Predicate over terms is an atomic formula, e.g. STUDENT(MOTHER(JOHN))
- ▶ Connectives applied to formulas (similar to propositional logic)

$$\text{STUDENT}(x) \wedge \text{HAPPY}(x)$$

- ▶ Quantifiers applied to formulas

$$\forall x \text{ STUDENT}(x) \implies \text{HAPPY}(x)$$

$$\exists x \text{ STUDENT}(x) \wedge \text{HAPPY}(x)$$

World model of first-order logic

How do we know if FRIENDS(JOHN, MARY) is true?

World model of propositional logic: **propositions**

proposition	truthful value
John is a friend of Mary	True
John is a friend of Joe	False

World model of first-order logic: **objects and their relations**

constant symbol	object
JOHN	a
MARY	b

predicate symbol	set of n -tuples
FRIENDS	$\{(a, b), (b, a)\}$

Graph representation of the world model

Summary

Syntax produces symbols and well-formed formulas.

Semantics grounds symbols to a world and allows for evaluation of formulas.

We have seen how it works for formal languages such as propositional logic and first-order logic.

Next, formal language to natural language.

Table of Contents

Introduction to semantics

Logical languages

Semantic parsing

System overview

Utterance Linguistic expression.
“Call John, please.”


Logical form Formal meaning representation of the utterance
CALL(JOHN) *program*

Denotation Output of the meaning representation with respect to the model
Calling XXX-XXX-XXXX ... *execution result*



Translate NL to logical language

Key idea: *compositionality*



- ▶ Sentence: READS(JOHN) (What's the denotation?)
- ▶ We would like to construct it recursively
 - ▶ John: JOHN (a unique entity)
 - ▶ reads: a predicate (function) that takes an entity (one argument)

A brief introduction to lambda calculus

Lambda calculus / λ -calculus

- ▶ A notation for applying a function to an argument

$$\lambda x. x^2 + x$$

- ▶ A function that is waiting for the value of a variable to be filled
- ▶ Function application by β -reduction

$$(\lambda x. x^2 + x)(2) = 2^2 + 2 = 6$$

- ▶ Takes multiple arguments by “currying”


$$(\lambda x. \lambda y. xy)(2) = \lambda y. 2y$$

$$(\lambda x. \lambda y. xy)(3)(2) = (\lambda y. 2y)(3) = 6$$

Translate NL to logical language

Verbs are predicates


- ▶ reads: $\lambda x. \text{READS}(x)$ (waiting for an NP)
- ▶ likes: $\lambda x. \lambda y. \text{LIKES}(x, y)$ (waiting for two NPs)



Translate NL to logical language

Verbs are predicates

- ▶ reads: $\lambda x. \text{READS}(x)$ (waiting for an NP)
- ▶ likes: $\lambda x. \lambda y. \text{LIKES}(x, y)$ (waiting for two NPs)



Compositional semantics

Bottom up parsing:

- ▶ Start with the semantics of each word
- ▶ Combine semantics of spans according to certain rules
 - ▶ Associate a combination rule with each grammar rule

$V:\lambda y.\lambda x.LIKES(x, y)$	\rightarrow	likes
$NP:JOHN$	\rightarrow	John
$VP:\alpha(\beta)$	\rightarrow	$V:\alpha$ $NP:\beta$
$S:\beta(\alpha)$	\rightarrow	$NP:\alpha$ $VP:\beta$

- ▶ Get semantics by function application
- ▶ Lexical rules can be complex!

Quantification

John bought a book

BOUGHT(JOHN, BOOK)?

“book” is not a unique entity! BOUGHT(MARY, BOOK)

Correct logical form: $\exists x \text{BOOK}(x) \wedge \text{BOUGHT}(\text{JOHN}, x)$

But what should be the semantics of “a”? $\lambda P. \lambda Q. \exists x P(x) \wedge Q(x)$


“a book”: $\lambda Q. \exists x \text{BOOK}(x) \wedge Q(x)$. (Need to change other NP rules)

What about “the”, “every”, “most”?

We also want to represent tense: “bought” vs “will buy”. (event variables)

Learning from derivations

Text: John bought a book (utterance)




Annotation:

Use approaches from (discriminative) constituent parsing

Learning from derivations

Text: John bought a book (utterance)



Annotation:

Use approaches from (discriminative) constituent parsing

Obstacles:

- ▶ Derivations are rarely annotated.
- ▶ Unlike syntactic parsing, cannot obtain derivations from logical forms.
- ▶ Spurious derivation: wrong derivations that reach the correct logical form.

Learning from logical forms

Text: John bought a book (utterance)

Annotation: $\exists x \text{BOOK}(x) \wedge \text{BOUGHT}(\text{JOHN}, x)$ (logical form)

Key idea: model derivation as a latent variable z [Zettlemoyer and Collins, 2005]

Learning: maximum marginal likelihood

$$\begin{aligned}\log p(y \mid x) &= \log \sum_z p(y, z \mid x) \\ &= \log \sum_z \frac{\exp(\theta \cdot \Phi(x, y, z))}{\sum_{z', y'} \exp(\theta \cdot \Phi(x, y', z'))}\end{aligned}$$


- ▶ Need to learn both the lexicon and the model parameters (for CCG)
- ▶ Use EM algorithm (with approximation)

Learning from denotations

Text: What states border Georgia?

Annotation: Alabama, Florida, North Carolina, South Carolina, Tennessee

Key idea: model the logical form as a latent variable z [Liang, 2013]



Datasets

Geo880

- ▶ 880 questions and database queries about US geography
- ▶ “what is the highest point in the largest state?”
- ▶ Compositional utterances in a clean, narrow domain

ATIS

- ▶ 5418 utterances of airline queries and paired logical forms
- ▶ “show me information on american airlines from fort worth texas to philadelphia”
- ▶ More flexible word order but simpler logic

Free917, WebQuestions

- ▶ Questions and paired logical forms on Freebase
- ▶ Logically less complex but scales to many more predicates

Text to SQL

Spider (Yu et al. 2018)


Expert-annotated, cross-domain, complex text-to-SQL dataset

Assumption:

- For each

	Train	Dev	Hidden
# DBs	146	20	40
# Examples	8,659	1,034	2,147

Database



Question What are the name and budget of the departments with average instructor salary above the overall average?

SQL

```
SELECT T2.name, T2.budget
FROM Instructor AS T1 JOIN Department AS T2 ON
T1.Department_ID = T2.ID
GROUP BY T1.Department_ID
HAVING AVG(T1.salary) >
(SELECT AVG(Salary) FROM Instructor)
```

(Slide from Victoria Lin)

Challenges

Design the logical representation and grammar

- ▶ Expressivity vs computation efficiency
- ▶ Domain-specific vs domain-general
- ▶ Interacts with annotation and learning

Learning from different supervision signals

- ▶ End-to-end (utterance to action)
- ▶ Reinforcement learning (robotics, visual grounding)
- ▶ Interactive learning (obtain user feedback)