# Cache Organization And Access Patterns

# Problem 1

The following table gives the parameters for a number of different caches, where m is the number of physical address bits, C is the cache size (number of data bytes), B is the block size in bytes, and E is the number of lines per set. For each cache, determine the number of cache sets (S), tag bits (t), set index bits (s), and block offset bits (b).

Cache	m	C	В	E	S	t	s	b
1.	32	1024	4	4				
2.	32	1024	4	256				
3.	32	1024	8	1				
4.	32	1024	8	128				
5.	32	1024	32	1				
6.	32	1024	32	4				

### **Problem2**

The following problem concerns basic cache lookups.

- The memory is byte addressable.
- Memory accesses are to **1-byte words** (not 4-byte words).
- Physical addresses are 13 bits wide.
- The cache is 2-way set associative, with a 4 byte line size and 16 total lines.

In the following tables, all numbers are given in hexadecimal. The contents of the cache are as follows:

	2-way Set Associative Cache											
Index	Tag	Valid	Byte 0	Byte 1	Byte 2	Byte 3	Tag	Valid	Byte 0	Byte 1	Byte 2	Byte 3
0	09	1	86	30	3F	10	00	0	99	04	03	48
1	45	1	60	4F	E0	23	38	1	00	BC	0B	37
2	ЕВ	0	2F	81	FD	09	0B	0	8F	E2	05	BD
3	06	0	3D	94	9B	F7	32	1	12	08	7B	AD
4	C7	1	06	78	07	C5	05	1	40	67	C2	3B
5	71	1	0В	DE	18	4B	6E	0	В0	39	D3	F7
6	91	1	A0	В7	26	2D	F0	0	0C	71	40	10
7	46	0	B1	0A	32	0F	DE	1	12	C0	88	37

### Part 1

The box below shows the format of a physical address. Indicate (by labeling the diagram) the fields that would be used to determine the following:

- CO The block offset within the cache line
- CI The cache index
- CT The cache tag

	12	11	10	9	8	7	6	5	4	3	2	1	0
ſ													
Į													

### Part 2

For the given physical address, indicate the cache entry accessed and the cache byte value returned **in hex**. Indicate whether a cache miss occurs.

If there is a cache miss, enter "-" (a dash) for "Cache Byte returned".

Physical address: 0E34

A. Physical address format (one bit per box)

	12	11	10	9	8	7	6	5	4	3	2	1	0

#### B. Physical memory reference

Parameter	Value
Byte offset	0x
Cache Index	0x
Cache Tag	0x
Cache Hit? (Y/N)	
Cache Byte returned	0x