

Connectedness

Outline

We will use graph traversals to determine:

- Whether one vertex is connected to another
- The connected sub-graphs of a graph

Connected

First, let us determine whether one vertex is connected to another

- v_j is connected to v_k if there is a path from the first to the second

Strategy:

- Perform a breadth-first traversal starting at v_j
- While looping, if the vertex v_k ever found to be adjacent to the front of the queue, return true
- If the loop ends, return false

Connected

Consider implementing a breadth-first traversal on a graph:




- Choose any vertex, mark it as visited and push it onto queue
- While the queue is not empty:
 - Pop to top vertex v from the queue
 - For each vertex adjacent to v that has not been visited:
 - Mark it visited, and
 - Push it onto the queue

This continues until the queue is empty

- Note: if there are no unvisited vertices, the graph is connected,



Determining Connections

Is A connected to D?




Determining Connections

Vertex A is marked as visited and pushed onto the queue




Determining Connections

Pop the head, A, and mark and push B, F and G



B	F	G			
---	---	---	--	--	--






B	F	G			
---	---	---	--	--	--

Determining Connections



Pop B and mark and, in the left graph, mark and push H

- On the right graph, B has no unvisited adjacent vertices




Determining Connections

Popping F results in the pushing of E




Determining Connections

In either graph, G has no adjacent vertices that are unvisited





H	E				
---	---	--	--	--	--



E					
---	--	--	--	--	--

Determining Connections



Popping H on the left graph results in C and I being pushed



Determining Connections

The queue on the right is empty




- We determine A is not connected to D



Determining Connections

On the left, we pop C and return true because D is adjacent to C




- In the left graph, A is connected to D



Determining Connections

On the left, we pop C and return true because D is adjacent to C

- In the left graph, A is connected to D



Connected Components

If we continued the traversal, we would find all vertices that are connected to A


Suppose we want to partition the vertices into connected sub-graphs

- While there are unvisited vertices in the tree:
 - Select an unvisited vertex and perform a traversal on that vertex
 - Each vertex that is visited in that traversal is added to the set initially containing the initial unvisited vertex
- Continue until all vertices are visited

We would use a disjoint set data structure for maximum efficiency

Connected Components


Here we start with a set of singletons



A	B	C	D	E	F	G	H	I	J	K
A	B	C	D	E	F	G	H	I	J	K

Connected Components


The vertex A is unvisited, so we start with it



A	B	C	D	E	F	G	H	I	J	K
A	B	C	D	E	F	G	H	I	J	K

Connected Components

Take the union of with its adjacent vertices: $\{A, B, H, I\}$




A	B	C	D	E	F	G	H	I	J	K
A	A	C	D	E	F	G	A	A	J	K

Connected Components

As the traversal continues, we take the union of the set $\{G\}$ with the set containing H: $\{A, B, G, H, I\}$


- The traversal is finished



A	B	C	D	E	F	G	H	I	J	K
A	A	C	D	E	F	A	A	A	J	K

Connected Components

Start another traversal with C: this defines a new set {C}




A	B	C	D	E	F	G	H	I	J	K
A	A	C	D	E	F	A	A	A	J	K

Connected Components

We take the union of $\{C\}$ and its adjacent vertex J: $\{C, J\}$


- This traversal is finished



A	B	C	D	E	F	G	H	I	J	K
A	A	C	D	E	F	A	A	A	C	K

Connected Components


We start again with the set $\{D\}$



A	B	C	D	E	F	G	H	I	J	K
A	A	C	D	E	F	A	A	A	C	K

Connected Components

K and E are adjacent to D, so take the unions creating $\{D, E, K\}$




A	B	C	D	E	F	G	H	I	J	K
A	A	C	D	D	F	A	A	A	C	D

Connected Components

Finally, during this last traversal we find that F is adjacent to E

- Take the union of $\{F\}$ with the set containing E: $\{D, E, F, K\}$




A	B	C	D	E	F	G	H	I	J	K
A	A	C	D	D	D	A	A	A	C	D

Connected Components

All vertices are visited, so we are done

- There are three connected sub-graphs {A, B, G, H, I}, {C, J}, {D, E, F, K}



A	B	C	D	E	F	G	H	I	J	K
A	A	C	D	D	D	A	A	A	C	D

Summary

This topic covered connectedness

- Determining if two vertices are connected
- Determining the connected sub-graphs of a graph
- Tracking unvisited vertices

References

Wikipedia, [http://en.wikipedia.org/wiki/Connectivity_\(graph_theory\)](http://en.wikipedia.org/wiki/Connectivity_(graph_theory))

These slides are provided for the ECE 250 *Algorithms and Data Structures* course. The material in it reflects Douglas W. Harder's best judgment in light of the information available to him at the time of preparation. Any reliance on these course slides by any party for any other purpose are the responsibility of such parties. Douglas W. Harder accepts no responsibility for damages, if any, suffered by any party as a result of decisions made or actions based on these course slides for any other purpose than that for which it was intended.