

From: TNZ Support support@tnz.co.nz
Subject: Re: Inbound SMS (MO) replies — capability and webhook contract
Date: 31 August 2026 at 5:18 PM
To: Nigel Corbett nzdog1@gmail.com

TS

Hi Nigel,

When we send to a number that's on our account's opt-out list, what does the API return? I'm after the HTTP status code and the response body. We're currently treating any 2xx as a successful send, and I want to be sure a blacklist rejection isn't arriving as a 2xx that we'd record as delivered.

The API will respond 200 to confirm the message has been accepted.

The status reporting (the status GET endpoint and/or the status webhook) will return a delivery failure with Status=Failed and Result=Destination is blacklisted.

Note - you should be working from delivery results and not assuming the API accepting a message means is a successful delivery.

Related — when Destinations contains several numbers and only some are blacklisted, what comes back? Is it a per-destination result, or a single status for the batch?

Webhooks are distributed per destination.

On the shared shortcode: if two of our customers both message the same person, and that person replies, is there anything in the inbound payload that would let us tell which customer the reply relates to? Or is a dedicated shortcode the only way to get that?

The reply is attributed to the last sent message, which is logical if you consider what the person is seeing on their phone.

A dedicated short code could help I suppose, but you'd need to be sending from different short codes for the two customers.

James Dennerly

helpdesk (NZ): +6499293000 **helpdesk (AU):** +61 2 8014 7060 **ddi:** +6499293004
mobile: 027 308 0156 **web:** www.tnz.co.nz



From: Nigel Corbett <nzdog1@gmail.com>
Date: Saturday, 29 August 2026 at 4:47 PM
To: TNZ Support <support@tnz.co.nz>
Subject: Re: Inbound SMS (MO) replies — capability and webhook contract

Hi James,

Thanks — that's exactly what I needed, and the opt-out handling at your layer is good to know.

Three follow-ups, all about the send side rather than inbound:

1. When we send to a number that's on our account's opt-out list, what does the API return? I'm after the HTTP status code and the response body. We're currently treating any 2xx as a successful send, and I want to be sure a blacklist rejection isn't arriving as a 2xx that we'd record as delivered.
2. Related — when Destinations contains several numbers and only some are blacklisted, what comes back? Is it a per-destination result, or a single status for the batch?
3. On the shared shortcode: if two of our customers both message the same person, and that person replies, is there anything in the inbound payload that would let us tell which customer the reply relates to? Or is a dedicated shortcode the only way to get that?

Thanks,
Nigel

On 18 Aug 2026, at 2:30 PM, TNZ Support <support@tnz.co.nz> wrote:

Hi Nigel,

Thanks for getting in touch.

1. Does our account support inbound (mobile-originated) replies? If so, what number do recipients reply to — and is it reply-capable? We're not currently passing a sender/From field on send, so I'd like to confirm what the account defaults to.

Yes - the system automatically allocates a sending number depending on the type of message you send. It'll be a short code number when sending to NZ Mobiles, or a Australian mobile number if sending to Aus Mobiles.

We can set up a [dedicated short code](#) if that's useful.

2. If inbound is supported, what is the webhook payload contract for mobile-originated messages? Specifically the Content-Type and field names. I'm aware of the delivery-receipt callback format (Status, Result, MessageID, Destination, etc.) — I'm asking about the MO contract, which I assume is different.

The SMS Received webhook for v2.04 is here:

<https://www.tnz.co.nz/Docs/RESTAPI/?version=2.04#receive-webhook>

3. How do you authenticate inbound callbacks to our endpoint? Signature header, shared secret, IP allowlist, or none?

The HTTP Headers include:

X-Timestamp="2024-05-01T03:51:42.000Z"

X-Sender="application@domain.com"

Authorization="ta8wr7ymd"

And the callback JSON body includes:

"Sender": "application@domain.com",
...

"APIKey": "ta8wr/ymd",

These values are configured in the TNZ Dashboard under Users -> Your API User -> API -> Reporting

<image.png>

4. Do you suppress STOP / opt-out keywords at your own layer, or is that entirely our responsibility downstream? If you do suppress, what keyword set do you match, and do you still forward the message to us?

By default, the platform automatically detects opt-out keywords and adds these mobiles to your Dashboard's Opt-Out list.

The full message is still passed to you via the webhook.

Future attempts to send to the number fail with "Destination is blacklisted"

More info: <https://www.tnz.co.nz/Help/unsubscribe-option-for-sms-messages>

5. Does inbound work for Australian (+61) recipients as well as New Zealand, or is it NZ-only?

Inbound works for Australia too.

James Dennerly

helpdesk (NZ): +6499293000 **helpdesk (AU):** +61 2 8014 7060
ddi: +6499293004 **mobile:** 027 308 0156 **web:** www.tnz.co.nz



From: Nigel Corbett <nzdog1@gmail.com>

Date: Saturday, 15 August 2026 at 4:36 PM

To: TNZ Support <support@tnz.co.nz>

Subject: Inbound SMS (MO) replies — capability and webhook contract

Hi,

We're using your v2.04 send/sms API for outbound SMS to New Zealand and Australian mobiles. I need to confirm what's available on the inbound side before we go live, and I couldn't find this in the docs.

Our outbound messages include "Reply STOP to opt out", so we need to reliably receive and process those replies.

Five questions:

1. Does our account support inbound (mobile-originated) replies? If so, what number do recipients reply to — and is it reply-capable? We're not currently passing a sender/From field on send, so I'd like to confirm what the account defaults to.

2. If inbound is supported, what is the webhook payload contract for mobile-originated messages? Specifically the Content-Type and field names. I'm aware of the delivery-receipt callback format (Status, Result, MessageID, Destination, etc.) — I'm asking about the MO contract, which I assume is different.

3. How do you authenticate inbound callbacks to our endpoint? Signature header, shared secret, IP allowlist, or none?

4. Do you suppress STOP / opt-out keywords at your own layer, or is that entirely our responsibility downstream? If you do suppress, what keyword set do you match, and do you still forward the message to us?

5. Does inbound work for Australian (+61) recipients as well as New Zealand, or is it NZ-only?

If inbound replies aren't available on our account, could you let me know what would be required to enable them, and any cost or lead time involved.

Thanks,
Nigel Corbett