

A series of overlapping, wavy lines in red, orange, yellow, green, and blue sweep across the middle of the page.

DOCUMENTATION

Administration Interfaces Jahia v6.61

Jahia's next-generation, open source CMS stems from a widely acknowledged vision of enterprise application convergence – web, document, search, social and portal – unified by the simplicity of web content management.

Jahia Solutions Group SA

*9 route des Jeunes,
CH-1227 Les acacias
Genève, Suisse*

<http://www.jahia.com>

Summary

DOCUMENTATION	1
Summary	2
Introduction to the Jahia Administration Center	4
1 Section One: Server Settings	6
1.1 The “Web Project Management”	6
1.1.1 Creating a Web Project	9
1.1.2 Deleting a Web Project	17
1.1.3 Exporting a Web Project	18
1.1.4 Editing Web Project Properties.....	22
1.1.5 Other Site-Related Settings.....	22
1.2 Manage Users	23
1.2.1 Creating a User.....	23
1.2.2 Editing User Properties	24
1.2.3 Removing a User	25
1.2.4 Locking a User	25
1.2.5 Batch-Importing Users	27
1.3 E-mail Settings	29
1.4 Manage Portlets	31
1.5 Edit Super Administrator Properties	33
1.6 Server and Cache Status	34
1.7 Password Policy	40
1.8 Manage Roles	41
1.8.1 Creating a New Role.....	42
1.8.2 Deleting or Copying a Role.....	47
1.8.3 Exporting and Importing Roles	47
1.9 Manage Modules.....	48
1.10 Report a Problem	50

1.11	Jahiapedia.....	50
1.12	About Jahia.....	50
2	Section Two: Site Settings	52
2.1	Manage Groups	54
	Creating a Group.....	55
2.1.1	Adding and Removing Members	56
2.1.2	Removing a Group	60
	Duplicating a Group.....	61
2.2	Manage Languages	62
2.2.1	Options disponibles pour chaque langue	62
2.2.2	Gestion multilingue.....	64
2.3	HTML Settings.....	68
2.4	Display Vanity URL.....	69
2.5	Manage Modules.....	70
2.6	Link Checker.....	70
2.6.1	Auditing External Links with the Link Checker.....	70

Introduction to the Jahia Administration Center

Jahia features a back-office panel designed to manage sites and the overall platform. This interface is called the “Administration Center” or “Admin Center”.

If you have administrative privileges, you can access the Jahia Administration Center:

- by typing the address of your Jahia server directly in your browser, followed by “/administration”
- from your user home page, via the links located at the top right of the screen
- from the toolbars that appear in some of the modes by clicking on “Administration”.

In Edit Mode:



In the Studio:



By default, after install and once a site has been created, Jahia comes with:

- A “root” user: this is the system’s “super user”. It is granted all permissions on the entire platform and can access all of its functionalities for all hosted sites. It is a system user whose rights cannot be altered, even though it is not directly listed in content object permissions. The “root” user is obviously not subject to system permissions control, it has all rights and they cannot be revoked.
- A “Site Administrators” group (site-administrators) for the users in charge of the site, who will have “complete control” over it (writing, workflows etc.) as well as a group of privileged users (site-privileged) for those who need access to the default workspace, used mainly in the Edit and Contribute Modes. This makes it possible to secure accesses. Please note that when a user is given a role that requires access to the default workspace (e.g., an editor role), then the user will be automatically added to this group.

- Finally, site or server administrators can delegate tasks to other users. For instance, the site administrator can grant other users access to user and group management. Of course, these users will be able to access the features defined by the site administrator, and only these features.

The first section of this guide covers the overall platform management features, mainly the creation of Web Projects (sites), users and roles. Most server management features are only available to the Super Administrator (root) account.


The second section covers the management features available for each Web Project created on the platform. These features are used more frequently than the platform management features and they are available to users with the “site administrator” role.

1 Section One: Server Settings

Access to the “Server Settings” tab is normally allowed to the Super Administrator only, since the actions and operations available in this section will affect all the sites hosted on the Jahia server (or cluster).

This section is where you can create users, add portlets or edit the roles available on the platform. This is also where you can list, manage, create or delete virtual sites.

💡 Just like in the “Site Settings” tab, the Super Administrator can grant other users access to one or more panels available in this section. This delegation option can be found in the “Manage Roles” panel.



1.1 The “Web Project Management”

You can create multiple Web projects (or “virtual sites”) within a single Jahia server. Each site will have its own set of pages, contents, files etc.

However, the notion of “virtual site” in Jahia does not refer to straightforward physical sharing of the platform but rather to the possibility of creating separate “virtual spaces”.

Each site can have:

- its own domain (i.e., you can choose to manage one site on www.domain-a.com and another site on www.domain-b.com, while hosting both on the same Jahia server),

- its own site map along with its own structure,
- its own groups (i.e., you can have two separate “Authors” groups with different members for site A and site B)
- its own settings (please see the features described in section two)

However, each site shares the following with the other sites:

- the same database and API: this makes it possible to access content objects available in other virtual sites. This means that identical contents can be easily re-used across multiple sites (e.g., news items that are the same for several departments with separate sites), although security issues may arise with shared platforms (e.g., the sites of two separate companies are hosted on the same server).
- the same sets of templates (for the sites that share the same set of templates).
- the same modules
- the same category tree
- the same users (LDAP or Jahia users: it is not possible for two separate users (e.g., John) to have the same ID between two sites. LDAP groups, like LDAP users, are also common to all sites.)

Creating a new virtual site is useful when a company needs to manage multiple Web projects (e.g., a public Website, one or more Extranets and several department Intranets). The concept of virtual sites allows for better role assignment and makes it possible to use different views (sitemap, themes, search results...) or URLs/domains for different sites, while keeping the ability to share contents, users or mashups.

Web Project List

Server settings | Web project settings: Site des partenair | Go to Studio | Go to Edit Mode | My Space | Logout | English

Main Menu

- Web Project management
- Manage users
- E-mail settings
- Manage portlets
- Edit Super Administrator Properties
- Server and Cache status
- Password policy
- Manage roles
- Manage modules
- Report a problem
- Documentation
- About Jahia

Web Project management

Create | Export | Export (Staging content) | Delete

Web Project List (2)

	Name	Web Project key	Web project host name	Template set	Action
<input type="checkbox"/>	ACME-SPACE	ACME-SPACE	localhost	Jahia Web Templates Space	
<input checked="" type="checkbox"/>	Site des partenaires	partenaires	www.partenaires-jahia.com	Jahia Intranet Templates	

System Site

Export

Use prepackaged project

Please select the project to be imported: ACME Space Website Demo 6.6 Proceed

Import archive

Please select the file to import : Choisissez un fichier | Aucun fichier choisi

Or give the path of an import file on the server : Import file

[Back to menu](#)

You can access the list of all existing Web projects from this interface.

The default Web project is the one with a green check mark next to it. Action icons to edit, delete or export a site are displayed at the end of each line.

1.1.1 Creating a Web Project

If the platform does not contain any site yet (which is unlikely on a production server, since development teams usually deliver a readily usable environment), Jahia has a dedicated settings screen to create a new Web project.

Web Project List

Server settings | Site settings: System Site | Go to Studio | Go to Edit Mode | My Space | Logout | English

Main Menu

- Web Project management
- Manage users
- E-mail settings
- Manage portlets
- Edit Super Administrator Properties
- Server and Cache status
- Password policy
- Report a problem
- Jahiapedia
- About Jahia

Web Project management

Create a new Web Project [Create a new Web Project](#)

Use prepackaged demo project (will be used as default)

Please select the demo to be imported: ACME Website Demo 6.5 [Proceed](#)

Import archive

Please select the file to import: [Parcourir...](#)

Or give the path of an import file on the server: [Import file](#)

[Back to menu](#)

© Copyright 2002-2011 Jahia Solutions Group SA - All rights reserved. Jahia 6.5.0.0 r38098

If there are already sites on the platform, a slightly different interface is displayed, although with the same options.

Web Project List

Server settings | Web project settings: System Site | Go to Studio | Go to Edit Mode | My Space | Logout | English

Main Menu

- Web Project management
- Manage users
- E-mail settings
- Manage portlets
- Edit Super Administrator Properties
- Server and Cache status
- Password policy
- Manage roles
- Manage modules
- Report a problem
- Documentation
- About Jahia

Web Project management

Create | Export | Export (Staging content) | Delete

Web Project List (1)

	Name	Web Project key	Web project host name	Template set	Action
<input type="checkbox"/>	ACME-SPACE	ACME-SPACE	localhost	Jahia Web Templates Space	

System Site

Export

Use prepackaged project

Please select the project to be imported: ACME Space Website Demo 6.6 Proceed

Import archive

Please select the file to import : Choisissez un fichier | Aucun fichier choisi

Or give the path of an import file on the server : Import file

Back to menu

There are three different ways to create a site. This documentation will only cover the first one in detail, since the second method is mostly used for training purposes and the third one to restore a site backup or to transfer a site from one server to another.

1.1.1.1 Creating a Web Project from Scratch

Step 1

Manage Web Projects

Server settings | Web project settings: System Site | Go to Studio | Go to Edit Mode | My Space | Logout | English

Main Menu

- Web Project management
- Manage users
- E-mail settings
- Manage portlets
- Edit Super Administrator Properties
- Server and Cache status
- Password policy
- Manage roles
- Manage modules
- Report a problem
- Documentation
- About Jahia

New Web Project properties Step 1 / 3

Web project title*
eg. My Web Site : Partners site

Web project host name*
eg. www.mywebsite.com : www.jahiapartners.com

Web Project key*
eg. mywebsite : partners
The Web project key appears in the URL and cannot be changed

Web project description : Extranet for our partners

Set as the default Web Project ☐

2. Administrator account

☒ Don't create any administrator

☐ Create a new user.

Back to Web Project list | Next step

Web project title: the value entered in this field will be used in various parts of the Jahia interface to designate the site. This value can be changed later on.

Web project name: the name of the domain where this site will be located. If the site you are creating is not going directly into production but is rather used as a test or development site, then leave *localhost* in the field, as this value can be properly configured on the production server later on. If in doubt, always leave the *localhost* value and ask an administrator or a hosting specialist. This value can be changed later on.

Web project key: the name of the root node of the site. This name will appear in the default URLs, since all pages and site contents will be stored under it. Therefore, it is recommended to enter a short and descriptive title. You will not be able to change this value later on, so make sure to choose it wisely.

Web project description: this informative field is used to add details about the site. This value can be changed later on.


Set as the default Web project: if this box is checked and the platform hosts several sites, visitors will be redirected to this site when they access the server without indicating the desired site. This value can be changed later on.

Don't create any administrator: no administrator account will be created for this Web project. Users with sufficient rights (including the "root" account of course) will be able to manage the site. It is recommended to use this option for platforms with multiple sites managed by a single Webmaster or with several Webmasters working on all sites.

Create a new user: using this option will create a user account with all permissions on the current site. This option is relevant if the site is going to have a specific Webmaster. If the Webmaster uses the "root" account or if a dedicated user account already exists (in Jahia or an enterprise directory), then it is not necessary to create a new account.

Once these fields have been filled, click on the "Next Step" button to select the site's template and default language.

Step 2



Please choose a template set: select the desired template set in this drop-down menu. If the template set has a preview image, it will be displayed in the area below the menu to facilitate its visual identification.

Choose modules: by default all web projects benefits from components/features that are part of the core software (*default* module). Modules listed in this screen are the ones deployed on the Jahia platform (the war files has been deployed) that can be optionally activated on the project you are creating. Each module listed here can provide new content types or new features usable by editors.

Note: when administrator creates a new site, developers or the project responsible is supposed to have given them previously the list of modules to be activated. If this is not the case, modules may be deployed later through the Studio (development or staging platforms) or through the “Manage Modules” panel in the Server Settings section of the Administration if it is a Production platform (when Production Mode is activated the Studio is not available).

Select the Web project default language: this drop-down list contains languages and their local variants. In the case of a multilingual site, select the language considered as the most important. Visitors will be redirected to this language if they try accessing the site without specifying the desired language.

Click on the “Next Step” button.

Step 3

The next screen displays a summary of all previously entered information in order to perform a last check before creating the Web project. If an error is detected, it is possible to return to the beginning of the creation process to modify the erroneous value. The information submitted on each screen is kept in memory until the user session expires, so there will be no need to re-type everything.

Manage Web Projects

Server settings | Web project settings: System Site | Go to Studio | Go to Edit Mode | My Space | Logout | English

Main Menu


- Web Project management
- Manage users
- E-mail settings
- Manage portlets
- Edit Super Administrator Properties
- Server and Cache status
- Password policy
- Manage roles
- Manage modules
- Report a problem
- Documentation
- About Jahia

Create your Web Project Step 3 / 3

Web Project properties	
Web Project key	partners
Web project title	Partners site
Web project host name	www.jahiapartners.com
Set as default site	No
Web project description	Extranet for our partners
Template set	templates-intranet
Modules	Jahia Article, Jahia Contact, Jahia Content retrieval, Jahia Event, Jahia News, Jahia Search, Jahia Sitemap, Jahia Skins
Theme	--
Language	English

Back to Web Project list | Create your Web Project

If all the information is correct, click on the “Create your Web Project” button. A floating box will appear while the server is working and disappear once the site has been created successfully.



Understanding Jahia: Why does it take some time to create a Web project?

Even though a new Web project seems almost empty, the creation process implies more than just creating a root node with the defined settings. Most of the processing time is actually spent copying the selected template set under the root node and assigning all the necessary permissions.

Once the site has been created, you are redirected to the main menu of the “Web Project Management” panel, where the new site should now be listed.

Web Project List

Server settings | Web project settings: Partners site | Go to Studio | Go to Edit Mode | My Space | Logout | English

Main Menu

- Web Project management
- Manage users
- E-mail settings
- Manage portlets
- Edit Super Administrator Properties
- Server and Cache status
- Password policy
- Manage roles
- Manage modules
- Report a problem
- Documentation
- About Jahia

Web Project management

Create | Export | Export (Staging content) | Delete

Web Project List (2)

	Name	Web Project key	Web project host name	Template set	Action
<input type="checkbox"/>	ACME-SPACE	ACME-SPACE	localhost	Jahia Web Templates Space	
<input type="checkbox"/>	Partners site	partners	www.jahiapartners.com	Jahia Intranet Templates	

System Site

Export

Use prepackaged project

Please select the project to be imported: ACME Space Website Demo 6.6 Proceed

Import archive

Please select the file to import : Choisissez un fichier. Aucun fichier choisi

Or give the path of an import file on the server : Import file

[Back to menu](#)

For direct access to the newly-created site, click on the “Go to Edit Mode” tab. You are redirected to the first page of the site. This page is more or less empty depending on the selected template set, but it is ready to be filled, as shown in the Editor’s Guide.

1.1.1.2 Using a Prepackaged Demo Project

This option can be used to create a new site containing ready-made pages and contents (typically, examples provided by Jahia as a demo): in the drop-down list, select the desired Web project and click on the “Proceed” button. In the next screen, provide the Web project’s title, domain name and unique identifier for default URLs, then click on the “Import” button.

Manage Web Projects

Server settings | Web project settings: Partners site | Go to Studio | Go to Edit Mode | My Space | Logout | English

Main Menu

- Web Project management
- Manage users
- E-mail settings
- Manage portlets
- Edit Super Administrator Properties
- Server and Cache status
- Password policy
- Manage roles
- Manage modules
- Report a problem
- Documentation
- About Jahia

Web Project variables


Name	
<input checked="" type="checkbox"/> Shared content: users.zip	
Web project title*	ACME
Web project host name*	localhost
<input checked="" type="checkbox"/> Web Project key*	ACME
Please choose a template set	templates-web-blue

Back to menu | Import

1.1.1.3 Importing a Previously Exported Web Project

This option makes it possible to select a .zip file from a previous exportation on a local hard drive. The exportation will have been carried out via the dedicated Jahia interface (see further down). A new Web project will be created, with the exact same settings and contents as the exported site.

1.1.2 Deleting a Web Project

To delete a single Web project, click on the corresponding red icon . Be aware that this action cannot be undone: it is highly recommended to export the site before deleting it.

Web Project List

Server settings | Web project settings: Partners site | Go to Studio | Go to Edit Mode | My Space | Logout | English

Main Menu

- Web Project management
- Manage users
- E-mail settings
- Manage portlets
- Edit Super Administrator Properties
- Server and Cache status
- Password policy
- Manage roles
- Manage modules
- Report a problem
- Documentation
- About Jahia

Web Project management

Create | Export | Export (Staging content) | Delete

Web Project List (2)

	Name	Web Project key	Web project host name	Template set	Action
<input type="checkbox"/>	ACME-SPACE	ACME-SPACE	localhost	Jahia Web Templates Space	
<input type="checkbox"/>	Partners site	partners	www.jahiapartners.com	Jahia Intranet Templates	

System Site

Export

Use prepackaged project

Please select the project to be imported: ACME Space Website Demo 6.6 | Proceed

Import archive

Please select the file to import: Choisissez un fichier | Aucun fichier choisi

Or give the path of an import file on the server: | Import file

Back to menu

To delete multiple Web projects, check the corresponding boxes, then click on the “Delete Selected Web Projects” button.

1.1.3 Exporting a Web Project

Several situations can require exporting a Web project:

- Backup: an exported site can be imported back in the exact same state as it was. However, this solution requires a manual intervention by an administrator and in no case should be considered a reliable backup method.
- Transfer to another server: can be used to duplicate a site at specific times to work on another server, to run tests, to use as a basis to start new projects etc.
- Transfer from a development server to a production server: it can be convenient to export a project that was completed and pre-filled with content in a development environment and then import it on its future production server.

Web Project List

Server settings | Web project settings: Partners site | Go to Studio | Go to Edit Mode | My Space | Logout | English

Main Menu

- Web Project management
- Manage users
- E-mail settings
- Manage portlets
- Edit Super Administrator Properties
- Server and Cache status
- Password policy
- Manage roles
- Manage modules
- Report a problem
- Documentation
- About Jahia

Web Project management

Create | Export | Export (Staging content) | Delete

Web Project List (2)

	Name	Web Project key	Web project host name	Template set	Action
<input type="checkbox"/>	ACME-SPACE	ACME-SPACE	localhost	Jahia Web Templates Space	
<input type="checkbox"/>	Partners site	partners	www.jahiapartners.com	Jahia Intranet Templates	

System Site

Export

Use prepackaged project

Please select the project to be imported: ACME Space Website Demo 6.6 Proceed

Import archive

Please select the file to import : Choisissez un fichier | Aucun fichier choisi

Or give the path of an import file on the server : Import file

Back to menu

You have the choice to export the staging version (default workspace) or both the staging and published version (live workspace).

To export staging version of a single web project web site only, use the icon in front of its name.

To export staging version only of multiple web sites, use checkboxes and the “export (staging content)” button.

Web Project List

Server settings | Web project settings: Partners site | Go to Studio | Go to Edit Mode | My Space | Logout | English









Main Menu

- Web Project management
- Manage users
- E-mail settings
- Manage portlets
- Edit Super Administrator Properties
- Server and Cache status
- Password policy
- Manage roles
- Manage modules
- Report a problem
- Documentation
- About Jahia


Web Project management

Create | Export | **Export (Staging content)** | Delete


Web Project List (2)

	Name	Web Project key	Web project host name	Template set	Action
<input type="checkbox"/>	ACME-SPACE	ACME-SPACE	localhost	Jahia Web Templates Space	   
<input type="checkbox"/>	Partners site	partners	www.jahiapartners.com	Jahia Intranet Templates	   

System Site


Export 

Use prepackaged project

Please select the project to be imported: ACME Space Website Demo 6.6  Proceed

Import archive

Please select the file to import : Choisissez un fichier | Aucun fichier choisi

Or give the path of an import file on the server :  Import file

[Back to menu](#)

To export staging and published version of a single Web project, click on the corresponding export icon  on the right.

To export staging and published version of multiple Web projects, check the corresponding boxes, then click on the “Export selected Web Projects” button.

Web Project List

Server settings | Web project settings: Partners site | Go to Studio | Go to Edit Mode | My Space | Logout | English

Main Menu

- Web Project management
- Manage users
- E-mail settings
- Manage portlets
- Edit Super Administrator Properties
- Server and Cache status
- Password policy
- Manage roles
- Manage modules
- Report a problem
- Documentation
- About Jahia

Web Project management

Create | **Export** | Export (Staging content) | Delete

Web Project List (2)

	Name	Web Project key	Web project host name	Template set	Action
<input type="checkbox"/>	ACME-SPACE	ACME-SPACE	localhost	Jahia Web Templates Space	
<input type="checkbox"/>	Partners site	partners	www.jahiapartners.com	Jahia Intranet Templates	

System Site

Export

Use prepackaged project

Please select the project to be imported: ACME Space Website Demo 6.6 Proceed

Import archive

Please select the file to import : Choisissez un fichier | Aucun fichier choisi

Or give the path of an import file on the server : Import file

[Back to menu](#)

The system policy site can also be exported (but not deleted, renamed or modified). This option is useful if, for instance, shared content has been stored here to make it usable from all sites.

Web Project List

Server settings | Web project settings: Partners site | Go to Studio | Go to Edit Mode | My Space | Logout | English

Main Menu

- Web Project management
- Manage users
- E-mail settings
- Manage portlets
- Edit Super Administrator Properties
- Server and Cache status
- Password policy
- Manage roles
- Manage modules
- Report a problem
- Documentation
- About Jahia

Web Project management

Create | Export | Export (Staging content) | Delete

Web Project List (2)

	Name	Web Project key	Web project host name	Template set	Action
<input type="checkbox"/>	ACME-SPACE	ACME-SPACE	localhost	Jahia Web Templates Space	
<input type="checkbox"/>	Partners site	partners	www.jahiapartners.com	Jahia Intranet Templates	

System Site

Export

Use prepackaged project

Please select the project to be imported: ACME Space Website Demo 6.6 Proceed

Import archive

Please select the file to import : Choisissez un fichier | Aucun fichier choisi

Or give the path of an import file on the server : Import file

[Back to menu](#)

1.1.4 Editing Web Project Properties

To edit a Web project's properties, click on its title. In the next screen, you can edit the following fields:

- Web project title
- Web project name
- Web project description

1.1.5 Other Site-Related Settings

Other settings are available directly in Edit Mode. In the Selector, you can use the contextual menu (right-click) to edit the node for a Website and access additional information and settings. More details can be found in the Webmaster's guide.

The screenshot displays the 'Edit ACME (Virtual site)' interface. At the top, there's a navigation bar with tabs: Content, Layout, Metadata, Tags, Categories, Options, Roles, Usages, Workflow, History, and SEO. The 'HTML settings' section includes checkboxes for 'WCAG Compliance' (checked) and 'Markup Filtering' (unchecked), followed by a 'Tags' input field. The 'Title' section contains a 'System name' field with 'acme' and a checkbox for 'Automatically synchronize name with title', and a 'Title' field with 'ACME'. The 'Virtual site' section includes fields for 'Site title' (ACME Demo site), 'Site server name' (localhost), 'Site description', 'Site ID' (2), 'Installed modules' (templates-web-blue, content-browser), 'Languages' (fr, en), 'Mandatory languages', 'Default language' (en), a checkbox for 'Mix languages when navigating site', 'Templates set' (templates-web-blue), 'j_siteType' (templatesSet), and 'j_dependencies'.

Image 1: virtual site settings available directly in the Edit Mode

1.2 Manage Users

Unlike groups, users are common to the entire system, in order to ensure their uniqueness. Therefore, their configuration can be found in the server settings.

1.2.1 Creating a User

Go to the “Manage users” panel and click on the “Create new user” button.

Manage users

Server settings | Site settings: ACME | Go to Studio | Go to Edit Mode | My Space | Logout | English

Main Menu

- Web Project management
- Manage users
- E-mail settings
- Manage portlets
- Edit Super Administrator Properties
- Server and Cache status
- Password policy
- Report a problem
- Jahiapedia
- About Jahia

Manage users

Create new user | Edit/View selected user properties | Remove selected user | Batch create users

User list

Search:

in: ☒ All properties ☐ Properties

Sort by user name | Sort by lastname

on: ☐ Everywhere ☒ Providers: ☒ jcr

Search

Search results	
guest	Unauthenticated user
jenifer	Farell Jenifer
john	Mac Cormick John
marc	Sanders Marc
max	Dupond Max

The user creation screen will be displayed, where you can enter the properties for the new user:

Create new user

Please fill-in the following input boxes then press Ok.

Note that :

- the User Name should be unique in the site.
- only characters (a..z, A..Z, 0..9, _-., @, (, ')) are valid for the User name.
- the input maximum length is 40 characters.

Username: (required)

First name:

Last name:

E-mail:

Organization:

Disable e-mail notifications: ☒

Preferred language:

Account locked: ☐

Password: (required)

Confirm password: (required)

1.2.2 Editing User Properties

To bring modifications to a user's properties, just double-click on their name. You will be redirected to a screen similar to the user creation screen and you will be able to edit all the properties, except for the user's name.

1.2.3 Removing a User

In the users' list, click on the one you want to delete to select it, then click on the "Remove selected user" button.

Manage users

Create new user Edit/View selected user properties Remove selected user Batch create users

User list

Search:

in: ☒ All properties ☐ Properties

☐ Username ☐ First name ☐ Last name ☐ E-mail ☐ Organization

on: ☐ Everywhere ☒ Providers:

☒ jcr

Sort by user name Sort by lastname

Search results	
guest	Unauthenticated user
jenifer	Farell Jenifer
john	Mac Cormick John
marc	Sanders Marc
max	Dupond Max

Search

1.2.4 Locking a User

It is possible to lock a user account, i.e., to disable their account, which will prevent them from logging in.

Locking an account can be convenient because it blocks the user without destroying their account, i.e., without deleting all the information, documents and contents in their personal directory.

To lock a user, you need to open their properties by double-clicking on their name in the users' list (or by selecting it and clicking on the "Edit/View selected user properties" button). Once the properties are displayed, check the "Account locked" box, then click on the "OK" button.

Starting with Jahia 6.6.1 as soon as an account is blocked, the session is immediately terminated.

View user properties

Server settings | Web project settings: Partners site | Go to Studio | Go to Edit Mode | My Space | Logout | English

Main Menu

- Web Project management
- Manage users
- E-mail settings
- Manage portlets
- Edit Super Administrator Properties
- Server and Cache status
- Password policy
- Manage roles
- Manage modules
- Report a problem
- Documentation
- About Jahia

Edit user

Please fill-in the following input boxes then press Ok.

Username: **jane**

First name:

Last name:

E-mail:

Organization:

Disable e-mail notifications: ☐

Preferred language:

Account locked ☐

Password: (no changes if left blank)

Confirm password: (no changes if left blank)


Group list

privileged	server	(site-privileged, ..
Guest users	server	Public
users	server	Authenticated Users
site-privileged	ACME-SPACE	(site-administrato..

Cancel OK

1.2.5 Batch-Importing Users

Users can be imported into Jahia in batches, using a CSV file.



It must contain at least a username and a password, but it may contain all properties for a user. The CSV fields must imperatively be specified via a header such as this one:

```
j:nodename,j:password,j:firstName,j:lastName
```

```
steven,steven1234,Steven,ACME
```

```
robert, robert1234, Robert, ABME
```

Finally, do not forget to specify the separator before importing, here the “,” character.

Bulk create users

CSV File Aucun fichier choisi

CSV field separator

File format must include a header line with at minimum the columns j:nodename (username) and j:password. You can include any supported user properties as values. Example:

```
j:nodename,j:password,j:firstName,j:lastName  
steven,steven1234,Steven,ACME
```

1.3 E-mail Settings

In this panel, you can edit the settings for the mail server used to send e-mail notifications. These parameters should have been entered previously when installing the Jahia server.

Image 2: the “E-mail Settings” panel

To configure your mail server correctly, start by entering your SMTP server address. Then you can enter the system administrator’s e-mail address. They will receive e-mail notifications if system errors occur. You can also define the e-mail address from which the automatic system-level notifications will originate. Of course, this e-mail address must be recognized and accepted by the SMTP server.

Here is additional information about these settings:

1. “Mail server”: this field contains the e-mail server’s SMTP address. It may contain some advanced properties like:
 - port number: if not using the standard SMTP port (25)
 - username and password: if the SMTP server requires authentication
 - additional properties: in order to enable TLS, for instance.

The value in this field should be formatted as follows:

`<username>:<password>@<smtp-host>:<smtp-port>[Parameter1=Value1,Parameter2=Value2,...]`

All arguments are optional, except `<smtp-host>`. Should you need more details, you will find examples of use further down.

2. The “Mail administrator” field contains one or more e-mail addresses separated by commas. Each of these users will receive system-level notifications (if enabled).

3. Finally, the “Mail from” field will be used as the sender address for the e-mail notifications.

In order to illustrate various possible configurations, here are a few examples of use:

1. The SMTP server does not require authentication and uses standard port 25:

`smtp.acme.com`

2. The SMTP server requires authentication and uses non-standard port 11019:

`username:secret-password@smtp.acme.com:11019`

3. Example for a Gmail account: the SMTP server requires authentication and TLS is enabled:

`acme@gmail.com: secret-password@smtp.gmail.com:587[mail.smtp.starttls.enable=true]`

4. If necessary, this enables advanced e-mail debugging options in order to see the details of communication with the SMTP server: `smtp.acme.com:25[mail.debug=true]`

Finally, the event notification level option is only used to send notification e-mails about system errors. Only system administrators of the platform are affected by this option (see further up for the list of recipients).

On the other hand, the e-mail server configuration affects all e-mail notifications in Jahia (including workflow notifications for instance) and not only system-level notifications.


1.4 *Manage Portlets*

Jahia supports the JSR168 (Portlet 1.0) and JSR286 (Portlet 2.0) standards natively. Generic portlets can be easily deployed and used within Jahia, which can act as an additional portal server.

A portlet is generally a small Web application that can manage several instances. For example, an administrator can deploy a generic portlet such as an “RSS Portlet”, used to read and display an RSS feed. This generic portlet can then be used in several pages or even sites to display totally different RSS feeds. Jahia will process each feed as an instance of the portlet. Each instance is saved and considered as a “mashup” available in the application.

The generic portlet is deployed and managed directly from this section of the administration center. The Super Administrator can then define which users are allowed to create new instances from this portlet (e.g., new RSS feeds). Each of these instances can then be assigned different user-specific rights. This method allows the administrator to define who can add feeds and who can place them inside a page in a specific site. This system only makes sense if the administrator wishes to keep control over the “mashup instances” that are generated. If not, just add the “users” group (all identified users) to each portlet and then each user will be free to create as many instances of the portlet as they want.

To learn how to develop new portlets or how to deploy an existing portlet in your Jahia environment, please refer to the online documentation available on www.jahia.com.



Like in the “Web Project Management” panel, you will find in the “Manage Portlets” panel a list of all deployed portlets in the upper part of the main menu. You can click on the available operations and actions next to each portlet to display more details, edit their access rights or display their usage list.

To deploy a portlet in Jahia’s default Tomcat application server, a developer will need to edit a configuration file provided with the portlet. Click on the “?” button to display a description of this operation. It can also be done automatically by clicking on the “Prepare portlet for deployment” or “Prepare and deploy portlets” button.

Deploy new portlets

Portlets WAR file:

If you use an application server other than Tomcat, you must perform this operation manually and deploy the portlets as specified in the documentation of your application server.

1.5 Edit Super Administrator Properties

As the Super Administrator, you can edit your own user properties (name, password, e-mail...) at any time.

View user properties

[Logout](#)
English

Main Menu

- Web Project management
- Manage users
- E-mail settings
- Manage portlets
- Edit Super Administrator Properties**
- Server and Cache status
- Password policy
- Report a problem
- Jahiapedia
- About Jahia

Edit user

Please fill-in the following input boxes then press Ok.

Username **root**

First name

Last name

E-mail

Organization

Disable e-mail notifications ☐

Preferred language

Password (no changes if left blank)

Confirm password (no changes if left blank)

Group list

site-privileged	ACME	{jenifer, site-adm..
users	server	Authenticated Users
site-administrators	My Site	{root}
site-administrators	ACME	{root, max}
administrators	server	{root}
site-privileged	System site	{site-administrato..

Once you have updated the desired information, click on the “OK” button.

1.6 Server and Cache Status

In this panel, the Super Administrator can find information about the various system parameters available from their Jahia server and they can monitor (and flush) the various cache levels managed by the application.

Server and cache status


The first line of this screen allows to launch a complete export of all parameters of the system in one click (thread dump, caches, environment...).



Cache

This panel allows to visualize the current state of all cache layers, front-end and back-end and to verify their level of efficiency.

The three buttons at the top of the panel launch a purge of the following caches



- Frontal caches : all the HTML cache fragments
- Back-end : hibernate caches
- Both at the same time

To purge more selectively the back-end caches, the end of the panel list each one of them.

Be careful: a cache purge is not a trivial action in term of data coherence, stability and performances.

Flushing front caches (HTML fragments) will oblige the platform to regenerate each fragment as soon as a content item is requested by a user and may imply a heavy CPU overload. Such flushing should never be done on a production platform unless you perfectly master the consequences and how the software will react, especially if your server is already facing a heavy charge.

Ehcache Statistics (Enable all statistics / Disable all statistics)	
ApplicationCache: Application cache for portlet definitions 2 entries Successful cache hits: 0 / 1 total, Efficiency: 0.00 % Statistics: enabled (accuracy: Best Effort) Disable Statistics	Flush
ApplicationContextCache: Applications context cache 1 entry Successful cache hits: 0 / 1 total, Efficiency: 0.00 % Statistics: enabled (accuracy: Best Effort) Disable Statistics	Flush
ApplicationEntryPointCache: Applications entry point cache 0 entries Successful cache hits: 0 / 0 total, Efficiency: 0.00 % Statistics: enabled (accuracy: Best Effort) Disable Statistics	Flush
FileContentCache: File cache 0 entries Successful cache hits: 0 / 11 total, Efficiency: 0.00 % Statistics: enabled (accuracy: Best Effort) Disable Statistics	Flush
FileLastModifiedCache: File last modified cache 11 entries Successful cache hits: 38 / 49 total, Efficiency: 77.55 % Statistics: enabled (accuracy: Best Effort) Disable Statistics	Flush
HTMLCache: HTML output cache 0 entries Successful cache hits: 0 / 0 total, Efficiency: 0.00 % Statistics: enabled (accuracy: Best Effort) Disable Statistics	Flush
HTMLDependenciesCache: HTML output dependencies cache 0 entries Successful cache hits: 0 / 70278 total, Efficiency: 0.00 % Statistics: enabled (accuracy: Best Effort) Disable Statistics	Flush
HTMLNodeUsersACLs: Node-user ACLs cache 0 entries Successful cache hits: 1 / 4 total, Efficiency: 25.00 % Statistics: enabled (accuracy: Best Effort) Disable Statistics	Flush
HTMLREGEXPDependenciesCache: HTML output dependencies (regexp) cache 0 entries Successful cache hits: 0 / 0 total, Efficiency: 0.00 % Statistics: enabled (accuracy: Best Effort) Disable Statistics	Flush
HTMLRequiredPermissionsCache: Required permissions cache 1 entry Successful cache hits: 1 / 2 total, Efficiency: 50.00 % Statistics: enabled (accuracy: Best Effort) Disable Statistics	Flush
JCRGroupCache: Group cache (JCR provider) 14 entries Successful cache hits: 10122 / 10166 total, Efficiency: 99.57 % Statistics: enabled (accuracy: Best Effort) Disable Statistics	Flush
JCRGroupMembershipCache: User-group membership cache (JCR provider) 2 entries Successful cache hits: 436 / 444 total, Efficiency: 98.20 % Statistics: enabled (accuracy: Best Effort) Disable Statistics	Flush
JCRUserCache: User cache (JCR provider) 6 entries Successful cache hits: 7045 / 7130 total, Efficiency: 98.81 % Statistics: enabled (accuracy: Best Effort) Disable Statistics	Flush

Hibernate statistics can be activated if necessary, through this panel

Hibernate Statistics
Enable Statistics

If Hibernate statistics are activated the panel will expand to display those statistics.

Statistiques Hibernate					
Number of opened session: 0		Number of closed session: 0			
Number of query cache hits: 0	Number of query cache miss: 0	Number of query cache put: 0	Number of query execution: 0	Max time for query execution in ms: 0	
Number of second level cache hits: 0		Number of second level cache miss: 0		Number of second level cache put: 0	
Names of second level caches:	Cache hits	Cache miss	Cache put	Size In Memory	
org.hibernate.cache.StandardQueryCache	0	0	0	875900	
org.hibernate.cache.UpdateTimestampsCache	0	0	0	0	
org.jahia.services.history.HistoryEntry	0	0	0	0	
org.jbpm.pvm.internal.history.model.HistoryActivityInstanceImpl	0	0	0	0	
org.jbpm.pvm.internal.history.model.HistoryDetailImpl	0	0	0	0	
org.jbpm.pvm.internal.history.model.HistoryProcessInstanceImpl	0	0	0	1405	
org.jbpm.pvm.internal.history.model.HistoryTaskImpl	0	0	0	0	
org.jbpm.pvm.internal.history.model.HistoryVariableImpl	0	0	0	3951	
org.jbpm.pvm.internal.id.PropertyImpl	0	0	0	1132	
org.jbpm.pvm.internal.identity.impl.GroupImpl	0	0	0	0	
org.jbpm.pvm.internal.identity.impl.MembershipImpl	0	0	0	0	
org.jbpm.pvm.internal.identity.impl.UserImpl	0	0	0	0	
org.jbpm.pvm.internal.job.JobImpl	0	0	0	0	
org.jbpm.pvm.internal.model.ExecutionImpl	0	0	0	1380	
org.jbpm.pvm.internal.repository.DeploymentImpl	0	0	0	4884	
org.jbpm.pvm.internal.repository.DeploymentImpl.objectProperties	0	0	0	4572	
org.jbpm.pvm.internal.repository.DeploymentImpl.resources	0	0	0	4488	
org.jbpm.pvm.internal.repository.DeploymentProperty	0	0	0	19722	
org.jbpm.pvm.internal.task.ParticipationImpl	0	0	0	2520	
org.jbpm.pvm.internal.task.SwimlaneImpl	0	0	0	0	
org.jbpm.pvm.internal.task.TaskImpl	0	0	0	1473	
org.jbpm.pvm.internal.type.Variable	0	0	0	12505	
Number of entity load count: 0	Number of entity fetch count: 0	Number of entity insert count: 0	Number of entity update count: 0	Number of entity delete count: 0	
Names of entity	Loaded	Fetches	Inserted	Updated	Deleted
org.jahia.hibernate.model.JahiaDbTest	0	0	0	0	0
org.jahia.services.history.HistoryEntry	0	0	0	0	0
org.jbpm.pvm.internal.history.model.HistoryActivityInstanceImpl	0	0	0	0	0
org.jbpm.pvm.internal.history.model.HistoryAutomaticInstanceImpl	0	0	0	0	0
org.jbpm.pvm.internal.history.model.HistoryCommentImpl	0	0	0	0	0

That statistical information can be useful on punctual basis in order to audit the system. They shouldn't be activated all the time on a production server.









Memory

Memory	
Maximum JVM Memory allowed :	1013 MB (1037376 KB)
Total JVM Memory used :	1013 MB (1037376 KB)
Free Memory :	790 MB (809277 KB)
 Run Garbage Collector	

This panel provides information about allocated memory, used memory and free memory.

It is possible to run the garbage collector to flush the memory in use (warning: the consequences of a forced memory flush on a production site can severely alter performance and only administrators with a thorough knowledge of application servers and JVM operation should use this option)

Thread Dump

Thread Dump	
 Perform thread dump (view in a new browser window)	
 Perform thread dump (download as a file)	
 Perform thread dump (System.out)	
 Perform thread dump (File)	
 Perform thread dump (multiple to a file) Count: <input type="text" value="10"/> Interval: <input type="text" value="10"/> seconds	
 Thread Monitor is started - Stop thread Monitor	
 Error File Dumper is started - Stop Error Dumper	
 Launch Thread Dump Analyzer	

This panel offers various options to run a thread dump and get the results

- In a new window of the browser
- In a downloadable file

- In the Java console
- In a file automatically stored on disk [Jahia install directory]/temp/Jahia-threads
- Perform a thread dump to analyze the currently running threads. A Thread Dump Analyzer is also available in this sub-section.
- Several dumps at a regular interval stored on disk

It is possible to stop Thread Monitoring and File Error Dumper. Those two features running in background and are in charge to dump as many information as possible when an error occurs. While very useful for support, those options should be deactivated on platforms submitted to heavy load, as those features themselves are resources intensive when they are called. If your platform encounters errors due to overload, those options will make things worse by adding load to the load.

The last line of that section refers to the launch of a thread analyzer tool.

System information

The last sub-section contains information about the system and environment where Jahia is running (OS, JVM, install path, database...).

System information	
java.vendor	Sun Microsystems Inc.
jahia.license	
jahia.jackrabbit.consistencyFix	false
sun.java.launcher	SUN_STANDARD
catalina.base	/home/jahia/install/jahia
sun.management.compiler	HotSpot 64-Bit Tiered Compilers
catalina.useNaming	true
os.name	Linux
sun.boot.class.path	/usr/java/jdk1.6.0_26/jre/lib/resources.jar:/usr/java/jdk1.6.0_26/jre/lib/rt.jar:/usr/java/jdk1.6.0_26/jre/lib/sunrsasign.jar:/usr/java/jdk1.6.0_26/jre/lib/jsse.jar:/usr/java/jdk1.6.0_26/jre/lib/jce.jar:/usr/java/jdk1.6.0_26/jre/lib/charsets.jar:/usr/java/jdk1.6.0_26/jre/lib/modules/jdk.boot.jar:/usr/java/jdk1.6.0_26/jre/classes
java.util.logging.config.file	/home/jahia/install/jahia/conf/logging.properties
java.vm.specification.vendor	Sun Microsystems Inc.
java.runtime.version	1.6.0_26-b03
user.name	jahia
shared.loader	
tomcat.util.buf.StringCache.byte.enabled	true
user.language	en
java.naming.factory.initial	org.apache.naming.java.javaURLContextFactory
derby.system.home	/home/jahia/install/jahia/webapps/ROOT/WEB-INF/var/dbdata
sun.boot.library.path	/usr/java/jdk1.6.0_26/jre/lib/amd64
webapp.root	/home/jahia/install/jahia/webapps/ROOT/
jahiaWebAppRoot	/home/jahia/install/jahia/webapps/ROOT/
java.version	1.6.0_26
java.util.logging.manager	org.apache.juli.ClassLoaderLogManager
user.timezone	Europe/Zurich
java.net.preferIPv4Stack	true
sun.arch.data.model	64
java.endorsed.dirs	/home/jahia/install/jahia/endorsed

1.7 Password Policy

The “Password Policy” panel is designed to manage the rules that will secure the users’ authentication data. Settings such as the minimum password length, the requirement for special characters, the obligation to change password after a certain time etc. can be adjusted from this menu.

Manage password policy

Server settings | Web project settings: Partners site | Go to Studio | Go to Edit Mode | My Space | Logout | English

Main Menu

- Web Project management
- Manage users
- E-mail settings
- Manage portlets
- Edit Super Administrator Properties
- Server and Cache status
- Password policy**
- Manage roles
- Manage modules
- Report a problem
- Documentation
- About Jahia

Password policy

Active	Name	Parameters
<input type="checkbox"/>	Do not allow users to change their passwords	
<input checked="" type="checkbox"/>	Minimum password length	length: <input type="text" value="6"/>
<input type="checkbox"/>	Maximum password length	length: <input type="text" value="64"/>
<input type="checkbox"/>	Number of digits required	count: <input type="text" value="1"/>
<input type="checkbox"/>	Number of special characters required	count: <input type="text" value="1"/> characters: <input type="text" value="_*-8\$!@"/>
<input type="checkbox"/>	Prevent using password similar to the user name	
<input type="checkbox"/>	Prevent password reuse. Remember last passwords	count: <input type="text" value="3"/>



It is important to note that the password policy only applies to local Jahia users and not to LDAP or Active Directory users, which are managed directly on these remote servers and subjected to their own rules.

1.8 Manage Roles

The permissions management system (the ability to access certain pages, to write, to use certain tools etc.) relies on combinations of permissions that define a role.

Manage roles

Server settings | Site settings: ACME | Go to Studio | Go to Edit Mode | My Space | Logout | English

Main Menu

- Web Project management
- Manage users
- E-mail settings
- Manage portlets
- Edit Super Administrator Properties
- Server and Cache status
- Password policy
- Manage roles**
- Report a problem
- Documentation
- About Jahia

Manage roles

Delete : editor

Name
contributor
editor
editor-in-chief
jahiapp-user
owner
privileged
reader
reviewer

Content | **Permissions**

	editor
permissions	<input type="checkbox"/>
actions	<input type="checkbox"/>
admin	<input checked="" type="checkbox"/>
contributeMode	<input checked="" type="checkbox"/>
docAccess	<input type="checkbox"/>
editMode	<input type="checkbox"/>


Save


By default, Jahia comes with permissions for repositories, i.e. read/write permissions to the live or default (Edit) workspaces, permissions to restrict access to management sections or permissions to manage access to the Contribute, Edit and Studio Modes. However, every panel deployed in Jahia can add its own permissions to implement its own access control. For example, this is the case for the blog platform or for comments, which define permissions allowing the creation of comments or blog entries directly in Live Mode. Finally, some operations in Jahia will generate permissions automatically, such as the deployment of portlets or templates, making it possible to manage the way these elements are used in the system.

The combination of several permissions defines a role. For instance, a translator role will need the permissions to access the Edit Mode and to edit contents in Edit Mode in a specific language, but not the permission to create any! An editor role, in charge of validating contents, will have the publish permission and the read permission to the Edit Mode, but not the write permission because they are only here to validate! And so on... You are free to create your own roles to meet your particular needs, e.g., a “blogger” role.

These roles can then be assigned to user groups or users for all or part of a site directly via the Edit Mode.

1.8.1 Creating a New Role

Click on the  button at the top left to create a new role. A pop-up window appears, where you can enter the system name for the role.



Once you have clicked on OK, the list of roles is updated and you can now select the new role with a single click to edit it:

Manage roles

Delete : my-role

Name
contributor
editor
editor-in-chief
jahiapp-user
my-role
owner
privileged
reader

Content

Permissions

Title

System name:

my-role

Automatically synchronize name with title: ☐

Title

Copy to all languages

Description

Save

Title and description


A role is first defined by a system-name, but can have an internationalized title (this title will be used in most GUI prior to the system-name). It is also possible to add a description for this role, in multiple languages.

Node types

It is possible to define node types (content types) in which a role can be applied. By default, a role can be granted to a user or group on any type of content type. By selecting specific types of content, the role in question appear in the access rights management interfaces for these types of content and will not be available for others types. This prevents Access Rights management interfaces from being overloaded and

from confusing users by making available roles that would have strictly no effects on the targeted object.

Node types:

External link on Image (Multi-Language)	   	
Facets list		
FAQ entry		
Field facet		
Fieldsets list		
File reference		

Automatic access to content in edit mode

This role grants read rights on default workspace, users will be placed in site-privileged group:

☐ This role grants read rights on default workspace, users will be placed in site-privileged group

If the role you’ve created requires read access to the default workspace (i.e to read content via the Contribute Mode, the Edit Mode or the Studio) you must check the box. When this box is checked, any user that will be associated with this role will be automatically placed in the group "site-privileged", which grants read-access to the default workspace.

Roles Group

This field allows you to define which tab of the “edit engine” this role should appear. By default there are two groups: “Public Roles”, “Edit Roles”.

When a role has permissions on the “Live” workspace only, it is recommended to place it in the group “Public Role”. If the role defines mixed permissions (Live workspace and Default) or edit permissions only (Default workspace), it is recommended to place it in the group “Edit Roles”. By default, the publishers do not see simple editing interfaces in the first tab (Public Role) which allows them to control their content once published, only users with greater rights have access to the “Edit Roles” tab in the Edit mode.

Groupe de rôles:

▼

Once those configurations are completed, it is time to define permissions associated to this new role. Click on the “Permissions” tab.

+

+

+

✗

Delete : my-role

Name

contributor

editor

editor-in-chief

jahiapp-user

my-role

owner

privileged

reader

Content

Permissions

my-role

permissions

actions

admin

contributeMode

docAccess

editMode

☐
☐
☐
☐
☐
☐

Save

Permissions are grouped into categories. When checking a category, all the sub-permissions are selected:


Category	Sub-category	Permission
permissions		<input type="checkbox"/>
actions		<input checked="" type="checkbox"/>
blog		<input checked="" type="checkbox"/>
comments		<input checked="" type="checkbox"/>
contactForm		<input checked="" type="checkbox"/>
default		<input checked="" type="checkbox"/>

The groups of permissions are:

- actions (participate to a blog, leave comments...)
- admin (access settings for various administration items)
- contributeMode (access settings for the Contribute Mode)
- editMode (access settings for the Edit Mode and customization of the Edit Mode)
- job (background jobs management settings)
- managers (access to management UIs: categories, tags, documents, repositories...)
- repository-permissions (read/write/edit permissions on the live and default worspaces)
- studioMode (access rights and customization of the Studio)
- templates (rights for the use of templates available on the platform)
- webapps (rights for the use of portlets or Webapps deployed on the system)
- wokflow-tasks (settings for the workflow steps accessible with the role)
- wysiwyg-editor-toolbar (settings for the type of FCK editor associated with the role)

1.8.2 Deleting or Copying a Role


Common operations such as deleting or copying a role are available in the management interface. Select a role with a single click, then click on the icon matching the action of your choice:



The screenshot shows the 'Manage roles' interface. At the top, there is a toolbar with icons for adding, deleting, and copying roles. The 'Delete : contributor' icon is highlighted with a red box. Below the toolbar is a list of roles: contributor, editor, editor-in-chief, jahiapp-user, my-role, owner, privileged, and reader. The 'contributor' role is selected. Below the list, there are two tabs: 'Content' and 'Permissions'. The 'Content' tab is active, showing a form for the role's details. The form includes a 'Title' section with a 'System name' field (containing 'contributor') and a checkbox for 'Automatically synchronize name with title'. There is also a 'Title' field with a 'Copy to all languages' button. Below the 'Content' tab is a 'Description' section. A 'Save' button is located at the bottom right of the form.

1.8.3 Exporting and Importing Roles

In order to avoid having to configure roles on a series of servers, they can be exported as an XML file or ZIP archive, making it possible to import them on other servers whenever you need it. Importing or exporting roles can be done via two dedicated icons in the “Manage Roles” panel.



1.9 Manage Modules

Modules management and availability (deployment) on any sites of the platform can be performed via the Studio when Jahia is in development mode.

In production mode, the settings of the platform are optimized, and, for security reasons, the Studio is not accessible.

This screen, thus, allows the deployment (add / update) of modules that are available on the platform.

There are three parts to this prompt :

First Part: two roll-down menus to select a specific module

The first roll-down menu features the four main types of modules:




- Jahiapp : A sophisticated module (or assembly of modules) that is meant to deliver a fully fledged web application
- Module : a standard, simple module
- My Space : modules linked to the Jahia user's settings and workspace
- Template set : Layout templates

The second roll-down menu displays the liste of modules that match the type selected in the first menu.



Module	Jahia Article (1.2-SNAPSHOT)
List of sites with this module already deployed	
	Name
List of sites that do not have this module deployed	
	Name
<input type="checkbox"/>	System Site
<input type="checkbox"/>	ACME-SPACE
<input type="checkbox"/>	ACME-REALESTATE
Deploy	Deploy on all sites

Second part: List of sites on which the selected module is already deployed.

When a module selected in the first part is already deployed on one or more sites, they are displayed and a button allows for one-click updating of all sites.

Manage modules	
Module	Jahia Poll (1.2-SNAPSHOT)
List of sites with this module already deployed	
	Name
	ACME-SPACE
 Update all sites already using this template set	
List of sites that do not have this module deployed	
	Name
<input type="checkbox"/>	System Site
<input type="checkbox"/>	ACME-REALESTATE
 Deploy  Deploy on all sites	

Third part: list of sites on which the selected module isn't deployed.

Manage modules	
Module	Jahia FAQ (1.2-SNAPSHOT)
List of sites with this module already deployed	
	Name
List of sites that do not have this module deployed	
	Name
<input type="checkbox"/>	System Site
<input type="checkbox"/>	ACME-SPACE
<input type="checkbox"/>	ACME-REALESTATE
 Deploy  Deploy on all sites	

It is possible to deploy the selected module on all sites of the platform that does not yet have one, or manually select one or more sites on which to perform the deployment.

1.10 Report a Problem

This shortcut redirects you to the Jahia online bug tracking system. Therefore, an Internet connection is required.

There are two bug tracking systems:

- The free online platform available to the Jahia community.
- The Enterprise online platform only available to clients with a valid support contract.

The community system is also designed to collect and follow up on enhancement suggestions. Do not hesitate to send your own ideas to improve the application. As these tickets are public, you should not mention your environment-specific parameters or any other confidential data.

The commercial bug tracking system is only available to clients. Each client has its own personal secure environment only accessible with specific credentials. All tickets submitted through this system are processed by employees of Jahia Solutions Group and subjected to standard confidentiality rules. Tickets are not shared with other customers and every client is guaranteed a response from the editor and a maximum response time.

1.11 Jahiapedia

This shortcut redirects you to the documentation area.

As for bug tracking system, there are two versions of the Jahia documentation:

- The free community documentation, available on jahia.org.
- The Enterprise documentation reserved for paid versions, available in the client Extranet area.

1.12 About Jahia

Finally, the “About Jahia” panel displays a summary of all the available functionalities depending on your type of license (number of users, restrictions on some modules, trial version expiry...).

About Jahia

Server settings | Site settings: My Site | Go to Studio | Go to Edit Mode | My Space | Logout | English

Main Menu

- Web Project management
- Manage users
- E-mail settings
- Manage portlets
- Edit Super Administrator Properties
- Server and Cache status
- Password policy
- Report a problem
- Jahiapedia
- About Jahia

Jahia xCM 6.5.0.0 Enterprise Edition, Build 37719

Your installed license is valid for the following resources.
Current usage of resources is shown for comparison.

Resource Type	Current	Maximum
Maximum usage in days	0	60
Release number	6.5	6.5 to 6.6
Jahia core framework	activated	n/a
LDAP	activated	n/a
Publication distante	activated	n/a
Vérificateur de liens	activated	n/a
Authentification NTLM	activated	n/a
Authentification JAAS	activated	n/a
Authentification SPNEGO	activated	n/a
Authentification CAS	activated	n/a
???org.jahia.admin.templates.label???	activated	n/a
???org.jahia.admin.roles.label???	activated	n/a

Jahia Enterprise Edition v6.5

Copyright (C) 2002-2011 Jahia Solutions Group. All rights reserved.

Jahia delivers the first Open Source Web Content Integration Software by combining Enterprise Web Content Management with Document Management and Portal features.

The Jahia Enterprise Edition is delivered ON AN "AS IS" BASIS, WITHOUT WARRANTY OF ANY KIND, EITHER EXPRESSED OR IMPLIED.

Jahia Enterprise Edition must be used in accordance with the terms contained in a separate license agreement between you and Jahia (Jahia Sustainable Enterprise License - JSEL).


If you are unsure which license is appropriate for your use, please contact the sales department at sales@jahia.com.

In this section you will also find the Jahia version number. This information also appears in the footer of each page of the Administration Center.

The version number must be mentioned in all bug reports, as this will help technical support resolve your problem.


2 Section Two: Site Settings

For a site administrator, the administration panel is displayed as shown in this screen capture:



This section contains all the necessary tools to manage a Jahia virtual site.


If the site administrator also has administrative rights on other Jahia Web projects, they can access these other sites via a drop-down menu and manage them using the same options.



A site administrator can access the “Server Settings” tab, but only a few options will be available. The other options are reserved to administrators with higher permissions and they will be greyed out.

Clicking on “Go to Edit Mode” will redirect the site administrator to the current site’s home page.

An advanced user with some administrative rights can access the options matching his permissions. The other options are greyed out. In the example below, the advanced user can only access the “Manage Groups” panel.



We will now cover the various options that are available to manage a site.

2.1 Manage Groups

Groups can be managed in the administration interface, from the “Site Settings” section. Unlike users, which are shared across the platform so as to ensure their uniqueness, each site has its own set of groups, which can be different from the groups of another site.

Group management : site ACME Demo site

Server settings | Site settings: ACME Demo site | Go to Studio | Go to Edit Mode | My Space | Logout | English

Main Menu

- Manage groups
- Manage languages
- HTML settings
- Display Vanity URL

Manage groups

Create new group | Copy selected group | Edit selected group | Remove selected group

View selected group memberships

Group list

Search:

Sort by source | Sort by group ID | Sort by property

in: ☒ All properties

☐ Properties :

- ☐ Groupname
- ☐ Description (LDAP)
- ☐ Members (LDAP)

on: ☐ Everywhere

☒ Providers :

- ☒ Jahia Repository (jahia_jcr)

site-administrators	{root, max}
site-privileged	{jenifer, site-adm..

Creating a Group


Click on the “Create new group” button and enter a name for it in the “Group name” field.

Once the group has been successfully created, the updated list of groups is displayed.


When a group is created, it is initially empty.

2.1.1 Adding and Removing Members

In the list of groups, double-click on the group that you want to edit. Alternatively, you can select this group and click on the “Edit selected group” button.



To add members to the group, click on the “Add members” button.



A floating window is displayed, containing a list of all users on the platform in alphabetical order. If the platform contains a large number of users, you can enter a name or part of a name in the search field at the top of the window.

To add a single user, select it in the list and click on the “Add” button. The floating window will be closed and the updated list of users in the group will be displayed.

To add several users, select them with ctrl+click and click on the “Add” button. Alternatively, you can double-click on each user you want to add and then close the window by clicking on the red cross at the top right. (Please note: users added via double-click will be added to the group immediately and clicking on the “Cancel” button will not remove the freshly added users).

When the user selection window is closed, the updated list of users in the group will be displayed.

Edit group

[Server settings](#)
[Site settings: ACME Demo site](#)
[Go to Studio](#)
[Go to Edit Mode](#)
[My Space](#)

[Logout](#)
English

Main Menu

- Manage groups
- Manage languages
- HTML settings
- Display Vanity URL

Edit selected group

Add members
 Remove members

Group name **marketing-dept**

Group members:

Sort by provider
 Sort by the identifier
 Sort by property

```

ul jcr | anne_T |
ul jcr | frederic_M |
ul jcr | jean_B |
          
```

Select all group members
 Invert group members selection

Cancel
 OK

To remove a member from a group, select the user in the list (or use ctrl+click to select several users) and click on the “Remove members” button. Please note that this action does not remove the user from the platform, but only from the group.

© 2002 – 2012 Jahia Solutions Group SA

Page 59 sur 73

2.1.2 Removing a Group

In the list of groups, click on the group you want to remove, then click on the “Remove selected group” button.

Group management : site ACME Demo site

Server settings Site settings: ACME Demo site Go to Studio Go to Edit Mode My Space Logout English

Main Menu

- Manage groups
- Manage languages
- HTML settings
- Display Vanity URL

Manage groups

Create new group Copy selected group Edit selected group Remove selected group

View selected group memberships

Group list

Search:

Sort by source Sort by group ID Sort by property

in: ☒ All properties

☐ Properties :

- ☐ Groupname
- ☐ Description (LDAP)
- ☐ Members (LDAP)

on: ☐ Everywhere

☒ Providers :

- ☒ Jahia Repository (jahia_jcr)

Search

marketing-dept	(jean B, frederic ..
site-administrators	(root)
site-privileged	(site-administrato..

Back to menu

Duplicating a Group

If you need to define a new group with similar members to those in another group, you can duplicate the existing group by selecting it and clicking on the “Copy selected group” button. Jahia will then ask you to enter a name for the new group. Now all you need to do is add or remove members from the new group, without having to go through the entire group configuration process again.

Group management : site ACME Demo site

Server settings | Site settings: ACME Demo site | Go to Studio | Go to Edit Mode | My Space | Logout | English

Main Menu

- Manage groups
- Manage languages
- HTML settings
- Display Vanity URL

Manage groups

Create new group | Copy selected group | Edit selected group | Remove selected group

View selected group memberships

Group list

Search:

Sort by source | Sort by group ID | Sort by property

in: ☒ All properties

☐ Properties:

- ☐ Groupname
- ☐ Description (LDAP)
- ☐ Members (LDAP)

on: ☐ Everywhere

☒ Providers:

- ☒ Jahia Repository (jahia_jcr)

marketing-dept	{jean B., frederic ..
site-administrators	{root}
site-privileged	{site-administrato..

2.2 Manage Languages

Ce panneau vous permet de gérer les paramètres concernant les langues du site courant.

La partie haute de l'interface affiche les langues déjà déclarées comme utilisables sur le site.

La partie basse affiche les langues pouvant être activées sur le site et des options quant à la gestion multilingue.

Manage languages: site Partners site

Server settings | Web project settings: Partners site | Go to Studio | Go to Edit Mode | My Space | Logout | English

Main Menu

- Manage groups
- Manage languages**
- HTML settings
- Display Vanity URL
- Manage modules
- Link Checker

Configured languages

Language	Default language	Mandatory	Active (Edit)	Active (Live)
German (de)	<input type="radio"/>	<input type="checkbox"/>	<input checked="" type="checkbox"/>	<input type="checkbox"/>
French (fr)	<input type="radio"/>	<input type="checkbox"/>	<input checked="" type="checkbox"/>	<input type="checkbox"/>
English (en)	<input checked="" type="radio"/>	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>

Options

☐ Replace untranslated content with the default language content

☐ Allow to use unlisted languages

Available languages

Albanian (sq)
Albanian (Albania) (sq_AL)
Arabic (ar)
Arabic (Algeria) (ar_DZ)
Arabic (Bahrain) (ar_BH)
Arabic (Egypt) (ar_EG)
Arabic (Iraq) (ar_IQ)
Arabic (Jordan) (ar_JO)
Arabic (Kuwait) (ar_KW)
Arabic (Lebanon) (ar_LB)

Add languages

Back to menu | Save

2.2.1 Options disponibles pour chaque langue

2.2.1.1 Langue par défaut

Une seule langue peut être définie comme langue par défaut parmi les langues déclarées.

La langue par défaut est celle dans laquelle

- les noms système (noms internes) des contenus pourront être saisis et modifiés (pour éviter des confusions, des renommages intempestifs influant sur les URLs, les noms systèmes sont invariants et éditables dans une seule langue)

- Jahia redirigera automatiquement les visiteurs s'il ne dispose pas d'instructions lui permettant de servir les pages dans une langue spécifique (voir ci-dessous)
- Jahia servira les contenus non traduits si la fonction de substitution a été activée sur le projet web

La langue par défaut est celle qui sera utilisée par Jahia pour servir le contenu s'il ne parvient pas à trouver une langue correspondant aux préférences exprimées explicitement ou implicitement par l'utilisateur. La détermination de cette préférence utilisateur se fait par une série de tests, qui s'enchainent tant que le résultat du test est négatif.

L'ordre des tests est le suivant

- Langue spécifiée dans l'url
- Langue spécifiée dans le profil utilisateur (pour les utilisateurs enregistrés)
- Langue préférée déclarée dans les options du navigateur
- Langue du navigateur

2.2.1.2 Langue obligatoire

Lorsque cette case est cochée, les contenus saisis dans cette langue ne pourront être publiés si les champs définis comme obligatoires (c'est-à-dire devant disposer d'une traduction propre) n'ont pas été remplis. Afin de préserver une certaine souplesse en matière d'édition, l'activation de cette option n'empêche pas de saisir du contenu dans une langue donnée sans lui ajouter immédiatement ses traductions dans les langues déclarées comme obligatoires, mais empêche bien son exploitation (le rendre disponible à la consultation) si les critères portant sur la langue obligatoire ne sont pas remplis.

2.2.1.3 Actif (Editer)

Cette option permet de dire si la langue est modifiable via les interfaces d'édition. Si cette option est décochée, les contenus saisis dans cette langue sont conservés, mais il n'est plus possible via les interfaces d'édition de basculer sur cette langue et donc de l'éditer.

Cette option est particulièrement appropriée si vous souhaitez arrêter de traduire les nouveaux contenus dans une langue donnée sur votre site et vous contenter de l'existant, ou que vous souhaitez désactiver complètement une langue (auquel cas cette case et la case suivante doivent être cochées) sans pour autant supprimer cette langue et donc perdre tout le contenu déjà traduit.

A tout instant, il est possible de réactiver une langue désactivée et les contenus déjà traduits réapparaissent.

2.2.1.4 Actif (En ligne)

Cette option permet de dire si cette langue est accessible par les personnes qui consultent la version publiée de votre projet web. Si cette case est décochée et même si des traductions dans cette langue existent, les utilisateurs ne pourront y avoir accès.

Lors de l'ajout d'une langue cette case est systématiquement décochée, il faut donc l'activer manuellement au moment jugé opportun.

Cette option est particulièrement utile lorsqu'une langue est ajoutée sur un site déjà actif et que l'on souhaite pouvoir commencer à traduire celui-ci et même publier des pages en ne rendant la langue effectivement utilisable par les visiteurs que quand le niveau de finition est considéré comme suffisant pour permettre une navigation correcte sur cette nouvelle langue.

2.2.2 Gestion multilingue

2.2.2.1 Ajouter des langues

Pour ajouter une ou des langues supplémentaires, sélectionnez une (clic) ou plusieurs langues (Ctrl-clic) dans la liste située en bas de l'écran, puis cliquez sur le bouton « Ajouter des langues »

Manage languages: site Partners site

Server settings | Web project settings: Partners site | Go to Studio | Go to Edit Mode | My Space | Logout | English

Main Menu

- Manage groups
- Manage languages
- HTML settings
- Display Vanity URL
- Manage modules
- Link Checker

Configured languages

Language	Default language	Mandatory	Active (Edit)	Active (Live)
German (de)	<input type="radio"/>	<input type="checkbox"/>	<input checked="" type="checkbox"/>	<input type="checkbox"/>
French (fr)	<input type="radio"/>	<input type="checkbox"/>	<input checked="" type="checkbox"/>	<input type="checkbox"/>
English (en)	<input checked="" type="radio"/>	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>


Options

☐ Replace untranslated content with the default language content

☐ Allow to use unlisted languages

Available languages

- Italian (Switzerland) (it_CH)
- Japanese (ja)
- Japanese (Japan, JP) (ja_JP_JP)
- Japanese (Japan) (ja_JP)
- Korean (ko)
- Korean (South Korea) (ko_KR)
- Latvian (lv)
- Latvian (Latvia) (lv_LV)
- Lithuanian (lt)
- Lithuanian (Lithuania) (lt_LT)




Back to menu | Save

Vous remarquerez que certaines langues sont listées plusieurs fois. En effet la liste est basée sur les langues locales (langue de la région), les langues disponibles sont en fait une combinaison entre une langue et sa région.

Jahia peut identifier ces langues locales en provenance des préférences du navigateur et saura réagir différemment suivant la langue détectée (fr_CA ou fr_FR par exemple). Vous pourriez avoir 2 sites distincts avec du contenu différent pour des français et canadiens.

Si vous préférez gérer le français de manière générique, il faudra alors choisir la langue française FR. Si vous n'avez pas l'intention d'avoir du contenu spécifique à un pays ou à une région (comme fr_CA ou fr_FR), vous devriez utiliser systématiquement la langue locale générique pour la langue spécifiée.

 La liste des langues et langues locales disponibles proviennent directement de la Machine Virtuelle Java (JVM) utilisée. Chaque JVM supporte des langages différents. Les langues officielles ISO peuvent ne pas être présentes suivant la JVM utilisée. Dans ce cas, vous pouvez utiliser une autre langue que vous n'utiliserez jamais (comme langue disponible sur le site) et modifier l'icône de la langue (drapeau) sur le disque ou le template. Jahia ne pourra pas automatiquement reconnaître cette langue à des fins de

redirection pour les utilisateurs, cependant ils pourront naviguer entre les différentes langues à partir de la page d'accueil.

2.2.2.2 Utiliser plusieurs langues lors de la navigation sur le site

Manage languages: site System Site

Server settings | Web project settings: System Site | Go to Studio | Go to Edit Mode | My Space | Logout | English

Main Menu

- Manage groups
- Manage languages
- HTML settings
- Display Vanity URL
- Manage modules
- Link Checker

Configured languages

Language	Default language	Mandatory	Active (Edit)	Active (Live)
German (de)	<input type="radio"/>	<input type="checkbox"/>	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>
French (fr)	<input type="radio"/>	<input type="checkbox"/>	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>
English (en)	<input checked="" type="radio"/>	<input type="checkbox"/>	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>

Options

- ☒ Replace untranslated content with the default language content
- ☐ Allow to use unlisted languages

Available languages

- Albanian (sq)
- Albanian (Albania) (sq_AL)
- Arabic (ar)
- Arabic (Algeria) (ar_DZ)
- Arabic (Bahrain) (ar_BH)
- Arabic (Egypt) (ar_EG)
- Arabic (Iraq) (ar_IQ)
- Arabic (Jordan) (ar_JO)
- Arabic (Kuwait) (ar_KW)
- Arabic (Lebanon) (ar_LB)

Add languages

Back to menu | Save

Pour des besoins intranet ou extranet, vous pourriez avoir besoin d'afficher du contenu indépendamment de la langue du navigateur de l'utilisateur. Dans le cas, par exemple, où vous ne voudriez pas de pages vides dans certaines langues sachant que tout le site n'a pas été entièrement traduit ou disponible dans toutes les langues, vous pouvez alors activer l'option de mixité des langues (Utiliser plusieurs langues lors de la navigation).

Si cette option est activée et que l'objet de contenu n'existe pas dans la langue courante, Jahia affichera le contenu dans la langue par défaut.

Si l'anglais est la langue par défaut et que certains contenus ne sont pas traduits en français, ceux-ci pourraient alors être remplacés automatiquement par de l'anglais.

L'utilisation de cette option n'est pas recommandée sur des sites ouverts au public car le résultat peut dérouter des utilisateurs non avertis, elle peut être envisagée sur des sites de type intranet si les personnes

sont au fait de ce choix et ne sont donc pas susceptibles d'être déroutées par des contenus en deux langues sur une même page.

2.2.2.3 Permettre l'accès même pour les langues non déclarées

Manage languages: site System Site

Server settings | Web project settings: System Site | Go to Studio | Go to Edit Mode | My Space | Logout | English

Main Menu

- Manage groups
- Manage languages
- HTML settings
- Display Vanity URL
- Manage modules
- Link Checker

Configured languages

Language	Default language	Mandatory	Active (Edit)	Active (Live)
German (de)	<input type="radio"/>	<input type="checkbox"/>	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>
French (fr)	<input type="radio"/>	<input type="checkbox"/>	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>
English (en)	<input checked="" type="radio"/>	<input type="checkbox"/>	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>

Options

- ☒ Replace untranslated content with the default language content
- ☒ Allow to use unlisted languages

Available languages

- Albanian (sq)
- Albanian (Albania) (sq_AL)
- Arabic (ar)
- Arabic (Algeria) (ar_DZ)
- Arabic (Bahrain) (ar_BH)
- Arabic (Egypt) (ar_EG)
- Arabic (Iraq) (ar_IQ)
- Arabic (Jordan) (ar_JO)
- Arabic (Kuwait) (ar_KW)
- Arabic (Lebanon) (ar_LB)

Add languages

Back to menu | Save

Par défaut, Jahia sert les pages dans la langue demandée via l'url et charge les resource bundle (fichiers de traductions pour les éléments statiques déclarés dans les pages jsp) de la langue correspondante.

Exemple : www.partners.com/fr/home/actualites/actualites2012.html

Si un utilisateur appelle une page dans une langue non déclarée, Jahia lui retournera logiquement une erreur 404 puisque la page en question n'existe pas dans cette langue.

Exemple : www.partners.com/sq/home/actualites2012.html (sq = albanais)

En activant cette option, Jahia ignorera l'indication de langue et servira la page demandée dans la langue par défaut du site, en chargeant éventuellement les resource bundles correspondant à la langue demandée si ceux-ci existent.

Important : cette option ne doit être activée que si l'option précédente (remplacement du contenu non traduit) est elle-même activée.

2.3 *HTML Settings*


When editing a site, contributors often use a rich HTML editor. Since contributors are allowed to use HTML tags and to copy and paste HTML content, W3C standards may not always be respected and the page layout may happen to be messed up.

Contributors can forget to close a tag, insert a table so wide that it messes up the page etc.


Jahia’s “WCAG Compliance” option lets you check if the generated code meets the standards.


You can also prevent the use of specific HTML tags in rich HTML fields. To do so, you must specify a comma-separated list of forbidden tags in the “Markup filtering” option. When the contributor’s HTML contents will be saved, Jahia will automatically remove those tags from the submitted contents.

Filtering example: H1,script,table,tr,td,strong,hr



HTML settings

WCAG Compliance: ☒ 

Markup Filtering: ☐ 

2.4 Display Vanity URL

This panel displays a list of all defined vanity URLs (user-friendly, search engine optimized URLs) in Jahia. For each URL, some information is displayed, including the corresponding “technical” URL, language, status and whether it is the default URL or not.

Display Urlmappings

Server settings | Site settings: ACME Demo site | Go to Studio | Go to Edit Mode | My Space | Logout | English

Main Menu

- Manage groups
- Manage languages
- HTML settings
- Display Vanity URL

All Urlmappings

previous 1 2 next

Mappings	Page	Lang	Active	Default
/news/acme-conclut-un-partenariat-avec-polytech-nice	/sites/ACME/home/news/maincontent/news_34	fr	true	true
/news/acme-renforce-sa-presence-aux-emirats-arabes-unis	/sites/ACME/home/news/maincontent/news_33	fr	true	true
/news/acme-signs-a-partnership-with-polytechnice	/sites/ACME/home/news/maincontent/news_34	en	true	true
/news/acme-strengthens-its-presence-in-the-emirates	/sites/ACME/home/news/maincontent/news_33	en	true	true
/news/lorem-ipsum-dolor-sit-amet-2008	/sites/ACME/home/news/Archvies 2008/maincontent/news_37-1	fr	true	true
/news/lorem-ipsum-dolor-sit-amet-2008-1	/sites/ACME/home/news/Archvies 2008/maincontent/news_37-1	en	true	true
/news/lorem-ipsum-dolor-sit-amet-2008-2	/sites/ACME/home/news/Archvies 2008/maincontent/news_37-2	fr	true	true
/news/lorem-ipsum-dolor-sit-amet-2008-3	/sites/ACME/home/news/Archvies 2008/maincontent/news_37-2	en	true	true
/news/lorem-ipsum-dolor-sit-amet-2008-4	/sites/ACME/home/news/Archvies 2008/maincontent/news_37-5	fr	true	true
/news/lorem-ipsum-dolor-sit-amet-2008-5	/sites/ACME/home/news/Archvies 2008/maincontent/news_37-5	en	true	true
/news/lorem-ipsum-dolor-sit-amet-2008-6	/sites/ACME/home/news/Archvies 2008/maincontent/news_37-4	fr	true	true
/news/lorem-ipsum-dolor-sit-amet-2008-7	/sites/ACME/home/news/Archvies 2008/maincontent/news_37-4	en	true	true
/news/lorem-ipsum-dolor-sit-amet-2009	/sites/ACME/home/news/Archives 2009/maincontent/news_37	en	true	true
/news/lorem-ipsum-dolor-sit-amet-2009-1	/sites/ACME/home/news/Archives 2009/maincontent/news_37-1	en	true	true
/news/lorem-ipsum-dolor-sit-amet-2009-10	/sites/ACME/home/news/Archives 2009/maincontent/news_37	fr	true	true

previous 1 2 next

[Back to menu](#)

You can access the page related to the vanity URL by clicking on the corresponding link.

2.5 *Manage Modules*

This section displays the list of templates, modules and Jahaapps currently deployed on the site


2.6 *Link Checker*

The link checker is a powerful administration tool that allows site administrators to check an entire Jahia site for “dead” or broken external links. An external link is a link pointing to pages outside the platform, therefore outside of Jahia’s control.

Typically, an external link is prone to become “broken”: the author may have mistyped the link (e.g., goggle.com instead of google.com) or the target page may simply disappear, change name or location after some time.

The link checker will browse all Jahia pages for external links submitted by authors. Then it will display a report that will help the site administrator to fix broken links.

The tool will scan all pages in the selected language and mode.



To launch the scan, just click on the “Start checking” button, then on the “Display progress” button to view the results. The “Display progress with auto refresh” button will refresh the page automatically. The “Clean stored results” button will clear older results before launching a new scan.

Please note that the link checker is very demanding for the server. Running it occasionally will help maintain high editorial quality for the site, but it is not recommended to use it continuously.


2.6.1 *Auditing External Links with the Link Checker*

2.6.1.1 Use Case Scenario

In the ACME demo site, on the “Home” page, the author entered text and mistyped a link to <http://beta.jahia.com> instead of <http://beta65.jahia.org>. This is a “dead” link, pointing to a site that does not exist. The link is embedded in a BigText paragraph typed via the rich text editor provided by Jahia.


2.6.1.2 Launching a Website Analysis

In order to audit the links and be able to repair “broken” links, the site administrator can click the link checker’s “Start checking” button:



The duration of the audit process will depend on the volume of data to be analyzed.

As soon as the administrator launches the link checker, activity status details will be available in the lower part of the panel when clicking on the “Display progress” button:



Note that only broken links are displayed. Valid links do not appear in the report.

2.6.1.3 Description of the Link Checker Report

There are five columns in the link checker report:

Links to be checked or number of bad links when check over: 1				
Chemin	Propriétés	Liens		
		Lien	Status	Code
/sites/ACME/home/aside/how-to-use-this-demonstration/bigText	text	http://beta.jahia.com	Unknown host	-1

- Path: the path of the node containing the broken link
- Properties: the property in the affected node that contains the broken link
- Link: the link that generates the error
- Status: a description of the problem
- Code: the HTTP error code

Note: the Tomcat console displays the path of the current node, the relevant HTML code and the connection attempts to the associated links.

```
Nodes:185
Node:/sites/ACME/home/aside/how-to-use-this-demonstration/bigText
property:text
<p>You can discover <strong><a href="http://beta.jahia.com">Jahia CE BETA v6.5</a></strong>
using the following users (login/password):</p>
<div>
  <div>
    <p>You can also decide to go to the <a href="/start"><strong>Jahia home
page</strong> by clicking here.</a></p>
    <p>&nbsp;</p>
    <p><a href="http://beta65.jahia.org/">Link to beta</a></p>
  </div>
</div>

Try to connect to http://beta.jahia.com
Try to connect to http://beta65.jahia.org/
```




Jahia Solutions Group SA

*9 route des Jeunes,
CH-1227 Les acacias
Genève, Suisse*

<http://www.jahia.com>