



UNIVERSITY  
*of* SAN CARLOS  
SCIENTIA • VIRTUS • DEVOTIO



# CIS 1101 – PROGRAMMING 1

## CONTROL STRUCTURES

### Part 1

# CONTROL STRUCTURES: DEFINITION

- These are the structures that are used to control the flow of a program.
- Structures are used to make decisions and alter the direction of program flow in one or the other path(s) available.



CONTROL  
STRUCTURES IN C



UNIVERSITY  
of SAN CARLOS  
SCIENTIA • VIRTUS • DEVOTIO

DCISM  
DEPARTMENT OF COMPUTER, INFORMATION SCIENCES AND MATHEMATICS


# TYPES OF CONTROL STRUCTURES IN C: SEQUENCE



## CONTROL STRUCTURES IN C

### 1. Sequence structure

- Statements are executed one after the other in the order in which they are written, that is, in sequence.



# TYPES OF CONTROL STRUCTURES IN C: SELECTION




CONTROL

STRUCTURES IN C

## 2. Selection structure

- It is a structure in which a question is asked, and depending on the answer, the program takes one of two courses of action, after which the program moves on to the next event.



UNIVERSITY  
of SAN CARLOS  
SCIENTIA • VIRTUS • DEVOTIO

DCISM  
DEPARTMENT OF COMPUTER, INFORMATION SCIENCES AND MATHEMATICS


# TYPES OF CONTROL STRUCTURES IN C: **ITERATION**



## CONTROL STRUCTURES IN C

### 3. Loop structure (iteration)

- A set of instructions or structures are repeated in a sequence a specified number of times or until a condition is met.



# BRANCHING



## CONTROL STRUCTURES IN C

- Basic concept in computer science which means an instruction that tells a computer to begin executing a different part of a program rather than executing statements one-by-one.
- Implemented as a series of control flow statements called **CONTROL STATEMENTS** in high-level programming languages.



# CONTROL STATEMENTS



## CONTROL STRUCTURES IN C

- Provided by the computer language to be used to implement the control structures.
- Statements that specify the flow of a program.
- Control the order in which the instructions in a program must be executed
- Statements that make it possible to make decisions, to perform tasks repeatedly or to jump from one section of code to another.





# CONDITIONAL BRANCHING



## CONTROL STRUCTURES IN C

- When program statements help to **jump** from one part of the program to another depending on whether a particular condition is satisfied or not.
- generally implemented with **IF**, **IF-ELSE**, and **SWITCH-CASE** statements





# IF STATEMENT



- A simple control statement that tests whether a condition is true or false.
- **Condition:** can include a variable, or be a variable.
- Tests for ONLY one action.



# IF STATEMENT



- If the condition is true, then an action occurs.
- If the condition is false, nothing is done.



# IF STATEMENT: SYNTAX



## CONTROL STRUCTURES IN C



- **if** variable is true  
Take this course of action
- **if** (condition)  
{  
    /\* Block of C statements here \*/  
    /\* These statements will only execute if the condition is true \*/  
}



# IF STATEMENT: FLOWCHART



## CONTROL STRUCTURES IN C



# IF STATEMENT: IMPORTANT NOTES

- Condition must be a **Boolean expression**
- Statement is any valid C statement
- Statement is only executed if the condition evaluates to true.
- If the condition evaluates to **false**,
  - then the statement is **skipped** and
  - the next line of code following the **if statement** is executed.
- The **curly braces may be omitted**
  - when the body contains **only one statement**.



CONTROL  
STRUCTURES IN C



UNIVERSITY  
of SAN CARLOS  
SCIENTIA • VIRTUS • DEVOTIO

DCISM  
DEPARTMENT OF COMPUTER, INFORMATION SCIENCES AND MATHEMATICS

# IF-ELSE STATEMENT



CONTROL

STRUCTURES IN C

- If the **condition** returns **true**, then the **statements** inside the **body of “if”** are **executed** and the statements inside the **body of “else”** are **skipped**.
- If the condition is true,
  - then an action occurs.
- If the **condition** returns **false**, then the statements inside the **body of “if”** are **skipped** and the **statements in “else”** are **executed**.
- If the condition is false,
  - take an alternate action.



UNIVERSITY  
of SAN CARLOS  
SCIENTIA • VIRTUS • DEVOTIO

DCISM  
DEPARTMENT OF COMPUTER, INFORMATION SCIENCES AND MATHEMATICS

# IF-ELSE STATEMENT: **SYNTAX**

- **if** variable is **true**  
Take this course of action  
**else** call another routine
- **if** (**condition**)  
{  
    /\* Statements inside body of **if** \*/  
}  
**else**  
{  
    /\* Statements inside body of **else** \*/  
}



CONTROL  
STRUCTURES IN C




UNIVERSITY  
of SAN CARLOS  
SCIENTIA • VIRTUS • DEVOTIO

**DCISM**  
DEPARTMENT OF COMPUTER, INFORMATION SCIENCES AND MATHEMATICS



# IF-ELSE STATEMENT: FLOWCHART



# IF-ELSE STATEMENT: NESTED

- It is when an **if-else statement** is **present** inside the body of another “if” or “else” statement.



## CONTROL STRUCTURES IN C



UNIVERSITY  
of SAN CARLOS  
SCIENTIA • VIRTUS • DEVOTIO

DCISM  
DEPARTMENT OF COMPUTER, INFORMATION SCIENCES AND MATHEMATICS

# NESTED IF-ELSE STATEMENT: SYNTAX

```
if (condition1)
{
    /* Nested if else inside the body of "if" */
    if (condition2)
    {
        /* Statements inside the body of nested "if" */
    }
    else
    {
        /* Statements inside the body of nested "else" */
    }
}
else
{
    /* Statements inside the body of "else" */
}
```



CONTROL  
STRUCTURES IN C



UNIVERSITY  
of SAN CARLOS  
SCIENTIA • VIRTUS • DEVOTIO

DCISM  
DEPARTMENT OF COMPUTER, INFORMATION SCIENCES AND MATHEMATICS

# NESTED IF-ELSE STATEMENT: EXAMPLE



CONTROL

STRUCTURES IN C

```
#include <stdio.h>
```

```
int main()  
{
```

```
    int var1, var2;
```

```
    printf("Enter the value of var1: ");  
    scanf("%d", &var1);
```

```
    printf("Enter the value of var2: ");  
    scanf("%d", &var2);
```

```
    if (var1 != var2)
```

```
    {
```

```
        printf("var1 is not equal to var2.\n");
```

```
        /* Nested if else */
```

```
        if (var1 > var2)
```

```
        {
```

```
            printf("var1 is greater than var2.\n");
```

```
        }
```

```
        else
```

```
        {
```

```
            printf("var2 is greater than var1.\n");
```

```
        }
```

```
    }
```

```
    else
```

```
    {
```

```
        printf("var1 is equal to var2.\n");
```

```
    }
```

```
    return 0;
```

```
}
```

# SWITCH-CASE STATEMENT



## CONTROL STRUCTURES IN C

- A better way of writing a program when a series of **if-else statements** occurs.
- Used for **multiple way selections** that will branch into different code segments or program statements based on the value of a **variable or expression**.
- **Variable or expression:**
  - must be of integer data type.



# SWITCH-CASE STATEMENT: SYNTAX





```
switch (expression)
{
    case value1:
        program statement;
        break;
    case value2:
        program statement;
        break;
    .
    .
    case valueN:
        program statement;
        break;
    default:
        default program statement;
}
```



# SWITCH-CASE STATEMENT: FLOWCHART



## CONTROL STRUCTURES IN C





# SWITCH-CASE STATEMENT: EXAMPLE



## CONTROL STRUCTURES IN C

```
#include<stdio.h>
```

```
int main( )  
{
```

```
    int day;
```

```
    printf("\nEnter the number of the day: ");  
    scanf("%d", &day);
```

```
        switch(day) {  
            case 1: printf("\nIt is a Sunday");  
                    break;  
            case 2: printf("\nIt is a Monday");  
                    break;  
            case 3: printf("\nIt is a Tuesday");  
                    break;  
            case 4: printf("\nIt is a Wednesday");  
                    break;  
            case 5: printf("\nIt is a Thursday");  
                    break;  
            case 6: printf("\nIt is a Friday");  
                    break;  
            case 7: printf("\nIt is a Saturday");  
                    break;  
            default: printf("\nIt is an Invalid choice!");  
                    break;  
        }  
    return 0;
```

```
}
```



# UNCONDITIONAL BRANCHING

- It is also known as UNCONDITIONAL CONTROL TRANSFER.
- It is when the programmer forces the execution of a program to jump to another part of the program.
- This can be done using a good combination of loops and if statements.
- This technique should always be avoided by a programmer and this is used only when it is very difficult to use a loop.



CONTROL  
STRUCTURES IN C



UNIVERSITY  
of SAN CARLOS  
SCIENTIA • VIRTUS • DEVOTIO

DCISM  
DEPARTMENT OF COMPUTER, INFORMATION SCIENCES AND MATHEMATICS

# UNCONDITIONAL BRANCHING: **GOTO**

- The **goto** statement is used for unconditional branching or transfer of the program execution to the labeled statement.
- This statement does not require any condition.
- This statement passes control anywhere in the program without considering any condition.
- Avoid using the **goto** statement.



# UNCONDITIONAL BRANCHING: GOTO



## CONTROL STRUCTURES IN C

```
goto label;  
-----  
-----  
-----  
label:
```

The goto statement

```
#include<stdio.h>
```

```
int main()
```

```
{
```

```
    int x;
```

```
    printf("\nEnter a number: ");
```

```
    scanf("%d",&x);
```

```
    if(x%2==0) {
```

```
        goto even;
```

```
    }else {
```

```
        goto odd;
```

```
    }
```

```
    even: printf("\nThe number is even.");
```

```
    odd: printf("\nThe number is odd.");
```

```
    return 0;
```

```
}
```



UNIVERSITY  
of SAN CARLOS  
SCIENTIA • VIRTUS • DEVOTIO

DCISM  
DEPARTMENT OF COMPUTER, INFORMATION SCIENCES AND MATHEMATICS

# UNCONDITIONAL BRANCHING: CONTINUE

- This statement works somewhat like the break statement.
- This statement **skips** the current iteration of the loop and **continues with the next iteration**.
- In the case of for loop, this statement initiates the testing condition and increment on steps has to be executed (while the other statements following continue are neglected).
- For while and do while, this statement causes control to pass on to conditional tests.
- It is useful in a programming situation where it is required that particular iterations occur only up to some extent or when some part of the code has to be neglected.



CONTROL  
STRUCTURES IN C



UNIVERSITY  
of SAN CARLOS  
SCIENTIA • VIRTUS • DEVOTIO

DCISM  
DEPARTMENT OF COMPUTER, INFORMATION SCIENCES AND MATHEMATICS

# UNCONDITIONAL BRANCHING: CONTINUE



## CONTROL STRUCTURES IN C

```
# include <stdio.h>
```

```
int main()
```

```
{
```

```
    int i;
```

```
    double number, sum = 0.0;
```

```
    for(i=1; i <= 10; ++i)
```

```
    {
```

```
        printf("Enter n%d: ",i);
```

```
        scanf("%lf", &number);
```

```
        if(number < 0.0)
```

```
        {
```

```
            continue;
```

```
        }
```

```
        sum += number;  /* sum = sum + number; */
```

```
    }
```

```
    printf("Sum = %.2lf",sum);
```

```
    return 0;
```

```
}
```



UNIVERSITY  
of SAN CARLOS  
SCIENTIA • VIRTUS • DEVOTIO

DCISM  
DEPARTMENT OF COMPUTER, INFORMATION SCIENCES AND MATHEMATICS

# UNCONDITIONAL BRANCHING: **BREAK**



- Terminates the **loop** or **switch** statement and transfers execution to the statement immediately following the **loop** or **switch**.
- The control then automatically passes on to the first statement after the loop or the block.
- This statement can be associated with all the conditional statements (especially **switch case**).
- This statement can be used in the nested loops.
- The widest used of this statement is in the switch case where it is used to avoid flow of control from one 'case' to the other.





# UNCONDITIONAL BRANCHING: **BREAK**



## CONTROL STRUCTURES IN C

```
# include <stdio.h>
```

```
int main()
```

```
{
```

```
    int i;
```

```
    double number, sum = 0.0;
```

```
    for(i=1; i <= 10; ++i)
```

```
    {
```

```
        printf("Enter a n%d: ",i);
```

```
        scanf("%lf",&number);
```

```
        /* If the user enters a negative number, the loop ends */
```

```
        if(number < 0.0)
```

```
        {
```

```
            break;
```

```
        }
```

```
        sum += number;    /* sum = sum + number; */
```

```
    }
```

```
    printf("Sum = %.2lf",sum);
```

```
    return 0;
```

```
}
```



# UNCONDITIONAL BRANCHING: **RETURN**



- The return statement terminates the execution of a function and returns control to the calling function.
- Execution resumes in the calling function at the point immediately following the call.
- A return statement can also return a value to the calling function.



# UNCONDITIONAL BRANCHING: **RETURN**

## ■ Syntax:

**return** **expression**;

- **return** keyword transfers program control to the caller.
- **expression** is optional and is used to return result of a valid C expression to the caller.

