

Advanced Probabilistic Machine Learning and Applications

Caterina De Bacco and Nicolás Ruggeri

1 Tutorial 8: TAP approach

Exercise 1: planted SK model

We consider a model similar to the SK model, with the difference that the J_{ij} are generated from a particular realization, called “planted”. Specifically, we start from the following generative model for the $P(\mathbf{s}, \mathbf{J})$:

$$s_i \sim \frac{1}{2} \delta(s_i - 1) + \frac{1}{2} \delta(s_i + 1) \quad , \quad i = 1, \dots, N \quad (1)$$

$$J_{ij} | s_i, s_j \sim \mathcal{N}\left(\frac{s_i s_j}{\sqrt{N}}, \sigma^2\right) \quad , \quad (i, j) \in N^2 \quad (2)$$

Goal: estimate the planted \mathbf{s} given the \mathbf{J} .

- (a) Use Bayes’ theorem to write the posterior distribution $P(\mathbf{s} | \mathbf{J})$.
- (b) Rewrite it as a Boltzmann distribution similar to the SK model with $\beta := \frac{1}{\sigma^2}$.
- (c) We would like to estimate the mean of $P(\mathbf{s} | \mathbf{J})$. However, this is not tractable analytically. We will instead use the approximation introduced in the class.
Write in a *jupyter* notebook a function to *sample* an instance of (\mathbf{s}, \mathbf{J}) .
- (d) In the same notebook, write a function that implements the TAP equation to approximate the mean $\hat{\mathbf{s}}$ of $P(\mathbf{s} | \mathbf{J})$. This is an iteration that, if it converges, gives a very good approximation for $\hat{\mathbf{s}}$ as $N \rightarrow \infty$.

For numerical reasons implement the fixed point iterations as follows:

$$m_i^{(t+1)} = \tanh\left(\frac{1}{\sigma^2 \sqrt{N}} \sum_j J_{ij} m_j^{(t)}\right) \quad \text{Mean Field}$$

$$m_i^{(t+1)} = \tanh\left(\frac{1}{\sigma^2 \sqrt{N}} \sum_j J_{ij} m_j^{(t)} - m_i^{(t-1)} \frac{1}{N \sigma^4} \sum_j J_{ij}^2 (1 - (m_j^{(t)})^2)\right) \quad \text{TAP}$$

- (e) Run some experiments ($N_{real} \in [10, 100]$ re-samplings of J, s at your choice) for $N = 10, 100, 1000, 5000$ and fixed $\sigma^2 = 0.1$ and check that the overlap¹ with ground-truth improves with the iterations.

¹The overlap is defined as: $overlap(\mathbf{m}, \mathbf{s}_0) := \left| \frac{\mathbf{m} \cdot \mathbf{s}_0}{N} \right|$

- (f) i) Run sum experiments ($N_{real} \in [10, 100]$ re-samplings of J, s at your choice) for $N = 10, 100, 1000, 5000$ and varying $\sigma^2 \in [0.1, 2]$.
 ii) Repeat the same experiments but using the MF approximation instead.
 iii) Plot the performance metrics values at convergence for TAP and MF as a function of the noise σ^2 for various N .
 Comment on what you observe.

Exercise 2: sampling from the SK model

Consider again the Hamiltonian of the SK model:

$$H(\mathbf{s}) = - \sum_{i \neq j} J_{ij} s_i s_j \quad . \quad (3)$$

We now want to *sample* configurations of N variables from the corresponding Boltzmann distribution for a particular realization of the couplings and comparing the empirical mean of the magnetizations with the one inferred using TAP and MF.

For sampling, we use the Monte-Carlo-Markov-Chain (MCMC) Metropolis-Hastings algorithm as we learned for the Curie Weiss model in tutorial 7.

- (a) Write a code to perform the MCMC dynamics, and start by configurations extracted uniformly at random.
 i) Sample a particular realization of $\mathbf{J} \sim \mathcal{N}(0, \sigma^2 / \sqrt{N})$, for $\sigma^2 = 1$ and $\beta = 1.1$.
 ii) Run your dynamics for a long enough time (say, with $t_{\max} = 10^3 N$ attempts to flips spins) and monitor the value of the magnetization $m = \sum_i s_i / N$ as a function of time. Make a plot for $N = 10, 100, 1000$ spins.
- (b) Iterate MF and TAP equations and compare the values obtained from the ground truth MCMC sampler. To do so, draw a scatter plot of the single values m_i obtained from the MCMC sampler and the approximations (one plot per approximation, for a total of 2 plots).
 Comment. Similarly to before, implement the consistency equations as

$$m_i^{(t+1)} = \tanh \left(\beta \sum_j J_{ij} m_j^{(t)} \right) \quad \text{Mean Field}$$

$$m_i^{(t+1)} = \tanh \left(\beta \sum_j J_{ij} m_j^{(t)} - \beta^2 m_i^{(t-1)} \sum_j J_{ij}^2 (1 - (m_j^{(t)})^2) \right) \quad \text{TAP}$$