GeeksforGeeks

A computer science portal for geeks

GeeksQuiz

- Home
- Algorithms
- DS
- GATE
- Interview Corner
- Q&A
- <u>C</u>
- <u>C++</u>
- Java
- Books
- Contribute
- Contests
- Jobs

<u>Array</u>

Bit Magic

<u>C/C++</u>

Articles

GFacts

Linked List

MCQ

Misc

Output

String

Tree

Graph

How to measure time taken by a function in C?

To calculate time taken by a process, we can use <u>clock()</u> function which is available *time.h.* We can call the clock function at the beginning and end of the code for which we measure time, subtract the values, and then divide by <u>CLOCKS PER SEC</u> (the number of clock ticks per second) to get processor time, like following.

```
#include <time.h>

clock_t start, end;
double cpu_time_used;

start = clock();
... /* Do the work. */
end = clock();
cpu_time_used = ((double) (end - start)) / CLOCKS_PER_SEC;
```

Following is a sample C program where we measure time taken by fun(). The function fun() waits for enter key press to terminate.

```
/* Program to demonstrate time taken by function fun() */
#include <stdio.h>
#include <time.h>
// A function that terminates when enter key is pressed
void fun()
{
   printf("fun() starts \n");
   printf("Press enter to stop fun \n");
   while(1)
    {
        if (getchar())
            break;
   printf("fun() ends \n");
}
// The main program calls fun() and measures time taken by fun()
int main()
{
    // Calculate the time taken by fun()
   clock t t;
    t = clock();
    fun();
    t = clock() - t;
    double time_taken = ((double)t)/CLOCKS PER SEC; // in seconds
    printf("fun() took %f seconds to execute \n", time taken);
    return 0;
}
```

Output: The following output is obtained after waiting for around 4 seconds and then hitting enter key.

```
fun() starts
Press enter to stop fun
fun() ends
fun() took 4.017000 seconds to execute
```

References:

http://www.gnu.org/software/libc/manual/html_node/CPU-Time.html http://www.cplusplus.com/reference/ctime/clock/?kw=clock

Please write comments if you find anything incorrect, or you want to share more information about the topic discussed above.

gettimeofday()

Do NOT use gettimeofday() to measure time!




Related Topics:

- Function Pointer in C
- Generic Linked List in C
- Bit Fields in C
- Write your own memcpy()
- Some Interesting facts about default arguments in C++
- Comparison of a float with a value in C
- Pure virtual destructor in C++
- C++ mutable keyword



Writing code in comment? Please use ideone.com and share the link here.






- Interview Experiences
 - Advanced Data Structures
 - Dynamic Programming
 Greedy Algorithms

 - Backtracking
 - Pattern Searching

 - Divide & ConquerMathematical Algorithms
 - Recursion
 - Geometric Algorithms



• Popular Posts

- All permutations of a given string
- Memory Layout of C Programs
- Understanding "extern" keyword in C
- Median of two sorted arrays
- Tree traversal without recursion and without stack!
- o Structure Member Alignment, Padding and Data Packing
- Intersection point of two Linked Lists
- Lowest Common Ancestor in a BST.
- Check if a binary tree is BST or not
- Sorted Linked List to Balanced BST
- Follow @GeeksforGeeks

• Recent Comments

• SiSi

without using boolean... jst print the keys of...

Print all nodes that are at distance k from a leaf node · 1 minute ago

• rochak

yeah.. u r right...i though so too.. i think it...

Calculate the angle between hour hand and minute hand · 3 minutes ago

• Mayank yaday

if (pole1TopDisk == INT_MIN) ? Can someone...

<u>Iterative Tower of Hanoi</u> · <u>13 minutes ago</u>

o rochak

yup...from...

Sieve of Eratosthenes · 23 minutes ago

o <u>ak</u>

bahut acche:P

Root to leaf path sum equal to a given number · 32 minutes ago

• shan

Given an unsorted array create a BST?? How? It...

Synopsys Interview Experience | Set 4 (For R&D Engineer I) · 48 minutes ago

Ads by Google	Ads by Google	Ads by Google
► Function	► C++ Programming	► C++ Example
► C++ Programs	▶ Geeksforgeeks	▶ GNU C++
► C++ Code	▶ Geeks Geeks	► C++ Reference

@geeksforgeeks, <u>Some rights reserved</u> <u>Contact Us!</u> <u>Abut Us!</u> Powered by <u>WordPress</u> & <u>MooTools</u>, customized by geeksforgeeks