Range plan: the hole size test (Program B)

One page to print and take to the range. NOTES-FROM-PLANNING.md entry 235; the reasons are in docs/RESEARCH.md, Program B.

Print: 10 sheets of GL-CF25-LTR-D, the 25 bull Letter load sheet, all at once on one printer and one paper, at 100 percent. Eight are used, two are spare.

Set up: one backing for every sheet, each stapled the same way; 50 yards; the rifle zeroed first, so every shot lands on its own bull.

Shoot, in this order, one shot to a bull, 25 shots a sheet, aimed at each bull's center:

1. .22 LR subsonic
2. .300 Blackout subsonic
3. .22 LR high velocity
4. 6.5 Creedmoor (or 6 ARC)
5. .22 LR subsonic
6. .300 Blackout subsonic
7. .22 LR high velocity
8. 6.5 Creedmoor (or 6 ARC)

That is the whole core set: eight sheets, two of each. Only if there is time, two sheets each, alternated in the same way: 8.6 Blackout subsonic, .510 Whisper, and whichever of 6 ARC and 6.5 Creedmoor was not shot above.

Write on each sheet's load block: the date; 50 yd; the cartridge; the bullet's weight and type; the powder and charge, or the maker if factory; the velocity if a chronograph was up; and in the serial box, the sheet's number from the list above.

Bring every shot sheet home and keep it flat until every one is scanned and GroupLab says it is done with them.

Afterwards: scan every sheet flat on the Brother flatbed at 600 dpi, lid closed, one sheet a scan, and name each file by its sheet number. Sheets that are not GroupLab's are photographed instead, square on, in even light.