



ABS (TMMK Made)

System Outline

This system controls the respective brake fluid pressures acting on the disc brake cylinders of the right front wheel, left front wheel and rear wheels when the brakes are applied in a panic stop so that the wheels do not lock. This results in improved directional stability and steerability during panic braking.

1. Input Signals

(1) Speed sensor signal

The speed of the wheels is detected and input to TERMINALS 5, 7, 10 and 19 of the skid control ECU with actuator.

(2) Stop light SW signal

A signal is input to TERMINAL 20 of the skid control ECU with actuator when the brake pedal is depressed.

2. System Operation

During sudden braking the skid control ECU with actuator has signals input from each sensor, which controls the current to the solenoid inside the actuator and lets the hydraulic pressure acting on each wheel cylinder escape to the reservoir. The pump inside the actuator is also operating at this time and it returns the brake fluid from the reservoir to the master cylinder, thus preventing locking of the vehicle wheels.

If the skid control ECU with actuator judges that the hydraulic pressure acting on the wheel cylinder is insufficient, the current on the solenoid is controlled and the hydraulic pressure is increased. Holding of the hydraulic pressure is also controlled by the skid control ECU with actuator, by the same method as above. Pressure reduction, holding and increase are repeated to maintain vehicle stability and to improve steerability during sudden braking.

) : Parts Location

Code	See Page Cod		de	See Page	Code		See Page
A4	38 (*1)	A32		44	J23	В	43
	40 (*2)	A33		44	P3	Α	43
A6	38 (*1)	C7	Α	42] ' '	В	43
	40 (*2)	C8	В	42	S1	_	39 (*1)
A7	38 (*1)	D3		42	31		41 (*2)
	40 (*2)	J22	Α	43	S	14	43

: Relay Blocks

Code	See Page	Relay Blocks (Relay Block Location)
1	22	Engine Room R/B (Engine Compartment Left)

: Junction Block and Wire Harness Connector

Code	See Page	Junction Block and Wire Harness (Connector Location)	
1C	25	Engine Room Main Wire and Engine Room J/B (Engine Compartment Left)	
1E		Engine Room Main Wile and Engine Room 3/B (Engine Compartment Left)	
2B	28	Instrument Panel Wire and Driver Side J/B (Lower Finish Panel)	
2G	28	Engine Room Main Wire and Driver Side J/B (Lower Finish Panel)	
2L			
2M]		
20	29	Instrument Panel Wire and Driver Side J/B (Lower Finish Panel)	
2P			
2S			
3A	34	Instrument Panel Wire and Passenger Side J/B (Instrument Panel Brace RH)	
3B	В	Instrument and write and assemger side 3/D (instrument Faller Diace NT)	

: Connector Joining Wire Harness and Wire Harness

Code	See Page	Joining Wire Harness and Wire Harness (Connector Location)	
ID1	50	Engine Room Main Wire and Floor Wire (Left Side of Driver Side J/B)	
IF3	50	Engine Room Main Wire and Instrument Panel Wire (Right Side of Steering Column Tube)	
IF4	30	Lingine Room wait whe and instrument Fanel whe (Right Side of Steering Column Tube)	
IL1	51	Engine Wire and Instrument Panel Wire (Behind the Glove Box)	
IL2] 31	Linguile wille and institution it alief wille (Defined the Glove Box)	
IN2	51	Instrument Panel Wire and Floor No.2 Wire (Right Kick Panel)	

^{* 1 : 1}MZ-FE, 3MZ-FE

^{* 2 : 2}AZ-FE

^{* 3 :} w/ Power Seat

^{* 4 :} w/o Power Seat



: Ground Points

Code	See Page	Ground Points Location
EA	48 (*1)	
	49 (*2)	Right Fender
EB	48 (*1)	
EB	49 (*2)	
ED	48 (*1)	Left Fender
	49 (*2)	Leitreliaei
IJ	50	Instrument Panel Brace LH