

TORQUE SPECIFICATION

Part Tightened	N·m	kgf·cm	ft·lbf
Bleeder plug	8.3	85	74 in·lbf
Brake booster clevis lock nut	26	265	19
Brake pedal sub-assy set bolt	37	375	27
Stop lamp lock nut	26	265	19
Brake pedal support assy x Reinforcement	20	204	15
Brake pedal support assy x Body	13	130	9
Master cylinder piston stopper bolt w/o VSC:	10	100	7
Brake master cylinder x Brake booster	13	130	9
Brake line union nut	15	155	11
Vacuum hose bracket set bolt	5.4	55	48 in·lbf
Chacoal canister bracket set bolt	43	440	32
Engine cover assy No. 1 set nut	7.0	71	62 in·lbf
Wheel nut	103	1,050	76
Front brake cylinder mounting x Steering knuckle	107	1,090	79
Front brake cylinder x Front brake cylinder mounting	34	350	25
Front brake cylinder x Flexible hose	29.4	300	22
Rear disc brake cylinder mounting set bolt	62	630	46
Rear disc brake cylinder slide pin x Rear disc brake cylinder mounting			
Upper side:	34	350	25
Lower side:	39	400	29
Rear disc brake cylinder x Flexible hose	29	300	22
Brake actuator assy x Actuator bracket	5.4	55	48 in·lbf
Brake actuator bracket x Body	19	194	14
ABS & TRAC actuator assy x Actuator bracket	5.4	55	48 in·lbf
ABS & TRACTION actuator bracket x Body	19	194	14
Front speed sensor x Steering knuckle	8.0	82	71 in·lbf
Front speed sensor wire harness clamp x shock absorber			
Bolt A:	5.0	51	44 in·lbf
Bolt B:	18.8	192	14
Rear axle hub set bolt	80	816	59
Yawrate sensor x Body	12.5	127	9
Skid control ECU x Body	5.5	56	49 in·lbf